

PostgreSQL Server Config

Merely a convenient reproduction of the advise given by Christophe Pettus during his excellent PyCon PostgreSQL workshop: Check out the video! .

Config Files

postgresql.conf pg_hba.conf

Aside from log files, these are the ONLY files you should edit in the main postgresSQL directory.

LOGGING (postgresql.conf)

```
log_destination = 'csvlog'
log_directory = 'pg_log'
logging_collector = on
log_filename = 'postgres-%Y-%m-%d_%H%M%S'
log_rotation_age = 1d
log_rotation_size = 1GB
log_min_duration_statement = 250ms
log_checkpoints = on
log_connections = on
log_disconnections = on
log_lock_waits = on
log_temp_files = 0
```

Be generous with logging; it has very low impact on the system.

NOTE: "Standard format" or "stderr" is obsolete. There is no good reason to use it anymore.

Changing Settings

Most settings just require a server reload to take effect.

Some require a full server restart (such as `shared_buffers`).

pg_hba.conf

```
local all postgres peer
local replication repl trust
local fugu fugu trust
host all all 127.0.0.1/32 md5
host all all ::1/128 md5
hostssl fugu fugu 178.79.191.8/32 md5
hostssl replication repl 178.79.191.8/32 md5
```

Example file

User Settings

By default, database traffic is not encrypted.

Turn on ssl if you are running in a cloud provider.

For pre-9.4, set `ssl_renegotiation_limit = 0`.

Memory Config

Consists of:

`shared_buffers`

`work_mem`

`maintenance_work_mem`

SHARED BUFFERS (postgresql.conf)

Below 2gb RAM?

20% Total System Memory

Below 64gm RAM?

25% Total System Memory

> 64gm RAM?

`shared_buffers = 16gb`

WORK MEM (postgresql.conf)

Start low: 32-64MB.

Look for 'temporary file' lines in logs.

THEN - Set to 2-3x the largest temp file you see.

Can cause a huge speed-up if set properly. But be careful: It can use that amount of memory per planner node.

MAINTENANCE WORK MEM

10% of system memory, up to 1GB.

DO NOT TOUCH

The contents and special files in the main PostgreSQL directories should never, ever be modified directly. Ever.

Exceptions: `pg_log` (if you put the log files there), and the configuration files.

`pg_xlog` and `pg_clog` are off-limits!

Checkpoint Config

Essentially, don't let `checkpoint_segments` get out of hand.

9.4 and earlier (postgresql.conf)

```
wal_buffers = 16MB
checkpoint_completion_target = 0.9
checkpoint_timeout = 10m-30m #
Depends on restart time
checkpoint_segments = 32 # To start.
```

`checkpoint_segments` happening more often than `checkpoint_timeout`?

Adjust `checkpoint_segments` so that checkpoints happen due to timeouts rather than filling segments.



By **aaronmyatt**
cheatography.com/aaronmyatt/

Published 6th September, 2016.
Last updated 6th September, 2016.
Page 1 of 2.

Sponsored by **Readability-Score.com**
Measure your website readability!
<https://readability-score.com>

9.5 and later (postgresql.conf)

```
wal_buffers = 16MB
checkpoint_completion_target = 0.9
checkpoint_timeout = 10m-30m # Depends on
restart time
min_wal_size = 512MB
max_wal_size = 2GB
```

checkpoint_segments happening more often than
checkpoint_timeout?

Step 1: Adjust min_wal_size so that checkpoints happen due to
timeouts rather filling segments.

Step 2: Adjust max_wal_size to be about three times
min_wal_size.

effective_cache_size

Set to the amount of file system cache available.

Otherwise:

If you don't know, set it to 75% of total system memory.

REFERENCE

<http://thebuild.com/presentations/pycon-2016-pppp.pdf>



By **aaronmyatt**
cheatography.com/aaronmyatt/

Published 6th September, 2016.
Last updated 6th September, 2016.
Page 2 of 2.

Sponsored by **Readability-Score.com**
Measure your website readability!
<https://readability-score.com>