Experiment 3a:

Code:

```
  GNU nano 9.0
#! /bin/zsh

if [ -f "$1" ]
then
echo "$1 is a file"
elif [ -d "$1" ]
then
echo "$1 is a directory"
else
echo"$1 doesn't exist"
fi
```

Output:

```
┌──(kali㉿sourav)-[~]
└─$ nano 10.sh

┌──(kali㉿sourav)-[~]
└─$ bash 10.sh myname.txt
myname.txt is a file

┌──(kali㉿sourav)-[~]
└─$ bash 10.sh MIET
MIET is a directory

┌──(kali㉿sourav)-[~]
└─$
```

Experiment 3b:

Code:

```
  GNU nano 9.0
!/bin/zsh

for file in "$@"
do
if [ -f "$file" ]
then
mv "$file" "$(echo "$file" | tr '[:lower:]' '[:upper:]')"
echo "$file changed"
else
echo "$file does not exist"
fi
done
```

Output:

```
┌──(kali㉿sourav)-[~]
└─$ nano exp3b.zsh

┌──(kali㉿sourav)-[~]
└─$ bash exp3b.zsh exp3b1.txt exp3b2.txt
exp3b.zsh: line 1: !/bin/zsh: No such file or directory
exp3b1.txt changed
exp3b2.txt changed

┌──(kali㉿sourav)-[~]
└─$
```