Technical Data Sheet

Model No: 34CLH4959 34dBi 2x2 MIMO Dish Antenna

4.9-5.9GHz 34dBi 2x2 MIMO

Features:

- Spread Spectrum – Unlicensed 5 GHz Band
- Public Safety – Licensed 4.9 GHz Band.
- Solids & High Performance.
- ConnectLH "Best In Class" Quality and Dependability.
- Type "N" Female connector for Superior outdoor environmental conditions.
- Reflector Material Aluminum/Stainless Steel.
- Antenna Dish Dia 4 feet, powder quoted.

Electrical Specifications

Frequency (MHz)	4900 – 5900
Gain (dBi)	34±1
VSWR (Max)	1.5 : 1
H Plane BW (°)	3±0.25
E Plane BW (°)	3±0.25
Polarization	Linear V & H
Port to Port Isolation (dB)	> 30
Max. Power Input (Watts)	50
Impedance (Ω)	50
Front to Back Ratio (dB)	>36
Cross Poln. (dB)	>28
Connector Termination	2 x N(F)

Environmental Specifications

Temperature Range (°C)	(-) 35 to (+) 65
Wind Speed (Km/Hr) Survival	200
Humidity	95% No Condensation
Ingress Protection	IP 65

email: reachus@youconnecttech.com

Mechanical Specifications

Dimension (mm)	Ø 1200 ±10
Reflector Material	Aluminum Alloy
Finish	Powder coated
Gross Weight (Kg)	12±1
Mounting Bracket	Galvanized Steel
Mounting Hardware	Stainless Steel
Mounting Style	Pole
Mounting Pole Diameter (inch)	90-120mm
Mounting Adjustment	H Plane ± 180°
	V Plane ± 15°

Connect LH™ are trademark of YouConnect Technologies
All specifications are subject to change without notice.

email: reachus@youconnecttech.com