



LIMITED WARRANTY — FIBERGLASS

SourcePoint Valera Fiberglass Doors

PRODUCT LINE	SourcePoint Valera Fiberglass Doors — entry doors, sidelites, and transoms
VERSION	1.0
EFFECTIVE	Products invoiced by SourcePoint on or after January 1, 2026

Read together with the SourcePoint Master Warranty Terms and the SourcePoint Valera Fiberglass Doors Care & Finishing Guide, both provided with this document. All three together form your warranty.



THREE THINGS DECIDE WHETHER YOUR COVERAGE HOLDS

The door must be **protected by adequate overhang** — see the Overhang Requirement below. A Valera door supplied primed must be **finished on all six sides within 30 days of installation** with a permitted finish system. And **no storm door of any type** may be installed in front of it. Read the Care & Finishing Guide before you hang the door.

THE MATERIAL

What a Valera Door Is

Valera doors are built with compression-molded fiberglass skins — smooth or woodgrain-textured — bonded to an internal wood stile-and-rail frame, with an insulating core between the skins. The fiberglass skin is what faces the weather. It does not absorb water, it does not rust or dent the way steel does, and it holds its shape far better than a solid wood face. That is what makes the slab term in this document possible.

There is wood inside the door. The skin protects it on the face and back; on the four edges, and at every bore hole and hinge rout, the finish you apply is the only thing between that wood and the weather. An unsealed edge lets water into the stile, and a wet stile swells, rots, and pushes the skin off. That is why every edge and every cut must be sealed, why the door must be finished on all six sides, and why this warranty — like every SourcePoint exterior door warranty — requires an overhang. Under one, sealed and finished, the slab is warranted for five years; the finish on it, the glass in it, and the moving parts around it are warranted for the periods below.

What We Claim, and What We Don't

Valera doors offer **the best weather resistance of any SourcePoint door material**. They are not maintenance-free, and SourcePoint does not describe them that way. The finish still needs to be applied correctly and kept up.

No statement by a dealer, installer, employee, or salesperson — and no statement in advertising, sales literature, or on a website — adds to, changes, or overrides the terms of this warranty.

COVERAGE

Coverage at a Glance

All coverage periods below run from the coverage start date — see the SourcePoint Master Warranty Terms, Section 1a.

Fiberglass slab — warp beyond tolerance, splitting, cracking, delamination of skin from frame or core; rot of the internal frame where edges are sealed as required	5 years
Composite frame and brickmould — rot, decay, delamination	5 years
Sidelite and transom panels — same conditions as the slab	5 years
Insulated glass — hermetic seal failure	3 years
Decorative glass — coming separation, seal failure	3 years
Factory-applied paint or stain finish	3 years
Threshold and sill, hinges, astragal — mechanical defects	5 years
Weatherstripping, door sweep, corner seals	1 year

Eligibility. Original purchaser, single-family residence. Multi-resident residential buildings carry a **2-year** term — see the SourcePoint Master Warranty Terms, Section 7. Commercial, hospitality, and other non-residential installations carry a **1-year** term.

WHAT IS COVERED

What Is Covered

The slab (5 years). For five years from the coverage start date, SourcePoint warrants that your Valera door, sidelite, and transom panels will not warp beyond the tolerances stated below, split, crack, or delaminate, provided the conditions of coverage in this document have been met.

Rot of the internal wood frame is covered on the same term, on one further condition: that every edge, bore hole, hinge rout, and cut surface was sealed and finished as required and kept sealed. Rot that begins at an unsealed or unmaintained edge or bore is water entry through the finish, not a defect in the door, and is not covered.

The frame (5 years). For five years from the coverage start date, SourcePoint warrants that the composite frame and brickmould supplied with your Valera unit will not rot, decay, or delaminate, provided the frame is installed without alteration (trimming brickmould to fit the opening is permitted), is caulked and flashed in accordance with the installation instructions, and the conditions of coverage in this document have been met.

Frame components (5 years). The threshold and sill system, hinges, and astragal are warranted against defects in material and workmanship that substantially impair their operation. **Hinge finish is not covered** — see Hardware below.

Weatherstripping, sweep, and corner seals (1 year). These are wear components. Replacement after the first year is normal owner maintenance.

Insulated and Decorative Glass

SourcePoint warrants that insulated glass units supplied with a Valera door will not, for **three (3) years** from the coverage start date, develop material obstruction of vision between the interior glass surfaces caused by failure of the hermetic seal. Decorative glass units are additionally warranted for the same period against separation of the coming from the glass.

SourcePoint's liability under this provision is limited to shipping a replacement glass unit or lite frame. This provision does not apply to broken glass, to glass units installed by others, or to units to which a retrofit film, tint, or coating has been applied.

Bubbles, seeds, streaks, and swirls in decorative glass are characteristics of how that glass is made and are not defects. An irregularity in any glass that is not visible from **six (6) feet** is not a defect.

Hardware

Locksets, handle sets, deadbolts, and multi-point locks are not part of the Valera unit and are not covered by this warranty, whether or not SourcePoint supplied them. Any warranty on those items is the hardware manufacturer's.

Hinges are covered for mechanical defects as stated above. **The finish on hinges is not covered** and is supplied as-is. Salt air, acid rain, and harsh cleaners will tarnish or pit any plated finish; that is exposure, not a defect.

Warp Tolerance

Warp is not a defect in a 6'8" door unless it exceeds 1/4" in the plane of the door, or in an 8'0" door unless it exceeds 3/8". No door taller than 8'0" is warranted against warp.

Warp includes bow, cup, and twist, and is measured by placing a straightedge, taut wire, or string on the suspected concave face at any angle and measuring the maximum distance between the straightedge and the face of the door, accounting for panel and glazing recesses.

Temporary bowing from heat is not warp. A fiberglass door in direct sun, particularly a dark one, can bow during the day and return flat overnight. Warp is measured at moderate temperature with the door out of direct sun.

Overhang Requirement

 **WARRANTY CONDITION**
A door that is not shielded from the elements by adequate overhang is **not covered by this warranty**.

Overhang is the single most important factor in the service life of an exterior door. The fiberglass skin does not rot or rust, but the door is not immune to weather: heat softens the core and the adhesive that bonds the skin to it, ultraviolet light breaks down every finish, driving rain works at the sealed edges where the wood frame sits, and water finds its way past weatherstripping on any door that takes weather head-on. An overhang is what keeps the door covered for the full term.

The formula

$$X = \frac{1}{2}Y$$

- Y = the vertical distance from the bottom of the door to the base of the overhang
- X = the required horizontal projection of the overhang from the wall

DISTANCE FROM BOTTOM OF DOOR TO BASE OF OVERHANG (Y)	REQUIRED PROJECTION (X)
8 ft (96 in)	4 ft (48 in)
10 ft (120 in)	5 ft (60 in)
12 ft (144 in)	6 ft (72 in)

Adjusting for exposure

The formula is a minimum for typical conditions. More projection is required where the door faces prevailing wind and driving rain, south or west exposure with long daily sun load, or coastal salt air.

Recessed and sheltered entries

Recessed entries, deep covered porches, and vestibules may satisfy this requirement without a projecting roof, provided the door is genuinely shielded from direct rain and sun.

If you cannot meet the requirement

Talk to your SourcePoint dealer before you order. A door installed without adequate overhang is not covered, and that cannot be corrected afterward.

Finishing Requirements

Valera doors are supplied either **factory-finished** or **primed**. The obligations differ.

Factory-finished doors

No further finishing is required. **Do not paint, stain, sand, or strip a factory-finished door.** Doing so ends the factory-finish coverage, and the appearance and performance of whatever is applied over it is not covered.

Primed doors

A primed Valera door must be finished on all six sides — face, back, both edges, top edge, and bottom edge — within 30 days of installation, or immediately if the door is installed during a wet season. Bore holes, mortise pockets, hinge routs, and any cut or trimmed edge must be sealed and finished as well.

Primer is not a finish. Factory primer is a bonding layer for your topcoat, not a weather coat. A door left in primer past the deadline is not covered against skin degradation, chalking, finish-related delamination, or rot of the internal frame.

The top and bottom edges are wood. They are the two surfaces nobody looks at and the two that let water into the door. A door with an unsealed top or bottom edge is not covered against rot, swelling, or delamination.

IF THE DOOR IS	THE FINISH SYSTEM MUST BE
Painted	A quality 100% acrylic exterior latex paint formulated for fiberglass or exterior doors, over the factory primer
Stained (woodgrain-textured doors)	A gel stain formulated for fiberglass , top-coated with an exterior-grade clear finish containing ultraviolet inhibitors

Do not use interior paints, interior polyurethane, lacquer, shellac, oil-based penetrating stains not formulated for fiberglass, or any solvent-based product that requires sanding the skin. Full application sequence and cure times are in the Care & Finishing Guide.

DARK FINISHES

Dark Paints and Stains

A dark finish absorbs significantly more heat than a light one. Surface temperatures on a dark, sun-exposed fiberglass door can exceed the softening point of the core and the adhesive that bonds the skin to it.

Damage caused by heat build-up where a dark paint or stain has been used is not covered. For this purpose, a dark finish is any finish with a **Light Reflectance Value (LRV) below 40**. LRV is published by every major paint manufacturer for every color, on a 0-100 scale where 0 is absolute black and 100 is pure white. Blacks, navies, hunter greens, dark browns, and deep reds all fall well below 40.

A dark finish does not void this warranty. The rest of your coverage stands. What is excluded is damage caused by the heat the dark finish creates: skin bubbling, delamination, excessive bow, and finish failure on the sun-facing elevation.

Factory-applied dark finishes are covered. Where SourcePoint applies a dark finish at the factory, SourcePoint has selected a coating system rated for it, and the factory-finish term and the slab term both apply in full.

FACTORY FINISH

Factory-Applied Finishes

Where SourcePoint supplies a Valera door with a factory-applied paint or stain finish, that finish is warranted for **three (3) years** from the coverage start date against peeling, blistering, cracking, checking, and adhesion failure.

Fading is not finish failure unless it exceeds **5 units as measured per ASTM D 2244** on a properly maintained and cleaned surface. **Uneven fading is not a covered condition**. Elevations receive unequal sun and weather, and the resulting variation is environmental.

The performance and appearance of any finish applied by anyone other than SourcePoint is not covered under any provision of this warranty.

COASTAL

Coastal and Saltwater Installations

The fiberglass skin and the composite frame are unaffected by salt air. **Slab, frame, glass, and factory-finish coverage are unchanged within two (2) miles of salt or brackish water.**

Plated and painted metal components are affected. Within that two-mile line, coverage on **hinges, threshold, and astragal is reduced to 1 year**, and corrosion, pitting, or tarnish of any metal component is not covered. Monthly rinsing with fresh water is required — see the Care & Finishing Guide.

Conditions of Coverage

1. **Protected by adequate overhang** as defined in the Overhang Requirement above.
2. **Finished on schedule** — primed doors finished on all six sides, with a permitted finish system, within 30 days of installation, per the Finishing Requirements above. Factory-finished doors left unaltered.
3. **Cut, bored, and machined surfaces sealed at hanging.** Any edge or surface exposed by fitting the door must be sealed when the door is hung, and the integrity of the finish maintained thereafter.
4. **Finish maintained** — inspected at least every **12 months** and recoated when it shows wear, per the Care & Finishing Guide. Keep a dated record; SourcePoint may ask for it to support a delamination or skin-failure claim.
5. **Stored correctly before installation** — flat or upright and fully supported, dry, out of direct sun, with packaging vented. See the Care & Finishing Guide.
6. **Installed plumb, square, and level**, with the sill flashed and sealed in accordance with the installation instructions, and the unit properly supported and shimmed so the door swings freely and the weatherstrip seals evenly.
7. **Frame unaltered** except for trimming brickmould to fit, and caulked as specified.
8. **No storm door of any type** — vented or non-vented. See the SourcePoint Master Warranty Terms, Section 6a.

EXCLUSIONS

Not Considered Defects

The following are characteristics of the material, or normal conditions of service, and are not defects:

- **Minor surface imperfections** in the fiberglass skin — pinholes, texture variation, slight mold lines — that are not visible from **six (6) feet** in normal light.
- **Woodgrain variation.** The molded grain pattern on textured doors repeats and varies; it will not match a sidelite or a wood door.
- **Color variation between components.** A stained fiberglass skin, a wood edge, a composite frame, and a lite frame are different materials and take stain differently.
- **Temporary heat bow** that recovers when the door cools.
- Minor warp within the tolerances stated above.
- **Chalking** of any field-applied finish, and fading of any finish within tolerance.
- **Seasonal change in weatherstrip contact** as the house and the opening move.
- Wear of weatherstrip, sweep, and corner seals after the first year.

Not Covered

- **Doors not shielded from the elements by adequate overhang**, as defined in the Overhang Requirement above.
- Damage from heat build-up where a dark paint or stain has been field-applied, as described above.
- Damage from finishing delays, incomplete finishing, use of a prohibited finish system, or failure to maintain the finish on schedule.
- Unsealed top edges, bottom edges, bore holes, mortises, or cut edges, and any damage arising from them — including rot, swelling, or delamination that begins at an unsealed edge or bore.
- The performance or appearance of finishes applied by others, and of anything applied over a factory finish.
- **Storm doors of any type** — vented or non-vented. See the SourcePoint Master Warranty Terms, Section 6a.
- Damage from improper handling or on-site storage, including skin damage from doors stacked without spacers, and heat damage from doors left in shipping wrap in the sun.
- Damage from on-site machining, re-boring, or hardware changes made after delivery.
- **Unauthorized modification of the door**, including cutting down, trimming, added cutouts, and the attachment or fastening of third-party items or accessories that penetrate the door — mail slots, speakeasies, pet doors, and similar. Hardware necessary to the operation of the door unit, such as locksets and hinges, is permitted.
- Locksets, handle sets, deadbolts, and multi-point locks, and the finish on any hardware.

- Defects caused by warp or bow of the rough opening, or by installation that prevents the door from swinging freely or the weatherstrip from sealing.
- Damage from impact, abrasion, chemicals, paint strippers, pressure washing, building settlement, or structural movement of the opening.
- Water entering around the door rather than through it. Flashing, sealant, threshold adjustment, and installation defects are the responsibility of the installer.
- Glass breakage, glass scratches, surface condensation, and aftermarket films or tints.
- Corrosion, pitting, or tarnish of metal components within two miles of salt water.
- Labor for finishing, refinishing, removal, or reinstallation, except as provided in the SourcePoint Master Warranty Terms, Section 4.
- Doors sold as “surplus” or “clearance.”

TERMS

Ownership and Eligibility

Original purchaser only. Non-transferable, and does not pass to any subsequent owner of the property. U.S. residential installations only, during your ownership.

INSTALLATION	SLAB AND FRAME TERM
Single-family residence	5 years
Condominium, apartment, or other multi-resident residential building	2 years — see the SourcePoint Master Warranty Terms, Section 7
Commercial, hospitality, and other non-residential	1 year

Glass, finish, and component terms are as stated in Coverage at a Glance, or the term above if shorter.

Clearance and Surplus

Valera doors sold as “surplus” or “clearance” are sold **as-is with no warranty. All sales final.**

Special Order

Valera doors custom-ordered to your specifications are **not eligible for return or exchange under any circumstance** and are supplied on estimated lead times only.

Claims, Returns, and Remedy

Claims are made through the dealer or representative from whom you purchased. Your dealer holds the records SourcePoint needs and submits the claim on your behalf.

See the SourcePoint Master Warranty Terms — Sections 4 (Our Remedy), 5 (Inspection, Reporting, and Claims), and 9 (Returns).

A trip charge applies only after a site visit, and only where SourcePoint or an approved vendor attends and the condition is found not to be covered by this warranty. The amount is quoted to you and agreed before the visit is scheduled.

SourcePoint Doors and Windows LLC

4363 Northeast Expressway, Atlanta, GA 30340 · 888-821-D00R (3667) · info@sourcepointdoors.com
· sourcepointdoors.com

SourcePoint Doors & Windows · Form SP-WAR-010 · Rev. September 2026 · Version 1.0