break statement

The break statement is used to jump out of a loop instantly without getting back to the conditional test. When break statement is encountered inside any loop, control automatically passes to the first statement after the loop.

Example:- C program to determine whether a number is prime or not.

```
#include <stdio.h>
void main()
{
        int i,n;
        printf("\n Enter the number");
        scanf("%d", &n);
        for(i=2; i<=n-1; i++)
        {
            if (n % i == 0)
            {
                printf("The number is not prime.");
                break;
            }
        }
        if (i==n)
            printf("The number is prime.");
}
```

continue statement

The continue statement is used to take the program control to the beginning of the loop, bypassing the statements inside the loop, which have not yet been executed. When continue is encountered inside any loop, the control automatically passes to the beginning of the loop.

As a result, the current iteration of the loop gets skipped and the control moves on to the next iteration.

Unlike break, continue statement cannot be used with a switch case.

Scanned by CamScanner

Example Program:-

```
#include <stdio.h>
void main()
{    int i, j;
     for (i=1; i<=2; i++)
     {
        for (j=1; j<=2; j++)
        {
           if (i==j)
           {   continue;
           }
           printf("%d %d \n", i, j);
        }
     }
}
```

Output:-

1 2

2 1

Here, when value of i becomes equal to j, the continue statement takes the control to the beginning of the inner for loop bypassing the rest of the statements pending execution in the inner for loop.

Scanned by CamScanner