

Interleaver Design for Deep Neural Networks

Sourya Dey, Peter Beerel, Keith Chugg

Asilomar Conference on Signals, Systems, and Computers

Oct-Nov 2017



Overview of Current DNNs

- ▶ Key machine learning technologies


Overview of Current DNNs

- ▶ Key machine learning technologies
- ▶ Lot of parameters - **Memory intensive**
- ▶ Slow to train - **Computationally intensive**

Overview of Current DNNs


- ▶ Key machine learning technologies
- ▶ Lot of parameters - **Memory intensive**
- ▶ Slow to train - **Computationally intensive**
- ▶ Training done **offline** in CPU/GPU
- ▶ Custom hardware used for **inference only**

Typical Supervised Network



Krizhevsky, A., Sutskever, I., Hinton, G.E.: Imagenet classification with deep convolutional neural networks. In: NIPS-2012, pp. 1097-1105 (2012)
Zhang, C., Wu, D., Sun, J., Sun, G., Luo, G., Cong, J.: Energy-efficient CNN implementation on a deeply pipelined FPGA cluster. In: ISLPED-2016. pp. 326- 331. ACM, New York (2016)

Focus of our Approach



Overview of our Research

- ▶ Predefined sparsity - **Memory friendly**
 - ▶ *2-3x savings on CL only network parameters*
 - ▶ *2 orders of magnitude savings on CL parameters of CNNs **

Dey, S., Shao, Y., Chugg, K.M., Beerel, P.A.: Accelerating Training of Deep Neural Networks via Sparse Edge Processing. In: Proc. ICANN-2017, pp. 273-280. LNCS (2017)

* Dey, S., Huang, K.W., Beerel, P.A., Chugg, K.M.: Characterizing Sparse Connectivity Patterns in Neural Networks. In: ICLR-2018 (submitted for publication)

Overview of our Research

- ▶ Predefined sparsity - **Memory friendly**
 - ▶ *2-3x savings on CL only network parameters*
 - ▶ *2 orders of magnitude savings on CL parameters of CNNs **
- ▶ Edge-based processing - **Computationally flexible**
- ▶ Hardware optimizations - **Fast** training

Dey, S., Shao, Y., Chugg, K.M., Beerel, P.A.: Accelerating Training of Deep Neural Networks via Sparse Edge Processing. In: Proc. ICANN-2017, pp. 273-280. LNCS (2017)

* Dey, S., Huang, K.W., Beerel, P.A., Chugg, K.M.: Characterizing Sparse Connectivity Patterns in Neural Networks. In: ICLR-2018 (submitted for publication)

Overview of our Research


- ▶ Predefined sparsity - **Memory friendly**
 - ▶ *2-3x savings on CL only network parameters*
 - ▶ *2 orders of magnitude savings on CL parameters of CNNs **
- ▶ Edge-based processing - **Computationally flexible**
- ▶ Hardware optimizations - **Fast** training
- ▶ FPGA based architecture - **Online training** and inference

Dey, S., Shao, Y., Chugg, K.M., Beerel, P.A.: Accelerating Training of Deep Neural Networks via Sparse Edge Processing. In: Proc. ICANN-2017, pp. 273-280. LNCS (2017)

* Dey, S., Huang, K.W., Beerel, P.A., Chugg, K.M.: Characterizing Sparse Connectivity Patterns in Neural Networks. In: ICLR-2018 (submitted for publication)


Sparsity

Sparsity




Fully connected (FC) network

Sparsity




Fully connected (FC) network
Fanout (fo) = 4

Sparsity




Fully connected (FC) network
Fanout (fo) = 4 Fanin (fi) = 8

Sparsity




Fully connected (FC) network
Fanout (fo) = 4 Fanin (fi) = 8
Connectivity = 100%

Sparsity




Fully connected (FC) network
Fanout (fo) = 4 Fanin (fi) = 8
Connectivity = 100%




Sparse network
 $fo = 1$, $fi = 2$
Connectivity = 25%

Sparsity - Predefined




Fully connected (FC) network
Fanout (fo) = 4 Fanin (fi) = 8
Connectivity = 100%




Sparse network
 $fo = 1, fi = 2$
Connectivity = 25%


Example of Parameter Savings




Present Work - Interleavers for Sparse Patterns



Present Work - Interleavers for Sparse Patterns



Present Work - Interleavers for Sparse Patterns



Interleaver algorithm ensures:

- ▶ Each output connected to a *good spatial chunk* of different inputs
- ▶ No neuron unconnected

Interleaver Requirements

- ▶ Optimized for computational efficiency in hardware
- ▶ Optimized for on-chip storage
- ▶ High values for metrics which are performance indicators

Degree of Parallelism = z

Degree of Parallelism = z


- z memories for all parameters of same type

Mem 0	Mem 1				Mem $z-1$
w_0	w_1	w_2			w_{z-1}
w_z					
w_{2z}					
w_{3z}					w_{W-1}

Degree of Parallelism = z

- ▶ z memories for all parameters of same type
- ▶ Process z parameters in 1 **cycle** => 1 from each mem


Mem 0	Mem 1				Mem $z-1$
w_0	w_1	w_2			w_{z-1}
w_z					
w_{2z}					
w_{3z}					w_{W-1}



Degree of Parallelism = z

- ▶ z memories for all parameters of same type
- ▶ Process z parameters in 1 **cycle** => 1 from each mem
- ▶ Process all parameters in a sweep

Mem 0	Mem 1				Mem $z-1$
w_0	w_1	w_2			w_{z-1}
w_z					
w_{2z}					
w_{3z}					w_{W-1}



Clash Freedom

Clash Freedom

- ▶ E.g. p activations, so depth of each memory = p/z
- ▶ Accessed in interleaved (permuted order)

p/z

Mem 0	Mem 1				Mem $z-1$
a_0	a_1	a_2			a_{z-1}
a_z					
a_{2z}					
a_{3z}					a_{p-1}

Clash Freedom

- ▶ E.g. p activations, so depth of each memory = p/z
- ▶ Accessed in interleaved (permuted order)

	Mem 0	Mem 1				Mem z-1
	a_0	a_1	a_2			a_{z-1}
	a_z					
	a_{2z}					
	a_{3z}					a_{p-1}

Clash-free access 😊

	Mem 0	Mem 1				Mem z-1
	a_z					
	a_{3z}					

Clash stalls processing 😞

Clash Freedom

- ▶ E.g. p activations, so depth of each memory = p/z
- ▶ Accessed in interleaved (permuted order)

Mem 0	Mem 1				Mem z-1
a_0	a_1	a_2			a_{z-1}
a_z					
a_{2z}					
a_{3z}					a_{p-1}


Clash-free access 😊

Mem 0	Mem 1				Mem z-1
a_z					
a_{3z}					

Clash stalls processing 😞


Interleaver must prevent clashes when accessing activations

Ease of Accesses




Design interleaver to have easy address computation

Ease of Accesses




Design interleaver to have easy address computation

Ease of Accesses



Design interleaver to have easy address computation

Ease of Accesses



Design interleaver to have easy address computation

Interleaver Design Algorithm

Interleaver Design Algorithm

- Let r be a random permutation of memory row index
=> Size p/z

Interleaver Design Algorithm

- ▶ Let r be a random permutation of memory row index
=> Size p/z
- ▶ Replicate or partition r to form s of z elements => Starting indices of all mems

Interleaver Design Algorithm

- ▶ Let r be a random permutation of memory row index
=> Size p/z
- ▶ Replicate or partition r to form s of z elements => Starting indices of all mems
- ▶ $t = \{s, s+1, \dots, s+p/z-1\} \%(p/z)$ => All p indices for all mems in order

Interleaver Design Algorithm

- ▶ Let r be a random permutation of memory row index
=> Size p/z
- ▶ Replicate or partition r to form s of z elements => Starting indices of all mems
- ▶ $t = \{s, s+1, \dots, s+p/z-1\} \% (p/z)$ => All p indices for all mems in order

$$\pi_W(i) = \left(t[i \% p] \times z + i \% z \right) \times fo + \lfloor i/p \rfloor$$

Interleaver Design Algorithm

Example: $p=32$, $fo=2$, $z=8 \Rightarrow i \in [0,63]$. Say $i = 45$

- ▶ Let r be a random permutation of memory row index \Rightarrow Size p/z
- ▶ Replicate or partition r to form s of z elements \Rightarrow Starting indices of all mems
- ▶ $t = \{s, s+1, \dots, s+p/z-1\} \% (p/z) \Rightarrow$ All p indices for all mems in order

$$\pi_W(i) = \left(t[i \% p] \times z + i \% z \right) \times fo + \lfloor i/p \rfloor$$

Interleaver Design Algorithm

Example: $p=32$, $fo=2$, $z=8 \Rightarrow i \in [0,63]$. Say $i = 45$

- ▶ Let r be a random permutation of memory row index \Rightarrow Size p/z

$$\pi_W(i) = \left(\underbrace{t[i \% p]} \times z + i \% z \right) \times fo + \lfloor i/p \rfloor$$

Activation Memory Bank Row = $45 \% 32 = 1$

Row1	a_8	a_9	a_{10}	a_{11}	a_{12}	a_{13}	a_{14}	a_{15}
------	-------	-------	----------	----------	----------	----------	----------	----------

- ▶ Replicate or partition r to form s of z elements \Rightarrow Starting indices of all mems
- ▶ $t = \{s, s+1, \dots, s+p/z-1\} \% (p/z) \Rightarrow$ All p indices for all mems in order

Interleaver Design Algorithm

Example: $p=32, fo=2, z=8 \Rightarrow i \in [0,63]$. Say $i = 45$

- ▶ Let r be a random permutation of memory row index \Rightarrow Size p/z

$$\pi_W(i) = \left(t[i \% p] \times z + i \% z \right) \times fo + \lfloor i/p \rfloor$$

Activation Memory Bank Row = $45 \% 32 = 1$

Row1	a_8	a_9	a_{10}	a_{11}	a_{12}	a_{13}	a_{14}	a_{15}
------	-------	-------	----------	----------	----------	----------	----------	----------

a_{13} Left side Neuron = $1 \times 8 + 45 \% 8 = 13$

- ▶ $t = \{s, s+1, \dots, s+p/z-1\} \% (p/z) \Rightarrow$ All p indices for all mems in order

Interleaver Design Algorithm

Example: $p=32, fo=2, z=8 \Rightarrow i \in [0,63]$. Say $i = 45$

- ▶ Let r be a random permutation of memory row index \Rightarrow Size p/z
- ▶ Replicate or partition r to form s of z elements \Rightarrow Starting indices of all mems
- ▶ $t = \{s, s+1, \dots, s+p/z-1\} \% (p/z) \Rightarrow$ All p indices for all mems in order

$$\pi_W(i) = \left(t[i \% p] \times z + i \% z \right) \times fo + \lfloor i/p \rfloor$$

Activation Memory Bank Row = $45 \% 32 = 1$

Row1	a_8	a_9	a_{10}	a_{11}	a_{12}	a_{13}	a_{14}	a_{15}
------	-------	-------	----------	----------	----------	----------	----------	----------

a_{13} Left side Neuron = $1 \times 8 + 45 \% 8 = 13$

a_{13} Left side Neuron's Weight = $13 \times 2 = 26$

Interleaver Design Algorithm

Example: $p=32, fo=2, z=8 \Rightarrow i \in [0,63]$. Say $i = 45$

- ▶ Let r be a random permutation of memory row index \Rightarrow Size p/z
- ▶ Replicate or partition r to form s of z elements \Rightarrow Starting indices of all mems
- ▶ $t = \{s, s+1, \dots, s+p/z-1\} \% (p/z) \Rightarrow$ All p indices for all mems in order


$$\pi_W(i) = \left(t[i \% p] \times z + i \% z \right) \times fo + \lfloor i/p \rfloor$$

Activation Memory Bank Row = $45 \% 32 = 1$

Row1	a_8	a_9	a_{10}	a_{11}	a_{12}	a_{13}	a_{14}	a_{15}
------	-------	-------	----------	----------	----------	----------	----------	----------

a_{13} Left side Neuron = $1 \times 8 + 45 \% 8 = 13$

Left side Neuron's Weight = $13 \times 2 = 26$



Weight Offset = 1

Interleaver Design Algorithm

Example: $p=32, fo=2, z=8 \Rightarrow i \in [0,63]$. Say $i = 45$

- ▶ Let r be a random permutation of memory row index \Rightarrow Size p/z
- ▶ Replicate or partition r to form s of z elements \Rightarrow Starting indices of all mems
- ▶ $t = \{s, s+1, \dots, s+p/z-1\} \% (p/z) \Rightarrow$ All p indices for all mems in order


$$\pi_W(i) = \left(t[i \% p] \times z + i \% z \right) \times fo + \lfloor i/p \rfloor$$

Activation Memory Bank Row = $45 \% 32 = 1$

Row1	a_8	a_9	a_{10}	a_{11}	a_{12}	a_{13}	a_{14}	a_{15}
------	-------	-------	----------	----------	----------	----------	----------	----------

a_{13} Left side Neuron = $1 \times 8 + 45 \% 8 = 13$

Left side Neuron's Weight = $13 \times 2 = 26$



Weight Offset = 1

Finally: w_{27}

13

Meeting Requirements

- ▶ Easily generated - Proof in paper
 - ▶ All variables involved are powers of 2 (add extra neurons)
 - ▶ Modulo = Bit select
 - ▶ Multiply = Bit shift
 - ▶ Only store r for a new pattern
 - ▶ Create t by accumulating 1s
- ▶ Clash freedom - Proof in paper

Variations

Variations

- Start Vector Shuffle (SV)

Original: $s = \{2, 0, 3, 1, 2, 0, 3, 1\}$

After SV: $s = \{2, 0, 3, 1, 3, 0, 1, 2\}$

Variations

- Start Vector Shuffle (SV)

Original: $s = \{2, 0, 3, 1, 2, 0, 3, 1\}$

After SV: $s = \{2, 0, 3, 1, 3, 0, 1, 2\}$

- Sweep Starter Shuffle (SS)

Original:

1st sweep $s = \{2, 0, 3, 1, 2, 0, 3, 1\}$

2nd sweep $s = \{2, 0, 3, 1, 2, 0, 3, 1\}$

After SS:

1st sweep $s = \{2, 0, 3, 1, 3, 0, 1, 2\}$

2nd sweep $s = \{0, 3, 2, 1, 0, 3, 2, 1\}$

Variations

- Start Vector Shuffle (SV)

Original: $s = \{2,0,3,1,2,0,3,1\}$

After SV: $s = \{2,0,3,1,3,0,1,2\}$

- Sweep Starter Shuffle (SS)

Original:

1st sweep $s = \{2,0,3,1,2,0,3,1\}$

2nd sweep $s = \{2,0,3,1,2,0,3,1\}$

After SS:

1st sweep $s = \{2,0,3,1,3,0,1,2\}$



2nd sweep $s = \{0,3,2,1,0,3,2,1\}$

- Memory Dither (MD)

$$\pi_W(i) = \left(t[i\%p] \times z + v[i\%z] \right) \times fo + \lfloor i/p \rfloor$$

$v[.]$ = Permutation of $[0,z-1]$

Some Weight Interleaver Patterns



Spread and Dispersion


- ▶ Spread: Connections that are close on 1 side should be far away on other
- ▶ Dispersion: Connections should be irregular, i.e. no patterns or trends

Spread and Dispersion

- Spread: Connections that are close on 1 side should be far away on other
- Dispersion: Connections should be irregular, i.e. no patterns or trends


Interleaver Variant	Spread	Dispersion
Basic	18.28	0.04
MD	7.48	0.22
SS	9.7	0.07
SS + MD	6.5	0.37
SV	6.6	0.08
SV + MD	7.31	0.23
SV + SS	5.05	0.09
SV + SS + MD	5.7	0.39

Dataset Results



* Sourya Dey: <https://cobaltfolly.wordpress.com/2017/10/15/morse-code-dataset-for-artificial-neural-networks/>

Morse Dataset Trends



Morse has fewer inputs and low redundancy
Spread should be high, dispersion hurts

Summary and Ongoing Work

- ▶ Pre-defined sparse hardware architecture to lower memory and computational footprint
- ▶ Interleaver algorithm to guarantee clash freedom and ease of storage
- ▶ Interleaver variations and effects on performance

- ▶ Extension to multiple junctions - Adjacency matrices
- ▶ Measures to characterize network performance

Thank you!

Questions?