

# SPECTRO LUBRICANT TECHNICAL DATA

## Heavy Duty Primary Chaincase



### Description

Heavy Duty Primary Chaincase Oil is a shear –stable petroleum transmission and chain case lubricant designed to withstand the punishment of high loads. Special polymers provide exceptional clutch engagement and temperature stability.

Meets all known OEM warranty requirements.

### Application

For use in all Harley® Sportster transmission / primary chain cases and Big Twin transmission & primary chaincases.

### Typical Inspections

Kinematic Viscosity @ 100° C cST	<b>85w</b> 19.6
Kinematic Viscosity @ 40° C cST	155
Flash Point, °C	230
Pourpoint, °C	-23
Viscosity Index	128

### Code

R.GAPCL  
X.GAPCL

### Description

12/1 Quart Bottles  
16 Gallon Drum

### Weight

25 Lbs.  
120 Lbs.

- MEETS ALL KNOWN MOTORCYCLE MANUFACTURERS' WARRANTY REQUIREMENTS AND RECOMMENDATIONS.
- FOR USE IN ALL SPORTSTER TRANSMISSIONS / CHAINCASES AND BIG TWIN CHAINCASES.
- LOW DRAG, LOW FRICTION LOSS, SAE 85W (10W40) VISCOSITY.
- ELIMINATES CLUTCH "DRAG" AND "SLIPPING".

SPECTRO OILS OF AMERICA  
993 Federal Rd., Brookfield, CT 06804  
203-775-1291 Fax 203-775-8720  
[www.spectro-oils.com](http://www.spectro-oils.com)



# SPECTRO LUBRICANT TECHNICAL DATA

## Spectro Golden Gear Lubricant



- MEETS ALL KNOW MOTORCYCLE MANUFACTURER'S WARRANTY REQUIREMENTS AND RECOMMENDATIONS.
- FOR USE IN ALL TWO-STROKE TRANSMISSIONS AND SEPARATE TRANSMISSIONS.
- LOW DRAG, LOW FRICTION LOSS SAE 80W (10W30) AND 85W (10W40) VISCOSITY
- ELIMINATES CLUTCH 'DRAG AND "SLIPPING."
- EXCELLENT FOR 2ND AND 3RD GEAR STARTS.
- A.P.I. GL-4

### Description

Spectro Golden Gear Lubricant is a shear-stable petroleum engine case lubricant designed to withstand the punishment of second and third gear starts. Special polymers provide exceptional clutch engagement and temperature stability

Meets all known OEM warranty requirements.

### Application

For use in all modern 2-cycle motocross machine engine/clutch cases where SAE 10w30 or SAE 10w40 SE/SF/SG or 80w lubricants are recommended.

### For Racing Use

Change frequently, preferably every race weekend.

### Typical Inspections

	80W	85W
Kinematic Viscosity @ 100° C cST	9.6	19.6
Kinematic Viscosity @ 40° C cST	60.3	155
Flash Point, °C	216	230
Pourpoint, °C	-27	-13
Viscosity Index	143	128

### Code

L.GSCGL80  
L.GSCGL85  
X.GSCGL80  
X.GSCGL85

### Description

12/1 Liter Bottles  
12/1 Liter Bottles  
16 gal Drum  
16 gal Drum

### Weight

26 Lbs.  
26 Lbs.  
120 Lbs.  
120 Lbs.

SPECTRO OILS OF AMERICA  
993 Federal Rd., Brookfield, CT 06804  
203-775-1291 Fax 203-775-8720  
[www.spectro-oils.com](http://www.spectro-oils.com)

