

**Products** 

<u>Home</u> > <u>Gear Oil for Manual Transmissions</u> > MT-90 75W90 GL-4 Gear Oil

My Account

Order Status

View Cart 0 Items (\$0.00)



MOTOR OIL FOR RACING

**GEAR OIL FOR DIFFERENTIALS** 

**GEAR OIL FOR MANUAL** TRANSMISSIONS

MT-90 75W90 GL-4 Gear Oil

MT-85 75W85 GL-4 Gear Oil

MTL 75W80 GL-4 Gear Oil

75W90 NS GL-5 Gear Oil

Lightweight ShockProof®

D6 ATF

SHOCKPROOF® GEAR OILS

AUTOMATIC

TRANSMISSION FLUIDS

WATERWETTER® COOLANT **ADDITIVES** 

**GASOLINE FUEL ADDITIVES** 

DIESEL FUEL ADDITIVES

POWER STEERING AND MISC.

MOTORCYCLES, ATVS, AND **POWERSPORTS** 

TWO-STROKE OILS

**GREASE AND ASSEMBLY** 

LUBE SUSPENSION FLUIDS

V-TWIN POWER PACKS

**KARTING** 

APPAREL



Manual Transmission Tech Info Manual Trans Lube Product Data



## MT-90 75W90 GL-4 Gear Oil

- 75W90 GL-4 gear oil (similar to SAE 5W40/10W40 engine oil viscosity)
- Popular in Nissan, Mazda, Mitsubishi, VW/Audi, Lotus Elise/Exige, Toyota
- Offers quicker shifts, perfect synchronizer coefficient of friction
- Safe for brass synchros, as it lacks the reactive sulfurs found in most GL-5 oils that cause
- High performance gear protection and longer synchro life
- Eliminates notchy shifting, even when cold
- Satisfies the gear oil viscosity requirements of 75W, 80W and motor oil viscosities of SAE 40, 10W40, and 15W40
- Recommended for GL-1, GL-3, and GL-4 applications, as well as where most special synchromesh fluids are specified

MT-90 75W90 GL-4 quart - \$15.95

O MT-90 75W90 GL-4 gallon - \$64.95

Quantity

Add to Cart

### ABOUT RED LINE GEAR OIL FOR MANUAL **TRANSMISSIONS**

- Appropriate coefficient of friction for most manual transmission synchronizers (other's synthetic gear oils are often too slippery for proper synchro engagement)
- Red Line offers lubricants to pinpoint nearly every transmission application
- MTL, MT-85 & MT-90 are not for use in differentials with hypoid gears
- Excellent gear and synchro protection, balanced slipperiness for easier shifting in cold climates
- Excellent for high- and low-mile transmissions
- Compatible with petroleums and other synthetics

### TYPICAL PROPERTIES

API Service Class	GL 4
SAE Viscosity Grade (Motor Oil)	15W40
SAE Viscosity Grade (Gear Oil)	75W90
Vis @ 100°C, cSt	15.6
Vis @ 40°C, cSt	90
Viscosity Index	185
Pour Point, °C	-45
Pour Point, °F	-49
Brookfield Viscosity @ -40°C, Poise	320

### ALSO AVAILABLE FROM OUR DEALERS

50304 - MT-90 75W90 GL-4 - quart 50305 - MT-90 75W90 GL-4 - gallon 50306 - MT-90 75W90 GL-4 - 5 gallon 50307 - MT-90 75W90 GL-4 - 16 gallon 50308 - MT-90 75W90 GL-4 - 55 gallon

74 1001100 01000	· ·
SAE Viscosity Grade (Motor Oil)	15W40
SAE Viscosity Grade (Gear Oil)	75W90
Vis @ 100°C, cSt	15.6
Vis @ 40°C, cSt	90
Viscosity Index	185
Pour Point, °C	-45
Pour Point, °F	-49
Brookfield Viscosity @ -40°C, Poise	320

# COMPANY

Why Red Line? Dealer Locator Wholesale Distributors Contact Us FAQs

# **TECHNICAL**

Application Guide Technical Articles Tech Files

# ORDER SUPPORT

Order Status Customer Service

### **DEALER SUPPORT**

Become a Red Line Oil Dealer Wholesale Distributors International Distributors Motorcycle Distributors

8/13/2014 7:54 PM 1 of 2

Copyright 2000-2014 Red Line Synthetic Oil Corporation

Select Language
Powered by Google Translate

Legal Contact Us