

Oracle Database Table Refresh Activity Guide

Comprehensive step-by-step documentation for Oracle Data Pump export/import schema refresh procedures [cite: 4].

Environment: Oracle Database 19c Enterprise Edition | **Objective:** Perform schema-level backup via Data Pump, transfer files across servers via SCP, and restore data using drop/recreate or truncate/append workflows [cite: 4].

1. Pre-Check & Row Count Validation

Verify user default tablespace settings and baseline row counts in source tables (e.g., JOBS table) [cite: 4].

SQL: Check User and Baseline Count

```
SQL> select username, default_tablespace from dba_users where username='HR';

USERNAME                                DEFAULT_TABLESPACE
-----                                -
HR                                           SYSAUX

SQL> SELECT COUNT(*) FROM JOBS;
COUNT(*)
-----
        19
```

2. Schema-Level Backup via Data Pump

Export the entire HR schema using Oracle Data Pump utility (expdp) [cite: 4].

Command: Run expdp Export

```
[oracle@souvik expdp_backup]$ expdp system/oracle directory=exp_dir dumpfile=HR_%U.dmp
schemas=hr
```

```
Processing object type SCHEMA_EXPORT/TABLE/TRIGGER
. . exported "HR"."EMPLOYEES"          17.08 KB      107 rows
. . exported "HR"."LOCATIONS"          8.437 KB       23 rows
. . exported "HR"."JOB_HISTORY"        7.195 KB       10 rows
. . exported "HR"."JOBS"               7.179 KB       21 rows
. . exported "HR"."DEPARTMENTS"        7.125 KB       27 rows
. . exported "HR"."COUNTRIES"          6.367 KB       25 rows
. . exported "HR"."REGIONS"            5.546 KB        4 rows
Master table "SYSTEM"."SYS_EXPORT_SCHEMA_01" successfully loaded/unloaded
Dump file set for SYSTEM.SYS_EXPORT_SCHEMA_01 is:
/u02/expdp_backup/HR_01.dmp
Job "SYSTEM"."SYS_EXPORT_SCHEMA_01" successfully completed
```

3. File Transfer to Target Database (SCP)

Securely transfer the generated dump file to the target production server (192.168.1.32) using scp [cite: 4].

Command: SCP Transfer

```
[oracle@souvik expdp_backup]$ scp HR_01.dmp oracle@192.168.1.32:/u02/backup
oracle@192.168.1.32's password:
HR_01.dmp                                100% 712KB 101.7KB/s 00:07
```

4. Method A: Drop and Recreate Schema Restore

The first approach drops the entire user schema with cascade option, then imports a clean copy [cite: 4].

Workflow Steps & Commands

```
SQL> drop user hr cascade;
User dropped.

[oracle@localhost backup]$ impdp system/oracle directory=exp_dir dumpfile=HR_01.dmp

SQL> conn hr/hr
Connected.
SQL> select count(*) from jobs;
COUNT(*)
-----
21
```

5. Method B: Truncate and Append Restore

Alternatively, disable constraints, truncate existing tables, and perform a data pump import with `table_exists_action=append` [cite: 4].

SQL/Impdp Commands

```
-- 1. Disable Constraints
ALTER TABLE LOCATIONS DISABLE CONSTRAINT LOC_C_ID_FK;
ALTER TABLE DEPARTMENTS DISABLE CONSTRAINT DEPT_LOC_FK;
ALTER TABLE EMPLOYEES DISABLE CONSTRAINT EMP_DEPT_FK;
...
-- 2. Truncate Tables
TRUNCATE TABLE COUNTRIES;
TRUNCATE TABLE DEPARTMENTS;
TRUNCATE TABLE EMPLOYEES;
TRUNCATE TABLE JOBS;
...
[oracle@localhost backup]$ impdp system/oracle directory=exp_dir dumpfile=HR_01.dmp
table_exists_action=append
```

Activity Summary

Activity Phase	Utility / Tool	Key Artifacts / Output
Backup	Data Pump (expdp)	HR_01.dmp (~712 KB schema export) [cite: 4]
Transfer	SCP	Sent to target host 192.168.1.32: /u02/ backup [cite: 4]
Restoration (Method 1)	Drop Cascade + impdp	Clean schema recreation [cite: 4]
Restoration (Method 2)	Constraints Disabled + Truncate + impdp (append)	In-place data refresh [cite: 4]