

# Point in time Recovery (PITR)

An Incomplete Recovery—commonly called Point-in-Time Recovery (PITR)—restores an Oracle database to a specific target time, SCN (System Change Number), or log sequence before an unwanted event (such as a dropped table or data corruption) occurred.

## STEP 1: Check the SCN number or the timestamp when table is deleted.

```
SELECT object_name, original_name, type, droptime FROM dba_recyclebin WHERE  
original_name ='EMP';
```

```
SQL> SELECT object_name, original_name, type, droptime FROM dba_recyclebin WHERE original_name ='EMP';
```

| OBJECT_NAME                          | ORIGINAL_NAME | TYPE  | DROPTIME            |
|--------------------------------------|---------------|-------|---------------------|
| BIN\$WRnH0lz0EGfgZQAA<br>AAAAAQ==\$0 | EMP           | TABLE | 2026-08-15:22:23:36 |

## STEP 2: Mount the Database: Requires database downtime.

Shut down the running instance and start it in MOUNT state.

```
RMAN> SHUTDOWN IMMEDIATE;  
RMAN> STARTUP MOUNT;
```

```
RMAN> SHUTDOWN IMMEDIATE;
```

```
using target database control file instead of recovery catalog  
database closed  
database dismounted  
Oracle instance shut down
```

```
RMAN> STARTUP MOUNT;
```

```
connected to target database (not started)  
Oracle instance started  
database mounted
```

```
Total System Global Area      1124072640 bytes
```

```
Fixed Size                      8895680 bytes
```

```
Variable Size                   788529152 bytes
```

```
Database Buffers                318767104 bytes
```

```
Redo Buffers                     7880704 bytes
```

### STEP 3: Run Restore and Recover Commands: Executes till the specified threshold.

Restore datafiles from backup and apply redo logs up to the exact target time.

```
RUN {  
  SET UNTIL TIME "TO_DATE('2026-08-15 22:45:00', 'YYYY-MM-DD HH24:MI:SS')";  
  RESTORE DATABASE;  
  RECOVER DATABASE;  
}
```

```
RMAN> RUN {  
  SET UNTIL TIME "TO_DATE('2026-08-15 22:45:00', 'YYYY-MM-DD HH24:MI:SS')";  
  RESTORE DATABASE;  
  RECOVER DATABASE;  
}2> 3> 4> 5>
```

executing command: SET until clause

Starting restore at 15-AUG-26  
flashing back control file to SCN 2257674  
allocated channel: ORA\_DISK\_1  
channel ORA\_DISK\_1: SID=34 device type=DISK

### STEP 4: Open Database with RESETLOGS: Establishes a new database incarnation.

Open the database and reset log sequence numbers to finalize incomplete recovery.

```
RMAN> ALTER DATABASE OPEN RESETLOGS;
```

```
RMAN> ALTER DATABASE OPEN RESETLOGS;
```

Statement processed

### STEP 5: To verify the table

```
SQL> CONN  
Enter user-name: SHAADMIN/ORACLE  
Connected.  
SQL>  
SQL>  
SQL>  
SQL> SELECT * FROM EMP;
```

| EMP_ID | NAME    | AGE |
|--------|---------|-----|
| 1      | Amal    | 32  |
| 2      | Govinda | 98  |
| 3      | Rohini  | 87  |
| 4      | Tul     | 1   |