

PROFILES

➤ How to check what is the default profile associated with Database?

The following command displays the DEFAULT profile and all of its resource limits:

```
SQL> SELECT PROFILE,RESOURCE_NAME,RESOURCE_TYPE,LIMIT FROM DBA_PROFILES WHERE PROFILE='DEFAULT';
```

PROFILE	RESOURCE_NAME	RESOURCE	LIMIT
DEFAULT	COMPOSITE_LIMIT	KERNEL	UNLIMITED
DEFAULT	SESSIONS_PER_USER	KERNEL	UNLIMITED
DEFAULT	CPU_PER_SESSION	KERNEL	UNLIMITED
DEFAULT	CPU_PER_CALL	KERNEL	UNLIMITED
DEFAULT	LOGICAL_READS_PER_SESSION	KERNEL	UNLIMITED
DEFAULT	LOGICAL_READS_PER_CALL	KERNEL	UNLIMITED
DEFAULT	IDLE_TIME	KERNEL	UNLIMITED
DEFAULT	CONNECT_TIME	KERNEL	UNLIMITED
DEFAULT	PRIVATE_SGA	KERNEL	UNLIMITED
DEFAULT	FAILED_LOGIN_ATTEMPTS	PASSWORD	10
DEFAULT	PASSWORD_LIFE_TIME	PASSWORD	180
DEFAULT	PASSWORD_REUSE_TIME	PASSWORD	UNLIMITED
DEFAULT	PASSWORD_REUSE_MAX	PASSWORD	UNLIMITED
DEFAULT	PASSWORD_VERIFY_FUNCTION	PASSWORD	NULL
DEFAULT	PASSWORD_LOCK_TIME	PASSWORD	1
DEFAULT	PASSWORD_GRACE_TIME	PASSWORD	7
DEFAULT	INACTIVE_ACCOUNT_TIME	PASSWORD	UNLIMITED

17 rows selected.

➤ How to create profile SHA_PR?

➤ Create a profile with password limits: PASSWORD_GRACE_TIME 10

➤ Create a profile with resource limits: SESSIONS_PER_USER UNLIMITED

```
SQL> CREATE PROFILE SHA_PR LIMIT
  2 PASSWORD_GRACE_TIME 10
  3 SESSIONS_PER_USER UNLIMITED;

Profile created.

SQL> SELECT PROFILE,RESOURCE_NAME,RESOURCE_TYPE,LIMIT FROM DBA_PROFILES WHERE PROFILE='SHA_PR';
```

PROFILE	RESOURCE_NAME	RESOURCE	LIMIT
SHA_PR	COMPOSITE_LIMIT	KERNEL	DEFAULT
SHA_PR	SESSIONS_PER_USER	KERNEL	UNLIMITED
SHA_PR	CPU_PER_SESSION	KERNEL	DEFAULT
SHA_PR	CPU_PER_CALL	KERNEL	DEFAULT
SHA_PR	LOGICAL_READS_PER_SESSION	KERNEL	DEFAULT
SHA_PR	LOGICAL_READS_PER_CALL	KERNEL	DEFAULT
SHA_PR	IDLE_TIME	KERNEL	DEFAULT
SHA_PR	CONNECT_TIME	KERNEL	DEFAULT
SHA_PR	PRIVATE_SGA	KERNEL	DEFAULT
SHA_PR	FAILED_LOGIN_ATTEMPTS	PASSWORD	DEFAULT
SHA_PR	PASSWORD_LIFE_TIME	PASSWORD	DEFAULT
SHA_PR	PASSWORD_REUSE_TIME	PASSWORD	DEFAULT
SHA_PR	PASSWORD_REUSE_MAX	PASSWORD	DEFAULT
SHA_PR	PASSWORD_VERIFY_FUNCTION	PASSWORD	DEFAULT
SHA_PR	PASSWORD_LOCK_TIME	PASSWORD	DEFAULT
SHA_PR	PASSWORD_GRACE_TIME	PASSWORD	10
SHA_PR	INACTIVE_ACCOUNT_TIME	PASSWORD	DEFAULT

17 rows selected.

➤ How to assigned profile SHA_PR to user SHAUSR

STEP 1: Assign the profile to respective user.

```
SQL> ALTER USER SHAUSR PROFILE SHA_PR;

User altered.
```

STEP 2: Check the profile is assign to the user.

```
SQL> SELECT USERNAME,profile FROM DBA_USERS WHERE PROFILE='SHA_PR';
```

USERNAME	PROFILE
SHAUSR	SHA_PR