

DB CONNECT & AUTOMATION GUIDE

Standard Operating Procedures • Oracle 19c Environment

1. Environment Overview

This document outlines the standardized procedures for configuring host identification, environment variables, and establishing a streamlined login workflow for Oracle 19c database administration [cite: 1].

Component	Target Setting
Database SID	infra
Oracle Home	/u01/app/oracle/product/19.0.0/dbhome_1

2. Creating the Interactive Connection Script

To eliminate repetitive typing of environment setup scripts and manual command sequences, create a robust automation script named `sql.sh` in your home directory [cite: 1].

Step 1: Open the script file for editing

```
vi sql.sh
```

Step 2: Add the automation logic

```
#!/bin/bash
export ORACLE_SID=infra
export ORAENV_ASK=NO
. oraenv > /dev/null 2>&1

echo "Select Login Type:"
echo "1) Normal User (e.g., scott)"
echo "2) SYSDBA"
read -p "Enter choice [1 or 2]: " choice

if [ "$choice" == "2" ]; then
    read -sp "Enter password for SYS: " password
    echo ""
    sqlplus "sys/$password as sysdba"
else
    read -p "Enter username: " username
    read -sp "Enter password: " password
    echo ""
    sqlplus "$username/$password"
fi
```

Step 3: Save, grant execution rights, and run

```
chmod +x sql.sh
./sql.sh
```

3. Hostname & Network Configuration

Ensure local resolution is correctly configured in `/etc/hosts` to prevent database connectivity latency and listener startup issues.

```
127.0.0.1    localhost localhost.localdomain localhost4 localhost4.localdomain4
souvik
```