

## TEMP TABLESPACE

- Create temp datafile sha\_tmp with 200M size.

**STEP 1:** Check the temporary tablespace.

```
SQL> SELECT FILE_ID, TABLESPACE_NAME, FILE_NAME, BYTES/1024/1024 AS "SIZE_MB", MAXBYTES/1024/1024/1024 AS "SIZE_GB", AUTOEXTENSIBLE
2 FROM DBA_TEMP_FILES;
```

| FILE_ID | TABLESPACE_NAME | FILE_NAME                               | SIZE_MB | SIZE_GB    | AUT |
|---------|-----------------|-----------------------------------------|---------|------------|-----|
| 1       | TEMP            | /u01/app/oracle/oradata/ORCL/temp01.dbf | 32      | 31.9999847 | YES |

**STEP 2:** Create temp file sha\_tmp size 200m.

```
SQL> CREATE TEMPORARY TABLESPACE SHA_TEMP TEMPFILE '/u01/app/oracle/oradata/ORCL/sha_temp.dbf' SIZE 200M;
Tablespace created.
```

```
SQL>
SQL> SELECT FILE_ID, TABLESPACE_NAME, FILE_NAME, BYTES/1024/1024 AS "SIZE_MB", MAXBYTES/1024/1024/1024 AS "SIZE_GB", STATUS
2 FROM DBA_TEMP_FILES ORDER BY FILE_ID;
```

| FILE_ID | TABLESPACE_NAME | FILE_NAME                                 | SIZE_MB | SIZE_GB    | STATUS |
|---------|-----------------|-------------------------------------------|---------|------------|--------|
| 1       | TEMP            | /u01/app/oracle/oradata/ORCL/temp01.dbf   | 32      | 31.9999847 | ONLINE |
| 2       | SHA_TEMP        | /u01/app/oracle/oradata/ORCL/sha_temp.dbf | 200     | 0          | ONLINE |

- Check number of temp datafiles with size

In the below command we have to check the number of temp files with size.

```
SQL> SELECT tablespace_name, COUNT(*) AS no_of_tempfiles FROM dba_temp_files GROUP BY tablespace_name;
```

| TABLESPACE_NAME | NO_OF_TEMPFILES |
|-----------------|-----------------|
| SHA_TEMP        | 1               |
| TEMP            | 1               |

```
SQL> SELECT FILE_ID, TABLESPACE_NAME, FILE_NAME, ROUND(bytes/1024/1024,2) AS SIZE_MB FROM DBA_TEMP_FILES;
```

| FILE_ID | TABLESPACE_NAME | FILE_NAME                                 | SIZE_MB |
|---------|-----------------|-------------------------------------------|---------|
| 2       | SHA_TEMP        | /u01/app/oracle/oradata/ORCL/sha_temp.dbf | 200     |
| 1       | TEMP            | /u01/app/oracle/oradata/ORCL/temp01.dbf   | 32      |

- Command to check temp tablespace Utilization (%free,%used)

SELECT TABLESPACE\_NAME,

ROUND(SUM(bytes\_used)/1024/1024,2) AS USED\_MB, ROUND(SUM(bytes\_free)/1024/1024,2) AS  
FREE\_MB, ROUND((SUM(bytes\_used))/(SUM(bytes\_used)+SUM(bytes\_free))\*100,2) AS pct\_used,  
ROUND((SUM(bytes\_free))/(SUM(bytes\_used)+SUM(bytes\_free))\*100,2) AS pct\_free FROM  
v\$temp\_space\_header GROUP BY tablespace\_name;

```
SQL> SELECT TABLESPACE_NAME, ROUND(SUM(bytes_used)/1024/1024,2) AS USED_MB, ROUND(SUM(bytes_free)/1024/1024,2) AS FREE_MB, ROUND((SUM(bytes_us
ed)/(SUM(bytes_used)+SUM(bytes_free))*100,2) AS pct_used, ROUND((SUM(bytes_free)/(SUM(bytes_used)+SUM(bytes_free))*100,2) AS pct_free FROM v
$temp_space_header GROUP BY tablespace_name;
```

| TABLESPACE_NAME | USED_MB | FREE_MB | PCT_USED | PCT_FREE |
|-----------------|---------|---------|----------|----------|
| TEMP            | 32      | 0       | 100      | 0        |
| SHA_TEMP        | 1       | 199     | .5       | 99.5     |

## ➤ How to Drop temp (Default) datafile?

If the temp file belongs to the default TEMP tablespace, Oracle will not allow you to drop the only temp file in use.

```
SQL> SELECT PROPERTY_VALUE FROM DATABASE_PROPERTIES WHERE PROPERTY_NAME='DEFAULT_TEMP_TABLESPACE';
```

| PROPERTY_VALUE |
|----------------|
| -----          |
| TEMP           |

```
SQL> SELECT FILE_ID, TABLESPACE_NAME, FILE_NAME, ROUND(bytes/1024/1024,2) AS SIZE_MB FROM DBA_TEMP_FILES;
```

| FILE_ID | TABLESPACE_NAME | FILE_NAME                                 | SIZE_MB |
|---------|-----------------|-------------------------------------------|---------|
| -----   | -----           | -----                                     | -----   |
| 2       | SHA_TEMP        | /u01/app/oracle/oradata/ORCL/sha_temp.dbf | 200     |
| 1       | TEMP            | /u01/app/oracle/oradata/ORCL/temp01.dbf   | 32      |

Before dropping the TEMP tablespace, make SHA\_TEMP the default temporary tablespace using `ALTER DATABASE DEFAULT TEMPORARY TABLESPACE SHA_TEMP;`. Once SHA\_TEMP becomes the default temporary tablespace, the TEMP tablespace can be dropped.

The drop command:

```
SQL>
SQL> DROP TABLESPACE SHA_TEMP INCLUDING CONTENTS AND DATAFILES;
```

Tablespace dropped.

```
SQL> SELECT TABLESPACE_NAME, ROUND(SUM(bytes_used)/1024/1024,2) AS USED_MB, ROUND(SUM(bytes_free)/1024/1024,2) AS FREE_MB, ROUND((SUM(bytes_u
sed)/(SUM(bytes_used)+SUM(bytes_free)))*100,2) AS pct_used, ROUND((SUM(bytes_free)/(SUM(bytes_used)+SUM(bytes_free)))*100,2) AS pct_free FROM
v$temp_space_header GROUP BY tablespace_name;
```

| TABLESPACE_NAME | USED_MB | FREE_MB | PCT_USED | PCT_FREE |
|-----------------|---------|---------|----------|----------|
| -----           | -----   | -----   | -----    | -----    |
| TEMP            | 32      | 0       | 100      | 0        |