

DB Link Setup

- **Connected to the pdb1 and pdb2 Database using following commands.**

Enter user-name: sys/oracle@pdb1 as sysdba

```
SQL> conn
Enter user-name: sys/oracle@pdb1 as sysdba
Connected.
```

```
SQL> show pdbs;

  CON_ID CON_NAME              OPEN MODE  RESTRICTED
-----
      3 PDB1                  READ WRITE NO
```

Same way, connected to the pdb2 Database.

Enter user-name: sys/oracle@pdb2 as sysdba

```
SQL> conn
Enter user-name: sys/oracle@pdb2 as sysdba
Connected.
```

```
SQL> show pdbs;

  CON_ID CON_NAME              OPEN MODE  RESTRICTED
-----
      4 PDB2                  READ WRITE NO
```

- **Create a User on PDB1**

CREATE USER Scott IDENTIFIED BY tiger quota 2g on users.

GRANT CREATE SESSION TO Scott;

- **Connect the user**

SQL> conn

Enter user-name: scott/tiger@pdb1

Connected.

- **Under user we have to create a table & insert the value.**

CREATE TABLE emp (empno NUMBER, ename VARCHAR2(20), sal NUMBER);

INSERT INTO emp VALUES (101,'SCOTT',5000); INSERT INTO emp VALUES (102,'SMITH',6000);
COMMIT;

```
SQL> select * from emp;

  EMPNO ENAME      SAL
-----
    101 SCOTT      5000
    102 SMITH      6000
```

- **Create the Database Link on PDB2**

SQL> conn

Enter user-name: sys/oracle@pdb2 as sysdba

Connected.

```
SQL> show pdbs;

  CON_ID CON_NAME              OPEN  MODE  RESTRICTED
  -----
         4 PDB2                READ  WRITE  NO
```

create database link pdb1_link connect to scott identified by tiger using 'pdb1';

```
SQL> create database link pdb1_link connect to scott identified by tiger using 'pdb1';
Database link created.
```

- **Verify the DB Link**

SELECT DB_LINK, USERNAME, HOST FROM USER_DB_LINKS WHERE DB_LINK='PDB1_LINK';

```
SQL> SELECT DB_LINK,USERNAME,HOST FROM USER_DB_LINKS WHERE DB_LINK='PDB1_LINK';

DB_LINK  USERNAME  HOST
-----
PDB1_LINK SCOTT     pdb1
```

- **Now access the Table in remotely**

Say example table is created in the PDB1 database but login the PDB2 database and access the pdb1 table through dB link.

```
SQL> show pdbs;

  CON_ID CON_NAME              OPEN  MODE  RESTRICTED
  -----
         4 PDB2                READ  WRITE  NO
```

```
SQL> select * from emp@pdb1_link;

EMPNO  ENAME      SAL
-----
    101 SCOTT      5000
    102 SMITH      6000
```

- **Drop the DB link in following commands**

DROP DATABASE LINK pdb2_link;

```
DROP DATABASE LINK pdb2_link;
```