

Schemas Refresh Activity

STEP 1: Create a user, name is "SHAADMIN"

```
create user shaadmin identified by oracle default tablespace users quota 1g on users;
```

```
SQL> create user shaadmin identified by oracle default tablespace users quota 1g on users;

User created.
```

STEP 2: Give the system level permission of the user.

```
grant create session, create table to shaadmin;
```

```
SQL> grant create session, create table to shaadmin;

Grant succeeded.
```

STEP 3: Under user we have to create a table name is "EMP". After create this table the user is converted to schema because user is a account but when a table is created under a user then it's called a schema. So, now SHAADMIN is a schema.

```
SQL> select * from emp;
```

EMP_ID	NAME	SAL
10	Avijit	45600
20	Anil	45321
30	Chintu	56789
40	Ayesha	76000

STEP 4: Now, I've to take a logical backup of schema level.

```
expdp system/oracle directory=exp_dir dumpfile=shaadmin.dmp schemas=shaadmin
```

```
[oracle@localhost ~]$ expdp system/oracle directory=exp_dir dumpfile=shaadmin.dmp schemas=shaadmin
```

```
Export: Release 19.0.0.0.0 - Production on Mon Aug 17 10:47:38 2026
Version 19.3.0.0.0
```

```
Copyright (c) 1982, 2019, Oracle and/or its affiliates. All rights reserved.
```

```
Connected to: Oracle Database 19c Enterprise Edition Release 19.0.0.0.0 - Production
Starting "SYSTEM"."SYS_EXPORT_SCHEMA_01": system/***** directory=exp_dir dumpfile=shaadmin.dmp sc
Processing object type SCHEMA_EXPORT/TABLE/TABLE_DATA
Processing object type SCHEMA_EXPORT/TABLE/STATISTICS/TABLE_STATISTICS
Processing object type SCHEMA_EXPORT/STATISTICS/MARKER
```

STEP 5: copy the dump file one database server to another database server.

```
scp shaadmin.dmp oracle@192.168.0.226:/u01
```

```
[oracle@localhost expdp_backup]$ scp shaadmin.dmp oracle@192.168.0.226:/u02/backup
oracle@192.168.0.226's password:
shaadmin.dmp                               100% 344KB 24.2MB/s
[oracle@localhost expdp_backup]$
```

STEP 6: Check the dump is coming to another server.

```
[oracle@localhost ~]$ cd /u01
[oracle@localhost u01]$ ll
total 307552
drwxrwxr-x. 4 oracle oinstall      40 Jul 10 14:19 app
-rw-rw----. 1 oracle oracle 314580992 Jul 25 15:38 sha01.dbf
-rw-rw----. 1 oracle oracle   352256 Aug 17 10:58 shaadmin.dmp
[oracle@localhost u01]$
```

STEP 7: Clean/Drop Target Schemas.

Run on the Target Database

Kill active sessions and drop the existing target schemas to ensure a clean restore:

```
SQL> select username,account_status from dba_users where username='SHAADMIN';
```

USERNAME	ACCOUNT_STATUS
SHAADMIN	OPEN

```
SQL> alter user shaadmin account lock;
```

User altered.

```
SQL> select username,account_status from dba_users where username='SHAADMIN';
```

USERNAME	ACCOUNT_STATUS
SHAADMIN	LOCKED

```
SELECT 'ALTER SYSTEM KILL SESSION '''||sid||','||serial#||' IMMEDIATE;' FROM v$session
WHERE username IN ('SHAADMIN');
```

```
SQL> SELECT 'ALTER SYSTEM KILL SESSION '''||sid||','||serial#||' IMMEDIATE;' FROM v$session WHERE username = 'SHAADMIN';
'ALTERSYSTEMKILLSESSION'''||SID||','||SERIAL#||'IMMEDIATE;'
-----
ALTER SYSTEM KILL SESSION '68,9352 IMMEDIATE;
```

STEP 8: Kill the active session.

```
ALTER SYSTEM KILL SESSION '68,9352';
```

```
SQL> ALTER SYSTEM KILL SESSION '68,9352';  
  
System altered.
```

STEP 9: Drop user.

```
SQL> DROP USER SHAADMIN CASCADE;  
  
User dropped.
```

STEP 10: Recreate the user accounts with basic privileges (CREATE USER shaadmin IDENTIFIED BY <pass>; GRANT CONNECT, RESOURCE TO shaadmin;)

```
create user shaadmin identified by oracle default tablespace users quota 1g on users;  
grant create session, resource to shaadmin;
```

```
SQL> create user shaadmin identified by oracle default tablespace users quota 1g on users;  
  
User created.  
  
SQL> grant create session, resource to shaadmin;  
  
Grant succeeded.
```

STEP 11: Import Schemas (impdp)

Run on the Target Database

Run the Data Pump import command on the target server:

```
impdp system/oracle directory=exp_dir dumpfile=shaadmin.dmp logfile=shaadmin.log  
schemas=shaadmin transform=disable_archive_logging:Y
```

```
[oracle@localhost backup]$ impdp system/oracle directory=exp_dir dumpfile=shaadmin.dmp logfile=shaadmin.log  
  
Import: Release 19.0.0.0.0 - Production on Mon Aug 17 11:34:18 2026  
Version 19.3.0.0.0  
  
Copyright (c) 1982, 2019, Oracle and/or its affiliates. All rights reserved.  
  
Connected to: Oracle Database 19c Enterprise Edition Release 19.0.0.0.0 - Production  
Master table "SYSTEM"."SYS_IMPORT_SCHEMA_01" successfully loaded/unloaded  
Starting "SYSTEM"."SYS_IMPORT_SCHEMA_01": system/***** directory=exp_dir dumpfile=shaadmin.dmp lo  
Processing object type SCHEMA_EXPORT/USER
```

STEP 12: Recompile Invalid Objects:

```
@?/rdbms/admin/utlrlp.sql
```

Step 13: Verify Object Status & Count:

```
SELECT object_type, count(*) FROM dba_objects WHERE owner = 'SHAADMIN' GROUP BY  
object_type;
```

```
SQL> SELECT object_type, count(*) FROM dba_objects WHERE owner = 'SHAADMIN' GROUP BY object_type;
```

OBJECT_TYPE	COUNT(*)
TABLE	1