

PDB CLONE (creating a new PDB from an existing PDB within the same Container Database)

Standard Procedure: Hot Cloning a Pluggable Database (PDB)

Operation Scope

Local CDB Container Environment

Target Database

PDB1 Cloned from Source PDB

Overview & Prerequisites

Cloning an existing Pluggable Database within the same Container Database (CDB) allows administrators to create an exact structural and data duplicate. Oracle supports *hot cloning*, enabling the source database to remain open and operational during the cloning process.

STEP 1: Check PDB Name and Status

Container Root

Verify current containers, IDs, and open modes prior to clone initiation.

```
show pdbs;
```

```
SQL> SHOW PDBS; CON_ID CON_NAME OPEN MOUNTED RESTRICTED -----  
----- 2 PDB$SEED READ ONLY NO 3 PDB READ WRITE NO
```

STEP 2: Execute the Clone Command

CDB\$ROOT

Create target PDB1 from source PDB with explicit storage directory mapping via FILE_NAME_CONVERT.

```
CREATE PLUGGABLE DATABASE pdb1 FROM pdb FILE_NAME_CONVERT =  
('/u01/app/oracle/oradata/CDB/pdb/', '/u01/app/oracle/oradata/CDB/pdb1/');
```

```
Pluggable database created.
```

Post-Clone Verification & Activation

STEP 3: Verify the New PDB State

SQL*Plus

Confirm that PDB1 has been successfully provisioned in a mounted state.

```
SELECT name, open_mode FROM v$pdb$seeds WHERE name = 'PDB1';
```

```
NAME OPEN_MODE ----- PDB1 MOUNTED
```

STEP 4: Open PDB1

SQL*Plus

Open the newly created pluggable database to make it accessible to applications.

```
ALTER PLUGGABLE DATABASE pdb1 OPEN;
```

```
Pluggable database altered.
```

STEP 5: Final Status Verification

CDB\$ROOT

List all container instances to verify PDB1 is open in READ WRITE mode.

```
SHOW PDBS;
```

```
SQL> SHOW PDBS; CON_ID CON_NAME OPEN MODE RESTRICTED -----  
----- 2 PDB$SEED READ ONLY NO 3 PDB READ WRITE NO 5 PDB1 READ WRITE  
NO
```