

STARTUP & SHUTDOWN STAGES

➤ How to start DB in restricted mode.

Startup restricted means DB is open but limited user can be access.

STEP 1:

```
SQL> STARTUP RESTRICT;  
ORACLE instance started.  
  
Total System Global Area  520091504 bytes  
Fixed Size                 8898416 bytes  
Variable Size             243269632 bytes  
Database Buffers          264241152 bytes  
Redo Buffers              3682304 bytes  
Database mounted.  
Database opened.
```

```
SQL> SELECT INSTANCE_NAME,STATUS,LOGINS FROM V$INSTANCE;  
  
INSTANCE_NAME  STATUS  LOGINS  
-----  
orcl           OPEN    RESTRICTED
```

STEP 2: Restricted mode allows only SYSDBA users and users with RESTRICTED SESSION privilege to connect to the database.

```
SQL> conn  
Enter user-name: scott  
Enter password:  
ERROR:  
ORA-01035: ORACLE only available to users with RESTRICTED SESSION privilege  
  
Warning: You are no longer connected to ORACLE.
```

```
SQL> conn  
Enter user-name: sys as sysdba  
Enter password:  
Connected.  
SQL>  
SQL> GRANT RESTRICTED SESSION TO SCOTT;  
Grant succeeded.  
  
SQL> conn  
Enter user-name: scott  
Enter password:  
Connected.
```

➤ How to bring DB to no restricted mode.

STEP 1: Check the database is restricted or not

```
SQL>  
SQL> SELECT INSTANCE_NAME,STATUS,LOGINS FROM V$INSTANCE;  
  
INSTANCE_NAME  STATUS  LOGINS  
-----  
orcl           OPEN    RESTRICTED
```

STEP 2: Change from restricted to allowed

```
SQL> ALTER SYSTEM DISABLE RESTRICTED SESSION;  
System altered.  
  
SQL> SELECT INSTANCE_NAME,STATUS,LOGINS FROM V$INSTANCE;  
  
INSTANCE_NAME  STATUS  LOGINS  
-----  
orcl           OPEN    ALLOWED
```