

VARIOUS TYPES OF DATABASE LINK

- Database link check

SELECT OWNER, DB_LINK, USERNAME, VALID FROM DBA_DB_LINKS;

```
SQL> SELECT OWNER,DB_LINK,USERNAME,VALID FROM DBA_DB_LINKS WHERE DB_LINK IN ('DB_ORCL','DB_ORCL_MULTI');
```

OWNER	DB_LINK	USERNAME	VALID
PUBLIC	DB_ORCL	HR	YES
PUBLIC	DB_ORCL_MULTI		YES

- Drop Database link

drop public database link "dblink_name";

```
SQL> drop public database link DB_ORCL;
```

Database link dropped.

➤ Public DB Link.

⇒ Available to all users/schemas within the local database.

CREATE PUBLIC DATABASE LINK db_orcl CONNECT TO hr IDENTIFIED BY hr_password USING 'orcl';

```
SQL> CREATE PUBLIC DATABASE LINK db_orcl CONNECT TO hr IDENTIFIED BY hr USING 'orcl';
```

Database link created.

```
SQL> SELECT OWNER,DB_LINK,USERNAME,VALID FROM DBA_DB_LINKS;
```

OWNER	DB_LINK	USERNAME	VAL
SYS	SYS_HUB		YES
PUBLIC	DB_ORCL	HR	YES

```
SQL> conn
Enter user-name: scott/tiger
Connected.
SQL>
SQL>
SQL> select * from locations@db_orcl;
```

LOCATION_ID	STREET_ADDRESS	POSTAL_CODE	CITY	STATE_PROVINCE	CO
1000	1297 Via Cola di Rie	00989	Roma		IT
1100	93091 Calle della Testa	10934	Venice		IT
1200	2017 Shinjuku-ku	1689	Tokyo	Tokyo Prefecture	JP
1300	9450 Kamiya-cho	6823	Hiroshima		JP
1400	2014 Jabberwocky Rd	26192	Southlake	Texas	US
1500	2011 Interiors Blvd	99236	South San Francisco	California	US
1600	2007 Zagora St	50090	South Brunswick	New Jersey	US
1700	2004 Charade Rd	98199	Seattle	Washington	US

➤ Private DB link

⇒ Only specific users/schemas within the local database.

CREATE DATABASE LINK DB_SCOTT CONNECT TO SCOTT IDENTIFIED BY TIGER USING 'ORCL';

```
SQL> GRANT CREATE DATABASE LINK TO scott;
Grant succeeded.

SQL> conn
Enter user-name: scott/tiger
Connected.
SQL> CREATE DATABASE LINK DB_SCOTT CONNECT TO SCOTT IDENTIFIED BY TIGER USING 'ORCL';
Database link created.

SQL> conn
Enter user-name: /as sysdba
Connected.
SQL> SELECT OWNER,DB_LINK,USERNAME,VALID FROM DBA_DB_LINKS;

OWNER          DB_LINK        USERNAME        VAL
-----
SYS            SYS_HUB        SYS_HUB         YES
PUBLIC         DB_ORCL        HR              YES
SCOTT          DB_SCOTT       SCOTT           YES
```

```
SQL> show user;
USER is "SCOTT"
SQL> select * from emp@db_scott;
```

	ID	NAME	LOCATION	DEPARTMENT
	1	Anup	Kolkata	IT
	2	Alok	Kolkata	Account
	3	Brishali	Kolkata	HR

• DIFFERENCE BETWEEN PUBLIC DBLINK & PRIVATE DBLINK

Public vs. Private DB Link Summary

Feature	Private DB Link	Public DB Link
Owner	Specific Schema User (e.g., HR)	PUBLIC
Accessibility	Owner schema only	All users in the database
Required Privilege	CREATE DATABASE LINK	CREATE PUBLIC DATABASE LINK
Drop Syntax	DROP DATABASE LINK link_name;	DROP PUBLIC DATABASE LINK link_name;