

A. Turtle Puzzle: Rearrange and Negate

time limit per test: 2 seconds

memory limit per test: 256 megabytes

input: standard input

output: standard output

You are given an array a of n integers. You must perform the following two operations on the array (the first, then the second):

1. Arbitrarily rearrange the elements of the array or leave the order of its elements unchanged.
2. Choose at most one contiguous segment of elements and replace the signs of all elements in this segment with their opposites. Formally, you can choose a pair of indices l, r such that $1 \leq l \leq r \leq n$ and assign $a_i = -a_i$ for all $l \leq i \leq r$ (negate elements). Note that you may choose not to select a pair of indices and leave all the signs of the elements unchanged.

What is the **maximum sum of the array elements** after performing these two operations (the first, then the second)?

Input

The first line of the input contains a single integer t ($1 \leq t \leq 1000$) — the number of test cases. The descriptions of the test cases follow.

The first line of each test case contains a single integer n ($1 \leq n \leq 50$) — the number of elements in array a .

The second line of each test case contains n integers a_1, a_2, \dots, a_n ($-100 \leq a_i \leq 100$) — elements of the array.

Output

For each test case, output the **maximum sum of the array elements** after sequentially performing the two given operations.

Example

input	Copy
8	
3	
-2 3 -3	
1	
0	
2	
0 1	
1	
-99	
4	
10 -2 -3 7	
5	
-1 -2 -3 -4 -5	
6	
-41 22 -69 73 -15 -50	
12	
1 2 3 4 5 6 7 8 9 10 11 12	

output	Copy
8	
0	
1	
99	
22	
15	
270	
78	

Codeforces Round 929 (Div. 3)

Finished

→ Practice?

Want to solve the contest problems after the official contest ends? Just register for practice and you will be able to submit solutions.

[Register for practice](#)

→ Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

[Start virtual contest](#)

→ Problem tags

[greedy](#) [math](#) [sortings](#)

No tag edit access

→ Contest materials

- [Announcement \(en\)](#)

Note

In the first test case, you can first rearrange the array to get $[3, -2, -3]$ (operation 1), then choose $l = 2, r = 3$ and get the sum $3 + -((-2) + (-3)) = 8$ (operation 2).

In the second test case, you can do nothing in both operations and get the sum 0.

In the third test case, you can do nothing in both operations and get the sum $0 + 1 = 1$.

In the fourth test case, you can first leave the order unchanged (operation 1), then choose $l = 1, r = 1$ and get the sum $-(-99) = 99$ (operation 2).

In the fifth test case, you can first leave the order unchanged (operation 1), then choose $l = 2, r = 3$ and get the sum $10 + -((-2) + (-3)) + 7 = 22$ (operation 2).

In the sixth test case, you can first leave the order unchanged (operation 1), then choose $l = 1, r = 5$ and get the sum $-((-1) + (-2) + (-3) + (-4) + (-5)) = 15$ (operation 2).

[Codeforces](#) (c) Copyright 2010-2024 Mike Mirzayanov

The only programming contests Web 2.0 platform

Server time: Feb/28/2024 14:40:03^{UTC+5.5} (g1).

Desktop version, switch to [mobile version](#).

[Privacy Policy](#)

Supported by



ITMO UNIVERSITY