

HOME TOP CATALOG CONTESTS GYM PROBLEMSET GROUPS RATING EDU API CALENDAR HELP

PROBLEMS SUBMIT CODE MY SUBMISSIONS STATUS HACKS STANDINGS CUSTOM INVOCATION

D. Inaccurate Subsequence Search

time limit per test: 2 seconds
memory limit per test: 256 megabytes
input: standard input
output: standard output

Maxim has an array a of n integers and an array b of m integers ($m \leq n$).

Maxim considers an array c of length m to be good if the elements of array c can be rearranged in such a way that at least k of them match the elements of array b .

For example, if $b = [1, 2, 3, 4]$ and $k = 3$, then the arrays $[4, 1, 2, 3]$ and $[2, 3, 4, 5]$ are good (they can be reordered as follows: $[1, 2, 3, 4]$ and $[5, 2, 3, 4]$), while the arrays $[3, 4, 5, 6]$ and $[3, 4, 3, 4]$ are not good.

Maxim wants to choose every subsegment of array a of length m as the elements of array c . Help Maxim count how many selected arrays will be good.

In other words, find the number of positions $1 \leq l \leq n - m + 1$ such that the elements $a_l, a_{l+1}, \dots, a_{l+m-1}$ form a good array.

Input
The first line contains an integer t ($1 \leq t \leq 10^4$) — the number of test cases.

The first line of each test case contains three integers n, m , and k ($1 \leq k \leq m \leq n \leq 2 \cdot 10^5$) — the number of elements in arrays a and b , the required number of matching elements.

The second line of each test case contains n integers a_1, a_2, \dots, a_n ($1 \leq a_i \leq 10^6$) — the elements of array a . Elements of the array a are not necessarily unique.

The third line of each test case contains m integers b_1, b_2, \dots, b_m ($1 \leq b_i \leq 10^6$) — the elements of array b . Elements of the array b are not necessarily unique.

It is guaranteed that the sum of n over all test cases does not exceed $2 \cdot 10^5$. Similarly, it is guaranteed that the sum of m over all test cases does not exceed $2 \cdot 10^5$.

Output
For each test case, output the number of good subsegments of array a on a separate line.

Example

input

5
7 4 2
4 1 2 3 4 5 6
1 2 3 4
7 4 3
4 1 2 3 4 5 6
1 2 3 4
7 4 4
4 1 2 3 4 5 6
1 2 3 4
11 5 3
9 9 2 2 10 9 7 6 3 6 3
6 9 7 8 10
4 1 1
4 1 5 6
6

output

4
3
2

Codeforces Round 938 (Div. 3)

Finished

→ Practice?

Want to solve the contest problems after the official contest ends? Just register for practice and you will be able to submit solutions.
[Register for practice](#)

→ Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.
[Start virtual contest](#)

→ Problem tags

data structures

two pointers

No tag edit access

→ Contest materials

Announcement

https://codeforces.com/contest/1955/problem/D

1/2

4

1

Note

In the first example, all subsegments are good.

In the second example, good subsegments start at positions 1, 2, and 3.

In the third example, good subsegments start at positions 1 and 2.

[Codeforces](#) (c) Copyright 2010-2024 Mike Mirzayanov

The only programming contests Web 2.0 platform

Server time: Apr/09/2024 08:06:43^{UTC+5.5} (h2).

Desktop version, switch to [mobile version](#).

[Privacy Policy](#)

Supported by



ITMO UNIVERSITY