SAFETY DATA SHEET



MOBIL SHC GEAR 460

Section 1. Identification

: MOBIL SHC GEAR 460 **Product name**

Product description : synthetic base stocks and additives

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Gear oil

Uses advised against : This product is not recommended for any industrial, professional or consumer use

other than the Identified Uses above.

Supplier : AMPOL AUSTRALIA PETROLEUM PTY LTD

> ABN 17 000 032 128 29-33 Bourke Rd Alexandria

New South Wales 2015 Australia

24 Hour Emergency

Telephone

: +61 2 9037 2994/1800 862 115 (CHEMTREC)

Product Technical

Information

: 1300364169

Supplier General Contact : +612 9250-5000 **FAX** : +612 9250-5742

SDS Internet Address : www.sds.exxonmobil.com

Section 2. Hazard(s) identification

Classification of the substance or mixture : Not classified.

Other hazards which do not : None known.

result in classification

Nota : This material should not be used for any other purpose than the intended use in

Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

Section 3. Composition and ingredient information

Substance/mixture : Mixture

Ingredient name	% (w/w)	Identifiers
benzenamine, n-phenyl-, reaction products with 2,4,4-trimethylpentene	≤1	CAS: 68411-46-1
kerosine (petroleum)	≤0.3	CAS: 8008-20-6
1h-benzotriazole-1-methanamine, n,n-bis(2-ethylhexyl)-ar-methyl-	≤0.3	CAS: 94270-86-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may

significantly reduce the ultimate extent of injury.

Ingestion : Wash out mouth with water. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Do not induce vomiting

unless directed to do so by medical personnel.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : Local necrosis as evidenced by delayed onset of pain and tissue damage a few

hours after injection.

Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing

: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing

media

media

: Do not use water jet.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being

discharged to any waterway, sewer or drain.

Hazardous combustion

products

: Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, sulfur oxides

Date of issue/Date of revision : 7 August Date of previous issue : No previous edition Version : 1 2/10

Section 5. Firefighting measures

Special protective actions for fire-fighters

: Use standard firefighting procedures and consider the hazards of other involved materials. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Assure an extended cooling down period to prevent reignition. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants. Warn other shipping. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Date of issue/Date of revision : 7 August Date of previous issue : No previous edition Version : 1 3/10

Section 7. Handling and storage

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Static Accumulator

: This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100x10E-12 Siemens per meter) and is considered a semiconductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semiconductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives and filtration can greatly influence the conductivity of a liquid.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls and personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
1-dodecene, polymer with 1-octene,	ExxonMobil (COMPANY)
hydrogenated	TWA 8 hours: 5 mg/m³. Form: Aerosols (thoracic fraction).
ditridecyl adipate	ExxonMobil (COMPANY)
	TWA 8 hours: 5 mg/m³.
1-decene, homopolymer hydrogenated	ExxonMobil (COMPANY)
	TWA 8 hours: 5 mg/m³. Form: Aerosols (thoracic fraction).
1-dodecene, polymer with 1-decene,	ExxonMobil (COMPANY)
hydrogenated	TWA 8 hours: 5 mg/m³. Form: Aerosols (thoracic fraction).
1-decene, polymer with 1-octene and	ExxonMobil (COMPANY)
1-dodecene, hydrogenated	TWA 8 hours: 5 mg/m³. Form: Aerosols (thoracic fraction).
kerosine (petroleum)	ACGIH TLV (United States, 1/2024) [Kerosene] Absorbed through
	skin.
	TWA 8 hours: 200 mg/m³ (as total hydrocarbon vapor).
	ExxonMobil (COMPANY) Absorbed through skin.
	TWA 8 hours: 5 mg/m³. Form: Stable Aerosol
	TWA 8 hours: 200 mg/m³. Form: Vapour

Appropriate engineering controls

Environmental exposure controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 8. Exposure controls and personal protection

Eve/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

: >315.56°C (>600°F) [Estimated]

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid.

Colour Colorless to Yellow **Odour** : Characteristic **Odour threshold** : Not available. Not applicable. **Melting point/freezing point** : Not available.

Boiling point or initial

boiling point and boiling

range

Flash point : Open cup: >210°C (>410°F) [ASTM D-92]

: Not available. **Evaporation rate Flammability** : Ignitable

Lower and upper explosion : Lower: 0.9% [Estimated] Upper: 7% [Estimated] limit/flammability limit

Vapour pressure : <0.1 mm Hg [20 °C] [Estimated]

Relative vapour density : >2 [Air = 1] [Estimated] Relative density : 0.85 [ASTM D4052]

Solubility in water : Negligible

Partition coefficient: n-

octanol/water

: >3.5 [Estimated]

: Not available. **Auto-ignition temperature** : Not available. **Decomposition temperature**

Date of issue/Date of revision Version :1 5/10 : 7 August Date of previous issue : No previous edition 2024

MOBIL SHC GEAR 460

Section 9. Physical and chemical properties and safety characteristics

Viscosity : 460 cSt [40 °C] [ASTM D 445]

Particle characteristics

Median particle size : Not applicable.

Particle characteristics

Median particle size : Not applicable.

Pour point : -27°C [ASTM D5950]

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : High energy sources of ignition. Excessive heat.

Incompatible materials : Strong oxidisers

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Test	Species	Result	Duration
1h-benzotriazole- 1-methanamine, n,n-bis (2-ethylhexyl)-ar-methyl-	LD50 Oral	Rat	3313 mg/kg	-

Conclusion/Summary

Inhalation: Minimally Toxic. No end point data for material. Based on assessment of the

components.

Dermal : Minimally Toxic. No end point data for material. Based on assessment of the

components.

Oral : Minimally Toxic. No end point data for material. Based on assessment of the

components.

Irritation/Corrosion

Conclusion/Summary

Skin : Negligible irritation to skin at ambient temperatures. No end point data for material.

Based on assessment of the components.

Eyes : May cause mild, short-lasting discomfort to eyes. No end point data for material.

Based on assessment of the components.

Respiratory: Negligible hazard at ambient/normal handling temperatures. No end point data for

material.

Respiratory or skin sensitization

Conclusion/Summary

Skin: Not expected to be a skin sensitizer. No end point data for material. Based on

assessment of the components.

Respiratory: Not expected to be a respiratory sensitizer. No end point data for material.

Mutagenicity

Date of issue/Date of revision : 7 August Date of previous issue : No previous edition Version : 1 6/10

MOBIL SHC GEAR 460

Section 11. Toxicological information

Conclusion/Summary

: Not expected to be a germ cell mutagen. No end point data for material. Based on assessment of the components.

Carcinogenicity

Conclusion/Summary

: Not expected to cause cancer. No end point data for material. Based on assessment of the components.

Classification

Product/ingredient name	IARC
kerosine (petroleum)	3

Reproductive toxicity

Conclusion/Summary

: Not expected to be a reproductive toxicant. No end point data for material. Based on assessment of the components.

Specific target organ toxicity (single exposure)

Conclusion/Summary

: Not expected to cause organ damage from a single exposure. No end point data for material.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Target organs
MOBIL SHC GEAR 460	Not applicable.	-

Conclusion/Summary

: Not expected to cause organ damage from prolonged or repeated exposure. No end point data for material. Based on assessment of the components.

Aspiration hazard

Conclusion/Summary

: Not expected to be an aspiration hazard. Based on physico-chemical properties of the material. Data available.

Other information

Contains

Synthetic base oils: Not expected to cause significant health effects under conditions of normal use, based on laboratory studies with the same or similar materials. Not mutagenic or genotoxic. Not sensitising in test animals and humans. Benzenamine, Nphenyl-, reaction products with 2,4,4-trimethylpentene (substituted DPA): Results from a supplier's extended one-generation dietary study with 10-week pre-mating administration of substituted DPA included decreased body weight and body weight gains in parental females during gestation and lactation, decreased number of implantation sites and decreased mean litter size. A representative formulation containing substituted DPA was tested in a rat oral gavage reproductive/ developmental toxicity screening study (OECD TG 421) with a 10-week pre-mating administration period. Study results included decreased body weight and body weight gain starting in pre-mating and continuing through gestation and lactation in parental females, decreased number of implantation sites and decreasing trend in litter size. A 5 wt% classification threshold for the reproductive effects of substituted DPA was derived based on the NOAEL (50 mg/kg/day) and is consistent with the NOAEL in the supplier's study.

Section 12. Ecological information

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

Toxicity

Conclusion/Summary

Acute toxicity : Not expected to be harmful to aquatic organisms.

Chronic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

Not determined.

Date of issue/Date of revision : 7 August Date of previous issue : No previous edition Version : 1 7/10 2024

Section 12. Ecological information

Bioaccumulative potential

Not determined.

Mobility in soil Mobility

: Base oil component -- Expected to partition to sediment and wastewater solids. Low solubility and floats and is expected to migrate from water to the land.

Other ecological information

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Section 14. Transport information

	ADG	IMDG	IATA
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (0,0,0- triphenyl phosphorothioate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (0,0,0- triphenyl phosphorothioate)	Environmentally hazardous substance, liquid, n.o.s. (o,o,o-triphenyl phosphorothioate)
Transport hazard class(es)	9	9	9
Label(s) / Mark(s)	1 1 1 1 1 1 1 1 1 1	1 1 1 1 1 1 1 1 1 1	1 1 1 1 1 1 1 1 1 1
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.

Additional information

Section 14. Transport information

ADC

: The product is not regulated as a dangerous good when transported by road or rail in either an IBC, or in other container types if ≤500 kg. This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Hazchem code •3Z

<u>Special provisions</u> 274, 331, 335, 375, AU01

IMDG
 : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2

and 4.1.1.4 to 4.1.1.8.

Emergency schedules F-A, S-F Special provisions 274, 335, 969

IATA : This product is not regulated as a dangerous good when transported in sizes of ≤5 L

or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1,

5.0.2.6.1.1 and 5.0.2.8.

Quantity limitation Passenger and Cargo Aircraft: 450 L. Packaging instructions: 964. Cargo Aircraft Only: 450 L. Packaging instructions: 964. Limited Quantities -

Passenger Aircraft: 30 kg. Packaging instructions: Y964.

Special provisions A97, A158, A197, A215

Special precautions for

user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according to IMO instruments

: Not applicable.

Section 15. Regulatory information

Standard for the Uniform Scheduling of Medicines and Poisons

Not regulated.

Inventory list

Australia inventory (AIIC)

Canada inventory (DSL-NDSL)

China inventory (IECSC)

Japan inventory (CSCL)

China inventory (CSCL)

All components are listed or exempted.

Japan inventory (industrial Safety and

Health Act)

: All components are listed or exempted.

New Zealand Inventory of Chemicals

(NZIoC)

Philippines inventory (PICCS) : All components are listed or exempted.

Korea inventory (KECI) : All components are listed or exempted.

Taiwan Chemical Substances Inventory

(TCSI)

: All components are listed or exempted.

United States inventory (TSCA 8b) : All components are active or exempted.

Section 16. Any other relevant information

History

Date of issue/Date of

revision

: 7 August 2024

Date of previous issue

: No previous edition

Version : 1

Date of issue/Date of revision : 7 August Date of previous issue : No previous edition Version : 1 9/10

MOBIL SHC GEAR 460

Section 16. Any other relevant information

Key to abbreviations

: ADG = Australian Dangerous Goods

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group

SUSMP = Standard Uniform Schedule of Medicine and Poisons

UN = United Nations

Procedure used to derive the classification

Not classified.

References: Not available.

✓ Indicates information that has changed from previously issued version.

Product code : 201560409050_1166252

Notice to reader

"The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, ""ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest."

Date of issue/Date of revision : 7 August Date of previous issue : No previous edition Version : 1 10/10

2024