agentbox cheatsheet (1.3.0)

First session

```
uv tool install -e ./cli          # host CLI (stdlib, Python >= 3.11)
claude setup-token                 # one-year token, pasted into setup
agentbox setup                     # Docker check, images, token, self-test
agentbox init myproj --mount ~/Projects/myproj
cd ~/Projects/myproj && agentbox claude
```

Where `[profile]` is optional, the CLI picks the profile whose mount holds the current directory. Put `--` after all agentbox options; the words after it go to the agent or command.

Boxes and sessions

Command	What it does
`agentbox claude/codex/pi [profile] [--model M] [-- args]`	Interactive agent session.
`agentbox shell [profile] [-- cmd]`	Bash, or one command, in the box.
`agentbox up [profile]` / `down [profile]`	Start and keep up / stop. Home volume stays.
`agentbox down -v [profile]`	Full reset: home and gateway OAuth volumes removed.
`agentbox ls`	Profiles, state, mode, mounts, `image outdated`.
`agentbox login <profile> codex/pi`	Subscription login in the box (once per profile).
`agentbox validate <file>`	Check a profile file and print it resolved.
`agentbox doctor [profile]`	Full isolation self-test. A fast subset runs on every `up`.

Network

Command	What it does
`agentbox denied [profile] [--since S]`	Recent blocked requests.
`agentbox allow [profile] <domain>`	Add a domain; live reload, no restart.

Modes: `strict` (default; presets plus `allow`) or `open` (any public domain). Both: port 443 only, no IP literals, no host or LAN, no metadata. Presets: `anthropic`, `openai`, `github`, `dev`.

Secrets

Command	What it does
`agentbox secret set [--shared or profile] NAME [--stdin]`	Store (hidden prompt). Keychain `agentbox/<profile>/NAME`.
`agentbox secret ls/rm [--shared or profile] [NAME]`	Names and status, never values / delete.
`agentbox secret set/rm/ls --stack <name> [NAME]`	Secrets of a plain Compose stack: `agentbox/_stack/<name>/NAME`.
`agentbox stack ls [-C DIR]`	Manifest secrets: name, ref, present or missing.
`agentbox stack run [-C DIR] -- <command...>`	Run with `AGENTBOX_SECRET_<NAME>` and `<NAME>` in the env only.

Stack manifest `agentbox-stack.toml` (names only, safe to commit):

```
[stack]
name = "myapp"
compose_files = ["compose.yaml", "compose.secrets.yaml"]   # sets COMPOSE_FILE
[secrets]
API_KEY = {}                               # default Keychain item
OTHER = { ref = "keychain:service-name" }   # explicit item, read raw
```

Overlay `compose.secrets.yaml`: `secrets: { API_KEY: { environment: AGENTBOX_SECRET_API_KEY } }` and per service `secrets: [API_KEY]`. The value lands at `/run/secrets/API_KEY` (root, 0444). Start with `agentbox stack run -- docker compose up -d`.

Headless runs, scheduling, MCP, models

Command	What it does
`agentbox run <profile> --agent A --prompt-file F [--timeout T]`	Headless agent run; transcript and exit code recorded.
`agentbox run <profile> --cmd-file F [--timeout T]`	Command job: a shell script in the box, no agent.
`agentbox schedule add/ls/rm/edit/run-now`	launchd (macOS) or cron (Linux) jobs on the host.
`agentbox schedule report [--since S] [--post]`	Fleet report: due, ran, idle boxes. `--install` for a daily job.
`agentbox mcp login/status/logout <profile> <server>`	OAuth for an MCP upstream; the token stays in the gateway.
`--model ollama/<name>` or `remote/<name>`	Session shortcut: host Ollama model or a `[models.remote.*]` entry.

Maintenance

Command	What it does
`agentbox update [--check]`	Bump tool pins, rebuild, self-test; rollback if doctor fails.
`agentbox update --python-patch [--install [--at HH:MM]]`	Python patch only; `--install` makes the daily job.
`agentbox update --python-line X.Y --eol YYYY-MM`	Move Python to another line, after the lock check.
`agentbox update --prune [--dry-run]`	Remove superseded images and old build cache.

Profile keys (`~/.config/agentbox/profiles/<name>.toml`)

Key	Default	Meaning
`[box] agents`	all three	`claude`, `codex`, `pi`.
`[box] resources.cpus` / `memory`	`4` / `"8g"`	Box limits.
`[box] packages`	`[]`	apt packages; builds a cached derived image.
`[box] web_tools` / `skip_permissions`	`true` / `true`	Provider web tools; Claude permission prompts off.
`[[mount]] host`, `path`, `mode`, `allow_dotpath`	- / host path / `ro` / `false`	Host dir, container path, `ro` or `rw`.
`[network] mode`, `presets`, `allow`, `allow_http`	`strict` / all / `[]` / `false`	Egress policy.
`[secrets] NAME = {}`	profile scope, to `agent`	`shared`, `ref`, `to` (`agent`, `router`, `mcp-gateway`).
`[models.remote.<n>] api_base`, `key`	-	Remote model through the router; `key` goes to the router only.
`[mcp.servers.<n>] url` or `command`, `bearer` or `auth="oauth"`, `tools`	-	Upstream MCP server; `tools` allowlist.

Paths

Path	Content
`~/.config/agentbox/profiles/<name>.toml`, `config.toml`	Profiles, host settings.
`~/.local/state/agentbox/<name>/`	Generated config, logs, runs, schedules (0700).
`<state>/logs/egress/egress.log`, `logs/mcp/calls.jsonl`	Proxy access log, MCP call log.
`<state>/runs/<time>-<agent>/`, `<state>/schedules/<job>/`	Run records, scheduled job files.
`/run/secrets/<NAME>` (in a container)	A delivered secret. Docs: `docs/USAGE.md`, `docs/SECURITY.md`.