


DEVOPS TRAINING

DAY – 1 JENKINS (Installing and setting up Jenkins on a Linux Machine)


ip addr

```
root@Ubuntu:~# visudo
root@Ubuntu:~# ip addr
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group defau
lt qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
2: enp0s3: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP g
roup default qlen 1000
    link/ether 08:00:27:d6:98:b2 brd ff:ff:ff:ff:ff:ff
    inet 10.0.2.15/24 brd 10.0.2.255 scope global dynamic noprefixroute enp0s3
        valid_lft 77307sec preferred_lft 77307sec
    inet6 fe80::162f:82f9:fd14:3918/64 scope link noprefixroute
        valid_lft forever preferred_lft forever
root@Ubuntu:~#
```

Execute Shell (Commands)



Console Output



```
Dashboard > Nginx-Install2 > #1 > Console Output
nginx.service: A high performance web server and a reverse proxy server
Loaded: loaded (/lib/systemd/system/nginx.service; enabled; vendor
preset: enabled)
Active: active (running) since Mon 2025-03-17 22:16:35 IST; 2min 45s ago
Docs: man:nginx(8)
Main PID: 10213 (nginx)
Tasks: 2 (limit: 3503)
CGroup: /system.slice/nginx.service
├─10213 nginx: master process /usr/sbin/nginx -g daemon on;
master_process on;
└─10214 nginx: worker process

Mar 17 22:16:34 Ubuntu systemd[1]: Starting A high performance web server
and a reverse proxy server...
Mar 17 22:16:35 Ubuntu systemd[1]: nginx.service: Failed to parse PID from
file /run/nginx.pid: Invalid argument
Mar 17 22:16:35 Ubuntu systemd[1]: Started A high performance web server and
a reverse proxy server.
Finished: SUCCESS
```

Welcome Page

