


Data Mining Cluster Analysis: Basic Concepts and Algorithms

Lecture Notes for Chapter 8

Introduction to Data Mining
by
Tan, Steinbach, Kumar

What is Cluster Analysis?

- Finding groups of objects such that the objects in a group will be similar (or related) to one another and different from (or unrelated to) the objects in other groups



Applications of Cluster Analysis


□ Understanding

- Group related documents for browsing, group genes and proteins that have similar functionality, or group stocks with similar price fluctuations

	<i>Discovered Clusters</i>	<i>Industry Group</i>
1	Applied-Matl-DOWN,Bay-Network-Down,3-COM-DOWN,Cabletron-Sys-DOWN,CISCO-DOWN,HP-DOWN,DSC-Comm-DOWN,INTEL-DOWN,LSI-Logic-DOWN,Micron-Tech-DOWN,Texas-Inst-Down,Tellabs-Inc-Down,Natl-Semiconduct-DOWN,Oracl-DOWN,SGI-DOWN,Sun-DOWN	Technology1-DOWN
2	Apple-Comp-DOWN,Autodesk-DOWN,DEC-DOWN,ADV-Micro-Device-DOWN,Andrew-Corp-DOWN,Computer-Assoc-DOWN,Circuit-City-DOWN,Compaq-DOWN,EMC-Corp-DOWN,Gen-Inst-DOWN,Motorola-DOWN,Microsoft-DOWN,Scientific-Atl-DOWN	Technology2-DOWN
3	Fannie-Mae-DOWN,Fed-Home-Loan-DOWN,MBNA-Corp-DOWN,Morgan-Stanley-DOWN	Financial-DOWN
4	Baker-Hughes-UP,Dresser-Inds-UP,Halliburton-HLD-UP,Louisiana-Land-UP,Phillips-Petro-UP,Unocal-UP,Schlumberger-UP	Oil-UP

□ Summarization

- Reduce the size of large data sets




Clustering precipitation
in Australia



What is not Cluster Analysis?

- Supervised classification
 - Have class label information
- Simple segmentation
 - Dividing students into different registration groups alphabetically, by last name
- Results of a query
 - Groupings are a result of an external specification



Notion of a Cluster can be Ambiguous





How many clusters?




Six Clusters



Two Clusters




Four Clusters





Types of Clusterings

- A **clustering** is a set of clusters
- Important distinction between **hierarchical** and **partitional** sets of clusters
- Partitional Clustering
 - A division data objects into non-overlapping subsets (clusters) such that each data object is in exactly one subset
- Hierarchical clustering
 - A set of nested clusters organized as a hierarchical tree

Partitional Clustering




Original Points




A Partitional Clustering

Hierarchical Clustering




Hierarchical Clustering



Dendrogram

Hierarchical clustering - example



Other Distinctions Between Sets of Clusters

□ Exclusive versus non-exclusive

- In non-exclusive clusterings, points may belong to multiple clusters.
- Can represent multiple classes or ‘border’ points

□ Fuzzy versus non-fuzzy

- In fuzzy clustering, a point belongs to every cluster with some weight between 0 and 1
- Weights must sum to 1
- Probabilistic clustering has similar characteristics

□ Partial versus complete

- In some cases, we only want to cluster some of the data
- Ex: sportspersons in a class; badminton, tennis.... Non-players.

□ Heterogeneous versus homogeneous

- Cluster of widely different sizes, shapes, and densities


Types of Clusters

- Well-separated clusters
- Center-based clusters
- Contiguous clusters
- Density-based clusters
- Property or Conceptual
- Described by an Objective Function

Types of Clusters: Well-Separated

□ Well-Separated Clusters:

- A cluster is a set of points such that any point in a cluster is closer (or more similar) to every other point in the cluster than to any point not in the cluster.




3 well-separated clusters

Types of Clusters: Center-Based

□ Center-based


- A cluster is a set of objects such that an object in a cluster is closer (more similar) to the “center” of a cluster, than to the center of any other cluster
- The center of a cluster is often a **centroid**, the average of all the points in the cluster, or a **medoid**, the most “representative” point of a cluster



4 center-based clusters

Types of Clusters: Contiguity-Based

- Contiguous Cluster (Nearest neighbor or Transitive)
 - A cluster is a set of points such that a point in a cluster is closer (or more similar) to one or more other points in the cluster than to any point not in the cluster.




8 contiguous clusters

Types of Clusters: Density-Based

□ Density-based

- A cluster is a dense region of points, which is separated by low-density regions, from other regions of high density.
- Used when the clusters are irregular or intertwined, and when noise and outliers are present.




6 density-based clusters

Types of Clusters: Conceptual Clusters

- Shared Property or Conceptual Clusters
 - Finds clusters that share some common property or represent a particular concept.

.



2 Overlapping Circles

Types of Clusters: Objective Function

□ Clusters Defined by an Objective Function

- Finds clusters that minimize or maximize an objective function.
- Enumerate all possible ways of dividing the points into clusters and evaluate the 'goodness' of each potential set of clusters by using the given objective function. (NP Hard)
- Can have global or local objectives.
 - ◆ Hierarchical clustering algorithms typically have local objectives
 - ◆ Partitional algorithms typically have global objectives
- A variation of the global objective function approach is to fit the data to a parameterized model.
 - ◆ Parameters for the model are determined from the data.
 - ◆ Mixture models assume that the data is a 'mixture' of a number of statistical distributions.

Types of Clusters: Objective Function ...


- Map the clustering problem to a different domain and solve a related problem in that domain
 - Proximity matrix defines a weighted graph, where the nodes are the points being clustered, and the weighted edges represent the proximities between points
 - Clustering is equivalent to breaking the graph into connected components, one for each cluster.
 - Want to minimize the edge weight between clusters and maximize the edge weight within clusters

Graph-based clustering - illustrations

Illustration #1:



Illustration #2:




Characteristics of the Input Data Are Important

- Type of proximity or density measure
 - This is a derived measure, but central to clustering
- Sparseness
 - Dictates type of similarity
 - Adds to efficiency
- Attribute type
 - Dictates type of similarity
- Type of Data
 - Dictates type of similarity
 - Other characteristics, e.g., autocorrelation
- Dimensionality
- Noise and Outliers
- Type of Distribution

Clustering Algorithms

- Prototype-based clustering
- Graph-based clustering
- Density-based clustering

Prototype-based clustering



Types of Prototype-based clustering methods

- k-means clustering
- k-medoids clustering
- Hierarchical clustering
- Fuzzy k-means clustering
- Scale-based clustering
- Incremental clustering
- Self-organizing maps

K-means Clustering



- Partitional clustering approach
- Each cluster is associated with a **centroid** (center point)
- Each point is assigned to the cluster with the closest centroid
- Number of clusters, K , must be specified
- The basic algorithm is very simple

-
- 1: Select K points as the initial centroids.
 - 2: **repeat**
 - 3: Form K clusters by assigning all points to the closest centroid.
 - 4: Recompute the centroid of each cluster.
 - 5: **until** The centroids don't change
-


K-means Clustering – Details

- Initial centroids are often chosen randomly.
 - Clusters produced vary from one run to another.
- The centroid is (typically) the mean of the points in the cluster.
- ‘Closeness’ is measured by Euclidean distance, cosine similarity, correlation, etc.
- K-means will converge for common similarity measures mentioned above.
- Most of the convergence happens in the first few iterations.
 - Often the stopping condition is changed to ‘Until relatively few points change clusters’
- Complexity is $O(n * K * I * d)$
 - n = number of points, K = number of clusters,
 I = number of iterations, d = number of attributes

Two different K-means Clusterings



Optimal Clustering



Sub-optimal Clustering

Evaluating K-means Clusters

- Most common measure is Sum of Squared Error (SSE)
 - For each point, the error is the distance to the nearest cluster
 - To get SSE, we square these errors and sum them.



$$SSE = \sum_{i=1}^K \sum_{x \in C_i} dist^2(m_i, x)$$

- x is a data point in cluster C_i and m_i is the representative point for cluster C_i
 - ◆ can show that m_i corresponds to the center (mean) of the cluster
- Given two clusters, we can choose the one with the smallest error
- One easy way to reduce SSE is to increase K , the number of clusters
 - ◆ A good clustering with smaller K can have a lower SSE than a poor clustering with higher K

K-Means generates Voronoi tessellations


K-means partitions the input space using Nearest Neighbor criterion

Examples with $K = 2$




The boundary is the perpendicular bisector of the two centroids


Partition with $K = 3$




General K




Such partitions are
Called
Voronoi Tessellations




Voronoi Tessellation in 3D




Importance of Choosing Initial Centroids








Importance of Choosing Initial Centroids



Importance of Choosing Initial Centroids ...



Importance of Choosing Initial Centroids ...



Problems with Selecting Initial Points


- If there are K 'real' clusters then the chance of selecting one centroid from each cluster is small.
 - Chance is relatively small when K is large
 - If clusters are the same size, n , then

$$P = \frac{\text{number of ways to select one centroid from each cluster}}{\text{number of ways to select } K \text{ centroids}} = \frac{K!n^K}{(Kn)^K} = \frac{K!}{K^K}$$

- For example, if $K = 10$, then probability = $10!/10^{10} = 0.00036$
- Sometimes the initial centroids will readjust themselves in 'right' way, and sometimes they don't
- Consider an example of five pairs of clusters





10 Clusters Example

Iteration 4



Starting with two initial centroids in one cluster of each pair of clusters


10 Clusters Example



Starting with two initial centroids in one cluster of each pair of clusters



10 Clusters Example

Iteration 4



Starting with some pairs of clusters having three initial centroids, while other have only one.

10 Clusters Example



Starting with some pairs of clusters having three initial centroids, while other have only one.


Solutions to Initial Centroids Problem

- Multiple runs
 - Helps, but probability is not on your side
- Sample and use hierarchical clustering to determine initial centroids
- Select more than k initial centroids and then select among these initial centroids
 - Select most widely separated
- Postprocessing
- Bisecting K-means
 - Not as susceptible to initialization issues

Handling Empty Clusters

- Basic K-means algorithm can yield empty clusters
- Several strategies
 - Choose a point from the cluster with the highest SSE
 - If there are several empty clusters, the above can be repeated several times.

Empty clusters - example



2 natural clusters

K=3. chosen points 3, 5, and 6 as our initial cluster centers.


http://www.ceng.metu.edu.tr/~tcan/ceng465_s1011/Schedule/KMeansEmpty.html

Empty clusters - example

At the end of first iteration points 3, 1, 2, and 7 will be in one cluster. 4 and 5 will be in another cluster. And 6 will be in the last cluster.

Note here that the distance between 3 and 4 is larger than the distance between 4 and 5 and so 4 is assigned to the cluster represented by 5


Now, the cluster center for the red cluster moved closer to point 4 due to 1, 2, and 7. And the cluster center for the blue cluster moved away from 5 due to point 4.



http://www.ceng.metu.edu.tr/~tcan/ceng465_s1011/Schedule/KMeansEmpty.html

Empty clusters - example

In the next iteration point 4 will decide that it is closer to the red cluster and point 5 will decide that it is closer to the green cluster. This will cause the blue cluster to be empty.



http://www.ceng.metu.edu.tr/~tcan/ceng465_s1011/Schedule/KMeansEmpty.html

Updating Centers Incrementally

- In the basic K-means algorithm, centroids are updated after all points are assigned to a centroid
- An alternative is to update the centroids after each assignment (incremental approach)
 - Each assignment updates zero or two centroids
 - More expensive
 - Introduces an order dependency
 - Never get an empty cluster
 - Can use “weights” to change the impact

Pre-processing and Post-processing

□ Pre-processing

- Normalize the data
- Eliminate outliers

□ Post-processing


- Eliminate small clusters that may represent outliers
- Split 'loose' clusters, i.e., clusters with relatively high SSE
- Merge clusters that are 'close' and that have relatively low SSE

Bisecting K-means


- Bisecting K-means algorithm
 - Variant of K-means that can produce a partitional or a hierarchical clustering

```
1: Initialize the list of clusters to contain the cluster containing all points.
2: repeat
3:   Select a cluster from the list of clusters
4:   for  $i = 1$  to number_of_iterations do
5:     Bisect the selected cluster using basic K-means
6:   end for
7:   Add the two clusters from the bisection with the lowest SSE to the list of clusters.
8: until Until the list of clusters contains  $K$  clusters
```

Bisecting k-means



Bisecting K-means Example




Limitations of K-means


- K-means has problems when clusters are of differing
 - Sizes
 - Densities
 - Non-globular shapes

- K-means has problems when the data contains outliers.

Limitations of K-means: Differing Sizes




Original Points




K-means (3 Clusters)

Limitations of K-means: Differing Density




Original Points




K-means (3 Clusters)

Limitations of K-means: Non-globular Shapes




Original Points




K-means (2 Clusters)

Overcoming K-means Limitations




Original Points




K-means Clusters

One solution is to use many clusters.
Find parts of clusters, but need to put together.

Overcoming K-means Limitations



Original Points



K-means Clusters

K - Medoids


- K-means requires calculation of a mean vector which assumes that it is possible to “ADD” data objects
- In some cases such “addition” of data objects is not defined
- Only a distance or similarity measure is available
- K-medoids is the solution in such cases

Partitioning Around Medoids (PAM) or K – Medoids algorithm

- Initialize: randomly select k of the n data points as the medoids
- Associate each data point to the “closest” medoid.
 - For each medoid m
 - For each non-medoid data point o
 - ◆ Swap m and o and compute the total cost (SSE) of the configuration
- Select the configuration with the lowest cost.
- Repeat steps 2 to 4 until there is no change in the medoid.

$$SSE = \sum_{i=1}^K \sum_{x \in C_i} dist^2(m_i, x)$$

K-medoids example



N = 10 data points


K = 2

$c_1 = (3,4)$ and $c_2 = (7,4)$

Cluster₁ = {(3,4)(2,6)(3,8)(4,7)}

Cluster₂ = {(7,4)(6,2)(6,4)(7,3)(8,5)(7,6)}

So the total cost involved is 20.



Select one of the nonmedoids O'
Let us assume $O' = (7,3)$
So now the medoids are $c_1(3,4)$ and $O'(7,3)$

Reassign data to Medoids.
Recalculate SSE
= 22
So the new $C2 = O' = (7,3)$ is not good.
Try another nonmedoid data point and continue