

Lecture 10: Elementary Sorts

BT 3051 – Data Structures and Algorithms for Biology

Karthik Raman

Department of Biotechnology
Bhupat and Jyoti Mehta School of Biosciences
Indian Institute of Technology Madras

INTRODUCTION

Introduction

- ▶ Sorting is a very critical operation
- ▶ Perhaps the first step to searching

Introduction

- ▶ Sorting is a very critical operation
- ▶ Perhaps the first step to searching

Introduction

- ▶ Sorting is a very critical operation
- ▶ Perhaps the first step to searching

THE CLASSIC WORK
NEWLY UPDATED AND REVISED

The Art of Computer Programming

VOLUME 3
Sorting and Searching
Second Edition

DONALD E. KNUTH

Comparison-based Sorting Algorithms

<http://www.sorting-algorithms.com/>

The ideal sorting algorithm would have the following properties:

- ▶ **Stable:** Equal keys are not reordered
- ▶ Operates in place, requiring $O(1)$ extra space
- ▶ Worst-case $O(n \lg n)$ key comparisons
- ▶ Worst-case $O(n)$ swaps
- ▶ Adaptive: Speeds up to $O(n)$ when data is nearly sorted or when there are few unique keys

Comparison-based Sorting Algorithms

<http://www.sorting-algorithms.com/>

The ideal sorting algorithm would have the following properties:

- ▶ Stable: Equal keys are not reordered
- ▶ Operates in place, requiring $O(1)$ extra space
- ▶ Worst-case $O(n \lg n)$ key comparisons
- ▶ Worst-case $O(n)$ swaps
- ▶ Adaptive: Speeds up to $O(n)$ when data is nearly sorted or when there are few unique keys

Comparison-based Sorting Algorithms

<http://www.sorting-algorithms.com/>

The ideal sorting algorithm would have the following properties:

- ▶ Stable: Equal keys are not reordered
- ▶ Operates in place, requiring $O(1)$ extra space
- ▶ Worst-case $O(n \lg n)$ key comparisons
- ▶ Worst-case $O(n)$ swaps
- ▶ Adaptive: Speeds up to $O(n)$ when data is nearly sorted or when there are few unique keys

Comparison-based Sorting Algorithms

<http://www.sorting-algorithms.com/>

The ideal sorting algorithm would have the following properties:

- ▶ Stable: Equal keys are not reordered
- ▶ Operates in place, requiring $O(1)$ extra space
- ▶ Worst-case $O(n \lg n)$ key comparisons
- ▶ Worst-case $O(n)$ swaps
- ▶ Adaptive: Speeds up to $O(n)$ when data is nearly sorted or when there are few unique keys

Comparison-based Sorting Algorithms

<http://www.sorting-algorithms.com/>

The ideal sorting algorithm would have the following properties:

- ▶ Stable: Equal keys are not reordered
- ▶ Operates in place, requiring $O(1)$ extra space
- ▶ Worst-case $O(n \lg n)$ key comparisons
- ▶ Worst-case $O(n)$ swaps
- ▶ Adaptive: Speeds up to $O(n)$ when data is nearly sorted or when there are few unique keys

Comparison-based Sorting Algorithms

<http://www.sorting-algorithms.com/>

The ideal sorting algorithm would have the following properties:

- ▶ Stable: Equal keys are not reordered
- ▶ Operates in place, requiring $O(1)$ extra space
- ▶ Worst-case $O(n \lg n)$ key comparisons
- ▶ Worst-case $O(n)$ swaps
- ▶ Adaptive: Speeds up to $O(n)$ when data is nearly sorted or when there are few unique keys

There is no algorithm that has all of these properties!

Comparison-based Sorting Algorithms

<http://www.sorting-algorithms.com/>

The ideal sorting algorithm would have the following properties:

- ▶ Stable: Equal keys are not reordered
- ▶ Operates in place, requiring $O(1)$ extra space
- ▶ Worst-case $O(n \lg n)$ key comparisons
- ▶ Worst-case $O(n)$ swaps
- ▶ Adaptive: Speeds up to $O(n)$ when data is nearly sorted or when there are few unique keys

There is no algorithm that has all of these properties!

Therefore, choice of sorting algorithm depends on application!

Introduction to Sorting: Video

https://www.youtube.com/watch?v=cVMKXKoGu_Y, courtesy of CS unplugged

ELEMENTARY SORTS

Selection Sort

```
def SelectionSort(a):  
    n = len(a)  
    for i in range(n):  
        k = i  
        for j in range(i+1,n):  
            if (a[j]<a[k]):  
                k = j  
        a[i],a[k] = a[k], a[i]  
    return a
```

Properties

- ▶ Not stable
- ▶ $O(1)$ extra space
- ▶ $\Theta(n^2)$ comparisons
- ▶ $\Theta(n)$ swaps
- ▶ Not adaptive

Selection Sort

```
def SelectionSort(a):  
    n = len(a)  
    for i in range(n):  
        k = i  
        for j in range(i+1,n):  
            if (a[j]<a[k]):  
                k = j  
        a[i],a[k] = a[k], a[i]  
    return a
```

Properties

- ▶ Not stable
- ▶ $O(1)$ extra space
- ▶ $\Theta(n^2)$ comparisons
- ▶ $\Theta(n)$ swaps
- ▶ Not adaptive

Selection Sort

```
def SelectionSort(a):  
    n = len(a)  
    for i in range(n):  
        k = i  
        for j in range(i+1,n):  
            if (a[j]<a[k]):  
                k = j  
        a[i],a[k] = a[k], a[i]  
    return a
```

Properties

- ▶ Not stable
- ▶ $O(1)$ extra space
- ▶ $\Theta(n^2)$ comparisons
- ▶ $\Theta(n)$ swaps
- ▶ Not adaptive

Selection Sort

```
def SelectionSort(a):  
    n = len(a)  
    for i in range(n):  
        k = i  
        for j in range(i+1,n):  
            if (a[j]<a[k]):  
                k = j  
        a[i],a[k] = a[k], a[i]  
    return a
```

Properties

- ▶ Not stable
- ▶ $O(1)$ extra space
- ▶ $\Theta(n^2)$ comparisons
- ▶ $\Theta(n)$ swaps
- ▶ Not adaptive

Selection Sort

```
def SelectionSort(a):  
    n = len(a)  
    for i in range(n):  
        k = i  
        for j in range(i+1,n):  
            if (a[j]<a[k]):  
                k = j  
        a[i],a[k] = a[k], a[i]  
    return a
```

Properties

- ▶ Not stable
- ▶ $O(1)$ extra space
- ▶ $\Theta(n^2)$ comparisons
- ▶ $\Theta(n)$ swaps
- ▶ Not adaptive

Selection Sort

- ▶ Selection sort has the property of *minimising the number of swaps*
- ▶ May be useful in applications where swap cost is high!

Selection Sort

- ▶ Selection sort has the property of *minimising the number of swaps*
- ▶ May be useful in applications where swap cost is high!

Bubble Sort

```
def BubbleSort(a):  
    n = len(a)  
    for i in range(n - 1):  
        for j in range(n - 1 - i):  
            if a[j] > a[j+1]:  
                a[j], a[j+1] = a[j+1], a[j]  
    return a
```

Properties

- ▶ Stable
- ▶ $O(1)$ extra space
- ▶ $O(n^2)$ comparisons and swaps
- ▶ Is it adaptive?

Bubble Sort

```
def BubbleSort(a):  
    n = len(a)  
    for i in range(n - 1):  
        for j in range(n - 1 - i):  
            if a[j] > a[j+1]:  
                a[j], a[j+1] = a[j+1], a[j]  
    return a
```

Properties

- ▶ Stable
- ▶ $O(1)$ extra space
- ▶ $O(n^2)$ comparisons and swaps
- ▶ Is it adaptive?

Bubble Sort

```
def BubbleSort(a):  
    n = len(a)  
    for i in range(n - 1):  
        for j in range(n - 1 - i):  
            if a[j] > a[j+1]:  
                a[j], a[j+1] = a[j+1], a[j]  
    return a
```

Properties

- ▶ Stable
- ▶ $O(1)$ extra space
- ▶ $O(n^2)$ comparisons and swaps
- ▶ Is it adaptive?

Bubble Sort

```
def BubbleSort(a):  
    n = len(a)  
    for i in range(n - 1):  
        for j in range(n - 1 - i):  
            if a[j] > a[j+1]:  
                a[j], a[j+1] = a[j+1], a[j]  
    return a
```

Properties

- ▶ Stable
- ▶ $O(1)$ extra space
- ▶ $O(n^2)$ comparisons and swaps
- ▶ Is it adaptive?

Bubble Sort: Making it Adaptive

```
def BubbleSort(a):  
    n = len(a)  
    for i in range(n - 1):  
        swapped = False  
        for j in range(n - 1 - i):  
            if a[j] > a[j+1]:  
                a[j], a[j+1] = a[j+1], a[j]  
                swapped = True  
        if not swapped:  
            break  
    return a
```

How did we make it adaptive?

