```
1
     5189: <bar>:
 2
     518d: pushq %rbp
 3
    51fa<foo>:
4
 5
    51b3: pushq %rbp
    51b4: mov %rsp, %rbp
 6
 7
     51b7: sub $0x10, %rsp
     51bb: mov %rdi, -0x8(%rbp)
8
9
10
     51d9: callq <bar>
11
     . . . . . .
12
     51f4: callq <foo>
1. callq
  |xxxxxxxx| \leftarrow \%rbp
                                    |xxxxxxxx| \leftarrow \%rbp
  |xxxxxxxx|
                              \Rightarrow
                                     |xxxxxxxxx|
  |xxxxxxxx| \leftarrow \%rsp
                                      |xxxxxxxx|
                                     |ret \quad addr| \leftarrow \%rsp
2. pushq %rbp
  |xxxxxxxx| \leftarrow \%rbp
                                     ||xxxxxxxxx|| \leftarrow \%rbp
                                      |xxxxxxxx|
  |xxxxxxxx|
                              \Rightarrow
  |xxxxxxxx|
                                      |xxxxxxxx|
  |ret \quad addr| \leftarrow \%rsp
                                       |ret \quad addr|
                                         \%rbp \mid \leftarrow \%rsp
3. mov %rsp, %rbp
  |xxxxxxxxx| \leftarrow \%rbp
                                      |xxxxxxxxx|
  |xxxxxxxxx|
                              \Rightarrow
                                       |xxxxxxxx|
                                       |xxxxxxxx|
  |xxxxxxxx|
  |ret \quad addr|
                                       |ret \quad addr|
      \%rbp \mid \leftarrow \%rsp
                                       |origin\%rbp| \leftarrow \%rsp, \%rbp
4. sub $0x10, %rsp
  |xxxxxxxx| \leftarrow \%rbp
                                       |xxxxxxxxx|
  |xxxxxxxxx|
                                       |xxxxxxxx|
                              \Rightarrow
  |xxxxxxxx|
                                       |xxxxxxxx|
                                       |ret \quad addr|
  |ret \quad addr|
   |origin\%rbp| \leftarrow \%rsp, \%rbp
                                        |origin\%rbp| \leftarrow \%rbp
                                       |xxxxxxxx|
                                       |xxxxxxxx| \leftarrow \%rsp
5. mov %rdi, -0x8(%rbp)
```

 $|xxxxxxxx| \leftarrow \%rbp$

|xxxxxxxxx|

xxxxxxxx	\Rightarrow	xxxxxxxx
xxxxxxxx		xxxxxxxx
ret addr		ret addr
$ origin\%rbp \leftarrow \%rbp$		$ origin\%rbp \leftarrow \%rbp$
xxxxxxxx		\mid % rdi \mid
$\boxed{ xxxxxxxx } \leftarrow \%rsp$		$\underline{ xxxxxxxx } \leftarrow \%rsp$

6. callq

$$\begin{array}{lll} |xxxxxxxx| \leftarrow \%rbp & |xxxxxxxx| \\ |xxxxxxxx| & \Rightarrow & |xxxxxxxx| \\ |xxxxxxxx| & |xxxxxxxx| \\ |ret | addr| & |ret | addr| \\ |origin\%rbp| \leftarrow \%rbp & |origin\%rbp| \leftarrow \%rbp \\ |origin\%rdi| & |origin\%rdi| \\ |\underline{xxxxxxxx}| \leftarrow \%rsp & |xxxxxxxx| \\ |ret | addr| \leftarrow \%rsp \end{array}$$

7. pushq %rbp

$Stack\ before\ 518e:$

$$egin{aligned} 0xfe2f8 &
ightarrow |ret \quad addr| \ 0xfe2f0 &
ightarrow |origin\%rbp| \leftarrow \%rbp \ 0xfe2e8 &
ightarrow |origin\%rdi| \ 0xfe2e0 &
ightarrow |xxxxxxxxx| \ 0xfe2d8 &
ightarrow |ret \quad addr| \ 0xfe2d0 &
ightarrow | \ \%rbp \quad | \leftarrow \%rsp \end{aligned}$$