

ICT 5 Web Development
Chapter 6.1. Using MySQL with PHP

Objectives

- ◆ To understand the advantages of using databases to store Web data
- ◆ To learn how to prepare a MySQL database for use with PHP
- ◆ To learn how to store, retrieve, and update data in a MySQL database

2

Content

- ⇒ 1. Database and MySQL Overview
2. Basic SQL commands
 3. Creating a table
 4. Inserting data to a table
 5. Retrieving data from a table
 6. Updating data for a table

3

What is a database?

- ◆ A set of data organized into one or more computer files.
- ◆ Using files for product inventory is a type of database
- ◆ Generally the term is reserved for more formal database systems like access, Oracle or MySQL.

4

Advantages of Databases Over Files

- ◆ Faster access
- ◆ Better concurrent access
- ◆ Easier changes to data and scripts
- ◆ Increased security

5

Relational Database?

- ◆ A database is a collection of tables with defined relationships between them
- ◆ Columns define attributes of the data
 - All data in a column must have the same data type
- ◆ A record is stored in a row

table name →

Employees		
First Name	Last Name	Phone
Nadia	Li	2687
Madhu	Charu	7856
Ajuna	Kinsaka	4489
Wade	Randal	5257
Helen	Clark	2147

row →

column ↑

Primary key ↓

Product Number	Product	Cost	Weight	Number Avail
0	Hammer	\$5.00	12	123
1	Screw Driver	\$3.00	2	144
2	Wrench	\$2.50	1.5	244

6


Which Database System

- ◆ PHP works with a variety of databases that include:
 - Oracle
 - Access
 - Ingres
 - SQL Server
 - MySQL
- ◆ Will use MySQL since simple to use, free and very popular.

7

Using A Query Language

- ◆ When using a database, use a separate query language to work with database
- ◆ Within MySQL, use Structured Query Language (SQL), to access database



8

Content

1. Database and MySQL Overview
- ⇒ 2. Basic SQL commands
3. Creating a table
4. Inserting data to a table
5. Retrieving data from a table
6. Updating data for a table

9

2. Basic SQL commands

- Connecting to MySQL from the Command Line
`mysql -uusername -p`

E.g.:
`>mysql -uroot`

- To EXIT MySQL:
`EXIT;`

2. Basic SQL Commands (2)

- ◆ SQL statements end with a semicolon
- ◆ View databases
`SHOW DATABASES;`
- ◆ Creating a database
`CREATE DATABASE trii;`
- ◆ Importing a database:
`mysql -uusername -ppassword
databasename < filename.sql`
E.g.:
`mysql -uroot trii < trii.sql`

2. Basic SQL Commands (2)

- ◆ Use database *databasename*
`USE databasename;`
- ◆ Display all tables in a database
`SHOW TABLES;`
- ◆ View column details for a table
`DESC tablename;`

Creating a Database Instance

- ◆ Once you have access to a server with MySQL installed, need to get a database instance created for you.
 - Usually created by a database administrator
 - Creates a database instance, userid and password.

13

Content

1. Database and MySQL Overview
2. Basic SQL commands
- ⇒ 3. Creating a table
4. Inserting data to a table
5. Retrieving data from a table
6. Updating data for a table

14

3. Creating a table

- ◆ Once database instance is created need to create your tables.
 - Use SQL CREATE TABLE command

The name of the table. →

```
CREATE TABLE Products
```

First table column can hold integer data. →

```
(ProductID INT,
```

Second table column can hold character data. →

```
Product_descr TEXT);
```

SQL commands are shown in upper case but either upper or lower case can be used.

15

MySQL Data Types

- ◆ TEXT
 - hold a large amount of character data
 - Use space inefficiently since it reserves space for up to 65,535 characters.
- ◆ CHAR(N)
 - hold a fixed length string of up to N characters (N must be less than 256).
- ◆ VARCHAR(N)
 - hold a variable length string of up to N characters
 - removes any unused spaces on the end of the entry.

16

MySQL Data Types (2)

- ◆ INT
 - hold an integer with a value from about –2 billion to about 2 billion.
- ◆ INT UNSIGNED
 - hold an integer with a value from 0 to about 4 billion.
- ◆ SMALLINT
 - hold an integer with a value from –32,768 to 32,767.
- ◆ SMALLINT UNSIGNED
 - hold an integer with a value from 0 to 65,535.
- ◆ DECIMAL(N,D)
 - a number that supports N total digits, of which D digits are to the right of the decimal point.

17

Some additional CREATE TABLE Options

- ◆ Can specify some additional options in CREATE TABLE:

```
CREATE TABLE Products
(ProductID INT UNSIGNED NOT NULL
Product_desc VARCHAR(50),
Cost INT,
Weight INT,
Numb INT);
```

An INT UNSIGNED means that ProductID must be positive values.

ProductID must be specified for each row.

AUTO INCREMENT PRIMARY KEY,

Up to 50 characters long

Automatically add one to each new ProductID.

Make this the primary key for table.

18

Issuing CREATE TABLE From PHP Script Segment

```
1. $connect = mysql_connect($server, $user, $pass);
2. if ( !$connect ) {
3.     die ("Cannot connect to $server using $user");
4. } else {
5.     mysql_select_db('MyDatabaseName');
6.     $SQLcmd = 'CREATE TABLE Products(
        ProductID INT UNSIGNED NOT NULL
        AUTO_INCREMENT PRIMARY KEY,
        Product_desc VARCHAR(50), Cost INT,
        Weight INT, Numb INT)';
7.     mysql_query($SQLcmd, $connect);
8.     mysql_close($connect);
9. }
```

Connect to MySQL

Issue the SQL query to the database.

Updated API: https://www.w3schools.com/php/php_mysql_connect.asp

19

Full Script

```
1. <html><head><title>Create Table</title></head><body>
2. <?php
3. $server = 'localhost';
4. $user = 'phppgm';
5. $pass = 'mypasswd';
6. $mydb = 'mydatabase';
7. $table_name = 'Products';
8. $connect = mysql_connect($server, $user, $pass);
9. if (!$connect) {
10.     die ("Cannot connect to $server using $user");
11. } else {
12.     $SQLcmd = "CREATE TABLE $table_name (
        ProductID INT UNSIGNED NOT NULL
        AUTO_INCREMENT PRIMARY KEY,
        Product_desc VARCHAR(50),
        Cost INT, Weight INT, Numb INT)";
```

20

Full Script (2)


```

13. mysql_select_db($mydb);
14. if (mysql_query($SQLcmd, $connect)){
15.     print '<font size="4" color="blue" >Created Table';
16.     print "<i>$table_name</i> in database<i>$mydb</i><br></font>";
17.     print "<br>SQLcmd=$SQLcmd";
18. } else {
19.     die ("Table Create Creation Failed SQLcmd=$SQLcmd");
20. }
21. mysql_close($connect);
22. }
23. ?></body></html>

```

21


Script Browser Output



22

MySQL Visual Designer Tools

- ◆ phpMyAdmin (web-app)
- ◆ MySQL Workbench (Win, Linux, Mac)
- ◆ **SQLyog**
- ◆ ...



23

Content

1. Database and MySQL Overview
2. Basic SQL commands
3. Creating a table
- ⇒ 4. Inserting data to a table
5. Retrieving data from a table
6. Updating data for a table

24

4. Inserting data to a table

- ◆ Once database is created will need to insert data
- ◆ Use the SQL INSERT command

```
INSERT INTO Products VALUES
( '0', 'Hammer', 5, 12, 123 );
```

Table Name

Each item goes into a separate table column in a table row.

25

A Full Example

- ◆ Consider an application that allows end-user to enter inventory data:

Item Description:

Weight:

Cost:

Number Available:


26

```
1. <html><head><title>Insert Results</title></head><body>
2. <?php
3. $host = 'localhost';
4. $user = 'phpgmn';
5. $passwd = 'mypasswd';
6. $database = 'mydatabase';
7. $connect = mysql_connect($host, $user, $passwd);
8. $table_name = 'Products';
9. $query = "INSERT INTO $table_name VALUES
10. ('0', '$Item', '$Cost', '$Weight', '$Quantity')";
11. print "The Query is <i>$query</i><br>";
12. mysql_select_db($database);
13. print "<br><font size='4' color='blue'>";
14. if (mysql_query($query, $connect)){
15.     print "Insert into $database was successful!</font>";
16. } else {
17.     print "Insert into $database failed!</font>";
18. } mysql_close ($connect);
19. ?></body></html>
```

Receiving PHP Script

27

Script Output



28

Content

1. Database and MySQL Overview
2. Basic SQL commands
3. Creating a table
4. Inserting data to a table
- ⇒ 5. Retrieving data from a table
6. Updating data for a table

29

5. Retrieving data from a table

- ◆ Two major ways to retrieve data:
 - Retrieving all elements from a table
 - Searching for specific records in a table
- ◆ To retrieve all data, use following SQL command

SQL SELECT Statement.

SELECT * FROM TableName;

The asterisk ("*") means get all the data

The name of the table to get the data from.

30

5. Retrieving Data (2)

- ◆ To retrieve all data, use following SQL command

SQL SELECT Statement.

SELECT * FROM TableName;

The asterisk ("*") means get all the data

The name of the table to get the data from.

- ◆ For example

1. `$connect = mysql_connect('localhost', 'phppgm', 'mypasswd');`
2. `$SQLcmd = 'SELECT * FROM Products';`
3. `mysql_select_db('MyDatabase');`
4. `$results_id = mysql_query($SQLcmd, $connect);`

31

5.1. Using mysql_fetch_row()

- ◆ Use the `mysql_fetch_row()` function to retrieve data on row at a time

Access each row from the `my_sql_query()` results. (A different row each iteration).

`$results_id` variable is set from `my_sql_query()` function call.

```
while ( $row = mysql_fetch_row($results_id) ) {  
    foreach ( $row as $field ) {  
        print "Field=$field ";  
    }  
}
```

Output each item of the `$row` array.

Access each field in the table row results.

32

A Script Example

```

1. <html><head><title>Table Output</title></head><body>
2. <?php
3. $host= 'localhost';
4. $user = 'phppgm';
5. $passwd = 'mypasswd';
6. $database = 'phppgm';
7. $connect = mysql_connect($host, $user, $passwd);
8. $table_name = 'Products';
9. print '<font size="5" color="blue">';
10. print "$table_name Data</font><br>";
11. $query = "SELECT * FROM $table_name";
12. print "The query is <i>$query </i><br>";
13. mysql_select_db($database);
14. $results_id = mysql_query($query, $connect);
15. if ($results_id) {
16.     print '<table border=1>';
17.     print '<th>Num<th>Product<th>Cost<th>Weight<th>Count';

```

33

A Script Example (2)

```

18.     while ($row = mysql_fetch_row($results_id)){
19.         print '<tr>';
20.         foreach ($row as $field) {
21.             print "<td>$field</td> ";
22.         }
23.         print '</tr>';
24.     }
25. } else { die ("Query=$query failed!"); }
26. mysql_close($connect);
27. ?> </table></body></html>

```

34

Script Output

Num	Product	Cost	Weight	Count
1	Hammer	12	5	123
2	Screw Driver	2	3	144
3	Wrench	1	2	244

35

5.2. Searching For Specific Records

- ◆ Use the SELECT SQL statement with a WHERE clause

– SELECT * FROM TableName WHERE (test expression);

The asterisk ("*") means look at all table columns.

Specify the table name to look at.

Specify a test expression to evaluate

36

Selected WHERE CLAUSE Test Operators

Operator	SQL Query Example	Meaning
=	SELECT * FROM Products WHERE (Product_desc = 'Hammer');	Retrieve those rows from the Products table that have a Product_desc column with a value equal to Hammer.
>	SELECT * FROM Products WHERE (Cost > '5');	Retrieve those rows from the Products table that have a Cost column with a value greater than 5.
<	SELECT * FROM Products WHERE (Numb < '3');	Retrieve those rows from the Products table that have a Numb column with a value less than 3.
<=	SELECT * FROM Products WHERE (Cost <= '3');	Retrieve those rows from the Products table that have a Cost column with a value less than or equal to 3.
>=	SELECT * FROM Products WHERE (Weight >= '10');	Retrieve those rows from the Products table that have a Weight column with a value greater than or equal to 10.

Slide 8-37

Consider the following example ...

- ◆ The following example searches a hardware inventory database for a specific part name entered by the user.
- ◆ The form uses the following key HTML form element definition.

```
-<input type="text" name="Search"
size="20">
```

38

PHP Source

```
1. <html><head><title>Search Results</title></head><body>
2. <?php
3. $host= 'localhost';
4. $user = 'phppgm';
5. $passwd = 'mypasswd';
6. $database = 'phppgm';
7. $connect = mysql_connect($host, $user, $passwd);
8. $table_name = 'Products';
9. print '<font size="5" color="blue">';
10. print "$table_name Data</font><br>";
11. $query = "SELECT * FROM $table_name WHERE
            (Product_desc = '$Search')";
12. print "The query is <i>$query</i> <br>";
13. mysql_select_db($database);
14. $results_id = mysql_query($query, $connect);
```


39

PHP Source (2)

```
15. if ($results_id) {
16.     print '<br><table border=1>';
17.     print '<th>Num<th>Product<th>Cost<th>Weight <th>Count';
18.     while ($row = mysql_fetch_row($results_id)) {
19.         print '<tr>';
20.         foreach ($row as $field) {
21.             print "<td>$field</td> ";
22.         }
23.         print '</tr>';
24.     }
25. } else { die ("query=$Query Failed");}
26. mysql_close($connect);
27. ?> </body></html>
```

40

Would have the following output ...



41

Content

1. Database and MySQL Overview
2. Basic SQL commands
3. Creating a table
4. Inserting data to a table
5. Retrieving data from a table
- ⇒ 6. Updating data for a table

42

6. Updating data for a table

- ◆ Use SQL UPDATE command when needing to update a database record:

```
UPDATE Table_name
SET col1=chng_express1,col2=chng_express2, ...
WHERE test_expression
```

Specify the name of the table to update.

Optionally specify a WHERE clause and test expression.

Specify one or more table column to receive the results of an expression. Optionally specify a WHERE

43

For Example ...

- ◆ The following searches the Products table for values of Product_desc equal to Hammer.

```
UPDATE Products
SET Cost=2
WHERE Product_desc = 'Hammer'
```

44

For Example ...

- ◆ The following looks through the Products table for values of Product_desc equal to Hammer.
- ◆ When it finds it, it decrements the Count column value by 1.

```
UPDATE Products
SET Count=Count-1
WHERE 'Product_desc=Hammer'
```

45

A Full Example ...

- ◆ Consider the following example
 - Displays current inventory
 - Asks end-user to decrement value for 1 item
 - Uses the following HTML

```
Hammer: <input type="radio" name="Product"
        value="Hammer">
Screwdriver: <input type="radio"
             name="Product" value="Screwdriver">
Wrench: <input type="radio" name="Product"
         value="Wrench">
```

46

Full Example

```
1. <html><head><title>Product Update
   Results</title></head><body>
2. <?php
3. $host= 'localhost';
4. $user = 'phppgm';
5. $passwd = 'mypasswd';
6. $database = 'phppgm';
7. $connect = mysql_connect($host, $user, $passwd);
8. $table_name = 'Products';
9. print '<font size="5" color="blue">';
10. print "Update Results for Table
    $table_name</font><br>\n";
11. $query = "UPDATE $table_name
    SET Numb = Numb-1
    WHERE (Product_desc = '$Product')";
12. print "The query is <i> $query </i> <br><br>\n";
13. mysql_select_db($database);
```

47

A Full Example (2)

```
14. $results_id = mysql_query($query, $connect);
15. if ($results_id){
16.   Show_all($connect, $database,$table_name);
17. } else {
18.   print "Update=$query failed";
19. }
20. mysql_close($connect);
```


48

A Full Example (3)

```
21. function Show_all($connect, $database, $table_name){
22.     $query = "SELECT * from $table_name";
23.     $results_id = mysql_query($query, $connect);
24.     print '<table border=1><th> Num </th>
        <th>Product</th><th>Cost</th>
        <th>Weight</th><th>Count</th>';
26.     while ($row = mysql_fetch_row($results_id)) {
27.         print '<tr>';
28.         foreach ($row as $field){
29.             print "<td>$field</td> ";
30.         }
31.         print '</tr>';
32.     }
33. }
34. ?> </body></html>
```

49

Would output the following:



Slide 8:50

Question?



51