1. Scope

1.1. This Regulation applies to test lamps of category T.

5. Specifications

5.1. The tests shall be made in the following order:

Table 1 Order of tests

Reference	Test	Samples		
		a	b	c
Annex 2	Heat: 48 h at 65 °C visual inspection	x x	x x	
5.3.	Colour	x		x
	Photometry		x	x

5.2. The intensity shall stay within these limits:

Limits expressed in cd		
Point	**Minimum**	**Maximum**
HV	0.3	30
10 U	0.1	5

5.3. The drive cycle is:

Time s	Speed per cent
1	0
2	1
3	4
4	9
5	16
6	25
7	36
8	49
9	64
10	81
11	100
12	100
13	100
14	
15	81
16	64
17	49
18	36
19	25
20	16
21	9
22	4

5.4. Without borders, a table stays as lines:

Red	R
Amber	A

5.5. The manufacturer shall fill in:

Rear (m)	Front (m)

5.6. The test points are:

No.	Point
1	Point P01
2	Point P02
3	Point P03
4	Point P04
5	Point P05
6	Point P06
7	Point P07
8	Point P08
9	Point P09
10	Point P10
11	Point P11
12	Point P12
13	Point P13
14	Point P14
15	Point P15
16	Point P16
17	Point P17
18	Point P18

5.7. The lamp shall be red.