UN R999 (version 2.1.0)

Consolidated text of this version, rendered by Certivity for the hackathon.
Role in the hackathon: base version.

Introduction

This made-up Regulation exists to test how regulation PDFs are split into paragraphs.

1. Scope

1.1. This Regulation applies to test lamps of category T.[1]

1 As defined in the Consolidated Resolution on test lamps.

1.2. This Regulation does not apply to:

1.2.1. Lamps that are not tested;

1.2.3. Lamps that are tested twice.

2. Definitions

For the purposes of this Regulation:

2.1. "Test lamp" means a lamp that is tested.

2.2. "Category T" means the category of test lamps.

5. Specifications

5.1. Photometric requirements

5.1.1. The luminous intensity shall not exceed 30 cd above the horizontal plane described in paragraph
5.3. of this Regulation, measured as in UN Regulation No.
149. Lamps of category T are measured once.

5.1.2. The intensity distribution shall be measured at the following points:
Point 01 at 0 degrees
Point 02 at 1 degree
Point 03 at 2 degrees
Point 04 at 3 degrees
Point 05 at 4 degrees
Point 06 at 5 degrees
Point 07 at 6 degrees
Point 08 at 7 degrees
Point 09 at 8 degrees
Point 10 at 9 degrees
Point 11 at 10 degrees
Point 12 at 11 degrees

Point 13 at 12 degrees
Point 14 at 13 degrees
Point 15 at 14 degrees
Point 16 at 15 degrees
Point 17 at 16 degrees
Point 18 at 17 degrees
Point 19 at 18 degrees
Point 20 at 19 degrees
Point 21 at 20 degrees
Point 22 at 21 degrees
Point 23 at 22 degrees
Point 24 at 23 degrees
Point 25 at 24 degrees
Point 26 at 25 degrees
Point 27 at 26 degrees
Point 28 at 27 degrees
Point 29 at 28 degrees
Point 30 at 29 degrees

1	Minimum intensity	0.3 cd
2	Maximum intensity	30 cd

5.2. The colour of the light shall be red.

6. Transitional provisions

6.1. No Contracting Party shall refuse approvals under this version.

Annex 1 Communication

(Maximum format: A4 (210 x 297 mm))

1. Name of the manufacturer: .....

2. Type of lamp: .....

Annex 2 Test procedures

Part 1 - Resistance to heat

1. Test procedure

1.1. The lamp shall be kept for 48 hours at 65 °C.

2. After this test, no cracking shall be visible.

Part 2 - Resistance to water

1. The lamp shall be immersed for 10 minutes in water.

Annex 2 - Appendix 1 Test report

1. Report number: .....

Annex 9 K Fire resistance

1. The lamp shall not burn.