

APLC Design Summary

Instrument	USORT
nPup	128 x 128 pixels
Coronagraphic throughput (transmitted energy)	0.2957
Core throughput (encircled energy)	0.24
Lyot stop inner diameter (% of inscribed circle)	0.0
Lyot stop outer diameter (% of inscribed circle)	0.99
Bandpass	15.0%
# wavelengths	5
FPM radius (grayscale)	3.8 λ/D
nFPM	150 pixels
IWA — OWA	3.7—14.0 λ/D
Contrast constraint	10^{-10}
Lyot Stop alignment tolerance	0 pixels


Input Files :

- ▷ *Pupil file* : USORT/TelAp_USORT_offaxis_ovsamp16_N0128.fits
- ▷ *Lyot stop file* : USORT/LS_USORT_hex_ID0000_OD0990_ovsamp16_N0128.fits


Solution File :

▷ 07_USORT_N128_FPM380M0150_IWA0370_OWA01400_C10_BW15_Nlam5_LS_ID_ID00_ODOD09_Is_0_ovsamp16_N.fits


Fri Oct 27 18:24:07 2023




*On – axis PSF in log irradiance,
normalized to the peak irradiance value.*




Radial intensity profile for the broadband APLC design at 11 simulated wavelengths centered around λ_0/D and equally spatially sampled over the 15.0% bandpass. The black curve shows the average intensity across the 11 wavelength samples. The dashed red vertical lines delimit the high-contrast dark zone (between 3.7 and $14.0 \lambda_0/D$). The blue dotted line delimits the FPM radius, set to $3.8 \lambda_0/D$.






Average broadband normalized irradiance
within 0 pixels of Lyot stop misalignment.



Analysis Summary

Apodizer &
Telescope Aperture



Lyot plane





Image plane



Lyot plane
w/lyot stop







Image plane
w/FPM




Final image plane






Pupil core throughput:	0.6163835963822561
Lyot stop core throughput:	0.44338273489435265
Maximum core throughput:	0.14793426808265467
Maximum core throughput w.r.t. pupil core throughput:	0.24000357723814542
Maximum core throughput w.r.t. Lyot stop core throughput:	0.33364913976161886
Inner working angle:	4.028276853284988 λ_0/D


$3.00 \lambda_0/D$




$3.25 \lambda_0/D$




$3.50 \lambda_0/D$




$3.75 \lambda_0/D$




$4.00 \lambda_0/D$




$4.25 \lambda_0/D$




$4.50 \lambda_0/D$




$4.75 \lambda_0/D$



Broadband normalized irradiance for four representative levels of residual pointing jitter.





Azimuthally averaged raw contrast for four representative levels of rms residual pointing jitter.