



ACCELIO™

Sample Data File

```
^reformat trunc
^symbolset WINLATIN1
^field trans_date
2000-01-1
^field description
Description for item #1
^field trans_type
TYPE1
^field trans_amount
11.00
^page 1
^field trans_date
2000-01-2
^field description
Description for item #2
^field trans_type
TYPE2
^field trans_amount
11.00
^page 1
^field trans_date
2000-01-3
^field description
Description for item #3
^field trans_type
TYPE3
```

Sample Bookmark File

```
[invoices]
Invoices by Date=0
trans_date=1,A
[type]
Invoices by Item Type=0
trans_type=1,A
[amount]
Invoices by Transaction Amount=0
trans_amount=1,D
```

The example bookmark file includes three distinct sections:

- Invoices sorted, ascending, by date.
- Invoices sorted, ascending, by item type.
- Invoices sorted, descending, by transaction amount.



Sample Files

This sample package contains:

Filename	Description
ap_bookmark.IFD	The template design.
ap_bookmark.mdf	The template targeted for PDF output.
ap_bookmark.dat	A sample data file in DAT format.
ap_bookmark.bmk	A sample bookmark file.
ap_bookmark.pdf	Sample PDF output.
ap_bookmark_doc.pdf	A document describing the sample.

Deploying the Sample

To deploy this sample in your environment:

1. Open the template design **ap_bookmark.IFD** in Output Designer and recompile the template for the appropriate presentment target.
2. Modify the **-z** option in the **^job** command in the data file **ap_bookmark.dat** to:
 - Identify the target output device.
 - Identify the bookmark file using the **-abmk** command.
 - Identify the section for which to generate bookmarks, if desired, using the **-abms** command.

For example,

To bookmark by ...	Use the command line parameter ...
Invoices	-abmk ap_bookmark.bmk -abms invoices
Type	-abmk ap_bookmark.bmk -abms type
Amount	-abmk ap_bookmark.bmk -abms amount



ACCELIO™

3. Place the accompanying files in directories consistent with your implementation:
 - Place **ap_bookmark.IFD** in the **Designs** subdirectory for Output Designer.
 - Place **ap_bookmark.mdf** in the forms subdirectory accessible to Central.
 - Place **ap_bookmark.bmk** in an addressable directory.

Running the Sample

- To run this sample, place **ap_bookmark.dat** in the collector directory scanned by Central.