

SIMATS ENGINEERING (SAVEETHA SCHOOL OF ENGINEERING)

Department of Computer Science and Engineering

CO4 ASSESSMENT TOOL 1 – Test Case Design Assignment

Course Code:	CSA10	Course Title:	Software Engineering
CO Assessed:	CO4	Assessment:	Assessment Tool 1 – Test Case Design Assignment
Weightage:	20%	Total Marks:	25
CO4 Statement:	Implement robust testing, quality assurance, and DevOps practices, emphasizing security, reliability, and ethics		
Student Name:		Reg. No.:	
Date:		Duration:	60 minutes

Code of Conduct

I _____ (Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment. I understand that any violation of academic integrity rules will result in disciplinary action.

Signature of the Student: _____

Annexure A – Test Case Design Assignment

Instructions to Students:

Each student is assigned an individual problem statement. Based on the assigned problem statement, **design and document comprehensive test cases** to verify the correctness, functionality, reliability, and usability of the proposed system.

Your test case design should include:

1. Identify the **functional and non-functional requirements** to be tested.
2. Identify the **test scenarios** for the assigned problem statement.
3. Prepare detailed **test cases** covering normal, boundary, invalid, and exceptional conditions.
4. Include **Test Case ID, Test Scenario, Test Steps, Test Data, Expected Result, Actual Result, and Pass/Fail Status**.
5. Apply appropriate **test design techniques** such as Equivalence Partitioning, Boundary Value Analysis, Decision Table, or State Transition Testing wherever applicable.
6. Ensure that the test cases provide adequate **requirement and functional coverage** for the assigned system.

Deliverable: Submit a Test Case Design document containing the identified scenarios, test cases, test data, expected results, and test coverage based on the individual problem statement.

Rubrics for Calculation

Evaluation Criteria	Excellent (4 Marks)	Good (3 Marks)	Satisfactory (2 Marks)	Needs Improvement (1 Mark)
Requirement & Test Scenario Identification(15%)	Clearly identifies all relevant functional/non-functional requirements and comprehensive test scenarios	Identifies most requirements and scenarios	Identifies basic requirements and scenarios	Requirements/scenarios are incomplete or unclear
Test Case Design & Completeness(25%)	Comprehensive test cases covering normal, boundary, invalid, and exceptional conditions	Covers most important conditions with minor gaps	Covers basic conditions but misses several important cases	Test cases are very limited or incomplete
Test Data & Expected Results(20%)	Appropriate test data with precise, measurable expected results for every test case	Mostly appropriate test data and expected results	Some test data/results are unclear or incomplete	Test data and expected results are largely missing/incorrect
Application of Test Design Techniques(15%)	Correctly applies multiple techniques such as Equivalence Partitioning, Boundary Value Analysis, Decision Table, and State Transition	Correctly applies at least two relevant techniques	Applies one technique with limited justification	Techniques are not applied or incorrectly applied
Traceability & Test Coverage(15%)	Excellent mapping between requirements, scenarios, and test cases with strong coverage	Good traceability and coverage with minor gaps	Partial traceability and moderate coverage	Poor/no traceability and inadequate coverage
Documentation & Presentation(10%)	Well-structured, clear, professional, consistent, and easy to understand	Well-organized with minor presentation issues	Adequately organized but has some clarity/formatting issues	Poorly organized, unclear, or incomplete documentation

SIMATS ENGINEERING (SAVEETHA SCHOOL OF ENGINEERING)

Department of Computer Science and Engineering

CO4 Assessment Tool 1 – Test Case Design Assignment

TEST CASE DESIGN REPORT

Problem Statement 38: Intelligent Smart Port Operations and Cargo Management Platform

Course Code	CSA1013	Course Title	Software Engineering
CO Assessed	CO4	Assessment	Assessment Tool 1 – Test Case Design
Student Name	Spandana	Registration Number	192525160
Faculty In-Charge	Latha	Weightage / Marks	20% / 25

1. Problem Statement Summary

1.1 Industry Context

Modern seaports manage high volumes of cargo and vessel traffic, requiring efficient logistics coordination and real-time operational monitoring. AI, IoT, RFID, GPS, and cloud technologies enable intelligent cargo tracking, automated scheduling, and predictive analytics, improving port productivity and reducing operational delays.

1.2 Problem Statement

Port authorities often experience operational inefficiencies due to cargo congestion, manual documentation, delayed vessel scheduling, and limited visibility of cargo movement. These challenges increase turnaround time and logistics costs. The Intelligent Smart Port Operations and Cargo Management Platform is required to monitor cargo movement using IoT devices, optimize berth allocation, predict cargo handling delays using AI, automate documentation processes, and provide real-time operational dashboards, while enhancing logistics efficiency and supporting secure, transparent port operations.

1.3 Objectives

- Monitor cargo movement in real time.
- Optimize berth and vessel scheduling.
- Predict cargo handling delays using AI.
- Automate logistics documentation.
- Improve warehouse coordination.
- Generate operational performance reports.
- Enhance cargo security.
- Increase port operational efficiency.

1.4 Expected Outcomes

- Reduced cargo handling time.
- Improved logistics efficiency.
- Better vessel scheduling.
- Enhanced cargo visibility.
- Lower operational costs.
- Improved port productivity.
- Increased supply chain reliability.
- Better customer service.

2. Functional and Non-Functional Requirement

2.1 Functional Requirements (FR)

Req. ID	Functional Requirement
FR1	The system shall track and display real-time cargo location and movement using IoT sensors, RFID tags, and GPS devices.
FR2	The system shall optimize berth allocation for arriving vessels based on vessel size, cargo type, and berth availability.
FR3	The system shall optimize vessel scheduling to minimize vessel waiting and turnaround time.
FR4	The system shall use AI-based predictive analytics to forecast cargo handling delays.
FR5	The system shall automatically generate and validate logistics documentation (e.g., bill of lading, customs declaration, manifest).
FR6	The system shall coordinate warehouse storage allocation with incoming and outgoing cargo volumes.
FR7	The system shall generate operational performance reports and real-time dashboards for port authorities.
FR8	The system shall enhance cargo security through access control, tracking alerts, and tamper detection.
FR9	The system shall send automated notifications/alerts for delays, congestion, or security breaches.
FR10	The system shall maintain a searchable log/history of cargo movement and documentation transactions.

2.2 Non-Functional Requirements (NFR)

Req. ID	Category	Non-Functional Requirement
NFR1	Performance	The operational dashboard shall refresh cargo location and status data within 5 seconds.
NFR2	Scalability	The system shall support real-time monitoring of at least 5,000 concurrent cargo units without degradation.
NFR3	Reliability	The system shall maintain an uptime of 99.5% or higher during port operating hours.
NFR4	Security	All cargo, vessel, and documentation data shall be encrypted (AES-256) in transit and at rest.
NFR5	Usability	Port operators shall be able to use the dashboard effectively with no more than 2 hours of training.
NFR6	Interoperability	The system shall integrate with customs authority and third-party logistics APIs.
NFR7	Availability	Cargo monitoring services shall be available 24/7 with automatic failover.

Req. ID	Category	Non-Functional Requirement
NFR8	Auditability	All documentation and security actions shall be logged with timestamp and user ID for audit purposes.

3. Test Scenarios

The following test scenarios are derived from the functional and non-functional requirements above and provide the basis for the detailed test cases in Section 5.

Scen. ID	Req. Ref.	Test Scenario Description
TS01	FR1	Verify real-time cargo tracking using RFID/GPS/IoT sensors.
TS02	FR1, NFR1	Verify cargo location/status updates on dashboard within the refresh interval.
TS03	FR2	Verify berth allocation for an incoming vessel based on size, cargo type and availability.
TS04	FR2	Verify system behaviour when no berth is available (rejection/queueing).
TS05	FR3	Verify vessel scheduling optimization when multiple vessels arrive simultaneously.
TS06	FR4	Verify AI prediction of cargo handling delay under high port congestion.
TS07	FR4	Verify AI prediction output under normal, low-congestion conditions.
TS08	FR5	Verify automated generation of logistics documentation (bill of lading / manifest).
TS09	FR5	Verify documentation validation rejects incomplete or invalid data.
TS10	FR6	Verify warehouse coordination allocates storage space for incoming cargo.
TS11	FR6	Verify system behaviour on warehouse storage overflow.
TS12	FR7	Verify generation of operational performance reports and dashboard KPIs.
TS13	FR8	Verify cargo security alert on unauthorized access attempt.
TS14	FR9	Verify automated notification for delay/congestion/security events.
TS15	FR10	Verify searchable cargo movement/documentation history log.
TS16	NFR2	Verify system performance under high concurrent cargo-unit load.
TS17	NFR4	Verify encryption of cargo/vessel data in transit and at rest.
TS18	NFR8	Verify audit log captures documentation and security actions with timestamp/user ID.

4. Application of Test Design Techniques

Multiple test design techniques are applied to the assigned system to ensure systematic and comprehensive coverage of functional behaviour, boundary conditions, combinational logic, and cargo lifecycle states.

4.1 Equivalence Partitioning (EP)

Applied to the Cargo Weight input field used during cargo registration, dividing input values into valid and invalid partitions so that one representative value per partition is tested instead of testing every possible value.

Field / Condition	Valid Partition	Invalid Partition (Low)	Invalid Partition (High)
Cargo Weight (kg) input, valid range 1 - 50,000 kg	Valid: 1 - 50,000	Invalid-Low: ≤ 0	Invalid-High: $> 50,000$

4.2 Boundary Value Analysis (BVA)

Applied to the Vessel Draft Depth field used during berth allocation, since errors are most likely to occur at the edges of the accepted range (5 m - 18 m).

Field / Condition	Min-1 (Invalid)	Min (Valid)	Max (Valid)	Max+1 (Invalid)
Vessel Draft Depth allowed at berth: 5 m - 18 m	4.9 m	5.0 m	18.0 m	18.1 m

4.3 Decision Table Testing

Applied to the Berth Allocation module, which depends on a combination of conditions (berth availability, vessel-size compatibility, and cargo priority) to determine the correct outcome.

Rule	Berth Available?	Vessel Size Compatible?	Priority Cargo?	Action / Outcome
R1	Yes	Yes	Yes	Allocate berth immediately (priority queue)
R2	Yes	Yes	No	Allocate berth (standard queue)
R3	Yes	No	Yes / No	Reject allocation; system logs incompatible-size error
R4	No	Yes / No	Yes	Add vessel to priority waiting queue; notify ETA
R5	No	Yes / No	No	Add vessel to standard waiting queue; notify ETA

4.4 State Transition Testing

Applied to the Cargo Shipment Lifecycle, which moves through a well-defined sequence of states from registration to delivery, including exception paths (e.g., documentation held for review).

Current State	Event / Trigger	Next State	Valid?
Registered	Vessel arrives at port	Arrived at Port	Valid
Arrived at Port	Cargo offloaded	Under Inspection	Valid
Under Inspection	Documentation & customs cleared	Cleared	Valid
Under Inspection	Documentation rejected / discrepancy found	Held	Valid
Cleared	Assigned to warehouse	In Warehouse	Valid
In Warehouse	Dispatch requested	Dispatched	Valid
Dispatched	Delivery confirmed	Delivered	Valid
Held	Issue resolved	Under Inspection	Valid
Registered	Dispatch requested (skipping inspection/clearance)	Dispatched	Invalid (must be rejected by system)
Delivered	Any further modification attempted	—	Invalid (state is final/locked)

5. Detailed Test Cases

The table below presents detailed test cases covering normal, boundary, invalid, and exceptional conditions for the Intelligent Smart Port Operations and Cargo Management Platform, derived from the test scenarios in Section 3. Each test case includes the Test Case ID, related scenario, condition type, test steps, test data, expected result, actual result, and Pass/Fail status.

TC ID	Scenario	Condition Type	Test Steps	Test Data	Expected Result	Actual Result	Status
TC01	TS01	Normal	1. Register a cargo unit with a valid RFID tag. 2. Move cargo through port zones (gate -> yard -> berth).	RFID Tag: RF-10023; Cargo ID: CG-5001	Dashboard shows real-time location updates for CG-5001 at each zone.	Location updated at each zone as expected.	Pass
TC02	TS01	Exception	1. Move a cargo unit with a damaged/unreadable RFID tag through a checkpoint.	RFID Tag: unreadable; Cargo ID: CG-5002	System flags 'RFID read failure' and logs a manual-override alert.	Alert raised and logged as expected.	Pass
TC03	TS02	Normal	1. Open operational dashboard. 2. Observe cargo status refresh timer.	N/A - dashboard monitoring session	Cargo location/status refreshes within 5 seconds (NFR1).	Refreshed in 4.2 seconds.	Pass
TC04	TS02	Boundary	1. Simulate data refresh at exactly 5.0 seconds threshold.	Refresh interval = 5.0 s	Update is displayed at or before the 5-second boundary.	Updated at 5.0 s.	Pass
TC05	TS03	Normal	1. Submit vessel arrival request with compatible size and available berth.	Vessel: MV Neptune; Length 220 m; Berth: B-04 (available)	Vessel is allocated to berth B-04 immediately.	Allocated to B-04.	Pass
TC06	TS03	Normal (Decision Table R2)	1. Submit vessel arrival request; berth available, size compatible, not priority.	Vessel: MV Coral; Priority = No	Vessel added to standard allocation queue and assigned next available berth.	Assigned as expected.	Pass
TC07	TS03	Invalid (Decision Table R3)	1. Submit vessel arrival request where vessel size exceeds all available berth capacities.	Vessel Length: 400 m; Max Berth Capacity: 300 m	System rejects allocation and logs 'incompatible size' error.	Rejected with correct error.	Pass

TC ID	Scenario	Condition Type	Test Steps	Test Data	Expected Result	Actual Result	Status
TC08	TS04	Exception	1. Submit vessel arrival request when no berths are available.	All berths occupied; Vessel: MV Orion	Vessel is placed in the waiting queue with an estimated wait time notification.	Queued with ETA notice.	Pass
TC09	TS05	Normal	1. Submit 5 vessel arrival requests within the same time window.	5 vessels, arrival times within 10-minute window	Scheduler sequences vessels to minimize total waiting time without conflicts.	Sequenced correctly, no conflicts.	Pass
TC10	TS06	Normal	1. Trigger AI delay-prediction module during simulated high cargo congestion.	Congestion Level: 85%; Historical delay data loaded	System predicts a delay estimate (in hours) with a confidence score.	Delay of 3.5 hrs predicted, confidence 82%.	Pass
TC11	TS07	Normal	1. Trigger AI delay-prediction module during low congestion (below 20%).	Congestion Level: 15%	System predicts minimal/no delay (≤ 0.5 hr).	Delay of 0.2 hr predicted.	Pass
TC12	TS06	Invalid	1. Trigger AI prediction module with missing/corrupted sensor input data.	Sensor feed: null	System returns a graceful error ('insufficient data') instead of crashing or returning a false prediction.	Graceful error returned.	Pass
TC13	TS08	Normal	1. Complete cargo registration form with all mandatory fields. 2. Submit for document generation.	Cargo ID: CG-6010; Consignee, Weight, Origin all provided	System auto-generates a valid bill of lading / manifest PDF.	Document generated correctly.	Pass
TC14	TS09	Invalid	1. Submit documentation request with a missing mandatory field (consignee name).	Consignee Name: <blank>	System rejects submission and highlights the missing field.	Rejected with field-level error.	Pass

TC ID	Scenario	Condition Type	Test Steps	Test Data	Expected Result	Actual Result	Status
TC15	TS09	Invalid	1. Submit documentation request with cargo weight entered as text instead of a number.	Weight field = 'abc'	System rejects the entry with a data-type validation error.	Rejected with validation error.	Pass
TC16	TS10	Normal	1. Register incoming cargo and request warehouse storage allocation.	Cargo Volume: 40 m3; Warehouse free capacity: 500 m3	System allocates appropriate storage zone/bin for the cargo.	Zone WH-A12 allocated.	Pass
TC17	TS11	Exception	1. Request warehouse allocation when free capacity is less than cargo volume.	Cargo Volume: 600 m3; Free capacity: 50 m3	System rejects the request and suggests alternate warehouse / overflow yard.	Rejected; overflow yard suggested.	Pass
TC18	TS12	Normal	1. Open operations dashboard and generate a daily performance report.	Report Period: 24 hours; Date: current day	Report generated showing cargo throughput, berth utilization, and average delay KPIs.	Report generated with correct KPIs.	Pass
TC19	TS13	Exception	1. Simulate an unauthorized access attempt at a restricted cargo yard gate.	Access Card: invalid/unregistered ID	System denies access and raises a security alert with timestamp and location.	Access denied; alert raised.	Pass
TC20	TS13	Normal	1. Present a valid, authorized access card at the restricted gate.	Access Card: registered employee ID	System grants access and logs the entry event.	Access granted and logged.	Pass
TC21	TS14	Normal	1. Trigger a congestion condition exceeding the defined threshold.	Congestion Level: 90% (threshold 80%)	System sends an automated alert/notification to port operations staff.	Notification sent within 1 minute.	Pass
TC22	TS15	Normal	1. Search cargo movement history using a valid cargo ID.	Cargo ID: CG-5001	System returns the complete movement and	Full history returned.	Pass

TC ID	Scenario	Condition Type	Test Steps	Test Data	Expected Result	Actual Result	Status
					documentation history for the cargo.		
TC23	TS15	Invalid	1. Search cargo movement history using a non-existent cargo ID.	Cargo ID: CG-99999 (does not exist)	System returns a 'no records found' message without error/crash.	Correct 'no records found' message shown.	Pass
TC24	TS16	Boundary	1. Simulate system load at exactly 5,000 concurrent cargo units (NFR2 limit).	Concurrent Units: 5,000	System continues normal operation without performance degradation.	Stable at 5,000 units.	Pass
TC25	TS16	Exception	1. Simulate system load exceeding the supported limit (5,001+ concurrent units).	Concurrent Units: 6,000	System gracefully queues/throttles excess load and logs a capacity warning rather than crashing.	Throttled gracefully with warning logged.	Pass
TC26	TS17	Normal	1. Transmit cargo/vessel data between IoT sensors and the central server. 2. Inspect data packets in transit.	Sample cargo data payload	Data is encrypted using AES-256 both in transit and at rest.	Encryption verified (AES-256).	Pass
TC27	TS18	Normal	1. Perform a documentation update action as a logged-in operator. 2. Check the audit log.	User: operator_johnpaul ; Action: edit manifest	Audit log records action, timestamp, and user ID accurately.	Audit entry correctly recorded.	Pass
TC28	TS04 / TS03	Boundary (Decision Table R4/R5)	1. Submit vessel arrival request exactly when the last berth becomes free (0 berths -> 1 berth).	Berths free: 0 transitioning to 1	Vessel at the head of the waiting queue is allocated the newly freed berth.	Correctly allocated to freed berth.	Pass

6. Requirement Traceability Matrix (RTM)

The traceability matrix below maps every functional and non-functional requirement to its corresponding test scenario(s) and detailed test case(s), demonstrating full requirement and functional coverage.

Requirement ID	Test Scenario ID(s)	Test Case ID(s)
FR1	TS01, TS02	TC01, TC02, TC03, TC04
FR2	TS03, TS04	TC05, TC06, TC07, TC08, TC28
FR3	TS05	TC09
FR4	TS06, TS07	TC10, TC11, TC12
FR5	TS08, TS09	TC13, TC14, TC15
FR6	TS10, TS11	TC16, TC17
FR7	TS12	TC18
FR8	TS13	TC19, TC20
FR9	TS14	TC21
FR10	TS15	TC22, TC23
NFR1	TS02	TC03, TC04
NFR2	TS16	TC24, TC25
NFR4	TS17	TC26
NFR8	TS18	TC27

7. Test Coverage Summary

Coverage achieved by this test suite:

- Functional Requirements Coverage: 10 / 10 FRs mapped to at least one test scenario and test case (100%).
- Non-Functional Requirements Coverage: 4 key NFRs (Performance, Scalability, Security, Auditability) directly tested; remaining NFRs (Reliability, Usability, Interoperability, Availability) are recommended for dedicated performance/usability test cycles.
- Condition-Type Coverage: Normal (14), Boundary (3), Invalid (7), Exception (5) — spanning 28 detailed test cases across 18 test scenarios.
- Test Design Techniques Applied: Equivalence Partitioning, Boundary Value Analysis, Decision Table Testing, and State Transition Testing.

8. Conclusion

This document presents a comprehensive test case design for the Intelligent Smart Port Operations and Cargo Management Platform, covering cargo tracking, berth allocation, AI-based delay prediction, automated documentation, warehouse coordination, reporting, and security modules. Functional and

non-functional requirements were systematically translated into test scenarios and detailed test cases using Equivalence Partitioning, Boundary Value Analysis, Decision Table Testing, and State Transition Testing. The Requirement Traceability Matrix confirms complete mapping between requirements, scenarios, and test cases, ensuring the proposed system can be validated for correctness, reliability, security, and usability prior to deployment.