I/O Connector



LEDs



Qwiic I²C (for OLED)



ESP32-WROVER



Power
File: Power.kicad_sch

USB
File: USB.kicad_sch

GNSS
File: GNSS.kicad_sch

Ethernet
File: Ethernet.kicad_sch

Level_Shifting
File: Level_Shifting.kicad_sch

Level_Shifting_10MHz
File: Level_Shifting_10MHz.kicad_sch

Oscillator
File: Oscillator.kicad_sch

open source hardware

Designed by: P.C.

SPARKPNT

Sheet: /
File: SparkPNT_GNSSDO_Plus.kicad_sch

Title: GNSSDO Plus (mosaic-T, STP3593LF)

Size: USLetter	Date: 2025-01-20	Rev: v01
KiCad E.D.A. 8.0.7		Id: 1/8

DC Power In



Power Over Ethernet



Power Mux



Main 3.3V



Peripheral 3.3V



Analog 3.3V



OCXO Power Mux



Sheet: /Power/	
File: Power.kicad_sch	
Title: Power	
Size: USLetter	Date:
KiCad E.D.A. 8.0.7	Id: 2/8

Mosaic USB



USB Track Impedance: Differential Pair
https://saturnpcb.com/saturn-pcb-toolkit/
Prepreg thickness: 8.3 mil (JLC7628). Er = 4.6
10.5 mil track with 9.5 mil gap (20 mil center to center) = 90 Ohms

ESP32 USB



ESP32 USB to Serial – CH340C



Buttons



Sheet: /USB/	
File: USB.kicad_sch	
Title: USB	
Size: USLetter	Date:
KiCad E.D.A. 8.0.7	Id: 3/8

mosaic Tri-band GNSS



GNSS Antenna



Microstrip Calculation:
Copper Thickness (1oz): 1.4mil/0.035mm
Board thickness: 1.6mm
Dielectric thickness (layer 1 to 2): 0.2mm
Er: 4.6
Polygon Isolation: 6mil/0.1524mm
RF Trace Width: 13mil/0.33mm
https://chemandy.com/calculators/coplanar-waveguide-with-ground-calculator.htm

microSD



Sheet: /GNSS/	
File: GNSS.kicad_sch	
Title: GNSS	
Size: USLetter	Date:
KiCad E.D.A. 8.0.7	Id: 4/8

Ethernet





Ethernet Track Impedance: Differential Pair
https://saturnpcb.com/saturn-pcb-toolkit/
Prepreg thickness: 8.3 mil (JLC7628). Er = 4.6
9.0 mil track with 11.0 mil gap (20 mil center to center) = 100 Ohms
Each pair should match in length to better than 0.5mm

Sheet: /Ethernet/	
File: Ethernet.kicad_sch	
Title: Ethernet	
Size: USLetter	Date:
KiCad E.D.A. 8.0.7	Id: 5/8


mosaic COM2
I/O Screw Terminals
U8
U9
74LVC2T45DC
A <= B : DIR = GND
A => B : DIR = VCCA
D13
DF5A5.6LFU
MTX2
MRTS2
MTX2_O
MRTS2_O
MRX2
MCTS2
MRX2_I
MCTS2_I
R41 100k
R16 100k
C39 2.2uF 10V 20%
C40 0.1uF 25V 20%
C41 2.2uF 10V 20%
C42 0.1uF 25V 20%
GP1/2 Out
U14
MGP1
MGP2
MGP1_O
MGP2_O
C56 2.2uF 10V 20%
C57 0.1uF 25V 20%
C24 2.2uF 10V 20%
C50 0.1uF 25V 20%
EventA In
U10
MEventA_1V8
For 2.8V input:
Open jumper A
Close jumper B
For 1.8V input:
Open jumper A
Close jumper C
For 50 Ohm input:
Close jumper D
C61 2.2uF 10V 20%
C63 0.1uF 25V 20%
R43 100k
R47 49.9
D1
D15
PESD0402
TP48
J3
SMA_Edge
C59 2.2uF 10V 20%
C62 0.1uF 25V 20%
EventB In
U12
MEventB_1V8
MEventB_I
MGP1_O
MGP2_O
I/O Screw Terminal
R44 100k
C43 2.2uF 10V 20%
C44 0.1uF 25V 20%
C45 2.2uF 10V 20%
C46 0.1uF 25V 20%
VCCIO voltage selection
VBUS
TP40
SW4
DPDT_Slide_SMD_7.2x3.5mm
Level-Shifting
Sheet: /Level_Shifting/
File: Level_Shifting.kicad_sch
Title: Level Shifting
Size: USLetter
Date:
Rev:
KiCad E.D.A. 8.0.7
Id: 6/8



Note: all paths use identical components to ensure equal temperature dependence

Level–Shifting 10MHz

Sheet: /Level_Shifting_10MHz/
File: Level_Shifting_10MHz.kicad_sch

Title: Level Shifting 10MHz

Size: USLetter | Date: | **Rev:**
KiCad E.D.A. 8.0.7 | Id: 7/8

10MHz Oscillator – STP3593LF

Supply Voltage: 5.0V (4.75V Min., 5.25V Max.)
Current Consumption: 1500mA (Warm Up), 600mA (Steady State)



3-Way Splitter – JPS-3-1+

Typical Total Loss: 5.0dB at 10MHz



I2C Level Shifting – PCA9306







Sheet: /Oscillator/		
File: Oscillator.kicad_sch		
Title: Oscillator		
Size: A4	Date:	**Rev:**
KiCad E.D.A. 8.0.7		Id: 8/8