I/O Connector



LEDs



Qwiic I²C (for OLED)



ESP32-WROVER



Use boot control pins with caution: 0, 2, 5, 12, 15
IO0: Pull-up at boot. Can be used a stat LED.
IO2: Pull-down at boot. Boot mode.
IO5: Pull-up at boot. SDIO timing.
IO12: Pull-down at boot. LDO voltage.
IO15: Pull-up. TXO debug active.

Power
File: Power.kicad_sch

USB
File: USB.kicad_sch

GNSS
File: GNSS.kicad_sch

Ethernet
File: Ethernet.kicad_sch

Level_Shifting
File: Level_Shifting.kicad_sch

Level_Shifting_10MHz
File: Level_Shifting_10MHz.kicad_sch

Oscillator
File: Oscillator.kicad_sch

open source hardware

Designed by: P.C.

SPARKPNT

Sheet: /
File: SparkPNT_GNSSDO_Plus.kicad_sch

Title: GNSSDO Plus (mosaic-T, STP3593LF)

Size: USLetter	Date: 2025-01-02	Rev: v10
KiCad E.D.A. 8.0.7		Id: 1/8

DC Power In



Power Over Ethernet



Power Mux



Main 3.3V



Peripheral 3.3V



OCXO Power Mux



Sheet: /Power/
File: Power.kicad_sch

Title: Power

Size: USLetter | Date: | **Rev:**

KiCad E.D.A. 8.0.7 | Id: 2/8

Mosaic USB



USB Track Impedance: Differential Pair
https://saturnpcb.com/saturn-pcb-toolkit/
Prepreg thickness: 8.3 mil (JLC7628). Er = 4.6
10.5 mil track with 9.5 mil gap (20 mil center to center) = 90 Ohms

ESP32 USB



ESP32 USB to Serial – CH340C



Buttons



Sheet: /USB/	
File: USB.kicad_sch	
Title: USB	
Size: USLetter	Date:
KiCad E.D.A. 8.0.7	Rev:
	Id: 3/8



Sheet: /GNSS/	
File: GNSS.kicad_sch	
Title: GNSS	
Size: USLetter	Date:
KiCad E.D.A. 8.0.7	Id: 4/8

Ethernet





Ethernet Track Impedance: Differential Pair
https://saturnpcb.com/saturn-pcb-toolkit/
Prepreg thickness: 8.3 mil (JLC7628). Er = 4.6
9.0 mil track with 11.0 mil gap (20 mil center to center) = 100 Ohms
Each pair should match in length to better than 0.5mm

Sheet: /Ethernet/		
File: Ethernet.kicad_sch		
Title: Ethernet		
Size: USLetter	Date:	**Rev:**
KiCad E.D.A. 8.0.7		Id: 5/8


mosaic COM2
I/O Screw Terminals
A <= B : DIR = GND
A => B : DIR = VCCA
74LVC2T45DC
GP1/2 Out
I/O Screw Terminal
EventA In
For 50 Ohm input:
Close jumper V
For 2.8V input:
Open jumper J
Close jumper K
For 1.8V input:
Open jumper J
Close jumper L
EventB In
VCCIO voltage selection
DPDT_Slide_SMD_7.2x3.5mm
Level-Shifting
Sheet: /Level_Shifting/
File: Level_Shifting.kicad_sch
Title: Level Shifting
Size: USLetter
Date:
Rev:
KiCad E.D.A. 8.0.7
Id: 6/8

10MHz Out



PPS Out (Inverting)



Note: 10MHz and PPS Out use identical components
to ensure equal temperature dependence

Level-Shifting 10MHz

Sheet: /Level_Shifting_10MHz/
File: Level_Shifting_10MHz.kicad_sch

Title: Level Shifting 10MHz

Size: USLetter	Date:	Rev:
KiCad E.D.A. 8.0.7		Id: 7/8

10MHz Oscillator – STP3593LF

Supply Voltage: 5.0V (4.75V Min., 5.25V Max.)
Current Consumption: 1500mA (Warm Up), 600mA (Steady State)





Delta 6dB Resistive Splitter



I2C Level Shifting – PCA9306







Sheet: /Oscillator/ File: Oscillator.kicad_sch		
Title:		
Size: A4	Date:	**Rev:**
KiCad E.D.A. 8.0.7		Id: 8/8