Tags	Description	Syntax
!DOCTYPE html	Declares the document type and HTML version.	<!DOCTYPE html>
abbreviation	Defines an abbreviation or acronym with a tooltip.	<abbr title=" "> ... </abbr>
acronym	Defines an acronym with extra semantic meaning. (Deprecated)	<acronym title=" "> ... </acronym>
address	Specifies contact information for a person or organization.	<address> ... </address>
anchor	Creates a hyperlink to another page or location.	 ...
applet	Embeds a Java applet. (Deprecated, use <object>)	<applet>....</applet>
area	Defines a clickable area inside an image map.	<area>
article	Represents a self-contained content section.	<article>..</article>
aside	Defines content aside from the main content.	<aside>..</aside>
audio	Embeds audio content like music or podcasts.	<audio>..</audio>
base	Sets a base URL for relative links.	<base href = " ">
basefont	Sets default font for the page. (Deprecated)	<basefont>
bdi	Isolates text direction from surrounding content.	<bdi> ... </bdi>
bdo	Overrides the current text direction explicitly.	<bdo dir> Contents... </bdo>
bgsound	Plays background sound. (Deprecated)	<bgsound src="">
big	Increases text size slightly. (Deprecated in HTML5)	<big> Contents... </big>
blockquote	Displays long quotations from other sources.	<blockquote> Contents... </blockquote>
body	Defines the main content of the HTML page.	<body> Contents... </body>
bold	Makes text bold without extra importance.	...

Tags	Description	Syntax
break	Inserts a line break.	
button	Defines a clickable button.	<button type = "button">
caption	Specifies a table's caption.	<caption align = "value"></caption>
canvas	Defines a drawable area for graphics and animations.	<canvas id = "script"> Contents</canvas>
center	Centers content horizontally. (Deprecated)	Contents.
cite	Marks the title of a work, displayed in italics.	<cite>Content</cite>
code	Represents computer code text.	<code>Contents</code>
colgroup	Groups columns in a table for styling.	<colgroup> Column lists </colgroup>
column	Sets properties for columns within a colgroup.	<col attribute = "value">
comment	Inserts a comment in the HTML code.	<!-- … -->
data	Associates content with a machine-readable value.	<data value=""> Contents </data>
datalist	Provides autocomplete options for input elements.	<datalist>Contents</datalist>
dd	Defines a description in a description list.	<dd>Contents</dd>
define	Marks the defining instance of a term.	<dfn>Contents</dfn>
delete	Marks deleted text.	~~Contents~~
details	Creates an expandable/collapsible section.	<details>Contents</details>
dialog	Defines a popup dialog box.	<dialog open> Contents... </dialog>
dir	Creates a directory list. (Deprecated)	<dir> Lists... </dir>
div	Groups content into a division or section.	Content
dl	Represents a description list.	<dl> Contents... </dl>
dt	Represents a term/name in a description list.	<dt> Content... </dt>

Tags	Description	Syntax
embed	Embeds external multimedia content like Flash.	<embed attributes>
fieldset	Groups related form elements together.	<fieldset>Contents</fieldset>
figcaption	Adds caption to a figure.	<figcaption> Figure caption </figcaption>
figure	Represents self-contained content, like images.	<figure> Image content... </figure>
font	Sets font, size, and color. (Deprecated)	 Content
footer	Defines footer content for a document/section.	<footer> ... </footer>
form	Represents a web form for user input.	<form> Form Content... </form>
frame	Defines a browser window frame. (Deprecated)	<frame/>
frameset	Groups frames in a window. (Deprecated)	<frameset cols = "pixels|%|*">
head	Contains metadata and links for the document.	<head>...</head>
header	Represents introductory content or a heading section.	<header> ...</header>
heading	Defines headings of the page from h1 as highest to h6 as lowest level.	Heading1 Heading2
hgroup	Groups multiple headings. (Deprecated)	<hgroup> ... </hgroup>
hr	Inserts a horizontal line.	<hr>
html	Defines the root element of the HTML page.	<html> Contents </html>
Iframes	Embeds another HTML document in a frame.	<iframe src="URL" title="description"> </iframe>
image	Displays an image.	<img src="url" alt="some_text" width="" height="">
input	Creates input controls in a form.	<input type = "value" .... />
ins	Marks inserted text.	<ins> Contents... </ins>

Tags	Description	Syntax
isindex	Creates a single-line text query. (Deprecated)	<isindex prompt="search">
italic	Italicizes text for emphasis or technical terms.	Contents
kbd	Marks text as keyboard input.	<kbd> text content ... </kbd>
keygen	Generates key-pair for forms. (Deprecated)	<keygen name = "name">
label	Provides label for form input elements.	<label> form content... </label>
legend	Titles a fieldset element.	<legend> Text </legend>
link	Links external resources like CSS or icons..	<link rel="stylesheet" href="styles.css">
list	Represents an item in a list.	List Items
main	Marks the main content of the page.	<main>Coontents</main>
mark	Highlights text for reference or attention.	<mark> Contents... </mark>
marquee	Scrolls text or images horizontally/vertically. (Deprecated)	<marquee>Contents</marquee>
menuitem	Defines a menu command. (Deprecated)	<menuitem label="" icon="" type> </menuitem>
meta	Stores metadata about the HTML document.	<meta attribute-name="value">
meter	Displays a scalar measurement within a known range.	<meter attributes...> </meter>
nav	Represents navigation links for the site.	<nav> Links... </nav>
nobreak	Prevents line breaks. (Deprecated)	<nobr> Statement </nobr>
noembed	Alternative content for unsupported embed.	<noembed> Element </noembed>
noscript	Displays content when scripts are disabled.	<noscript> Contents... </noscript>
object	Embeds multimedia content.	<object>...</object>
optgroup	Groups options in a dropdown menu.	<optgroup>...</optgroup>
option	Defines a choice in a dropdown list.	<option> Contents... </option>
output	Displays results from calculations or scripts.	<output> Results... </output>

Tags	Description	Syntax
paragraphs	Represents a paragraph of text.	Content
param	Defines parameters for an object element.	<param name="" value="">
phrase	Marks text with emphasis.	Text Content
pre	Displays preformatted text.	<pre> Contents... </pre>
progress	Represents progress of a task.	<progress . . . > . . . </progress>
q	Represents a short inline quotation.	<q> Contents... </q>
rp	Provides parentheses for ruby annotations.	<rp> . . . </rp>
rt	Provides ruby annotation text.	<rt> Explanation... </rt>
ruby	Marks text with ruby annotations.	<ruby attributes> Contents... </ruby>
s	Marks text as no longer correct.	<s> Contents... </s>
samp	Represents sample computer output.	<samp> Contents... </samp>
script	Embeds client-side script like JavaScript.	<script> Script Contents... </script>
section	Represents a standalone section of content.	<section> Section Contents </section>
small	Reduces font size.	Contents...
source	Defines media source for audio/video.	<source src="" type=""> </source>
spacer	Creates empty space. (Deprecated)	<spacer type="" size="">
span	Generic inline container for text or elements.	Some Text
strike	Strikethrough text. (Deprecated)	<strike> Contents </strike>
strong	Marks text as important, bold style.	Contents...
style	Adds CSS styling within HTML.	<tagname style="property:value;">
sub	Adds subscript text.	_{subscript text}
sup	Adds superscript text.	^{superscript text}
summary	Adds summary for a <details> element.	<summary> Content </summary>

Tags	Description	Syntax
svg	Defines Scalable Vector Graphics content.	<svg height="" width="">
table	Represents tabular data in rows and columns.	<table>... </table>
tbody	Groups table body rows.	<tbody> // Table contents </tbody>
td	Represents a standard table cell and insert data in it.	<td>.....</td>
template	Stores reusable HTML fragments.	<template> Contents </template>
tfoot	Defines table footer.	<tfoot> // Table footer contents... </tfoot>
th	Represents a table header cell.	<th> Contents... </th>
thead	Groups table header rows.	<thead>Table head Contents...</thead>
time	Represents a specific date/time.	<time attribute> Time... </time>
title	Sets the document title.	<title> Title name </title>
tr	Defines a table row.	<tr>.....</tr>
track	Provides text tracks for media elements.	<track attribute>
tt	Teletype text. (Deprecated), It was used for marking Keyboard input.	<tt> Contents... </tt>
underline	Underlines text.	<u> Contents... </u>
var	Represents a variable in code or math.	<var> Contents... </var>
video	Embeds video content.	<video src="" controls> </video>
wbr	Suggests a line break opportunity.	<wbr>
xmp	Displays preformatted text literally. (Deprecated)	<xmp> statement </xmp