

Notes

Introduction to Computer Science (CS50) on EdX

Sparsh Jain

November 18, 2020

Contents

1	Computational Thinking, Scratch	5
1.1	Binary Number System	5
1.2	Algorithms	5
1.3	Time Complexity	5
1.4	Pseudocode	5
1.5	Scratch	5
2	C	6
2.1	Hello World	6
2.2	Input	6
2.3	Initialization	8
2.4	Increment	8
2.5	Conditionals	8
2.6	Loops	8
2.6.1	While Loop	8
2.6.2	For Loop	9
2.7	Additional Info	9
2.7.1	Datatypes	9
2.7.2	Functions	9
2.7.3	Placeholders	10
2.7.4	Arithmetic Operations	10
2.8	Examples	10
2.8.1	Arithmetic	10
2.8.2	Conditional	13
2.8.3	Logical	14
2.8.4	Loop	15
2.8.5	Function	16
2.9	Limitations	21

3	Arrays	23
3.1	Compiling	23
3.1.1	Preprocessing	23
3.1.2	Compiling	23
3.1.3	Assembling	23
3.1.4	Linking	23
3.2	Debugging	23
3.3	Casting	24
3.4	Array	24
3.5	String	27
3.6	Command Line Arguments	32
4	Algorithms	34
4.1	Linear Search	34
4.2	Binary Search	34
4.3	Efficiency	35
4.3.1	\mathcal{O} Notation:	35
4.3.2	Ω Notation:	35
4.4	Examples	36
4.4.1	Linear Search	36
4.4.2	Bad Design	37
4.4.3	Good Design - <code>typedef struct</code>	38
4.5	Bubble Sort	39
4.6	Selection Sort	39
4.7	Better Bubble Sort	40
4.8	Recursion	40
4.9	Merge Sort	43
4.9.1	Θ Notation	43

List of Programs

2.1	Hello World in C	6
2.2	Hello User in C	7
2.3	int.c	11
2.4	float.c	11
2.5	parity.c	12
2.6	conditions.c	13
2.7	agree.c	14
2.8	cough0.c	15
2.9	cough1.c	15
2.10	cough2.c	16
2.11	cough3.c	17
2.12	positive.c	18
2.13	mario0.c	18
2.14	mario2.c	19
2.15	mario8.c	20
2.16	floats.c	21
2.17	overflow.c	21
3.1	casting	24
3.2	scores0.c	24
3.3	scores1.c	25
3.4	scores2.c	25
3.5	scores3.c	26
3.6	names.c	27
3.7	string0.c	28
3.8	string1.c	28
3.9	string2.c	29
3.10	uppercase0.c	30
3.11	uppercase1.c	31
3.12	argv.c	32
3.13	argv2.c	33
3.14	exit.c	33

4.1	Linear Search Pseudocode	34
4.2	Binary Search Pseudocode	34
4.3	Linear Search on numbers	36
4.4	Linear Search on names	37
4.5	Linear Search in a phonebook	38
4.6	Linear Search in phonebook with <code>typedef struct</code>	39
4.7	Iteration Pseudocode	40
4.8	Recursion Pseudocode	41
4.9	Iteration C code	41
4.10	Recursion C code	42
4.11	Merge Sort Pseudocode	43

Chapter 1

Computational Thinking, Scratch

1.1 Binary Number System

1.2 Algorithms

1.3 Time Complexity

1.4 Pseudocode

1.5 Scratch

This was only an introductory lecture. [Click here](#) for more details.

Chapter 2

C

2.1 Hello World

```
1  #include <stdio.h>
2
3  int main(void)
4  {
5      printf("Hello, World!\n");
6  }
```

Program 2.1: Hello World in C

Remark. Need to compile using a compiler like clang or gcc.

2.2 Input

Remark. In case of errors in compiling, start by trying to *fix* the first one, and so on.

Remark. Use `-lcs50` to link `cs50.h` header.

Remark. Use `make` to ease your life compiling!

```
1  #include <cs50.h>
2  #include <stdio.h>
3
4  int main(void)
5  {
6      string answer = get_string("What's your name?\n");
7      printf("Hello, %s!\n", answer);
8  }
```

Program 2.2: Hello User in C

2.3 Initialization

```
int counter = 0;
```

2.4 Increment

```
counter = counter + 1;  
counter += 1;  
counter++; // Syntactic Sugar
```

2.5 Conditionals

```
if (x < y)  
{  
    printf("x is less than y!\n");  
}  
else if (x > y)  
{  
    printf("x is greater than y!\n");  
}  
else // if (x == y)  
{  
    printf("x is equal to y!\n");  
}
```

2.6 Loops

2.6.1 While Loop

Infinite Loop

```
while(true)  
{  
  
}
```

Repeat

```
int i = 0;  
while(i < 50)
```

```
{  
    printf("Hello World!\n");  
    i = i+1;  
}
```

2.6.2 For Loop

```
for(int i = 0; i < 50; i += 1)  
{  
    printf("Hello World!\n");  
}
```

2.7 Additional Info

2.7.1 Datatypes

Some of these (like string) are implemented in `cs50.h` library.

- `bool`
- `char`
- `double`
- `float`
- `int`
- `long`
- `string`
- ...

2.7.2 Functions

They are implemented in `cs50.h` library.

- `get_char`
- `get_float`
- `get_double`

- `get_int`
- `get_long`
- `get_string`
- ...

2.7.3 Placeholders

- `%c` for `char`
- `%f` for `float`
- `%i` for `int`
- `%li` for `long`
- `%s` for `string`

2.7.4 Arithmetic Operations

- `+`
- `-`
- `*`
- `/`
- `%`

2.8 Examples

2.8.1 Arithmetic

```

1  #include <cs50.h>
2  #include <stdio.h>
3
4  int main(void)
5  {
6      int age = get_int("What's your age?\n");
7      // int days = age * 365;
8      // printf("You are atleast %i days old.\n", days);
9      printf("You are atleast %i days old.\n", age * 365);
10 }
```

Program 2.3: int.c

```

1  #include <cs50.h>
2  #include <stdio.h>
3
4  int main(void)
5  {
6      float price = get_float("What's the price?\n");
7      // printf("Your total is %f.\n", price * 1.18);
8      printf("Your total is %.2f.\n", price * 1.18);
9  }
```

Program 2.4: float.c

```
1  #include <cs50.h>
2  #include <stdio.h>
3
4  int main(void)
5  {
6      int n = get_int("n: ");
7
8      if (n % 2 == 0)
9      {
10         printf("even.\n");
11     }
12     else
13     {
14         printf("odd.\n");
15     }
16 }
```

Program 2.5: parity.c

2.8.2 Conditional

```
1 // Conditions and relational operators
2
3 #include <cs50.h>
4 #include <stdio.h>
5
6 int main(void)
7 {
8     // Prompt user for x
9     int x = get_int("x: ");
10
11     // Prompt user for y
12     int y = get_int("y: ");
13
14     // Compare x and y
15     if (x < y)
16     {
17         printf("x is less than y\n");
18     }
19     else if (x > y)
20     {
21         printf("x is greater than y\n");
22     }
23     else
24     {
25         printf("x is equal to y\n");
26     }
27 }
```

Program 2.6: conditions.c

2.8.3 Logical

```
1 // Logical operators
2 #include <cs50.h>
3 #include <stdio.h>
4 int main(void)
5 {
6     // Prompt user to agree
7     char c = get_char("Do you agree?\n");
8     // Check whether agreed
9     if (c == 'Y' || c == 'y')
10    {
11        printf("Agreed.\n");
12    }
13    else if (c == 'N' || c == 'n')
14    {
15        printf("Not agreed.\n");
16    }
17 }
```

Program 2.7: agree.c

2.8.4 Loop

```
1  // Opportunity for better design
2
3  #include <stdio.h>
4
5  int main(void)
6  {
7      printf("cough\n");
8      printf("cough\n");
9      printf("cough\n");
10 }
```

Program 2.8: cough0.c

```
1  // Better design
2
3  #include <stdio.h>
4
5  int main(void)
6  {
7      for (int i = 0; i < 3; i++)
8      {
9          printf("cough\n");
10     }
11 }
```

Program 2.9: cough1.c

2.8.5 Function

```
1  // Abstraction
2
3  #include <stdio.h>
4
5  void cough(void);
6
7  int main(void)
8  {
9      for (int i = 0; i < 3; i++)
10     {
11         cough();
12     }
13 }
14
15 // Cough once
16 void cough(void)
17 {
18     printf("cough\n");
19 }
```

Program 2.10: cough2.c

```
1  // Abstraction with parameterization
2
3  #include <stdio.h>
4
5  void cough(int n);
6
7  int main(void)
8  {
9      cough(3);
10 }
11
12 // Cough some number of times
13 void cough(int n)
14 {
15     for (int i = 0; i < n; i++)
16     {
17         printf("cough\n");
18     }
19 }
```

Program 2.11: cough3.c

```

1  // Abstraction and scope
2
3  #include <cs50.h>
4  #include <stdio.h>
5
6  int get_positive_int(void);
7
8  int main(void)
9  {
10     int i = get_positive_int();
11     printf("%i\n", i);
12 }
13
14 // Prompt user for positive integer
15 int get_positive_int(void)
16 {
17     int n;
18     do
19     {
20         n = get_int("Positive Integer: ");
21     }
22     while (n < 1);
23     return n;
24 }

```

Program 2.12: positive.c

```

1  // Prints a row of 4 question marks
2
3  #include <stdio.h>
4
5  int main(void)
6  {
7     printf("????\n");
8 }

```

Program 2.13: mario0.c

```

1  // Prints a row of n question marks with a loop
2
3  #include <cs50.h>
4  #include <stdio.h>
5
6  int main(void)
7  {
8      int n;
9      do
10     {
11         n = get_int("Width: ");
12     }
13     while (n < 1);
14     for (int i = 0; i < n; i++)
15     {
16         printf("?");
17     }
18     printf("\n");
19 }

```

Program 2.14: mario2.c

```

1  // Prints an n-by-n grid of bricks with a loop
2
3  #include <cs50.h>
4  #include <stdio.h>
5
6  int main(void)
7  {
8      int n;
9      do
10     {
11         n = get_int("Size: ");
12     }
13     while (n < 1);
14     for (int i = 0; i < n; i++)
15     {
16         for (int j = 0; j < n; j++)
17         {
18             printf("#");
19         }
20         printf("\n");
21     }
22 }

```

Program 2.15: mario8.c

2.9 Limitations

```
1  // Floating-point arithmetic with float
2
3  #include <cs50.h>
4  #include <stdio.h>
5
6  int main(void)
7  {
8      // Prompt user for x
9      float x = get_float("x: ");
10
11     // Prompt user for y
12     float y = get_float("y: ");
13
14     // Perform division
15     printf("x / y = %.50f\n", x / y);
16 }
```

Program 2.16: floats.c

```
1  // Integer overflow
2
3  #include <stdio.h>
4  #include <unistd.h>
5
6  int main(void)
7  {
8      // Iteratively double i
9      for (int i = 1; ; i *= 2)
10     {
11         printf("%i\n", i);
12         sleep(1);
13     }
14 }
```

Program 2.17: overflow.c

[Click here for more examples.](#)

Chapter 3

Arrays

3.1 Compiling

3.1.1 Preprocessing

Expansion/Inclusion of header files, macros, etc.

3.1.2 Compiling

C code → Assembly code.

3.1.3 Assembling

Assembly code → Machine code.

3.1.4 Linking

Linking all relevant files.

3.2 Debugging

- Can use `help50` to understand error msgs in this course.
- Can use (poor man's) `printf`.
- Can use `debug50` for proper debugging (in this course).

Remark. Use `style50` for styling your code.

3.3 Casting

```
1 // Prints ASCII codes
2
3 #include <stdio.h>
4
5 int main(void)
6 {
7     char c1 = 'H';
8     char c2 = 'I';
9     char c3 = '!';
10    printf("%i %i %i\n", c1, c2, c3);
11 }
```

Program 3.1: casting

3.4 Array

Follow through the following examples:

```
1 // Averages three numbers
2
3 #include <cs50.h>
4 #include <stdio.h>
5
6 int main(void)
7 {
8     // Scores
9     int score1 = 72;
10    int score2 = 73;
11    int score3 = 33;
12
13    // Print average
14    printf("Average: %i\n", (score1 + score2 + score3) / 3);
15 }
```

Program 3.2: scores0.c

```

1  // Averages three numbers using an array
2
3  #include <cs50.h>
4  #include <stdio.h>
5
6  int main(void)
7  {
8      // Scores
9      int scores[3];
10     scores[0] = 72;
11     scores[1] = 73;
12     scores[2] = 33;
13
14     // Print average
15     printf("Average: %i\n", (scores[0] + scores[1] + scores[2]) / 3);
16 }

```

Program 3.3: scores1.c

```

1  // Averages three numbers using an array and a constant
2
3  #include <cs50.h>
4  #include <stdio.h>
5
6  const int N = 3;
7
8  int main(void)
9  {
10     // Scores
11     int scores[N];
12     scores[0] = 72;
13     scores[1] = 73;
14     scores[2] = 33;
15
16     // Print average
17     printf("Average: %i\n", (scores[0] + scores[1] + scores[2]) / N);
18 }

```

Program 3.4: scores2.c

```

1  // Averages numbers using a helper function
2
3  #include <cs50.h>
4  #include <stdio.h>
5
6  float average(int length, int array[]);
7
8  int main(void)
9  {
10     // Get number of scores
11     int n = get_int("Scores: ");
12
13     // Get scores
14     int scores[n];
15     for (int i = 0; i < n; i++)
16     {
17         scores[i] = get_int("Score %i: ", i + 1);
18     }
19
20     // Print average
21     printf("Average: %.1f\n", average(n, scores));
22 }
23
24 float average(int length, int array[])
25 {
26     int sum = 0;
27     for (int i = 0; i < length; i++)
28     {
29         sum += array[i];
30     }
31     return (float) sum / (float) length;
32 }

```

Program 3.5: scores3.c

3.5 String

string is just (or a little more) than an array of chars.

```
1  // Stores names using an array
2
3  #include <cs50.h>
4  #include <stdio.h>
5  #include <string.h>
6
7  int main(void)
8  {
9      // Names
10     string names[4];
11     names[0] = "EMMA";
12     names[1] = "RODRIGO";
13     names[2] = "BRIAN";
14     names[3] = "DAVID";
15
16     // Print Emma's name
17     printf("%s\n", names[0]);
18     printf("%c%c%c%c\n", names[0][0], names[0][1], names[0][2], names[0][3]);
19 }
```

Program 3.6: names.c

```

1  // Prints string char by char, one per line
2
3  #include <cs50.h>
4  #include <stdio.h>
5
6  int main(void)
7  {
8      string s = get_string("Input: ");
9      printf("Output: ");
10     for (int i = 0; s[i] != '\0'; i++)
11     {
12         printf("%c", s[i]);
13     }
14     printf("\n");
15 }

```

Program 3.7: string0.c

```

1  // Prints string char by char, one per line, using strlen
2
3  #include <cs50.h>
4  #include <stdio.h>
5  #include <string.h>
6
7  int main(void)
8  {
9      string s = get_string("Input: ");
10     printf("Output: ");
11     for (int i = 0; i < strlen(s); i++)
12     {
13         printf("%c", s[i]);
14     }
15     printf("\n");
16 }

```

Program 3.8: string1.c

```

1  // Prints string char by char, one per line, using strlen, remembering string's
2
3  #include <cs50.h>
4  #include <stdio.h>
5  #include <string.h>
6
7  int main(void)
8  {
9      string s = get_string("Input: ");
10     printf("Output: ");
11     for (int i = 0, n = strlen(s); i < n; i++)
12     {
13         printf("%c", s[i]);
14     }
15     printf("\n");
16 }

```

Program 3.9: string2.c

```

1  // Uppercases a string
2
3  #include <cs50.h>
4  #include <stdio.h>
5  #include <string.h>
6
7  int main(void)
8  {
9      string s = get_string("Before: ");
10     printf("After: ");
11     for (int i = 0, n = strlen(s); i < n; i++)
12     {
13         if (s[i] >= 'a' && s[i] <= 'z')
14         {
15             printf("%c", s[i] - 32);
16         }
17         else
18         {
19             printf("%c", s[i]);
20         }
21     }
22     printf("\n");
23 }

```

Program 3.10: uppercase0.c

```

1  // Uppercases string using ctype library (and an unnecessary condition)
2
3  #include <cs50.h>
4  #include <ctype.h>
5  #include <stdio.h>
6  #include <string.h>
7
8  int main(void)
9  {
10     string s = get_string("Before: ");
11     printf("After: ");
12     for (int i = 0, n = strlen(s); i < n; i++)
13     {
14         if (islower(s[i]))
15         {
16             printf("%c", toupper(s[i]));
17         }
18         else
19         {
20             printf("%c", s[i]);
21         }
22     }
23     printf("\n");
24 }

```

Program 3.11: uppercase1.c

3.6 Command Line Arguments

```
1  // Printing a command-line argument
2
3  #include <cs50.h>
4  #include <stdio.h>
5
6  int main(int argc, string argv[])
7  {
8      if (argc == 2)
9      {
10         printf("hello, %s\n", argv[1]);
11     }
12     else
13     {
14         printf("hello, world\n");
15     }
16 }
```

Program 3.12: argv.c

```

1  // Printing characters in an array of strings
2
3  #include <cs50.h>
4  #include <stdio.h>
5  #include <string.h>
6
7  int main(int argc, string argv[])
8  {
9      for (int i = 0; i < argc; i++)
10     {
11         for (int j = 0, n = strlen(argv[i]); j < n; j++)
12         {
13             printf("%c\n", argv[i][j]);
14         }
15         printf("\n");
16     }
17 }

```

Program 3.13: argv2.c

```

1  // Returns explicit value from main
2
3  #include <cs50.h>
4  #include <stdio.h>
5
6  int main(int argc, string argv[])
7  {
8      if (argc != 2)
9      {
10         printf("missing command-line argument\n");
11         return 1;
12     }
13     printf("hello, %s\n", argv[1]);
14     return 0;
15 }

```

Program 3.14: exit.c

Chapter 4

Algorithms

4.1 Linear Search

```
1         for i from 0 to n-1
2             if ith element is 50
3                 return true;
4         return false;
```

Program 4.1: Linear Search Pseudocode

4.2 Binary Search

```
1         if no items
2             return false;
3         if middle item is 50
4             return true;
5         else if 50 < middle item
6             search left half
7         else if 50 > middle item
8             search right half
```

Program 4.2: Binary Search Pseudocode

4.3 Efficiency

4.3.1 \mathcal{O} Notation:

Worst case scenario

$$\begin{aligned}n^2 &: \mathcal{O}(n^2) \\n \log_n n &: \mathcal{O}(n \log n) \\n &: \mathcal{O}(n) \text{ (LinearSearch)} \\n/2 &: \mathcal{O}(n) \\\log_2 n &: \mathcal{O}(\log n) \text{ (BinarySearch)} \\constant &: \mathcal{O}(1)\end{aligned}$$

4.3.2 Ω Notation:

Best case scenario

$$\begin{aligned}\Omega(n^2) \\ \Omega(n \log n) \\ \Omega(n) \\ \Omega(n) \\ \Omega(\log n) \\ \Omega(1)\end{aligned}$$

Q: Better to have a really good \mathcal{O} value or a really good Ω value?

A: \mathcal{O} , or even *average* case.

4.4 Examples

4.4.1 Linear Search

Numbers

```
1 // Implements linear search for numbers
2
3 #include <cs50.h>
4 #include <stdio.h>
5
6 int main(void)
7 {
8     // An array of numbers
9     int numbers[] = {4, 8, 15, 16, 23, 42};
10
11     // Search for 50
12     for (int i = 0; i < 6; i++)
13     {
14         if (numbers[i] == 50)
15         {
16             printf("Found\n");
17             return 0;
18         }
19     }
20     printf("Not found\n");
21     return 1;
22 }
```

Program 4.3: Linear Search on numbers

Names

```
1 // Implements linear search for names
2
3 #include <cs50.h>
4 #include <stdio.h>
5 #include <string.h>
6
7 int main(void)
8 {
9     // An array of names
```

```

10     string names[] = {"EMMA", "RODRIGO", "BRIAN", "DAVID"};
11
12     // Search for EMMA
13     for (int i = 0; i < 4; i++)
14     {
15         if (strcmp(names[i], "EMMA") == 0)
16         {
17             printf("Found\n");
18             return 0;
19         }
20     }
21     printf("Not found\n");
22     return 1;
23 }

```

Program 4.4: Linear Search on names

4.4.2 Bad Design

Correct/Working code but bad design!

```

1  // Implements a phone book without structs
2
3  #include <cs50.h>
4  #include <stdio.h>
5  #include <string.h>
6
7  int main(void)
8  {
9      string names[] = {"EMMA", "RODRIGO", "BRIAN", "DAVID"};
10     string numbers[] = {"617-555-0100", "617-555-0101",
11                          "617-555-0102", "617-555-0103"};
12
13     for (int i = 0; i < 4; i++)
14     {
15         if (!strcmp(names[i], "EMMA"))
16         {
17             printf("Found %s\n", numbers[i]);
18             return 0;
19         }
20     }
21 }

```

```

20     printf("Not found\n");
21     return 1;
22 }

```

Program 4.5: Linear Search in a phonebook

4.4.3 Good Design - typedef struct

Using `typedef struct` for better design!

```

1  // Implements a phone book with structs
2
3  #include <cs50.h>
4  #include <stdio.h>
5  #include <string.h>
6
7  typedef struct
8  {
9      string name;
10     string number;
11 }
12 person;
13
14 int main(void)
15 {
16     person people[4];
17
18     people[0].name = "EMMA";
19     people[0].number = "617-555-0100";
20
21     people[1].name = "RODRIGO";
22     people[1].number = "617-555-0101";
23
24     people[2].name = "BRIAN";
25     people[2].number = "617-555-0102";
26
27     people[3].name = "DAVID";
28     people[3].number = "617-555-0103";
29
30     // Search for EMMA
31     for (int i = 0; i < 4; i++)

```

```

32     {
33         if (strcmp(people[i].name, "EMMA") == 0)
34         {
35             printf("Found %s\n", people[i].number);
36             return 0;
37         }
38     }
39     printf("Not found\n");
40     return 1;
41 }

```

Program 4.6: Linear Search in phonebook with `typedef struct`

4.5 Bubble Sort

```

1  repeat n-1 times
2      for i = 0 to n-2
3          if ith and i+1th elements out of order
4              swap them

```

$\mathcal{O}(n^2)$

$\Omega(n^2)$

4.6 Selection Sort

```

1  for i from 0 to n-1
2      find smallest item between ith item and last item
3      swap smallest item and ith item

```

$\mathcal{O}(n^2)$

$\Omega(n^2)$

4.7 Better Bubble Sort

```
1 repeat until swap
2     for i = 0 to n-2
3         if ith and i+1th elements out of order
4             swap them
```

$\mathcal{O}(n^2)$

$\Omega(n)$

4.8 Recursion

```
1 Pick up phone book
2 Open to middle of phone book
3 Look at page
4 if Smith is on page
5     Call Mike
6 else if Smith is earlier in book
7     Open to middle of left half of book
8     Go back to line 3
9 else if Smith is later in book
10    Open to middle of right half of book
11    Go back to line 3
12 else
13    Quit
```

Program 4.7: Iteration Pseudocode

Can we do a better design?

```
1 Pick up phone book
2 Open to middle of phone book
3 Look at page
4 if Smith is on page
5     Call Mike
6 else if Smith is earlier in book
7     Search left half of book
8 else if Smith is later in book
9     Search right half of book
```

```

10  else
11      Quit

```

Program 4.8: Recursion Pseudocode

```

1  // Draws a pyramid using iteration
2
3  #include <cs50.h>
4  #include <stdio.h>
5
6  void draw(int h);
7
8  int main(void)
9  {
10     // Get height of pyramid
11     int height = get_int("Height: ");
12
13     // Draw pyramid
14     draw(height);
15 }
16
17 void draw(int h)
18 {
19     // Draw pyramid of height h
20     for (int i = 1; i <= h; i++)
21     {
22         for (int j = 1; j <= i; j++)
23         {
24             printf("#");
25         }
26         printf("\n");
27     }
28 }

```

Program 4.9: Iteration C code

```

1  // Draws a pyramid using recursion
2
3  #include <cs50.h>
4  #include <stdio.h>

```

```

5
6 void draw(int h);
7
8 int main(void)
9 {
10     // Get height of pyramid
11     int height = get_int("Height: ");
12
13     // Draw pyramid
14     draw(height);
15 }
16
17 void draw(int h)
18 {
19     // If nothing to draw
20     if (h == 0)
21     {
22         return;
23     }
24
25     // Draw pyramid of height h - 1
26     draw(h - 1);
27
28     // Draw one more row of width h
29     for (int i = 0; i < h; i++)
30     {
31         printf("#");
32     }
33     printf("\n");
34 }

```

Program 4.10: Recursion C code

4.9 Merge Sort

```
1  if only 1 item
2      return
3  else
4      sort left half of items
5      sort right half of items
6      merge sorted halves
```

Program 4.11: Merge Sort Pseudocode

$\mathcal{O}(n \log n)$

$\Omega(n \log n)$

4.9.1 Θ Notation

When $\mathcal{O} = \Omega$!