

Retina LRS Analyses Overview

Sowmya Parthiban

2025-07-24

Table of contents

1	FASTQ processing	2
1.0.1	Analysis 1: code/01_fastq_processing/02_MinIONQC.sh	2
1.0.2	Analysis 2: code/01_fastq_processing/03_fastq_qc.sh	2
1.0.3	Analysis 3: code/01_fastq_processing/minionQC_yaml.R	2
2	FASTQ to BAM	3
2.0.1	Analysis 4: code/01b_fastq_to_bam/01_fastq_to_bam_gencode_splice.sh	3
2.0.2	Analysis 5: code/01b_fastq_to_bam/01b_fastq_to_bam_transcriptome_gencode.sh	3
2.0.3	Analysis 6: code/01b_fastq_to_bam/02_high_quality_bam_genome.sh . .	3
3	BAM QC Visualization	3
3.0.1	Analysis 7: code/01b_fastq_to_bam/02_high_quality_bam_genome.sh . .	3
3.0.2	Analysis 8: code/02_bam_QC/01a_multi_exon_pcg_sample_specific.sh . .	4
3.0.3	Analysis 9: code/02_bam_QC/read_type_percentages.R	4
3.0.4	Analysis 10:	4
3.0.5	Quantification with code/03_quantification/05_bambu	4
3.0.6	Analysis 11: code/03_quantification/05_bambu/01_generate_sample_wise_read_class.sh	
3.0.7	Analysis 12: code/03_quantification/05_bambu/02_bambu_generate_rcs.sh	4
3.0.8	Analysis 13: code/03_quantification/05_bambu/05_sqanti.sh	5
3.0.9	Analysis 14: code/03_quantification/05_bambu/03_bambu_quantification.R	5
3.0.10	Analysis 15: code/03_quantification/05_bambu/07_gene_names_for_novel_isoforms.R	5
4	Isoquant	5
5	Analysis 16: code/03_quantification/01_IsoQuant/isoquant_all_samples.sh	5
6	Compare gtfs	5
6.0.1	Analysis 17: code/03_quantification/10_compare_gtfs/compare_gtfs.sh	5
7	Cleaning up counts matrix	6
7.0.1	Analysis 18: code/03_quantification/11_cleaning_up_counts_matrix/cleaning_up_counts_	
7.0.2	Analysis 19: code/04_dtu_dge_dte/01b_filter_matrix_by_common_isoforms.R	6
7.0.3	Analysis 20: code/04_dtu_dge_dte/01c_filter_by_gene_biotypes.R . . .	6

8 DTU DGE DTE Analysis	6
8.0.1 Analysis 21:	6
8.0.2 Analysis 22:	7
8.0.3 Analysis 23: code/04_dtu_dge_dte/pfam/external_protein_analysis.sh	7
8.0.4 Analysis 24: code/04_dtu_dge_dte/02_create_DGE_DTE_DTU.R	7
9 DGE_DTE_DTU Visualization	7
9.0.1 Analysis 25: code/05_visualization/01_PCA.R	7
9.0.2 Analysis 26: code/05_visualization/02_heatmaps.R	7
9.0.3 Analysis 27: code/05_visualization/03_volcano_plots.R	8
9.0.4 Analysis 28: code/05_visualization/04_retnet_dtu_genes.R	8
9.0.5 Analysis 29: code/05_visualization/04b_retnet_dtu_switchplots.R	8
9.0.6 Analysis 30: code/05_visualization/05_splicing_factor_analysis.R	8
9.0.7 Analysis 31: code/05_visualization/05b_splicing_factor_volcano.R	8
9.1 Analysis 32: code/05_visualization/06_splicing_factor_switchplots.R	8
9.2 Analysis 33: code/05_visualization/06_go_analysis.R	9
9.3 Analysis 34: code/05_visualization/07_upset.R	9
9.4 Analysis 35: code/05_visualization/07b_upset_only_DTUs.R	9
9.5 Analysis 36: code/05_visualization/07c_DTU_only_GO_analysis.R	9
9.6 Analysis 37: code/05_visualization/08_short_read_comparison.R	9
9.7 Analysis 38: code/05_visualization/09_isoforms_per_gene.R	10

Code can be found here: https://github.com/sparthib/retina_lrs

1 FASTQ processing

1.0.1 Analysis 1: code/01_fastq_processing/02_MinIONQC.sh

- **Question:** Read statistics - read length, base quality, N50 distribution
- **Input:** Raw FASTQ
- **Method:** MinIONQC was ran.
- **Output:** summary yaml and individual plots on read length distribution, base quality distribution, yield over time

1.0.2 Analysis 2: code/01_fastq_processing/03_fastq_qc.sh

- **Question:** Remove low quality reads based on Phred score.
- **Input:** Raw FASTQ, counts matrix, etc.
- **Method:** Nanofilt removes reads in fastq based on ONT summary text file.
- **Output:** processed FASTQ

1.0.3 Analysis 3: code/01_fastq_processing/minionQC_yaml.R

- **Question:** Produce boxplots of mean read length, median q value, median N50 and total number of reads across all samples.

- **Input:** YAML summary file produced by MinIONQC.
- **Method:** ggplot2
- **Output:** boxplots

2 FASTQ to BAM

2.0.1 Analysis 4: `code/01b_fastq_to_bam/01_fastq_to_bam_gencode_splice.sh`

- **Question:** Alignment with genome
- **Input:** Nanofilt processed FASTQ
- **Method:** Minimap2 was used to align reads to the genome.
- **Output:** bam

2.0.2 Analysis 5: `code/01b_fastq_to_bam/01b_fastq_to_bam_transcriptome_gencode.sh`

- **Question:** Alignment with transcriptome
- **Input:** Nanofilt processed FASTQ
- **Method:** Minimap2 was used to align reads to the transcriptome.
- **Output:** bam

2.0.3 Analysis 6: `code/01b_fastq_to_bam/02_high_quality_bam_genome.sh`

- **Question:** Removes alignments with MAPQ < 30. Only keeps primary mapped alignments in chr 1-22, X, Y, M.
- **Input:** Nanofilt processed FASTQ
- **Method:** samtools was used to filter the bam file, and create flagstat summary.
- **Output:** bam, summary stats on alignments.

3 BAM QC Visualization

3.0.1 Analysis 7: `code/01b_fastq_to_bam/02_high_quality_bam_genome.sh`

- **Question:** Removes alignments with MAPQ < 30. Only keeps primary mapped alignments in chr 1-22, X, Y, M.
- **Input:** Nanofilt processed FASTQ
- **Method:** samtools was used to filter the bam file, and create flagstat summary.
- **Output:** bam, summary stats on alignments.

3.0.2 Analysis 8: `code/02_bam_QC/01a_multi_exon_pcg_sample_specific.sh`

- **Question:** Exon-exon junction distribution
- **Input:** bam files produced in analysis 5
- **Method:** Multi-exon (PCG and all genes) junctions were quantified using python script `01_multi_exon_pcg.py` and `02_multi_exon_all_genes.py`. Visualization was done using R script `01_multi_exon_pcg.R` and `code/02_bam_QC/exon_exon_boxplots.R`
- **Output:** plots

3.0.3 Analysis 9: `code/02_bam_QC/read_type_percentages.R`

- **Question:** Percentage of alignments that are primary, supplementary, and unmapped.
- **Input:** flagstat file produced in analysis 4: `/retina_lrs/05_bams/genome/primary_assembly/logs/all.fl`
- **Method:** R script `read_type_percentages.R` was used to parse the flagstat file and create a bar plot of read types.
- **Output:** plots

3.0.4 Analysis 10:

- **Question:** Percentage of alignments that are primary, supplementary, and unmapped.
- **Input:** flagstat file produced in analysis 4: `/retina_lrs/05_bams/genome/primary_assembly/logs/all.fl`
- **Method:** R script `read_type_percentages.R` was used to parse the flagstat file and create a bar plot of read types.
- **Output:** plots

3.0.5 Quantification with `code/03_quantification/05_bambu`

3.0.6 Analysis 11:

`code/03_quantification/05_bambu/01_generate_sample_wise_read_class.sh`

- **Question:** Read class RDS files are generated for each sample individually.
- **Input:** bam files from analysis 6.
- **Method:** R script `read_type_percentages.R` was used to parse the flagstat file and create a bar plot of read types.
- **Output:** rds files

3.0.7 Analysis 12: `code/03_quantification/05_bambu/02_bambu_generate_rcs.sh`

- **Question:** Read classes are analyzed together for all samples to produce a common extended notation.
- **Input:** rds files from analysis 11.
- **Method:** R script `read_type_percentages.R` was used to parse the flagstat file and create a bar plot of read types.
- **Output:** final se object, counts matrix, extended annotation gtf.

3.0.8 Analysis 13: `code/03_quantification/05_bambu/05_sqanti.sh`

- **Question:** What type of novel isoforms were discovered?
- **Input:** extended annotation from analysis 12 and GENCODE references. polyA motif and CAGE peak experiments available from SQANTI example data.
- **Output:** `classification.txt`, `CDS.gtf`, `corrected.gtf` and `corrected.fasta` files.

3.0.9 Analysis 14: `code/03_quantification/05_bambu/03_bambu_quantification.R`

- **Question:** Read classes are analyzed together for all samples to produce a common extended notation.
- **Input:** `rds` files from analysis 11.
- **Method:** R script `read_type_percentages.R` was used to parse the `flagstat` file and create a bar plot of read types.
- **Output:** intermediate `se` object

3.0.10 Analysis 15:

`code/03_quantification/05_bambu/07_gene_names_for_novel_isoforms.R`

- **Question:** Get gene names for isoforms that are common between bambu and isoquant.
- **Input:** `"/dcs04/hicks/data/sparthib/retina_lrs/06_quantification/bambu"`, `"bambu_isoquant_refmap.txt"` from analysis 17.
- **Method:** R script for getting the gene names of common novel isoforms between bambu and isoquant.
- **Output:** `tsv`

TODO: Archive `03_bambu_quantification.R`, `04_switch_plots.R`, `06_number_of_isoforms_per_gene.R`

4 Isoquant

5 Analysis 16:

`code/03_quantification/01_IsoQuant/isoquant_all_samples.sh`

- **Question:** Isoquant quantification of all samples.
- **Input:** `bam` files from analysis 6.
- **Method:** Isoquant was used to quantify the reads.
- **Output:** isoquant output files including counts matrix, extended annotation, and SQANTI3 like output of quality of isoforms.

6 Compare gtfs

6.0.1 Analysis 17: `code/03_quantification/10_compare_gtfs/compare_gtfs.sh`

- **Question:** Compare the GTFs produced by bambu and isoquant.
- **Input:** GTF files from bambu and isoquant.

- **Method:** `gffcompare` was used to compare the GTF files and produce a summary of the differences.
- **Output:** `txt` file of common isoforms between bambu and isoquant.

7 Cleaning up counts matrix

7.0.1 Analysis 18:

`code/03_quantification/11_cleaning_up_counts_matrix/cleaning_up_counts_matrix.R`

- **Question:** Clean up column and row names.
- **Input:** Counts matrix from bambu.
- **Output:** FT vs RGC and ROs specific gene and isoforms counts matrices.

7.0.2 Analysis 19: `code/04_dtu_dge_dte/01b_filter_matrix_by_common_isoforms.R`

- **Question:** Filter the counts matrix by common isoforms between bambu and isoquant.
- **Input:** Isoform counts matrices from Analysis 18, and output from Analysis 17.
- **Method:** R script `filter_matrix_by_common_isoforms.R` was used to filter the counts matrix by common isoforms between bambu and isoquant and other known isoforms.

7.0.3 Analysis 20: `code/04_dtu_dge_dte/01c_filter_by_gene_biotypes.R`

- **Question:** Filter the counts matrix by gene biotypes.
- **Input:** Counts matrices from Analysis 19.
- **Method:** R script `filter_by_gene_biotypes.R` was used to filter the counts matrix to only keep protein coding genes. `edgeR::filterByExpr` was used to filter the counts matrix by expression levels, for gene counts and isoform counts separately, and converted to cpm.
- **Output:** PCG gene and isoform counts and cpm matrices.

8 DTU DGE DTE Analysis

8.0.1 Analysis 21:

`code/04_dtu_dge_dte/bambu/FT_vs_RGC/bambu_FT_vs_RGC_DTE_DGE.R`

`code/04_dtu_dge_dte/bambu/ROs/bambu_ROs_DGE_DTE.R` `code/04_dtu_dge_dte/bambu/RO_vs_RGC/RO_vs_RGC_DTE_DGE.R`

- **Question:** Differential transcript expression (DTE) and differential gene expression (DGE) analysis.
- **Input:** counts matrix from bambu.
- **Method:** R script `___DTE_DGE.R` was used to perform DTE and DGE analysis for 1. between FT and RGC, 2. between RO stages, 3. among RO stages and RGCs.
- **Output:** `tsv` files of DGE and DTE results.

8.0.2 Analysis 22:

code/04_dtu_dge_dte/bambu/FT_vs_RGC/bambu_FT_vs_RGC_DTU.R code/04_dtu_dge_dte/bambu/ROs/bambu_R
code/04_dtu_dge_dte/bambu/RO_vs_RGC/RO_vs_RGC_DTU.R - **Question:** Differential transcript usage (DTU) analysis using IsoformSwitchAnalyzeR. - **Input:** counts and cpm matrix from Analysis 20, extended annotation from bambu, CDS annotation from SQANTI3. - **Method:** R script ____DTU.R was used to perform DTU analysis for 1. between FT and RGC, 2. between RO stages, 3. among RO stages and RGCs. - **Output:** tsv files of DTU results, other files from IsoformSwitchAnalyzeR such as on splicing, switch consequences, switchplots.

8.0.3 Analysis 23: code/04_dtu_dge_dte/pfam/external_protein_analysis.sh

- **Question:** Pfam domain analysis, SignalP and CPC2.
- **Input:** SwitchAnalysisPart1 input from Analysis 22.
- **Method:** CPC2 was used to predict coding potential, SignalP was used to predict signal peptides, and Pfam was used to predict protein domains.
- **Output:** tsv files of coding potential, signal peptides, and protein domains incorporated into the switch plots in Analysis 22.

8.0.4 Analysis 24: code/04_dtu_dge_dte/02_create_DGE_DTE_DTU.R

- **Question:** Create a summary of DGE, DTE, and DTU results.
- **Input:** DGE, DTE, and DTU results from Analysis 21 and 22.
- **Method:** R script create_DGE_DTE_DTU.R was used to create a summary of DGE, DTE, and DTU results.
- **Output:** merged tsv files of DGE, DTE, and DTU results.

9 DGE_DTE_DTU Visualization

9.0.1 Analysis 25: code/05_visualization/01_PCA.R

- **Question:** PCA of gene and isoform expression for all comparisons.
- **Input:** CPM matrix from Analysis 20.
- **Method:** R script PCA.R was used to perform PCA analysis on the counts matrix.
- **Output:** PCA plots for gene and isoform expression.

9.0.2 Analysis 26: code/05_visualization/02_heatmaps.R

- **Question:** Heatmaps of gene and isoform expression for DGE genes and DTE/DTU isoforms for all comparisons.
- **Input:** CPM matrix from Analysis 20.
- **Method:** ComplexHeatmap was used to create heatmaps of gene and isoform expression.
- **Output:** Heatmap pdfs for gene and isoform expression.

9.0.3 Analysis 27: `code/05_visualization/03_volcano_plots.R`

- **Question:** Volcano plots of DGE, DTE, and DTU results.
- **Input:** DGE, DTE, and DTU results from Analysis 24.
- **Method:** R script `volcano_plots.R` was used to create volcano plots of DGE, DTE, and DTU results.
- **Output:** Volcano plots for DGE, DTE, and DTU results.

9.0.4 Analysis 28: `code/05_visualization/04_retnet_dtu_genes.R`

- **Question:** Which IRD genes have strong DTU or DTE events in our comparisons?
- **Input:** DGE, DTE, and DTU results from Analysis 24, gene list from RetNet database.
- **Method:** R script was used to create heatmaps for 30 or less genes with top DTU or DTE events.
- **Output:** Heatmaps of IRD genes with DTE and DTU events in all comparisons.

9.0.5 Analysis 29: `code/05_visualization/04b_retnet_dtu_switchplots.R`

- **Question:** Switchplots of DTU and DTE genes from Analysis 28.
- **Input:** SwitchAnalyzeR results from Analysis 22, gene list from Analysis 28.
- **Method:** R script was used to create switchplots for 30 or less genes with top DTU or DTE events.
- **Output:** Switchplots of IRD genes with DTE and DTU events in all comparisons.

9.0.6 Analysis 30: `code/05_visualization/05_splicing_factor_analysis.R`

- **Question:** Which splicing factor genes have strong DTE or DTU events in our comparisons?
- **Input:** DGE, DTE, and DTU results from Analysis 24, gene list from gene cards.
- **Method:** R script was used to create heatmaps similar to Analysis 28 for splicing factors.
- **Output:** Heatmaps of splicing factor genes with DTE and DTU events in all comparisons.

9.0.7 Analysis 31: `code/05_visualization/05b_splicing_factor_volcano.R`

- **Question:** Volcano plots of DGE, DTE, and DTU results for splicing factor genes.
- **Input:** DGE, DTE, and DTU results from Analysis 24, gene list from gene cards.
- **Method:** R script was used to create volcano plots for splicing factor genes.

9.1 Analysis 32: `code/05_visualization/06_splicing_factor_switchplots.R`

- **Question:** Switchplots of DTU and DTE splicing factor genes from Analysis 30.
- **Input:** SwitchAnalyzeR results from Analysis 22, gene list from Analysis 30.
- **Method:** R script was used to create switchplots for 30 or less splicing factor genes with top DTU or DTE events.

9.2 Analysis 33: `code/05_visualization/06_go_analysis.R`

- **Question:** What are the main biological processes that are associated at the gene and isoform level with DGE, DTE, and DTU for each comparison?
- **Input:** DGE, DTE, and DTU results from Analysis 24.
- **Method:** R script was used to perform GO analysis using `clusterProfiler`.
- **Output:** `enrichGO` dotplots for DGE, DTE, and DTU genes and isoforms.

9.3 Analysis 34: `code/05_visualization/07_upset.R`

- **Question:** What are the common genes and isoforms between DGE, DTE, and DTU for each comparison?
- **Input:** DGE, DTE, and DTU results from Analysis 24.
- **Method:** `UpsetR` was used to create upset plots for common genes and isoforms between DGE, DTE, and DTU for each comparison.

9.4 Analysis 35: `code/05_visualization/07b_upset_only_DTUs.R`

- **Question:** What are the genes that had DTU events common between multiple RO stages? Which ones were unique to a certain pairwise comparisons?
- **Input:** DTU results from Analysis 24.
- **Method:** `UpsetR` was used to create upset plots for common DTU genes between multiple RO stages.
- **Output:** Upset plot of DTU genes across the multiple RO stages.

9.5 Analysis 36: `code/05_visualization/07c_DTU_only_GO_analysis.R`

- **Question:** What are the main biological processes that are associated with the 166 genes that were DTU across all stage comparisons?
- **Input:** DTU results from Analysis 24.
- **Method:** R script was used to perform GO analysis using `clusterProfiler`.
- **Output:** `enrichGO` dotplot for DTU genes across all stage comparisons.

9.6 Analysis 37: `code/05_visualization/08_short_read_comparison.R`

- **Question:** How does the long read gene expression in our RO samples compare to the short read gene expression in a previous study?
- **Input:** RO gene CPM matrix from Analysis 20.
- **Method:** R script was used to create a geom tile heatmap of the sample-wise spearman correlations.
- **Output:** Heatmap of sample-wise spearman correlations between long read and short read gene expression across the different RO stages.

9.7 Analysis 38: `code/05_visualization/09_isoforms_per_gene.R`

- **Question:** How many isoforms are there per gene in our RO samples?
- **Input:** extended annotation from bambu filtered by isoforms present in Analysis 20 of all RO samples.
- **Method:** R script was used to create the distribution of isoform counts per gene number across samples.
- **Output:** Barplot of isoforms per gene across samples.

TODO: remove `code/06_rbp_analysis` dir TODO: archive `code/09_RBF0X_motif_genes` dir