

Schema documentation for spase-2_2_0.xsd

6 january 2011

Table of Contents

Namespace: "http://www.spase-group.org/data/schema"	4
Schemas	4
Main schema spase-2_2_0.xsd	4
Elements	4
Element Spase	4
Element Version	5
Element ResourceEntity	5
Element Catalog	6
Element ResourceID	8
Element ResourceHeader	8
Element ResourceName	9
Element AlternateName	9
Element ReleaseDate	9
Element ExpirationDate	10
Element Description	10
Element Acknowledgement	11
Element Contact	11
Element PersonID	12
Element Role	12
Element InformationURL	13
Element Name	13
Element URL	14
Element Language	14
Element Association	15
Element AssociationID	15
Element AssociationType	15
Element Note	16
Element PriorID	16
Element AccessInformation	16
Element RepositoryID	17
Element Availability	17
Element AccessRights	18
Element AccessURL	18
Element Format	19
Element Encoding	21
Element DataExtent	22
Element Quantity	23
Element Units	23
Element Per	24
Element ProviderResourceName	24
Element ProviderVersion	25
Element InstrumentID	25
Element PhenomenonType	25
Element TimeSpan	27
Element StartDate	28
Element StopDateEntity	28
Element Caveats	28
Element Keyword	29
Element InputResourceID	29
Element Parameter	29
Element Set	31
Element ParameterKey	31
Element Cadence	31
Element UnitsConversion	32
Element CoordinateSystem	32
Element CoordinateRepresentation	33
Element CoordinateSystemName	33
Element RenderingHints	37
Element DisplayType	38
Element AxisLabel	39
Element RenderingAxis	39
Element Index	40
Element ValueFormat	40

Element ScaleMin	41
Element ScaleMax	41
Element ScaleType	41
Element Structure	42
Element Size	42
Element Element	43
Element Qualifier	43
Element ValidMin	47
Element ValidMax	47
Element FillValue	47
Element ParameterEntity	47
Element Extension	48
Element Field	49
Element FieldQuantity	49
Element FrequencyRange	50
Element SpectralRange	50
Element Low	52
Element High	52
Element Bin	52
Element BandName	53
Element Particle	53
Element ParticleType	54
Element ParticleQuantity	54
Element AtomicNumber	56
Element EnergyRange	56
Element AzimuthalAngleRange	57
Element PolarAngleRange	57
Element Wave	58
Element WaveType	58
Element WaveQuantity	59
Element WavelengthRange	60
Element Mixed	61
Element MixedQuantity	62
Element Support	62
Element SupportQuantity	63
Element DisplayData	64
Element ProcessingLevel	65
Element ProviderProcessingLevel	65
Element MeasurementType	66
Element TemporalDescription	68
Element Exposure	68
Element DisplayCadence	68
Element ObservedRegion	69
Element NumericalData	72
Element Document	74
Element DocumentType	74
Element Granule	75
Element ParentID	76
Element StopDate	76
Element Source	76
Element SourceType	77
Element MirrorURL	78
Element Checksum	78
Element HashValue	78
Element HashFunction	79
Element Instrument	79
Element InstrumentType	80
Element InvestigationName	84
Element OperatingSpan	84
Element ObservatoryID	84
Element Observatory	85
Element ObservatoryGroupID	85
Element Location	86
Element ObservatoryRegion	86
Element Latitude	89
Element Longitude	90
Element Elevation	90
Element Person	90
Element PersonName	91
Element OrganizationName	92
Element Address	92
Element Email	92

Element PhoneNumber	93
Element FaxNumber	93
Element Registry	93
Element Repository	94
Element Service	95
Element Annotation	95
Element ImageURL	96
Element AnnotationType	97
Element ClassificationMethod	97
Element ConfidenceRating	97
Element ObservationExtent	98
Element StartLocation	98
Element StopLocation	99
Element RelativeStopDate	99
Complex Types	99
Complex Type Spase	99
Complex Type Catalog	100
Complex Type ResourceHeader	101
Complex Type Contact	102
Complex Type InformationURL	103
Complex Type Association	103
Complex Type AccessInformation	104
Complex Type AccessURL	104
Complex Type DataExtent	105
Complex Type TimeSpan	105
Complex Type Parameter	106
Complex Type CoordinateSystem	108
Complex Type RenderingHints	108
Complex Type Structure	109
Complex Type Element	109
Complex Type Field	110
Complex Type FrequencyRange	110
Complex Type Bin	111
Complex Type Particle	111
Complex Type EnergyRange	112
Complex Type AzimuthalAngleRange	113
Complex Type PolarAngleRange	113
Complex Type Wave	114
Complex Type WavelengthRange	114
Complex Type Mixed	115
Complex Type Support	115
Complex Type DisplayData	116
Complex Type TemporalDescription	117
Complex Type NumericalData	117
Complex Type Document	119
Complex Type Granule	119
Complex Type Source	120
Complex Type Checksum	121
Complex Type Instrument	121
Complex Type OperatingSpan	122
Complex Type Observatory	123
Complex Type Location	123
Complex Type Person	124
Complex Type Registry	125
Complex Type Repository	125
Complex Type Service	125
Complex Type Annotation	126
Complex Type ObservationExtent	127
Simple Types	127
Simple Type enumVersion	127
Simple Type enumRole	128
Simple Type enumAssociationType	130
Simple Type enumAvailability	131
Simple Type enumAccessRights	131
Simple Type enumFormat	132
Simple Type enumEncoding	138
Simple Type enumPhenomenonType	140
Simple Type enumCoordinateRepresentation	144
Simple Type enumCoordinateSystemName	145
Simple Type enumDisplayType	153
Simple Type enumRenderingAxis	154
Simple Type typeSequence	155

Simple Type enumScaleType	155
Simple Type enumQualifier	156
Simple Type enumFieldQuantity	164
Simple Type enumSpectralRange	165
Simple Type enumParticleType	168
Simple Type enumParticleQuantity	169
Simple Type enumWaveType	173
Simple Type enumWaveQuantity	174
Simple Type enumMixedQuantity	177
Simple Type enumSupportQuantity	179
Simple Type enumProcessingLevel	180
Simple Type enumMeasurementType	181
Simple Type enumRegion	185
Simple Type enumDocumentType	192
Simple Type enumSourceType	193
Simple Type enumHashFunction	194
Simple Type enumInstrumentType	195
Simple Type enumAnnotationType	202
Simple Type enumClassificationMethod	203
Simple Type enumConfidenceRating	203
Simple Type enumComponent	204
Simple Type enumDirectionAngle	205
Simple Type enumEarth	206
Simple Type enumHardcopy	210
Simple Type enumHeliosphere	211
Simple Type enumIntegral	212
Simple Type enumIonosphere	212
Simple Type enumMagnetosphere	213
Simple Type enumNearSurface	214
Simple Type enumProjection	217
Simple Type enumSun	218
Simple Type enumText	219
Simple Type enumWaves	220
Namespace: ""	220
Attributes	220
Attribute Spase / @lang	220

Namespace: "http://www.spase-group.org/data/schema"

Schemas

Main schema spase-2_2_0.xsd

Namespace	http://www.spase-group.org/data/schema
Properties	attribute form default: unqualified element form default: qualified
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Elements

Element Spase

Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class Spase { <<Abstract true>> @lang Type xsd:string Default en Version Type enumVersion } </pre>
Type	Spase

Properties	content: complex				
Model	Version , ResourceEntity+				
Children	ResourceEntity, Version				
Instance	<Spase lang="en"> <Version>{1,1}</Version> <ResourceEntity>{1,unbounded}</ResourceEntity> </Spase>				
Attributes	QName	Type	Fixed	Default	Use
	lang	xsd:string		en	optional
Source	<xsd:element name="Spase" type="Spase" />				
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd				


Element Version

Namespace	http://www.spase-group.org/data/schema				
Annotations	Indicates the release identifier. When used to indicate the release of the SPASE data model, it is in the form Major.Minor.Fix where Major: A significant change in the architecture of the model or rewrite of the implementation. This includes major changes in design or implementation language. This number starts at 0 (zero). Minor: An addition of terms or features that require changes in documentation/external API. This number starts at 0 (zero). Fix: Any change that doesn't require documentation/external API changes. This number starts at 0 (zero).				
Diagram	<pre> classDiagram class Version { <<enumVersion>> } Version "1..1" -- "0..1" enumVersion </pre>				
Type	enumVersion				
Properties	content: simple				
Facets	enumeration 2.2.0				
Used by	Complex Type Spase				
Source	<pre> <xsd:element name="Version" type="enumVersion"> <xsd:annotation> <xsd:documentation xml:lang="en">Indicates the release identifier. When used to indicate the release of the SPASE data model, it is in the form Major.Minor.Fix where Major: A significant change in the architecture of the model or rewrite of the implementation. This includes major changes in design or implementation language. This number starts at 0 (zero). Minor: An addition of terms or features that require changes in documentation/external API. This number starts at 0 (zero). Fix: Any change that doesn't require documentation/external API changes. This number starts at 0 (zero).</xsd:documentation> </xsd:annotation> </xsd:element> </pre>				
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd				

Element ResourceEntity

Namespace	http://www.spase-group.org/data/schema				
-----------	--	--	--	--	--

Diagram



Properties

abstract: true

Substitution Group

- Catalog
- DisplayData
- NumericalData
- Document
- Granule
- Instrument
- Observatory
- Person
- Registry
- Repository
- Service
- Annotation
- Extension

Used by

Complex Type Spase

Source

<xsd:element name="ResourceEntity" abstract="true"/>


Schema location

file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Catalog


Namespace	http://www.spase-group.org/data/schema
-----------	---

Diagram




Type	Catalog
Properties	content: complex
Substitution Group Affiliation	<ul style="list-style-type: none"> ResourceEntity
Model	ResourceID , ResourceHeader , AccessInformation+ , ProviderResourceName{0,1} , ProviderVersion{0,1} , InstrumentID* , PhenomenonType+ , TimeSpan{0,1} , Caveats{0,1} , Keyword* , InputResourceID* , Parameter* , Extension*
Children	AccessInformation, Caveats, Extension, InputResourceID, InstrumentID, Keyword, Parameter, PhenomenonType, ProviderResourceName, ProviderVersion, ResourceHeader, ResourceID, TimeSpan
Instance	<Catalog> <ResourceID>{1,1}</ResourceID> <ResourceHeader>{1,1}</ResourceHeader> <AccessInformation>{1,unbounded}</AccessInformation> <ProviderResourceName>{0,1}</ProviderResourceName> <ProviderVersion>{0,1}</ProviderVersion> <InstrumentID>{0,unbounded}</InstrumentID> <PhenomenonType>{1,unbounded}</PhenomenonType> <TimeSpan>{0,1}</TimeSpan> <Caveats>{0,1}</Caveats> <Keyword>{0,unbounded}</Keyword> <InputResourceID>{0,unbounded}</InputResourceID> <Parameter>{0,unbounded}</Parameter> <Extension>{0,unbounded}</Extension> </Catalog>
Source	<xsd:element name="Catalog" type="Catalog" substitutionGroup="ResourceEntity"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ResourceID


Namespace	http://www.spase-group.org/data/schema
Annotations	A Resource ID is a URI that has the form "scheme://authority/path" where "scheme" is "spase" for those resources administered through the SPASE framework, "authority" is the unique identifier for the resource provider registered within the SPASE framework and "path" is the unique identifier of the resource within the context of the "authority". The resource ID must be unique within the SPASE framework.
Diagram	
Type	xsd:string
Properties	content: simple
Used by	Complex Types Annotation, Catalog, DisplayData, Document, Granule, Instrument, NumericalData, Observatory, Person, Registry, Repository, Service
Source	<pre><xsd:element name="ResourceID" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">A Resource ID is a URI that has the form "scheme://authority/path" where "scheme" is "spase" for those resources administered through the SPASE framework, "authority" is the unique identifier for the resource provider registered within the SPASE framework and "path" is the unique identifier of the resource within the context of the "authority". The resource ID must be unique within the SPASE framework.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ResourceHeader


Namespace	http://www.spase-group.org/data/schema
Diagram	
Type	ResourceHeader
Properties	content: complex

Used by	Complex Types Annotation, Catalog, DisplayData, Document, Instrument, NumericalData, Observatory, Registry, Repository, Service
Model	ResourceName , AlternateName* , ReleaseDate , ExpirationDate{0,1} , Description , Acknowledgement{0,1} , Contact+ , InformationURL* , Association* , PriorID*
Children	Acknowledgement, AlternateName, Association, Contact, Description, ExpirationDate, InformationURL, PriorID, ReleaseDate, ResourceName
Instance	<ResourceHeader> <ResourceName>{1,1}</ResourceName> <AlternateName>{0,unbounded}</AlternateName> <ReleaseDate>{1,1}</ReleaseDate> <ExpirationDate>{0,1}</ExpirationDate> <Description>{1,1}</Description> <Acknowledgement>{0,1}</Acknowledgement> <Contact>{1,unbounded}</Contact> <InformationURL>{0,unbounded}</InformationURL> <Association>{0,unbounded}</Association> <PriorID>{0,unbounded}</PriorID> </ResourceHeader>
Source	<xsd:element name="ResourceHeader" type="ResourceHeader" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ResourceName


Namespace	http://www.spase-group.org/data/schema
Annotations	A short textual description of a resource which may be useful when read by a person.
Diagram	
Type	xsd:string
Properties	content: simple
Used by	Complex Type ResourceHeader
Source	<xsd:element name="ResourceName" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">A short textual description of a resource which may be useful when read by a person.</xsd:documentation> </xsd:annotation> </xsd:element>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element AlternateName


Namespace	http://www.spase-group.org/data/schema
Annotations	An alternative or shortened name used to refer to a resource. This includes acronyms, expanded names or a synonym for a resource.
Diagram	
Type	xsd:string
Properties	content: simple
Used by	Complex Type ResourceHeader
Source	<xsd:element name="AlternateName" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">An alternative or shortened name used to refer to a resource. This includes acronyms, expanded names or a synonym for a resource.</xsd:documentation> </xsd:annotation> </xsd:element>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ReleaseDate

Namespace	http://www.spase-group.org/data/schema
-----------	--

Annotations	The date and time when a resource is made available. The availability of a resource coincides with the release of a resource description. If the Release Date is specified as a future date then it indicates that resource should not be made available until that time. However, this is only advisory and in practice the Release Date should be the actual date the resource description was published.
Diagram	
Type	xsd:dateTime
Properties	content: simple
Used by	Complex Types Granule, Person, ResourceHeader
Source	<pre><xsd:element name="ReleaseDate" type="xsd:dateTime"> <xsd:annotation> <xsd:documentation xml:lang="en">The date and time when a resource is made available. The availability of a resource coincides with the release of a resource description. If the Release Date is specified as a future date then it indicates that resource should not be made available until that time. However, this is only advisory and in practice the Release Date should be the actual date the resource description was published.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ExpirationDate

Namespace	http://www.spase-group.org/data/schema
Annotations	The date and time when a resource is no longer available. If the Expiration Date is specified then it indicates that resource should not be made available after that time. However, this is only advisory and in practice a resource description should be unpublished to eliminate access to a resource.
Diagram	
Type	xsd:dateTime
Properties	content: simple
Used by	Complex Types Granule, ResourceHeader
Source	<pre><xsd:element name="ExpirationDate" type="xsd:dateTime"> <xsd:annotation> <xsd:documentation xml:lang="en">The date and time when a resource is no longer available. If the Expiration Date is specified then it indicates that resource should not be made available after that time. However, this is only advisory and in practice a resource description should be unpublished to eliminate access to a resource.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Description


Namespace	http://www.spase-group.org/data/schema
Annotations	A narrative explanation with detail appropriate for the item it describes. For example a description of data resource should include discussions of the main quantities in the resource, possible uses and search terms. A description should also include whether any corrections (i.e.,

	geometry, inertial) have been applied to the resource.
Diagram	
Type	xsd:string
Properties	content: simple
Used by	Complex Types AccessURL, InformationURL, Parameter, ResourceHeader, Structure
Source	<pre><xsd:element name="Description" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">A narrative explanation with detail appropriate for the item it describes. For example a description of data resource should include discussions of the main quantities in the resource, possible uses and search terms. A description should also include whether any corrections (i.e, geometry, inertial) have been applied to the resource.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Acknowledgement

Namespace	http://www.spase-group.org/data/schema
Annotations	The individual, group or organization which should be acknowledged when the data is used in or contributes to a presentation or publication.
Diagram	
Type	xsd:string
Properties	content: simple
Used by	Complex Types AccessInformation, ResourceHeader
Source	<pre><xsd:element name="Acknowledgement" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The individual, group or organization which should be acknowledged when the data is used in or contributes to a presentation or publication.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Contact

Namespace	http://www.spase-group.org/data/schema
Diagram	
Type	Contact
Properties	content: complex
Used by	Complex Type ResourceHeader
Model	PersonID , Role+
Children	PersonID, Role
Instance	<pre><Contact> <PersonID>{1,1}</PersonID> <Role>{1..unbounded}</Role> </Contact></pre>

Source	<xsd:element name="Contact" type="Contact" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element PersonID

Namespace	http://www.spase-group.org/data/schema
Annotations	The identifier assigned to a Person description.
Diagram	A UML class diagram fragment showing a class named "PersonID" with a multiplicity of 0..1. It has a directed association labeled "Type" pointing to a class named "xsd:string" with a multiplicity of 1..1.
Type	xsd:string
Properties	content: simple
Used by	Complex Type Contact
Source	<pre><xsd:element name="PersonID" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The identifier assigned to a Person description.</ xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Role

Namespace	http://www.spase-group.org/data/schema																														
Annotations	The assigned or assumed function or position of an individual.																														
Diagram	A UML class diagram fragment showing a class named "Role" with a multiplicity of 0..1. It has a directed association labeled "Type" pointing to a class named "enumRole" with a multiplicity of 1..1.																														
Type	enumRole																														
Properties	content: simple																														
Facets	<table border="1"> <tr> <td>enumeration</td> <td>ArchiveSpecialist</td> <td>An individual who is an expert on a collection of resources and may also be knowledgeable of the phenomenon and related physics represented by the resources. This includes librarians, curators, archive scientists and other experts.</td> </tr> <tr> <td>enumeration</td> <td>CoInvestigator</td> <td>An individual who is a scientific peer and major participant in an investigation.</td> </tr> <tr> <td>enumeration</td> <td>Contributor</td> <td>An entity responsible for making contributions to the content of the resource.</td> </tr> <tr> <td>enumeration</td> <td>DataProducer</td> <td>An individual who generated the resource and is familiar with its provenance.</td> </tr> <tr> <td>enumeration</td> <td>DeputyPI</td> <td>An individual who is an administrative or scientific leader for an investigation operating under the supervision of a Principal Investigator.</td> </tr> <tr> <td>enumeration</td> <td>FormerPI</td> <td>An individual who had served as the administrative and scientific lead for an investigation, but no longer assumes that role.</td> </tr> <tr> <td>enumeration</td> <td>GeneralContact</td> <td>An individual who can provide information on a range of subjects or who can direct you to a domain expert.</td> </tr> <tr> <td>enumeration</td> <td>MetadataContact</td> <td>An individual who can affect a change in the metadata describing a resource.</td> </tr> <tr> <td>enumeration</td> <td>PrincipalInvestigator</td> <td>An individual who is the administrative and scientific lead for an investigation.</td> </tr> <tr> <td>enumeration</td> <td>ProjectScientist</td> <td>An individual who is an expert in the phenomenon and related physics explored by the project.</td> </tr> </table>	enumeration	ArchiveSpecialist	An individual who is an expert on a collection of resources and may also be knowledgeable of the phenomenon and related physics represented by the resources. This includes librarians, curators, archive scientists and other experts.	enumeration	CoInvestigator	An individual who is a scientific peer and major participant in an investigation.	enumeration	Contributor	An entity responsible for making contributions to the content of the resource.	enumeration	DataProducer	An individual who generated the resource and is familiar with its provenance.	enumeration	DeputyPI	An individual who is an administrative or scientific leader for an investigation operating under the supervision of a Principal Investigator.	enumeration	FormerPI	An individual who had served as the administrative and scientific lead for an investigation, but no longer assumes that role.	enumeration	GeneralContact	An individual who can provide information on a range of subjects or who can direct you to a domain expert.	enumeration	MetadataContact	An individual who can affect a change in the metadata describing a resource.	enumeration	PrincipalInvestigator	An individual who is the administrative and scientific lead for an investigation.	enumeration	ProjectScientist	An individual who is an expert in the phenomenon and related physics explored by the project.
enumeration	ArchiveSpecialist	An individual who is an expert on a collection of resources and may also be knowledgeable of the phenomenon and related physics represented by the resources. This includes librarians, curators, archive scientists and other experts.																													
enumeration	CoInvestigator	An individual who is a scientific peer and major participant in an investigation.																													
enumeration	Contributor	An entity responsible for making contributions to the content of the resource.																													
enumeration	DataProducer	An individual who generated the resource and is familiar with its provenance.																													
enumeration	DeputyPI	An individual who is an administrative or scientific leader for an investigation operating under the supervision of a Principal Investigator.																													
enumeration	FormerPI	An individual who had served as the administrative and scientific lead for an investigation, but no longer assumes that role.																													
enumeration	GeneralContact	An individual who can provide information on a range of subjects or who can direct you to a domain expert.																													
enumeration	MetadataContact	An individual who can affect a change in the metadata describing a resource.																													
enumeration	PrincipalInvestigator	An individual who is the administrative and scientific lead for an investigation.																													
enumeration	ProjectScientist	An individual who is an expert in the phenomenon and related physics explored by the project.																													

		A project scientist may also have a managerial role within the project.
	enumeration Publisher	An individual, organization, institution or government department responsible for the production and dissemination of a document.
	enumeration Scientist	An individual who is an expert in the phenomenon and related physics represented by the resource.
	enumeration TeamLeader	An individual who is the designated leader of an investigation.
	enumeration TeamMember	An individual who is a major participant in an investigation.
	enumeration TechnicalContact	An individual who can provide specific information with regard to the resource or supporting software
Used by	Complex Type Contact	
Source		<pre><xsd:element name="Role" type="enumRole"> <xsd:annotation> <xsd:documentation xml:lang="en">The assigned or assumed function or position of an individual.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location		file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element InformationURL

Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class InformationURL { Name : xsd:string URL : xsd:string Description : xsd:string Language : xsd:string } InformationURL "2" --> "2" InformationURL </pre>
Type	InformationURL
Properties	content: complex
Used by	Complex Type ResourceHeader
Model	Name{0,1} , URL , Description{0,1} , Language{0,1}
Children	Description, Language, Name, URL
Instance	<pre> <InformationURL> <Name>{0,1}</Name> <URL>{1,1}</URL> <Description>{0,1}</Description> <Language>{0,1}</Language> </InformationURL> </pre>
Source	<xsd:element name="InformationURL" type="InformationURL" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Name

Namespace	http://www.spase-group.org/data/schema
Annotations	A language unit by which a person or thing is known.
Diagram	<pre> classDiagram class Name { Name : xsd:string Type : xsd:string } Name "2" --> "2" Name </pre>

Type	xsd:string
Properties	content: simple
Used by	Complex Types AccessURL, Element, InformationURL, Parameter
Source	<pre><xsd:element name="Name" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">A language unit by which a person or thing is known.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element URL

Namespace	http://www.spase-group.org/data/schema
Annotations	<p>Uniform Resource Locator (URL) is the global address of documents and other resources on the World Wide Web. The first part of the address indicates what protocol to use, and the second part specifies the IP address or the domain name where the resource is located followed by the pathname of the resource.</p> <p>A URL is specified in the form protocol://server.domain.name:port/pathname. Example protocols are HTTP or FTP, server domain name is the Internet name.</p>
Diagram	<pre> classDiagram class URL { Type xsd:string } xsd:string URL "1" -- "0..1" xsd:string </pre>
Type	xsd:string
Properties	content: simple
Used by	Complex Types AccessURL, InformationURL, Source
Source	<pre><xsd:element name="URL" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">Uniform Resource Locator (URL) is the global address of documents and other resources on the World Wide Web. The first part of the address indicates what protocol to use, and the second part specifies the IP address or the domain name where the resource is located followed by the pathname of the resource. A URL is specified in the form protocol://server.domain.name:port/pathname. Example protocols are HTTP or FTP, server domain name is the Internet name.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Language

Namespace	http://www.spase-group.org/data/schema
Annotations	The two character indicator of language selected from the ISO 630-1 codes for the representation of names of languages.
Diagram	<pre> classDiagram class Language { Type xsd:string } xsd:string Language "1" -- "0..1" xsd:string </pre>
Type	xsd:string
Properties	content: simple
Used by	Complex Types AccessURL, InformationURL
Source	<pre><xsd:element name="Language" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The two character indicator of language selected from the ISO 630-1 codes for the representation of names of languages.</xsd:documentation> </xsd:annotation> </xsd:element></pre>

Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd
-----------------	---

Element Association

Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class Association { <<Association>> <<AssociationID>> xsd:string <<AssociationType>> enumAssociationType <<Note>> xsd:string } </pre>
Type	Association
Properties	content: complex
Used by	Complex Type ResourceHeader
Model	AssociationID{0,1} , AssociationType{0,1} , Note{0,1}
Children	AssociationID, AssociationType, Note
Instance	<Association> <AssociationID>{0,1}</AssociationID> <AssociationType>{0,1}</AssociationType> <Note>{0,1}</Note> </Association>
Source	<xsd:element name="Association" type="Association"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element AssociationID

Namespace	http://www.spase-group.org/data/schema
Annotations	The resource identifier for a resource with which this resource is closely associated.
Diagram	<pre> classDiagram class AssociationID { <<AssociationID>> <<xsd:string>> } </pre>
Type	xsd:string
Properties	content: simple
Used by	Complex Type Association
Source	<xsd:element name="AssociationID" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The resource identifier for a resource with which this resource is closely associated.</xsd:documentation> </xsd:annotation> </xsd:element>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element AssociationType

Namespace	http://www.spase-group.org/data/schema
Annotations	A characterization of the role or purpose of an associated resource.
Diagram	<pre> classDiagram class AssociationType { <<AssociationType>> <<enumAssociationType>> } </pre>
Type	enumAssociationType
Properties	content: simple
Facets	enumeration

	enumeration	DerivedFrom	A transformed or altered version of a resource instance.
	enumeration	ObservedBy	Detected or originating from another resource.
	enumeration	Other	Not classified with more specific terms. The context of its usage may be described in related text.
	enumeration	PartOf	A portion of a larger resource.
	enumeration	RevisionOf	A modified version of a resource instance.
Used by	Complex Type	Association	
Source	<xsd:element name="AssociationType" type="enumAssociationType"> <xsd:annotation> <xsd:documentation xml:lang="en">A characterization of the role or purpose of an associated resource.</xsd:documentation> </xsd:annotation> </xsd:element>		
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd		

Element Note

Namespace	http://www.spase-group.org/data/schema	
Annotations	Information which is useful or important for the understanding of a value or parameter.	
Diagram	 A UML class diagram element labeled "Note". It has a note above it stating "Type xsd:string". A line connects "Note" to a rounded rectangle labeled "xsd:string".	
Type	xsd:string	
Properties	content: simple	
Used by	Complex Types	Association, ObservationExtent, OperatingSpan, Person, TimeSpan
Source	<xsd:element name="Note" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">Information which is useful or important for the understanding of a value or parameter.</xsd:documentation> </xsd:annotation> </xsd:element>	
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd	


Element PriorID

Namespace	http://www.spase-group.org/data/schema	
Annotations	The resource identifier for a resource that is superseded or replaced by a resource.	
Diagram	 A UML class diagram element labeled "PriorID". It has a note above it stating "Type xsd:string". A line connects "PriorID" to a rounded rectangle labeled "xsd:string".	
Type	xsd:string	
Properties	content: simple	
Used by	Complex Types	Granule, ResourceHeader
Source	<xsd:element name="PriorID" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The resource identifier for a resource that is superseded or replaced by a resource.</xsd:documentation> </xsd:annotation> </xsd:element>	
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd	

Element AccessInformation

Namespace	http://www.spase-group.org/data/schema	

Diagram



Type	AccessInformation
Properties	content: complex
Used by	Complex Types Catalog, DisplayData, Document, NumericalData
Model	RepositoryID , Availability{0,1} , AccessRights{0,1} , AccessURL+ , Format , Encoding{0,1} , DataExtent{0,1} , Acknowledgement{0,1}
Children	AccessRights, AccessURL, Acknowledgement, Availability, DataExtent, Encoding, Format, RepositoryID
Instance	<AccessInformation> <RepositoryID>{1,1}</RepositoryID> <Availability>{0,1}</Availability> <AccessRights>{0,1}</AccessRights> <AccessURL>{1,unbounded}</AccessURL> <Format>{1,1}</Format> <Encoding>{0,1}</Encoding> <DataExtent>{0,1}</DataExtent> <Acknowledgement>{0,1}</Acknowledgement> </AccessInformation>
Source	<xsd:element name="AccessInformation" type="AccessInformation"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element RepositoryID

Namespace	http://www.spase-group.org/data/schema
Annotations	The identifier of an Repository resource.
Diagram	<pre> class RepositoryID { <--> xsd:string } </pre> <p>The diagram shows the <code>RepositoryID</code> element defined in the schema. It has a self-referencing relationship to the <code>xsd:string</code> type.</p>
Type	xsd:string
Properties	content: simple
Used by	Complex Type AccessInformation
Source	<xsd:element name="RepositoryID" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The identifier of an Repository resource.</xsd:documentation> </xsd:annotation> </xsd:element>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Availability

Namespace	http://www.spase-group.org/data/schema
Annotations	An indication of the method or service which

	may be used to access the resource.				
Diagram		Type	enumAvailability		
Type	enumAvailability				
Properties	content: simple				
Facets	enumeration	Offline	Not directly accessible electronically. This includes resources which may be moved to an on-line status in response to a given request.		
	enumeration	Online	Directly accessible electronically.		
Used by	Complex Type	AccessInformation			
Source	<pre><xsd:element name="Availability" type="enumAvailability"> <xsd:annotation> <xsd:documentation xml:lang="en">An indication of the method or service which may be used to access the resource.</xsd:documentation> </xsd:annotation> </xsd:element></pre>				
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd				

Element AccessRights

Namespace	http://www.spase-group.org/data/schema				
Annotations	Permissions granted or denied by the host of a product to allow other users to access and use the resource.				
Diagram					
Type	enumAccessRights				
Properties	content: simple				
Facets	enumeration	Open	Access is granted to everyone.		
	enumeration	Restricted	Access to the product is regulated and requires some form of identification.		
Used by	Complex Type	AccessInformation			
Source	<pre><xsd:element name="AccessRights" type="enumAccessRights"> <xsd:annotation> <xsd:documentation xml:lang="en">Permissions granted or denied by the host of a product to allow other users to access and use the resource.</xsd:documentation> </xsd:annotation> </xsd:element></pre>				
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd				

Element AccessURL

Namespace	http://www.spase-group.org/data/schema		
Diagram	<pre> classDiagram class AccessURL { Name URL Description Language } AccessURL < -- AccessURL </pre>		
Type	AccessURL		
Properties	content: complex		

Used by	Complex Types AccessInformation, Registry, Repository, Service
Model	Name{0,1} , URL , Description{0,1} , Language{0,1}
Children	Description, Language, Name, URL
Instance	<AccessURL> <Name>{0,1}</Name> <URL>{1,1}</URL> <Description>{0,1}</Description> <Language>{0,1}</Language> </AccessURL>
Source	<xsd:element name="AccessURL" type="AccessURL" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Format

Namespace	http://www.spase-group.org/data/schema		
Annotations	The organization of data according to preset specifications. The value is selected from a list of accepted names for known, well documented formats.		
Diagram	<pre> classDiagram class Format { <<Format>> <<Type>> enumFormat } class enumFormat { <<enumFormat>> } Format "1" -- "0..1" enumFormat </pre>		
Type	enumFormat		
Properties	content: simple		
Facets	enumeration	AVI	Audio Video Interleave (AVI) a digital format for movies that conforms to the Microsoft Windows Resource Interchange File Format (RIFF).
	enumeration	Binary	A direct representation of the bits which may be stored in memory on a computer.
	enumeration	CDF	Common Data Format (CDF). A binary storage format developed at Goddard Space Flight Center (GSFC).
	enumeration	CEF	Cluster Exchange Format (CEF) is a self-documenting ASCII format designed for the exchange of data. There are two versions of CEF which are not totally compatible.
	enumeration	CEF1	Cluster Exchange Format (CEF), version 1, is a self-documenting ASCII format designed for the exchange of data. The metadata contains information compatible with the ISTP recommendations for CDF.
	enumeration	CEF2	Cluster Exchange Format (CEF), version 2, is a self-documenting ASCII format designed for the exchange of data and introduced for Cluster Active Archive. Compared to version 1, the metadata description of vectors and tensors is different.
	enumeration	Excel	A Microsoft spreadsheet format used to hold a variety of data in tables which can include calculations.
	enumeration	FITS	Flexible Image Transport System (FITS) is a digital format primarily designed to store scientific data sets consisting of multi-dimensional arrays (1-D spectra, 2-D images or 3-D data cubes) and 2-dimensional tables containing rows and columns of data.
	enumeration	GIF	Graphic Interchange Format (GIF) first introduced in 1987 by CompuServe. GIF uses LZW compression and images are limited to 256 colours.


enumeration	Hardcopy	A permanent reproduction, or copy in the form of a physical object, of any media suitable for direct use by a person.
enumeration	Hardcopy.Film	An image recording medium on which usually a "negative" analog image is registered. A "positive" image can be recovered or reproduced from film, which is usually made of flexible materials for ease of storage and transportation.
enumeration	Hardcopy.Microfiche	A sheet of microfilm on which many pages of material have been photographed; a magnification system is used to read the material.
enumeration	Hardcopy.Microfilm	Film rolls on which materials are photographed at greatly reduced size; a magnification system is used to read the material.
enumeration	Hardcopy.Photograph	An image (positive or negative) registered on a piece of photo-sensitive paper
enumeration	Hardcopy.PhotographicPlate	A rigid (typically glass) medium that functions like film. Its rigidity is for guarding against image distortion due to medium deformation (caused by heat and humidity). Photographic plates are often used for astronomical photography.
enumeration	Hardcopy.Print	A sheet of any written or printed material which may include notes or graphics. Multiple printed pages may be bound into a manuscript or book.
enumeration	HDF	Hierarchical Data Format
enumeration	HDF4	Hierarchical Data Format, Version 4
enumeration	HDF5	Hierarchical Data Format, Version 5
enumeration	HTML	A text file containing structured information represented in the HyperText Mark-up Language (HTML). See < http://www.w3.org/MarkUp/ >
enumeration	IDFS	Instrument Data File Set (IDFS) is a set of files written in a prescribed format which contain data, timing data, and meta-data. IDFS was developed at Southwest Research Institute (SwRI).
enumeration	IDL	Interactive Data Language (IDL) save set. IDL is a proprietary format.
enumeration	JPEG	A binary format for still images defined by the Joint Photographic Experts Group
enumeration	MATLAB_4	MATLAB Workspace save set, version 4. MAT-files are double-precision, binary, MATLAB format files. MATLAB is a proprietary product of The MathWorks.
enumeration	MATLAB_6	MATLAB Workspace save set, version 6. MAT-files are double-precision, binary, MATLAB format files. MATLAB is a proprietary product of The MathWorks.
enumeration	MATLAB_7	MATLAB Workspace save set, version 7. MAT-files are double-precision, binary, MATLAB format files. Version 7 includes data compression and Unicode encoding. MATLAB is a proprietary product of The MathWorks.
enumeration	MPEG	A digital format for movies defined by the Motion Picture Experts Group

enumeration	NCAR	The National Center for Atmospheric Research (NCAR) format. A complete description of that standard is given in appendix C of the "Report on Establishment & Operation of the Incoherent-Scatter Data Base", dated August 23, 1984, obtainable from NCAR, P.O. Box 3000 Boulder, Colorado 80307-3000.
enumeration	NetCDF	Unidata Program Centers Network Common Data Form (NetCDF). A self-describing portable data format for array-oriented data access. See < http://my.unidata.ucar.edu/content/ >

Diagram	<pre> classDiagram Encoding < -- enumEncoding Encoding < -- Base64 Encoding < -- BZIP2 Encoding < -- GZIP Encoding < -- None Encoding < -- S3_BUCKET Encoding < -- TAR Encoding < -- Unicode Encoding < -- ZIP </pre>	
Type	enumEncoding	
Properties	content: simple	
Facets	enumeration	ASCII A sequence of characters that adheres to American Standard Code for Information Interchange (ASCII) which is an 7-bit character-coding scheme.
	enumeration	Base64 A data encoding scheme whereby binary-encoded data is converted to printable ASCII characters. It is defined as a MIME content transfer encoding for use in Internet e-mail. The only characters used are the upper- and lower-case Roman alphabet characters (A-Z, a-z), the numerals (0-9), and the "+" and "/" symbols, with the "=" symbol as a special suffix (padding) code.
	enumeration	BZIP2 An open standard algorithm by Julian Seward using Burrows-Wheeler block sorting and Huffman coding. See < http://www.bzip.org/ >
	enumeration	GZIP An open standard algorithm distributed by GHU based on LZ77 and Huffman coding. See < http://www.gnu.org/software/gzip/gzip.html > or < http://www.gzip.org/ >
	enumeration	None A lack or absence of anything.
	enumeration	S3_BUCKET A container of objects that comply with the Amazon Simple Storage Service (S3) specifications. A bucket has a unique, user-assigned key (name). A bucket can contain any number of objects with an aggregate size of 5 gigabytes. A bucket may be accompanied by up to 2 kilobytes of metadata.
	enumeration	TAR A file format used to collate collections of files into one larger file, for distribution or archiving, while preserving file system information such as user and group permissions, dates, and directory structures. The format was standardized by POSIX.1-1988 and later POSIX.1-2001.
	enumeration	Unicode Text in multi-byte Unicode format.
	enumeration	ZIP An open standard for compression which is a variation of the LZW method and was originally used in the PKZIP utility.
Used by	Complex Type	AccessInformation
Source	<pre> <xsd:element name="Encoding" type="enumEncoding"> <xsd:annotation> <xsd:documentation xml:lang="en">A set of unambiguous rules that establishes the representation of information within a file.</xsd:documentation> </xsd:annotation> </xsd:element> </pre>	
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd	

Element DataExtent

Namespace	http://www.spase-group.org/data/schema
-----------	---


Diagram	
Type	DataExtent
Properties	content: complex
Used by	Complex Types AccessInformation, Source
Model	Quantity , Units{0,1} , Per{0,1}
Children	Per, Quantity, Units
Instance	<DataExtent> <Quantity>{1,1}</Quantity> <Units>{0,1}</Units> <Per>{0,1}</Per> </DataExtent>
Source	<xsd:element name="DataExtent" type="DataExtent" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Quantity


Namespace	http://www.spase-group.org/data/schema
Annotations	A value that describes a characteristic of a system.
Diagram	
Type	xsd:double
Properties	content: simple
Used by	Complex Type DataExtent
Source	<xsd:element name="Quantity" type="xsd:double"> <xsd:annotation> <xsd:documentation xml:lang="en">A value that describes a characteristic of a system.</xsd:documentation> </xsd:annotation> </xsd:element>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Units

Namespace	http://www.spase-group.org/data/schema
Annotations	A description of the standardized measurement increments in which a value is specified. The description is represented as a mathematical phrase. Units should be represented by widely accepted representation. For example, units should conform to the International System of Units (SI) which is maintained by BIPM (Bureau International des Poids et Mesures (see < http://www.bipm.fr/ >) when appropriate or use tokens like "Re" to represent units of the Radius of the Earth. Within a phrase the circumflex (^) is used to indicate a power, a star (*) is used to indicate multiplication and a slash (/) division. When symbols are not separated by a mathematical operator, multiplication is assumed. Symbols for base units can be found at: < http://www.bipm.fr/en/si/si_brochure/chapter2/2-1/#symbols > and those for common derived units can be found at: < http://www.bipm.fr/en/si/derived_units/2-2-2.html >

Diagram	
Type	xsd:string
Properties	content: simple
Used by	Complex Types AzimuthalAngleRange, DataExtent, Element, EnergyRange, FrequencyRange, Parameter, PolarAngleRange, WavelengthRange
Source	<pre><xsd:element name="Units" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">A description of the standardized measurement increments in which a value is specified. The description is represented as a mathematical phrase. Units should be represented by widely accepted representation. For example, units should conform to the International System of Units (SI) which is maintained by BIPM (Bureau International des Poids et Mesures (see <http://www.bipm.fr/>)) when appropriate or use tokens like "Re" to represent units of the Radius of the Earth. Within a phrase the circumflex (^) is used to indicate a power, a star (*) is used to indicate multiplication and a slash (/) division. When symbols are not separated by a mathematical operator, multiplication is assumed. Symbols for base units can be found at: <http://www.bipm.fr/en/si/si_brochure/chapter2/2-1/> #symbols> and those for common derived units can be found at: <http://www.bipm.fr/en/si/derived_units/2-2-2.html></ <xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Per

Namespace	http://www.spase-group.org/data/schema
Annotations	The time interval over which a characterization applies. For example, the number of bytes generated each day.
Diagram	
Type	xsd:duration
Properties	content: simple
Used by	Complex Type DataExtent
Source	<pre><xsd:element name="Per" type="xsd:duration"> <xsd:annotation> <xsd:documentation xml:lang="en">The time interval over which a characterization applies. For example, the number of bytes generated each day.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ProviderResourceName

Namespace	http://www.spase-group.org/data/schema
Annotations	A short textual description of a resource used by the provider which may be used to identify a resource.
Diagram	
Type	xsd:string
Properties	content: simple
Used by	Complex Types Catalog, DisplayData, NumericalData

Source	<pre><xsd:element name="ProviderResourceName" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">A short textual description of a resource used by the provider which may be used to identify a resource.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ProviderVersion

Namespace	http://www.spase-group.org/data/schema
Annotations	Describes the release or edition of the product used by the provider. The formation rule may vary between providers. It is intended to aid in queries to the provider regarding the product.
Diagram	A UML class diagram showing a class named 'ProviderVersion' with a multiplicity of 0..1. It has a directed association labeled 'xsd:string' pointing to another class represented by a purple rounded rectangle.
Type	xsd:string
Properties	content: simple
Used by	Complex Types Catalog, DisplayData, NumericalData
Source	<pre><xsd:element name="ProviderVersion" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">Describes the release or edition of the product used by the provider. The formation rule may vary between providers. It is intended to aid in queries to the provider regarding the product.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element InstrumentID

Namespace	http://www.spase-group.org/data/schema
Annotations	The identifier of an Instrument resource.
Diagram	A UML class diagram showing a class named 'InstrumentID' with a multiplicity of 0..1. It has a directed association labeled 'xsd:string' pointing to another class represented by a purple rounded rectangle.
Type	xsd:string
Properties	content: simple
Used by	Complex Types Catalog, DisplayData, NumericalData
Source	<pre><xsd:element name="InstrumentID" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The identifier of an Instrument resource.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element PhenomenonType

Namespace	http://www.spase-group.org/data/schema
Annotations	The characteristics or categorization of an event type.
Diagram	A UML class diagram showing a class named 'PhenomenonType' with a multiplicity of 0..1. It has a directed association labeled 'enumPhenomenonType' pointing to another class represented by a purple rounded rectangle. The association has a multiplicity of 0..1 at the target end and a '+' sign at the source end.
Type	enumPhenomenonType
Properties	content: simple
Facets	enumeration ActiveRegion A localized, transient volume of the solar atmosphere in which PLAGEs, SUNSPOTS, FACULAE,

		FLAREs, etc. may be observed.
enumeration	Aurora	An atmospheric phenomenon consisting of bands of light caused by charged solar particles following the earths magnetic lines of force.
enumeration	BowShockCrossing	A crossing of the boundary between the undisturbed (except for foreshock effects) solar wind and the shocked, decelerated solar wind of the magnetosheath.
enumeration	CoronalHole	An extended region of the corona, exceptionally low in density and associated with unipolar photospheric regions. A coronal hole can be an "open" magnetic field in the corona and (perhaps) inner heliosphere which has a faster than average outflow (wind); A region of lower than "quiet" ion and electron density in the corona; or a region of lower peak electron temperature in the corona than in the "quiet" corona.
enumeration	CoronalMassEjection	A solar event (CME) that involves a burst of plasma ejected into the interplanetary medium. CMEs may be observed remotely near the sun or in situ in the interplanetary medium. The latter type of observations are often referred to as Interplanetary CMEs (ICMEs).
enumeration	EITWave	A wave in the corona of the Sun which produce shock waves on the Suns chromosphere (Moreton Waves). EIT Waves are produced by large solar flare and expand outward at about 1,000 km/s. It usually appears as a slowly moving diffuse arc of brightening in H-alpha, and may travel for several hundred thousand km.
enumeration	EnergeticSolarParticleEvent	Enhancement of interplanetary fluxes of energetic ions accelerated by interplanetary shocks and/or solar flares.
enumeration	ForbushDecrease	A rapid decrease in the observed galactic cosmic ray intensity following the passage of an outwardly convecting interplanetary magnetic field disturbance, such as those associated with large CMEs, that sweep some galactic cosmic rays away from Earth.
enumeration	GeomagneticStorm	A magnetospheric disturbance typically defined by variations in the horizontal component of the Earths surface magnetic field. The variation typically starts with a field enhancement associated with a solar wind pressure pulse and continues with a field depression associated with an enhancement of the diamagnetic magnetospheric ring current.
enumeration	InterplanetaryShock	A shock propagating generally anti-sunward through the slower solar wind, often seen in front of CME-associated plasma clouds.
enumeration	MagneticCloud	A transient event observed in the solar wind characterized as a region of enhanced magnetic field strength, smooth rotation of the magnetic


		field vector and low proton density and temperature.
enumeration	MagnetopauseCrossing	A crossing of the interface between the shocked solar wind in the magnetosheath and the magnetic field and plasma in the magnetosphere.
enumeration	RadioBurst	Emissions of the sun in radio wavelengths from centimeters to dekameters, under both quiet and disturbed conditions. Radio Bursts can be "Type I" consisting of many short, narrow-band bursts in the metric range (300 - 50 MHz); "Type II" consisting of narrow-band emission that begins in the meter range (300 MHz) and sweeps slowly (tens of minutes) toward dekameter wavelengths (10 MHz); "Type III" consisting of narrow-band bursts that sweep rapidly (seconds) from decimeter to dekameter wavelengths (500 - 0.5 MHz); and "Type IV" consisting of a smooth continuum of broad-band bursts primarily in the meter range (300 - 30 MHz).
enumeration	SolarFlare	An explosive event in the Sun's atmosphere which produces electromagnetic radiation across the electromagnetic spectrum at multiple wavelengths from long-wave radio to the shortest wavelength gamma rays.
enumeration	SolarWindExtreme	Intervals of unusually large or small values of solar wind attributes such as flow speed and ion density.
enumeration	StreamInteractionRegion	The region (SIR) where two solar wind streams, typically having differing characteristics and solar sources, abut up against (and possibly partially interpenetrate) each other.
enumeration	Substorm	A process by which plasma in the magnetotail becomes energized at a fast rate.
Used by	Complex Types	Annotation, Catalog
Source	<xsd:element name="PhenomenonType" type="enumPhenomenonType"> <xsd:annotation> <xsd:documentation xml:lang="en">The characteristics or categorization of an event type.</xsd:documentation> </xsd:annotation> </xsd:element>	
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd	

Element TimeSpan


Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class TimeSpan { StartDate : xsd:dateTime StopDateEntity { abstract true } Note : xsd:string } TimeSpan "0..oo" --> "0..oo" TimeSpan </pre>
Type	TimeSpan
Properties	content: complex
Used by	Complex Types Annotation, Catalog, TemporalDescription

Model	StartDate , StopDateEntity , Note*
Children	Note, StartDate, StopDateEntity
Instance	<TimeSpan> <StartDate>{1,1}</StartDate> <StopDateEntity>{1,1}</StopDateEntity> <Note>{0,unbounded}</Note> </TimeSpan>
Source	<xsd:element name="TimeSpan" type="TimeSpan" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element StartDate

Namespace	http://www.spase-group.org/data/schema
Annotations	The specification of a starting point in time.
Diagram	
Type	xsd:dateTime
Properties	content: simple
Used by	Complex Types Granule, OperatingSpan, TimeSpan
Source	<xsd:element name="StartDate" type="xsd:dateTime"> <xsd:annotation> <xsd:documentation xml:lang="en">The specification of a starting point in time.</xsd:documentation> </xsd:annotation> </xsd:element>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element StopDateEntity


Namespace	http://www.spase-group.org/data/schema
Diagram	
Properties	abstract: true
Substitution Group	<ul style="list-style-type: none"> RelativeStopDate StopDate
Used by	Complex Type TimeSpan
Source	<xsd:element name="StopDateEntity" abstract="true"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Caveats

Namespace	http://www.spase-group.org/data/schema
Annotations	Information which may be important in the avoidance of the misuse of the resource, for instance instrument maladies, corruption or contamination.
Diagram	
Type	xsd:string
Properties	content: simple

Used by	Complex Types Catalog, DisplayData, Instrument, NumericalData, Parameter
Source	<pre><xsd:element name="Caveats" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">Information which may be important in the avoidance of the misuse of the resource, for instance instrument maladies, corruption or</pre>


Diagram




Type	Parameter
Properties	content: complex
Used by	Complex Types Catalog, DisplayData, NumericalData
Model	Name , Set* , ParameterKey{0,1} , Description{0,1} , Caveats{0,1} , Cadence{0,1} , Units{0,1} , UnitsConversion{0,1} , CoordinateSystem{0,1} , RenderingHints* , Structure{0,1} , ValidMin{0,1} , ValidMax{0,1} , FillValue{0,1} , ParameterEntity
Children	Cadence, Caveats, CoordinateSystem, Description, FillValue, Name, ParameterEntity, ParameterKey, RenderingHints, Set, Structure, Units, UnitsConversion, ValidMax, ValidMin
Instance	<pre> <Parameter> <Name>{1,1}</Name> <Set>{0,unbounded}</Set> <ParameterKey>{0,1}</ParameterKey> <Description>{0,1}</Description> <Caveats>{0,1}</Caveats> <Cadence>{0,1}</Cadence> <Units>{0,1}</Units> <UnitsConversion>{0,1}</UnitsConversion> <CoordinateSystem>{0,1}</CoordinateSystem> <RenderingHints>{0,unbounded}</RenderingHints> <Structure>{0,1}</Structure> <ValidMin>{0,1}</ValidMin> <ValidMax>{0,1}</ValidMax> <FillValue>{0,1}</FillValue> <ParameterEntity>{1,1}</ParameterEntity> </Parameter> </pre>
Source	<xsd:element name="Parameter" type="Parameter"/>

Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd
-----------------	---


Element Set

Namespace	http://www.spase-group.org/data/schema
Annotations	A collection of items for a particular purpose.
Diagram	
Type	xsd:string
Properties	content: simple
Used by	Complex Type Parameter
Source	<pre><xsd:element name="Set" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">A collection of items for a particular purpose.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ParameterKey

Namespace	http://www.spase-group.org/data/schema
Annotations	The name or identifier which can be used to access the parameter in the resource. The associated value is dependent on the service used to access the resource.
Diagram	
Type	xsd:string
Properties	content: simple
Used by	Complex Types Element, Parameter
Source	<pre><xsd:element name="ParameterKey" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The name or identifier which can be used to access the parameter in the resource. The associated value is dependent on the service used to access the resource.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Cadence

Namespace	http://www.spase-group.org/data/schema
Annotations	The time interval between the start of successive measurements.
Diagram	
Type	xsd:duration
Properties	content: simple
Used by	Complex Types Parameter, TemporalDescription
Source	<pre><xsd:element name="Cadence" type="xsd:duration"> <xsd:annotation> <xsd:documentation xml:lang="en">The time interval between the start of successive measurements.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element UnitsConversion

Namespace	http://www.spase-group.org/data/schema
Annotations	<p>The multiplicative factor for converting a unit into International System of Units (SI) units. The factor is expressed in the form "number > x", where "number" is a numerical value and "x" is the appropriate SI units. The basic SI units are Enumerated: m (meter), N (newton), kg (kilogram), Pa (pascal), s (second), Hz (hertz), A (ampere), V (volt), K (kelvin), W (watt), rad (radian), J (joule), sr (steradian), C (coulomb), T (tesla), ohm (ohm), mho (mho or seimens), H (henry), and F (farad). Two useful units which are not SI units are: degree (angle), and unitless (no units). An example is: "1.0E-5>T" which converts the units, presumably nT, to tesla. Another example is: "1.0e+3>m/s" which converts a velocity expressed in kilometers per second to meters per second.</p>
Diagram	<pre> classDiagram class UnitsConversion { <<xsd:string>> } </pre>
Type	xsd:string
Properties	content: simple
Used by	Complex Types Element, Parameter
Source	<pre> <xsd:element name="UnitsConversion" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The multiplicative factor for converting a unit into International System of Units (SI) units. The factor is expressed in the form "number > x", where "number" is a numerical value and "x" is the appropriate SI units. The basic SI units are Enumerated: m (meter), N (newton), kg (kilogram), Pa (pascal), s (second), Hz (hertz), A (ampere), V (volt), K (kelvin), W (watt), rad (radian), J (joule), sr (steradian), C (coulomb), T (tesla), ohm (ohm), mho (mho or seimens), H (henry), and F (farad). Two useful units which are not SI units are: degree (angle), and unitless (no units). An example is: "1.0E-5>T" which converts the units, presumably nT, to tesla. Another example is: "1.0e+3>m/s" which converts a velocity expressed in kilometers per second to meters per second.</xsd:documentation> </xsd:annotation> </xsd:element> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element CoordinateSystem

Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class CoordinateSystem { <<CoordinateSystem>> <<CoordinateRepresentation>> <<CoordinateSystemName>> } </pre>
Type	CoordinateSystem
Properties	content: complex
Used by	Complex Type Parameter
Model	CoordinateRepresentation{0,1} , CoordinateSystemName{0,1}
Children	CoordinateRepresentation, CoordinateSystemName
Instance	<pre> <CoordinateSystem> <CoordinateRepresentation>{0,1}</CoordinateRepresentation> <CoordinateSystemName>{0,1}</CoordinateSystemName> </pre>

	</CoordinateSystem>
Source	<xsd:element name="CoordinateSystem" type="CoordinateSystem"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element CoordinateRepresentation

Namespace	http://www.spase-group.org/data/schema											
Annotations	The method or form for specifying a given point or vector in a given coordinate system.											
Diagram	<pre> classDiagram class CoordinateRepresentation { <<Type enumCoordinateRepresentation>> } class enumCoordinateRepresentation CoordinateRepresentation "1" -- "1" enumCoordinateRepresentation </pre>											
Type	enumCoordinateRepresentation											
Properties	content: simple											
Facets	<table> <tr> <td>enumeration</td> <td>Cartesian</td> <td>A representation in which a position vector or a measured vector (e.g., field or flow) is specified by its components along the base axes of the coordinate system.</td> </tr> <tr> <td>enumeration</td> <td>Cylindrical</td> <td>A coordinate representation of a position vector or measured vector (field or flow) by its k-component, the magnitude of its projection into the i-j plane, and the azimuthal angle of the i-j plane projection.</td> </tr> <tr> <td>enumeration</td> <td>Spherical</td> <td>A coordinate representation of a position vector or of a measured vector by its magnitude and two direction angles. The angles are relative to the base axes of the coordinate system used. Typically the angles are phi [azimuth angle, =arctan (j/i)] and theta, where theta may be a polar angle, arctan {[SQRT(i^2+j^2)]/k}, or an elevation angle, arctan [k/SQRT (i^2+j^2)].</td> </tr> </table>			enumeration	Cartesian	A representation in which a position vector or a measured vector (e.g., field or flow) is specified by its components along the base axes of the coordinate system.	enumeration	Cylindrical	A coordinate representation of a position vector or measured vector (field or flow) by its k-component, the magnitude of its projection into the i-j plane, and the azimuthal angle of the i-j plane projection.	enumeration	Spherical	A coordinate representation of a position vector or of a measured vector by its magnitude and two direction angles. The angles are relative to the base axes of the coordinate system used. Typically the angles are phi [azimuth angle, =arctan (j/i)] and theta, where theta may be a polar angle, arctan {[SQRT(i^2+j^2)]/k}, or an elevation angle, arctan [k/SQRT (i^2+j^2)].
enumeration	Cartesian	A representation in which a position vector or a measured vector (e.g., field or flow) is specified by its components along the base axes of the coordinate system.										
enumeration	Cylindrical	A coordinate representation of a position vector or measured vector (field or flow) by its k-component, the magnitude of its projection into the i-j plane, and the azimuthal angle of the i-j plane projection.										
enumeration	Spherical	A coordinate representation of a position vector or of a measured vector by its magnitude and two direction angles. The angles are relative to the base axes of the coordinate system used. Typically the angles are phi [azimuth angle, =arctan (j/i)] and theta, where theta may be a polar angle, arctan {[SQRT(i^2+j^2)]/k}, or an elevation angle, arctan [k/SQRT (i^2+j^2)].										
Used by	Complex Type	CoordinateSystem										
Source	<pre> <xsd:element name="CoordinateRepresentation" type="enumCoordinateRepresentation"> <xsd:annotation> <xsd:documentation xml:lang="en">The method or form for specifying a given point or vector in a given coordinate system.</xsd:documentation> </xsd:annotation> </xsd:element> </pre>											
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd											

Element CoordinateSystemName

Namespace	http://www.spase-group.org/data/schema								
Annotations	Identifies the coordinate system in which the position, direction or observation has been expressed.								
Diagram	<pre> classDiagram class CoordinateSystemName { <<Type enumCoordinateSystemName>> } class enumCoordinateSystemName CoordinateSystemName "1" -- "1" enumCoordinateSystemName </pre>								
Type	enumCoordinateSystemName								
Properties	content: simple								
Facets	<table> <tr> <td>enumeration</td> <td>Carrington</td> <td>A coordinate system which is centered at the Sun and is "fixed" with respect to the synodic rotation rate; the mean synodic value is about 27.2753 days. The Astronomical Almanac gives a value for Carrington longitude of 349.03 degrees at 0000 UT on 1 January 1995.</td> </tr> <tr> <td>enumeration</td> <td>CGM</td> <td>Corrected Geomagnetic - A coordinate system from a spatial point with GEO radial distance</td> </tr> </table>			enumeration	Carrington	A coordinate system which is centered at the Sun and is "fixed" with respect to the synodic rotation rate; the mean synodic value is about 27.2753 days. The Astronomical Almanac gives a value for Carrington longitude of 349.03 degrees at 0000 UT on 1 January 1995.	enumeration	CGM	Corrected Geomagnetic - A coordinate system from a spatial point with GEO radial distance
enumeration	Carrington	A coordinate system which is centered at the Sun and is "fixed" with respect to the synodic rotation rate; the mean synodic value is about 27.2753 days. The Astronomical Almanac gives a value for Carrington longitude of 349.03 degrees at 0000 UT on 1 January 1995.							
enumeration	CGM	Corrected Geomagnetic - A coordinate system from a spatial point with GEO radial distance							

		<p>and geomagnetic latitude and longitude, follow the epoch-appropriate IGRF/DGRF model field vector through to the point where the field line crosses the geomagnetic dipole equatorial plane. Then trace the dipole magnetic field vector Earthward from that point on the equatorial plane, in the same hemisphere as the original point, until the initial radial distance is reached. Designate the dipole latitude and longitude at that point as the CGM latitude and longitude of the original point. See <http://nssdc.gsfc.nasa.gov/space/cgm/cgmm_des.html></p>
enumeration	DM	<p>Dipole Meridian - A coordinate system centered at the observation point. Z axis is parallel to the Earth's dipole axis, positive northward. X is in the plane defined by Z and the line linking the observation point with the Earth's center. Y is positive eastward. See <http://cdpp.cnes.fr/00428.pdf></p>
enumeration	GEI	<p>Geocentric Equatorial Inertial - A coordinate system where the Z axis is along Earth's spin vector, positive northward. X axis points towards the first point of Aries (from the Earth towards the Sun at the vernal equinox). See Russell, 1971</p>
enumeration	GEO	<p>Geographic - geocentric corotating - A coordinate system where the Z axis is along Earth's spin vector, positive northward. X axis lies in Greenwich meridian, positive towards Greenwich. See Russell, 1971.</p>
enumeration	GSE	<p>Geocentric Solar Ecliptic - A coordinate system where the X axis is from Earth to Sun. Z axis is normal to the ecliptic, positive northward. See Russell, 1971.</p>
enumeration	GSEQ	<p>Geocentric Solar Equatorial - A coordinate system where the X axis is from Earth to Sun. Y axis is parallel to solar equatorial plane. Z axis is positive northward. See Russell, 1971</p>
enumeration	GSM	<p>Geocentric Solar Magnetospheric - A coordinate system where the X axis is from Earth to Sun, Z axis is northward in a plane containing the X axis and the geomagnetic dipole axis. See Russell, 1971</p>
enumeration	HAE	<p>Heliocentric Aries Ecliptic - A coordinate system where the Z axis is normal to the ecliptic plane, positive northward. X axis is positive towards the first point of Aries (from Earth to Sun at vernal equinox). Same as SE below. See Hapgood, 1992.</p>
enumeration	HCC	<p>Heliocentric Cartesian - A 3-D orthonormal coordinate system that is primarily intended to specify with two dimensions a point on the solar disk. The Z axis points toward the observer. The Y axis lies in the plane defined</p>

		<p>by the solar spin vector and the Z axis, positive northward. The X axis is perpendicular to the Y and Z axes, positive toward solar west.</p> <p>Standard representation for this system is via the points x and y values, expressed either as physical distances or as fractions of the solar disk radius.</p>
enumeration	HCI	Heliographic Carrington Inertial.
enumeration	HCR	<p>Heliocentric Radial - A 3-D orthonormal coordinate system that is primarily intended to specify with two dimensions a point on the solar disk.</p> <p>The Z axis points toward the observer. The Y axis lies in the plane defined by the solar spin vector and the Z axis, positive northward.</p> <p>The X axis is perpendicular to the Y and Z axes, positive toward solar west. Standard representation for this system is via the points distance rho from the Z axis [$\rho = \sqrt{x^2 + y^2}$] and its phase angle psi measured counterclockwise from the +Y axis [$\psi = \arctan(-y/x)$]</p>
enumeration	HEE	<p>Heliocentric Earth Ecliptic - A coordinate system where the Z axis is normal to the ecliptic plane, positive northward. X axis points from Sun to Earth. See Hapgood, 1992</p>
enumeration	HEEQ	<p>Heliocentric Earth Equatorial - A coordinate system where the Z axis is normal to the solar equatorial plane, positive northward. X axis is generally Earthward in the plane defined by the Z axis and the Sun-Earth direction. See Hapgood, 1992.</p>
enumeration	HG	<p>Heliographic - A heliocentric rotating coordinate system where the Z axis is normal to the solar equatorial plane, positive northward. X, Y axes rotate with a 25.38 day period. The zero longitude (X axis) is defined as the longitude that passed through the ascending node of the solar equator on the ecliptic plane on 1 January, 1854 at 12 UT. See http://nssdc.gsfc.nasa.gov/space/helios/coor_des.html</p>
enumeration	HGI	<p>Heliographic Inertial - A heliocentric coordinate system where the Z axis is normal to the solar equatorial plane, positive northward. X axis is along the intersection line between solar equatorial and ecliptic planes. The X axis was positive at SE longitude of 74.367 deg on Jan 1, 1900. (See SE below.) See http://nssdc.gsfc.nasa.gov/space/helios/coor_des.html</p>
enumeration	HPC	<p>Helio-projective Cartesian = A 3-D orthonormal (left-handed) coordinate system that is primarily intended to specify with two dimensions a point on the solar disk. The Z axis points from the observer to the center of the solar disk. The Y axis lies in the plane defined by the solar spin vector and the Z axis, positive northward. The X axis is perpendicular to the Y and Z axes, positive toward solar west.</p> <p>Given as the distance between the observer</p>


		and the center of the solar disk, the standard representation of an (x,y) point on the solar disk is via the points longitude angle [arctan (x/d)] and latitude angle [arctan y/d].
enumeration	HPR	<p>Helioprojective Radial - A 3-D orthonormal (left-handed) coordinate system that is primarily intended to specify with two dimensions a point on the solar disk. The Z axis points from the observer to the center of the solar disk. The Y axis lies in the plane defined by the solar spin vector and the Z axis, positive northward. The X axis is perpendicular to the Y and Z axes, positive toward solar west.</p> <p>Given as the distance between the observer and the center of the solar disk, the standard representation for this system of an (x,y) point on the solar disk is via the points latitude angle theta (= arctan [SQRT(x**2 + y**2)/d]) or equivalent declination parameter delta (= theta - 90 deg), and its phase angle psi as measured counter-clockwise from the +Y axis [psi = arctan (-y/x)].</p>
enumeration	J2000	An astronomical coordinate system which uses the mean equator and equinox of Julian date 2451545.0 TT (Terrestrial Time), or January 1, 2000, noon TT. (aka J2000) to define a celestial reference frame.
enumeration	LGM	<p>Local Geomagnetic - A coordinate system used mainly for Earth surface or near Earth surface magnetic field data. X axis northward from observation point in a geographic meridian. Z axis downward towards Earth's center. In this system, H (total horizontal component) = SQRT (Bx^2 + By^2) and D (declination angle) = arctan (By/Bx)</p>
enumeration	MAG	<p>Geomagnetic - geocentric. Z axis is parallel to the geomagnetic dipole axis, positive north.</p> <p>X is in the plane defined by the Z axis and the Earth's rotation axis. If N is a unit vector from the Earth's center to the north geographic pole, the signs of the X and Y axes are given by Y = N x Z, X = Y x Z.. See Russell, 1971, and <http://cdpp.cnes.fr/00428.pdf></p>
enumeration	MFA	<p>Magnetic Field Aligned - A coordinate system spacecraft-centered system with Z in the direction of the ambient magnetic field vector. X is in the plane defined by Z and the spacecraft-Sun line, positive sunward. See <http://cdpp.cnes.fr/00428.pdf></p>
enumeration	RTN	Radial Tangential Normal. Typically centered at a spacecraft. Used for IMF and plasma V vectors. R (radial) axis is radially away from the Sun, T (tangential) axis is normal to the plane formed by R and the Sun's spin vector, positive in the direction of planetary motion. N (normal) is R x T.
enumeration	SC	<p>Spacecraft - A coordinate system defined by the spacecraft geometry and/or spin. Often has Z axis parallel to spacecraft spin vector.</p> <p>X and Y axes may or may not corotate with the spacecraft. See SR and SR2 below.</p>

	enumeration	SE	Solar Ecliptic - A heliocentric coordinate system where the Z axis is normal to the ecliptic plane, positive northward. X axis is positive towards the first point of Aries (from Earth to Sun at vernal equinox). Same as HAE above. See < http://nssdc.gsfc.nasa.gov/space/helios/coor_des.html >
	enumeration	SM	Solar Magnetic - A geocentric coordinate system where the Z axis is northward along Earth's dipole axis, X axis is in plane of z axis and Earth-Sun line, positive sunward. See Russell, 1971.
	enumeration	SpacecraftOrbitPlane	A coordinate system where X lies in the plane normal to and in the direction of motion of the spacecraft, Z is normal to this plane and Y completes the triad in a right-handed coordinate system.
	enumeration	SR	Spin Reference - A special case of a Spacecraft (SC) coordinate system for a spinning spacecraft. Z is parallel to the spacecraft spin vector. X and Y rotate with the spacecraft. See < http://cdpp.cnes.fr/00428.pdf >
	enumeration	SR2	Spin Reference 2 - A special case of a Spacecraft (SC) coordinate system for a spinning spacecraft. Z is parallel to the spacecraft spin vector. X is in the plane defined by Z and the spacecraft-Sun line, positive sunward. See < http://cdpp.cnes.fr/00428.pdf >
	enumeration	SSE	Spacecraft Solar Ecliptic - A coordinate system used for deep space spacecraft, for example Helios. - X axis from spacecraft to Sun. Z axis normal to ecliptic plane, positive northward. Note: Angle between normals to ecliptic and to Helios orbit plane ~ 0.25 deg.
	enumeration	SSE_L	Selenocentric Solar Ecliptic. The X axis points from the center of the Earth's moon to the sun, the Z axis is normal to the ecliptic plane, positive northward. And the Y axis completes the right-handed set of axes.
	enumeration	WGS84	The World Geodetic System (WGS) defines a reference frame for the earth, for use in geodesy and navigation. The WGS84 uses the zero meridian as defined by the Bureau International de l'Heure.
Used by	Complex Types	CoordinateSystem, Location	
Source	<xsd:element name="CoordinateSystemName" type="enumCoordinateSystemName"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifies the coordinate system in which the position, direction or observation has been expressed.</xsd:documentation> </xsd:annotation> </xsd:element>		
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd		

Element RenderingHints

Namespace	http://www.spase-group.org/data/schema
-----------	---

Diagram



Type	RenderingHints
Properties	content: complex
Used by	Complex Type Parameter
Model	DisplayType{0,1} , AxisLabel{0,1} , RenderingAxis{0,1} , Index{0,1} , ValueFormat{0,1} , ScaleMin{0,1} , ScaleMax{0,1} , ScaleType{0,1}
Children	AxisLabel, DisplayType, Index, RenderingAxis, ScaleMax, ScaleMin, ScaleType, ValueFormat
Instance	<RenderingHints> <DisplayType>{0,1}</DisplayType> <AxisLabel>{0,1}</AxisLabel> <RenderingAxis>{0,1}</RenderingAxis> <Index>{0,1}</Index> <ValueFormat>{0,1}</ValueFormat> <ScaleMin>{0,1}</ScaleMin> <ScaleMax>{0,1}</ScaleMax> <ScaleType>{0,1}</ScaleType> </RenderingHints>
Source	<xsd:element name="RenderingHints" type="RenderingHints"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element DisplayType

Namespace	http://www.spase-group.org/data/schema											
Annotations	The general styling or type of plot that is suitable for the variable.											
Diagram												
Type	enumDisplayType											
Properties	content: simple											
Facets	<table border="1"> <tr> <td>enumeration</td> <td>Image</td> <td>A two-dimensional representation of data with values at each element of the array related to an intensity or a color.</td> </tr> <tr> <td>enumeration</td> <td>Plasmagram</td> <td>The characterization of signal strengths in active sounding measurements as a function of virtual range or signal delay time and sounding frequency. A Plasmagram is also referred to as an Ionogram.</td> </tr> <tr> <td>enumeration</td> <td>Spectrogram</td> <td>The characterization of signal strengths as a function of frequency (or energy) and time.</td> </tr> </table>			enumeration	Image	A two-dimensional representation of data with values at each element of the array related to an intensity or a color.	enumeration	Plasmagram	The characterization of signal strengths in active sounding measurements as a function of virtual range or signal delay time and sounding frequency. A Plasmagram is also referred to as an Ionogram.	enumeration	Spectrogram	The characterization of signal strengths as a function of frequency (or energy) and time.
enumeration	Image	A two-dimensional representation of data with values at each element of the array related to an intensity or a color.										
enumeration	Plasmagram	The characterization of signal strengths in active sounding measurements as a function of virtual range or signal delay time and sounding frequency. A Plasmagram is also referred to as an Ionogram.										
enumeration	Spectrogram	The characterization of signal strengths as a function of frequency (or energy) and time.										

	enumeration	StackPlot	A representation of data showing multiple sets of observations on a single plot, possibly offsetting each plot by some uniform amount.
	enumeration	TimeSeries	A representation of data showing a set of observations taken at different points in time and charted as a time series.
	enumeration	WaveForm	Spatial or temporal variations of wave amplitude over wave-period timescales.
Used by	Complex Type	RenderingHints	
Source		<xsd:element name="DisplayType" type="enumDisplayType"> <xsd:annotation> <xsd:documentation xml:lang="en">The general styling or type of plot that is suitable for the variable.</xsd:documentation> </xsd:annotation> </xsd:element>	
Schema location		file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd	

Element AxisLabel


Namespace	http://www.spase-group.org/data/schema		
Annotations	A short character string (approximately 10 characters, but preferably 6 characters - more only if absolutely required for clarity) which can be used to label a y-axis for a plot or to provide a heading for a data listing.		
Diagram	<pre> classDiagram class AxisLabel { <<xsd:string>> } AxisLabel "1" -- "0..1" xsd:string </pre>		
Type	xsd:string		
Properties	content: simple		
Used by	Complex Type	RenderingHints	
Source	<xsd:element name="AxisLabel" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">A short character string (approximately 10 characters, but preferably 6 characters - more only if absolutely required for clarity) which can be used to label a y-axis for a plot or to provide a heading for a data listing.</xsd:documentation> </xsd:annotation> </xsd:element>		
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd		

Element RenderingAxis


Namespace	http://www.spase-group.org/data/schema		
Annotations	A reference component of a plot or rendering of data. A plot typically is a 2-dimensional rendering with a horizontal and vertical axis. A third dimension can be introduced with a color coding of the rendered data.		
Diagram	<pre> classDiagram class RenderingAxis { <<enumRenderingAxis>> } RenderingAxis "1" -- "1" enumRenderingAxis </pre>		
Type	enumRenderingAxis		
Properties	content: simple		
Facets	enumeration	ColorBar	A spectrum or set of colors used to represent data values.
	enumeration	Horizontal	Parallel to or in the plane of the horizon or a base line.
	enumeration	Vertical	Perpendicular to the plane of the horizon or a base line.
Used by	Complex Type	RenderingHints	
Source	<xsd:element name="RenderingAxis" type="enumRenderingAxis">		

	<pre> <xsd:annotation> <xsd:documentation xml:lang="en">A reference component of a plot or rendering of data. A plot typically is a 2-dimensional rendering with a horizontal and vertical axis. A third dimension can be introduced with a color coding of the rendered data.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Index

Namespace	http://www.spase-group.org/data/schema
Annotations	The location of an item in an array or vector. An index can be multivalued to represent the location in a multidimensional object. The index of the first item is "1". A value of "0" is a wild card for all elements at the location in an array. A value of "-1" is a reference to the dimension at the location in the array. A "-1" is used when describing the attributes of the dimension, where as "0" or a positive integer is used to describe attributes of individual elements.
Diagram	
Type	typeSequence
Properties	content: simple
Used by	Complex Types Element, RenderingHints
Source	<pre> <xsd:element name="Index" type="typeSequence"> <xsd:annotation> <xsd:documentation xml:lang="en">The location of an item in an array or vector. An index can be multivalued to represent the location in a multidimensional object. The index of the first item is "1". A value of "0" is a wild card for all elements at the location in an array. A value of "-1" is a reference to the dimension at the location in the array. A "-1" is used when describing the attributes of the dimension, where as "0" or a positive integer is used to describe attributes of individual elements.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ValueFormat

Namespace	http://www.spase-group.org/data/schema
Annotations	A string defining the output format used when extracting data values out to a file or screen. The magnitude and the number of significant figures needed should be carefully considered. The output format string can be in either Fortran or C syntax.
Diagram	
Type	xsd:string
Properties	content: simple
Used by	Complex Type RenderingHints
Source	<pre> <xsd:element name="ValueFormat" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">A string defining the output format used when extracting data values out to file or screen. The magnitude and the number of significant figures needed should be carefully considered. The output format string can be in either Fortran or C syntax.</xsd:documentation> </xsd:annotation> </xsd:element></pre>

	</xsd:element>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ScaleMin

Namespace	http://www.spase-group.org/data/schema
Annotations	The minimum value that the variable is expected to attain. Used, for example, by automated plotting software.
Diagram	
Type	xsd:double
Properties	content: simple
Used by	Complex Type RenderingHints
Source	<pre><xsd:element name="ScaleMin" type="xsd:double"> <xsd:annotation> <xsd:documentation xml:lang="en">The minimum value that the variable is expected to attain. Used, for example, by automated plotting software.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ScaleMax

Namespace	http://www.spase-group.org/data/schema
Annotations	The maximum value that the variable is expected to attain. Used, for example, by automated plotting software.
Diagram	
Type	xsd:double
Properties	content: simple
Used by	Complex Type RenderingHints
Source	<pre><xsd:element name="ScaleMax" type="xsd:double"> <xsd:annotation> <xsd:documentation xml:lang="en">The maximum value that the variable is expected to attain. Used, for example, by automated plotting software.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ScaleType

Namespace	http://www.spase-group.org/data/schema						
Annotations	The scaling to apply to an axis. If this attribute is not present, linear scale should be assumed.						
Diagram							
Type	enumScaleType						
Properties	content: simple						
Facets	<table> <tr> <td>enumeration</td> <td>LinearScale</td> <td>Intervals which are equally spaced.</td> </tr> <tr> <td>enumeration</td> <td>LogScale</td> <td>Intervals which are spaced proportionally to the logarithms of the values being represented.</td> </tr> </table>	enumeration	LinearScale	Intervals which are equally spaced.	enumeration	LogScale	Intervals which are spaced proportionally to the logarithms of the values being represented.
enumeration	LinearScale	Intervals which are equally spaced.					
enumeration	LogScale	Intervals which are spaced proportionally to the logarithms of the values being represented.					
Used by	Complex Type RenderingHints						
Source	<pre><xsd:element name="ScaleType" type="enumScaleType"> <xsd:annotation> <xsd:documentation xml:lang="en">The scaling to apply to an axis. If this attribute is not present, linear scale should be assumed.</xsd:documentation></pre>						

	</xsd:annotation> </xsd:element>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Structure


Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class Structure { Size Description Element * } class Structure { <> } Structure < -- Structure Size < -- typeSequence Description < -- xsd:string Element < -- Element </pre>
Type	Structure
Properties	content: complex
Used by	Complex Type Parameter
Model	Size{0,1} , Description{0,1} , Element*
Children	Description, Element, Size
Instance	<Structure> <Size>{0,1}</Size> <Description>{0,1}</Description> <Element>{0,unbounded}</Element> </Structure>
Source	<xsd:element name="Structure" type="Structure"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Size


Namespace	http://www.spase-group.org/data/schema
Annotations	<p>The number of elements in each dimension of a multi-dimensional array. A scalar has a size of 1. A multi-dimensional vector will have a size for each dimension. Note that the number of elements in the size of an N-dimensional array conveys the arrays dimensionality while the product of those numbers conveys the total number of elements in the array. When size is used to describe a tensor it is the number of elements in the tensor. As such it has a limited set of values. A tensor of rank 1 has a size of 3, rank 2 a size of 9, rank 3 a size of 27 and rank n a size of 3^n.</p>
Diagram	<pre> classDiagram class Size { <> } class typeSequence { <> } Size --o typeSequence </pre>
Type	typeSequence
Properties	content: simple
Used by	Complex Type Structure
Source	<xsd:element name="Size" type="typeSequence"> <xsd:annotation> <xsd:documentation xml:lang="en">The number of elements in each dimension of a multi-dimensional array. A scalar has a size of 1. A multi-dimensional vector will have a size for each dimension. Note that the number of elements in the size of an N-dimensional array conveys the arrays dimensionality while the product of those numbers conveys the total number of elements in the array. When size is used to describe a tensor it is the number of elements in the tensor. As such it has a limited set of values. A tensor of rank 1 has a size of 3, rank 2 a size of 9, rank 3 a size of 27 and rank n a size of 3^n .</xsd:documentation> </xsd:annotation> </xsd:element>

	</xsd:annotation> </xsd:element>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Element

Namespace	http://www.spase-group.org/data/schema
Diagram	
Type	Element
Properties	content: complex
Used by	Complex Type Structure
Model	Name , Qualifier* , Index , ParameterKey{0,1} , Units{0,1} , UnitsConversion{0,1} , ValidMin{0,1} , ValidMax{0,1} , FillValue{0,1}
Children	FillValue, Index, Name, ParameterKey, Qualifier, Units, UnitsConversion, ValidMax, ValidMin
Instance	<pre> <Element> <Name>{1,1}</Name> <Qualifier>{0,unbounded}</Qualifier> <Index>{1,1}</Index> <ParameterKey>{0,1}</ParameterKey> <Units>{0,1}</Units> <UnitsConversion>{0,1}</UnitsConversion> <ValidMin>{0,1}</ValidMin> <ValidMax>{0,1}</ValidMax> <FillValue>{0,1}</FillValue> </Element> </pre>
Source	<xsd:element name="Element" type="Element" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Qualifier

Namespace	http://www.spase-group.org/data/schema						
Annotations	Characterizes the refinement to apply to a type or attribute of a quantity.						
Diagram							
Type	enumQualifier						
Properties	content: simple						
Facets	<table border="1"> <tr> <td>enumeration</td> <td>Anisotropy</td> <td>Direction-dependent property.</td> </tr> <tr> <td>enumeration</td> <td>Array</td> <td>A sequence of values corresponding to the</td> </tr> </table>	enumeration	Anisotropy	Direction-dependent property.	enumeration	Array	A sequence of values corresponding to the
enumeration	Anisotropy	Direction-dependent property.					
enumeration	Array	A sequence of values corresponding to the					

		elements in a rectilinear, n-dimension matrix. Each value can be referenced by a unique index.
enumeration	Average	The statistical mean; the sum of a set of values divided by the number of values in the set.
enumeration	Characteristic	A quantity which can be easily identified and measured in a given environment.
enumeration	Circular	Relative to polarization, right-hand circularly polarized light is defined such that the electric field is rotating clockwise as seen by an observer towards whom the wave is moving. Left-hand circularly polarized light is defined such that the electric field is rotating counterclockwise as seen by an observer towards whom the wave is moving. The polarization of magnetohydrodynamic waves is specified with respect to the ambient mean magnetic field : right-hand polarized waves have a transverse electric field component which turns in a right-handed sense (that of the gyrating electrons) around the magnetic field.
enumeration	Column	A two-dimensional measure of a quantity. The column is the area over which the quantity is measured.
enumeration	Component	Projection of a vector along one of the base axes of a coordinate system.
enumeration	Component.I	Projection of a vector along the first named axis of a coordinate system. Typically the X axis, but could be the R axis for an RTN coordinate system.
enumeration	Component.J	Projection of a vector along the second named axis of a coordinate system. Typically the Y axis, but could be the T axis for an RTN coordinate system.
enumeration	Component.K	Projection of a vector along the third named axis of a coordinate system. Typically the Z axis, but could be the N axis for an RTN coordinate system.
enumeration	CrossSpectrum	The Fourier transform of the cross correlation of two physical or empirical observations.
enumeration	Deviation	The difference between an observed value and the expected value of a quantity.
enumeration	Differential	A measurement within a narrow range of energy and/or solid angle.
enumeration	Direction	The spatial relation between an object and another object, the orientation of the object or the course along which the object points or moves.
enumeration	DirectionAngle	The angle between a position vector or measured vector (or one of its projections onto a plane) and one of the base axes of the coordinate system.
enumeration	DirectionAngle.AzimuthAngle	The angle between the projection into the i-j plane of a position or measured vector and the i-axis of the coordinate system. Mathematically defined as $\arctan(j/i)$.
enumeration	DirectionAngle.ElevationAngle	The angle between the position or measured vector and the i-j plane of the coordinate

		system. Mathematically defined as $\arctan(k / \sqrt{i^2 + j^2})$.
enumeration	DirectionAngle.PolarAngle	The angle between the position or measured vector and the k-axis of the coordinate system. Mathematically defined as $\arctan([\sqrt{i^2 + j^2}] / k)$.
enumeration	Directional	A measurement within a narrow range of solid angle.
enumeration	FieldAligned	The component of a quantity which is oriented in the same direction of a field.
enumeration	Fit	Values that make a model agree with the data.
enumeration	Group	An assemblage of values that a certain relation or common characteristic.
enumeration	Integral	A flux measurement in a broad range of energy and solid angle.
enumeration	Integral.Area	Integration over the extent of a planar region, or of the surface of a solid.
enumeration	Integral.Bandwidth	Integration over the width a frequency band.
enumeration	Integral.SolidAngle	Integration over the angle in three-dimensional space that an object subtends at a point.
enumeration	LineOfSight	The line of sight is the line that connects the observer with the observed object. This expression is often used with measurements of Doppler velocity and magnetic field in magnetograms, where only the component of the vector field directed along the line of sight is measured.
enumeration	Linear	Polarization where the E-field vector is confined to a given plane
enumeration	Magnitude	A measure of the strength of a vector quantity or length of its representational vector.
enumeration	Maximum	The largest value of a batch or sample or the upper bound of a probability distribution.
enumeration	Median	The measure of central tendency of a set of n. values computed by ordering the values and taking the value at position (n. + 1) / 2 when n. is odd or the arithmetic mean of the values at positions n. / 2 and (n. / 2) + 1 when n. is even.
enumeration	Minimum	The smallest value of a batch or sample or the lower bound of a probability distribution.
enumeration	Moment	Parameters determined by integration over a distribution function convolved with a power of velocity.
enumeration	Parallel	Having the same direction as a given direction
enumeration	Peak	The maximum value for the quantity in question, over a period of time which is usually equal to the cadence.
enumeration	Perpendicular	At right angles to a given direction.
enumeration	Perturbation	Variations in the state of a system.
enumeration	Phase	A point or portion in a recurring series of changes.
enumeration	PhaseAngle	Phase difference between two or more waves, normally expressed in degrees.
enumeration	Projection	A measure of the length of a position or measured

		vector as projected into a plane of the coordinate system.
enumeration	Projection.IJ	A measure of the length of a position or measured vector projected into the i-j (typically X-Y) plane of the coordinate system.
enumeration	Projection.IK	A measure of the length of a position or measured vector projected into the i-k (typically X-Z) plane of the coordinate system.
enumeration	Projection.JK	A measure of the length of a position or measured vector projected into the j-k (typically Y-Z) plane of the coordinate system.
enumeration	Pseudo	Similar to or having the appearance of something else. Can be used to indicate an estimation or approximation of a particular quantity.
enumeration	Ratio	The relative magnitudes of two quantities.
enumeration	Scalar	A quantity that is completely specified by its magnitude and has no direction.
enumeration	Spectral	Characterized as a range or continuum of frequencies
enumeration	StandardDeviation	The square root of the average of the squares of deviations about the mean of a set of data. Standard deviation is a statistical measure of spread or variability.
enumeration	StokesParameters	A set of four parameters (usually called I,Q,U and V) which describe the polarization state of an electromagnetic wave propagating through space.
enumeration	Symmetric	Equal distribution about one or more axes.
enumeration	Tensor	A generalized linear "quantity" or "geometrical entity" that can be expressed as a multi-dimensional array relative to a choice of basis of the particular space on which it is defined.
enumeration	Total	The summation of quantities over all possible species.
enumeration	Trace	The sum of the elements on the main diagonal (the diagonal from the upper left to the lower right) of a square matrix.
enumeration	Uncertainty	A statistically defined discrepancy between a measured quantity and the true value of that quantity that cannot be corrected by calculation or calibration.
enumeration	Variance	A measure of dispersion of a set of data points around their mean value. The expectation value of the squared deviations from the mean.
enumeration	Vector	A set of parameter values each along some independent variable (e.g., components of a field in three orthogonal spatial directions; atmospheric temperature values at several altitudes, or at a given latitude and longitude;).
Used by	Complex Types	Element, Field, Mixed, Particle, Support, Wave
Source	<xsd:element name="Qualifier" type="enumQualifier">	

	<pre> <xsd:annotation> <xsd:documentation xml:lang="en">Characterizes the refinement to apply to a type or attribute of a quantity.</xsd:documentation> </xsd:annotation> </xsd:element> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element validMin

Namespace	http://www.spase-group.org/data/schema
Annotations	The smallest legitimate value.
Diagram	<pre> classDiagram class ValidMin { <<xsd:string>> } ValidMin "1" -- "0..1"xsd:string </pre>
Type	xsd:string
Properties	content: simple
Used by	Complex Types Element, Parameter
Source	<pre> <xsd:element name="ValidMin" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The smallest legitimate value.</xsd:documentation> </xsd:annotation> </xsd:element> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element validMax

Namespace	http://www.spase-group.org/data/schema
Annotations	The largest legitimate value.
Diagram	<pre> classDiagram class ValidMax { <<xsd:string>> } ValidMax "1" -- "0..1"xsd:string </pre>
Type	xsd:string
Properties	content: simple
Used by	Complex Types Element, Parameter
Source	<pre> <xsd:element name="ValidMax" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The largest legitimate value.</xsd:documentation> </xsd:annotation> </xsd:element> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd


Element FillValue

Namespace	http://www.spase-group.org/data/schema
Annotations	A value that indicates that a quantity is undefined.
Diagram	<pre> classDiagram class FillValue { <<xsd:string>> } FillValue "1" -- "0..1"xsd:string </pre>
Type	xsd:string
Properties	content: simple
Used by	Complex Types Element, Parameter
Source	<pre> <xsd:element name="FillValue" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">A value that indicates that a quantity is undefined.</xsd:documentation> </xsd:annotation> </xsd:element> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ParameterEntity

Namespace	http://www.spase-group.org/data/schema
-----------	--

Diagram



Properties

abstract: true

Substitution Group

- Field
- Particle
- Wave
- Mixed
- Support

Used by

Complex Type Parameter

Source

<xsd:element name="ParameterEntity" abstract="true"/>

Schema location

file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Extension


Namespace

http://www.spase-group.org/data/schema

Annotations

A container of other metadata which is not part of the SPASE data model. The contents of this element are defined by individual usage. The organization and content are constrained by the implementation. For example, in an XML representation of the SPASE metadata the content must conform to the XML specifications.

Diagram



Properties

content: complex

Substitution Group Affiliation

- ResourceEntity

Used by

Complex Types Annotation, Catalog, DisplayData, Instrument, NumericalData, Observatory, Person, Registry, Repository, Service

Model

ANY element from ANY namespace OTHER than 'http://www.spase-group.org/data/schema'

Source

```

<xsd:element name="Extension" substitutionGroup="ResourceEntity">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A container of other metadata which is not part of the SPASE data model. The contents of this element are defined by individual usage. The organization and content are constrained by the implementation. For example, in an XML representation of the SPASE metadata the content must conform to the XML specifications.</xsd:documentation>
  </xsd:annotation>
  <xsd:complexType>
    <xsd:sequence>
      <xsd:any namespace="##other" processContents="lax" minOccurs="0" maxOccurs="unbounded" />
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
  
```

	</xsd:complexType> </xsd:element>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Field


Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class Field { <<Field<> <<Field<> } class Qualifier { <<Qualifier<> Type enumQualifier } class FieldQuantity { <<FieldQuantity<> Type enumFieldQuantity } class FrequencyRange { <<FrequencyRange<> Type FrequencyRange } class ParameterEntity { <<ParameterEntity<> Abstract true } Field "0..oo" --> "Field" Field --> Qualifier Field --> SubstitutionGroup Qualifier --> FieldQuantity Qualifier --> FrequencyRange SubstitutionGroup --> ParameterEntity </pre>
Type	Field
Properties	content: complex
Substitution Group Affiliation	<ul style="list-style-type: none"> ParameterEntity
Model	Qualifier*, FieldQuantity, FrequencyRange{0,1}
Children	FieldQuantity, FrequencyRange, Qualifier
Instance	<pre> <Field> <Qualifier>{0,unbounded}</Qualifier> <FieldQuantity>{1,1}</FieldQuantity> <FrequencyRange>{0,1}</FrequencyRange> </Field> </pre>
Source	<xsd:element name="Field" type="Field" substitutionGroup="ParameterEntity" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element FieldQuantity


Namespace	http://www.spase-group.org/data/schema												
Annotations	The physical attribute of the field.												
Diagram	<pre> classDiagram class FieldQuantity { <<FieldQuantity<> Type enumFieldQuantity } class enumFieldQuantity { <<enumFieldQuantity<> } FieldQuantity --> enumFieldQuantity </pre>												
Type	enumFieldQuantity												
Properties	content: simple												
Facets	<table border="1"> <tr> <td>enumeration</td> <td>Current</td> <td>The flow of electrons through a conductor caused by a potential difference.</td> </tr> <tr> <td>enumeration</td> <td>Electric</td> <td>The physical attribute that exerts an electrical force.</td> </tr> <tr> <td>enumeration</td> <td>Electromagnetic</td> <td>Electric and magnetic field variations in time and space that propagate through a medium or a vacuum with the waves propagation, electric field, and magnetic field vectors forming an orthogonal triad. Waves in this category are detected by having their field quantities measured.</td> </tr> <tr> <td>enumeration</td> <td>Gyrofrequency</td> <td>The number of gyrations around a magnetic guiding center (field line) a charged particle makes per unit time due to the Lorentz force.</td> </tr> </table>	enumeration	Current	The flow of electrons through a conductor caused by a potential difference.	enumeration	Electric	The physical attribute that exerts an electrical force.	enumeration	Electromagnetic	Electric and magnetic field variations in time and space that propagate through a medium or a vacuum with the waves propagation, electric field, and magnetic field vectors forming an orthogonal triad. Waves in this category are detected by having their field quantities measured.	enumeration	Gyrofrequency	The number of gyrations around a magnetic guiding center (field line) a charged particle makes per unit time due to the Lorentz force.
enumeration	Current	The flow of electrons through a conductor caused by a potential difference.											
enumeration	Electric	The physical attribute that exerts an electrical force.											
enumeration	Electromagnetic	Electric and magnetic field variations in time and space that propagate through a medium or a vacuum with the waves propagation, electric field, and magnetic field vectors forming an orthogonal triad. Waves in this category are detected by having their field quantities measured.											
enumeration	Gyrofrequency	The number of gyrations around a magnetic guiding center (field line) a charged particle makes per unit time due to the Lorentz force.											

	enumeration	Magnetic	The physical attribute attributed to a magnet or its equivalent.
	enumeration	PlasmaFrequency	A number-density-dependent characteristic frequency of a plasma.
	enumeration	Potential	A field which obeys Laplaces Equation.
	enumeration	PoyntingFlux	Electromagnetic energy flux transported by a wave characterized as the rate of energy transport per unit area per steradian.
Used by	Complex Type Field		
Source	<xsd:element name="FieldQuantity" type="enumFieldQuantity"> <xsd:annotation> <xsd:documentation xml:lang="en">The physical attribute of the field.</xsd:documentation> </xsd:annotation> </xsd:element>		
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd		

Element FrequencyRange

Namespace	http://www.spase-group.org/data/schema
Diagram	
Type	FrequencyRange
Properties	content: complex
Used by	Complex Types Field, Wave
Model	SpectralRange{0,1} , Low , High , Units , Bin*
Children	Bin, High, Low, SpectralRange, Units
Instance	<FrequencyRange> <SpectralRange>{0,1}</SpectralRange> <Low>{1,1}</Low> <High>{1,1}</High> <Units>{1,1}</Units> <Bin>{0,unbounded}</Bin> </FrequencyRange>
Source	<xsd:element name="FrequencyRange" type="FrequencyRange" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element SpectralRange

Namespace	http://www.spase-group.org/data/schema
Annotations	The general term used to describe wavelengths or frequencies within a given span of values for those quantities.
Diagram	
Type	enumSpectralRange
Properties	content: simple

Facets	enumeration	CaK	A spectrum with a wavelength of range centered near 393.5 nm. VSO nickname: Ca-K image with range of 391.9 nm to 395.2 nm.
	enumeration	ExtremeUltraviolet	A spectrum with a wavelength range of 10.0 nm to 125.0nm. VSO nickname: EUV image with a range of 10.0 nm to 125.0 nm
	enumeration	FarUltraviolet	A spectrum with a wavelength range of 122 nm to 200.0nm. VSO nickname: FUV image with a range of 122.0 nm to 200 nm
	enumeration	GammaRays	Photons with a wavelength range: 0.00001 to 0.001 nm
	enumeration	Halpha	A spectrum with a wavelength range centered at 656.3 nm. VSO nickname: H-alpha image with a spectrum range of 655.8 nm to 656.8 nm.
	enumeration	HardXrays	Photons with a wavelength range: 0.001 to 0.1 nm and an energy range of 12 keV to 120 keV
	enumeration	He10830	A spectrum with a wavelength range centered at 1082.9 nm. VSO nickname: He 10830 image with a range of 1082.5 nm to 1083.3 nm.
	enumeration	He304	A spectrum centered around the resonance line of ionised helium at 304 Angstrom (30.4 nm).
	enumeration	Infrared	Photons with a wavelength range: 760 to 1.00x10^6 nm
	enumeration	K7699	A spectrum with a wavelength range centred at 769.9 nm. VSO nickname: K-7699 dopplergram with a range of 769.8 nm to 770.0 nm.
	enumeration	LBHBand	Lyman-Birge-Hopfield band in the far ultraviolet range with wavelength range of 140nm to 170 nm.
	enumeration	Microwave	Photons with a wavelength range: 1.00x10^6 to 1.50x10^7 nm
	enumeration	NaD	A spectrum with a wavelength range of centered at 589.3 nm. VSO nickname: Na-D image with a range of 588.8 nm to 589.8 nm.
	enumeration	Ni6768	A spectrum with a wavelength range centered at 676.8 nm. VSO nickname: Ni-6768 dopplergram with a range of 676.7 nm to 676.9 nm.
	enumeration	Optical	Photons with a wavelength range: 380 to 760 nm
Used by	enumeration	RadioFrequency	Photons with a wavelength range: 100,000 to 1.00x10^11 nm
	enumeration	SoftXRays	X-Rays with an energy range of 0.12 keV to 12 keV.
	enumeration	Ultraviolet	Photons with a wavelength range: 10 to 400 nm.
	enumeration	WhiteLight	Photons with a wavelength in the visible range for humans.
	enumeration	XRays	Photons with a wavelength range: 0.001 <= x < 10 nm
Source	<xsd:element name="SpectralRange" type="enumSpectralRange"> <xsd:annotation> <xsd:documentation xml:lang="en">The general term used to describe wavelengths or frequencies within a given span of values for those quantities.</xsd:documentation> </xsd:annotation> </xsd:element>		
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd		


Element Low

Namespace	http://www.spase-group.org/data/schema
Annotations	The smallest value within a range of possible values.
Diagram	
Type	xsd:double
Properties	content: simple
Used by	Complex Types AzimuthalAngleRange, Bin, EnergyRange, FrequencyRange, PolarAngleRange, WavelengthRange
Source	<pre><xsd:element name="Low" type="xsd:double"> <xsd:annotation> <xsd:documentation xml:lang="en">The smallest value within a range of possible values.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element High

Namespace	http://www.spase-group.org/data/schema
Annotations	The largest value within a range of possible values.
Diagram	
Type	xsd:double
Properties	content: simple
Used by	Complex Types AzimuthalAngleRange, Bin, EnergyRange, FrequencyRange, PolarAngleRange, WavelengthRange
Source	<pre><xsd:element name="High" type="xsd:double"> <xsd:annotation> <xsd:documentation xml:lang="en">The largest value within a range of possible values.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Bin

Namespace	http://www.spase-group.org/data/schema
Diagram	
Type	Bin
Properties	content: complex
Used by	Complex Types AzimuthalAngleRange, EnergyRange, FrequencyRange, PolarAngleRange, WavelengthRange
Model	BandName{0,1} , Low , High
Children	BandName, High, Low
Instance	<pre><Bin> <BandName>{0,1}</BandName> <Low>{1,1}</Low> <High>{1,1}</High></pre>

	</Bin>
Source	<xsd:element name="Bin" type="Bin"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element BandName

Namespace	http://www.spase-group.org/data/schema
Annotations	A common or provider assigned name for a range of values.
Diagram	A UML class diagram fragment showing the 'BandName' element. It is represented by a rounded rectangle labeled 'BandName' with a small circle to its left, indicating it is a simple type. A line connects it to another rounded rectangle labeled 'xsd:string' with a small square to its left, indicating it is derived from the XML Schema string type.
Type	xsd:string
Properties	content: simple
Used by	Complex Type Bin
Source	<pre><xsd:element name="BandName" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">A common or provider assigned name for a range of values.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Particle

Namespace	http://www.spase-group.org/data/schema
Diagram	A UML class diagram fragment showing the 'Particle' element. It is represented by a rounded rectangle labeled 'Particle' with a small circle to its left, indicating it is a complex type. Inside a dashed box, there is a list of components: 'ParticleType' (multiplicity 1..infinity, type enumParticleType), 'Qualifier' (multiplicity 0..infinity, type enumQualifier), 'ParticleQuantity' (multiplicity 0..infinity, type enumParticleQuantity), 'AtomicNumber' (multiplicity 0..infinity, type xsd:double), 'EnergyRange' (multiplicity 0..infinity, type EnergyRange), 'AzimuthalAngleRange' (multiplicity 0..infinity, type AzimuthalAngleRange), and 'PolarAngleRange' (multiplicity 0..infinity, type PolarAngleRange). Below this, under a 'Substitution Group' heading, is 'ParameterEntity' (Abstract true).
Type	Particle
Properties	content: complex
Substitution Group Affiliation	• ParameterEntity
Model	ParticleType+, Qualifier*, ParticleQuantity, AtomicNumber*, EnergyRange{0,1}, AzimuthalAngleRange{0,1}, PolarAngleRange{0,1}
Children	AtomicNumber, AzimuthalAngleRange, EnergyRange, ParticleQuantity, ParticleType, PolarAngleRange, Qualifier
Instance	<pre><Particle> <ParticleType>{1,unbounded}</ParticleType> <Qualifier>{0,unbounded}</Qualifier> <ParticleQuantity>{1,1}</ParticleQuantity> <AtomicNumber>{0,unbounded}</AtomicNumber> <EnergyRange>{0,1}</EnergyRange> <AzimuthalAngleRange>{0,1}</AzimuthalAngleRange></pre>

	<PolarAngleRange>{0,1}</PolarAngleRange> </Particle>
Source	<xsd:element name="Particle" type="Particle" substitutionGroup="ParameterEntity"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ParticleType

Namespace	http://www.spase-group.org/data/schema																												
Annotations	A characterization of the kind of particle observed by the measurement.																												
Diagram	<pre> classDiagram class ParticleType { <<Particle>> } class enumParticleType { <<enumParticleType>> } ParticleType < -- enumParticleType </pre>																												
Type	enumParticleType																												
Properties	content: simple																												
Facets	<table border="1"> <tr> <td>enumeration</td> <td>Aerosol</td> <td>A suspension of fine solid or liquid particles in a gas.</td> </tr> <tr> <td>enumeration</td> <td>AlphaParticle</td> <td>A positively charged nuclear particle that consists of two protons and two neutrons.</td> </tr> <tr> <td>enumeration</td> <td>Atom</td> <td>Matter consisting of a nucleus surrounded by electrons which has no net charge.</td> </tr> <tr> <td>enumeration</td> <td>Dust</td> <td>Free microscopic particles of solid material.</td> </tr> <tr> <td>enumeration</td> <td>Electron</td> <td>An elementary particle consisting of a charge of negative electricity equal to about 1.602×10^{-19} Coulomb and having a mass when at rest of about 9.109534×10^{-28} gram.</td> </tr> <tr> <td>enumeration</td> <td>Ion</td> <td>An atom that has acquired a net electric charge by gaining or losing one or more electrons. (Note: $Z>2$)</td> </tr> <tr> <td>enumeration</td> <td>Molecule</td> <td>A group of atoms so united and combined by chemical affinity that they form a complete, integrated whole, being the smallest portion of any particular compound that can exist in a free state</td> </tr> <tr> <td>enumeration</td> <td>Neutron</td> <td>An elementary particle that has no net charge and is a constituent of atomic nuclei, and that has a mass slightly larger than a proton (1.673×10^{-24} gram.)</td> </tr> <tr> <td>enumeration</td> <td>Proton</td> <td>An elementary particle that is a constituent of all atomic nuclei, that carries a positive charge numerically equal to the charge of an electron, and that has a mass of 1.673×10^{-24} gram.</td> </tr> </table>		enumeration	Aerosol	A suspension of fine solid or liquid particles in a gas.	enumeration	AlphaParticle	A positively charged nuclear particle that consists of two protons and two neutrons.	enumeration	Atom	Matter consisting of a nucleus surrounded by electrons which has no net charge.	enumeration	Dust	Free microscopic particles of solid material.	enumeration	Electron	An elementary particle consisting of a charge of negative electricity equal to about 1.602×10^{-19} Coulomb and having a mass when at rest of about 9.109534×10^{-28} gram.	enumeration	Ion	An atom that has acquired a net electric charge by gaining or losing one or more electrons. (Note: $Z>2$)	enumeration	Molecule	A group of atoms so united and combined by chemical affinity that they form a complete, integrated whole, being the smallest portion of any particular compound that can exist in a free state	enumeration	Neutron	An elementary particle that has no net charge and is a constituent of atomic nuclei, and that has a mass slightly larger than a proton (1.673×10^{-24} gram.)	enumeration	Proton	An elementary particle that is a constituent of all atomic nuclei, that carries a positive charge numerically equal to the charge of an electron, and that has a mass of 1.673×10^{-24} gram.
enumeration	Aerosol	A suspension of fine solid or liquid particles in a gas.																											
enumeration	AlphaParticle	A positively charged nuclear particle that consists of two protons and two neutrons.																											
enumeration	Atom	Matter consisting of a nucleus surrounded by electrons which has no net charge.																											
enumeration	Dust	Free microscopic particles of solid material.																											
enumeration	Electron	An elementary particle consisting of a charge of negative electricity equal to about 1.602×10^{-19} Coulomb and having a mass when at rest of about 9.109534×10^{-28} gram.																											
enumeration	Ion	An atom that has acquired a net electric charge by gaining or losing one or more electrons. (Note: $Z>2$)																											
enumeration	Molecule	A group of atoms so united and combined by chemical affinity that they form a complete, integrated whole, being the smallest portion of any particular compound that can exist in a free state																											
enumeration	Neutron	An elementary particle that has no net charge and is a constituent of atomic nuclei, and that has a mass slightly larger than a proton (1.673×10^{-24} gram.)																											
enumeration	Proton	An elementary particle that is a constituent of all atomic nuclei, that carries a positive charge numerically equal to the charge of an electron, and that has a mass of 1.673×10^{-24} gram.																											
Used by	Complex Types	Mixed, Particle																											
Source	<xsd:element name="ParticleType" type="enumParticleType"> <xsd:annotation> <xsd:documentation xml:lang="en">A characterization of the kind of particle observed by the measurement.</xsd:documentation> </xsd:annotation> </xsd:element>																												
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd																												

Element ParticleQuantity

Namespace	http://www.spase-group.org/data/schema	
Annotations	A characterization of the physical properties of the particle.	
Diagram	<pre> classDiagram class ParticleQuantity { <<ParticleQuantity>> } class enumParticleQuantity { <<enumParticleQuantity>> } ParticleQuantity < -- enumParticleQuantity </pre>	
Type	enumParticleQuantity	

Properties	content:	simple
Facets	enumeration	ArrivalDirection An angular measure of the direction from which an energetic particle or photon was incident on a detector. The angles may be measured in any coordinate system.
	enumeration	AtomicNumberDetected The number of protons in the nucleus of an atom as determined by a detector.
	enumeration	AverageChargeState A measure of the composite deficit (positive) or excess (negative) of electrons with respect to protons.
	enumeration	ChargeState Charge of a fully or partially stripped ion, in units of the charge of a proton. Charge state of a bare proton = 1.
	enumeration	CountRate The number of events per unit time.
	enumeration	Counts The number of detection events occurring in a detector over the detector accumulation time.
	enumeration	Energy The capacity for doing work as measured by the capability of doing work (potential energy) or the conversion of this capability to motion (kinetic energy)
	enumeration	EnergyDensity The amount of energy per unit volume.
	enumeration	EnergyFlux The amount of energy passing through a unit area in a unit time.
	enumeration	FlowSpeed The rate at which particles or energy is passing through a unit area in a unit time.
	enumeration	FlowVelocity The volume of matter passing through a unit area perpendicular to the direction of flow in a unit of time.
	enumeration	Fluence The time integral of a flux. A fluence does not have any "per unit time" in its units.
	enumeration	Gyrofrequency The number of gyrations around a magnetic guiding center (field line) a charged particle makes per unit time due to the Lorentz force.
	enumeration	HeatFlux Flow of thermal energy through a gas or plasma; typically computed as third moment of a distribution function.
	enumeration	Mass The measure of inertia (mass) of individual objects (e.g., aerosols).
	enumeration	MassDensity The mass of particles per unit volume.
	enumeration	MassNumber The total number of protons and neutrons (together known as nucleons) in an atomic nucleus.
	enumeration	NumberDensity The number of particles per unit volume.
	enumeration	NumberFlux The number of particles passing a unit area in unit time, possibly also per unit energy (or equivalent) and/or per unit look direction.
	enumeration	PhaseSpaceDensity The number of particles per unit volume in the six-dimensional space of position and velocity.
	enumeration	PlasmaFrequency A number-density-dependent characteristic frequency of a plasma.
	enumeration	Pressure The force per unit area exerted by a particle distribution or field.
	enumeration	SonicMachNumber The ratio of the bulk flow speed to the speed

		of sound in the medium.
enumeration	SoundSpeed	The speed at which sound travels through a medium.
enumeration	Temperature	A measure of the kinetic energy of random motion with respect to the average. Temperature is properly defined only for an equilibrium particle distribution (Maxwellian distribution).
enumeration	ThermalSpeed	For a Maxwellian distribution, the difference between the mean speed and the speed within which ~69% (one sigma) of all the members of the speed distribution occur.
enumeration	Velocity	Rate of change of position. Also used for the average velocity of a collection of particles, also referred to as "bulk velocity".
Used by	Complex Type	Particle
Source		<pre><xsd:element name="ParticleQuantity" type="enumParticleQuantity"> <xsd:annotation> <xsd:documentation xml:lang="en">A characterization of the physical properties of the particle.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location		file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element AtomicNumber

Namespace	http://www.spase-group.org/data/schema
Annotations	The number of protons in the nucleus of an atom.
Diagram	
Type	xsd:double
Properties	content: simple
Used by	Complex Type
Source	<pre><xsd:element name="AtomicNumber" type="xsd:double"> <xsd:annotation> <xsd:documentation xml:lang="en">The number of protons in the nucleus of an atom.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element EnergyRange

Namespace	http://www.spase-group.org/data/schema
Diagram	
Type	EnergyRange
Properties	content: complex
Used by	Complex Types
	Particle, Wave

Model	Low , High , Units , Bin*
Children	Bin, High, Low, Units
Instance	<pre><EnergyRange> <Low>{1,1}</Low> <High>{1,1}</High> <Units>{1,1}</Units> <Bin>{0,unbounded}</Bin> </EnergyRange></pre>
Source	<xsd:element name="EnergyRange" type="EnergyRange" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element AzimuthalAngleRange

Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class AzimuthalAngleRange { Low : xsd:double High : xsd:double Units : xsd:string Bin : Bin* } AzimuthalAngleRange < -- AzimuthalAngleRange </pre>
Type	AzimuthalAngleRange
Properties	content: complex
Used by	Complex Type Particle
Model	Low , High , Units , Bin*
Children	Bin, High, Low, Units
Instance	<pre><AzimuthalAngleRange> <Low>{1,1}</Low> <High>{1,1}</High> <Units>{1,1}</Units> <Bin>{0,unbounded}</Bin> </AzimuthalAngleRange></pre>
Source	<xsd:element name="AzimuthalAngleRange" type="AzimuthalAngleRange" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element PolarAngleRange

Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class PolarAngleRange { Low : xsd:double High : xsd:double Units : xsd:string Bin : Bin* } PolarAngleRange < -- PolarAngleRange </pre>
Type	PolarAngleRange
Properties	content: complex
Used by	Complex Type Particle
Model	Low , High , Units , Bin*
Children	Bin, High, Low, Units

Instance	<PolarAngleRange> <Low>{1,1}</Low> <High>{1,1}</High> <Units>{1,1}</Units> <Bin>{0,unbounded}</Bin> </PolarAngleRange>
Source	<xsd:element name="PolarAngleRange" type="PolarAngleRange" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Wave

Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class Wave { WaveType Qualifier WaveQuantity EnergyRange FrequencyRange WavelengthRange } class Wave { <<ParameterEntity Abstract true>> } Wave < -- Wave WaveType < -- enumWaveType Qualifier < -- enumQualifier WaveQuantity < -- enumWaveQuantity EnergyRange < -- EnergyRange FrequencyRange < -- FrequencyRange WavelengthRange < -- WavelengthRange ParameterEntity < -- Abstract true </pre>
Type	Wave
Properties	content: complex
Substitution Group Affiliation	<ul style="list-style-type: none"> ParameterEntity
Model	WaveType , Qualifier* , WaveQuantity , EnergyRange{0,1} , FrequencyRange{0,1} , WavelengthRange{0,1}
Children	EnergyRange, FrequencyRange, Qualifier, WaveQuantity, WaveType, WavelengthRange
Instance	<Wave> <WaveType>{1,1}</WaveType> <Qualifier>{0,unbounded}</Qualifier> <WaveQuantity>{1,1}</WaveQuantity> <EnergyRange>{0,1}</EnergyRange> <FrequencyRange>{0,1}</FrequencyRange> <WavelengthRange>{0,1}</WavelengthRange> </Wave>
Source	<xsd:element name="Wave" type="Wave" substitutionGroup="ParameterEntity"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element WaveType

Namespace	http://www.spase-group.org/data/schema			
Annotations	A characterization of the carrier or phenomenon of wave information observed by the measurement.			
Diagram	<pre> classDiagram class WaveType class enumWaveType WaveType --> enumWaveType </pre>			
Type	enumWaveType			
Properties	content: simple			
Facets	<table border="1"> <tr> <td>enumeration</td> <td>Electromagnetic</td> <td>Electric and magnetic field variations in time and space that propagate through a medium</td> </tr> </table>	enumeration	Electromagnetic	Electric and magnetic field variations in time and space that propagate through a medium
enumeration	Electromagnetic	Electric and magnetic field variations in time and space that propagate through a medium		

		or a vacuum with the waves propagation, electric field, and magnetic field vectors forming an orthogonal triad. Waves in this category are detected by having their field quantities measured.
enumeration	Electrostatic	Collective longitudinal electric-field and plasma oscillations trapped within a body of plasma.
enumeration	Hydrodynamic	Periodic or quasi-periodic oscillations of fluid quantities.
enumeration	MHD	Hydrodynamic waves in a magnetized plasma in which the background magnetic field plays a key role in controlling the wave propagation characteristics.
enumeration	Photon	Electromagnetic waves detected by techniques that utilize their corpuscular character (e.g., CCD, CMOS, photomultipliers).
enumeration	PlasmaWaves	Self-consistent collective oscillations of particles and fields (electric and magnetic) in a plasma.
Used by	Complex Type	Wave
Source	<xsd:element name="WaveType" type="enumWaveType"> <xsd:annotation> <xsd:documentation xml:lang="en">A characterization of the carrier or phenomenon of wave information observed by the measurement.</xsd:documentation> </xsd:annotation> </xsd:element>	
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd	


Element WaveQuantity

Namespace	http://www.spase-group.org/data/schema																									
Annotations	A characterization of the physical properties of a wave.																									
Diagram	<pre> classDiagram class WaveQuantity { <<WaveQuantity>> <<Type>> } class enumWaveQuantity { <<enumWaveQuantity>> } WaveQuantity "0..1" o--> enumWaveQuantity </pre>																									
Type	enumWaveQuantity																									
Properties	content: simple																									
Facets	<table border="1"> <tr> <td>enumeration</td> <td>Absorption</td> <td>Decrease of radiant energy (relative to the background continuum spectrum).</td> </tr> <tr> <td>enumeration</td> <td>ACElectricField</td> <td>Alternating electric field component of a wave.</td> </tr> <tr> <td>enumeration</td> <td>ACMagneticField</td> <td>Alternating magnetic field component of a wave.</td> </tr> <tr> <td>enumeration</td> <td>DopplerFrequency</td> <td>Change in the frequency of a propagating wave due to motion of the source, the observer, the reflector, or the propagation medium.</td> </tr> <tr> <td>enumeration</td> <td>Emissivity</td> <td>The energy emitted spontaneously per unit bandwidth (typically frequency) per unit time per unit mass of source. Emissivity is usually integrated over all directions/solid angles.</td> </tr> <tr> <td>enumeration</td> <td>EnergyFlux</td> <td>The amount of energy passing through a unit area in a unit time.</td> </tr> <tr> <td>enumeration</td> <td>EquivalentWidth</td> <td>The spectral width of a total absorption line having the amount of absorbed radiant energy being equivalent to that in an observed absorption line.</td> </tr> <tr> <td>enumeration</td> <td>Frequency</td> <td>The number of occurrences of a repeating event</td> </tr> </table>		enumeration	Absorption	Decrease of radiant energy (relative to the background continuum spectrum).	enumeration	ACElectricField	Alternating electric field component of a wave.	enumeration	ACMagneticField	Alternating magnetic field component of a wave.	enumeration	DopplerFrequency	Change in the frequency of a propagating wave due to motion of the source, the observer, the reflector, or the propagation medium.	enumeration	Emissivity	The energy emitted spontaneously per unit bandwidth (typically frequency) per unit time per unit mass of source. Emissivity is usually integrated over all directions/solid angles.	enumeration	EnergyFlux	The amount of energy passing through a unit area in a unit time.	enumeration	EquivalentWidth	The spectral width of a total absorption line having the amount of absorbed radiant energy being equivalent to that in an observed absorption line.	enumeration	Frequency	The number of occurrences of a repeating event
enumeration	Absorption	Decrease of radiant energy (relative to the background continuum spectrum).																								
enumeration	ACElectricField	Alternating electric field component of a wave.																								
enumeration	ACMagneticField	Alternating magnetic field component of a wave.																								
enumeration	DopplerFrequency	Change in the frequency of a propagating wave due to motion of the source, the observer, the reflector, or the propagation medium.																								
enumeration	Emissivity	The energy emitted spontaneously per unit bandwidth (typically frequency) per unit time per unit mass of source. Emissivity is usually integrated over all directions/solid angles.																								
enumeration	EnergyFlux	The amount of energy passing through a unit area in a unit time.																								
enumeration	EquivalentWidth	The spectral width of a total absorption line having the amount of absorbed radiant energy being equivalent to that in an observed absorption line.																								
enumeration	Frequency	The number of occurrences of a repeating event																								


		per unit time.
enumeration	Gyrofrequency	The number of gyrations around a magnetic guiding center (field line) a charged particle makes per unit time due to the Lorentz force.
enumeration	Intensity	The measurement of radiant or wave energy per unit detector area per unit bandwidth per unit solid angle per unit time.
enumeration	LineDepth	The measure of the amount of absorption below the continuum (depth) in a particular wavelength or frequency in an absorption spectrum.
enumeration	MagneticField	A region of space near a magnetized body where magnetic forces can be detected (as measured by methods such as Zeeman splitting, etc.).
enumeration	ModeAmplitude	In helioseismology the magnitude of oscillation of waves of a particular geometry.
enumeration	PlasmaFrequency	A number-density-dependent characteristic frequency of a plasma.
enumeration	Polarization	Direction of the electric vector of an electromagnetic wave. The wave can be linearly polarized in any direction perpendicular to the direction of travel, circularly polarized (clockwise or counterclockwise), unpolarized, or mixtures of the above.
enumeration	PoyntingFlux	Electromagnetic energy flux transported by a wave characterized as the rate of energy transport per unit area per steradian.
enumeration	PropagationTime	Time difference between transmission and reception of a wave in an active wave experiment.
enumeration	StokesParameters	A set of four parameters (usually called I, Q, U and V) which describe the polarization state of an electromagnetic wave propagating through space.
enumeration	Velocity	Rate of change of position. Also used for the average velocity of a collection of particles, also referred to as "bulk velocity".
enumeration	Wavelength	The peak-to-peak distance over one wave period.
Used by	Complex Type	Wave
Source	<xsd:element name="WaveQuantity" type="enumWaveQuantity"> <xsd:annotation> <xsd:documentation xml:lang="en">A characterization of the physical properties of a wave.</xsd:documentation> </xsd:annotation> </xsd:element>	
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd	

Element WavelengthRange

Namespace	http://www.spase-group.org/data/schema
-----------	---

Diagram	
Type	WavelengthRange
Properties	content: complex
Used by	Complex Type Wave
Model	SpectralRange{0,1} , Low , High , Units , Bin*
Children	Bin, High, Low, SpectralRange, Units
Instance	<WavelengthRange> <SpectralRange>{0,1}</SpectralRange> <Low>{1,1}</Low> <High>{1,1}</High> <Units>{1,1}</Units> <Bin>{0,unbounded}</Bin> </WavelengthRange>
Source	<xsd:element name="WavelengthRange" type="WavelengthRange" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Mixed


Namespace	http://www.spase-group.org/data/schema
Diagram	
Type	Mixed
Properties	content: complex
Substitution Group Affiliation	• ParameterEntity
Model	MixedQuantity , ParticleType* , Qualifier*
Children	MixedQuantity, ParticleType, Qualifier
Instance	<Mixed> <MixedQuantity>{1,1}</MixedQuantity> <ParticleType>{0,unbounded}</ParticleType> <Qualifier>{0,unbounded}</Qualifier> </Mixed>
Source	<xsd:element name="Mixed" type="Mixed" substitutionGroup="ParameterEntity" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element MixedQuantity


Namespace	http://www.spase-group.org/data/schema																													
Annotations	A characterization of the combined attributes of a quantity.																													
Diagram	<pre> classDiagram class MixedQuantity { <<Type enumMixedQuantity>> } MixedQuantity < -- enumMixedQuantity </pre>																													
Type	enumMixedQuantity																													
Properties	content: simple																													
Facets	<table border="1"> <tr> <td>enumeration</td> <td>AkasofuEpsilon</td> <td>A measure of the magnetopause energy flux and an indicator of the solar wind power available for subsequent magnetospheric energization. Defined as: $V*B^2*l^2\sin(\theta/2)^4$ where B is the IMF, l is an empirical scaling parameter equal to 7 RE, and theta = tan(BY /BZ)⁻¹ the IMF clock angle.</td> </tr> <tr> <td>enumeration</td> <td>AlfvenMachNumber</td> <td>The ratio of the bulk flow speed to the Alfven speed.</td> </tr> <tr> <td>enumeration</td> <td>AlfvenVelocity</td> <td>Phase velocity of the Alfven wave; In SI units it is the velocity of the magnetic field divided by the square root of the mass density times the permeability of free space (μ_0).</td> </tr> <tr> <td>enumeration</td> <td>FrequencyToGyrofrequencyRatio</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MagnetosonicMachNumber</td> <td>The ratio of the velocity of fast mode waves to the Alfven velocity.</td> </tr> <tr> <td>enumeration</td> <td>Other</td> <td>Not classified with more specific terms. The context of its usage may be described in related text.</td> </tr> <tr> <td>enumeration</td> <td>PlasmaBeta</td> <td>The ratio of the plasma pressure (nkT) to the magnetic pressure ($B^2/2\mu_0$) of the fluid.</td> </tr> <tr> <td>enumeration</td> <td>TotalPressure</td> <td>In an MHD fluid it is the number density (N) times Boltzmann constant times the temperature in Kelvin.</td> </tr> <tr> <td>enumeration</td> <td>VCrossB</td> <td>The cross product of the charge velocity (V) and the magnetic field (B). It is the electric field exerted on a point charge by a magnetic field.</td> </tr> </table>			enumeration	AkasofuEpsilon	A measure of the magnetopause energy flux and an indicator of the solar wind power available for subsequent magnetospheric energization. Defined as: $V*B^2*l^2\sin(\theta/2)^4$ where B is the IMF, l is an empirical scaling parameter equal to 7 RE, and theta = tan(BY /BZ) ⁻¹ the IMF clock angle.	enumeration	AlfvenMachNumber	The ratio of the bulk flow speed to the Alfven speed.	enumeration	AlfvenVelocity	Phase velocity of the Alfven wave; In SI units it is the velocity of the magnetic field divided by the square root of the mass density times the permeability of free space (μ_0).	enumeration	FrequencyToGyrofrequencyRatio		enumeration	MagnetosonicMachNumber	The ratio of the velocity of fast mode waves to the Alfven velocity.	enumeration	Other	Not classified with more specific terms. The context of its usage may be described in related text.	enumeration	PlasmaBeta	The ratio of the plasma pressure (nkT) to the magnetic pressure ($B^2/2\mu_0$) of the fluid.	enumeration	TotalPressure	In an MHD fluid it is the number density (N) times Boltzmann constant times the temperature in Kelvin.	enumeration	VCrossB	The cross product of the charge velocity (V) and the magnetic field (B). It is the electric field exerted on a point charge by a magnetic field.
enumeration	AkasofuEpsilon	A measure of the magnetopause energy flux and an indicator of the solar wind power available for subsequent magnetospheric energization. Defined as: $V*B^2*l^2\sin(\theta/2)^4$ where B is the IMF, l is an empirical scaling parameter equal to 7 RE, and theta = tan(BY /BZ) ⁻¹ the IMF clock angle.																												
enumeration	AlfvenMachNumber	The ratio of the bulk flow speed to the Alfven speed.																												
enumeration	AlfvenVelocity	Phase velocity of the Alfven wave; In SI units it is the velocity of the magnetic field divided by the square root of the mass density times the permeability of free space (μ_0).																												
enumeration	FrequencyToGyrofrequencyRatio																													
enumeration	MagnetosonicMachNumber	The ratio of the velocity of fast mode waves to the Alfven velocity.																												
enumeration	Other	Not classified with more specific terms. The context of its usage may be described in related text.																												
enumeration	PlasmaBeta	The ratio of the plasma pressure (nkT) to the magnetic pressure ($B^2/2\mu_0$) of the fluid.																												
enumeration	TotalPressure	In an MHD fluid it is the number density (N) times Boltzmann constant times the temperature in Kelvin.																												
enumeration	VCrossB	The cross product of the charge velocity (V) and the magnetic field (B). It is the electric field exerted on a point charge by a magnetic field.																												
Used by	Complex Type	Mixed																												
Source	<pre> <xsd:element name="MixedQuantity" type="enumMixedQuantity"> <xsd:annotation> <xsd:documentation xml:lang="en">A characterization of the combined attributes of a quantity.</xsd:documentation> </xsd:annotation> </xsd:element> </pre>																													
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd																													

Element Support

Namespace	http://www.spase-group.org/data/schema
-----------	---

Diagram	
Type	Support
Properties	content: complex
Substitution Group Affiliation	• ParameterEntity
Model	Qualifier*, SupportQuantity
Children	Qualifier, SupportQuantity
Instance	<Support> <Qualifier>{0,unbounded}</Qualifier> <SupportQuantity>{1,1}</SupportQuantity> </Support>
Source	<xsd:element name="Support" type="Support" substitutionGroup="ParameterEntity"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element SupportQuantity

Namespace	http://www.spase-group.org/data/schema																	
Annotations	A characterization of the support information.																	
Diagram																		
Type	enumSupportQuantity																	
Properties	content: simple																	
Facets	<table border="1"> <tr> <td>enumeration</td> <td>InstrumentMode</td> <td>An indication of a state (mode) in which the instrument is operating. How a mode influences the interpretation and representation of data is described in instrument related documentation.</td> </tr> <tr> <td>enumeration</td> <td>Other</td> <td>Not classified with more specific terms. The context of its usage may be described in related text.</td> </tr> <tr> <td>enumeration</td> <td>Positional</td> <td>The specification of the location of an object or measurement within a reference coordinate system. The position is usually expressed as a set of values corresponding to the location along a set of orthogonal axes together with the date/time of the observation.</td> </tr> <tr> <td>enumeration</td> <td>Temporal</td> <td>Pertaining to time.</td> </tr> <tr> <td>enumeration</td> <td>Velocity</td> <td>Rate of change of position. Also used for the average velocity of a collection of particles, also referred to as "bulk velocity".</td> </tr> </table>			enumeration	InstrumentMode	An indication of a state (mode) in which the instrument is operating. How a mode influences the interpretation and representation of data is described in instrument related documentation.	enumeration	Other	Not classified with more specific terms. The context of its usage may be described in related text.	enumeration	Positional	The specification of the location of an object or measurement within a reference coordinate system. The position is usually expressed as a set of values corresponding to the location along a set of orthogonal axes together with the date/time of the observation.	enumeration	Temporal	Pertaining to time.	enumeration	Velocity	Rate of change of position. Also used for the average velocity of a collection of particles, also referred to as "bulk velocity".
enumeration	InstrumentMode	An indication of a state (mode) in which the instrument is operating. How a mode influences the interpretation and representation of data is described in instrument related documentation.																
enumeration	Other	Not classified with more specific terms. The context of its usage may be described in related text.																
enumeration	Positional	The specification of the location of an object or measurement within a reference coordinate system. The position is usually expressed as a set of values corresponding to the location along a set of orthogonal axes together with the date/time of the observation.																
enumeration	Temporal	Pertaining to time.																
enumeration	Velocity	Rate of change of position. Also used for the average velocity of a collection of particles, also referred to as "bulk velocity".																
Used by	Complex Type	Support																
Source	<pre><xsd:element name="SupportQuantity" type="enumSupportQuantity"> <xsd:annotation> <xsd:documentation xml:lang="en">A characterization of the support information.</xsd:documentation> </xsd:annotation> </xsd:element></pre>																	

Schema location

file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element DisplayData

Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class DisplayData { ResourceID ResourceHeader AccessInformation "1..oo" ProcessingLevel ProviderResourceName ProviderProcessingLevel ProviderVersion InstrumentID "0..oo" MeasurementType "1..oo" TemporalDescription SpectralRange "0..oo" DisplayCadence ObservedRegion "0..oo" Caveats Keyword "0..oo" InputResourceId Parameter "0..oo" Extension } DisplayData < -- ResourceEntity ResourceEntity { Abstract true } </pre>
Type	DisplayData
Properties	content: complex
Substitution Group Affiliation	<ul style="list-style-type: none"> • ResourceEntity
Model	ResourceID , ResourceHeader , AccessInformation{1,oo} , ProcessingLevel{0,1} , ProviderResourceName{0,1} , ProviderProcessingLevel{0,1} , ProviderVersion{0,1} , InstrumentID* , MeasurementType+ , TemporalDescription{0,1} , SpectralRange* , DisplayCadence{0,1} , ObservedRegion* , Caveats{0,1} , Keyword* , InputResourceId* , Parameter* , Extension*

Children	AccessInformation, Caveats, DisplayCadence, Extension, InputResourceID, InstrumentID, Keyword, MeasurementType, ObservedRegion, Parameter, ProcessingLevel, ProviderProcessingLevel, ProviderResourceName, ProviderVersion, ResourceHeader, ResourceID, SpectralRange, TemporalDescription
Instance	<DisplayData> <ResourceID>{1,1}</ResourceID> <ResourceHeader>{1,1}</ResourceHeader> <AccessInformation>{1,unbounded}</AccessInformation> <ProcessingLevel>{0,1}</ProcessingLevel> <ProviderResourceName>{0,1}</ProviderResourceName> <ProviderProcessingLevel>{0,1}</ProviderProcessingLevel> <ProviderVersion>{0,1}</ProviderVersion> <InstrumentID>{0,unbounded}</InstrumentID> <MeasurementType>{1,unbounded}</MeasurementType> <TemporalDescription>{0,1}</TemporalDescription> <SpectralRange>{0,unbounded}</SpectralRange> <DisplayCadence>{0,1}</DisplayCadence> <ObservedRegion>{0,unbounded}</ObservedRegion> <Caveats>{0,1}</Caveats> <Keyword>{0,unbounded}</Keyword> <InputResourceID>{0,unbounded}</InputResourceID> <Parameter>{0,unbounded}</Parameter> <Extension>{0,unbounded}</Extension> </DisplayData>
Source	<xsd:element name="DisplayData" type="DisplayData" substitutionGroup="ResourceEntity"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ProcessingLevel

Namespace	http://www.spase-group.org/data/schema											
Annotations	The standard classification of the processing performed on the product.											
Diagram	<pre> classDiagram class ProcessingLevel { <<enum>> } class enumProcessingLevel { <<enumeration>> } ProcessingLevel "1" -- "0..1" enumProcessingLevel </pre>											
Type	enumProcessingLevel											
Properties	content: simple											
Facets	<table border="1"> <tr> <td>enumeration</td> <td>Calibrated</td> <td>Data wherein sensor outputs have been convolved with instrument response function, often irreversibly, to yield data in physical units.</td> </tr> <tr> <td>enumeration</td> <td>Raw</td> <td>Data in its original state with no processing to account for calibration!!!</td> </tr> <tr> <td>enumeration</td> <td>Uncalibrated</td> <td>Duplicate data are removed from the data stream and data are time ordered. Values are not adjusted for any potential biases or external factors.</td> </tr> </table>			enumeration	Calibrated	Data wherein sensor outputs have been convolved with instrument response function, often irreversibly, to yield data in physical units.	enumeration	Raw	Data in its original state with no processing to account for calibration!!!	enumeration	Uncalibrated	Duplicate data are removed from the data stream and data are time ordered. Values are not adjusted for any potential biases or external factors.
enumeration	Calibrated	Data wherein sensor outputs have been convolved with instrument response function, often irreversibly, to yield data in physical units.										
enumeration	Raw	Data in its original state with no processing to account for calibration!!!										
enumeration	Uncalibrated	Duplicate data are removed from the data stream and data are time ordered. Values are not adjusted for any potential biases or external factors.										
Used by	Complex Types	DisplayData, NumericalData										
Source	<xsd:element name="ProcessingLevel" type="enumProcessingLevel"> <xsd:annotation> <xsd:documentation xml:lang="en">The standard classification of the processing performed on the product.</xsd:documentation> </xsd:annotation> </xsd:element>											
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd											

Element ProviderProcessingLevel

Namespace	http://www.spase-group.org/data/schema		
Annotations	The provider specific classification of the processing performed on the product.		
Diagram	<pre> classDiagram class ProviderProcessingLevel { <<xsd:string>> } class xsd:string { <<string>> } ProviderProcessingLevel "1" -- "0..1" xsd:string </pre>		
Type	xsd:string		

Properties	content: simple
Used by	Complex Types DisplayData, NumericalData
Source	<xsd:element name="ProviderProcessingLevel" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The provider specific classification of the processing performed on the product.</xsd:documentation> </xsd:annotation> </xsd:element>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element MeasurementType

Namespace	http://www.spase-group.org/data/schema		
Annotations	A characterization of the quantitative assessment of a phenomenon.		
Diagram	<pre> classDiagram class MeasurementType { <<MeasurementType>> <<Type enumMeasurementType>> } class enumMeasurementType { <<enumMeasurementType>> } MeasurementType "1" -- "0..1" enumMeasurementType </pre>		
Type	enumMeasurementType		
Properties	content: simple		
Facets	enumeration	ActivityIndex	An indication, derived from one or more measurements, of the level of activity of an object or region, such as sunspot number, F10.7 flux, Dst, or the Polar Cap Indices.
	enumeration	Dopplergram	A map or image depicting the spatial distribution of line-of-sight velocities of the observed object.
	enumeration	Dust	Free microscopic particles of solid material.
	enumeration	ElectricField	A region of space around a charged particle, or between two voltages within which a force is exerted on charged objects in its vicinity. An electric field is the electric force per unit charge.
	enumeration	EnergeticParticles	Pieces of matter that are moving very fast. Energetic particles include protons, electrons, neutrons, neutrinos, the nuclei of atoms, and other sub-atomic particles.
	enumeration	Ephemeris	The spatial coordinates of a body as a function of time. When used as an Instrument Type it represents the process or methods used to generate spatial coordinates.
	enumeration	ImageIntensity	Measurements of the two-dimensional distribution of the intensity of photons from some region or object such as the Sun or the polar auroral regions; can be in any wavelength band, and polarized, etc.
	enumeration	InstrumentStatus	A quantity directly related to the operation or function of an instrument.
	enumeration	IonComposition	In situ measurements of the relative flux or density of electrically charged particles in the space environment. May give simple fluxes, but full distribution functions are sometimes measured.
	enumeration	Irradiance	Irradiance - A radiometric term for the power of electromagnetic radiation at a surface, per unit area. "Irradiance" is used when the electromagnetic radiation is incident on the surface. Irradiance data may be reported in any units (i.e. counts/s) due to, for example,

		being at a particular wavelength, or to being a not-fully-calibrated relative measurement.
enumeration	MagneticField	A region of space near a magnetized body where magnetic forces can be detected (as measured by methods such as Zeeman splitting, etc.).
enumeration	Magnetogram	Measurements of the vector or line-of-sight magnetic field determined from remote sensing measurements of the detailed structure of spectral lines, including their splitting and polarization. ("Magnetogram.")
enumeration	NeutralAtomImages	Measurements of neutral atom fluxes as a function of look direction; often related to remote energetic charged particles that lose their charge through charge-exchange and then reach the detector on a line-of-sight trajectory.
enumeration	NeutralGas	Measurements of neutral atomic and molecular components of a gas.
enumeration	Profile	Measurements of a quantity as a function of height above an object such as the limb of a body.
enumeration	Radiance	A radiometric measurement that describes the amount of electromagnetic radiation that passes through or is emitted from a particular area, and falls within a given solid angle in a specified direction. They are used to characterize both emission from diffuse sources and reflection from diffuse surfaces.
enumeration	Spectrum	The distribution of a characteristic of a physical system or phenomenon, such as the energy emitted by a radiant source, arranged in the order of wavelengths.
enumeration	ThermalPlasma	Measurements of the plasma in the energy regime where the most of the plasma occurs. May be the basic fluxes in the form of distribution functions or the derived bulk parameters (density, flow velocity, etc.).
enumeration	Waves	Data resulting from observations of wave experiments and natural wave phenomena. Wave experiments are typically active and natural wave phenomena are passive. Examples of wave experiments include coherent/incoherent scatter radars, radio soundings, VLF propagation studies, ionospheric scintillation of beacon satellite signals, etc. Examples of natural wave phenomena include micropulsations, mesospheric gravity waves, auroral/plasmaspheric hiss, Langmuir waves, AKR, Jovian decametric radiation, solar radio bursts, etc.
enumeration	Waves.Active	Exerting an influence or producing a change or effect. An active measurement is one which produces a transmission or excitation as a part of the measurement cycle.
enumeration	Waves.Passive	Movement or effect produced by outside influence. A passive measurement is one which does not produce a transmission or excitation as a part of the measurement cycle.
Used by	Complex Types	DisplayData, NumericalData

Source	<pre><xsd:element name="MeasurementType" type="enumMeasurementType"> <xsd:annotation> <xsd:documentation xml:lang="en">A characterization of the quantitative assessment of a phenomenon.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element TemporalDescription

Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class TemporalDescription { TimeSpan Cadence Exposure } TimeSpan < -- TemporalDescription Cadence < -- TemporalDescription Exposure < -- TemporalDescription </pre>
Type	TemporalDescription
Properties	content: complex
Used by	Complex Types DisplayData, NumericalData
Model	TimeSpan , Cadence{0,1} , Exposure{0,1}
Children	Cadence, Exposure, TimeSpan
Instance	<pre> <TemporalDescription> <TimeSpan>{1,1}</TimeSpan> <Cadence>{0,1}</Cadence> <Exposure>{0,1}</Exposure> </TemporalDescription> </pre>
Source	<xsd:element name="TemporalDescription" type="TemporalDescription"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Exposure

Namespace	http://www.spase-group.org/data/schema
Annotations	The time interval over which an individual measurement is taken.
Diagram	<pre> classDiagram class Exposure { xsd:duration } Exposure < -- TemporalDescription </pre>
Type	xsd:duration
Properties	content: simple
Used by	Complex Type TemporalDescription
Source	<pre> <xsd:element name="Exposure" type="xsd:duration"> <xsd:annotation> <xsd:documentation xml:lang="en">The time interval over which an individual measurement is taken.</xsd:documentation> </xsd:annotation> </xsd:element> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element DisplayCadence

Namespace	http://www.spase-group.org/data/schema
Annotations	The time interval between the successive display elements.
Diagram	<pre> classDiagram class DisplayCadence { xsd:duration } DisplayCadence < -- TemporalDescription </pre>
Type	xsd:duration
Properties	content: simple

Used by	Complex Type	DisplayData
Source	<pre><xsd:element name="DisplayCadence" type="xsd:duration"> <xsd:annotation> <xsd:documentation xml:lang="en">The time interval between the successive display elements.</xsd:documentation> </xsd:annotation> </xsd:element></pre>	
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd	

Element ObservedRegion

Namespace	http://www.spase-group.org/data/schema																																			
Annotations	<p>The portion of space measured by the instrument at the time of an observation. A region is distinguished by certain natural features or physical characteristics. It is the location of the observatory for in situ data, the location or region sensed by remote sensing observatories and the location-of-relevance for parameters that are derived from observational data.</p>																																			
Diagram	<pre> classDiagram class ObservedRegion { <<Type enumRegion>> } class enumRegion ObservedRegion "1" -- "2" enumRegion </pre>																																			
Type	enumRegion																																			
Properties	content: simple																																			
Facets	<table border="1"> <tr> <td>enumeration</td> <td>Asteroid</td> <td>A small extraterrestrial body consisting mostly of rock and metal that is in orbit around the sun.</td> </tr> <tr> <td>enumeration</td> <td>Comet</td> <td>A relatively small extraterrestrial body consisting of a frozen mass that travels around the sun in a highly elliptical orbit.</td> </tr> <tr> <td>enumeration</td> <td>Earth</td> <td>The third planet from the sun in our solar system.</td> </tr> <tr> <td>enumeration</td> <td>Earth.Magnetsheath</td> <td>The region between the bow shock and the magnetopause, characterized by very turbulent plasma.</td> </tr> <tr> <td>enumeration</td> <td>Earth.Magnetosphere</td> <td>The region of space above the atmosphere or surface of the planet, and bounded by the magnetopause, that is under the direct influence of the planets magnetic field.</td> </tr> <tr> <td>enumeration</td> <td>Earth.Magnetosphere.Magnetotail</td> <td>The region on the night side of the body where the magnetic field is stretched backwards by the force of the solar wind. For Earth, the magnetotail begins at a night-side radial distance of 10 Re (X > -10Re).</td> </tr> <tr> <td>enumeration</td> <td>Earth.Magnetosphere.Main</td> <td>The region of the magnetosphere where the magnetic field lines are closed, but does not include the gaseous region gravitationally bound to the body.</td> </tr> <tr> <td>enumeration</td> <td>Earth.Magnetosphere.Polar</td> <td>The region near the pole of a body. For a magnetosphere the polar region is the area where magnetic field lines are open and includes the auroral zone.</td> </tr> <tr> <td>enumeration</td> <td>Earth.Magnetosphere.RadiationBelt</td> <td>The region within a magnetosphere where high-energy particles could potentially be trapped in a magnetic field.</td> </tr> <tr> <td>enumeration</td> <td>Earth.NearSurface</td> <td>The gaseous and possibly ionized environment of a body extending from the surface to some specified altitude. For the Earth, this altitude is 2000 km.</td> </tr> <tr> <td>enumeration</td> <td>Earth.NearSurface.Atmosphere</td> <td>The neutral gases surrounding a body that extends from the surface and is bound to the</td> </tr> </table>			enumeration	Asteroid	A small extraterrestrial body consisting mostly of rock and metal that is in orbit around the sun.	enumeration	Comet	A relatively small extraterrestrial body consisting of a frozen mass that travels around the sun in a highly elliptical orbit.	enumeration	Earth	The third planet from the sun in our solar system.	enumeration	Earth.Magnetsheath	The region between the bow shock and the magnetopause, characterized by very turbulent plasma.	enumeration	Earth.Magnetosphere	The region of space above the atmosphere or surface of the planet, and bounded by the magnetopause, that is under the direct influence of the planets magnetic field.	enumeration	Earth.Magnetosphere.Magnetotail	The region on the night side of the body where the magnetic field is stretched backwards by the force of the solar wind. For Earth, the magnetotail begins at a night-side radial distance of 10 Re (X > -10Re).	enumeration	Earth.Magnetosphere.Main	The region of the magnetosphere where the magnetic field lines are closed, but does not include the gaseous region gravitationally bound to the body.	enumeration	Earth.Magnetosphere.Polar	The region near the pole of a body. For a magnetosphere the polar region is the area where magnetic field lines are open and includes the auroral zone.	enumeration	Earth.Magnetosphere.RadiationBelt	The region within a magnetosphere where high-energy particles could potentially be trapped in a magnetic field.	enumeration	Earth.NearSurface	The gaseous and possibly ionized environment of a body extending from the surface to some specified altitude. For the Earth, this altitude is 2000 km.	enumeration	Earth.NearSurface.Atmosphere	The neutral gases surrounding a body that extends from the surface and is bound to the
enumeration	Asteroid	A small extraterrestrial body consisting mostly of rock and metal that is in orbit around the sun.																																		
enumeration	Comet	A relatively small extraterrestrial body consisting of a frozen mass that travels around the sun in a highly elliptical orbit.																																		
enumeration	Earth	The third planet from the sun in our solar system.																																		
enumeration	Earth.Magnetsheath	The region between the bow shock and the magnetopause, characterized by very turbulent plasma.																																		
enumeration	Earth.Magnetosphere	The region of space above the atmosphere or surface of the planet, and bounded by the magnetopause, that is under the direct influence of the planets magnetic field.																																		
enumeration	Earth.Magnetosphere.Magnetotail	The region on the night side of the body where the magnetic field is stretched backwards by the force of the solar wind. For Earth, the magnetotail begins at a night-side radial distance of 10 Re (X > -10Re).																																		
enumeration	Earth.Magnetosphere.Main	The region of the magnetosphere where the magnetic field lines are closed, but does not include the gaseous region gravitationally bound to the body.																																		
enumeration	Earth.Magnetosphere.Polar	The region near the pole of a body. For a magnetosphere the polar region is the area where magnetic field lines are open and includes the auroral zone.																																		
enumeration	Earth.Magnetosphere.RadiationBelt	The region within a magnetosphere where high-energy particles could potentially be trapped in a magnetic field.																																		
enumeration	Earth.NearSurface	The gaseous and possibly ionized environment of a body extending from the surface to some specified altitude. For the Earth, this altitude is 2000 km.																																		
enumeration	Earth.NearSurface.Atmosphere	The neutral gases surrounding a body that extends from the surface and is bound to the																																		

		body by virtue of the gravitational attraction.
enumeration	Earth.NearSurface.AuroralRegion	Region in the atmosphere where electrically-charged particles bombarding the upper atmosphere of a planet in the presence of a magnetic field produce an optical phenomenon.
enumeration	Earth.NearSurface.EquatorialRegion	A region centered on the equator and limited in latitude by approximately 23 degrees north and south of the equator.
enumeration	Earth.NearSurface.Ionosphere	Charged or ionized gases surrounding a body that are nominally bound to the body by virtue of the gravitational attraction.
enumeration	Earth.NearSurface.IonosphereLayer	The layer of the ionosphere that exists approximately 50 to 95 km above the surface of the Earth. One of several layers in the ionosphere.
enumeration	Earth.NearSurface.IonosphereLayerE	A layer of ionised gas occurring at 90-150km above the ground. One of several layers in the ionosphere. Also called the The Kennelly-Heaviside layer.
enumeration	Earth.NearSurface.IonosphereLayerF	A layer that contains ionized gases at a height of around 150-800 km above sea level, placing it in the thermosphere. the F region has the highest concentration of free electrons and ions anywhere in the atmosphere. It may be thought of as comprising two layers, the F1-and F2-layers. One of several layers in the ionosphere. Also known as the Appleton layer.
enumeration	Earth.NearSurface.IonosphereLayerP	The region in the upper most areas of the ionosphere.
enumeration	Earth.NearSurface.Mesosphere	The layer of the atmosphere that extends from the Stratosphere to a range of 80 km to 85 km, temperature decreasing with height.
enumeration	Earth.NearSurface.Plasmasphere	A region of the magnetosphere consisting of low energy (cool) plasma. It is located above the ionosphere. The outer boundary of the plasmasphere is known as the plasmapause, which is defined by an order of magnitude drop in plasma density.
enumeration	Earth.NearSurface.PolarCap	The areas of the globe surrounding the poles and consisting of the region north of 60 degrees north latitude an the region south of 60 degrees south latitude.
enumeration	Earth.NearSurface.SouthAtmosphericAnomalyRegion	Planetary Anomaly Region Earths inner van Allen radiation belt makes its closest approach to the planets surface. The result is that, for a given altitude, the radiation intensity is higher over this region than elsewhere.
enumeration	Earth.NearSurface.Stratosphere	The layer of the atmosphere that extends from the troposphere to about 30 km, temperature increases with height. The stratosphere contains the ozone layer.
enumeration	Earth.NearSurface.Thermosphere	The layer of the atmosphere that extends from the Mesosphere to 640+ km, temperature increasing with height.
enumeration	Earth.NearSurface.Troposphere	The lowest layer of the atmosphere which begins at the surface and extends to between 7 km (4.4 mi) at the poles and 17 km (10.6 mi)


		at the equator, with some variation due to weather factors.
enumeration	Earth.Surface	The outermost area of a solid object.
enumeration	Heliosphere	The solar atmosphere extending roughly from the outer corona to the edge of the solar plasma at the heliopause separating primarily solar plasma from interstellar plasma.
enumeration	Heliosphere.Heliosheath	The region extending radially outward from the heliospheric termination shock and in which the decelerated solar wind plasma is still significant.
enumeration	Heliosphere.Inner	The region of the heliosphere extending radially outward from the solar coronal base to just inside 1 AU.
enumeration	Heliosphere.NearEarth	The heliospheric region near the Earth which extends to and includes the area near the L1 and L2 Lagrange point.
enumeration	Heliosphere.Outer	The region of the heliosphere extending radially outward from just outside 1 AU to the heliospheric termination shock.
enumeration	Heliosphere.Remote1AU	A roughly toroidal region that includes the Earth's orbit, but exclusive of the region near the Earth.
enumeration	Interstellar	The region between stars outside of the stars heliopause.
enumeration	Jupiter	The fifth planet from the sun in our solar system.
enumeration	Mars	The forth planet from the sun in our solar system.
enumeration	Mercury	The first planet from the sun in our solar system.
enumeration	Neptune	The seventh planet from the sun in our solar system.
enumeration	Pluto	The ninth (sub)planet from the sun in our solar system.
enumeration	Saturn	The sixth planet from the sun in our solar system.
enumeration	Sun	The star upon which our solar system is centered.
enumeration	Sun.Chromosphere	The region of the Sun's (or a stars) atmosphere above the temperature minimum and below the Transition Region. The solar chromosphere is approximately 400 km to 2100 km above the photosphere, and characterized by temperatures from 4500 - 28000 K.
enumeration	Sun.Corona	The outermost atmospheric region of the Sun or a star, characterized by ionization temperatures above 10^5 K. The solar corona starts at about 2100 km above the photosphere; there is no generally defined upper limit.
enumeration	Sun.Interior	The region inside the body which is not visible from outside the body.
enumeration	Sun.Photosphere	The atmospheric layer of the Sun or a star from which continuum radiation, especially optical, is emitted to space. For the Sun, the photosphere is about 500 km thick.
enumeration	Sun.TransitionRegion	A very narrow (<100 km) layer between the chromosphere and the corona where the temperature rises abruptly from about 8000 to about 500,000

		K.
enumeration	Uranus	The eighth planet from the sun in our solar system.
enumeration	Venus	The second planet from the sun in our solar system.
Used by	Complex Types	DisplayData, NumericalData, ObservationExtent
Source	<pre><xsd:element name="ObservedRegion" type="enumRegion"> <xsd:annotation> <xsd:documentation xml:lang="en">The portion of space measured by the instrument at the time of an observation. A region is distinguished by certain natural features or physical characteristics. It is the location of the observatory for in situ data, the location or region sensed by remote sensing observatories and the location-of-relevance for parameters that are derived from observational data.</xsd:documentation> </xsd:annotation> </xsd:element></pre>	
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd	

Element NumericalData

Namespace	http://www.spase-group.org/data/schema
-----------	---

Diagram



Type	<code>NumericalData</code>
Properties	content: complex
Substitution Group Affiliation	• <code>ResourceEntity</code>
Model	<code>ResourceID</code> , <code>ResourceHeader</code> , <code>AccessInformation</code> + , <code>ProcessingLevel</code> {0,1} , <code>ProviderResourceName</code> {0,1} , <code>ProviderProcessingLevel</code> {0,1} , <code>ProviderVersion</code> {0,1} , <code>InstrumentID</code> * , <code>MeasurementType</code> + , <code>TemporalDescription</code> {0,1} , <code>SpectralRange</code> * , <code>ObservedRegion</code> * , <code>Caveats</code> {0,1} , <code>Keyword</code> * , <code>InputResourceID</code> * , <code>Parameter</code> * , <code>Extension</code> *
Children	<code>AccessInformation</code> , <code>Caveats</code> , <code>Extension</code> , <code>InputResourceID</code> , <code>InstrumentID</code> , <code>Keyword</code> , <code>MeasurementType</code> , <code>ObservedRegion</code> , <code>Parameter</code> , <code>ProcessingLevel</code> , <code>ProviderProcessingLevel</code> , <code>ProviderResourceName</code> , <code>ProviderVersion</code> , <code>ResourceHeader</code> , <code>ResourceID</code> , <code>SpectralRange</code> , <code>TemporalDescription</code>
Instance	<pre><NumericalData> <ResourceID>{1,1}</ResourceID> <ResourceHeader>{1,1}</ResourceHeader> <AccessInformation>{1,unbounded}</AccessInformation> <ProcessingLevel>{0,1}</ProcessingLevel> <ProviderResourceName>{0,1}</ProviderResourceName></pre>

	<pre><ProviderProcessingLevel>{0,1}</ProviderProcessingLevel> <ProviderVersion>{0,1}</ProviderVersion> <InstrumentID>{0,unbounded}</InstrumentID> <MeasurementType>{1,unbounded}</MeasurementType> <TemporalDescription>{0,1}</TemporalDescription> <SpectralRange>{0,unbounded}</SpectralRange> <ObservedRegion>{0,unbounded}</ObservedRegion> <Caveats>{0,1}</Caveats> <Keyword>{0,unbounded}</Keyword> <InputResourceID>{0,unbounded}</InputResourceID> <Parameter>{0,unbounded}</Parameter> <Extension>{0,unbounded}</Extension> </NumericalData></pre>
Source	<xsd:element name="NumericalData" type="NumericalData" substitutionGroup="ResourceEntity"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Document

Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class Document { ResourceID : xsd:string ResourceHeader : ResourceHeader AccessInformation : AccessInformation Keyword : xsd:string DocumentType : enumDocumentType InputResourceID : xsd:string } class Substitution Group { ResourceEntity : Abstract true } Document < -- ResourceEntity </pre>
Type	Document
Properties	content: complex
Substitution Group Affiliation	<ul style="list-style-type: none"> • ResourceEntity
Model	ResourceID , ResourceHeader , AccessInformation+ , Keyword* , DocumentType , InputResourceID*
Children	AccessInformation, DocumentType, InputResourceID, Keyword, ResourceHeader, ResourceID
Instance	<pre><Document> <ResourceID>{1,1}</ResourceID> <ResourceHeader>{1,1}</ResourceHeader> <AccessInformation>{1,unbounded}</AccessInformation> <Keyword>{0,unbounded}</Keyword> <DocumentType>{1,1}</DocumentType> <InputResourceID>{0,unbounded}</InputResourceID> </Document></pre>
Source	<xsd:element name="Document" type="Document" substitutionGroup="ResourceEntity"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element DocumentType


Namespace	http://www.spase-group.org/data/schema
Annotations	A characterization of the content or purpose of a document.
Diagram	<pre> classDiagram class DocumentType { Type : enumDocumentType } enumDocumentType < -- DocumentType </pre>

Type	enumDocumentType				
Properties	content: simple				
Facets	enumeration	Paper	A formal presentation of an idea or discovery typically more than a few pages in length.		
Used by	Complex Type	Document			
Source	<pre><xsd:element name="DocumentType" type="enumDocumentType"> <xsd:annotation> <xsd:documentation xml:lang="en">A characterization of the content or purpose of a document.</xsd:documentation> </xsd:annotation> </xsd:element></pre>				
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd				


Element Granule

Namespace	http://www.spase-group.org/data/schema		
Diagram			
Type	Granule		
Properties	content: complex		
Substitution Group Affiliation	<ul style="list-style-type: none"> ResourceEntity 		
Model	ResourceID , ReleaseDate , ExpirationDate{0,1} , ParentID , PriorID* , StartDate , StopDate , Source+		
Children	ExpirationDate, ParentID, PriorID, ReleaseDate, ResourceID, Source, StartDate, StopDate		
Instance	<pre><Granule> <ResourceID>{1,1}</ResourceID> <ReleaseDate>{1,1}</ReleaseDate> <ExpirationDate>{0,1}</ExpirationDate> <ParentID>{1,1}</ParentID> <PriorID>{0,unbounded}</PriorID> <StartDate>{1,1}</StartDate> <StopDate>{1,1}</StopDate> <Source>{1,unbounded}</Source> </Granule></pre>		
Source	<xsd:element name="Granule" type="Granule" substitutionGroup="ResourceEntity"/>		
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd		

Element ParentID

Namespace	http://www.spase-group.org/data/schema
Annotations	The resource identifier for a resource that a resource is a part of. The resource inherits the attributes of the referenced resource. Attributes defined in the resource override attributes of the parent in the manner prescribed by the containing resource.
Diagram	
Type	xsd:string
Properties	content: simple
Used by	Complex Type Granule
Source	<pre><xsd:element name="ParentID" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The resource identifier for a resource that a resource is a part of. The resource inherits the attributes of the referenced resource. Attributes defined in the resource override attributes of the parent in the manner prescribed by the containing resource.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd


Element StopDate

Namespace	http://www.spase-group.org/data/schema
Annotations	The specification of a stopping point in time.
Diagram	
Type	xsd:dateTime
Properties	content: simple
Substitution Group Affiliation	• StopDateEntity
Used by	Complex Types Granule, OperatingSpan
Source	<pre><xsd:element name="StopDate" type="xsd:dateTime" substitutionGroup="StopDateEntity"> <xsd:annotation> <xsd:documentation xml:lang="en">The specification of a stopping point in time.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Source

Namespace	http://www.spase-group.org/data/schema
-----------	--

Diagram



Type	Source
Properties	content: complex
Used by	Complex Type Granule
Model	SourceType , URL , MirrorURL* , Checksum{0,1} , DataExtent{0,1}
Children	Checksum, DataExtent, MirrorURL, SourceType, URL
Instance	<Source> <SourceType>{1,1}</SourceType> <URL>{1,1}</URL> <MirrorURL>{0..unbounded}</MirrorURL> <Checksum>{0,1}</Checksum> <DataExtent>{0,1}</DataExtent> </Source>
Source	<xsd:element name="Source" type="Source"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element SourceType

Namespace	http://www.spase-group.org/data/schema																	
Annotations	A characterization of the function or purpose of the source.																	
Diagram																		
Type	enumSourceType																	
Properties	content: simple																	
Facets	<table border="1"> <tr> <td>enumeration</td> <td>Ancillary</td> <td>A complementary item which can be subordinate, subsidiary, auxiliary, supplementary to the primary item.</td> </tr> <tr> <td>enumeration</td> <td>Browse</td> <td>A representation of an image which is suitable to reveal most or all of the details of the image.</td> </tr> <tr> <td>enumeration</td> <td>Data</td> <td>A collection of organized information, usually the results of experience, observation or experiment, or a set of premises. This may consist of numbers, words, or images, particularly as measurements or observations of a set of variables.</td> </tr> <tr> <td>enumeration</td> <td>Layout</td> <td>The structured arrangement of items in a collection.</td> </tr> <tr> <td>enumeration</td> <td>Thumbnail</td> <td>A small representation of an image which is suitable to infer what the full-sized image is like.</td> </tr> </table>			enumeration	Ancillary	A complementary item which can be subordinate, subsidiary, auxiliary, supplementary to the primary item.	enumeration	Browse	A representation of an image which is suitable to reveal most or all of the details of the image.	enumeration	Data	A collection of organized information, usually the results of experience, observation or experiment, or a set of premises. This may consist of numbers, words, or images, particularly as measurements or observations of a set of variables.	enumeration	Layout	The structured arrangement of items in a collection.	enumeration	Thumbnail	A small representation of an image which is suitable to infer what the full-sized image is like.
enumeration	Ancillary	A complementary item which can be subordinate, subsidiary, auxiliary, supplementary to the primary item.																
enumeration	Browse	A representation of an image which is suitable to reveal most or all of the details of the image.																
enumeration	Data	A collection of organized information, usually the results of experience, observation or experiment, or a set of premises. This may consist of numbers, words, or images, particularly as measurements or observations of a set of variables.																
enumeration	Layout	The structured arrangement of items in a collection.																
enumeration	Thumbnail	A small representation of an image which is suitable to infer what the full-sized image is like.																
Used by	Complex Type Source																	
Source	<xsd:element name="SourceType" type="enumSourceType"> <xsd:annotation>																	

	<pre> <xsd:documentation xml:lang="en">A characterization of the function or purpose of the source.</xsd:documentation> </xsd:annotation> </xsd:element> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element MirrorURL

Namespace	http://www.spase-group.org/data/schema
Annotations	A Uniform Resource Locator (URL) to an alternate location of a resource.
Diagram	<pre> classDiagram class MirrorURL { <<xsd:string>> } xsd:string MirrorURL "1" --> "1" xsd:string </pre>
Type	xsd:string
Properties	content: simple
Used by	Complex Type Source
Source	<pre> <xsd:element name="MirrorURL" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">A Uniform Resource Locator (URL) to an alternate location of a resource.</xsd:documentation> </xsd:annotation> </xsd:element> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Checksum

Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class Checksum { HashValue HashFunction } HashValue HashFunction Checksum "1" --> "1" HashValue Checksum "1" --> "1" HashFunction </pre>
Type	Checksum
Properties	content: complex
Used by	Complex Type Source
Model	HashValue , HashFunction
Children	HashFunction, HashValue
Instance	<pre> <Checksum> <HashValue>{1,1}</HashValue> <HashFunction>{1,1}</HashFunction> </Checksum> </pre>
Source	<xsd:element name="Checksum" type="Checksum" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element HashValue

Namespace	http://www.spase-group.org/data/schema
Annotations	The value calculated by a hash function, e.g. the message digest of a digital data object.
Diagram	<pre> classDiagram class HashValue { <<xsd:string>> } xsd:string HashValue "1" --> "1" xsd:string </pre>
Type	xsd:string
Properties	content: simple
Used by	Complex Type Checksum

Source	<pre><xsd:element name="HashValue" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The value calculated by a hash function, e.g. the message digest of a digital data object.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd


Element HashFunction

Namespace	http://www.spase-group.org/data/schema											
Annotations	A function or algorithm that converts a digital data object into a hash value. Typically the hash value is small and concise when compared to the digital data object.											
Diagram	<pre> classDiagram class HashFunction { <<enumHashFunction>> } class enumHashFunction HashFunction "1" -- "0..1" enumHashFunction </pre>											
Type	enumHashFunction											
Properties	content: simple											
Facets	<table> <tr> <td>enumeration</td> <td>MD5</td> <td>Message Digest 5 (MD5) is a 128-bit message digest algorithm created in 1991 by Professor Ronald Rivest.</td> </tr> <tr> <td>enumeration</td> <td>SHA1</td> <td>Secure Hash Algorithm (SHA), a 160-bit message digest algorithm developed by the NSA and described in Federal Information Processing Standard (FIPS) publication 180-1.</td> </tr> <tr> <td>enumeration</td> <td>SHA256</td> <td>Secure Hash Algorithm (SHA), a 256-bit message digest algorithm developed by the NSA and described in Federal Information Processing Standard (FIPS) publication 180-1.</td> </tr> </table>			enumeration	MD5	Message Digest 5 (MD5) is a 128-bit message digest algorithm created in 1991 by Professor Ronald Rivest.	enumeration	SHA1	Secure Hash Algorithm (SHA), a 160-bit message digest algorithm developed by the NSA and described in Federal Information Processing Standard (FIPS) publication 180-1.	enumeration	SHA256	Secure Hash Algorithm (SHA), a 256-bit message digest algorithm developed by the NSA and described in Federal Information Processing Standard (FIPS) publication 180-1.
enumeration	MD5	Message Digest 5 (MD5) is a 128-bit message digest algorithm created in 1991 by Professor Ronald Rivest.										
enumeration	SHA1	Secure Hash Algorithm (SHA), a 160-bit message digest algorithm developed by the NSA and described in Federal Information Processing Standard (FIPS) publication 180-1.										
enumeration	SHA256	Secure Hash Algorithm (SHA), a 256-bit message digest algorithm developed by the NSA and described in Federal Information Processing Standard (FIPS) publication 180-1.										
Used by	Complex Type	Checksum										
Source	<pre><xsd:element name="HashFunction" type="enumHashFunction"> <xsd:annotation> <xsd:documentation xml:lang="en">A function or algorithm that converts a digital data object into a hash value. Typically the hash value is small and concise when compared to the digital data object.</xsd:documentation> </xsd:annotation> </xsd:element></pre>											
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd											

Element Instrument

Namespace	http://www.spase-group.org/data/schema
-----------	--

Diagram



Type	Instrument
Properties	content: complex
Substitution Group Affiliation	<ul style="list-style-type: none"> • ResourceEntity
Model	ResourceID , ResourceHeader , InstrumentType+ , InvestigationName+ , OperatingSpan{0,1} , ObservatoryID , Caveats{0,1} , Extension*
Children	Caveats, Extension, InstrumentType, InvestigationName, ObservatoryID, OperatingSpan, ResourceHeader, ResourceID
Instance	<pre> <Instrument> <ResourceID>{1,1}</ResourceID> <ResourceHeader>{1,1}</ResourceHeader> <InstrumentType>{1,unbounded}</InstrumentType> <InvestigationName>{1,unbounded}</InvestigationName> <OperatingSpan>{0,1}</OperatingSpan> <ObservatoryID>{1,1}</ObservatoryID> <Caveats>{0,1}</Caveats> <Extension>{0,unbounded}</Extension> </Instrument> </pre>
Source	<xsd:element name="Instrument" type="Instrument" substitutionGroup="ResourceEntity" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element InstrumentType

Namespace	http://www.spase-group.org/data/schema		
Annotations	A characterization of an integrated collection of software and hardware containing one or more sensors and associated controls used to produce data on an environment.		
Diagram			
Type	enumInstrumentType		
Properties	content: simple		
Facets	enumeration	Antenna	A sensor used to measure electric potential.
	enumeration	Channeltron	An instrument that detects electrons, ions, and UV-radiation, according to the principle of a secondary emission multiplier. It is typically used in electron spectroscopy and mass spectrometry.

enumeration	Coronograph	An instrument which can image things very close to the Sun by using a disk to block the Sun's bright surface which reveals the faint solar corona and other celestial objects.
enumeration	DoubleSphere	A dipole antenna of which the active (sensor) elements are small spheres located at the ends of two wires deployed in the equatorial plane, on opposite sides of a spinning spacecraft.
enumeration	DustDetector	An instrument which determines the mass and speed of ambient dust particles.
enumeration	ElectronDriftInstrument	An active experiment to measure the electron drift velocity based on sensing the displacement of a weak beam of electrons after one gyration in the ambient magnetic field.
enumeration	ElectrostaticAnalyser	An instrument which uses charged plates to analyze the mass, charge and kinetic energies of charged particles which enter the instrument.
enumeration	EnergeticParticleInstrument	An instrument that measures fluxes of charged particles as a function of time, direction of motion, mass, charge and/or species.
enumeration	FaradayCup	An instrument consisting of an electrode from which electrical current is measured while a charged particle beam (electrons or ions) impinges on it. Used to determine energy spectrum and sometimes ion composition of the impinging particles.
enumeration	FluxFeedback	A search coil whose bandwidth and signal/noise ratio are increased by the application of negative feedback at the sensor (flux) level by driving a collocated coil with a signal from the preamplifier.
enumeration	FourierTransformSpectrometer	An instrument that determines the spectra of a radiative source, using time-domain measurements and a Fourier transform.
enumeration	GeigerMuellerTube	An instrument which measures density of ionizing radiation based on interactions with a gas.
enumeration	Imager	An instrument which samples the radiation from an area at one or more spectral ranges emitted or reflected by an object.
enumeration	ImagingSpectrometer	An instrument which is a multispectral scanner with a very large number of channels (64-256 channels) with very narrow band widths.
enumeration	Interferometer	An instrument to study the properties of two or more waves from the pattern of interference created by their superposition.
enumeration	IonChamber	A device in which the collected electrical charge from ionization in a gas-filled cavity is taken to be the proportion to some parameter (e.g. dose or exposure) of radiation field
enumeration	IonDrift	A device which measures the current produced by the displacement of ambient ions on a grid, thereby allowing the determination of the ion trajectory and velocity.
enumeration	LangmuirProbe	A monopole antenna associated with an instrument.


		The instrument applies a potential to the antenna which is swept to determine the voltage/current characteristic. This provides information about the plasma surrounding the probe and spacecraft.
enumeration	LongWire	A dipole antenna whose active (sensor) elements are two wires deployed in the equatorial plane on opposite sides of a spinning spacecraft, and whose length is several times greater than the spacecraft diameter.
enumeration	Magnetometer	An instrument which measures the ambient magnetic field.
enumeration	MassSpectrometer	An instrument which distinguishes chemical species in terms of their different isotopic masses.
enumeration	MicrochannelPlate	An instrument used for the detection of elementary particles, ions, ultraviolet rays and soft X-rays constructed from very thin conductive glass capillaries.
enumeration	MultispectralImager	An instrument which captures images at multiple spectral ranges.
enumeration	NeutralAtomImager	An instrument which measures the quantity and properties of neutral particles over a range of angles. Measured properties can include mass and energy.
enumeration	NeutralParticleDetector	An instrument which measures the quantity and properties of neutral particles. Measured properties can include mass and plasma bulk densities.
enumeration	ParticleCorrelator	An instrument which correlates particle flux to help identify wave/particle interactions.
enumeration	ParticleDetector	An instrument which detects particle flux!!!
enumeration	Photometer	An instrument which measures the strength of electromagnetic radiation within a spectral band which can range from ultraviolet to infrared and includes the visible spectrum.
enumeration	Photopolarimeter	An instrument which measures the intensity and polarization or radiant energy. A photopolarimeter is a combination of a photometer and a polarimeter.
enumeration	Platform	A collection of components which can be positioned and oriented as a single unit. A platform may contain other platforms. For example, a spacecraft is a platform which may have components that can be articulated and are also considered platforms.
enumeration	ProportionalCounter	An instrument which measures energy of ionization radiation based on interactions with a gas.
enumeration	QuadrисphericalAnalyser	An instrument used for the 3-D detection of plasma, energetic electrons and ions, and for positive-ion composition measurements.
enumeration	Radar	An instrument that uses directional properties of returned power to infer spatial and/or other characteristics of a remote object.
enumeration	Radiometer	An instrument for detecting or measuring radiant energy. Radiometers are commonly limited to infrared radiation.

	enumeration	ResonanceSounder	A combination of a radio receiver and a pulsed transmitter used to study the plasma surrounding a spacecraft by identifying resonances or cut-offs (of the wave dispersion relation), whose frequencies are related to the ambient plasma density and magnetic field. When the transmitter is off it is essentially a high frequency-resolution spectral power receiver.
	enumeration	RetardingPotentialAnalyser	An instrument which measures ion temperatures and ion concentrations using a planar ion trap.
	enumeration	Riometer	An instrument which measure the signal strength in various directions of the galactic radio signals. Variations in these signals are influenced by solar flare activity and geomagnetic storm and substorm processes.
	enumeration	ScintillationDetector	An instrument which detects flourescences of a material which is excited by high energy (ionizing) electromagnetic or charged particle radiation.
	enumeration	SearchCoil	An instrument which measures the time variation of the magnetic flux threading a loop by measurement of the electric potential difference induced between the ends of the wire.
	enumeration	Sounder	An instrument which measures the radiances from an object. A sounder may measure radiances at multiple spectral ranges.
	enumeration	SpacecraftPotentialControl	An instrument to control the electric potential of a spacecraft with respect to the ambient plasma by emitting a variable current of positive ions.
	enumeration	SpectralPowerReceiver	A radio receiver which determines the power spectral density of the electric or magnetic field, or both, at one or more frequencies.
	enumeration	Spectrometer	An instrument that measures the component wavelengths of light (or other electromagnetic radiation) by splitting the light up into its component wavelengths.
	enumeration	TimeOfFlight	An instrument which measures the time it takes for a particle to travel between two detectors.
	enumeration	Unspecified	A value which is not provided.
	enumeration	WaveformReceiver	A radio receiver which outputs the value of one or more components of the electric and/or magnetic field as a function of time.
Used by	Complex Type	Instrument	
Source	<xsd:element name="InstrumentType" type="enumInstrumentType"> <xsd:annotation> <xsd:documentation xml:lang="en">A characterization of an integrated collection of software and hardware containing one or more sensors and associated controls used to produce data on an environment.</xsd:documentation> </xsd:annotation> </xsd:element>		
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd		

Element InvestigationName

Namespace	http://www.spase-group.org/data/schema
Annotations	The name given to the contract or engagement which enabled the data to be produced. Each investigation is associated with a Principal Investigator or Guest Investigator who was responsible for the original proposal. For single PI missions each major subsystem having its own identified Team Leader may also be classed as an "Investigation" for the purposes of data archiving.
Diagram	
Type	xsd:string
Properties	content: simple
Used by	Complex Type Instrument
Source	<pre><xsd:element name="InvestigationName" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The name given to the contract or engagement which enabled the data to be produced. Each investigation is associated with a Principal Investigator or Guest Investigator who was responsible for the original proposal. For single PI missions each major subsystem having its own identified Team Leader may also be classed as an "Investigation" for the purposes of data archiving.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element OperatingSpan

Namespace	http://www.spase-group.org/data/schema
Diagram	
Type	OperatingSpan
Properties	content: complex
Used by	Complex Types Instrument, Observatory
Model	StartDate , StopDate{0,1} , Note*
Children	Note, StartDate, StopDate
Instance	<pre><OperatingSpan> <StartDate>{1,1}</StartDate> <StopDate>{0,1}</StopDate> <Note>{0..unbounded}</Note> </OperatingSpan></pre>
Source	<xsd:element name="OperatingSpan" type="OperatingSpan" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ObservatoryID

Namespace	http://www.spase-group.org/data/schema
Annotations	The identifier of an Observatory resource.
Diagram	

Type	xsd:string
Properties	content: simple
Used by	Complex Type Instrument
Source	<pre><xsd:element name="ObservatoryID" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The identifier of an Observatory resource.</ xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Observatory

Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class Observatory { ResourceID : xsd:string ResourceHeader : ResourceHeader ObservatoryGroupID : xsd:string Location : Location OperatingSpan : OperatingSpan Extension : xsd:string } class ResourceEntity { Abstract : true } Observatory < -- ResourceEntity </pre>
Type	Observatory
Properties	content: complex
Substitution Group Affiliation	• ResourceEntity
Model	ResourceID , ResourceHeader , ObservatoryGroupID* , Location , OperatingSpan{0,1} , Extension*
Children	Extension, Location, ObservatoryGroupID, OperatingSpan, ResourceHeader, ResourceID
Instance	<pre> <Observatory> <ResourceID>{1,1}</ResourceID> <ResourceHeader>{1,1}</ResourceHeader> <ObservatoryGroupID>{0,unbounded}</ObservatoryGroupID> <Location>{1,1}</Location> <OperatingSpan>{0,1}</OperatingSpan> <Extension>{0,unbounded}</Extension> </Observatory> </pre>
Source	<xsd:element name="Observatory" type="Observatory" substitutionGroup="ResourceEntity"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ObservatoryGroupID

Namespace	http://www.spase-group.org/data/schema
Annotations	The identifier of an Observatory resource which the referring resource is a member of.
Diagram	<pre> classDiagram class ObservatoryGroupID { <-- xsd:string } </pre>
Type	xsd:string
Properties	content: simple

Used by	Complex Type Observatory
Source	<pre><xsd:element name="ObservatoryGroupID" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The identifier of an Observatory resource which the referring resource is a member of.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Location

Namespace	http://www.spase-group.org/data/schema
Diagram	
Type	Location
Properties	content: complex
Used by	Complex Type Observatory
Model	ObservatoryRegion+, CoordinateSystemName{0,1} , Latitude{0,1} , Longitude{0,1} , Elevation{0,1}
Children	CoordinateSystemName, Elevation, Latitude, Longitude, ObservatoryRegion
Instance	<pre><Location> <ObservatoryRegion>{1,unbounded}</ObservatoryRegion> <CoordinateSystemName>{0,1}</CoordinateSystemName> <Latitude>{0,1}</Latitude> <Longitude>{0,1}</Longitude> <Elevation>{0,1}</Elevation> </Location></pre>
Source	<xsd:element name="Location" type="Location" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ObservatoryRegion

Namespace	http://www.spase-group.org/data/schema									
Annotations	A spatial location distinguished by certain natural features or physical characteristics where an observatory is located.									
Diagram										
Type	enumRegion									
Properties	content: simple									
Facets	<table> <tr> <td>enumeration</td> <td>Asteroid</td> <td>A small extraterrestrial body consisting mostly of rock and metal that is in orbit around the sun.</td> </tr> <tr> <td>enumeration</td> <td>Comet</td> <td>A relatively small extraterrestrial body consisting of a frozen mass that travels around the sun in a highly elliptical orbit.</td> </tr> <tr> <td>enumeration</td> <td>Earth</td> <td>The third planet from the sun in our solar system.</td> </tr> </table>	enumeration	Asteroid	A small extraterrestrial body consisting mostly of rock and metal that is in orbit around the sun.	enumeration	Comet	A relatively small extraterrestrial body consisting of a frozen mass that travels around the sun in a highly elliptical orbit.	enumeration	Earth	The third planet from the sun in our solar system.
enumeration	Asteroid	A small extraterrestrial body consisting mostly of rock and metal that is in orbit around the sun.								
enumeration	Comet	A relatively small extraterrestrial body consisting of a frozen mass that travels around the sun in a highly elliptical orbit.								
enumeration	Earth	The third planet from the sun in our solar system.								

enumeration	Earth.Magnetosheath	The region between the bow shock and the magnetopause, characterized by very turbulent plasma.
enumeration	Earth.Magnetosphere	The region of space above the atmosphere or surface of the planet, and bounded by the magnetopause, that is under the direct influence of the planets magnetic field.
enumeration	Earth.Magnetosphere.Magnetotail	The region on the night side of the body where the magnetic field is stretched backwards by the force of the solar wind. For Earth, the magnetotail begins at a night-side radial distance of 10 Re ($X > -10Re$).
enumeration	Earth.Magnetosphere.Main	The region of the magnetosphere where the magnetic field lines are closed, but does not include the gaseous region gravitationally bound to the body.
enumeration	Earth.Magnetosphere.Polar	The region near the pole of a body. For a magnetosphere the polar region is the area where magnetic field lines are open and includes the auroral zone.
enumeration	Earth.Magnetosphere.RadiationBelt	The region within a magnetosphere where high-energy particles could potentially be trapped in a magnetic field.
enumeration	Earth.NearSurface	The gaseous and possibly ionized environment of a body extending from the surface to some specified altitude. For the Earth, this altitude is 2000 km.
enumeration	Earth.NearSurface.Atmosphere	The neutral gases surrounding a body that extends from the surface and is bound to the body by virtue of the gravitational attraction.
enumeration	Earth.NearSurface.AuroralRegion	The region in the atmospheric where electrically-charged particles bombarding the upper atmosphere of a planet in the presence of a magnetic field produce an optical phenomenon.
enumeration	Earth.NearSurface.EquatorialRegion	A ring centered on the equator and limited in latitude by approximately 23 degrees north and south of the equator.
enumeration	Earth.NearSurface.Ionosphere	The charged or ionized gases surrounding a body that are nominally bound to the body by virtue of the gravitational attraction.
enumeration	Earth.NearSurface.IonosphereDRegion	The D Region of the ionosphere that exists approximately 50 to 95 km above the surface of the Earth. One of several layers in the ionosphere.
enumeration	Earth.NearSurface.IonosphereERegion	The E Region gas occurring at 90-150km above the ground. One of several layers in the ionosphere. Also called the The Kennelly-Heaviside layer.
enumeration	Earth.NearSurface.IonosphereFRegion	The F Region contains ionized gases at a height of around 150-800 km above sea level, placing it in the thermosphere. the F region has the highest concentration of free electrons and ions anywhere in the atmosphere. It may be thought of as comprising two layers, the F1- and F2-layers. One of several layers in the ionosphere. Also known as the Appleton layer.
enumeration	Earth.NearSurface.IonosphereFRegion	The F Region is the upper most areas of the ionosphere.

enumeration	Earth.NearSurface.Mesosphere	The layer of the atmosphere that extends from the Stratosphere to a range of 80 km to 85 km, temperature decreasing with height.
enumeration	Earth.NearSurface.Plasmasphere	A region of the magnetosphere consisting of low energy (cool) plasma. It is located above the ionosphere. The outer boundary of the plasmasphere is known as the plasmapause, which is defined by an order of magnitude drop in plasma density.
enumeration	Earth.NearSurface.PolarCap	The areas of the globe surrounding the poles and consisting of the region north of 60 degrees north latitude and the region south of 60 degrees south latitude.
enumeration	Earth.NearSurface.SouthAtlanticAnomalyRegion	The inner van Allen radiation belt makes its closest approach to the planets surface. The result is that, for a given altitude, the radiation intensity is higher over this region than elsewhere.
enumeration	Earth.NearSurface.Stratosphere	The layer of the atmosphere that extends from the troposphere to about 30 km, temperature increases with height. The stratosphere contains the ozone layer.
enumeration	Earth.NearSurface.Thermosphere	The layer of the atmosphere that extends from the Mesosphere to 640+ km, temperature increasing with height.
enumeration	Earth.NearSurface.Troposphere	The lowest layer of the atmosphere which begins at the surface and extends to between 7 km (4.4 mi) at the poles and 17 km (10.6 mi) at the equator, with some variation due to weather factors.
enumeration	Earth.Surface	The outermost area of a solid object.
enumeration	Heliosphere	The solar atmosphere extending roughly from the outer corona to the edge of the solar plasma at the heliopause separating primarily solar plasma from interstellar plasma.
enumeration	Heliosphere.Heliosheath	The region extending radially outward from the heliospheric termination shock and in which the decelerated solar wind plasma is still significant.
enumeration	Heliosphere.Inner	The region of the heliosphere extending radially outward from the solar coronal base to just inside 1 AU.
enumeration	Heliosphere.NearEarth	The heliospheric region near the Earth which extends to and includes the area near the L1 and L2 Lagrange point.
enumeration	Heliosphere.Outer	The region of the heliosphere extending radially outward from just outside 1 AU to the heliospheric termination shock.
enumeration	Heliosphere.RemoteAU	A roughly toroidal region that includes the Earth's orbit, but exclusive of the region near the Earth.
enumeration	Interstellar	The region between stars outside of the stars heliopause.
enumeration	Jupiter	The fifth planet from the sun in our solar system.
enumeration	Mars	The forth planet from the sun in our solar system.
enumeration	Mercury	The first planet from the sun in our solar

		system.
enumeration	Neptune	The seventh planet from the sun in our solar system.
enumeration	Pluto	The ninth (sub)planet from the sun in our solar system.
enumeration	Saturn	The sixth planet from the sun in our solar system.
enumeration	Sun	The star upon which our solar system is centered.
enumeration	Sun.Chromosphere	The region of the Suns (or a stars) atmosphere above the temperature minimum and below the Transition Region. The solar chromosphere is approximately 400 km to 2100 km above the photosphere, and characterized by temperatures from 4500 - 28000 K.
enumeration	Sun.Corona	The outermost atmospheric region of the Sun or a star, characterized by ionization temperatures above 10^5 K. The solar corona starts at about 2100 km above the photosphere; there is no generally defined upper limit.
enumeration	Sun.Interior	The region inside the body which is not visible from outside the body.
enumeration	Sun.Photosphere	The atmospheric layer of the Sun or a star from which continuum radiation, especially optical, is emitted to space. For the Sun, the photosphere is about 500 km thick.
enumeration	Sun.TransitionRegion	A very narrow (<100 km) layer between the chromosphere and the corona where the temperature rises abruptly from about 8000 to about 500,000 K.
enumeration	Uranus	The eighth planet from the sun in our solar system.
enumeration	Venus	The second planet from the sun in our solar system.
Used by	Complex Type	Location
Source	<xsd:element name="ObservatoryRegion" type="enumRegion"> <xsd:annotation> <xsd:documentation xml:lang="en">A spatial location distinguished by certain natural features or physical characteristics where an observatory is located.</xsd:documentation> </xsd:annotation> </xsd:element>	
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd	

Element Latitude

Namespace	http://www.spase-group.org/data/schema	
Annotations	The angular distance north (positive) or south (negative) from the equator, measured along the meridian passing through the point.	
Diagram	<pre> classDiagram class Latitude { <<Latitude>> <<Type xsd:double>> } Latitude "0..1" -- "1..1" xsd:double </pre>	
Type	xsd:double	
Properties	content: simple	
Used by	Complex Type	Location
Source	<xsd:element name="Latitude" type="xsd:double"> <xsd:annotation> <xsd:documentation xml:lang="en">The angular distance north (positive) or south (negative) from the equator, measured along the meridian passing through the point.</xsd:documentation>	

	</xsd:annotation> </xsd:element>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Longitude

Namespace	http://www.spase-group.org/data/schema
Annotations	The angular distance measured west (positive) or east (negative) from a north-south line called the Prime Meridian.
Diagram	
Type	xsd:double
Properties	content: simple
Used by	Complex Type Location
Source	<pre><xsd:element name="Longitude" type="xsd:double"> <xsd:annotation> <xsd:documentation xml:lang="en">The angular distance measured west (positive) or east (negative) from a north-south line called the Prime Meridian.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd


Element Elevation

Namespace	http://www.spase-group.org/data/schema
Annotations	The distance in meters above (positive) or below (negative) the "zero elevation" defined by the World Geodetic System reference frame (WGS84).
Diagram	
Type	xsd:double
Properties	content: simple
Used by	Complex Type Location
Source	<pre><xsd:element name="Elevation" type="xsd:double"> <xsd:annotation> <xsd:documentation xml:lang="en">The distance in meters above (positive) or below (negative) the "zero elevation" defined by the World Geodetic System reference frame (WGS84).</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Person

Namespace	http://www.spase-group.org/data/schema
-----------	--

Diagram



Type	Person
Properties	content: complex
Substitution Group Affiliation	<ul style="list-style-type: none"> • ResourceEntity
Model	ResourceID , ReleaseDate{0,1} , PersonName{0,1} , OrganizationName , Address{0,1} , Email* , PhoneNumber* , FaxNumber{0,1} , Note{0,1} , Extension*
Children	Address, Email, Extension, FaxNumber, Note, OrganizationName, PersonName, PhoneNumber, ReleaseDate, ResourceID
Instance	<Person> <ResourceID>{1,1}</ResourceID> <ReleaseDate>{0,1}</ReleaseDate> <PersonName>{0,1}</PersonName> <OrganizationName>{1,1}</OrganizationName> <Address>{0,1}</Address> <Email>{0,unbounded}</Email> <PhoneNumber>{0,unbounded}</PhoneNumber> <FaxNumber>{0,1}</FaxNumber> <Note>{0,1}</Note> <Extension>{0,unbounded}</Extension> </Person>
Source	<xsd:element name="Person" type="Person" substitutionGroup="ResourceEntity"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element PersonName

Namespace	http://www.spase-group.org/data/schema
Annotations	The words used to address an individual.
Diagram	
Type	xsd:string
Properties	content: simple
Used by	Complex Type Person

Source	<pre><xsd:element name="PersonName" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The words used to address an individual.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element OrganizationName

Namespace	http://www.spase-group.org/data/schema
Annotations	A unit within a company or other entity (e.g., Government agency or branch of service) within which many projects are managed as a whole.
Diagram	<pre> classDiagram class OrganizationName { <<xsd:string>> } OrganizationName < -- xsd:string </pre>
Type	xsd:string
Properties	content: simple
Used by	Complex Type Person
Source	<pre><xsd:element name="OrganizationName" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">A unit within a company or other entity (e.g., Government agency or branch of service) within which many projects are managed as a whole.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Address

Namespace	http://www.spase-group.org/data/schema
Annotations	Directions for finding some location; written on letters or packages that are to be delivered to that location.
Diagram	<pre> classDiagram class Address { <<xsd:string>> } Address < -- xsd:string </pre>
Type	xsd:string
Properties	content: simple
Used by	Complex Type Person
Source	<pre><xsd:element name="Address" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">Directions for finding some location; written on letters or packages that are to be delivered to that location.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Email

Namespace	http://www.spase-group.org/data/schema
Annotations	The electronic address at which the individual may be contacted expressed in the form "local-part@domain".
Diagram	<pre> classDiagram class Email { <<xsd:string>> } Email < -- xsd:string </pre>
Type	xsd:string
Properties	content: simple
Used by	Complex Type Person

Source	<pre><xsd:element name="Email" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The electronic address at which the individual may be contacted expressed in the form "local-part@domain".</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element PhoneNumber

Namespace	http://www.spase-group.org/data/schema
Annotations	The symbols and numerals required to contact an individual by telephone. The string may contain punctuation marks such as dash (-) or dot (.) to separate fields within the string.
Diagram	
Type	xsd:string
Properties	content: simple
Used by	Complex Type Person
Source	<pre><xsd:element name="PhoneNumber" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The symbols and numerals required to contact an individual by telephone. The string may contain punctuation marks such as dash (-) or dot (.) to separate fields within the string.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element FaxNumber

Namespace	http://www.spase-group.org/data/schema
Annotations	The symbols and numerals required to send a facsimile (FAX) to an individual by telephone. The string may contain punctuation marks such as dash (-) or dot (.) to separate fields within the string.
Diagram	
Type	xsd:string
Properties	content: simple
Used by	Complex Type Person
Source	<pre><xsd:element name="FaxNumber" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The symbols and numerals required to send a facsimile (FAX) to an individual by telephone. The string may contain punctuation marks such as dash (-) or dot (.) to separate fields within the string.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Registry

Namespace	http://www.spase-group.org/data/schema
-----------	--


Diagram	<pre> classDiagram class Registry { ResourceID : xsd:string ResourceHeader : ResourceHeader AccessURL : AccessURL Extension : Extension * (0..) } Registry < -- Registry Registry < -- Substitution Group "ResourceEntity" Registry < -- Substitution Group "ResourceEntity" </pre>
Type	Registry
Properties	content: complex
Substitution Group Affiliation	• ResourceEntity
Model	ResourceID , ResourceHeader , AccessURL , Extension*
Children	AccessURL, Extension, ResourceHeader, ResourceID
Instance	<pre> <Registry> <ResourceID>{1,1}</ResourceID> <ResourceHeader>{1,1}</ResourceHeader> <AccessURL>{1,1}</AccessURL> <Extension>{0,unbounded}</Extension> </Registry> </pre>
Source	<xsd:element name="Registry" type="Registry" substitutionGroup="ResourceEntity"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Repository

Namespace	http://www.spase-group.org/data/schema
Diagram	<pre> classDiagram class Repository { ResourceID : xsd:string ResourceHeader : ResourceHeader AccessURL : AccessURL Extension : Extension * (0..) } Repository < -- Repository Repository < -- Substitution Group "ResourceEntity" Repository < -- Substitution Group "ResourceEntity" </pre>
Type	Repository
Properties	content: complex
Substitution Group Affiliation	• ResourceEntity
Model	ResourceID , ResourceHeader , AccessURL , Extension*
Children	AccessURL, Extension, ResourceHeader, ResourceID
Instance	<pre> <Repository> <ResourceID>{1,1}</ResourceID> <ResourceHeader>{1,1}</ResourceHeader> <AccessURL>{1,1}</AccessURL> <Extension>{0,unbounded}</Extension> </Repository> </pre>

Source	<xsd:element name="Repository" type="Repository" substitutionGroup="ResourceEntity" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd


Element Service

Namespace	http://www.spase-group.org/data/schema
Diagram	
Type	Service
Properties	content: complex
Substitution Group Affiliation	• ResourceEntity
Model	ResourceID , ResourceHeader , AccessURL , Extension*
Children	AccessURL, Extension, ResourceHeader, ResourceID
Instance	<pre> <Service> <ResourceID>{1,1}</ResourceID> <ResourceHeader>{1,1}</ResourceHeader> <AccessURL>{1,1}</AccessURL> <Extension>{0,unbounded}</Extension> </Service> </pre>
Source	<xsd:element name="Service" type="Service" substitutionGroup="ResourceEntity" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element Annotation

Namespace	http://www.spase-group.org/data/schema
-----------	--

Diagram



Type	Annotation
Properties	content: complex
Substitution Group Affiliation	• ResourceEntity
Model	ResourceID , ResourceHeader , ImageURL{0,1} , AnnotationType , PhenomenonType{0,1} , ClassificationMethod{0,1} , ConfidenceRating{0,1} , TimeSpan* , ObservationExtent* , Extension*
Children	AnnotationType, ClassificationMethod, ConfidenceRating, Extension, ImageURL, ObservationExtent, PhenomenonType, ResourceHeader, ResourceID, TimeSpan
Instance	<pre> <Annotation> <ResourceID>{1,1}</ResourceID> <ResourceHeader>{1,1}</ResourceHeader> <ImageURL>{0,1}</ImageURL> <AnnotationType>{1,1}</AnnotationType> <PhenomenonType>{0,1}</PhenomenonType> <ClassificationMethod>{0,1}</ClassificationMethod> <ConfidenceRating>{0,1}</ConfidenceRating> <TimeSpan>{0,unbounded}</TimeSpan> <ObservationExtent>{0,unbounded}</ObservationExtent> <Extension>{0,unbounded}</Extension> </Annotation> </pre>
Source	<xsd:element name="Annotation" type="Annotation" substitutionGroup="ResourceEntity" />
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element ImageURL

Namespace	http://www.spase-group.org/data/schema
Annotations	A URL to graphic, image or movie.
Diagram	<pre> ImageURL : xsd:string --o--> xsd:string </pre>
Type	xsd:string
Properties	content: simple
Used by	Complex Type Annotation

Source	<pre><xsd:element name="ImageURL" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">A URL to graphic, image or movie.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element AnnotationType


Namespace	http://www.spase-group.org/data/schema											
Annotations	A classification for an annotation.											
Diagram	<pre> graph LR AT[AnnotationType Type enumAnnotationType] --> EAT[enumAnnotationType] style AT fill:#e0f2e0,stroke:#3399cc,stroke-width:1px style EAT fill:#fff,stroke:#3399cc,stroke-width:1px </pre>											
Type	enumAnnotationType											
Properties	content: simple											
Facets	<table> <tr> <td>enumeration</td> <td>Anomaly</td> <td>An interval where measurements or observations may be adversely affected.</td> </tr> <tr> <td>enumeration</td> <td>Event</td> <td>An action or observation which occurs at a point in time.</td> </tr> <tr> <td>enumeration</td> <td>Feature</td> <td>A prominent or distinctive characteristic that occurs at a location or persists over a period of time.</td> </tr> </table>			enumeration	Anomaly	An interval where measurements or observations may be adversely affected.	enumeration	Event	An action or observation which occurs at a point in time.	enumeration	Feature	A prominent or distinctive characteristic that occurs at a location or persists over a period of time.
enumeration	Anomaly	An interval where measurements or observations may be adversely affected.										
enumeration	Event	An action or observation which occurs at a point in time.										
enumeration	Feature	A prominent or distinctive characteristic that occurs at a location or persists over a period of time.										
Used by	Complex Type	Annotation										
Source	<pre><xsd:element name="AnnotationType" type="enumAnnotationType"> <xsd:annotation> <xsd:documentation xml:lang="en">A classification for an annotation.</xsd:documentation> </xsd:annotation> </xsd:element></pre>											
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd											

Element ClassificationMethod


Namespace	http://www.spase-group.org/data/schema											
Annotations	The technique used to determine the characteristics of an object.											
Diagram	<pre> graph LR CM[ClassificationMethod Type enumClassificationMethod] --> ECM[enumClassificationMethod] style CM fill:#e0f2e0,stroke:#3399cc,stroke-width:1px style ECM fill:#fff,stroke:#3399cc,stroke-width:1px </pre>											
Type	enumClassificationMethod											
Properties	content: simple											
Facets	<table> <tr> <td>enumeration</td> <td>Automatic</td> <td>Determined by the analysis or assessment performed by a program or server.</td> </tr> <tr> <td>enumeration</td> <td>Inferred</td> <td>Determined by the analysis of other information or resources.</td> </tr> <tr> <td>enumeration</td> <td>Inspection</td> <td>Determined by the analysis or assessment performed by a person.</td> </tr> </table>			enumeration	Automatic	Determined by the analysis or assessment performed by a program or server.	enumeration	Inferred	Determined by the analysis of other information or resources.	enumeration	Inspection	Determined by the analysis or assessment performed by a person.
enumeration	Automatic	Determined by the analysis or assessment performed by a program or server.										
enumeration	Inferred	Determined by the analysis of other information or resources.										
enumeration	Inspection	Determined by the analysis or assessment performed by a person.										
Used by	Complex Type	Annotation										
Source	<pre><xsd:element name="ClassificationMethod" type="enumClassificationMethod"> <xsd:annotation> <xsd:documentation xml:lang="en">The technique used to determine the characteristics of an object.</xsd:documentation> </xsd:annotation> </xsd:element></pre>											
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd											

Element ConfidenceRating

Namespace	http://www.spase-group.org/data/schema
-----------	--

Annotations	A classification of the certainty of an assertion.		
Diagram			
Type	enumConfidenceRating		
Properties	content: simple		
Facets	enumeration	Probable	Likely given the available evidence. Considered in the range of 4-7 on a scale of 0-10.
	enumeration	Strong	Highly likely given the available evidence. Considered in the range of 7-10 on a scale of 0-10.
	enumeration	Unlikely	Not likely given the available evidence. Considered in the range of 0 on a scale of 0-10.
	enumeration	Weak	Slightly likely given the available evidence. Considered in the range of 1-4 on a scale of 0-10.
Used by	Complex Type	Annotation	
Source	<xsd:element name="ConfidenceRating" type="enumConfidenceRating"> <xsd:annotation> <xsd:documentation xml:lang="en">A classification of the certainty of an assertion.</xsd:documentation> </xsd:annotation> </xsd:element>		
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd		

Element ObservationExtent

Namespace	http://www.spase-group.org/data/schema		
Diagram			
Type	ObservationExtent		
Properties	content: complex		
Used by	Complex Type	Annotation	
Model	ObservedRegion{0,1} , StartLocation , StopLocation , Note*		
Children	Note, ObservedRegion, StartLocation, StopLocation		
Instance	<ObservationExtent> <ObservedRegion>{0,1}</ObservedRegion> <StartLocation>{1,1}</StartLocation> <StopLocation>{1,1}</StopLocation> <Note>{0,unbounded}</Note> </ObservationExtent>		
Source	<xsd:element name="ObservationExtent" type="ObservationExtent" />		
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd		

Element StartLocation

Namespace	http://www.spase-group.org/data/schema		
Annotations	The initial position in space.		

Diagram	A UML class diagram fragment showing a class 'StartLocation' with a 'Type' association to 'xsd:string'. The 'xsd:string' type is represented by a rounded rectangle with a purple border.
Type	xsd:string
Properties	content: simple
Used by	Complex Type ObservationExtent
Source	<pre><xsd:element name="StartLocation" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The initial position in space.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element StopLocation

Namespace	http://www.spase-group.org/data/schema
Annotations	The final position in space.
Diagram	A UML class diagram fragment showing a class 'StopLocation' with a 'Type' association to 'xsd:string'. The 'xsd:string' type is represented by a rounded rectangle with a purple border.
Type	xsd:string
Properties	content: simple
Used by	Complex Type ObservationExtent
Source	<pre><xsd:element name="StopLocation" type="xsd:string"> <xsd:annotation> <xsd:documentation xml:lang="en">The final position in space.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Element RelativeStopDate

Namespace	http://www.spase-group.org/data/schema
Annotations	An indication of the nominal end date relative to the present.
Diagram	A UML class diagram fragment showing a class 'RelativeStopDate' with a 'Type' association to 'xsd:duration'. A 'Substitution Group' box contains an abstract class 'StopDateEntity' with an 'Abstract true' note. There is also a direct association from 'RelativeStopDate' to 'xsd:duration'.
Type	xsd:duration
Properties	content: simple
Substitution Group Affiliation	• StopDateEntity
Source	<pre><xsd:element name="RelativeStopDate" type="xsd:duration" substitutionGroup="StopDateEntity"> <xsd:annotation> <xsd:documentation xml:lang="en">An indication of the nominal end date relative to the present.</xsd:documentation> </xsd:annotation> </xsd:element></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Types

Complex Type Spase

Namespace	http://www.spase-group.org/data/schema
-----------	--

Annotations	Space Physics Archive Search and Extract (SPASE). The outermost container or envelope for SPASE metadata. This indicates the start of the SPASE metadata.										
Diagram	<pre> classDiagram class Spase { @ lang : xsd:string @ Version : enumVersion <<ResourceEntity>> * ResourceEntity } Spase < -- ResourceEntity Spase < -- Version </pre>										
Used by	Element Spase										
Model	Version , ResourceEntity+										
Children	ResourceEntity, Version										
Attributes	<table border="1"> <thead> <tr> <th>QName</th> <th>Type</th> <th>Fixed</th> <th>Default</th> <th>Use</th> </tr> </thead> <tbody> <tr> <td>lang</td> <td>xsd:string</td> <td></td> <td>en</td> <td>optional</td> </tr> </tbody> </table>	QName	Type	Fixed	Default	Use	lang	xsd:string		en	optional
QName	Type	Fixed	Default	Use							
lang	xsd:string		en	optional							
Source	<pre> <xsd:complexType name="Spase"> <xsd:annotation> <xsd:documentation xml:lang="en">Space Physics Archive Search and Extract (SPASE). The outermost container or envelope for SPASE metadata. This indicates the start of the SPASE metadata.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="Version" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ResourceEntity" minOccurs="1" maxOccurs="unbounded"/> </xsd:sequence> <xsd:attribute name="lang" type="xsd:string" default="en"/> </xsd:complexType> </pre>										
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd										

Complex Type Catalog

Namespace	http://www.spase-group.org/data/schema
Annotations	A tabular listing of events or observational notes, especially those that have utility in aiding a user in locating data. Catalogues include lists of events, files in a product, and data availability.

Diagram	
Used by	Element Catalog
Model	ResourceID , ResourceHeader , AccessInformation+ , ProviderResourceName{0,1} , ProviderVersion{0,1} , InstrumentID* , PhenomenonType+ , TimeSpan{0,1} , Caveats{0,1} , Keyword* , InputResourceID* , Parameter* , Extension*
Children	AccessInformation, Caveats, Extension, InputResourceID, InstrumentID, Keyword, Parameter, PhenomenonType, ProviderResourceName, ProviderVersion, ResourceHeader, TimeSpan
Source	<pre><xsd:complexType name="Catalog"> <xsd:annotation> <xsd:documentation xml:lang="en">A tabular listing of events or observational notes, especially those that have utility in aiding a user in locating data. Catalogues include lists of events, files in a product, and data availability.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="ResourceID" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ResourceHeader" minOccurs="1" maxOccurs="1"/> <xsd:element ref="AccessInformation" minOccurs="1" maxOccurs="unbounded"/> <xsd:element ref="ProviderResourceName" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ProviderVersion" minOccurs="0" maxOccurs="1"/> <xsd:element ref="InstrumentID" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="PhenomenonType" minOccurs="1" maxOccurs="unbounded"/> <xsd:element ref="TimeSpan" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Caveats" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Keyword" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="InputResourceID" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="Parameter" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="Extension" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type ResourceHeader

Namespace	http://www.spase-group.org/data/schema
Annotations	Attributes of a resource which pertain to the provider of the resource and descriptive

	information about the resource.
Diagram	<pre> classDiagram class ResourceHeader { ResourceName AlternateName "0..∞" ReleaseDate ExpirationDate Description Acknowledgement Contact "1..∞" InformationURL "0..∞" Association "0..∞" PriorID "0..∞" } </pre>
Used by	Element ResourceHeader
Model	ResourceName , AlternateName* , ReleaseDate , ExpirationDate{0,1} , Description , Acknowledgement{0,1} , Contact+ , InformationURL* , Association* , PriorID*
Children	Acknowledgement, AlternateName, Association, Contact, Description, ExpirationDate, InformationURL, PriorID, ReleaseDate, ResourceName
Source	<pre> <xsd:complexType name="ResourceHeader"> <xsd:annotation> <xsd:documentation xml:lang="en">Attributes of a resource which pertain to the provider of the resource and descriptive information about the resource.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="ResourceName" minOccurs="1" maxOccurs="1"/> <xsd:element ref="AlternateName" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="ReleaseDate" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ExpirationDate" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Description" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Acknowledgement" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Contact" minOccurs="1" maxOccurs="unbounded"/> <xsd:element ref="InformationURL" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="Association" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="PriorID" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Contact

Namespace	http://www.spase-group.org/data/schema
Annotations	The person or organization who may be able to provide special assistance or serve as a channel for communication for additional information about a resource.
Diagram	<pre> classDiagram class Contact { PersonID Role "1..∞" } </pre>
Used by	Element Contact
Model	PersonID , Role+

Children	PersonID, Role
Source	<pre><xsd:complexType name="Contact"> <xsd:annotation> <xsd:documentation xml:lang="en">The person or organization who may be able to provide special assistance or serve as a channel for communication for additional information about a resource.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="PersonID" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Role" minOccurs="1" maxOccurs="unbounded" /> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type InformationURL

Namespace	http://www.spase-group.org/data/schema
Annotations	Attributes of the method of acquiring additional information.
Diagram	<pre> classDiagram class InformationURL { Name : xsd:string URL : xsd:string Description : xsd:string Language : xsd:string } </pre>
Used by	Element InformationURL
Model	Name{0,1} , URL , Description{0,1} , Language{0,1}
Children	Description, Language, Name, URL
Source	<pre><xsd:complexType name="InformationURL"> <xsd:annotation> <xsd:documentation xml:lang="en">Attributes of the method of acquiring additional information.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="Name" minOccurs="0" maxOccurs="1"/> <xsd:element ref="URL" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Description" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Language" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Association

Namespace	http://www.spase-group.org/data/schema
Annotations	Attributes of a relationship a resource has with another resource.
Diagram	<pre> classDiagram class Association { AssociationID : xsd:string AssociationType : enumAssociationType Note : xsd:string } </pre>
Used by	Element Association
Model	AssociationID{0,1} , AssociationType{0,1} , Note{0,1}
Children	AssociationID, AssociationType, Note
Source	<pre><xsd:complexType name="Association"> <xsd:annotation></pre>

	<pre> <xsd:documentation xml:lang="en">Attributes of a relationship a resource has with another resource.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="AssociationID" minOccurs="0" maxOccurs="1"/> <xsd:element ref="AssociationType" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Note" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type AccessInformation

Namespace	http://www.spase-group.org/data/schema
Annotations	Attributes of the resource which pertain to how to accessing the resource, availability and storage format.
Diagram	<pre> classDiagram class AccessInformation { RepositoryID : xsd:string Availability : enumAvailability AccessRights : enumAccessRights AccessURL : AccessURL Format : enumFormat Encoding : enumEncoding DataExtent : DataExtent Acknowledgement : xsd:string } AccessURL { multiplicity 1..oo } </pre>
Used by	Element AccessInformation
Model	RepositoryID , Availability{0,1} , AccessRights{0,1} , AccessURL+ , Format , Encoding{0,1} , DataExtent{0,1} , Acknowledgement{0,1}
Children	AccessRights, AccessURL, Acknowledgement, Availability, DataExtent, Encoding, Format, RepositoryID
Source	<pre> <xsd:complexType name="AccessInformation"> <xsd:annotation> <xsd:documentation xml:lang="en">Attributes of the resource which pertain to how to accessing the resource, availability and storage format.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="RepositoryID" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Availability" minOccurs="0" maxOccurs="1"/> <xsd:element ref="AccessRights" minOccurs="0" maxOccurs="1"/> <xsd:element ref="AccessURL" minOccurs="1" maxOccurs="unbounded"/> <xsd:element ref="Format" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Encoding" minOccurs="0" maxOccurs="1"/> <xsd:element ref="DataExtent" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Acknowledgement" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type AccessURL

Namespace	http://www.spase-group.org/data/schema
Annotations	Attributes of the method for accessing a resource including a URL, name and description.

Diagram	
Used by	Element AccessURL
Model	Name{0,1} , URL , Description{0,1} , Language{0,1}
Children	Description, Language, Name, URL
Source	<pre><xsd:complexType name="AccessURL"> <xsd:annotation> <xsd:documentation xml:lang="en">Attributes of the method for accessing a resource including a URL, name and description.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="Name" minOccurs="0" maxOccurs="1"/> <xsd:element ref="URL" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Description" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Language" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type DataExtent

Namespace	http://www.spase-group.org/data/schema
Annotations	The area of storage in a file system required to store the contents of a resource. The default units for data extent is bytes.
Diagram	
Used by	Element DataExtent
Model	Quantity , Units{0,1} , Per{0,1}
Children	Per, Quantity, Units
Source	<pre><xsd:complexType name="DataExtent"> <xsd:annotation> <xsd:documentation xml:lang="en">The area of storage in a file system required to store the contents of a resource. The default units for data extent is bytes.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="Quantity" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Units" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Per" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type TimeSpan

Namespace	http://www.spase-group.org/data/schema
Annotations	The duration of an interval in time.

Diagram	A UML class diagram showing the structure of the TimeSpan complex type. It consists of a central class box labeled 'TimeSpan' with three directed associations pointing to child classes: 'StartDate' (with type 'xsd:dateTime'), 'StopDateEntity' (with 'Abstract' checked and 'true' in the 'Type' field), and 'Note' (with type 'xsd:string'). Each child class has a circled plus sign (+) indicating it is an optional element.
Used by	Element TimeSpan
Model	StartDate , StopDateEntity , Note*
Children	Note, StartDate, StopDateEntity
Source	<pre><xsd:complexType name="TimeSpan"> <xsd:annotation> <xsd:documentation xml:lang="en">The duration of an interval in time.</ xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="StartDate" minOccurs="1" maxOccurs="1"/> <xsd:element ref="StopDateEntity" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Note" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd


Complex Type Parameter

Namespace	http://www.spase-group.org/data/schema
Annotations	A container of information regarding a parameter whose values are part of the product. Every product contains or can be related to one or more parameters.


Diagram	<pre> classDiagram class Parameter { Name : xsd:string Set : xsd:string ParameterKey : xsd:string Description : xsd:string Caveats : xsd:string Cadence : xsd:duration Units : xsd:string UnitsConversion : xsd:string CoordinateSystem : CoordinateSystem RenderingHints : RenderingHints Structure : Structure ValidMin : xsd:string ValidMax : xsd:string FillValue : xsd:string ParameterEntity { <<Abstract true>> } } </pre>
Used by	Element Parameter
Model	Name , Set* , ParameterKey{0,1} , Description{0,1} , Caveats{0,1} , Cadence{0,1} , Units{0,1} , UnitsConversion{0,1} , CoordinateSystem{0,1} , RenderingHints* , Structure{0,1} , ValidMin{0,1} , ValidMax{0,1} , FillValue{0,1} , ParameterEntity
Children	Cadence, Caveats, CoordinateSystem, Description, FillValue, Name, ParameterEntity, ParameterKey, RenderingHints, Set, Structure, Units, UnitsConversion, ValidMax, ValidMin
Source	<pre> <xsd:complexType name="Parameter"> <xsd:annotation> <xsd:documentation xml:lang="en">A container of information regarding a parameter whose values are part of the product. Every product contains or can be related to one or more parameters.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="Name" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Set" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="ParameterKey" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Description" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Caveats" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Cadence" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Units" minOccurs="0" maxOccurs="1"/> <xsd:element ref="UnitsConversion" minOccurs="0" maxOccurs="1"/> <xsd:element ref="CoordinateSystem" minOccurs="0" maxOccurs="1"/> <xsd:element ref="RenderingHints" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="Structure" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ValidMin" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ValidMax" minOccurs="0" maxOccurs="1"/> <xsd:element ref="FillValue" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ParameterEntity" minOccurs="1" maxOccurs="1"/> </xsd:sequence> </xsd:complexType> </pre>

Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd
-----------------	---

Complex Type CoordinateSystem

Namespace	http://www.spase-group.org/data/schema
Annotations	The specification of the orientation of a set of (typically) orthogonal base axes.
Diagram	
Used by	Element CoordinateSystem
Model	CoordinateRepresentation{0,1} , CoordinateSystemName{0,1}
Children	CoordinateRepresentation, CoordinateSystemName
Source	<pre><xsd:complexType name="CoordinateSystem"> <xsd:annotation> <xsd:documentation xml:lang="en">The specification of the orientation of a set of (typically) orthogonal base axes.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="CoordinateRepresentation" minOccurs="0" maxOccurs="1"/> <xsd:element ref="CoordinateSystemName" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type RenderingHints

Namespace	http://www.spase-group.org/data/schema
Annotations	Attributes to aid in the rendering of parameter.
Diagram	
Used by	Element RenderingHints
Model	DisplayType{0,1} , AxisLabel{0,1} , RenderingAxis{0,1} , Index{0,1} , ValueFormat{0,1} , ScaleMin{0,1} , ScaleMax{0,1} , ScaleType{0,1}
Children	AxisLabel, DisplayType, Index, RenderingAxis, ScaleMax, ScaleMin, ScaleType, ValueFormat
Source	<pre><xsd:complexType name="RenderingHints"> <xsd:annotation> <xsd:documentation xml:lang="en">Attributes to aid in the rendering of parameter.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="DisplayType" minOccurs="0" maxOccurs="1"/> <xsd:element ref="AxisLabel" minOccurs="0" maxOccurs="1"/> <xsd:element ref="RenderingAxis" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Index" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ValueFormat" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ScaleMin" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ScaleMax" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>

	<pre> <xsd:element ref="Index" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ValueFormat" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ScaleMin" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ScaleMax" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ScaleType" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Structure

Namespace	http://www.spase-group.org/data/schema
Annotations	The organization and relationship of individual values within a quantity.
Diagram	<pre> classDiagram class Structure { Size Description Element } class Element class Size class Description class Element Element < -- Element </pre>
Used by	Element Structure
Model	Size{0,1} , Description{0,1} , Element*
Children	Description, Element, Size
Source	<pre> <xsd:complexType name="Structure"> <xsd:annotation> <xsd:documentation xml:lang="en">The organization and relationship of individual values within a quantity.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="Size" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Description" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Element" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Element

Namespace	http://www.spase-group.org/data/schema
Annotations	A component or individual unit of a multiple value quantity such as an array or vector.
Diagram	<pre> classDiagram class Element { Name Qualifier Index ParameterKey Units UnitsConversion ValidMin ValidMax FillValue } class Name class Qualifier class Index class ParameterKey class Units class UnitsConversion class ValidMin class ValidMax class FillValue class enumQualifier Element < -- Element </pre>
Source	<pre> <xsd:complexType name="Element"> <xsd:annotation> <xsd:documentation xml:lang="en">A component or individual unit of a multiple value quantity such as an array or vector.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="Name" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Qualifier" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Index" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ParameterKey" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Units" minOccurs="0" maxOccurs="1"/> <xsd:element ref="UnitsConversion" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ValidMin" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ValidMax" minOccurs="0" maxOccurs="1"/> <xsd:element ref="FillValue" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>

Used by	Element	Element
Model	Name , Qualifier* , Index , ParameterKey{0,1} , Units{0,1} , UnitsConversion{0,1} , ValidMin{0,1} , ValidMax{0,1} , FillValue{0,1}	
Children	FillValue, Index, Name, ParameterKey, Qualifier, Units, UnitsConversion, ValidMax, ValidMin	
Source		<pre><xsd:complexType name="Element"> <xsd:annotation> <xsd:documentation xml:lang="en">A component or individual unit of a multiple value quantity such as an array or vector.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="Name" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Qualifier" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="Index" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ParameterKey" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Units" minOccurs="0" maxOccurs="1"/> <xsd:element ref="UnitsConversion" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ValidMin" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ValidMax" minOccurs="0" maxOccurs="1"/> <xsd:element ref="FillValue" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>
Schema location		file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd


Complex Type Field

Namespace	http://www.spase-group.org/data/schema	
Annotations	The space around a radiating body within which its electromagnetic attributes can exert force on another similar body that is not in direct contact.	
Diagram	<pre> classDiagram class Field class Qualifier { *--> Field *--> FieldQuantity } class FieldQuantity { *--> Field *--> FrequencyRange } class FrequencyRange { *--> FieldQuantity } </pre>	
Used by	Element Field	
Model	Qualifier* , FieldQuantity , FrequencyRange{0,1}	
Children	FieldQuantity, FrequencyRange, Qualifier	
Source	<pre><xsd:complexType name="Field"> <xsd:annotation> <xsd:documentation xml:lang="en">The space around a radiating body within which its electromagnetic attributes can exert force on another similar body that is not in direct contact.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="Qualifier" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="FieldQuantity" minOccurs="1" maxOccurs="1"/> <xsd:element ref="FrequencyRange" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>	
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd	


Complex Type FrequencyRange

Namespace	http://www.spase-group.org/data/schema	
Annotations	The range of possible values for the observed frequency.	

Diagram	<p>The diagram illustrates the structure of the <code>FrequencyRange</code> element. It is a composite element containing four simple elements: <code>SpectralRange</code>, <code>Low</code>, <code>High</code>, and <code>Units</code>. Additionally, it has a multiplicity of <code>0..∞</code> for the <code>Bin</code> component, which is defined as a type <code>Bin</code>.</p>
Used by	Element FrequencyRange
Model	

Diagram	
Used by	Element Particle
Model	ParticleType+, Qualifier*, ParticleQuantity , AtomicNumber*, EnergyRange{0,1} , AzimuthalAngleRange{0,1} , PolarAngleRange{0,1}
Children	AtomicNumber, AzimuthalAngleRange, EnergyRange, ParticleQuantity, ParticleType, PolarAngleRange, Qualifier
Source	<pre><xsd:complexType name="Particle"> <xsd:annotation> <xsd:documentation xml:lang="en">A description of the types of particles observed in the measurement. This includes both direct observations and inferred observations.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="ParticleType" minOccurs="1" maxOccurs="unbounded"/> <xsd:element ref="Qualifier" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="ParticleQuantity" minOccurs="1" maxOccurs="1"/> <xsd:element ref="AtomicNumber" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="EnergyRange" minOccurs="0" maxOccurs="1"/> <xsd:element ref="AzimuthalAngleRange" minOccurs="0" maxOccurs="1"/> <xsd:element ref="PolarAngleRange" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type EnergyRange

Namespace	http://www.spase-group.org/data/schema
Annotations	The minimum and maximum energy values of the particles represented by a given "physical parameter" description.
Diagram	
Used by	Element EnergyRange
Model	Low , High , Units , Bin*
Children	Bin, High, Low, Units
Source	<pre><xsd:complexType name="EnergyRange"> <xsd:annotation> <xsd:documentation xml:lang="en">The minimum and maximum energy values of the particles represented by a given "physical parameter" description.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="Low" minOccurs="1" maxOccurs="1"/> <xsd:element ref="High" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Units" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Bin" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType></pre>

	<pre> <xsd:element ref="Units" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Bin" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type AzimuthalAngleRange

Namespace	http://www.spase-group.org/data/schema
Annotations	The range of possible azimuthal angles for a group of energy observations. Default units are degrees.
Diagram	<pre> classDiagram class AzimuthalAngleRange { Low : xsd:double High : xsd:double Units : xsd:string Bin : xsd:Bin } </pre>
Used by	Element AzimuthalAngleRange
Model	Low , High , Units , Bin*
Children	Bin, High, Low, Units
Source	<pre> <xsd:complexType name="AzimuthalAngleRange"> <xsd:annotation> <xsd:documentation xml:lang="en">The range of possible azimuthal angles for a group of energy observations. Default units are degrees.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="Low" minOccurs="1" maxOccurs="1"/> <xsd:element ref="High" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Units" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Bin" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type PolarAngleRange

Namespace	http://www.spase-group.org/data/schema
Annotations	The range of possible polar angles for a group of energy observations. Defaults units are degrees.
Diagram	<pre> classDiagram class PolarAngleRange { Low : xsd:double High : xsd:double Units : xsd:string Bin : xsd:Bin } </pre>
Used by	Element PolarAngleRange
Model	Low , High , Units , Bin*
Children	Bin, High, Low, Units
Source	<pre> <xsd:complexType name="PolarAngleRange"> <xsd:annotation> <xsd:documentation xml:lang="en">The range of possible polar angles for a group of energy observations. Defaults units are degrees.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="Low" minOccurs="1" maxOccurs="1"/> </xsd:sequence> </xsd:complexType> </pre>

	<pre> <xsd:element ref="High" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Units" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Bin" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Wave

Namespace	http://www.spase-group.org/data/schema
Annotations	Periodic or quasi-periodic (AC) variations of physical quantities in time and space, capable of propagating or being trapped within particular regimes.
Diagram	
Used by	Element Wave
Model	WaveType , Qualifier*, WaveQuantity , EnergyRange{0,1} , FrequencyRange{0,1} , WavelengthRange{0,1}
Children	EnergyRange, FrequencyRange, Qualifier, WaveQuantity, WaveType, WavelengthRange
Source	<pre> <xsd:complexType name="Wave"> <xsd:annotation> <xsd:documentation xml:lang="en">Periodic or quasi-periodic (AC) variations of physical quantities in time and space, capable of propagating or being trapped within particular regimes.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="WaveType" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Qualifier" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="WaveQuantity" minOccurs="1" maxOccurs="1"/> <xsd:element ref="EnergyRange" minOccurs="0" maxOccurs="1"/> <xsd:element ref="FrequencyRange" minOccurs="0" maxOccurs="1"/> <xsd:element ref="WavelengthRange" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type WavelengthRange

Namespace	http://www.spase-group.org/data/schema
Annotations	The range of possible values for the observed wavelength.
Diagram	

Used by	Element WavelengthRange
Model	SpectralRange{0,1} , Low , High , Units , Bin*
Children	Bin, High, Low, SpectralRange, Units
Source	<pre><xsd:complexType name="WavelengthRange"> <xsd:annotation> <xsd:documentation xml:lang="en">The range of possible values for the observed wavelength.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="SpectralRange" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Low" minOccurs="1" maxOccurs="1"/> <xsd:element ref="High" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Units" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Bin" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Mixed

Namespace	http://www.spase-group.org/data/schema
Annotations	A parameter derived from more than one of the type of parameter. For example, plasma beta, the ratio of plasma particle energy density to the energy density of the magnetic field permeating the plasma, is "mixed."
Diagram	<pre> classDiagram class Mixed { <<Mixed>> } class MixedQuantity { <<MixedQuantity>> <<enumMixedQuantity>> } class ParticleType { <<ParticleType>> <<enumParticleType>> } class Qualifier { <<Qualifier>> <<enumQualifier>> } Mixed "0..∞" --> MixedQuantity Mixed "0..∞" --> ParticleType Mixed "0..∞" --> Qualifier </pre>
Used by	Element Mixed
Model	MixedQuantity , ParticleType* , Qualifier*
Children	MixedQuantity, ParticleType, Qualifier
Source	<pre><xsd:complexType name="Mixed"> <xsd:annotation> <xsd:documentation xml:lang="en">A parameter derived from more than one of the type of parameter. For example, plasma beta, the ratio of plasma particle energy density to the energy density of the magnetic field permeating the plasma, is "mixed."</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="MixedQuantity" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ParticleType" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="Qualifier" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Support

Namespace	http://www.spase-group.org/data/schema
Annotations	Information useful in understanding the context of an observation, typically observed or measured coincidentally with a physical observation.
Diagram	<pre> classDiagram class Support { <<Support>> } class Qualifier { <<Qualifier>> <<enumQualifier>> } class SupportQuantity { <<SupportQuantity>> <<enumSupportQuantity>> } Support "0..∞" --> Qualifier Qualifier --> SupportQuantity </pre>
Used by	Element Support
Model	Qualifier* , SupportQuantity
Children	Qualifier, SupportQuantity

Source	<pre><xsd:complexType name="Support"> <xsd:annotation> <xsd:documentation xml:lang="en">Information useful in understanding the context of an observation, typically observed or measured coincidentally with a physical observation.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="Qualifier" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="SupportQuantity" minOccurs="1" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type DisplayData

Namespace	http://www.spase-group.org/data/schema
Annotations	A graphical representation of data wherein the underlying numeric values are not (readily) accessible for analysis.. Examples are line plots and spectrograms.
Diagram	<pre> classDiagram class ResourceID class ResourceHeader class AccessInformation class ProcessingLevel class ProviderResourceName class ProviderProcessingLevel class ProviderVersion class InstrumentID class MeasurementType class TemporalDescription class SpectralRange class DisplayCadence class ObservedRegion class Caveats class Keyword class InputResourceId class Parameter class Extension ResourceID < -- ResourceHeader ResourceHeader < -- AccessInformation AccessInformation < -- ProcessingLevel ProcessingLevel < -- ProviderResourceName ProviderResourceName < -- ProviderProcessingLevel ProviderProcessingLevel < -- ProviderVersion ProviderVersion < -- InstrumentID InstrumentID < -- MeasurementType MeasurementType < -- TemporalDescription TemporalDescription < -- SpectralRange SpectralRange < -- DisplayCadence DisplayCadence < -- ObservedRegion ObservedRegion < -- Caveats Caveats < -- Keyword Keyword < -- InputResourceId InputResourceId < -- Parameter Parameter < -- Extension </pre>
Used by	Element DisplayData
Model	ResourceID , ResourceHeader , AccessInformation+ , ProcessingLevel{0,1} , ProviderResourceName{0,1} , ProviderProcessingLevel{0,1} , ProviderVersion{0,1} , InstrumentID* , MeasurementType+ ,

	TemporalDescription{0,1} , SpectralRange* , DisplayCadence{0,1} , ObservedRegion* , Caveats{0,1} , Keyword* , InputResourceID* , Parameter* , Extension*
Children	AccessInformation, Caveats, DisplayCadence, Extension, InputResourceID, InstrumentID, Keyword, MeasurementType, ObservedRegion, Parameter, ProcessingLevel, ProviderProcessingLevel, ProviderResourceName, ProviderVersion, ResourceHeader, ResourceID, SpectralRange, TemporalDescription
Source	<pre><xsd:complexType name="DisplayData"> <xsd:annotation> <xsd:documentation xml:lang="en">A graphical representation of data wherein the underlying numeric values are not (readily) accessible for analysis.. Examples are line plots and spectrograms.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="ResourceID" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ResourceHeader" minOccurs="1" maxOccurs="1"/> <xsd:element ref="AccessInformation" minOccurs="1" maxOccurs="unbounded"/> <xsd:element ref="ProcessingLevel" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ProviderResourceName" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ProviderProcessingLevel" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ProviderVersion" minOccurs="0" maxOccurs="1"/> <xsd:element ref="InstrumentID" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="MeasurementType" minOccurs="1" maxOccurs="unbounded"/> <xsd:element ref="TemporalDescription" minOccurs="0" maxOccurs="1"/> <xsd:element ref="SpectralRange" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="DisplayCadence" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ObservedRegion" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="Caveats" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Keyword" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="InputResourceID" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="Parameter" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="Extension" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd


Complex Type TemporalDescription

Namespace	http://www.spase-group.org/data/schema
Annotations	A characterization of the time over which the measurement was taken.
Diagram	<pre> classDiagram class TemporalDescription class TimeSpan class Cadence class Exposure TemporalDescription < -- TimeSpan TemporalDescription < -- Cadence TemporalDescription < -- Exposure </pre>
Used by	Element TemporalDescription
Model	TimeSpan , Cadence{0,1} , Exposure{0,1}
Children	Cadence, Exposure, TimeSpan
Source	<pre><xsd:complexType name="TemporalDescription"> <xsd:annotation> <xsd:documentation xml:lang="en">A characterization of the time over which the measurement was taken.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="TimeSpan" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Cadence" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Exposure" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type NumericalData

Namespace	http://www.spase-group.org/data/schema
Annotations	Data product stored as numerical values in a specified format.

Diagram



Used by	Element	NumericalData
Model		ResourceID , ResourceHeader , AccessInformation+ , ProcessingLevel{0,1} , ProviderResourceName{0,1} , ProviderProcessingLevel{0,1} , ProviderVersion{0,1} , InstrumentID* , MeasurementType+ , TemporalDescription{0,1} , SpectralRange* , ObservedRegion* , Caveats{0,1} , Keyword* , InputResourceID* , Parameter* , Extension*
Children		AccessInformation, Caveats, Extension, InputResourceID, InstrumentID, Keyword, MeasurementType, ObservedRegion, Parameter, ProcessingLevel, ProviderProcessingLevel, ProviderResourceName, ProviderVersion, ResourceHeader, ResourceID, SpectralRange, TemporalDescription
Source		<pre> <xsd:complexType name="NumericalData"> <xsd:annotation> <xsd:documentation xml:lang="en">Data product stored as numerical values in a specified format.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="ResourceID" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ResourceHeader" minOccurs="1" maxOccurs="1"/> <xsd:element ref="AccessInformation" minOccurs="1" maxOccurs="unbounded"/> <xsd:element ref="ProcessingLevel" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ProviderResourceName" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ProviderProcessingLevel" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ProviderVersion" minOccurs="0" maxOccurs="1"/> <xsd:element ref="InstrumentID" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="MeasurementType" minOccurs="1" maxOccurs="unbounded"/> <xsd:element ref="TemporalDescription" minOccurs="0" maxOccurs="1"/> <xsd:element ref="SpectralRange" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="ObservedRegion" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="Caveats" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType> </pre>

	<pre> <xsd:element ref="Keyword" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="InputResourceID" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="Parameter" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="Extension" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Document

Namespace	http://www.spase-group.org/data/schema
Annotations	A set of information designed and presented as an individual entity. A document may contain plain or formatted text, in-line graphics, sound, other multimedia data, or hypermedia references. Some examples of documents include a paper, letter, book, user guide, map, drawing, photograph, or image.
Diagram	<pre> classDiagram class Document { ResourceID : xsd:string ResourceHeader : ResourceHeader AccessInformation : AccessInformation Keyword : xsd:string DocumentType : enumDocumentType InputResourceID : xsd:string } Document < -- ResourceID Document < -- ResourceHeader Document < -- AccessInformation Document < -- Keyword Document < -- DocumentType Document < -- InputResourceID </pre>
Used by	Element Document
Model	ResourceID , ResourceHeader , AccessInformation+ , Keyword* , DocumentType , InputResourceID*
Children	AccessInformation, DocumentType, InputResourceID, Keyword, ResourceHeader, ResourceID
Source	<pre> <xsd:complexType name="Document"> <xsd:annotation> <xsd:documentation xml:lang="en">A set of information designed and presented as an individual entity. A document may contain plain or formatted text, in-line graphics, sound, other multimedia data, or hypermedia references. Some examples of documents include a paper, letter, book, user guide, map, drawing, photograph, or image.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="ResourceID" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ResourceHeader" minOccurs="1" maxOccurs="1"/> <xsd:element ref="AccessInformation" minOccurs="1" maxOccurs="unbounded"/> <xsd:element ref="Keyword" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="DocumentType" minOccurs="1" maxOccurs="1"/> <xsd:element ref="InputResourceID" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd


Complex Type Granule

Namespace	http://www.spase-group.org/data/schema
Annotations	An accessible portion of another resource. A Granule may be composed of one or more physical pieces (files) which are considered inseparable. For example, a data storage format that maintains metadata and binary data in separate, but tightly coupled files. Granules should not be used to group files that have simple relationships or which are associated through a parent resource. For example, each file containing a time interval data for a Numerical Data resource would each


	<p>be considered a Granule. The ParentID of a Granule resource must be a NumericalData resource. The attributes of a Granule supersede the corresponding attributes in the NumericalData resource.</p>
Diagram	<pre> classDiagram class Granule { ResourceID : xsd:string ReleaseDate : xsd:dateTime ExpirationDate : xsd:dateTime ParentID : xsd:string PriorID : xsd:string <-- multiplicity 0..infinity StartDate : xsd:dateTime StopDate : xsd:dateTime Source : Source <-- multiplicity 1..infinity } </pre>
Used by	Element Granule
Model	ResourceID , ReleaseDate , ExpirationDate{0,1} , ParentID , PriorID* , StartDate , StopDate , Source+
Children	ExpirationDate, ParentID, PriorID, ReleaseDate, ResourceID, Source, StartDate, StopDate
Source	<pre> <xsd:complexType name="Granule"> <xsd:annotation> <xsd:documentation xml:lang="en">An accessible portion of another resource. A Granule may be composed of one or more physical pieces (files) which are considered inseparable. For example, a data storage format that maintains metadata and binary data in separate, but tightly coupled files. Granules should not be used to group files that have simple relationships or which are associated through a parent resource. For example, each file containing a time interval data for a Numerical Data resource would each be considered a Granule. The ParentID of a Granule resource must be a NumericalData resource. The attributes of a Granule supersede the corresponding attributes in the NumericalData resource.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="ResourceID" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ReleaseDate" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ExpirationDate" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ParentID" minOccurs="1" maxOccurs="1"/> <xsd:element ref="PriorID" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="StartDate" minOccurs="1" maxOccurs="1"/> <xsd:element ref="StopDate" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Source" minOccurs="1" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Source

Namespace	http://www.spase-group.org/data/schema
Annotations	The location and attributes of an object.

Diagram	
Used by	Element Source
Model	SourceType , URL , MirrorURL* , Checksum{0,1} , DataExtent{0,1}
Children	Checksum, DataExtent, MirrorURL, SourceType, URL
Source	<pre><xsd:complexType name="Source"> <xsd:annotation> <xsd:documentation xml:lang="en">The location and attributes of an object.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="SourceType" minOccurs="1" maxOccurs="1"/> <xsd:element ref="URL" minOccurs="1" maxOccurs="1"/> <xsd:element ref="MirrorURL" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="Checksum" minOccurs="0" maxOccurs="1"/> <xsd:element ref="DataExtent" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Checksum

Namespace	http://www.spase-group.org/data/schema
Annotations	A computed value that is dependent upon the contents of a digital data object. Primarily used to check whether errors or alterations have occurred during the transmission or storage of a data object.
Diagram	
Used by	Element Checksum
Model	HashValue , HashFunction
Children	HashFunction, HashValue
Source	<pre><xsd:complexType name="Checksum"> <xsd:annotation> <xsd:documentation xml:lang="en">A computed value that is dependent upon the contents of a digital data object. Primarily used to check whether errors or alterations have occurred during the transmission or storage of a data object.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="HashValue" minOccurs="1" maxOccurs="1"/> <xsd:element ref="HashFunction" minOccurs="1" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Instrument

Namespace	http://www.spase-group.org/data/schema
Annotations	A device that makes measurements used to characterize a physical phenomenon, or a family of like devices.

Diagram	<pre> classDiagram class Instrument { ResourceID ResourceHeader 1..oo InstrumentType 1..oo InvestigationName OperatingSpan ObservatoryID Caveats 0..oo Extension } </pre>
Used by	Element Instrument
Model	ResourceID , ResourceHeader , InstrumentType+ , InvestigationName+ , OperatingSpan{0,1} , ObservatoryID , Caveats{0,1} , Extension*
Children	Caveats, Extension, InstrumentType, InvestigationName, ObservatoryID, OperatingSpan, ResourceHeader, ResourceID 0 -1 Elementrefg=
Source	<pre> <xsd:complexType name="Instrument"> <xsd:annotation> <xsd:documentation>A device that makes measurements used to characterise a physical phenomenon, or a family of like devices.</xsd:documentation> </xsd:annotation> <xsd:sequence> 0 -1 Elementrefg= </pre>

```

</xsd:sequence> ] TJ 1 0 0 -1 01428.7519989 Tm [ (/<xsd:complexType>D) ] TJ ET Q q 1 0 0 1 9.454154.936 c

```

	<pre> <xsd:sequence> <xsd:element ref="StartDate" minOccurs="1" maxOccurs="1"/> <xsd:element ref="StopDate" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Note" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Observatory

Namespace	http://www.spase-group.org/data/schema
Annotations	The host (spacecraft, network, facility) for instruments making observations, or a family of closely related hosts.
Diagram	<pre> classDiagram class Observatory class ResourceID class ResourceHeader class ObservatoryGroupID class Location class OperatingSpan class Extension Observatory "0..1" -- "0..1" ResourceID Observatory "0..1" -- "0..1" ResourceHeader Observatory "0..1" -- "0..1" ObservatoryGroupID Observatory "0..1" -- "0..1" Location Observatory "0..1" -- "0..1" OperatingSpan ObservatoryGroupID "0..1" -- "0..1" ObservatoryGroupID </pre>
Used by	Element Observatory
Model	ResourceID , ResourceHeader , ObservatoryGroupID* , Location , OperatingSpan{0,1} , Extension*
Children	Extension, Location, ObservatoryGroupID, OperatingSpan, ResourceHeader, ResourceID
Source	<pre> <xsd:complexType name="Observatory"> <xsd:annotation> <xsd:documentation xml:lang="en">The host (spacecraft, network, facility) for instruments making observations, or a family of closely related hosts.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="ResourceID" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ResourceHeader" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ObservatoryGroupID" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="Location" minOccurs="1" maxOccurs="1"/> <xsd:element ref="OperatingSpan" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Extension" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Location

Namespace	http://www.spase-group.org/data/schema
Annotations	A position in space definable by a regional referencing system and geographic coordinates.
Diagram	<pre> classDiagram class Location class ObservatoryRegion class CoordinateSystemName class Latitude class Longitude class Elevation Location "0..1" -- "1..1" ObservatoryRegion Location "0..1" -- "0..1" CoordinateSystemName Location "0..1" -- "0..1" Latitude Location "0..1" -- "0..1" Longitude Location "0..1" -- "0..1" Elevation </pre>
Used by	Element Location

Model	ObservatoryRegion+, CoordinateSystemName{0,1}, Latitude{0,1}, Longitude{0,1}, Elevation{0,1}
Children	CoordinateSystemName, Elevation, Latitude, Longitude, ObservatoryRegion
Source	<pre> <xsd:complexType name="Location"> <xsd:annotation> <xsd:documentation xml:lang="en">A position in space definable by a regional referencing system and geographic coordinates.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="ObservatoryRegion" minOccurs="1" maxOccurs="unbounded"/> <xsd:element ref="CoordinateSystemName" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Latitude" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Longitude" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Elevation" minOccurs="0" maxOccurs="1"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Person

Namespace	http://www.spase-group.org/data/schema
Annotations	An individual human being.
Diagram	<pre> classDiagram class Person { ResourceID : xsd:string ReleaseDate : xsd:dateTime PersonName : xsd:string OrganizationName : xsd:string Address : xsd:string Email : xsd:string PhoneNumber : xsd:string FaxNumber : xsd:string Note : xsd:string Extension : xsd:string } </pre>
Used by	Element Person
Model	ResourceID, ReleaseDate{0,1}, PersonName{0,1}, OrganizationName, Address{0,1}, Email*, PhoneNumber*, FaxNumber{0,1}, Note{0,1}, Extension*
Children	Address, Email, Extension, FaxNumber, Note, OrganizationName, PersonName, PhoneNumber, ReleaseDate, ResourceID
Source	<pre> <xsd:complexType name="Person"> <xsd:annotation> <xsd:documentation xml:lang="en">An individual human being.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="ResourceID" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ReleaseDate" minOccurs="0" maxOccurs="1"/> <xsd:element ref="PersonName" minOccurs="0" maxOccurs="1"/> <xsd:element ref="OrganizationName" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Address" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Email" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="PhoneNumber" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="FaxNumber" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Note" minOccurs="0" maxOccurs="1"/> <xsd:element ref="Extension" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Registry

Namespace	http://www.spase-group.org/data/schema
Annotations	A location or facility where resources are cataloged.
Diagram	<pre> classDiagram class Registry { <<Registry>> <<A location or facility where resources are cataloged.>> <<ResourceID, ResourceHeader, AccessURL, Extension*>> } class ResourceID { <<ResourceID>> <<xsd:string>> } class ResourceHeader { <<ResourceHeader>> <<ResourceHeader>> } class AccessURL { <<AccessURL>> <<AccessURL>> } class Extension { <<Extension>> <<0..>> } Registry "1" -- "*" ResourceID Registry "1" -- "*" ResourceHeader Registry "1" -- "*" AccessURL Registry "1" -- "*" Extension </pre>
Used by	Element Registry
Model	ResourceID , ResourceHeader , AccessURL , Extension*
Children	AccessURL, Extension, ResourceHeader, ResourceID
Source	<pre> <xsd:complexType name="Registry"> <xsd:annotation> <xsd:documentation xml:lang="en">A location or facility where resources are cataloged.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="ResourceID" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ResourceHeader" minOccurs="1" maxOccurs="1"/> <xsd:element ref="AccessURL" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Extension" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Repository

Namespace	http://www.spase-group.org/data/schema
Annotations	A location or facility where resources are stored.
Diagram	<pre> classDiagram class Repository { <<Repository>> <<A location or facility where resources are stored.>> <<ResourceID, ResourceHeader, AccessURL, Extension*>> } class ResourceID { <<ResourceID>> <<xsd:string>> } class ResourceHeader { <<ResourceHeader>> <<ResourceHeader>> } class AccessURL { <<AccessURL>> <<AccessURL>> } class Extension { <<Extension>> <<0..>> } Repository "1" -- "*" ResourceID Repository "1" -- "*" ResourceHeader Repository "1" -- "*" AccessURL Repository "1" -- "*" Extension </pre>
Used by	Element Repository
Model	ResourceID , ResourceHeader , AccessURL , Extension*
Children	AccessURL, Extension, ResourceHeader, ResourceID
Source	<pre> <xsd:complexType name="Repository"> <xsd:annotation> <xsd:documentation xml:lang="en">A location or facility where resources are stored.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="ResourceID" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ResourceHeader" minOccurs="1" maxOccurs="1"/> <xsd:element ref="AccessURL" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Extension" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Service

Namespace	http://www.spase-group.org/data/schema
Annotations	A location or facility that can perform a

	well defined task.
Diagram	<pre> classDiagram class Service class ResourceID { <<xsd:string>> } class ResourceHeader { <<ResourceHeader>> } class AccessURL { <<AccessURL>> } class Extension { <<Extension>> } Service < -- ResourceID Service < -- ResourceHeader Service < -- AccessURL Service < -- Extension *{0..infinity} </pre>
Used by	Element Service
Model	ResourceID , ResourceHeader , AccessURL , Extension*
Children	AccessURL, Extension, ResourceHeader, ResourceID
Source	<pre> <xsd:complexType name="Service"> <xsd:annotation> <xsd:documentation xml:lang="en">A location or facility that can perform a well defined task.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="ResourceID" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ResourceHeader" minOccurs="1" maxOccurs="1"/> <xsd:element ref="AccessURL" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Extension" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type Annotation

Namespace	http://www.spase-group.org/data/schema
Annotations	Information which is explanatory or descriptive which is associated with another resource.
Diagram	<pre> classDiagram class Annotation class ResourceID { <<xsd:string>> } class ResourceHeader { <<ResourceHeader>> } class imageURL { <<xsd:string>> } class AnnotationType { <<enumAnnotationType>> } class PhenomenonType { <<enumPhenomenonType>> } class ClassificationMethod { <<enumClassificationMethod>> } class ConfidenceRating { <<enumConfidenceRating>> } class TimeSpan { <<TimeSpan>> } class ObservationExtent { <<ObservationExtent>> } class Extension { <<Extension>> } Annotation < -- ResourceID *{0..infinity} Annotation < -- ResourceHeader *{0..infinity} Annotation < -- imageURL *{0..infinity} Annotation < -- AnnotationType *{0..infinity} Annotation < -- PhenomenonType *{0..infinity} Annotation < -- ClassificationMethod *{0..infinity} Annotation < -- ConfidenceRating *{0..infinity} TimeSpan *{0..infinity} --> Annotation ObservationExtent *{0..infinity} --> Annotation Extension *{0..infinity} --> Annotation </pre>
Used by	Element Annotation
Model	ResourceID , ResourceHeader , imageURL{0,1} , AnnotationType , PhenomenonType{0,1} , ClassificationMethod{0,1} , ConfidenceRating{0,1} , TimeSpan* , ObservationExtent* , Extension*
Children	AnnotationType, ClassificationMethod, ConfidenceRating, Extension, imageURL, ObservationExtent, PhenomenonType, ResourceHeader, ResourceID, TimeSpan
Source	<pre> <xsd:complexType name="Annotation"> <xsd:annotation> <xsd:documentation xml:lang="en">Information which is explanatory or descriptive which is associated with another resource.</xsd:documentation> </xsd:annotation> </xsd:complexType> </pre>

Used by	<pre></xsd:annotation> <xsd:sequence> <xsd:element ref="ResourceID" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ResourceHeader" minOccurs="1" maxOccurs="1"/> <xsd:element ref="ImageURL" minOccurs="0" maxOccurs="1"/> <xsd:element ref="AnnotationType" minOccurs="1" maxOccurs="1"/> <xsd:element ref="PhenomenonType" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ClassificationMethod" minOccurs="0" maxOccurs="1"/> <xsd:element ref="ConfidenceRating" minOccurs="0" maxOccurs="1"/> <xsd:element ref="TimeSpan" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="ObservationExtent" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="Extension" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Complex Type ObservationExtent

Namespace	http://www.spase-group.org/data/schema
Annotations	The spatial area encompassed by an observation.
Diagram	<pre> classDiagram class ObservationExtent { +ObservedRegion : enumRegion +StartLocation : xsd:string +StopLocation : xsd:string +Note : xsd:string } ObservationExtent < -- ObservedRegion ObservationExtent < -- StartLocation ObservationExtent < -- StopLocation ObservationExtent < -- Note </pre>
Used by	Element ObservationExtent
Model	ObservedRegion{0,1} , StartLocation , StopLocation , Note*
Children	Note, ObservedRegion, StartLocation, StopLocation
Source	<pre><xsd:complexType name="ObservationExtent"> <xsd:annotation> <xsd:documentation xml:lang="en">The spatial area encompassed by an observation.</xsd:documentation> </xsd:annotation> <xsd:sequence> <xsd:element ref="ObservedRegion" minOccurs="0" maxOccurs="1"/> <xsd:element ref="StartLocation" minOccurs="1" maxOccurs="1"/> <xsd:element ref="StopLocation" minOccurs="1" maxOccurs="1"/> <xsd:element ref="Note" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> </xsd:complexType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Types

Simple Type enumVersion

Namespace	http://www.spase-group.org/data/schema
Annotations	Version number.
Diagram	

Simple Type enumRole

Namespace	http://www.spase-group.org/data/schema																																														
Annotations	Identifiers for the assigned or assumed function or position of an individual.																																														
Diagram	<pre> classDiagram enumRole < -- xsd:string </pre>																																														
Type	restriction of xsd:string																																														
Facets	<table border="1"> <tr> <td>enumeration</td> <td>ArchiveSpecialist</td> <td>An individual who is an expert on a collection of resources and may also be knowledgeable of the phenomenon and related physics represented by the resources. This includes librarians, curators, archive scientists and other experts.</td> </tr> <tr> <td>enumeration</td> <td>CoInvestigator</td> <td>An individual who is a scientific peer and major participant in an investigation.</td> </tr> <tr> <td>enumeration</td> <td>Contributor</td> <td>An entity responsible for making contributions to the content of the resource.</td> </tr> <tr> <td>enumeration</td> <td>DataProducer</td> <td>An individual who generated the resource and is familiar with its provenance.</td> </tr> <tr> <td>enumeration</td> <td>DeputyPI</td> <td>An individual who is an administrative or scientific leader for an investigation operating under the supervision of a Principal Investigator.</td> </tr> <tr> <td>enumeration</td> <td>FormerPI</td> <td>An individual who had served as the administrative and scientific lead for an investigation, but no longer assumes that role.</td> </tr> <tr> <td>enumeration</td> <td>GeneralContact</td> <td>An individual who can provide information on a range of subjects or who can direct you to a domain expert.</td> </tr> <tr> <td>enumeration</td> <td>MetadataContact</td> <td>An individual who can affect a change in the metadata describing a resource.</td> </tr> <tr> <td>enumeration</td> <td>PrincipalInvestigator</td> <td>An individual who is the administrative and scientific lead for an investigation.</td> </tr> <tr> <td>enumeration</td> <td>ProjectScientist</td> <td>An individual who is an expert in the phenomenon and related physics explored by the project. A project scientist may also have a managerial role within the project.</td> </tr> <tr> <td>enumeration</td> <td>Publisher</td> <td>An individual, organization, institution or government department responsible for the production and dissemination of a document.</td> </tr> <tr> <td>enumeration</td> <td>Scientist</td> <td>An individual who is an expert in the phenomenon and related physics represented by the resource.</td> </tr> <tr> <td>enumeration</td> <td>TeamLeader</td> <td>An individual who is the designated leader of an investigation.</td> </tr> <tr> <td>enumeration</td> <td>TeamMember</td> <td>An individual who is a major participant in an investigation.</td> </tr> <tr> <td>enumeration</td> <td>TechnicalContact</td> <td>An individual who can provide specific information with regard to the resource or supporting software</td> </tr> </table>		enumeration	ArchiveSpecialist	An individual who is an expert on a collection of resources and may also be knowledgeable of the phenomenon and related physics represented by the resources. This includes librarians, curators, archive scientists and other experts.	enumeration	CoInvestigator	An individual who is a scientific peer and major participant in an investigation.	enumeration	Contributor	An entity responsible for making contributions to the content of the resource.	enumeration	DataProducer	An individual who generated the resource and is familiar with its provenance.	enumeration	DeputyPI	An individual who is an administrative or scientific leader for an investigation operating under the supervision of a Principal Investigator.	enumeration	FormerPI	An individual who had served as the administrative and scientific lead for an investigation, but no longer assumes that role.	enumeration	GeneralContact	An individual who can provide information on a range of subjects or who can direct you to a domain expert.	enumeration	MetadataContact	An individual who can affect a change in the metadata describing a resource.	enumeration	PrincipalInvestigator	An individual who is the administrative and scientific lead for an investigation.	enumeration	ProjectScientist	An individual who is an expert in the phenomenon and related physics explored by the project. A project scientist may also have a managerial role within the project.	enumeration	Publisher	An individual, organization, institution or government department responsible for the production and dissemination of a document.	enumeration	Scientist	An individual who is an expert in the phenomenon and related physics represented by the resource.	enumeration	TeamLeader	An individual who is the designated leader of an investigation.	enumeration	TeamMember	An individual who is a major participant in an investigation.	enumeration	TechnicalContact	An individual who can provide specific information with regard to the resource or supporting software
enumeration	ArchiveSpecialist	An individual who is an expert on a collection of resources and may also be knowledgeable of the phenomenon and related physics represented by the resources. This includes librarians, curators, archive scientists and other experts.																																													
enumeration	CoInvestigator	An individual who is a scientific peer and major participant in an investigation.																																													
enumeration	Contributor	An entity responsible for making contributions to the content of the resource.																																													
enumeration	DataProducer	An individual who generated the resource and is familiar with its provenance.																																													
enumeration	DeputyPI	An individual who is an administrative or scientific leader for an investigation operating under the supervision of a Principal Investigator.																																													
enumeration	FormerPI	An individual who had served as the administrative and scientific lead for an investigation, but no longer assumes that role.																																													
enumeration	GeneralContact	An individual who can provide information on a range of subjects or who can direct you to a domain expert.																																													
enumeration	MetadataContact	An individual who can affect a change in the metadata describing a resource.																																													
enumeration	PrincipalInvestigator	An individual who is the administrative and scientific lead for an investigation.																																													
enumeration	ProjectScientist	An individual who is an expert in the phenomenon and related physics explored by the project. A project scientist may also have a managerial role within the project.																																													
enumeration	Publisher	An individual, organization, institution or government department responsible for the production and dissemination of a document.																																													
enumeration	Scientist	An individual who is an expert in the phenomenon and related physics represented by the resource.																																													
enumeration	TeamLeader	An individual who is the designated leader of an investigation.																																													
enumeration	TeamMember	An individual who is a major participant in an investigation.																																													
enumeration	TechnicalContact	An individual who can provide specific information with regard to the resource or supporting software																																													
Used by	Element	Role																																													
Source	<pre> <xsd:simpleType name="enumRole"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the assigned or assumed function or position of an individual.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="ArchiveSpecialist"> <xsd:annotation> <xsd:documentation xml:lang="en">An individual who is an expert on a collection </xsd:documentation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>																																														

```
of resources and may also be knowledgeable
of the phenomenon and related physics represented
by the resources. This includes librarians,
curators, archive scientists and other experts.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="CoInvestigator">
<xsd:annotation>
<xsd:documentation xml:lang="en">An individual who is a scientific peer and
major participant in an investigation.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Contributor">
<xsd:annotation>
<xsd:documentation xml:lang="en">An entity responsible for making contributions
to the content of the resource.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="DataProducer">
<xsd:annotation>
<xsd:documentation xml:lang="en">An individual who generated the resource and
is familiar with its provenance.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="DeputyPI">
<xsd:annotation>
<xsd:documentation xml:lang="en">An individual who is an administrative or
scientific leader for an investigation operating
under the supervision of a Principal Investigator.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="FormerPI">
<xsd:annotation>
<xsd:documentation xml:lang="en">An individual who had served as the
administrative
and scientific lead for an investigation,
but no longer assumes that role.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="GeneralContact">
<xsd:annotation>
<xsd:documentation xml:lang="en">An individual who can provide information
on a range of subjects or who can direct you
to a domain expert.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="MetadataContact">
<xsd:annotation>
<xsd:documentation xml:lang="en">
```

	<pre> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="TeamMember"> <xsd:annotation> <xsd:documentation xml:lang="en">An individual who is a major participant in an investigation.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="TechnicalContact"> <xsd:annotation> <xsd:documentation xml:lang="en">An individual who can provide specific information with regard to the resource or supporting software</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumAssociationType

Namespace	http://www.spase-group.org/data/schema																			
Annotations	Identifiers for resource associations.																			
Diagram	<pre> classDiagram enumAssociationType < -- xsd:string </pre>																			
Type	restriction of xsd:string																			
Facets	<table border="1"> <tr> <td>enumeration</td> <td>ChildEventOf</td> <td>A descendant or caused by another resource.</td> </tr> <tr> <td>enumeration</td> <td>DerivedFrom</td> <td>A transformed or altered version of a resource instance.</td> </tr> <tr> <td>enumeration</td> <td>ObservedBy</td> <td>Detected or originating from another resource.</td> </tr> <tr> <td>enumeration</td> <td>Other</td> <td>Not classified with more specific terms. The context of its usage may be described in related text.</td> </tr> <tr> <td>enumeration</td> <td>PartOf</td> <td>A portion of a larger resource.</td> </tr> <tr> <td>enumeration</td> <td>RevisionOf</td> <td>A modified version of a resource instance.</td> </tr> </table>		enumeration	ChildEventOf	A descendant or caused by another resource.	enumeration	DerivedFrom	A transformed or altered version of a resource instance.	enumeration	ObservedBy	Detected or originating from another resource.	enumeration	Other	Not classified with more specific terms. The context of its usage may be described in related text.	enumeration	PartOf	A portion of a larger resource.	enumeration	RevisionOf	A modified version of a resource instance.
enumeration	ChildEventOf	A descendant or caused by another resource.																		
enumeration	DerivedFrom	A transformed or altered version of a resource instance.																		
enumeration	ObservedBy	Detected or originating from another resource.																		
enumeration	Other	Not classified with more specific terms. The context of its usage may be described in related text.																		
enumeration	PartOf	A portion of a larger resource.																		
enumeration	RevisionOf	A modified version of a resource instance.																		
Used by	Element	AssociationType																		
Source	<pre> <xsd:simpleType name="enumAssociationType"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for resource associations.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="ChildEventOf"> <xsd:annotation> <xsd:documentation xml:lang="en">A descendant or caused by another resource.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="DerivedFrom"> <xsd:annotation> <xsd:documentation xml:lang="en">A transformed or altered version of a resource instance.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="ObservedBy"> <xsd:annotation> <xsd:documentation xml:lang="en">Detected or originating from another resource.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Other"> <xsd:annotation> <xsd:documentation xml:lang="en">Not classified with more specific terms. The context of its usage may be described in related text.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="PartOf"> <xsd:annotation> </pre>																			

	<pre> <xsd:documentation xml:lang="en">A portion of a larger resource.</ xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="RevisionOf"> <xsd:annotation> <xsd:documentation xml:lang="en">A modified version of a resource instance.</ xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumAvailability

Namespace	http://www.spase-group.org/data/schema								
Annotations	Identifiers for indicating the method or service which may be used to access the resource.								
Diagram									
Type	restriction of xsd:string								
Facets	<table> <tr> <td>enumeration</td> <td>Offline</td> <td>Not directly accessible electronically. This includes resources which may be moved to an on-line status in response to a given request.</td> </tr> <tr> <td>enumeration</td> <td>Online</td> <td>Directly accessible electronically.</td> </tr> </table>			enumeration	Offline	Not directly accessible electronically. This includes resources which may be moved to an on-line status in response to a given request.	enumeration	Online	Directly accessible electronically.
enumeration	Offline	Not directly accessible electronically. This includes resources which may be moved to an on-line status in response to a given request.							
enumeration	Online	Directly accessible electronically.							
Used by	Element	Availability							
Source	<pre> <xsd:simpleType name="enumAvailability"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for indicating the method or service which may be used to access the resource.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Offline"> <xsd:annotation> <xsd:documentation xml:lang="en">Not directly accessible electronically. This includes resources which may be moved to an on-line status in response to a given request.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Online"> <xsd:annotation> <xsd:documentation xml:lang="en">Directly accessible electronically.</ xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>								
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd								

Simple Type enumAccessRights

Namespace	http://www.spase-group.org/data/schema								
Annotations	Identifiers for permissions granted or denied by the host of a product to allow other users to access and use the resource.								
Diagram									
Type	restriction of xsd:string								
Facets	<table> <tr> <td>enumeration</td> <td>Open</td> <td>Access is granted to everyone.</td> </tr> <tr> <td>enumeration</td> <td>Restricted</td> <td>Access to the product is regulated and requires some form of identification.</td> </tr> </table>			enumeration	Open	Access is granted to everyone.	enumeration	Restricted	Access to the product is regulated and requires some form of identification.
enumeration	Open	Access is granted to everyone.							
enumeration	Restricted	Access to the product is regulated and requires some form of identification.							
Used by	Element	AccessRights							
Source	<pre> <xsd:simpleType name="enumAccessRights"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for permissions granted or denied by the host of a product to allow other users to access and use the resource.</xsd:documentation></pre>								

```

</xsd:annotation>
<xsd:restriction base="xsd:string">
    <xsd:enumeration value="Open">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">Access is granted to everyone.</
xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="Restricted">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">Access to the product is regulated and requires
some form of identification.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
</xsd:restriction>
</xsd:simpleType>

```

Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd
-----------------	---

Simple Type enumFormat

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for data organized according to preset specifications.		
Diagram	<pre> classDiagram class enumFormat class xsd.string enumFormat "1" -- "2" xsd.string </pre>		
Type	restriction of xsd:string		
Facets	enumeration	AVI	Audio Video Interleave (AVI) a digital format for movies that conforms to the Microsoft Windows Resource Interchange File Format (RIFF).
	enumeration	Binary	A direct representation of the bits which may be stored in memory on a computer.
	enumeration	CDF	Common Data Format (CDF). A binary storage format developed at Goddard Space Flight Center (GSFC).
	enumeration	CEF	Cluster Exchange Format (CEF) is a self-documenting ASCII format designed for the exchange of data. There are two versions of CEF which are not totally compatible.
	enumeration	CEF1	Cluster Exchange Format (CEF), version 1, is a self-documenting ASCII format designed for the exchange of data. The metadata contains information compatible with the ISTP recommendations for CDF.
	enumeration	CEF2	Cluster Exchange Format (CEF), version 2, is a self-documenting ASCII format designed for the exchange of data and introduced for Cluster Active Archive. Compared to version 1, the metadata description of vectors and tensors is different.
	enumeration	Excel	A Microsoft spreadsheet format used to hold a variety of data in tables which can include calculations.
	enumeration	FITS	Flexible Image Transport System (FITS) is a digital format primarily designed to store scientific data sets consisting of multi-dimensional arrays (1-D spectra, 2-D images or 3-D data cubes) and 2-dimensional tables containing rows and columns of data.
	enumeration	GIF	Graphic Interchange Format (GIF) first introduced in 1987 by CompuServe. GIF uses LZW compression and images are limited to 256 colours.
	enumeration	Hardcopy	A permanent reproduction, or copy in the form of a physical object, of any media suitable

		for direct use by a person.
enumeration	Hardcopy.Film	An image recording medium on which usually a "negative" analog image is registered. A "positive" image can be recovered or reproduced from film, which is usually made of flexible materials for ease of storage and transportation.
enumeration	Hardcopy.Microfiche	A sheet of microfilm on which many pages of material have been photographed; a magnification system is used to read the material.
enumeration	Hardcopy.Microfilm	Film rolls on which materials are photographed at greatly reduced size; a magnification system is used to read the material.
enumeration	Hardcopy.Photograph	An image (positive or negative) registered on a piece of photo-sensitive paper
enumeration	Hardcopy.PhotographicPlate	A rigid (typically glass) medium that functions like film. Its rigidity is for guarding against image distortion due to medium deformation (caused by heat and humidity). Photographic plates are often used for astronomical photography.
enumeration	Hardcopy.Print	A sheet of any written or printed material which may include notes or graphics. Multiple printed pages may be bound into a manuscript or book.
enumeration	HDF	Hierarchical Data Format
enumeration	HDF4	Hierarchical Data Format, Version 4
enumeration	HDF5	Hierarchical Data Format, Version 5
enumeration	HTML	A text file containing structured information represented in the HyperText Mark-up Language (HTML). See < http://www.w3.org/MarkUp/ >
enumeration	IDFS	Instrument Data File Set (IDFS) is a set of files written in a prescribed format which contain data, timing data, and meta-data. IDFS was developed at Southwest Research Institute (SwRI).
enumeration	IDL	Interactive Data Language (IDL) save set. IDL is a proprietary format.
enumeration	JPEG	A binary format for still images defined by the Joint Photographic Experts Group
enumeration	MATLAB_4	MATLAB Workspace save set, version 4. MAT-files are double-precision, binary, MATLAB format files. MATLAB is a proprietary product of The MathWorks.
enumeration	MATLAB_6	MATLAB Workspace save set, version 6. MAT-files are double-precision, binary, MATLAB format files. MATLAB is a proprietary product of The MathWorks.
enumeration	MATLAB_7	MATLAB Workspace save set, version 7. MAT-files are double-precision, binary, MATLAB format files. Version 7 includes data compression and Unicode encoding. MATLAB is a proprietary product of The MathWorks.
enumeration	MPEG	A digital format for movies defined by the Motion Picture Experts Group
enumeration	NCAR	The National Center for Atmospheric Research (NCAR) format. A complete description of that

		<p>standard is given in appendix C of the "Report on Establishment & Operation of the Incoherent-Scatter Data Base", dated August 23, 1984, obtainable from NCAR, P.O. Box 3000 Boulder, Colorado 80307-3000.</p>
enumeration	NetCDF	Unidata Program Centers Network Common Data Form (NetCDF). A self-describing portable data format for array-oriented data access. See < http://my.unidata.ucar.edu/content/software/netcdf >
enumeration	PDF	A document expressed in the Portable Document Format (PDF) as defined by Adobe.
enumeration	PNG	A digital format for still images. Portable Network Graphics (PNG)
enumeration	Postscript	A page description programming language created by Adobe Systems Inc. that is a device-independent industry standard for representing text and graphics.
enumeration	QuickTime	A format for digital movies, as defined by Apple Computer. See < http://developer.apple.com/quicktime/ >
enumeration	Text	A sequence of characters which may have an imposed structure or organization.
enumeration	Text.ASCII	A sequence of characters that adheres to American Standard Code for Information Interchange (ASCII) which is an 7-bit character-coding scheme.
enumeration	Text.Unicode	Text in multi-byte Unicode format.
enumeration	TIFF	A binary format for still pictures. Tagged Image Format File (TIFF). Originally developed by Aldus and now controlled by Adobe.
enumeration	UDF	Universal Data Format (UDF). The Optical Technology Storage Associations Universal Disk Format, based on ISO 13346. See < http://www.osta.org/specs/index.htm >
enumeration	VOTable	A proposed IVOA standard designed as a flexible storage and exchange format for tabular data.
enumeration	XML	eXtensible Mark-up Language (XML). A structured format for representing information. See < http://www.w3.org/XML/ >
Used by	Element	Format
Source	<pre> <xsd:simpleType name="enumFormat"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for data organized according to preset specifications.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="AVI"> <xsd:annotation> <xsd:documentation xml:lang="en">Audio Video Interleave (AVI) a digital format for movies that conforms to the Microsoft Windows Resource Interchange File Format (RIFF).</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Binary"> <xsd:annotation> <xsd:documentation xml:lang="en">A direct representation of the bits which may be stored in memory on a computer.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="CDF"> <xsd:annotation> <xsd:documentation xml:lang="en">Common Data Format (CDF). A binary storage </pre>	

```

        format developed at Goddard Space Flight Center
        (GSFC).</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="CEF">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Cluster Exchange Format (CEF) is a self-
documenting
            ASCII format designed for the exchange of
            data. There are two versions of CEF which
            are not totally compatible.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="CEF1">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Cluster Exchange Format (CEF), version 1,
            is a self-documenting ASCII format designed
            for the exchange of data. The metadata contains
            information compatible with the ISTP recommendations
            for CDF.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="CEF2">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Cluster Exchange Format (CEF), version 2,
            is a self-documenting ASCII format designed
            for the exchange of data and introduced for
            Cluster Active Archive. Compared to version
            1, the metadata description of vectors and
            tensors is different.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Excel">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A Microsoft spreadsheet format used to hold
            a variety of data in tables which can include
            calculations.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="FITS">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Flexible Image Transport System (FITS) is
            a digital format primarily designed to store
            scientific data sets consisting of multi-dimensional
            arrays (1-D spectra, 2-D images or 3-D data
            cubes) and 2-dimensional tables containing
            rows and columns of data.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="GIF">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Graphic Interchange Format (GIF) first introduced
            in 1987 by CompuServe. GIF uses LZW compression
            and images are limited to 256 colours.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Hardcopy">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A permanent reproduction, or copy in the form
            of a physical object, of any media suitable
            for direct use by a person.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Hardcopy.Film">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">An image recording medium on which usually
            a "negative" analog image is registered. A
            "positive" image can be recovered or reproduced
            from film, which is usually made of flexible
            materials for ease of storage and transportation.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Hardcopy.Microfiche">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A sheet of microfilm on which many pages of
            material have been photographed; a magnification
            system is used to read the material.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Hardcopy.Microfilm">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Film rolls on which materials are photographed
            at greatly reduced size; a magnification system

```

```

        is used to read the material.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Hardcopy.Photograph">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">An image (positive or negative) registered
            on a piece of photo-sensitive paper</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Hardcopy.PhotographicPlate">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A rigid (typically glass) medium that functions
            like film. Its rigidity is for guarding against
            image distortion due to medium deformation
            (caused by heat and humidity). Photographic
            plates are often used for astronomical photography.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Hardcopy.Print">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A sheet of any written or printed material
            which may include notes or graphics. Multiple
            printed pages may be bound into a manuscript
            or book.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HDF">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Hierarchical Data Format</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HDF4">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Hierarchical Data Format, Version 4</
xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HDF5">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Hierarchical Data Format, Version 5</
xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HTML">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A text file containing structured information
            represented in the HyperText Mark-up Language
            (HTML). See <a href="http://www.w3.org/MarkUp/"></a></xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="IDFS">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Instrument Data File Set (IDFS) is a set of
            files written in a prescribed format which
            contain data, timing data, and meta-data.
            IDFS was developed at Southwest Research Institute
            (SwRI).</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="IDL">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Interactive Data Language (IDL) save set.
            IDL is a proprietary format.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="JPEG">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A binary format for still images defined by
            the Joint Photographic Experts Group</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="MATLAB_4">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">MATLAB Workspace save set, version 4. MAT-files
            are double-precision, binary, MATLAB format
            files. MATLAB is a proprietary product of
            The MathWorks.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="MATLAB_6">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">MATLAB Workspace save set, version 6. MAT-files
            are double-precision, binary, MATLAB format

```

```

        files. MATLAB is a proprietary product of
        The MathWorks.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="MATLAB_7">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">MATLAB Workspace save set, version 7. MAT-files
            are double-precision, binary, MATLAB format
            files. Version 7 includes data compression
            and Unicode encoding. MATLAB is a proprietary
            product of The MathWorks.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="MPEG">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A digital format for movies defined by the
            Motion Picture Experts Group</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="NCAR">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The National Center for Atmospheric Research
            (NCAR) format. A complete description of that
            standard is given in appendix C of the "Report
            on Establishment & Operation of the Incoherent-
            Scatter Data Base", dated August 23, 1984,
            obtainable from NCAR, P.O. Box 3000 Boulder,
            Colorado 80307-3000.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="NetCDF">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Unidata Program Center's Network Common Data
            Form (NetCDF). A self-describing portable
            data format for array-oriented data access.
            See <a href="http://my.unidata.ucar.edu/content/software/netcdf"></xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="PDF">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A document expressed in the Portable Document
            Format (PDF) as defined by Adobe.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="PNG">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A digital format for still images. Portable
            Network Graphics (PNG)</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Postscript">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A page description programming language created
            by Adobe Systems Inc. that is a device-independent
            industry standard for representing text and
            graphics.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="QuickTime">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A format for digital movies, as defined by
            Apple Computer. See <a href="http://developer.apple.com/quicktime/"></xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Text">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A sequence of characters which may have an
            imposed structure or organization.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Text.ASCII">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A sequence of characters that adheres to American
            Standard Code for Information Interchange
            (ASCII) which is an 7-bit character-coding
            scheme.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Text.Unicode">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Text in multi-byte Unicode format.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>

```

	<pre> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="TIFF"> <xsd:annotation> <xsd:documentation xml:lang="en">A binary format for still pictures. Tagged Image Format File (TIFF). Originally developed by Aldus and now controlled by Adobe.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="UDF"> <xsd:annotation> <xsd:documentation xml:lang="en">Universal Data Format (UDF). The Optical Technology Storage Association's Universal Disk Format, based on ISO 13346. See <http://www.osta.org/specs/index.htm></ xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="VOTable"> <xsd:annotation> <xsd:documentation xml:lang="en">A proposed IVOA standard designed as a flexible storage and exchange format for tabular data.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="XML"> <xsd:annotation> <xsd:documentation xml:lang="en">eXtensible Markup Language (XML). A structured format for representing information. See <http://www.w3.org/XML/></ xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumEncoding

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for unambiguous rules that establishes the representation of information within a file.		
Diagram	<pre> graph LR enumEncoding --- xsdstring classDef="enumEncoding" classDef="xsdstring" </pre>		
Type	restriction of xsd:string		
Facets	enumeration	ASCII	A sequence of characters that adheres to American Standard Code for Information Interchange (ASCII) which is an 7-bit character-coding scheme.
	enumeration	Base64	A data encoding scheme whereby binary-encoded data is converted to printable ASCII characters. It is defined as a MIME content transfer encoding for use in Internet e-mail. The only characters used are the upper- and lower-case Roman alphabet characters (A-Z, a-z), the numerals (0-9), and the "+" and "/" symbols, with the "=" symbol as a special suffix (padding) code.
	enumeration	BZIP2	An open standard algorithm by Julian Seward using Burrows-Wheeler block sorting and Huffman coding. See < http://www.bzip.org/ >
	enumeration	GZIP	An open standard algorithm distributed by GHU based on LZ77 and Huffman coding. See < http://www.gnu.org/software/gzip/gzip.html > or < http://www.gzip.org/ >
	enumeration	None	A lack or absence of anything.
	enumeration	S3_BUCKET	A container of objects that comply with the Amazon Simple Storage Service (S3) specifications. A bucket has a unique, user-assigned key (name).

		A bucket can contain any number of objects with an aggregate size of 5 gigabytes. A bucket may be accompanied by up to 2 kilobytes of metadata.
	enumeration	TAR
	enumeration	Unicode
	enumeration	ZIP
Used by	Element	Encoding
Source		<pre> <xsd:simpleType name="enumEncoding"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for unambiguous rules that establishes the representation of information within a file.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="ASCII"> <xsd:annotation> <xsd:documentation xml:lang="en">A sequence of characters that adheres to American Standard Code for Information Interchange (ASCII) which is an 7-bit character-coding scheme.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Base64"> <xsd:annotation> <xsd:documentation xml:lang="en">A data encoding scheme whereby binary-encoded data is converted to printable ASCII characters. It is defined as a MIME content transfer encoding for use in Internet e-mail. The only characters used are the upper- and lower-case Roman alphabet characters (A-Z, a-z), the numerals (0-9), and the "+" and "/" symbols, with the "=" symbol as a special suffix (padding) code.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="BZIP2"> <xsd:annotation> <xsd:documentation xml:lang="en">An open standard algorithm by Julian Seward using Burrows-Wheeler block sorting and Huffman coding. See </xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="GZIP"> <xsd:annotation> <xsd:documentation xml:lang="en">An open standard algorithm distributed by GHU based on LZ77 and Huffman coding. See or </xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="None"> <xsd:annotation> <xsd:documentation xml:lang="en">A lack or absence of anything.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="S3_BUCKET"> <xsd:annotation> <xsd:documentation xml:lang="en">A container of objects that comply with the Amazon Simple Storage Service (S3) specifications. A bucket has a unique, user-assigned key (name). A bucket can contain any number of objects with an aggregate size of 5 gigabytes. A bucket may be accompanied by up to 2 kilobytes of metadata.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>

```

<xsd:enumeration value="TAR">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A file format used to collate collections
      of files into one larger file, for distribution
      or archiving, while preserving file system
      information such as user and group permissions,
      dates, and directory structures. The format
      was standardized by POSIX.1-1988 and later
      POSIX.1-2001.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Unicode">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Text in multi-byte Unicode format.</
xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="ZIP">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">An open standard for compression which is
      a variation of the LZW method and was originally
      used in the PKZIP utility.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
</xsd:restriction>
</xsd:simpleType>

```

Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd
-----------------	---

Simple Type enumPhenomenonType

Namespace	http://www.spase-group.org/data/schema	
Annotations	Identifiers for the characteristics or categorization of an observation. Note: Joe King to provide.	
Diagram	<pre> classDiagram enumPhenomenonType < -- xsd:string </pre>	
Type	restriction of xsd:string	
Facets	enumeration ActiveRegion enumeration Aurora enumeration BowShockCrossing enumeration CoronalHole enumeration CoronalMassEjection enumeration EITWave	<p>A localized, transient volume of the solar atmosphere in which PLAGEs, SUNSPOTS, FACULAE, FLAREs, etc. may be observed.</p> <p>An atmospheric phenomenon consisting of bands of light caused by charged solar particles following the earth's magnetic lines of force.</p> <p>A crossing of the boundary between the undisturbed (except for foreshock effects) solar wind and the shocked, decelerated solar wind of the magnetosheath.</p> <p>An extended region of the corona, exceptionally low in density and associated with unipolar photospheric regions. A coronal hole can be an "open" magnetic field in the corona and (perhaps) inner heliosphere which has a faster than average outflow (wind); A region of lower than "quiet" ion and electron density in the corona; or a region of lower peak electron temperature in the corona than in the "quiet" corona.</p> <p>A solar event (CME) that involves a burst of plasma ejected into the interplanetary medium. CMEs may be observed remotely near the sun or in situ in the interplanetary medium. The latter type of observations are often referred to as Interplanetary CMEs (ICMEs).</p> <p>A wave in the corona of the Sun which produce</p>

		<p>shock waves on the Sun's chromosphere (Moreton Waves). EIT Waves are produced by large solar flare and expand outward at about 1,000 km/s. It usually appears as a slowly moving diffuse arc of brightening in H-alpha, and may travel for several hundred thousand km.</p>
enumeration	EnergeticSolarParticleEvent	A enhancement of interplanetary fluxes of energetic ions accelerated by interplanetary shocks and/or solar flares.
enumeration	ForbushDecrease	A rapid decrease in the observed galactic cosmic ray intensity following the passage of an outwardly convecting interplanetary magnetic field disturbance, such as those associated with large CMEs, that sweep some galactic cosmic rays away from Earth.
enumeration	GeomagneticStorm	A magnetospheric disturbance typically defined by variations in the horizontal component of the Earth's surface magnetic field. The variation typically starts with a field enhancement associated with a solar wind pressure pulse and continues with a field depression associated with an enhancement of the diamagnetic magnetospheric ring current.
enumeration	InterplanetaryShock	A shock propagating generally anti-sunward through the slower solar wind, often seen in front of CME-associated plasma clouds.
enumeration	MagneticCloud	A transient event observed in the solar wind characterized as a region of enhanced magnetic field strength, smooth rotation of the magnetic field vector and low proton density and temperature.
enumeration	MagnetopauseCrossing	A crossing of the interface between the shocked solar wind in the magnetosheath and the magnetic field and plasma in the magnetosphere.
enumeration	RadioBurst	Emissions of the sun in radio wavelengths from centimeters to dekameters, under both quiet and disturbed conditions. Radio Bursts can be "Type I" consisting of many short, narrow-band bursts in the metric range (300 - 50 MHz); "Type II" consisting of narrow-band emission that begins in the meter range (300 MHz) and sweeps slowly (tens of minutes) toward dekameter wavelengths (10 MHz); "Type III" consisting of narrow-band bursts that sweep rapidly (seconds) from decimeter to dekameter wavelengths (500 - 0.5 MHz); and "Type IV" consisting of a smooth continuum of broad-band bursts primarily in the meter range (300 - 30 MHz).
enumeration	SolarFlare	An explosive event in the Sun's atmosphere which produces electromagnetic radiation across the electromagnetic spectrum at multiple wavelengths from long-wave radio to the shortest wavelength gamma rays.
enumeration	SolarWindExtreme	Intervals of unusually large or small values of solar wind attributes such as flow speed and ion density.

	enumeration	StreamInteractionRegion The region (SIR) where two solar wind streams, typically having differing characteristics and solar sources, abut up against (and possibly partially interpenetrate) each other.
	enumeration	Substorm A process by which plasma in the magnetotail becomes energized at a fast rate.
Used by	Element	PhenomenonType
Source	<pre> <xsd:simpleType name="enumPhenomenonType"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the characteristics or categorization of an observation. Note: Joe King to provide.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="ActiveRegion"> <xsd:annotation> <xsd:documentation xml:lang="en">A localized, transient volume of the solar atmosphere in which PLAGEs, SUNSPOTS, FACULAE, FLARES, etc. may be observed.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Aurora"> <xsd:annotation> <xsd:documentation xml:lang="en">An atmospheric phenomenon consisting of bands of light caused by charged solar particles following the earth's magnetic lines of force.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="BowShockCrossing"> <xsd:annotation> <xsd:documentation xml:lang="en">A crossing of the boundary between the undisturbed (except for foreshock effects) solar wind and the shocked, decelerated solar wind of the magnetosheath.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="CoronalHole"> <xsd:annotation> <xsd:documentation xml:lang="en">An extended region of the corona, exceptionally low in density and associated with unipolar photospheric regions. A coronal hole can be an "open" magnetic field in the corona and (perhaps) inner heliosphere which has a faster than average outflow (wind); A region of lower than "quiet" ion and electron density in the corona; or a region of lower peak electron temperature in the corona than in the "quiet" corona.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="CoronalMassEjection"> <xsd:annotation> <xsd:documentation xml:lang="en">A solar event (CME) that involves a burst of plasma ejected into the interplanetary medium. CME's may be observed remotely relatively near the sun or in situ in the interplanetary medium. The latter type of observations are often referred to as Interplanetary CME's (ICME's).</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="EITWave"> <xsd:annotation> <xsd:documentation xml:lang="en">A wave in the corona of the Sun which produce shock waves on the Sun's chromosphere (Moreton Waves). EIT Waves are produced by large solar flare and expand outward at about 1,000 km/s. It usually appears as a slowly moving diffuse arc of brightening in H-alpha, and may travel for several hundred thousand km.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="EnergeticSolarParticleEvent"> <xsd:annotation> <xsd:documentation xml:lang="en">An enhancement of interplanetary fluxes of energetic ions accelerated by interplanetary shocks and/or solar flares.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>	

```

    </xsd:enumeration>
    <xsd:enumeration value="ForbushDecrease">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">A rapid decrease in the observed galactic
                cosmic ray intensity following the passage
                of an outwardly convecting interplanetary
                magnetic field disturbance, such as those
                associated with large CME's, that sweep some
                galactic cosmic rays away from Earth.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="GeomagneticStorm">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">A magnetospheric disturbance typically defined
                by variations in the horizontal component
                of the Earth's surface magnetic field. The
                variation typically starts with a field enhancement
                associated with a solar wind pressure pulse
                and continues with a field depression associated
                with an enhancement of the diamagnetic magnetospheric
                ring current.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="InterplanetaryShock">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">A shock propagating generally anti-sunward
                through the slower solar wind, often seen
                in front of CME-associated plasma clouds.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="MagneticCloud">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">A transient event observed in the solar wind
                characterized as a region of enhanced magnetic
                field strength, smooth rotation of the magnetic
                field vector and low proton density and temperature.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="MagnetopauseCrossing">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">A crossing of the interface between the shocked
                solar wind in the magnetosheath and the magnetic
                field and plasma in the magnetosphere.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="RadioBurst">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">Emissions of the sun in radio wavelengths
                from centimeters to dekameters, under both
                quiet and disturbed conditions. Radio Bursts
                can be "Type I" consisting of many short,
                narrow-band bursts in the metric range (300
                - 50 MHz); "Type II" consisting of narrow-band
                emission that begins in the meter range (300
                MHz) and sweeps slowly (tens of minutes) toward
                dekameter wavelengths (10 MHz); "Type III"
                consisting of narrow-band bursts that sweep
                rapidly (seconds) from decimeter to dekameter
                wavelengths (500 - 0.5 MHz); and "Type IV"
                consisting of a smooth continuum of broad-band
                bursts primarily in the meter range (300 -
                30 MHz).</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="SolarFlare">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">An explosive event in the Sun's atmosphere
                which produces electromagnetic radiation across
                the electromagnetic spectrum at multiple wavelengths
                from long-wave radio to the shortest wavelength
                gamma rays.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="SolarWindExtreme">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">Intervals of unusually large or small values
                of solar wind attributes such as flow speed
                and ion density.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="StreamInteractionRegion">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">The region (SIR) where two solar wind streams,

```

	<pre> typically having differing characteristics and solar sources, abut up against (and possibly partially interpenetrate) each other.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Substorm"> <xsd:annotation> <xsd:documentation xml:lang="en">A process by which plasma in the magnetotail becomes energized at a fast rate.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumCoordinateRepresentation

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers of the method or form for specifying a given point or vector in a given coordinate system.		
Diagram	<pre> classDiagram class enumCoordinateRepresentation class xsd:string enumCoordinateRepresentation --> > xsd:string </pre>		
Type	restriction of xsd:string		
Facets	enumeration	Cartesian	A representation in which a position vector or a measured vector (e.g., field or flow) is specified by its components along the base axes of the coordinate system.
	enumeration	Cylindrical	A coordinate representation of a position vector or measured vector (field or flow) by its k-component, the magnitude of its projection into the i-j plane, and the azimuthal angle of the i-j plane projection.
	enumeration	Spherical	A coordinate representation of a position vector or of a measured vector by its magnitude and two direction angles. The angles are relative to the base axes of the coordinate system used. Typically the angles are phi [azimuth angle, =arctan (j/i)] and theta, where theta may be a polar angle, arctan {[SQRT(i^2+j^2)]/k}, or an elevation angle, arctan [k/SQRT (i^2+j^2)].
Used by	Element	CoordinateRepresentation	
Source	<pre> <xsd:simpleType name="enumCoordinateRepresentation"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers of the method or form for specifying a given point or vector in a given coordinate system.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Cartesian"> <xsd:annotation> <xsd:documentation xml:lang="en">A representation in which a position vector or a measured vector (e.g., field or flow) is specified by its components along the base axes of the coordinate system.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Cylindrical"> <xsd:annotation> <xsd:documentation xml:lang="en">A coordinate representation of a position vector or measured vector (field or flow) by its k-component, the magnitude of its projection into the i-j plane, and the azimuthal angle of the i-j plane projection.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Spherical"> <xsd:annotation> <xsd:documentation xml:lang="en">A coordinate representation of a position</pre>		

	<pre> vector or of a measured vector by its magnitude and two direction angles. The angles are relative to the base axes of the coordinate system used. Typically the angles are phi [azimuth angle, =arctan (j/i)] and theta, where theta may be a polar angle, arctan {[SQRT(i^2+j^2)]/k}, or an elevation angle, arctan [k/SQRT (i^2+j^2)].</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumCoordinateSystemName

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers of the origin and orientation of a set of typically orthogonal axes.		
Diagram	<pre> classDiagram class enumCoordinateSystemName { <<enum>> } class xsdString { <<xs:string>> } enumCoordinateSystemName ⊞ xsdString </pre>		
Type	restriction of xsd:string		
Facets	enumeration	Carrington	A coordinate system which is centered at the Sun and is "fixed" with respect to the synodic rotation rate; the mean synodic value is about 27.2753 days. The Astronomical Almanac gives a value for Carrington longitude of 349.03 degrees at 0000 UT on 1 January 1995.
	enumeration	CGM	Corrected Geomagnetic - A coordinate system from a spatial point with GEO radial distance and geomagnetic latitude and longitude, follow the epoch-appropriate IGRF/DGRF model field vector through to the point where the field line crosses the geomagnetic dipole equatorial plane. Then trace the dipole magnetic field vector Earthward from that point on the equatorial plane, in the same hemisphere as the original point, until the initial radial distance is reached. Designate the dipole latitude and longitude at that point as the CGM latitude and longitude of the original point. See < http://nssdc.gsfc.nasa.gov/space/cgm/cgmm_des.html >
	enumeration	DM	Dipole Meridian - A coordinate system centered at the observation point. Z axis is parallel to the Earth's dipole axis, positive northward. X is in the plane defined by Z and the line linking the observation point with the Earth's center. Y is positive eastward. See < http://cdpp.cnes.fr/00428.pdf >
	enumeration	GEI	Geocentric Equatorial Inertial - A coordinate system where the Z axis is along Earth's spin vector, positive northward. X axis points towards the first point of Aries (from the Earth towards the Sun at the vernal equinox). See Russell, 1971
	enumeration	GEO	Geographic - geocentric corotating - A coordinate system where the Z axis is along Earth's spin vector, positive northward. X axis lies in Greenwich meridian, positive towards Greenwich. See Russell, 1971.
	enumeration	GSE	Geocentric Solar Ecliptic - A coordinate system

		where the X axis is from Earth to Sun. Z axis is normal to the ecliptic, positive northward. See Russell, 1971.
enumeration	GSEQ	Geocentric Solar Equatorial - A coordinate system where the X axis is from Earth to Sun. Y axis is parallel to solar equatorial plane. Z axis is positive northward. See Russell, 1971
enumeration	GSM	Geocentric Solar Magnetospheric - A coordinate system where the X axis is from Earth to Sun, Z axis is northward in a plane containing the X axis and the geomagnetic dipole axis. See Russell, 1971
enumeration	HAE	Heliocentric Aries Ecliptic - A coordinate system where the Z axis is normal to the ecliptic plane, positive northward. X axis is positive towards the first point of Aries (from Earth to Sun at vernal equinox). Same as SE below. See Hapgood, 1992.
enumeration	HCC	Heliocentric Cartesian - A 3-D orthonormal coordinate system that is primarily intended to specify with two dimensions a point on the solar disk. The Z axis points toward the observer. The Y axis lies in the plane defined by the solar spin vector and the Z axis, positive northward. The X axis is perpendicular to the Y and Z axes, positive toward solar west. Standard representation for this system is via the points x and y values, expressed either as physical distances or as fractions of the solar disk radius.
enumeration	HCI	Heliographic Carrington Inertial.
enumeration	HCR	Heliocentric Radial - A 3-D orthonormal coordinate system that is primarily intended to specify with two dimensions a point on the solar disk. The Z axis points toward the observer. The Y axis lies in the plane defined by the solar spin vector and the Z axis, positive northward. The X axis is perpendicular to the Y and Z axes, positive toward solar west. Standard representation for this system is via the points distance rho from the Z axis [Rho = SQRT(x**2 + y**2)] and its phase angle psi measured counterclockwise from the +Y axis [psi = arctan (-y/x)]
enumeration	HEE	Heliocentric Earth Ecliptic - A coordinate system where the Z axis is normal to the ecliptic plane, positive northward. X axis points from Sun to Earth. See Hapgood, 1992
enumeration	HEEQ	Heliocentric Earth Equatorial - A coordinate system where the Z axis is normal to the solar equatorial plane, positive northward. X axis is generally Earthward in the plane defined by the Z axis and the Sun-Earth direction. See Hapgood, 1992.
enumeration	HG	Heliographic - A heliocentric rotating coordinate system where the Z axis is normal to the solar equatorial plane, positive northward. X, Y

		<p>axes rotate with a 25.38 day period. The zero longitude (X axis) is defined as the longitude that passed through the ascending node of the solar equator on the ecliptic plane on 1 January, 1854 at 12 UT. See <http://nssdc.gsfc.nasa.gov/space/helios/coor_des.html></p>
enumeration	HGI	<p>Heliographic Inertial - A heliocentric coordinate system where the Z axis is normal to the solar equatorial plane, positive northward. X axis is along the intersection line between solar equatorial and ecliptic planes. The X axis was positive at SE longitude of 74.367 deg on Jan 1, 1900. (See SE below.) See <http://nssdc.gsfc.nasa.gov/space/helios/coor_des.html></p>
enumeration	HPC	<p>Helio-projective Cartesian = A 3-D orthonormal (left-handed) coordinate system that is primarily intended to specify with two dimensions a point on the solar disk. The Z axis points from the observer to the center of the solar disk. The Y axis lies in the plane defined by the solar spin vector and the Z axis, positive northward. The X axis is perpendicular to the Y and Z axes, positive toward solar west. Given as the distance between the observer and the center of the solar disk, the standard representation of an (x,y) point on the solar disk is via the points longitude angle [$\arctan(x/d)$] and latitude angle [$\arctan(y/d)$].</p>
enumeration	HPR	<p>Helio-projective Radial - A 3-D orthonormal (left-handed) coordinate system that is primarily intended to specify with two dimensions a point on the solar disk. The Z axis points from the observer to the center of the solar disk. The Y axis lies in the plane defined by the solar spin vector and the Z axis, positive northward. The X axis is perpendicular to the Y and Z axes, positive toward solar west. Given as the distance between the observer and the center of the solar disk, the standard representation for this system of an (x,y) point on the solar disk is via the points latitude angle theta [= $\arctan(\sqrt{x^2 + y^2}/d)$] or equivalent declination parameter delta (= theta - 90 deg), and its phase angle psi as measured counter-clockwise from the +Y axis [psi = $\arctan(-y/x)$].</p>
enumeration	J2000	<p>An astronomical coordinate system which uses the mean equator and equinox of Julian date 2451545.0 TT (Terrestrial Time), or January 1, 2000, noon TT. (aka J2000) to define a celestial reference frame.</p>
enumeration	LGM	<p>Local Geomagnetic - A coordinate system used mainly for Earth surface or near Earth surface magnetic field data. X axis northward from observation point in a geographic meridian. Z axis downward towards Earth's center. In this system, H (total horizontal component) = $\sqrt{B_x^2 + B_y^2}$ and D (declination angle) = $\arctan(B_y/B_x)$</p>

enumeration	MAG	Geomagnetic - geocentric. Z axis is parallel to the geomagnetic dipole axis, positive north. X is in the plane defined by the Z axis and the Earth's rotation axis. If N is a unit vector from the Earth's center to the north geographic pole, the signs of the X and Y axes are given by $Y = N \times Z$, $X = Y \times Z$. See Russell, 1971, and http://cdpp.cnes.fr/00428.pdf
enumeration	MFA	Magnetic Field Aligned - A coordinate system spacecraft-centered system with Z in the direction of the ambient magnetic field vector. X is in the plane defined by Z and the spacecraft-Sun line, positive sunward. See http://cdpp.cnes.fr/00428.pdf
enumeration	RTN	Radial Tangential Normal. Typically centered at a spacecraft. Used for IMF and plasma V vectors. R (radial) axis is radially away from the Sun, T (tangential) axis is normal to the plane formed by R and the Sun's spin vector, positive in the direction of planetary motion. N (normal) is $R \times T$.
enumeration	SC	Spacecraft - A coordinate system defined by the spacecraft geometry and/or spin. Often has Z axis parallel to spacecraft spin vector. X and Y axes may or may not corotate with the spacecraft. See SR and SR2 below.
enumeration	SE	Solar Ecliptic - A heliocentric coordinate system where the Z axis is normal to the ecliptic plane, positive northward. X axis is positive towards the first point of Aries (from Earth to Sun at vernal equinox). Same as HAE above. See http://nssdc.gsfc.nasa.gov/space/helios/coor_des.html
enumeration	SM	Solar Magnetic - A geocentric coordinate system where the Z axis is northward along Earth's dipole axis, X axis is in plane of z axis and Earth-Sun line, positive sunward. See Russell, 1971.
enumeration	SpacecraftOrbitPlane	A coordinate system where X lies in the plane normal to and in the direction of motion of the spacecraft, Z is normal to this plane and Y completes the triad in a right-handed coordinate system.
enumeration	SR	Spin Reference - A special case of a Spacecraft (SC) coordinate system for a spinning spacecraft. Z is parallel to the spacecraft spin vector. X and Y rotate with the spacecraft. See http://cdpp.cnes.fr/00428.pdf
enumeration	SR2	Spin Reference 2 - A special case of a Spacecraft (SC) coordinate system for a spinning spacecraft. Z is parallel to the spacecraft spin vector. X is in the plane defined by Z and the spacecraft-Sun line, positive sunward. See http://cdpp.cnes.fr/00428.pdf
enumeration	SSE	Spacecraft Solar Ecliptic - A coordinate system used for deep space spacecraft, for example Helios. - X axis from spacecraft to Sun. Z axis normal to ecliptic plane, positive northward. Note: Angle between normals to ecliptic and

		to Helios orbit plane ~ 0.25 deg.
	enumeration SSE_L	Selenocentric Solar Ecliptic. The X axis points from the center of the Earth's moon to the sun, the Z axis is normal to the ecliptic plane, positive northward. And the Y axis completes the right-handed set of axes.
	enumeration WGS84	The World Geodetic System (WGS) defines a reference frame for the earth, for use in geodesy and navigation. The WGS84 uses the zero meridian as defined by the Bureau International de l'Heure.
Used by	Element	CoordinateSystemName
Source		<pre> <xsd:simpleType name="enumCoordinateSystemName"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers of the origin and orientation of a set of typically orthogonal axes.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Carrington"> <xsd:annotation> <xsd:documentation xml:lang="en">A coordinate system which is centered at the Sun and is "fixed" with respect to the synodic rotation rate; the mean synodic value is about 27.2753 days. The Astronomical Almanac gives a value for Carrington longitude of 349.03 degrees at 0000 UT on 1 January 1995.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="CGM"> <xsd:annotation> <xsd:documentation xml:lang="en">Corrected Geomagnetic - A coordinate system from a spatial point with GEO radial distance and geomagnetic latitude and longitude, follow the epoch-appropriate IGRF/DGRF model field vector through to the point where the field line crosses the geomagnetic dipole equatorial plane. Then trace the dipole magnetic field vector Earthward from that point on the equatorial plane, in the same hemisphere as the original point, until the initial radial distance is reached. Designate the dipole latitude and longitude at that point as the CGM latitude and longitude of the original point. See <http://nssdc.gsfc.nasa.gov/space/cgm/cgmm_des.html></xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="DM"> <xsd:annotation> <xsd:documentation xml:lang="en">Dipole Meridian - A coordinate system centered at the observation point. Z axis is parallel to the Earth's dipole axis, positive northward. X is in the plane defined by Z and the line linking the observation point with the Earth's center. Y is positive eastward. See <http://cdpp.cnrs.fr/00428.pdf></ <xsd:annotation> </xsd:enumeration> <xsd:enumeration value="GEI"> <xsd:annotation> <xsd:documentation xml:lang="en">Geocentric Equatorial Inertial - A coordinate system where the Z axis is along Earth's spin vector, positive northward. X axis points towards the first point of Aries (from the Earth towards the Sun at the vernal equinox). See Russell, 1971</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="GEO"> <xsd:annotation> <xsd:documentation xml:lang="en">Geographic - geocentric corotating - A coordinate system where the Z axis is along Earth's spin vector, positive northward. X axis lies in Greenwich meridian, positive towards Greenwich. See Russell, 1971.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="GSE"> <xsd:annotation></pre>

```

<xsd:documentation xml:lang="en">Geocentric Solar Ecliptic - A coordinate system
where the X axis is from Earth to Sun. Z axis
is normal to the ecliptic, positive northward.
See Russell, 1971.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="GSEQ">
<xsd:annotation>
<xsd:documentation xml:lang="en">Geocentric Solar Equatorial - A coordinate
system where the X axis is from Earth to Sun.
Y axis is parallel to solar equatorial plane.
Z axis is positive northward. See Russell,
1971</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="GSM">
<xsd:annotation>
<xsd:documentation xml:lang="en">Geocentric Solar Magnetospheric - A coordinate
system where the X axis is from Earth to Sun,
Z axis is northward in a plane containing
the X axis and the geomagnetic dipole axis.
See Russell, 1971</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HAE">
<xsd:annotation>
<xsd:documentation xml:lang="en">Heliocentric Aries Ecliptic - A coordinate
system where the Z axis is normal to the ecliptic
plane, positive northward. X axis is positive
towards the first point of Aries (from Earth
to Sun at vernal equinox). Same as SE below.
See Hapgood, 1992.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HCC">
<xsd:annotation>
<xsd:documentation xml:lang="en">Heliocentric Cartesian - A 3-D orthonormal
coordinate system that is primarily intended
to specify with two dimensions a point on
the solar disk. The Z axis points toward the
observer. The Y axis lies in the plane defined
by the solar spin vector and the Z axis, positive
northward. The X axis is perpendicular to
the Y and Z axes, positive toward solar west.
Standard representation for this system is
via the point's x and y values, expressed
either as physical distances or as fractions
of the solar disk radius.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HCI">
<xsd:annotation>
<xsd:documentation xml:lang="en">Heliographic Carrington Inertial.</
xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HCR">
<xsd:annotation>
<xsd:documentation xml:lang="en">Heliocentric Radial - A 3-D orthonormal
coordinate
system that is primarily intended to specify
with two dimensions a point on the solar disk.
The Z axis points toward the observer. The
Y axis lies in the plane defined by the solar
spin vector and the Z axis, positive northward.
The X axis is perpendicular to the Y and Z
axes, positive toward solar west. Standard
representation for this system is via the
point's distance rho from the Z axis [Rho
= SQRT(x**2 + y**2)] and its phase angle psi
measured counterclockwise from the +Y axis
[psi = arctan (-y/x)]</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HEE">
<xsd:annotation>
<xsd:documentation xml:lang="en">Heliocentric Earth Ecliptic - A coordinate
system where the Z axis is normal to the ecliptic
plane, positive northward. X axis points from
Sun to Earth. See Hapgood, 1992</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HEEQ">

```

```

<xsd:annotation>
  <xsd:documentation xml:lang="en">Heliocentric Earth Equatorial - A coordinate
  system where the Z axis is normal to the solar
  equatorial plane, positive northward. X axis
  is generally Earthward in the plane defined
  by the Z axis and the Sun-Earth direction.
  See Hapgood, 1992.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HG">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Heliographic - A heliocentric rotating coordinate
    system where the Z axis is normal to the solar
    equatorial plane, positive northward. X, Y
    axes rotate with a 25.38 day period. The zero
    longitude (X axis) is defined as the longitude
    that passed through the ascending node of
    the solar equator on the ecliptic plane on
    1 January, 1854 at 12 UT. See <http://nssdc.gsfc.nasa.gov/space/helios/coor\_des.html></xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HGI">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Heliographic Inertial - A heliocentric coordinate
    system where the Z axis is normal to the solar
    equatorial plane, positive northward. X axis
    is along the intersection line between solar
    equatorial and ecliptic planes. The X axis
    was positive at SE longitude of 74.367 deg
    on Jan 1, 1900. (See SE below.) See <http://nssdc.gsfc.nasa.gov/space/helios/coor\_des.html></xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HPC">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Helioprojective Cartesian = A 3-D orthonormal
    (left-handed) coordinate system that is primarily
    intended to specify with two dimensions a
    point on the solar disk. The Z axis points
    from the observer to the center of the solar
    disk. The Y axis lies in the plane defined
    by the solar spin vector and the Z axis, positive
    northward. The X axis is perpendicular to
    the Y and Z axes, positive toward solar west.
    Given as the distance between the observer
    and the center of the solar disk, the standard
    representation of an (x,y) point on the solar
    disk is via the point's longitude angle [ $\arctan(x/d)$ ] and latitude angle [ $\arctan(y/d)$ .</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HPR">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Helioprojective Radial - A 3-D orthonormal
    (left-handed) coordinate system that is primarily
    intended to specify with two dimensions a
    point on the solar disk. The Z axis points
    from the observer to the center of the solar
    disk. The Y axis lies in the plane defined
    by the solar spin vector and the Z axis, positive
    northward. The X axis is perpendicular to
    the Y and Z axes, positive toward solar west.
    Given as the distance between the observer
    and the center of the solar disk, the standard
    representation for this system of an (x,y)
    point on the solar disk is via the point's
    latitude angle theta [=  $\arctan(\sqrt{x^2 + y^2}/d)$ ] or equivalent declination parameter
    delta (= theta - 90 deg), and its phase angle
    psi as measured counter-clockwise from the
    +Y axis [psi =  $\arctan(-y/x)$ ].</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="J2000">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">An astronomical coordinate system which uses
    the mean equator and equinox of Julian date
    2451545.0 TT (Terrestrial Time), or January
    1, 2000, noon TT. (aka J2000) to define a
    celestial reference frame.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>

```

```

<xsd:enumeration value="LGM">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Local Geomagnetic - A coordinate system used
      mainly for Earth surface or near Earth surface
      magnetic field data. X axis northward from
      observation point in a geographic meridian.
      Z axis downward towards Earth's center. In
      this system, H (total horizontal component)
      =  $\sqrt{B_x^2 + B_y^2}$  and D (declination angle)
      =  $\arctan(B_y/B_x)$ </xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="MAG">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Geomagnetic - geocentric. Z axis is parallel
      to the geomagnetic dipole axis, positive north.
      X is in the plane defined by the Z axis and
      the Earth's rotation axis. If N is a unit
      vector from the Earth's center to the north
      geographic pole, the signs of the X and Y
      axes are given by Y = N x Z, X = Y x Z.. See
      Russell, 1971, and <http://cdpp.cnes.fr/00428.pdf></xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="MFA">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Magnetic Field Aligned - A coordinate system
      spacecraft-centered system with Z in the direction
      of the ambient magnetic field vector. X is
      in the plane defined by Z and the spacecraft-Sun
      line, positive sunward. See <http://cdpp.cnes.fr/00428.pdf></xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="RTN">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Radial Tangential Normal. Typically centered
      at a spacecraft. Used for IMF and plasma V
      vectors. R (radial) axis is radially away
      from the Sun, T (tangential) axis is normal
      to the plane formed by R and the Sun's spin
      vector, positive in the direction of planetary
      motion. N (normal) is R x T.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="SC">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Spacecraft - A coordinate system defined by
      the spacecraft geometry and/or spin. Often
      has Z axis parallel to spacecraft spin vector.
      X and Y axes may or may not corotate with
      the spacecraft. See SR and SR2 below.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="SE">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Solar Ecliptic - A heliocentric coordinate
      system where the Z axis is normal to the ecliptic
      plane, positive northward. X axis is positive
      towards the first point of Aries (from Earth
      to Sun at vernal equinox). Same as HAE above.
      See <http://nssdc.gsfc.nasa.gov/space/helios/coor\_des.html></xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="SM">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Solar Magnetic - A geocentric coordinate system
      where the Z axis is northward along Earth's
      dipole axis, X axis is in plane of z axis
      and Earth-Sun line, positive sunward. See
      Russell, 1971.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="SpacecraftOrbitPlane">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A coordinate system where X lies in the plane
      normal to and in the direction of motion of
      the spacecraft, Z is normal to this plane
      and Y completes the triad in a right-handed
      coordinate system.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>

```


```

<xsd:enumeration value="SR">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Spin Reference - A special case of a Spacecraft
      (SC) coordinate system for a spinning spacecraft.
      Z is parallel to the spacecraft spin vector.
      X and Y rotate with the spacecraft. See <http://cdpp.cnes.fr/00428.pdf></
    <xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="SR2">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Spin Reference 2 - A special case of a Spacecraft
      (SC) coordinate system for a spinning spacecraft.
      Z is parallel to the spacecraft spin vector.
      X is in the plane defined by Z and the spacecraft-Sun
      line, positive sunward. See <http://cdpp.cnes.fr/00428.pdf></
    <xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="SSE">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Spacecraft Solar Ecliptic - A coordinate system
      used for deep space spacecraft, for example
      Helios. - X axis from spacecraft to Sun. Z
      axis normal to ecliptic plane, positive northward.
      Note: Angle between normals to ecliptic and
      to Helios orbit plane ~ 0.25 deg.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="SSE_L">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Selenocentric Solar Ecliptic. The X axis
      points from the center of the Earth's moon
      to the sun, the Z axis is normal to the ecliptic
      plane, positive northward. And the Y axis
      completes the right-handed set of axes.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="WGS84">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">The World Geodetic System (WGS) defines a
      reference frame for the earth, for use in
      geodesy and navigation. The WGS84 uses the
      zero meridian as defined by the Bureau International
      de l'Heure.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
</xsd:restriction>
</xsd:simpleType>

```

Schema location file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumDisplayType

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for types or classes of rendered data.		
Diagram			
Type	restriction of xsd:string		
Facets	enumeration	Image	A two-dimensional representation of data with values at each element of the array related to an intensity or a color.
	enumeration	Plasmagram	The characterization of signal strengths in active sounding measurements as a function of virtual range or signal delay time and sounding frequency. A Plasmagram is also referred to as an Ionogram.
	enumeration	Spectrogram	The characterization of signal strengths as a function of frequency (or energy) and time.
	enumeration	StackPlot	A representation of data showing multiple sets of observations on a single plot, possibly offsetting each plot by some uniform amount.
	enumeration	TimeSeries	A representation of data showing a set of

		observations taken at different points in time and charted as a time series.
	enumeration WaveForm	Spatial or temporal variations of wave amplitude over wave-period timescales.
Used by	Element DisplayType	
Source	<xsd:simpleType name="enumDisplayType"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for types or classes of rendered data.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Image"> <xsd:annotation> <xsd:documentation xml:lang="en">A two-dimensional representation of data with values at each element of the array related to an intensity or a color.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Plasmagram"> <xsd:annotation> <xsd:documentation xml:lang="en">The characterization of signal strengths in active sounding measurements as a function of virtual range or signal delay time and sounding frequency. A Plasmagram is also referred to as an Ionogram.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Spectrogram"> <xsd:annotation> <xsd:documentation xml:lang="en">The characterization of signal strengths as a function of frequency (or energy) and time.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="StackPlot"> <xsd:annotation> <xsd:documentation xml:lang="en">A representation of data showing multiple sets of observations on a single plot, possibly offsetting each plot by some uniform amount.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="TimeSeries"> <xsd:annotation> <xsd:documentation xml:lang="en">A representation of data showing a set of observations taken at different points in time and charted as a time series.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="WaveForm"> <xsd:annotation> <xsd:documentation xml:lang="en">Spatial or temporal variations of wave amplitude over wave-period timescales.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType>	
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd	

Simple Type enumRenderingAxis

Namespace	http://www.spase-group.org/data/schema	
Annotations	Identifiers for the reference component of a plot or rendering of data.	
Diagram		
Type	restriction of xsd:string	
Facets	enumeration ColorBar	A spectrum or set of colors used to represent data values.
	enumeration Horizontal	Parallel to or in the plane of the horizon or a base line.
	enumeration Vertical	Perpendicular to the plane of the horizon or a base line.
Used by	Element RenderingAxis	

Source	<pre> <xsd:simpleType name="enumRenderingAxis"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the reference component of a plot or rendering of data.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="ColorBar"> <xsd:annotation> <xsd:documentation xml:lang="en">A spectrum or set of colors used to represent data values.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Horizontal"> <xsd:annotation> <xsd:documentation xml:lang="en">Parallel to or in the plane of the horizon or a base line.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Vertical"> <xsd:annotation> <xsd:documentation xml:lang="en">Perpendicular to the plane of the horizon or a base line.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type typeSequence

Namespace	http://www.spase-group.org/data/schema
Diagram	
Type	list of xsd:integer
Used by	Elements Index, Size
Source	<pre> <xsd:simpleType name="typeSequence"> <xsd:list itemType="xsd:integer" /> </xsd:simpleType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumScaleType

Namespace	http://www.spase-group.org/data/schema						
Annotations	Identifiers for scaling applied to a set of numbers.						
Diagram							
Type	restriction of xsd:string						
Facets	<table> <tr> <td>enumeration</td> <td>LinearScale</td> <td>Intervals which are equally spaced.</td> </tr> <tr> <td>enumeration</td> <td>LogScale</td> <td>Intervals which are spaced proportionally to the logarithms of the values being represented.</td> </tr> </table>	enumeration	LinearScale	Intervals which are equally spaced.	enumeration	LogScale	Intervals which are spaced proportionally to the logarithms of the values being represented.
enumeration	LinearScale	Intervals which are equally spaced.					
enumeration	LogScale	Intervals which are spaced proportionally to the logarithms of the values being represented.					
Used by	Element ScaleType						
Source	<pre> <xsd:simpleType name="enumScaleType"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for scaling applied to a set of numbers.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="LinearScale"> <xsd:annotation> <xsd:documentation xml:lang="en">Intervals which are equally spaced.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="LogScale"> <xsd:annotation> <xsd:documentation xml:lang="en">Intervals which are spaced proportionally to the logarithms of the values being represented.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>						

	</xsd:simpleType>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumQualifier

Namespace	http://www.spase-group.org/data/schema																																											
Annotations	Identifiers for terms which refine the type or attribute of a quantity.																																											
Diagram																																												
Type	restriction of xsd:string																																											
Facets	<table border="1"> <tr> <td>enumeration</td> <td>Anisotropy</td> <td>Direction-dependent property.</td> </tr> <tr> <td>enumeration</td> <td>Array</td> <td>A sequence of values corresponding to the elements in a rectilinear, n-dimension matrix. Each value can be referenced by a unique index.</td> </tr> <tr> <td>enumeration</td> <td>Average</td> <td>The statistical mean; the sum of a set of values divided by the number of values in the set.</td> </tr> <tr> <td>enumeration</td> <td>Characteristic</td> <td>A quantity which can be easily identified and measured in a given environment.</td> </tr> <tr> <td>enumeration</td> <td>Circular</td> <td>Relative to polarization, right-hand circularly polarized light is defined such that the electric field is rotating clockwise as seen by an observer towards whom the wave is moving. Left-hand circularly polarized light is defined such that the electric field is rotating counterclockwise as seen by an observer towards whom the wave is moving. The polarization of magnetohydrodynamic waves is specified with respect to the ambient mean magnetic field : right-hand polarized waves have a transverse electric field component which turns in a right-handed sense (that of the gyrating electrons) around the magnetic field.</td> </tr> <tr> <td>enumeration</td> <td>Column</td> <td>A two-dimensional measure of a quantity. The column is the area over which the quantity is measured.</td> </tr> <tr> <td>enumeration</td> <td>Component</td> <td>Projection of a vector along one of the base axes of a coordinate system.</td> </tr> <tr> <td>enumeration</td> <td>Component.I</td> <td>Projection of a vector along the first named axis of a coordinate system. Typically the X axis, but could be the R axis for an RTN coordinate system.</td> </tr> <tr> <td>enumeration</td> <td>Component.J</td> <td>Projection of a vector along the second named axis of a coordinate system. Typically the Y axis, but could be the T axis for an RTN coordinate system.</td> </tr> <tr> <td>enumeration</td> <td>Component.K</td> <td>Projection of a vector along the third named axis of a coordinate system. Typically the Z axis, but could be the N axis for an RTN coordinate system.</td> </tr> <tr> <td>enumeration</td> <td>CrossSpectrum</td> <td>The Fourier transform of the cross correlation of two physical or empirical observations.</td> </tr> <tr> <td>enumeration</td> <td>Deviation</td> <td>The difference between an observed value and the expected value of a quantity.</td> </tr> <tr> <td>enumeration</td> <td>Differential</td> <td>A measurement within a narrow range of energy and/or solid angle.</td> </tr> <tr> <td>enumeration</td> <td>Direction</td> <td>The spatial relation between an object and</td> </tr> </table>		enumeration	Anisotropy	Direction-dependent property.	enumeration	Array	A sequence of values corresponding to the elements in a rectilinear, n-dimension matrix. Each value can be referenced by a unique index.	enumeration	Average	The statistical mean; the sum of a set of values divided by the number of values in the set.	enumeration	Characteristic	A quantity which can be easily identified and measured in a given environment.	enumeration	Circular	Relative to polarization, right-hand circularly polarized light is defined such that the electric field is rotating clockwise as seen by an observer towards whom the wave is moving. Left-hand circularly polarized light is defined such that the electric field is rotating counterclockwise as seen by an observer towards whom the wave is moving. The polarization of magnetohydrodynamic waves is specified with respect to the ambient mean magnetic field : right-hand polarized waves have a transverse electric field component which turns in a right-handed sense (that of the gyrating electrons) around the magnetic field.	enumeration	Column	A two-dimensional measure of a quantity. The column is the area over which the quantity is measured.	enumeration	Component	Projection of a vector along one of the base axes of a coordinate system.	enumeration	Component.I	Projection of a vector along the first named axis of a coordinate system. Typically the X axis, but could be the R axis for an RTN coordinate system.	enumeration	Component.J	Projection of a vector along the second named axis of a coordinate system. Typically the Y axis, but could be the T axis for an RTN coordinate system.	enumeration	Component.K	Projection of a vector along the third named axis of a coordinate system. Typically the Z axis, but could be the N axis for an RTN coordinate system.	enumeration	CrossSpectrum	The Fourier transform of the cross correlation of two physical or empirical observations.	enumeration	Deviation	The difference between an observed value and the expected value of a quantity.	enumeration	Differential	A measurement within a narrow range of energy and/or solid angle.	enumeration	Direction	The spatial relation between an object and
enumeration	Anisotropy	Direction-dependent property.																																										
enumeration	Array	A sequence of values corresponding to the elements in a rectilinear, n-dimension matrix. Each value can be referenced by a unique index.																																										
enumeration	Average	The statistical mean; the sum of a set of values divided by the number of values in the set.																																										
enumeration	Characteristic	A quantity which can be easily identified and measured in a given environment.																																										
enumeration	Circular	Relative to polarization, right-hand circularly polarized light is defined such that the electric field is rotating clockwise as seen by an observer towards whom the wave is moving. Left-hand circularly polarized light is defined such that the electric field is rotating counterclockwise as seen by an observer towards whom the wave is moving. The polarization of magnetohydrodynamic waves is specified with respect to the ambient mean magnetic field : right-hand polarized waves have a transverse electric field component which turns in a right-handed sense (that of the gyrating electrons) around the magnetic field.																																										
enumeration	Column	A two-dimensional measure of a quantity. The column is the area over which the quantity is measured.																																										
enumeration	Component	Projection of a vector along one of the base axes of a coordinate system.																																										
enumeration	Component.I	Projection of a vector along the first named axis of a coordinate system. Typically the X axis, but could be the R axis for an RTN coordinate system.																																										
enumeration	Component.J	Projection of a vector along the second named axis of a coordinate system. Typically the Y axis, but could be the T axis for an RTN coordinate system.																																										
enumeration	Component.K	Projection of a vector along the third named axis of a coordinate system. Typically the Z axis, but could be the N axis for an RTN coordinate system.																																										
enumeration	CrossSpectrum	The Fourier transform of the cross correlation of two physical or empirical observations.																																										
enumeration	Deviation	The difference between an observed value and the expected value of a quantity.																																										
enumeration	Differential	A measurement within a narrow range of energy and/or solid angle.																																										
enumeration	Direction	The spatial relation between an object and																																										

		another object, the orientation of the object or the course along which the object points or moves.
enumeration	DirectionAngle	The angle between a position vector or measured vector (or one of its projections onto a plane) and one of the base axes of the coordinate system.
enumeration	DirectionAngle.AzimuthAngle	The angle between the projection into the i-j plane of a position or measured vector and the i-axis of the coordinate system. Mathematically defined as $\arctan(j/i)$.
enumeration	DirectionAngle.ElevationAngle	The angle between the position or measured vector and the i-j plane of the coordinate system. Mathematically defined as $\arctan(k/\sqrt{i^2+j^2})$.
enumeration	DirectionAngle.PolarAngle	The angle between the position or measured vector and the k-axis of the coordinate system. Mathematically defined as $\arctan(\sqrt{i^2+j^2}/k)$.
enumeration	Directional	A measurement within a narrow range of solid angle.
enumeration	FieldAligned	The component of a quantity which is oriented in the same direction of a field.
enumeration	Fit	Values that make a model agree with the data.
enumeration	Group	An assemblage of values that a certain relation or common characteristic.
enumeration	Integral	A flux measurement in a broad range of energy and solid angle.
enumeration	Integral.Area	Integration over the extent of a planar region, or of the surface of a solid.
enumeration	Integral.Bandwidth	Integration over the width a frequency band.
enumeration	Integral.SolidAngle	Integration over the angle in three-dimensional space that an object subtends at a point.
enumeration	LineOfSight	The line of sight is the line that connects the observer with the observed object. This expression is often used with measurements of Doppler velocity and magnetic field in magnetograms, where only the component of the vector field directed along the line of sight is measured.
enumeration	Linear	Polarization where the E-field vector is confined to a given plane
enumeration	Magnitude	A measure of the strength of a vector quantity or length of its representational vector.
enumeration	Maximum	The largest value of a batch or sample or the upper bound of a probability distribution.
enumeration	Median	The measure of central tendency of a set of n. values computed by ordering the values and taking the value at position $(n. + 1)/2$ when n. is odd or the arithmetic mean of the values at positions $n. / 2$ and $(n. / 2) + 1$ when n. is even.
enumeration	Minimum	The smallest value of a batch or sample or the lower bound of a probability distribution.
enumeration	Moment	Parameters determined by integration over a distribution function convolved with a power

		of velocity.
enumeration	Parallel	Having the same direction as a given direction
enumeration	Peak	The maximum value for the quantity in question, over a period of time which is usually equal to the cadence.
enumeration	Perpendicular	At right angles to a given direction.
enumeration	Perturbation	Variations in the state of a system.
enumeration	Phase	A point or portion in a recurring series of changes.
enumeration	PhaseAngle	Phase difference between two or more waves, normally expressed in degrees.
enumeration	Projection	A measure of the length of a position or measured vector as projected into a plane of the coordinate system.
enumeration	Projection.IJ	A measure of the length of a position or measured vector projected into the i-j (typically X-Y) plane of the coordinate system.
enumeration	Projection.IK	A measure of the length of a position or measured vector projected into the i-k (typically X-Z) plane of the coordinate system.
enumeration	Projection.JK	A measure of the length of a position or measured vector projected into the j-k (typically Y-Z) plane of the coordinate system.
enumeration	Pseudo	Similar to or having the appearance of something else. Can be used to indicate an estimation or approximation of a particular quantity.
enumeration	Ratio	The relative magnitudes of two quantities.
enumeration	Scalar	A quantity that is completely specified by its magnitude and has no direction.
enumeration	Spectral	Characterized as a range or continuum of frequencies
enumeration	StandardDeviation	The square root of the average of the squares of deviations about the mean of a set of data. Standard deviation is a statistical measure of spread or variability.
enumeration	StokesParameters	A set of four parameters (usually called I,Q,U and V) which describe the polarization state of an electromagnetic wave propagating through space.
enumeration	Symmetric	Equal distribution about one or more axes.
enumeration	Tensor	A generalized linear "quantity" or "geometrical entity" that can be expressed as a multi-dimensional array relative to a choice of basis of the particular space on which it is defined.
enumeration	Total	The summation of quantities over all possible species.
enumeration	Trace	The sum of the elements on the main diagonal (the diagonal from the upper left to the lower right) of a square matrix.
enumeration	Uncertainty	A statistically defined discrepancy between a measured quantity and the true value of

		that quantity that cannot be corrected by calculation or calibration.
	enumeration	Variance A measure of dispersion of a set of data points around their mean value. The expectation value of the squared deviations from the mean.
	enumeration	Vector A set of parameter values each along some independent variable (e.g., components of a field in three orthogonal spatial directions; atmospheric temperature values at several altitudes, or at a given latitude and longitude;).
Used by	Element	Qualifier
Source		<pre> <xsd:simpleType name="enumQualifier"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for terms which refine the type or attribute of a quantity.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Anisotropy"> <xsd:annotation> <xsd:documentation xml:lang="en">Direction-dependent property.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Array"> <xsd:annotation> <xsd:documentation xml:lang="en">A sequence of values corresponding to the elements in a rectilinear, n-dimension matrix. Each value can be referenced by a unique index.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Average"> <xsd:annotation> <xsd:documentation xml:lang="en">The statistical mean; the sum of a set of values divided by the number of values in the set.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Characteristic"> <xsd:annotation> <xsd:documentation xml:lang="en">A quantity which can be easily identified and measured in a given environment.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Circular"> <xsd:annotation> <xsd:documentation xml:lang="en">Relative to polarization, right-hand circularly polarized light is defined such that the electric field is rotating clockwise as seen by an observer towards whom the wave is moving. Left-hand circularly polarized light is defined such that the electric field is rotating counterclockwise as seen by an observer towards whom the wave is moving. The polarization of magnetohydrodynamic waves is specified with respect to the ambient mean magnetic field : right-hand polarized waves have a transverse electric field component which turns in a right-handed sense (that of the gyrating electrons) around the magnetic field.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Column"> <xsd:annotation> <xsd:documentation xml:lang="en">A two-dimensional measure of a quantity. The column is the area over which the quantity is measured.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Component"> <xsd:annotation> <xsd:documentation xml:lang="en">Projection of a vector along one of the base axes of a coordinate system.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Component.I"> <xsd:annotation> <xsd:documentation xml:lang="en">Projection of a vector along the first named</pre>

```

axis of a coordinate system. Typically the
X axis, but could be the R axis for an RTN
coordinate system.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Component.J">
<xsd:annotation>
<xsd:documentation xml:lang="en">Projection of a vector along the second named
axis of a coordinate system. Typically the
Y axis, but could be the T axis for an RTN
coordinate system.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Component.K">
<xsd:annotation>
<xsd:documentation xml:lang="en">Projection of a vector along the third named
axis of a coordinate system. Typically the
Z axis, but could be the N axis for an RTN
coordinate system.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="CrossSpectrum">
<xsd:annotation>
<xsd:documentation xml:lang="en">The Fourier transform of the cross correlation
of two physical or empirical observations.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Deviation">
<xsd:annotation>
<xsd:documentation xml:lang="en">The difference between an observed value and
the expected value of a quantity.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Differential">
<xsd:annotation>
<xsd:documentation xml:lang="en">A measurement within a narrow range of energy
and/or solid angle.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Direction">
<xsd:annotation>
<xsd:documentation xml:lang="en">The spatial relation between an object and
another object, the orientation of the object
or the course along which the object points
or moves.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="DirectionAngle">
<xsd:annotation>
<xsd:documentation xml:lang="en">The angle between a position vector or measured
vector (or one of its projections onto a plane)
and one of the base axes of the coordinate
system.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="DirectionAngle.AzimuthAngle">
<xsd:annotation>
<xsd:documentation xml:lang="en">The angle between the projection into the
i-j plane of a position or measured vector
and the i-axis of the coordinate system. Mathematically
defined as arctan(j/i).</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="DirectionAngle.ElevationAngle">
<xsd:annotation>
<xsd:documentation xml:lang="en">The angle between the position or measured
vector and the i-j plane of the coordinate
system. Mathematically defined as arctan(k/SQRT(i^2+j^2)).</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="DirectionAngle.PolarAngle">
<xsd:annotation>
<xsd:documentation xml:lang="en">The angle between the position or measured
vector and the k-axis of the coordinate system.
Mathematically defined as arctan([SQRT(i^2+j^2)]/k).</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Directional">
<xsd:annotation>
<xsd:documentation xml:lang="en">A measurement within a narrow range of solid
angle.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>

```

```

<xsd:enumeration value="FieldAligned">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">The component of a quantity which is oriented
      in the same direction of a field.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Fit">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Values that make a model agree with the data.</
xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Group">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">An assemblage of values that a certain relation
      or common characteristic.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Integral">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A flux measurement in a broad range of energy
      and solid angle.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Integral.Area">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Integration over the extent of a planar region,
      or of the surface of a solid.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Integral.Bandwidth">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Integration over the width a frequency band.</
xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Integral.SolidAngle">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Integration over the angle in three-dimensional
      space that an object subtends at a point.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="LineOfSight">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">The line of sight is the line that connects
      the observer with the observed object. This
      expression is often used with measurements
      of Doppler velocity and magnetic field in
      magnetograms, where only the component of
      the vector field directed along the line of
      sight is measured.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Linear">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Polarization where the E-field vector is confined
      to a given plane</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Magnitude">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A measure of the strength of a vector quantity
      or length of its representational vector.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Maximum">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">The largest value of a batch or sample or
      the upper bound of a probability distribution.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Median">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">The measure of central tendency of a set of
      n. values computed by ordering the values
      and taking the value at position (n. + 1)
      / 2 when n. is odd or the arithmetic mean
      of the values at positions n. / 2 and (n.
      / 2) + 1 when n. is even.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Minimum">
  <xsd:annotation>

```

```

<xsd:documentation xml:lang="en">The smallest value of a batch or sample or
the lower bound of a probability distribution.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Moment">
<xsd:annotation>
<xsd:documentation xml:lang="en">Parameters determined by integration over
a distribution function convolved with a power
of velocity.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Parallel">
<xsd:annotation>
<xsd:documentation xml:lang="en">Having the same direction as a given direction</
xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Peak">
<xsd:annotation>
<xsd:documentation xml:lang="en">The maximum value for the quantity in question,
over a period of time which is usually equal
to the cadence.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Perpendicular">
<xsd:annotation>
<xsd:documentation xml:lang="en">At right angles to a given direction.</
xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Perturbation">
<xsd:annotation>
<xsd:documentation xml:lang="en">Variations in the state of a system.</
xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Phase">
<xsd:annotation>
<xsd:documentation xml:lang="en">A point or portion in a recurring series of
changes.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="PhaseAngle">
<xsd:annotation>
<xsd:documentation xml:lang="en">Phase difference between two or more waves,
normally expressed in degrees.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Projection">
<xsd:annotation>
<xsd:documentation xml:lang="en">A measure of the length of a position or measured
vector as projected into a plane of the coordinate
system.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Projection.IJ">
<xsd:annotation>
<xsd:documentation xml:lang="en">A measure of the length of a position or measured
vector projected into the i-j (typically X-Y)
plane of the coordinate system.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Projection.IK">
<xsd:annotation>
<xsd:documentation xml:lang="en">A measure of the length of a position or measured
vector projected into the i-k (typically X-Z)
plane of the coordinate system.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Projection.JK">
<xsd:annotation>
<xsd:documentation xml:lang="en">A measure of the length of a position or measured
vector projected into the j-k (typically Y-Z)
plane of the coordinate system.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Pseudo">
<xsd:annotation>
<xsd:documentation xml:lang="en">Similar to or having the appearance of something
else. Can be used to indicate an estimation
or approximation of a particular quantity.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>

```

```

<xsd:enumeration value="Ratio">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">The relative magnitudes of two quantities.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Scalar">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A quantity that is completely specified by its magnitude and has no direction.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Spectral">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Characterized as a range or continuum of frequencies</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="StandardDeviation">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">The square root of the average of the squares of deviations about the mean of a set of data. Standard deviation is a statistical measure of spread or variability.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="StokesParameters">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A set of four parameters (usually called I,Q,U and V) which describe the polarization state of an electromagnetic wave propagating through space.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Symmetric">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Equal distribution about one or more axes.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Tensor">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A generalized linear "quantity" or "geometrical entity" that can be expressed as a multi-dimensional array relative to a choice of basis of the particular space on which it is defined.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Total">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">The summation of quantities over all possible species.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Trace">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">The sum of the elements on the main diagonal (the diagonal from the upper left to the lower right) of a square matrix.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Uncertainty">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A statistically defined discrepancy between a measured quantity and the true value of that quantity that cannot be corrected by calculation or calibration.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Variance">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A measure of dispersion of a set of data points around their mean value. The expectation value of the squared deviations from the mean.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Vector">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A set of parameter values each along some independent variable (e.g., components of a field in three orthogonal spatial directions; atmospheric temperature values at several altitudes, or at a given latitude and longitude;).</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>

```

	<pre> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumFieldQuantity

Namespace	http://www.spase-group.org/data/schema	
Annotations	Identifiers for the physical attribute of the field.	
Diagram	<pre> classDiagram enumFieldQuantity "1" -- "0..1" xsd:string </pre>	
Type	restriction of xsd:string	
Facets	enumeration Current enumeration Electric enumeration Electromagnetic enumeration Gyrofrequency enumeration Magnetic enumeration PlasmaFrequency enumeration Potential enumeration PoyntingFlux	<p>The flow of electrons through a conductor caused by a potential difference.</p> <p>The physical attribute that exerts an electrical force.</p> <p>Electric and magnetic field variations in time and space that propagate through a medium or a vacuum with the waves propagation, electric field, and magnetic field vectors forming an orthogonal triad. Waves in this category are detected by having their field quantities measured.</p> <p>The number of gyrations around a magnetic guiding center (field line) a charged particle makes per unit time due to the Lorentz force.</p> <p>The physical attribute attributed to a magnet or its equivalent.</p> <p>A number-density-dependent characteristic frequency of a plasma.</p> <p>A field which obeys Laplaces Equation.</p> <p>Electromagnetic energy flux transported by a wave characterized as the rate of energy transport per unit area per steradian.</p>
Used by	Element	FieldQuantity
Source	<pre> <xsd:simpleType name="enumFieldQuantity"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the physical attribute of the field.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Current"> <xsd:annotation> <xsd:documentation xml:lang="en">The flow of electrons through a conductor caused by a potential difference.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Electric"> <xsd:annotation> <xsd:documentation xml:lang="en">The physical attribute that exerts an electrical force.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Electromagnetic"> <xsd:annotation> <xsd:documentation xml:lang="en">Electric and magnetic field variations in time and space that propagate through a medium or a vacuum with the wave's propagation, electric field, and magnetic field vectors forming an orthogonal triad. Waves in this category are detected by having their field quantities measured.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>	

```

        </xsd:enumeration>
        <xsd:enumeration value="Gyrofrequency">
            <xsd:annotation>
                <xsd:documentation xml:lang="en">The number of gyrations around a magnetic
                    guiding center (field line) a charged particle
                    makes per unit time due to the Lorentz force.</xsd:documentation>
            </xsd:annotation>
        </xsd:enumeration>
        <xsd:enumeration value="Magnetic">
            <xsd:annotation>
                <xsd:documentation xml:lang="en">The physical attribute attributed to a magnet
                    or its equivalent.</xsd:documentation>
            </xsd:annotation>
        </xsd:enumeration>
        <xsd:enumeration value="PlasmaFrequency">
            <xsd:annotation>
                <xsd:documentation xml:lang="en">A number-density-dependent characteristic
                    frequency of a plasma.</xsd:documentation>
            </xsd:annotation>
        </xsd:enumeration>
        <xsd:enumeration value="Potential">
            <xsd:annotation>
                <xsd:documentation xml:lang="en">A field which obeys Laplace's Equation.</xsd:documentation>
            </xsd:annotation>
        </xsd:enumeration>
        <xsd:enumeration value="PoyntingFlux">
            <xsd:annotation>
                <xsd:documentation xml:lang="en">Electromagnetic energy flux transported by
                    a wave characterized as the rate of energy
                    transport per unit area per steradian.</xsd:documentation>
            </xsd:annotation>
        </xsd:enumeration>
    </xsd:restriction>
</xsd:simpleType>

```

Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd
-----------------	---

Simple Type enumSpectralRange

Namespace	http://www.spase-group.org/data/schema																							
Annotations	Identifiers for names associated with wavelengths. Based on the ISO 21348 Solar Irradiance Standard. Additions have been made to extend the frequency ranges to include those used in space physics. Those additions are indicated in blue text. The "Total Solar Irradiance" category has not been included since it is a type of measurement and not a specific spectral range. See Appendix A - Comparison of Spectrum Domains for a comparison of the spectral ranges with other systems.																							
Diagram																								
Type	restriction of xsd:string																							
Facets	<table border="1"> <tr> <td>enumeration</td> <td>CaK</td> <td>A spectrum with a wavelength of range centered near 393.5 nm. VSO nickname: Ca-K image with range of 391.9 nm to 395.2 nm.</td> </tr> <tr> <td>enumeration</td> <td>ExtremeUltraviolet</td> <td>A spectrum with a wavelength range of 10.0 nm to 125.0 nm. VSO nickname: EUV image with a range of 10.0 nm to 125.0 nm</td> </tr> <tr> <td>enumeration</td> <td>FarUltraviolet</td> <td>A spectrum with a wavelength range of 122 nm to 200.0 nm. VSO nickname: FUV image with a range of 122.0 nm to 200 nm</td> </tr> <tr> <td>enumeration</td> <td>GammaRays</td> <td>Photons with a wavelength range: 0.00001 to 0.001 nm</td> </tr> <tr> <td>enumeration</td> <td>Halpha</td> <td>A spectrum with a wavelength range centered at 656.3 nm. VSO nickname: H-alpha image with a spectrum range of 655.8 nm to 656.8 nm.</td> </tr> <tr> <td>enumeration</td> <td>HardXrays</td> <td>Photons with a wavelength range: 0.001 to 0.1 nm and an energy range of 12 keV to 120 keV</td> </tr> <tr> <td>enumeration</td> <td>He10830</td> <td>A spectrum with a wavelength range centered at 1082.9 nm. VSO nickname: He 10830 image with a range of 1082.5 nm to 1083.3 nm.</td> </tr> </table>			enumeration	CaK	A spectrum with a wavelength of range centered near 393.5 nm. VSO nickname: Ca-K image with range of 391.9 nm to 395.2 nm.	enumeration	ExtremeUltraviolet	A spectrum with a wavelength range of 10.0 nm to 125.0 nm. VSO nickname: EUV image with a range of 10.0 nm to 125.0 nm	enumeration	FarUltraviolet	A spectrum with a wavelength range of 122 nm to 200.0 nm. VSO nickname: FUV image with a range of 122.0 nm to 200 nm	enumeration	GammaRays	Photons with a wavelength range: 0.00001 to 0.001 nm	enumeration	Halpha	A spectrum with a wavelength range centered at 656.3 nm. VSO nickname: H-alpha image with a spectrum range of 655.8 nm to 656.8 nm.	enumeration	HardXrays	Photons with a wavelength range: 0.001 to 0.1 nm and an energy range of 12 keV to 120 keV	enumeration	He10830	A spectrum with a wavelength range centered at 1082.9 nm. VSO nickname: He 10830 image with a range of 1082.5 nm to 1083.3 nm.
enumeration	CaK	A spectrum with a wavelength of range centered near 393.5 nm. VSO nickname: Ca-K image with range of 391.9 nm to 395.2 nm.																						
enumeration	ExtremeUltraviolet	A spectrum with a wavelength range of 10.0 nm to 125.0 nm. VSO nickname: EUV image with a range of 10.0 nm to 125.0 nm																						
enumeration	FarUltraviolet	A spectrum with a wavelength range of 122 nm to 200.0 nm. VSO nickname: FUV image with a range of 122.0 nm to 200 nm																						
enumeration	GammaRays	Photons with a wavelength range: 0.00001 to 0.001 nm																						
enumeration	Halpha	A spectrum with a wavelength range centered at 656.3 nm. VSO nickname: H-alpha image with a spectrum range of 655.8 nm to 656.8 nm.																						
enumeration	HardXrays	Photons with a wavelength range: 0.001 to 0.1 nm and an energy range of 12 keV to 120 keV																						
enumeration	He10830	A spectrum with a wavelength range centered at 1082.9 nm. VSO nickname: He 10830 image with a range of 1082.5 nm to 1083.3 nm.																						

	enumeration	He304	A spectrum centered around the resonance line of ionised helium at 304 Angstrom (30.4 nm).
	enumeration	Infrared	Photons with a wavelength range: 760 to 1.00×10^6 nm
	enumeration	K7699	A spectrum with a wavelength range centred at 769.9 nm. VSO nickname: K-7699 dopplergram with a range of 769.8 nm to 770.0 nm.
	enumeration	LBHBand	Lyman-Birge-Hopfield band in the far ultraviolet range with wavelength range of 140nm to 170 nm.
	enumeration	Microwave	Photons with a wavelength range: 1.00×10^6 to 1.50×10^7 nm
	enumeration	NaD	A spectrum with a wavelength range of centered at 589.3 nm. VSO nickname: Na-D image with a range of 588.8 nm to 589.8 nm.
	enumeration	Ni6768	A spectrum with a wavelength range centered at 676.8 nm. VSO nickname: Ni-6768 dopplergram with a range of 676.7 nm to 676.9 nm.
	enumeration	Optical	Photons with a wavelength range: 380 to 760 nm
	enumeration	RadioFrequency	Photons with a wavelength range: 100,000 to 1.00×10^{11} nm
	enumeration	SoftXRays	X-Rays with an energy range of 0.12 keV to 12 keV.
	enumeration	Ultraviolet	Photons with a wavelength range: 10 to 400 nm.
	enumeration	WhiteLight	Photons with a wavelength in the visible range for humans.
	enumeration	XRays	Photons with a wavelength range: $0.001 \leq x < 10$ nm
Used by	Element	SpectralRange	
Source			<pre> <xsd:simpleType name="enumSpectralRange"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for names associated with wavelengths. Based on the ISO 21348 Solar Irradiance Standard. Additions have been made to extend the frequency ranges to include those used in space physics. Those additions are indicated in blue text. The "Total Solar Irradiance" category has not been included since it is a type of measurement and not a specific spectral range. See Appendix A - Comparison of Spectrum Domains for a comparison of the spectral ranges with other systems.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="CaK"> <xsd:annotation> <xsd:documentation xml:lang="en">A spectrum with a wavelength of range centered near 393.5 nm. VSO nickname: Ca-K image with range of 391.9 nm to 395.2 nm.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="ExtremeUltraviolet"> <xsd:annotation> <xsd:documentation xml:lang="en">A spectrum with a wavelength range of 10.0 nm to 125.0nm. VSO nickname: EUV image with a range of 10.0 nm to 125.0 nm</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="FarUltraviolet"> <xsd:annotation> <xsd:documentation xml:lang="en">A spectrum with a wavelength range of 122 nm to 200.0nm. VSO nickname: FUV image with a range of 122.0 nm to 200 nm</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="GammaRays"> </pre>

```

<xsd:annotation>
  <xsd:documentation xml:lang="en">Photons with a wavelength range: 0.00001 to
  0.001 nm</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Halpha">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A spectrum with a wavelength range centered
    at 656.3 nm. VSO nickname: H-alpha image with
    a spectrum range of of 655.8 nm to 656.8 nm.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HardXrays">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Photons with a wavelength range: 0.001 to
    0.1 nm and an energy range of 12 keV to 120
    keV</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="He10830">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A spectrum with a wavelength range centered
    at 1082.9 nm. VSO nickname: He 10830 image
    with a range of 1082.5 nm to 1083.3 nm.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="He304">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A spectrum centered around the resonance line
    of ionised helium at 304 Angstrom (30.4 nm).</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Infrared">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Photons with a wavelength range: 760 to 1.00x10^6
    nm</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="K7699">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A spectrum with a wavelength range centred
    at 769.9 nm. VSO nickname: K-7699 dopplergram
    with a range of 769.8 nm to 770.0 nm.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="LBHBand">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Lyman-Birge-Hopfield band in the far ultraviolet
    range with wavelength range of 140nm to 170
    nm.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Microwave">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Photons with a wavelength range: 1.00x10^6
    to 1.50x10^7 nm</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="NaD">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A spectrum with a wavelength range of centered
    at 589.3 nm. VSO nickname: Na-D image with
    a range of 588.8 nm to 589.8 nm.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Ni6768">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A spectrum with a wavelength range centered
    at 676.8 nm. VSO nickname: Ni-6768 dopplergram
    with a range of of 676.7 nm to 676.9 nm.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Optical">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Photons with a wavelength range: 380 to 760
    nm</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="RadioFrequency">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">Photons with a wavelength range: 100,000 to
    1.00x10^11 nm</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>

```

	<pre> </xsd:enumeration> <xsd:enumeration value="SoftXRays"> <xsd:annotation> <xsd:documentation xml:lang="en">X-Rays with an energy range of 0.12 keV to 12 keV.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Ultraviolet"> <xsd:annotation> <xsd:documentation xml:lang="en">Photons with a wavelength range: 10 to 400 nm.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="WhiteLight"> <xsd:annotation> <xsd:documentation xml:lang="en">Photons with a wavelength in the visible range for humans.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="XRays"> <xsd:annotation> <xsd:documentation xml:lang="en">Photons with a wavelength range: 0.001 <= x < 10 nm</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumParticleType

Namespace	http://www.spase-group.org/data/schema																												
Annotations	Identifiers for the characterization of the kind of particle observed by the measurement.																												
Diagram	<pre> classDiagram class enumParticleType class xsd:string enumParticleType --o xsd:string </pre>																												
Type	restriction of xsd:string																												
Facets	<table border="1"> <tr> <td>enumeration</td> <td>Aerosol</td> <td>A suspension of fine solid or liquid particles in a gas.</td> </tr> <tr> <td>enumeration</td> <td>AlphaParticle</td> <td>A positively charged nuclear particle that consists of two protons and two neutrons.</td> </tr> <tr> <td>enumeration</td> <td>Atom</td> <td>Matter consisting of a nucleus surrounded by electrons which has no net charge.</td> </tr> <tr> <td>enumeration</td> <td>Dust</td> <td>Free microscopic particles of solid material.</td> </tr> <tr> <td>enumeration</td> <td>Electron</td> <td>An elementary particle consisting of a charge of negative electricity equal to about 1.602×10^{-19} Coulomb and having a mass when at rest of about 9.109534×10^{-28} gram.</td> </tr> <tr> <td>enumeration</td> <td>Ion</td> <td>An atom that has acquired a net electric charge by gaining or losing one or more electrons. (Note: $Z>2$)</td> </tr> <tr> <td>enumeration</td> <td>Molecule</td> <td>A group of atoms so united and combined by chemical affinity that they form a complete, integrated whole, being the smallest portion of any particular compound that can exist in a free state</td> </tr> <tr> <td>enumeration</td> <td>Neutron</td> <td>An elementary particle that has no net charge and is a constituent of atomic nuclei, and that has a mass slightly large than a proton (1.673×10^{-24} gram.)</td> </tr> <tr> <td>enumeration</td> <td>Proton</td> <td>An elementary particle that is a constituent of all atomic nuclei, that carries a positive charge numerically equal to the charge of an electron, and that has a mass of 1.673×10^{-24} gram.</td> </tr> </table>		enumeration	Aerosol	A suspension of fine solid or liquid particles in a gas.	enumeration	AlphaParticle	A positively charged nuclear particle that consists of two protons and two neutrons.	enumeration	Atom	Matter consisting of a nucleus surrounded by electrons which has no net charge.	enumeration	Dust	Free microscopic particles of solid material.	enumeration	Electron	An elementary particle consisting of a charge of negative electricity equal to about 1.602×10^{-19} Coulomb and having a mass when at rest of about 9.109534×10^{-28} gram.	enumeration	Ion	An atom that has acquired a net electric charge by gaining or losing one or more electrons. (Note: $Z>2$)	enumeration	Molecule	A group of atoms so united and combined by chemical affinity that they form a complete, integrated whole, being the smallest portion of any particular compound that can exist in a free state	enumeration	Neutron	An elementary particle that has no net charge and is a constituent of atomic nuclei, and that has a mass slightly large than a proton (1.673×10^{-24} gram.)	enumeration	Proton	An elementary particle that is a constituent of all atomic nuclei, that carries a positive charge numerically equal to the charge of an electron, and that has a mass of 1.673×10^{-24} gram.
enumeration	Aerosol	A suspension of fine solid or liquid particles in a gas.																											
enumeration	AlphaParticle	A positively charged nuclear particle that consists of two protons and two neutrons.																											
enumeration	Atom	Matter consisting of a nucleus surrounded by electrons which has no net charge.																											
enumeration	Dust	Free microscopic particles of solid material.																											
enumeration	Electron	An elementary particle consisting of a charge of negative electricity equal to about 1.602×10^{-19} Coulomb and having a mass when at rest of about 9.109534×10^{-28} gram.																											
enumeration	Ion	An atom that has acquired a net electric charge by gaining or losing one or more electrons. (Note: $Z>2$)																											
enumeration	Molecule	A group of atoms so united and combined by chemical affinity that they form a complete, integrated whole, being the smallest portion of any particular compound that can exist in a free state																											
enumeration	Neutron	An elementary particle that has no net charge and is a constituent of atomic nuclei, and that has a mass slightly large than a proton (1.673×10^{-24} gram.)																											
enumeration	Proton	An elementary particle that is a constituent of all atomic nuclei, that carries a positive charge numerically equal to the charge of an electron, and that has a mass of 1.673×10^{-24} gram.																											
Used by	Element	ParticleType																											

Source	<pre> <xsd:simpleType name="enumParticleType"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the characterization of the kind of particle observed by the measurement.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Aerosol"> <xsd:annotation> <xsd:documentation xml:lang="en">A suspension of fine solid or liquid particles in a gas.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="AlphaParticle"> <xsd:annotation> <xsd:documentation xml:lang="en">A positively charged nuclear particle that consists of two protons and two neutrons.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Atom"> <xsd:annotation> <xsd:documentation xml:lang="en">Matter consisting of a nucleus surrounded by electrons which has no net charge.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Dust"> <xsd:annotation> <xsd:documentation xml:lang="en">Free microscopic particles of solid material.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Electron"> <xsd:annotation> <xsd:documentation xml:lang="en">An elementary particle consisting of a charge of negative electricity equal to about 1.602 x 10^(-19) Coulomb and having a mass when at rest of about 9.109534 x 10^(-28) gram.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Ion"> <xsd:annotation> <xsd:documentation xml:lang="en">An atom that has acquired a net electric charge by gaining or losing one or more electrons.(Note: Z>2)</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Molecule"> <xsd:annotation> <xsd:documentation xml:lang="en">A group of atoms so united and combined by chemical affinity that they form a complete, integrated whole, being the smallest portion of any particular compound that can exist in a free state</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Neutron"> <xsd:annotation> <xsd:documentation xml:lang="en">An elementary particle that has no net charge and is a constituent of atomic nuclei, and that has a mass slightly large than a proton (1.673 x 10^(-24) gram.)</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Proton"> <xsd:annotation> <xsd:documentation xml:lang="en">An elementary particle that is a constituent of all atomic nuclei, that carries a positive charge numerically equal to the charge of an electron, and that has a mass of 1.673 x 10^(-24) gram.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumParticleQuantity

Namespace	http://www.spase-group.org/data/schema
Annotations	Identifiers for the characterization of the physical properties of the particle.

Diagram	<pre> classDiagram enumParticleQuantity < -- xsd:string </pre>	
Type	restriction of xsd:string	
Facets	enumeration	ArrivalDirection An angular measure of the direction from which an energetic particle or photon was incident on a detector. The angles may be measured in any coordinate system.
	enumeration	AtomicNumberDetected The number of protons in the nucleus of an atom as determined by a detector.
	enumeration	AverageChargeState A measure of the composite deficit (positive) or excess (negative) of electrons with respect to protons.
	enumeration	ChargeState Charge of a fully or partially stripped ion, in units of the charge of a proton. Charge state of a bare proton = 1.
	enumeration	CountRate The number of events per unit time.
	enumeration	Counts The number of detection events occurring in a detector over the detector accumulation time.
	enumeration	Energy The capacity for doing work as measured by the capability of doing work (potential energy) or the conversion of this capability to motion (kinetic energy)
	enumeration	EnergyDensity The amount of energy per unit volume.
	enumeration	EnergyFlux The amount of energy passing through a unit area in a unit time.
	enumeration	FlowSpeed The rate at which particles or energy is passing through a unit area in a unit time.
	enumeration	FlowVelocity The volume of matter passing through a unit area perpendicular to the direction of flow in a unit of time.
	enumeration	Fluence The time integral of a flux. A fluence does not have any "per unit time" in its units.
	enumeration	Gyrofrequency The number of gyrations around a magnetic guiding center (field line) a charged particle makes per unit time due to the Lorentz force.
	enumeration	HeatFlux Flow of thermal energy through a gas or plasma; typically computed as third moment of a distribution function.
	enumeration	Mass The measure of inertia (mass) of individual objects (e.g., aerosols).
	enumeration	MassDensity The mass of particles per unit volume.
	enumeration	MassNumber The total number of protons and neutrons (together known as nucleons) in an atomic nucleus.
	enumeration	NumberDensity The number of particles per unit volume.
	enumeration	NumberFlux The number of particles passing a unit area in unit time, possibly also per unit energy (or equivalent) and/or per unit look direction.
	enumeration	PhaseSpaceDensity The number of particles per unit volume in the six-dimensional space of position and velocity.
	enumeration	PlasmaFrequency A number-density-dependent characteristic frequency of a plasma.
	enumeration	Pressure The force per unit area exerted by a particle distribution or field.

	enumeration	SonicMachNumber	The ratio of the bulk flow speed to the speed of sound in the medium.
	enumeration	SoundSpeed	The speed at which sound travels through a medium.
	enumeration	Temperature	A measure of the kinetic energy of random motion with respect to the average. Temperature is properly defined only for an equilibrium particle distribution (Maxwellian distribution).
	enumeration	ThermalSpeed	For a Maxwellian distribution, the difference between the mean speed and the speed within which ~69% (one sigma) of all the members of the speed distribution occur.
	enumeration	Velocity	Rate of change of position. Also used for the average velocity of a collection of particles, also referred to as "bulk velocity".
Used by	Element	ParticleQuantity	
Source			<pre> <xsd:simpleType name="enumParticleQuantity"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the characterization of the physical properties of the particle.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="ArrivalDirection"> <xsd:annotation> <xsd:documentation xml:lang="en">An angular measure of the direction from which an energetic particle or photon was incident on a detector. The angles may be measured in any coordinate system.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="AtomicNumberDetected"> <xsd:annotation> <xsd:documentation xml:lang="en">The number of protons in the nucleus of an atom as determined by a detector.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="AverageChargeState"> <xsd:annotation> <xsd:documentation xml:lang="en">A measure of the composite deficit (positive) or excess (negative) of electrons with respect to protons.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="ChargeState"> <xsd:annotation> <xsd:documentation xml:lang="en">Charge of a fully or partially stripped ion, in units of the charge of a proton. Charge state of a bare proton = 1.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="CountRate"> <xsd:annotation> <xsd:documentation xml:lang="en">The number of events per unit time.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Counts"> <xsd:annotation> <xsd:documentation xml:lang="en">The number of detection events occurring in a detector over the detector accumulation time.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Energy"> <xsd:annotation> <xsd:documentation xml:lang="en">The capacity for doing work as measured by the capability of doing work (potential energy) or the conversion of this capability to motion (kinetic energy)</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="EnergyDensity"> <xsd:annotation> </pre>

```

<xsd:documentation xml:lang="en">The amount of energy per unit volume.</
xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="EnergyFlux">
<xsd:annotation>
<xsd:documentation xml:lang="en">The amount of energy passing through a unit
area in a unit time.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="FlowSpeed">
<xsd:annotation>
<xsd:documentation xml:lang="en">The rate at which particles or energy is passing
through a unit area in a unit time.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="FlowVelocity">
<xsd:annotation>
<xsd:documentation xml:lang="en">The volume of matter passing through a unit
area perpendicular to the direction of flow
in a unit of time.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Fluence">
<xsd:annotation>
<xsd:documentation xml:lang="en">The time integral of a flux. A fluence does
not have any "per unit time" in its units.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Gyrofrequency">
<xsd:annotation>
<xsd:documentation xml:lang="en">The number of gyrations around a magnetic
guiding center (field line) a charged particle
makes per unit time due to the Lorentz force.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="HeatFlux">
<xsd:annotation>
<xsd:documentation xml:lang="en">Flow of thermal energy through a gas or plasma;
typically computed as third moment of a distribution
function.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Mass">
<xsd:annotation>
<xsd:documentation xml:lang="en">The measure of inertia (mass) of individual
objects (e.g., aerosols).</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="MassDensity">
<xsd:annotation>
<xsd:documentation xml:lang="en">The mass of particles per unit volume.</
xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="MassNumber">
<xsd:annotation>
<xsd:documentation xml:lang="en">The total number of protons and neutrons
(together
known as nucleons) in an atomic nucleus.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="NumberDensity">
<xsd:annotation>
<xsd:documentation xml:lang="en">The number of particles per unit volume.</
xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="NumberFlux">
<xsd:annotation>
<xsd:documentation xml:lang="en">The number of particles passing a unit area
in unit time, possibly also per unit energy
(or equivalent) and/or per unit look direction.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="PhaseSpaceDensity">
<xsd:annotation>
<xsd:documentation xml:lang="en">The number of particles per unit volume in
the six-dimensional space of position and
velocity.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="PlasmaFrequency">
```

	<pre> <xsd:annotation> <xsd:documentation xml:lang="en">A number-density-dependent characteristic frequency of a plasma.</xsd:documentation> </xsd:annotation> <xsd:enumeration value="Pressure"> <xsd:annotation> <xsd:documentation xml:lang="en">The force per unit area exerted by a particle distribution or field.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="SonicMachNumber"> <xsd:annotation> <xsd:documentation xml:lang="en">The ratio of the bulk flow speed to the speed of sound in the medium.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="SoundSpeed"> <xsd:annotation> <xsd:documentation xml:lang="en">The speed at which sound travels through a medium.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Temperature"> <xsd:annotation> <xsd:documentation xml:lang="en">A measure of the kinetic energy of random motion with respect to the average. Temperature is properly defined only for an equilibrium particle distribution (Maxwellian distribution).</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="ThermalSpeed"> <xsd:annotation> <xsd:documentation xml:lang="en">For a Maxwellian distribution, the difference between the mean speed and the speed within which ~69% (one sigma) of all the members of the speed distribution occur.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Velocity"> <xsd:annotation> <xsd:documentation xml:lang="en">Rate of change of position. Also used for the average velocity of a collection of particles, also referred to as "bulk velocity".</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumWaveType

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for the carrier or phenomenon of wave information observed by the measurement.		
Diagram	<pre> classDiagram class enumWaveType class xsdString enumWaveType "1" -- "0..1" xsdString </pre>		
Type	restriction of xsd:string		
Facets	enumeration	Electromagnetic	Electric and magnetic field variations in time and space that propagate through a medium or a vacuum with the waves propagation, electric field, and magnetic field vectors forming an orthogonal triad. Waves in this category are detected by having their field quantities measured.
	enumeration	Electrostatic	Collective longitudinal electric-field and plasma oscillations trapped within a body of plasma.
	enumeration	Hydrodynamic	Periodic or quasi-periodic oscillations of fluid quantities.
	enumeration	MHD	Hydrodynamic waves in a magnetized plasma in which the background magnetic field plays a key role in controlling the wave propagation

		characteristics.
	enumeration	Photon Electromagnetic waves detected by techniques that utilize their corpuscular character (e.g., CCD, CMOS, photomultipliers).
	enumeration	PlasmaWaves Self-consistent collective oscillations of particles and fields (electric and magnetic) in a plasma.
Used by	Element	WaveType
Source	<pre><xsd:simpleType name="enumWaveType"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the carrier or phenomenon of wave information observed by the measurement.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Electromagnetic"> <xsd:annotation> <xsd:documentation xml:lang="en">Electric and magnetic field variations in time and space that propagate through a medium or a vacuum with the wave's propagation, electric field, and magnetic field vectors forming an orthogonal triad. Waves in this category are detected by having their field quantities measured.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Electrostatic"> <xsd:annotation> <xsd:documentation xml:lang="en">Collective longitudinal electric-field and plasma oscillations trapped within a body of plasma.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Hydrodynamic"> <xsd:annotation> <xsd:documentation xml:lang="en">Periodic or quasi-periodic oscillations of fluid quantities.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="MHD"> <xsd:annotation> <xsd:documentation xml:lang="en">Hydrodynamic waves in a magnetized plasma in which the background magnetic field plays a key role in controlling the wave propagation characteristics.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Photon"> <xsd:annotation> <xsd:documentation xml:lang="en">Electromagnetic waves detected by techniques that utilize their corpuscular character (e.g., CCD, CMOS, photomultipliers).</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="PlasmaWaves"> <xsd:annotation> <xsd:documentation xml:lang="en">Self-consistent collective oscillations of particles and fields (electric and magnetic) in a plasma.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>	
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd	

Simple Type enumWaveQuantity

Namespace	http://www.spase-group.org/data/schema	
Annotations	Identifiers for the characterization of the physical properties of a wave.	
Diagram	<pre> classDiagram class enumWaveQuantity class xsdString enumWaveQuantity < -- xsdString </pre>	
Type	restriction of xsd:string	
Facets	enumeration	Absorption Decrease of radiant energy (relative to the background continuum spectrum).

enumeration	ACElectricField	Alternating electric field component of a wave.
enumeration	ACMagneticField	Alternating magnetic field component of a wave.
enumeration	DopplerFrequency	Change in the frequency of a propagating wave due to motion of the source, the observer, the reflector, or the propagation medium.
enumeration	Emissivity	The energy emitted spontaneously per unit bandwidth (typically frequency) per unit time per unit mass of source. Emissivity is usually integrated over all directions/solid angles.
enumeration	EnergyFlux	The amount of energy passing through a unit area in a unit time.
enumeration	EquivalentWidth	The spectral width of a total absorption line having the amount of absorbed radiant energy being equivalent to that in an observed absorption line.
enumeration	Frequency	The number of occurrences of a repeating event per unit time.
enumeration	Gyrfrequency	The number of gyrations around a magnetic guiding center (field line) a charged particle makes per unit time due to the Lorentz force.
enumeration	Intensity	The measurement of radiant or wave energy per unit detector area per unit bandwidth per unit solid angle per unit time.
enumeration	LineDepth	The measure of the amount of absorption below the continuum (depth) in a particular wavelength or frequency in an absorption spectrum.
enumeration	MagneticField	A region of space near a magnetized body where magnetic forces can be detected (as measured by methods such as Zeeman splitting, etc.).
enumeration	ModeAmplitude	In helioseismology the magnitude of oscillation of waves of a particular geometry.
enumeration	PlasmaFrequency	A number-density-dependent characteristic frequency of a plasma.
enumeration	Polarization	Direction of the electric vector of an electromagnetic wave. The wave can be linearly polarized in any direction perpendicular to the direction of travel, circularly polarized (clockwise or counterclockwise), unpolarized, or mixtures of the above.
enumeration	PoyntingFlux	Electromagnetic energy flux transported by a wave characterized as the rate of energy transport per unit area per steradian.
enumeration	PropagationTime	Time difference between transmission and reception of a wave in an active wave experiment.
enumeration	StokesParameters	A set of four parameters (usually called I, Q, U and V) which describe the polarization state of an electromagnetic wave propagating through space.
enumeration	Velocity	Rate of change of position. Also used for the average velocity of a collection of particles, also referred to as "bulk velocity".

	enumeration	Wavelength	The peak-to-peak distance over one wave period.
Used by	Element	WaveQuantity	
Source		<xsd:simpleType name="enumWaveQuantity"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the characterization of the physical properties of a wave.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Absorption"> <xsd:annotation> <xsd:documentation xml:lang="en">Decrease of radiant energy (relative to the background continuum spectrum).</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="ACElectricField"> <xsd:annotation> <xsd:documentation xml:lang="en">Alternating electric field component of a wave.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="ACMagneticField"> <xsd:annotation> <xsd:documentation xml:lang="en">Alternating magnetic field component of a wave.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="DopplerFrequency"> <xsd:annotation> <xsd:documentation xml:lang="en">Change in the frequency of a propagating wave due to motion of the source, the observer, the reflector, or the propagation medium.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Emissivity"> <xsd:annotation> <xsd:documentation xml:lang="en">The energy emitted spontaneously per unit bandwidth (typically frequency) per unit time per unit mass of source. Emissivity is usually integrated over all directions/solid angles.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="EnergyFlux"> <xsd:annotation> <xsd:documentation xml:lang="en">The amount of energy passing through a unit area in a unit time.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="EquivalentWidth"> <xsd:annotation> <xsd:documentation xml:lang="en">The spectral width of a total absorption line having the amount of absorbed radiant energy being equivalent to that in an observed absorption line.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Frequency"> <xsd:annotation> <xsd:documentation xml:lang="en">The number of occurrences of a repeating event per unit time.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Gyrofrequency"> <xsd:annotation> <xsd:documentation xml:lang="en">The number of gyrations around a magnetic guiding center (field line) a charged particle makes per unit time due to the Lorentz force.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Intensity"> <xsd:annotation> <xsd:documentation xml:lang="en">The measurement of radiant or wave energy per unit detector area per unit bandwidth per unit solid angle per unit time.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="LineDepth"> <xsd:annotation> <xsd:documentation xml:lang="en">The measure of the amount of absorption below the continuum (depth) in a particular wavelength	

```

        or frequency in an absorption spectrum.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="MagneticField">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A region of space near a magnetized body where
            magnetic forces can be detected (as measured
            by methods such as Zeeman splitting, etc.).</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="ModeAmplitude">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">In helioseismology the magnitude of oscillation
            of waves of a particular geometry.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="PlasmaFrequency">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A number-density-dependent characteristic
            frequency of a plasma.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Polarization">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Direction of the electric vector of an
            electromagnetic
            wave. The wave can be linearly polarized in
            any direction perpendicular to the direction
            of travel, circularly polarized (clockwise
            or counterclockwise), unpolarized, or mixtures
            of the above.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="PoyntingFlux">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Electromagnetic energy flux transported by
            a wave characterized as the rate of energy
            transport per unit area per steradian.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="PropagationTime">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Time difference between transmission and
            reception
            of a wave in an active wave experiment.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="StokesParameters">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A set of four parameters (usually called I,Q,
            U and V) which describe the polarization state
            of an electromagnetic wave propagating through
            space.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Velocity">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Rate of change of position. Also used for
            the average velocity of a collection of particles,
            also referred to as "bulk velocity".</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Wavelength">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The peak-to-peak distance over one wave period.</
            xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
</xsd:restriction>
</xsd:simpleType>

```

Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd
-----------------	---

Simple Type enumMixedQuantity

Namespace	http://www.spase-group.org/data/schema
Annotations	Identifiers for the combined attributes of a mixed parameter quantity.
Diagram	

Type	restriction of xsd:string		
Facets	enumeration	AkasofuEpsilon	A measure of the magnetopause energy flux and an indicator of the solar wind power available for subsequent magnetospheric energization. Defined as: $V^*B^2*l^2\sin(\theta/2)^4$ where B is the IMF, l is an empirical scaling parameter equal to 7 RE, and $\theta = \tan(BY/BZ)^{-1}$ the IMF clock angle.
	enumeration	AlfvenMachNumber	The ratio of the bulk flow speed to the Alfvén speed.
	enumeration	AlfvenVelocity	Phase velocity of the Alfvén wave; In SI units it is the velocity of the magnetic field divided by the square root of the mass density times the permeability of free space (μ_0).
	enumeration	FrequencyToGyrofrequencyRatio	
	enumeration	MagnetosonicMachNumber	The ratio of the velocity of fast mode waves to the Alfvén velocity.
	enumeration	Other	Not classified with more specific terms. The context of its usage may be described in related text.
	enumeration	PlasmaBeta	The ratio of the plasma pressure (nkT) to the magnetic pressure ($B^2/2\mu_0$) of the fluid: $\Sigma n k T / (\Sigma B^2 / 2 \mu_0)$.
	enumeration	TotalPressure	In an MHD fluid it is the number density (N) times Boltzmann constant times the temperature in Kelvin.
	enumeration	VCrossB	The cross product of the charge velocity (V) and the magnetic field (B). It is the electric field vector: $E = -V \times B$.

	<pre> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="MagnetosonicMachNumber"> <xsd:annotation> <xsd:documentation xml:lang="en">The ratio of the velocity of fast mode waves to the Alfvén velocity.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Other"> <xsd:annotation> <xsd:documentation xml:lang="en">Not classified with more specific terms. The context of its usage may be described in related text.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="PlasmaBeta"> <xsd:annotation> <xsd:documentation xml:lang="en">The ratio of the plasma pressure (nkT) to the magnetic pressure ($B^2/2\mu_0$) of the $SUM(nkT)/(B^2/2\mu_0)$.</ xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="TotalPressure"> <xsd:annotation> <xsd:documentation xml:lang="en">In an MHD fluid it is the number density (N) times Boltzmann constant times the temperature in Kelvin.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="VCrossB"> <xsd:annotation> <xsd:documentation xml:lang="en">The cross product of the charge velocity (V) and the magnetic field (B). It is the electric field exerted on a point charge by a magnetic field.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumSupportQuantity

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for the information useful in understanding the context of an observation, typically observed or measured coincidentally with a physical observation.		
Diagram			
Type	restriction of xsd:string		
Facets	enumeration	InstrumentMode	An indication of a state (mode) in which the instrument is operating. How a mode influences the interpretation and representation of data is described in instrument related documentation.
	enumeration	Other	Not classified with more specific terms. The context of its usage may be described in related text.
	enumeration	Positional	The specification of the location of an object or measurement within a reference coordinate system. The position is usually expressed as a set of values corresponding to the location along a set of orthogonal axes together with the date/time of the observation.
	enumeration	Temporal	Pertaining to time.
	enumeration	Velocity	Rate of change of position. Also used for the average velocity of a collection of particles, also referred to as "bulk velocity".

Used by	Element	SupportQuantity
Source		<pre> <xsd:simpleType name="enumSupportQuantity"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the information useful in understanding the context of an observation, typically observed or measured coincidentally with a physical observation.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="InstrumentMode"> <xsd:annotation> <xsd:documentation xml:lang="en">An indication of a state (mode) in which the instrument is operating. How a mode influences the interpretation and representation of data is described in instrument related documentation.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Other"> <xsd:annotation> <xsd:documentation xml:lang="en">Not classified with more specific terms. The context of its usage may be described in related text.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Positional"> <xsd:annotation> <xsd:documentation xml:lang="en">The specification of the location of an object or measurement within a reference coordinate system. The position is usually expressed as a set of values corresponding to the location along a set of orthogonal axes together with the date/time of the observation.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Temporal"> <xsd:annotation> <xsd:documentation xml:lang="en">Pertaining to time.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Velocity"> <xsd:annotation> <xsd:documentation xml:lang="en">Rate of change of position. Also used for the average velocity of a collection of particles, also referred to as "bulk velocity".</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>
Schema location		file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumProcessingLevel

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers to characterize the amount and type of manipulation which has been applied to the sampled data.		
Diagram	<pre> classDiagram enumProcessingLevel < -- xsd:string </pre>		
Type	restriction of xsd:string		
Facets	enumeration	Calibrated	Data wherein sensor outputs have been convolved with instrument response function, often irreversibly, to yield data in physical units.
	enumeration	Raw	Data in its original state with no processing to account for calibration!!!
	enumeration	Uncalibrated	Duplicate data are removed from the data stream and data are time ordered. Values are not adjusted for any potential biases or external factors.
Used by	Element	ProcessingLevel	

Source	<pre> <xsd:simpleType name="enumProcessingLevel"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers to characterize the amount and type of manipulation which has been applied to the sampled data.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Calibrated"> <xsd:annotation> <xsd:documentation xml:lang="en">Data wherein sensor outputs have been convolved with instrument response function, often irreversibly, to yield data in physical units.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Raw"> <xsd:annotation> <xsd:documentation xml:lang="en">Data in its original state with no processing to account for calibration!!!</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Uncalibrated"> <xsd:annotation> <xsd:documentation xml:lang="en">Duplicate data are removed from the data stream and data are time ordered. Values are not adjusted for any potential biases or external factors.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumMeasurementType

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for the method of making an estimated value of a quantity that forms the basis of an observation.		
Diagram	<pre> classDiagram class enumMeasurementType { <<xsd:string>> } enumMeasurementType < -- xsd:string </pre>		
Type	restriction of xsd:string		
Facets	enumeration	ActivityIndex	An indication, derived from one or more measurements, of the level of activity of an object or region, such as sunspot number, F10.7 flux, Dst, or the Polar Cap Indices.
	enumeration	Dopplergram	A map or image depicting the spatial distribution of line-of-sight velocities of the observed object.
	enumeration	Dust	Free microscopic particles of solid material.
	enumeration	ElectricField	A region of space around a charged particle, or between two voltages within which a force is exerted on charged objects in its vicinity. An electric field is the electric force per unit charge.
	enumeration	EnergeticParticles	Pieces of matter that are moving very fast. Energetic particles include protons, electrons, neutrons, neutrinos, the nuclei of atoms, and other sub-atomic particles.
	enumeration	Ephemeris	The spatial coordinates of a body as a function of time. When used as an Instrument Type it represents the process or methods used to generate spatial coordinates.
	enumeration	ImageIntensity	Measurements of the two-dimensional distribution of the intensity of photons from some region or object such as the Sun or the polar auroral regions; can be in any wavelength band, and

		polarized, etc.
enumeration	InstrumentStatus	A quantity directly related to the operation or function of an instrument.
enumeration	IonComposition	In situ measurements of the relative flux or density of electrically charged particles in the space environment. May give simple fluxes, but full distribution functions are sometimes measured.
enumeration	Irradiance	Irradiance - A radiometric term for the power of electromagnetic radiation at a surface, per unit area. "Irradiance" is used when the electromagnetic radiation is incident on the surface. Irradiance data may be reported in any units (i.e. counts/s) due to, for example, being at a particular wavelength, or to being a not-fully-calibrated relative measurement.
enumeration	MagneticField	A region of space near a magnetized body where magnetic forces can be detected (as measured by methods such as Zeeman splitting, etc.).
enumeration	Magnetogram	Measurements of the vector or line-of-sight magnetic field determined from remote sensing measurements of the detailed structure of spectral lines, including their splitting and polarization. ("Magnetogram.")
enumeration	NeutralAtomImages	Measurements of neutral atom fluxes as a function of look direction; often related to remote energetic charged particles that lose their charge through charge-exchange and then reach the detector on a line-of-sight trajectory.
enumeration	NeutralGas	Measurements of neutral atomic and molecular components of a gas.
enumeration	Profile	Measurements of a quantity as a function of height above an object such as the limb of a body.
enumeration	Radiance	A radiometric measurement that describes the amount of electromagnetic radiation that passes through or is emitted from a particular area, and falls within a given solid angle in a specified direction. They are used to characterize both emission from diffuse sources and reflection from diffuse surfaces.
enumeration	Spectrum	The distribution of a characteristic of a physical system or phenomenon, such as the energy emitted by a radiant source, arranged in the order of wavelengths.
enumeration	ThermalPlasma	Measurements of the plasma in the energy regime where the most of the plasma occurs. May be the basic fluxes in the form of distribution functions or the derived bulk parameters (density, flow velocity, etc.).
enumeration	Waves	Data resulting from observations of wave experiments and natural wave phenomena. Wave experiments are typically active and natural wave phenomena are passive. Examples of wave experiments include coherent/incoherent scatter radars, radio soundings, VLF propagation studies, ionospheric scintillation of beacon satellite signals, etc. Examples of natural wave phenomena include micropulsations, mesospheric gravity

		waves, auroral/plasmaspheric hiss, Langmuir waves, AKR, Jovian decametric radiation, solar radio bursts, etc.
	enumeration	Waves.Active
		Exerting an influence or producing a change or effect. An active measurement is one which produces a transmission or excitation as a part of the measurement cycle.
	enumeration	Waves.Passive
		Movement or effect produced by outside influence. A passive measurement is one which does not produce a transmission or excitation as a part of the measurement cycle.
Used by	Element	MeasurementType
Source		<pre><xsd:simpleType name="enumMeasurementType"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the method of making an estimated value of a quantity that forms the basis of an observation.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="ActivityIndex"> <xsd:annotation> <xsd:documentation xml:lang="en">An indication, derived from one or more measurements, of the level of activity of an object or region, such as sunspot number, F10.7 flux, Dst, or the Polar Cap Indices.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Dopplergram"> <xsd:annotation> <xsd:documentation xml:lang="en">A map or image depicting the spatial distribution of line-of-sight velocities of the observed object.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Dust"> <xsd:annotation> <xsd:documentation xml:lang="en">Free microscopic particles of solid material.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="ElectricField"> <xsd:annotation> <xsd:documentation xml:lang="en">A region of space around a charged particle, or between two voltages within which a force is exerted on charged objects in its vicinity. An electric field is the electric force per unit charge.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="EnergeticParticles"> <xsd:annotation> <xsd:documentation xml:lang="en">Pieces of matter that are moving very fast. Energetic particles include protons, electrons, neutrons, neutrinos, the nuclei of atoms, and other sub-atomic particles.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Ephemeris"> <xsd:annotation> <xsd:documentation xml:lang="en">The spatial coordinates of a body as a function of time. When used as an Instrument Type it represents the process or methods used to generate spatial coordinates.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="ImageIntensity"> <xsd:annotation> <xsd:documentation xml:lang="en">Measurements of the two-dimensional distribution of the intensity of photons from some region or object such as the Sun or the polar auroral regions; can be in any wavelength band, and polarized, etc.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="InstrumentStatus"> <xsd:annotation></pre>

```

<xsd:documentation xml:lang="en">A quantity directly related to the operation
or function of an instrument.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="IonComposition">
<xsd:annotation>
<xsd:documentation xml:lang="en">In situ measurements of the relative flux
or density of electrically charged particles
in the space environment. May give simple
fluxes, but full distribution functions are
sometimes measured.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Irradiance">
<xsd:annotation>
<xsd:documentation xml:lang="en">Irradiance - A radiometric term for the power
of electromagnetic radiation at a surface,
per unit area. "Irradiance" is used when the
electromagnetic radiation is incident on the
surface. Irradiance data may be reported
in any units (i.e. counts/s) due to, for example,
being at a particular wavelength, or to being
a not-fully-calibrated relative measurement.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="MagneticField">
<xsd:annotation>
<xsd:documentation xml:lang="en">A region of space near a magnetized body where
magnetic forces can be detected (as measured
by methods such as Zeeman splitting, etc.).</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Magnetogram">
<xsd:annotation>
<xsd:documentation xml:lang="en">Measurements of the vector or line-of-sight
magnetic field determined from remote sensing
measurements of the detailed structure of
spectral lines, including their splitting
and polarization. ("Magnetogram.")</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="NeutralAtomImages">
<xsd:annotation>
<xsd:documentation xml:lang="en">Measurements of neutral atom fluxes as a function
of look direction; often related to remote
energetic charged particles that lose their
charge through charge-exchange and then reach
the detector on a line-of-sight trajectory.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="NeutralGas">
<xsd:annotation>
<xsd:documentation xml:lang="en">Measurements of neutral atomic and molecular
components of a gas.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Profile">
<xsd:annotation>
<xsd:documentation xml:lang="en">Measurements of a quantity as a function of
height above an object such as the limb of
a body.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Radiance">
<xsd:annotation>
<xsd:documentation xml:lang="en">A radiometric measurement that describes the
amount of electromagnetic radiation that passes
through or is emitted from a particular area,
and falls within a given solid angle in a
specified direction. They are used to characterize
both emission from diffuse sources and reflection
from diffuse surfaces.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Spectrum">
<xsd:annotation>
<xsd:documentation xml:lang="en">The distribution of a characteristic of a
physical system or phenomenon, such as the
energy emitted by a radiant source, arranged
in the order of wavelengths.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="ThermalPlasma">

```

	<pre> <xsd:annotation> <xsd:documentation xml:lang="en">Measurements of the plasma in the energy regime where the most of the plasma occurs. May be the basic fluxes in the form of distribution functions or the derived bulk parameters (density, flow velocity, etc.).</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Waves"> <xsd:annotation> <xsd:documentation xml:lang="en">Data resulting from observations of wave experiments and natural wave phenomena. Wave experiments are typically active and natural wave phenomena are passive. Examples of wave experiments include coherent/incoherent scatter radars, radio soundings, VLF propagation studies, ionospheric scintillation of beacon satellite signals, etc. Examples of natural wave phenomena include micropulsations, mesospheric gravity waves, auroral/plasmaspheric hiss, Langmuir waves, AKR, Jovian decametric radiation, solar radio bursts, etc.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Waves.Active"> <xsd:annotation> <xsd:documentation xml:lang="en">Exerting an influence or producing a change or effect. An active measurement is one which produces a transmission or excitation as a part of the measurement cycle.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Waves.Passive"> <xsd:annotation> <xsd:documentation xml:lang="en">Movement or effect produced by outside influence. A passive measurement is one which does not produce a transmission or excitation as a part of the measurement cycle.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumRegion

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for areas of the physical world which may be occupied or observed.		
Diagram			
Type	restriction of xsd:string		
Facets	enumeration	Asteroid	A small extraterrestrial body consisting mostly of rock and metal that is in orbit around the sun.
	enumeration	Comet	A relatively small extraterrestrial body mostly in a highly elliptical orbit

		the magnetotail begins at a night-side radial distance of 10 Re ($X > -10Re$).
enumeration	Earth.Magnetosphere.Main	The region of the magnetosphere where the magnetic field lines are closed, but does not include the gaseous region gravitationally bound to the body.
enumeration	Earth.Magnetosphere.Polar	The region near the pole of a body. For a magnetosphere the polar region is the area where magnetic field lines are open and includes the auroral zone.
enumeration	Earth.Magnetosphere.RadiationBelt	Region within a magnetosphere where high-energy particles could potentially be trapped in a magnetic field.
enumeration	Earth.NearSurface	The gaseous and possibly ionized environment of a body extending from the surface to some specified altitude. For the Earth, this altitude is 2000 km.
enumeration	Earth.NearSurface.Atmosphere	The neutral gases surrounding a body that extends from the surface and is bound to the body by virtue of the gravitational attraction.
enumeration	Earth.NearSurface.AuroralRegion	The region in the atmosphere where electrically-charged particles bombarding the upper atmosphere of a planet in the presence of a magnetic field produce an optical phenomenon.
enumeration	Earth.NearSurface.EquatorialRegion	A region centered on the equator and limited in latitude by approximately 23 degrees north and south of the equator.
enumeration	Earth.NearSurface.Ionosphere	The charged or ionized gases surrounding a body that are nominally bound to the body by virtue of the gravitational attraction.
enumeration	Earth.NearSurface.IonosphereD	The layer of the ionosphere that exists approximately 50 to 95 km above the surface of the Earth. One of several layers in the ionosphere.
enumeration	Earth.NearSurface.IonosphereE	The layer of ionised gas occurring at 90-150km above the ground. One of several layers in the ionosphere. Also called the The Kennelly-Heaviside layer.
enumeration	Earth.NearSurface.IonosphereF	The F region contains ionized gases at a height of around 150-800 km above sea level, placing it in the thermosphere. the F region has the highest concentration of free electrons and ions anywhere in the atmosphere. It may be thought of as comprising two layers, the F1-and F2-layers. One of several layers in the ionosphere. Also known as the Appleton layer.
enumeration	Earth.NearSurface.IonosphereT	The region of the upper most areas of the ionosphere.
enumeration	Earth.NearSurface.Mesosphere	The layer of the atmosphere that extends from the Stratosphere to a range of 80 km to 85 km, temperature decreasing with height.
enumeration	Earth.NearSurface.Plasmasphere	A region of the magnetosphere consisting of low energy (cool) plasma. It is located above the ionosphere. The outer boundary of the plasmasphere is known as the plasmapause, which is defined by an order of magnitude drop in plasma density.
enumeration	Earth.NearSurface.PolarCap	The areas of the globe surrounding the poles and consisting of the region north of 60 degrees

		north latitude an the region south of 60 degrees south latitude.
enumeration	Earth.NearSurface.SouthAtmosphericRegion	The innermost region of Earth's atmosphere where the radiation belt makes its closest approach to the planets surface. The result is that, for a given altitude, the radiation intensity is higher over this region than elsewhere.
enumeration	Earth.NearSurface.Stratosphere	The layer of the atmosphere that extends from the troposphere to about 30 km, temperature increases with height. The stratosphere contains the ozone layer.
enumeration	Earth.NearSurface.Thermosphere	The layer of the atmosphere that extends from the Mesosphere to 640+ km, temperature increasing with height.
enumeration	Earth.NearSurface.Troposphere	The lowest layer of the atmosphere which begins at the surface and extends to between 7 km (4.4 mi) at the poles and 17 km (10.6 mi) at the equator, with some variation due to weather factors.
enumeration	Earth.Surface	The outermost area of a solid object.
enumeration	Heliosphere	The solar atmosphere extending roughly from the outer corona to the edge of the solar plasma at the heliopause separating primarily solar plasma from interstellar plasma.
enumeration	Heliosphere.Heliosheath	The region extending radially outward from the heliospheric termination shock and in which the decelerated solar wind plasma is still significant.
enumeration	Heliosphere.Inner	The region of the heliosphere extending radially outward from the solar coronal base to just inside 1 AU.
enumeration	Heliosphere.NearEarth	The heliospheric region near the Earth which extends to and includes the area near the L1 and L2 Lagrange point.
enumeration	Heliosphere.Outer	The region of the heliosphere extending radially outward from just outside 1 AU to the heliospheric termination shock.
enumeration	Heliosphere.Remote1AU	A roughly toroidal region that includes the Earth's orbit, but exclusive of the region near the Earth.
enumeration	Interstellar	The region between stars outside of the stars heliopause.
enumeration	Jupiter	The fifth planet from the sun in our solar system.
enumeration	Mars	The forth planet from the sun in our solar system.
enumeration	Mercury	The first planet from the sun in our solar system.
enumeration	Neptune	The seventh planet from the sun in our solar system.
enumeration	Pluto	The ninth (sub)planet from the sun in our solar system.
enumeration	Saturn	The sixth planet from the sun in our solar system.
enumeration	Sun	The star upon which our solar system is centered.
enumeration	Sun.Chromosphere	The region of the Suns (or a stars) atmosphere above the temperature minimum and below the Transition Region. The solar chromosphere

		is approximately 400 km to 2100 km above the photosphere, and characterized by temperatures from 4500 - 28000 K.
enumeration	Sun.Corona	The outermost atmospheric region of the Sun or a star, characterized by ionization temperatures above 10^5 K. The solar corona starts at about 2100 km above the photosphere; there is no generally defined upper limit.
enumeration	Sun.Interior	The region inside the body which is not visible from outside the body.
enumeration	Sun.Photosphere	The atmospheric layer of the Sun or a star from which continuum radiation, especially optical, is emitted to space. For the Sun, the photosphere is about 500 km thick.
enumeration	Sun.TransitionRegion	A very narrow (<100 km) layer between the chromosphere and the corona where the temperature rises abruptly from about 8000 to about 500,000 K.
enumeration	Uranus	The eighth planet from the sun in our solar system.
enumeration	Venus	The second planet from the sun in our solar system.
Used by	Elements	ObservatoryRegion, ObservedRegion
Source	<pre> <xsd:simpleType name="enumRegion"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for areas of the physical world which may be occupied or observed.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Asteroid"> <xsd:annotation> <xsd:documentation xml:lang="en">A small extraterrestrial body consisting mostly of rock and metal that is in orbit around the sun.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Comet"> <xsd:annotation> <xsd:documentation xml:lang="en">A relatively small extraterrestrial body consisting of a frozen mass that travels around the sun in a highly elliptical orbit.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Earth"> <xsd:annotation> <xsd:documentation xml:lang="en">The third planet from the sun in our solar system.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Earth.Magnetosheath"> <xsd:annotation> <xsd:documentation xml:lang="en">The region between the bow shock and the magnetopause, characterized by very turbulent plasma.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Earth.Magnetosphere"> <xsd:annotation> <xsd:documentation xml:lang="en">The region of space above the atmosphere or surface of the planet, and bounded by the magnetopause, that is under the direct influence of the planet's magnetic field.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Earth.Magnetosphere.Magnetotail"> <xsd:annotation> <xsd:documentation xml:lang="en">The region on the night side of the body where the magnetic field is stretched backwards by the force of the solar wind. For Earth, the magnetotail begins at a night-side radial </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>	

```

        distance of 10 Re (X > -10Re).</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.Magnetosphere.Main">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The region of the magnetosphere where the
            magnetic field lines are closed, but does
            not include the gaseous region gravitationally
            bound to the body.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.Magnetosphere.Polar">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The region near the pole of a body. For a
            magnetosphere the polar region is the area
            where magnetic field lines are open and includes
            the auroral zone.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.Magnetosphere.RadiationBelt">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The region within a magnetosphere where high-
            energy
                particles could potentially be trapped in
                a magnetic field.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The gaseous and possibly ionized environment
            of a body extending from the surface to some
            specified altitude. For the Earth, this altitude
            is 2000 km.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface.Atmosphere">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The neutral gases surrounding a body that
            extends from the surface and is bound to the
            body by virtue of the gravitational attraction.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface.AuroralRegion">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The region in the atmospheric where electrically-
            charged
                particles bombarding the upper atmosphere
                of a planet in the presence of a magnetic
                field produce an optical phenomenon.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface.EquatorialRegion">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A region centered on the equator and limited
            in latitude by approximately 23 degrees north
            and south of the equator.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface.Ionosphere">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The charged or ionized gases surrounding a
            body that are nominally bound to the body
            by virtue of the gravitational attraction.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface.Ionosphere.DRegion">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The layer of the ionosphere that exists
            approximately
                50 to 95 km above the surface of the Earth.
                One of several layers in the ionosphere.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface.Ionosphere.ERegion">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A layer of ionised gas occurring at 90-150km
            above the ground. One of several layers in
            the ionosphere. Also called the The Kennelly-Heaviside
            layer.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface.Ionosphere.FRegion">
    <xsd:annotation>

```

```

<xsd:documentation xml:lang="en">A layer that contains ionized gases at a height
of around 150-800 km above sea level, placing
it in the thermosphere. the F region has the
highest concentration of free electrons and
ions anywhere in the atmosphere. It may be
thought of as comprising two layers, the F1-and
F2-layers. One of several layers in the ionosphere.
Also known as the Appleton layer.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface.Ionosphere.Topside">
<xsd:annotation>
<xsd:documentation xml:lang="en">The region at the upper most areas of the
ionosphere.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface.Mesosphere">
<xsd:annotation>
<xsd:documentation xml:lang="en">The layer of the atmosphere that extends from
the Stratosphere to a range of 80 km to 85
km, temperature decreasing with height.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface.Plasmasphere">
<xsd:annotation>
<xsd:documentation xml:lang="en">A region of the magnetosphere consisting of
low energy (cool) plasma. It is located above
the ionosphere. The outer boundary of the
plasmasphere is known as the plasmapause,
which is defined by an order of magnitude
drop in plasma density.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface.PolarCap">
<xsd:annotation>
<xsd:documentation xml:lang="en">The areas of the globe surrounding the poles
and consisting of the region north of 60 degrees
north latitude an the region south of 60 degrees
south latitude.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface.SouthAtlanticAnomalyRegion">
<xsd:annotation>
<xsd:documentation xml:lang="en">The region where the Earth's inner van Allen
radiation belt makes its closest approach
to the planet's surface. The result is that,
for a given altitude, the radiation intensity
is higher over this region than elsewhere.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface.Stratosphere">
<xsd:annotation>
<xsd:documentation xml:lang="en">The layer of the atmosphere that extends from
the troposphere to about 30 km, temperature
increases with height. The stratosphere contains
the ozone layer.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface.Thermosphere">
<xsd:annotation>
<xsd:documentation xml:lang="en">The layer of the atmosphere that extends from
the Mesosphere to 640+ km, temperature increasing
with height.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.NearSurface.Troposphere">
<xsd:annotation>
<xsd:documentation xml:lang="en">The lowest layer of the atmosphere which begins
at the surface and extends to between 7 km
(4.4 mi) at the poles and 17 km (10.6 mi)
at the equator, with some variation due to
weather factors.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Earth.Surface">
<xsd:annotation>
<xsd:documentation xml:lang="en">The outermost area of a solid object.</
xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Heliosphere">
<xsd:annotation>
<xsd:documentation xml:lang="en">The solar atmosphere extending roughly from

```

```

        the outer corona to the edge of the solar
        plasma at the heliopause separating primarily
        solar plasma from interstellar plasma.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Heliosphere.Heliosheath">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The region extending radially outward from
            the heliospheric termination shock and in
            which the decelerated solar wind plasma is
            still significant.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Heliosphere.Inner">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The region of the heliosphere extending radially
            outward from the solar coronal base to just
            inside 1 AU.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Heliosphere.NearEarth">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The heliospheric region near the Earth which
            extends to and includes the area near the
            L1 and L2 Lagrange point.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Heliosphere.Outer">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The region of the heliosphere extending radially
            outward from just outside 1 AU to the heliospheric
            termination shock.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Heliosphere.RemoteAU">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A roughly toroidal region that includes the
            Earth's orbit, but exclusive of the region
            near the Earth.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Interstellar">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The region between stars outside of the
        star's
            heliopause.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Jupiter">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The fifth planet from the sun in our solar
            system.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Mars">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The forth planet from the sun in our solar
            system.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Mercury">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The first planet from the sun in our solar
            system.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Neptune">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The seventh planet from the sun in our solar
            system.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Pluto">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The ninth (sub)planet from the sun in our
            solar system.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Saturn">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">The sixth planet from the sun in our solar
            system.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>

```

	<pre> </xsd:enumeration> <xsd:enumeration value="Sun"> <xsd:annotation> <xsd:documentation xml:lang="en">The star upon which our solar system is centered.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Sun.Chromosphere"> <xsd:annotation> <xsd:documentation xml:lang="en">The region of the Sun's (or a star's) atmosphere above the temperature minimum and below the Transition Region. The solar chromosphere is approximately 400 km to 2100 km above the photosphere, and characterized by temperatures from 4500 - 28000 K.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Sun.Corona"> <xsd:annotation> <xsd:documentation xml:lang="en">The outermost atmospheric region of the Sun or a star, characterized by ionization temperatures above 10⁵ K. The solar corona starts at about 2100 km above the photosphere; there is no generally defined upper limit.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Sun.Interior"> <xsd:annotation> <xsd:documentation xml:lang="en">The region inside the body which is not visible from outside the body.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Sun.Photosphere"> <xsd:annotation> <xsd:documentation xml:lang="en">The atmospheric layer of the Sun or a star from which continuum radiation, especially optical, is emitted to space. For the Sun, the photosphere is about 500 km thick.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Sun.TransitionRegion"> <xsd:annotation> <xsd:documentation xml:lang="en">A very narrow (<100 km) layer between the chromosphere and the corona where the temperature rises abruptly from about 8000 to about 500,000 K.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Uranus"> <xsd:annotation> <xsd:documentation xml:lang="en">The eighth planet from the sun in our solar system.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Venus"> <xsd:annotation> <xsd:documentation xml:lang="en">The second planet from the sun in our solar system.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumDocumentType

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for the characterization of the content or purpose of a document.		
Diagram			
Type	restriction of xsd:string		
Facets	enumeration	Paper	A formal presentation of an idea or discovery typically more than a few pages in length.
Used by	Element	DocumentType	

Source	<pre><xsd:simpleType name="enumDocumentType"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the characterization of the content or purpose of a document.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Paper"> <xsd:annotation> <xsd:documentation xml:lang="en">A formal presentation of an idea or discovery typically more than a few pages in length.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumSourceType

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for the characterization of the function or purpose of a source.		
Diagram	<pre> classDiagram enumSourceType < -- xsd:string </pre>		
Type	restriction of xsd:string		
Facets	enumeration	Ancillary	A complementary item which can be subordinate, subsidiary, auxiliary, supplementary to the primary item.
	enumeration	Browse	A representation of an image which is suitable to reveal most or all of the details of the image.
	enumeration	Data	A collection of organized information, usually the results of experience, observation or experiment, or a set of premises. This may consist of numbers, words, or images, particularly as measurements or observations of a set of variables.
	enumeration	Layout	The structured arrangement of items in a collection.
	enumeration	Thumbnail	A small representation of an image which is suitable to infer what the full-sized image is like.
Used by	Element	SourceType	
Source	<pre><xsd:simpleType name="enumSourceType"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the characterization of the function or purpose of a source.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Ancillary"> <xsd:annotation> <xsd:documentation xml:lang="en">A complementary item which can be subordinate, subsidiary, auxiliary, supplementary to the primary item.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Browse"> <xsd:annotation> <xsd:documentation xml:lang="en">A representation of an image which is suitable to reveal most or all of the details of the image.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Data"> <xsd:annotation> <xsd:documentation xml:lang="en">A collection of organized information, usually the results of experience, observation or experiment, or a set of premises. This may consist of numbers, words, or images, particularly as measurements or observations of a set of variables.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>		

	<pre> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Layout"> <xsd:annotation> <xsd:documentation xml:lang="en">The structured arrangement of items in a collection.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Thumbnail"> <xsd:annotation> <xsd:documentation xml:lang="en">A small representation of an image which is suitable to infer what the full-sized imaged is like.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumHashFunction

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for functions or algorithms that convert a digital data object into a hash value.		
Diagram			
Type	restriction of xsd:string		
Facets	enumeration	MD5	Message Digest 5 (MD5) is a 128-bit message digest algorithm created in 1991 by Professor Ronald Rivest.
	enumeration	SHA1	Secure Hash Algorithm (SHA), a 160-bit message digest algorithm developed by the NSA and described in Federal Information Processing Standard (FIPS) publication 180-1.
	enumeration	SHA256	Secure Hash Algorithm (SHA), a 256-bit message digest algorithm developed by the NSA and described in Federal Information Processing Standard (FIPS) publication 180-1.
Used by	Element	HashFunction	
Source	<pre> <xsd:simpleType name="enumHashFunction"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for functions or algorithms that convert a digital data object into a hash value.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="MD5"> <xsd:annotation> <xsd:documentation xml:lang="en">Message Digest 5 (MD5) is a 128-bit message digest algorithm created in 1991 by Professor Ronald Rivest.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="SHA1"> <xsd:annotation> <xsd:documentation xml:lang="en">Secure Hash Algorithm (SHA), a 160-bit message digest algorithm developed by the NSA and described in Federal Information Processing Standard (FIPS) publication 180-1.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="SHA256"> <xsd:annotation> <xsd:documentation xml:lang="en">Secure Hash Algorithm (SHA), a 256-bit message digest algorithm developed by the NSA and described in Federal Information Processing Standard (FIPS) publication 180-1.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>		

Schema location

file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumInstrumentType

Namespace	http://www.spase-group.org/data/schema	
Annotations	Identifiers for the type of experiment the instrument performs. This is the technique of observation.	
Diagram	<pre> classDiagram enumInstrumentType < -- xsd:string </pre>	
Type	restriction of xsd:string	
Facets	enumeration	Antenna A sensor used to measure electric potential.
	enumeration	Channeltron An instrument that detects electrons, ions, and UV-radiation, according to the principle of a secondary emission multiplier. It is typically used in electron spectroscopy and mass spectrometry.
	enumeration	Coronograph An instrument which can image things very close to the Sun by using a disk to block the Sun's bright surface which reveals the faint solar corona and other celestial objects.
	enumeration	DoubleSphere A dipole antenna of which the active (sensor) elements are small spheres located at the ends of two wires deployed in the equatorial plane, on opposite sides of a spinning spacecraft.
	enumeration	DustDetector An instrument which determines the mass and speed of ambient dust particles.
	enumeration	ElectronDriftInstrument An active experiment to measure the electron drift velocity based on sensing the displacement of a weak beam of electrons after one gyration in the ambient magnetic field.
	enumeration	ElectrostaticAnalyser An instrument which uses charged plates to analyze the mass, charge and kinetic energies of charged particles which enter the instrument.
	enumeration	EnergeticParticleInstrument An instrument that measures fluxes of charged particles as a function of time, direction of motion, mass, charge and/or species.
	enumeration	FaradayCup An instrument consisting of an electrode from which electrical current is measured while a charged particle beam (electrons or ions) impinges on it. Used to determine energy spectrum and sometimes ion composition of the impinging particles.
	enumeration	FluxFeedback A search coil whose bandwidth and signal/noise ratio are increased by the application of negative feedback at the sensor (flux) level by driving a collocated coil with a signal from the preamplifier.
	enumeration	FourierTransformSpectrometer An instrument that determines the spectra of a radiative source, using time-domain measurements and a Fourier transform.
	enumeration	GeigerMuellerTube An instrument which measures density of ionizing radiation based on interactions with a gas.
	enumeration	Imager An instrument which samples the radiation from an area at one or more spectral ranges emitted or reflected by an object.
	enumeration	ImagingSpectrometer An instrument which is a multispectral scanner

		with a very large number of channels (64-256 channels) with very narrow band widths.
enumeration	Interferometer	An instrument to study the properties of two or more waves from the pattern of interference created by their superposition.
enumeration	IonChamber	A device in which the collected electrical charge from ionization in a gas-filled cavity is taken to be the proportion to some parameter (e.g. dose or exposure) of radiation field
enumeration	IonDrift	A device which measures the current produced by the displacement of ambient ions on a grid, thereby allowing the determination of the ion trajectory and velocity.
enumeration	LangmuirProbe	A monopole antenna associated with an instrument. The instrument applies a potential to the antenna which is swept to determine the voltage/current characteristic. This provides information about the plasma surrounding the probe and spacecraft.
enumeration	LongWire	A dipole antenna whose active (sensor) elements are two wires deployed in the equatorial plane on opposite sides of a spinning spacecraft, and whose length is several times greater than the spacecraft diameter.
enumeration	Magnetometer	An instrument which measures the ambient magnetic field.
enumeration	MassSpectrometer	An instrument which distinguishes chemical species in terms of their different isotopic masses.
enumeration	MicrochannelPlate	An instrument used for the detection of elementary particles, ions, ultraviolet rays and soft X-rays constructed from very thin conductive glass capillaries.
enumeration	MultispectralImager	An instrument which captures images at multiple spectral ranges.
enumeration	NeutralAtomImager	An instrument which measures the quantity and properties of neutral particles over a range of angles. Measured properties can include mass and energy.
enumeration	NeutralParticleDetector	An instrument which measures the quantity and properties of neutral particles. Measured properties can include mass and plasma bulk densities.
enumeration	ParticleCorrelator	An instrument which correlates particle flux to help identify wave/particle interactions.
enumeration	ParticleDetector	An instrument which detects particle flux!!!
enumeration	Photometer	An instrument which measures the strength of electromagnetic radiation within a spectral band which can range from ultraviolet to infrared and includes the visible spectrum.
enumeration	Photopolarimeter	An instrument which measures the intensity and polarization or radiant energy. A photopolarimeter is a combination of a photometer and a polarimeter.
enumeration	Platform	A collection of components which can be positioned and oriented as a single unit. A platform may contain other platforms. For example,

		a spacecraft is a platform which may have components that can be articulated and are also considered platforms.
enumeration	ProportionalCounter	An instrument which measures energy of ionization radiation based on interactions with a gas.
enumeration	QuadrисphericalAnalyser	An instrument used for the 3-D detection of plasma, energetic electrons and ions, and for positive-ion composition measurements.
enumeration	Radar	An instrument that uses directional properties of returned power to infer spatial and/or other characteristics of a remote object.
enumeration	Radiometer	An instrument for detecting or measuring radiant energy. Radiometers are commonly limited to infrared radiation.
enumeration	ResonanceSounder	A combination of a radio receiver and a pulsed transmitter used to study the plasma surrounding a spacecraft by identifying resonances or cut-offs (of the wave dispersion relation), whose frequencies are related to the ambient plasma density and magnetic field. When the transmitter is off it is essentially a high frequency-resolution spectral power receiver.
enumeration	RetardingPotentialAnalyser	An instrument which measures ion temperatures and ion concentrations using a planar ion trap.
enumeration	Riometer	An instrument which measure the signal strength in various directions of the galactic radio signals. Variations in these signals are influenced by solar flare activity and geomagnetic storm and substorm processes.
enumeration	ScintillationDetector	An instrument which detects flourescences of a material which is excited by high energy (ionizing) electromagnetic or charged particle radiation.
enumeration	SearchCoil	An instrument which measures the time variation of the magnetic flux threading a loop by measurement of the electric potential difference induced between the ends of the wire.
enumeration	Sounder	An instrument which measures the radiances from an object. A sounder may measure radiances at multiple spectral ranges.
enumeration	SpacecraftPotentialController	An instrument to control the electric potential of a spacecraft with respect to the ambient plasma by emitting a variable current of positive ions.
enumeration	SpectralPowerReceiver	A radio receiver which determines the power spectral density of the electric or magnetic field, or both, at one or more frequencies.
enumeration	Spectrometer	An instrument that measures the component wavelengths of light (or other electromagnetic radiation) by splitting the light up into its component wavelengths.
enumeration	TimeOfFlight	An instrument which measures the time it takes for a particle to travel between two detectors.
enumeration	Unspecified	A value which is not provided.

	enumeration	WaveformReceiver	A radio receiver which outputs the value of one or more components of the electric and/or magnetic field as a function of time.
Used by	Element	InstrumentType	
Source		<xsd:simpleType name="enumInstrumentType"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the type of experiment the instrument performs. This is the technique of observation.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Antenna"> <xsd:annotation> <xsd:documentation xml:lang="en">A sensor used to measure electric potential.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Channeltron"> <xsd:annotation> <xsd:documentation xml:lang="en">An instrument that detects electrons, ions, and UV-radiation, according to the principle of a secondary emission multiplier. It is typically used in electron spectroscopy and mass spectrometry.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Coronograph"> <xsd:annotation> <xsd:documentation xml:lang="en">An instrument which can image things very close to the Sun by using a disk to block the Sun's bright surface which reveals the faint solar corona and other celestial objects.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="DoubleSphere"> <xsd:annotation> <xsd:documentation xml:lang="en">A dipole antenna of which the active (sensor) elements are small spheres located at the ends of two wires deployed in the equatorial plane, on opposite sides of a spinning spacecraft.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="DustDetector"> <xsd:annotation> <xsd:documentation xml:lang="en">An instrument which determines the mass and speed of ambient dust particles.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="ElectronDriftInstrument"> <xsd:annotation> <xsd:documentation xml:lang="en">An active experiment to measure the electron drift velocity based on sensing the displacement of a weak beam of electrons after one gyration in the ambient magnetic field.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="ElectrostaticAnalyser"> <xsd:annotation> <xsd:documentation xml:lang="en">An instrument which uses charged plates to analyze the mass, charge and kinetic energies of charged particles which enter the instrument.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="EnergeticParticleInstrument"> <xsd:annotation> <xsd:documentation xml:lang="en">An instrument that measures fluxes of charged particles as a function of time, direction of motion, mass, charge and/or species.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="FaradayCup"> <xsd:annotation> <xsd:documentation xml:lang="en">An instrument consisting of an electrode from which electrical current is measured while a charged particle beam (electrons or ions) impinges on it. Used to determine energy spectrum and sometimes ion composition of the impinging particles.</xsd:documentation> </xsd:annotation> </xsd:enumeration>	

```

</xsd:enumeration>
<xsd:enumeration value="FluxFeedback">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A search coil whose bandwidth and signal/noise
      ratio are increased by the application of
      negative feedback at the sensor (flux) level
      by driving a collocated coil with a signal
      from the preamplifier.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="FourierTransformSpectrograph">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">An instrument that determines the spectra
      of a radiative source, using time-domain measurements
      and a Fourier transform.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="GeigerMuellerTube">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">An instrument which measures density of ionizing
      radiation based on interactions with a gas.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Imager">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">An instrument which samples the radiation
      from an area at one or more spectral ranges
      emitted or reflected by an object.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="ImagingSpectrometer">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">An instrument which is a multispectral scanner
      with a very large number of channels (64-256
      channels) with very narrow band widths.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Interferometer">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">An instrument to study the properties of two
      or more waves from the pattern of interference
      created by their superposition.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="IonChamber">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A device in which the collected electrical
      charge from ionization in a gas-filled cavity
      is taken to be the proportion to some parameter
      (e.g. dose or exposure) of radiation field</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="IonDrift">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A device which measures the current produced
      by the displacement of ambient ions on a grid,
      thereby allowing the determination of the
      ion trajectory and velocity.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="LangmuirProbe">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A monopole antenna associated with an instrument.
      The instrument applies a potential to the
      antenna which is swept to determine the voltage/current
      characteristic. This provides information
      about the plasma surrounding the probe and
      spacecraft.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="LongWire">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A dipole antenna whose active (sensor) elements
      are two wires deployed in the equatorial plane
      on opposite sides of a spinning spacecraft,
      and whose length is several times greater
      than the spacecraft diameter.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Magnetometer">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">An instrument which measures the ambient magnetic
      field.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>

```

```

        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="MassSpectrometer">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">An instrument which distinguishes chemical
                species in terms of their different isotopic
                masses.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="MicrochannelPlate">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">An instrument used for the detection of
                elementary
                    particles, ions, ultraviolet rays and soft
                    X-rays constructed from very thin conductive
                    glass capillaries.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="MultispectralImager">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">An instrument which captures images at multiple
                spectral ranges.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="NeutralAtomImager">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">An instrument which measures the quantity
                and properties of neutral particles over a
                range of angles. Measured properties can include
                mass and energy.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="NeutralParticleDetector">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">An instrument which measures the quantity
                and properties of neutral particles. Measured
                properties can include mass and plasma bulk
                densities.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="ParticleCorrelator">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">An instrument which correlates particle flux
                to help identify wave/particle interactions.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="ParticleDetector">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">An instrument which detects particle flux!!!</
xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="Photometer">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">An instrument which measures the strength
                of electromagnetic radiation within a spectral
                band which can range from ultraviolet to infrared
                and includes the visible spectrum.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="Photopolarimeter">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">An instrument which measures the intensity
                and polarization or radiant energy. A photopolarimeter
                is a combination of a photometer and a polarimeter.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="Platform">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">A collection of components which can be
                positioned
                    and oriented as a single unit. A platform
                    may contain other platforms. For example,
                    a spacecraft is a platform which may have
                    components that can be articulated and are
                    also considered platforms.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="ProportionalCounter">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">An instrument which measures energy of ionization
                radiation based on interactions with a gas.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>

```

```

</xsd:enumeration>
<xsd:enumeration value="QuadrисphericalAnalyser">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">An instrument used for the 3-D detection of
            plasma, energetic electrons and ions, and
            for positive-ion composition measurements.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Radar">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">An instrument that uses directional properties
            of returned power to infer spatial and/or
            other characteristics of a remote object.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Radiometer">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">An instrument for detecting or measuring radiant
            energy. Radiometers are commonly limited to
            infrared radiation.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="ResonanceSounder">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">A combination of a radio receiver and a pulsed
            transmitter used to study the plasma surrounding
            a spacecraft by identifying resonances or
            cut-offs (of the wave dispersion relation),
            whose frequencies are related to the ambient
            plasma density and magnetic field. When the
            transmitter is off it is essentially a high
            frequency-resolution spectral power receiver.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="RetardingPotentialAnalyser">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">An instrument which measures ion temperatures
            and ion concentrations using a planar ion
            trap.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Riometer">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">An instrument which measure the signal strength
            in various directions of the galactic radio
            signals. Variations in these signals are influenced
            by solar flare activity and geomagnetic storm
            and substorm processes.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="ScintillationDetector">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">An instrument which detects flourescences of
            a material which is excited by high energy
            (ionizing) electromagnetic or charged particle
            radiation.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="SearchCoil">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">An instrument which measures the time variation
            of the magnetic flux threading a loop by measurement
            of the electric potential difference induced
            between the ends of the wire.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Sounder">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">An instrument which measures the radiances
            from an object. A sounder may measure radiances
            at multiple spectral ranges.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="SpacecraftPotentialControl">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">An instrument to control the electric potential
            of a spacecraft with respect to the ambient
            plasma by emitting a variable current of positive
            ions.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="SpectralPowerReceiver">
    <xsd:annotation>

```

```

<xsd:documentation xml:lang="en">A radio receiver which determines the power
spectral density of the electric or magnetic
field, or both, at one or more frequencies.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Spectrometer">
<xsd:annotation>
<xsd:documentation xml:lang="en">An instrument that measures the component
wavelengths of light (or other electromagnetic
radiation) by splitting the light up into
its component wavelengths.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="TimeOfFlight">
<xsd:annotation>
<xsd:documentation xml:lang="en">An instrument which measures the time it takes
for a particle to travel between two detectors.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Unspecified">
<xsd:annotation>
<xsd:documentation xml:lang="en">A value which is not provided.</
xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="WaveformReceiver">
<xsd:annotation>
<xsd:documentation xml:lang="en">A radio receiver which outputs the value of
one or more components of the electric and/or
magnetic field as a function of time.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
</xsd:restriction>
</xsd:simpleType>

```

Schema location file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumAnnotationType

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for an classification of an annotation.		
Diagram			
Type	restriction of xsd:string		
Facets	enumeration	Anomaly	An interval where measurements or observations may be adversely affected.
	enumeration	Event	An action or observation which occurs at a point in time.
	enumeration	Feature	A prominent or distinctive characteristic that occurs at a location or persists over a period of time.
Used by	Element	AnnotationType	
Source	<pre> <xsd:simpleType name="enumAnnotationType"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for an classification of an annotation.</ xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Anomaly"> <xsd:annotation> <xsd:documentation xml:lang="en">An interval where measurements or observations may be adversely affected.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Event"> <xsd:annotation> <xsd:documentation xml:lang="en">An action or observation which occurs at a point in time.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Feature"> <xsd:annotation> <xsd:documentation xml:lang="en">A prominent or distinctive characteristic that occurs at a location or persists over a period of time.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>		

	<pre> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumClassificationMethod

Namespace	http://www.spase-group.org/data/schema				
Annotations	Identifiers for the technique used to determine the characteristics of an object.				
Diagram	<pre> classDiagram enumClassificationMethod < -- xsd:string </pre>				
Type	restriction of xsd:string				
Facets	enumeration	Automatic	Determined by the analysis or assessment performed by a program or server.		
	enumeration	Inferred	Determined by the analysis of other information or resources.		
	enumeration	Inspection	Determined by the analysis or assessment performed by a person.		
Used by	Element	ClassificationMethod			
Source	<pre> <xsd:simpleType name="enumClassificationMethod"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the technique used to determine the characteristics of an object.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Automatic"> <xsd:annotation> <xsd:documentation xml:lang="en">Determined by the analysis or assessment performed by a program or server.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Inferred"> <xsd:annotation> <xsd:documentation xml:lang="en">Determined by the analysis of other information or resources.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Inspection"> <xsd:annotation> <xsd:documentation xml:lang="en">Determined by the analysis or assessment performed by a person.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>				
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd				

Simple Type enumConfidenceRating

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for the classification of the certainty of an assertion.		
Diagram	<pre> classDiagram enumConfidenceRating < -- xsd:string </pre>		
Type	restriction of xsd:string		
Facets	enumeration	Probable	Likely given the available evidence. Considered in the range of 4-7 on a scale of 0-10.
	enumeration	Strong	Highly likely given the available evidence. Considered in the range of 7-10 on a scale of 0-10.
	enumeration	Unlikely	Not likely given the available evidence. Considered

			in the range of 0 on a scale of 0-10.
	enumeration	Weak	Slightly likely given the available evidence. Considered in the range of 1-4 on a scale of 0-10.
Used by	Element	ConfidenceRating	
Source	<pre><xsd:simpleType name="enumConfidenceRating"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the classification of the certainty of an assertion.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Probable"> <xsd:annotation> <xsd:documentation xml:lang="en">Likely given the available evidence. Considered in the range of 4-7 on a scale of 0-10.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Strong"> <xsd:annotation> <xsd:documentation xml:lang="en">Highly likely given the available evidence. Considered in the range of 7-10 on a scale of 0-10.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Unlikely"> <xsd:annotation> <xsd:documentation xml:lang="en">Not likely given the available evidence. </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Weak"> <xsd:annotation> <xsd:documentation xml:lang="en">Slightly likely given the available evidence. Considered in the range of 1-4 on a scale of 0-10.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>		
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd		

Simple Type enumComponent

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for the axis of coordinate systems.		
Diagram			
Type	restriction of xsd:string		
Facets	enumeration	I	Projection of a vector along the first named axis of a coordinate system. Typically the X axis, but could be the R axis for an RTN coordinate system.
	enumeration	J	Projection of a vector along the second named axis of a coordinate system. Typically the Y axis, but could be the T axis for an RTN coordinate system.
	enumeration	K	Projection of a vector along the third named axis of a coordinate system. Typically the Z axis, but could be the N axis for an RTN coordinate system.
Source	<pre><xsd:simpleType name="enumComponent"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the axis of coordinate systems.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="I"> <xsd:annotation> <xsd:documentation xml:lang="en">Projection of a vector along the first named axis of a coordinate system. Typically the X axis, but could be the R axis for an RTN</pre>		

```

        coordinate system.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="J">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Projection of a vector along the second named
            axis of a coordinate system. Typically the
            Y axis, but could be the T axis for an RTN
            coordinate system.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="K">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">Projection of a vector along the third named
            axis of a coordinate system. Typically the
            Z axis, but could be the N axis for an RTN
            coordinate system.</xsd:documentation>
    </xsd:annotation>
</xsd:enumeration>
</xsd:restriction>
</xsd:simpleType>

```

Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd
-----------------	---

Simple Type enumDirectionAngle

Namespace	http://www.spase-group.org/data/schema										
Annotations	Identifiers for the angle between a vector and a base axis.										
Diagram	<pre> classDiagram class enumDirectionAngle { <<restriction of xsd:string>> } </pre>										
Type	restriction of xsd:string										
Facets	<table border="1"> <tr> <td>enumeration</td> <td>AzimuthAngle</td> <td>The angle between the projection into the i-j plane of a position or measured vector and the i-axis of the coordinate system. Mathematically defined as $\arctan(j/i)$.</td> </tr> <tr> <td>enumeration</td> <td>ElevationAngle</td> <td>The angle between the position or measured vector and the i-j plane of the coordinate system. Mathematically defined as $\arctan(k/\sqrt{i^2+j^2})$.</td> </tr> <tr> <td>enumeration</td> <td>PolarAngle</td> <td>The angle between the position or measured vector and the k-axis of the coordinate system. Mathematically defined as $\arctan([\sqrt{i^2+j^2}]/k)$.</td> </tr> </table>	enumeration	AzimuthAngle	The angle between the projection into the i-j plane of a position or measured vector and the i-axis of the coordinate system. Mathematically defined as $\arctan(j/i)$.	enumeration	ElevationAngle	The angle between the position or measured vector and the i-j plane of the coordinate system. Mathematically defined as $\arctan(k/\sqrt{i^2+j^2})$.	enumeration	PolarAngle	The angle between the position or measured vector and the k-axis of the coordinate system. Mathematically defined as $\arctan([\sqrt{i^2+j^2}]/k)$.	
enumeration	AzimuthAngle	The angle between the projection into the i-j plane of a position or measured vector and the i-axis of the coordinate system. Mathematically defined as $\arctan(j/i)$.									
enumeration	ElevationAngle	The angle between the position or measured vector and the i-j plane of the coordinate system. Mathematically defined as $\arctan(k/\sqrt{i^2+j^2})$.									
enumeration	PolarAngle	The angle between the position or measured vector and the k-axis of the coordinate system. Mathematically defined as $\arctan([\sqrt{i^2+j^2}]/k)$.									
Source	<pre> <xsd:simpleType name="enumDirectionAngle"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the angle between a vector and a base axis.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="AzimuthAngle"> <xsd:annotation> <xsd:documentation xml:lang="en">The angle between the projection into the i-j plane of a position or measured vector and the i-axis of the coordinate system. Mathematically defined as $\arctan(j/i)$.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="ElevationAngle"> <xsd:annotation> <xsd:documentation xml:lang="en">The angle between the position or measured vector and the i-j plane of the coordinate system. Mathematically defined as $\arctan(k/\sqrt{i^2+j^2})$.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="PolarAngle"> <xsd:annotation> <xsd:documentation xml:lang="en">The angle between the position or measured vector and the k-axis of the coordinate system. Mathematically defined as $\arctan([\sqrt{i^2+j^2}]/k)$.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>										
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd										

Simple Type enumEarth

Namespace	http://www.spase-group.org/data/schema	
Annotations	Identifiers for the regions surrounding the Earth.	
Diagram	<pre> classDiagram enumEarth < -- xsd:string </pre>	
Type	restriction of xsd:string	
Facets	enumeration	Magnetosheath The region between the bow shock and the magnetopause, characterized by very turbulent plasma.
	enumeration	Magnetosphere The region of space above the atmosphere or surface of the planet, and bounded by the magnetopause, that is under the direct influence of the planets magnetic field.
	enumeration	Magnetosphere.Magnetotail The region on the night side of the body where the magnetic filed is stretched backwards by the force of the solar wind. For Earth, the magnetotail begins at a night-side radial distance of 10 Re ($X > -10Re$).
	enumeration	Magnetosphere.Main The region of the magnetosphere where the magnetic field lines are closed, but does not include the gaseous region gravitationally bound to the body.
	enumeration	Magnetosphere.Polar The region near the pole of a body. For a magnetosphere the polar region is the area where magnetic field lines are open and includes the auroral zone.
	enumeration	Magnetosphere.RadiationBelts The region within a magnetosphere where high-energy particles could potentially be trapped in a magnetic field.
	enumeration	NearSurface The gaseous and possibly ionized environment of a body extending from the surface to some specified altitude. For the Earth, this altitude is 2000 km.
	enumeration	NearSurface.Atmosphere The neutral gases surrounding a body that extends from the surface and is bound to the body by virtue of the gravitational attraction.
	enumeration	NearSurface.AuroralRegion The region in the atmospheric where electrically-charged particles bombarding the upper atmosphere of a planet in the presence of a magnetic field produce an optical phenomenon.
	enumeration	NearSurface.EquatorialRegion A region centered on the equator and limited in latitude by approximately 23 degrees north and south of the equator.
	enumeration	NearSurface.Ionosphere The charged or ionized gases surrounding a body that are nominally bound to the body by virtue of the gravitational attraction.
	enumeration	NearSurface.Ionosphere.DRegion The layer of the ionosphere that exists approximately 50 to 95 km above the surface of the Earth. One of several layers in the ionosphere.
	enumeration	NearSurface.Ionosphere.ERegion A region of ionised gas occurring at 90-150km above the ground. One of several layers in the ionosphere. Also called the The Kennelly-Heaviside layer.
	enumeration	NearSurface.Ionosphere.FRegion A region that contains ionized gases at a height of around 150-800 km above sea level, placing it in the thermosphere. the F region has the highest concentration of free electrons and

		<p>ions anywhere in the atmosphere. It may be thought of as comprising two layers, the F1- and F2-layers. One of several layers in the ionosphere.</p> <p>Also known as the Appleton layer.</p>
enumeration	NearSurface.Ionosphere.Topside	The region at the upper most areas of the ionosphere.
enumeration	NearSurface.Mesosphere	The layer of the atmosphere that extends from the Stratosphere to a range of 80 km to 85 km, temperature decreasing with height.
enumeration	NearSurface.Plasmasphere	A region of the magnetosphere consisting of low energy (cool) plasma. It is located above the ionosphere. The outer boundary of the plasmasphere is known as the plasmapause, which is defined by an order of magnitude drop in plasma density.
enumeration	NearSurface.PolarCap	The areas of the globe surrounding the poles and consisting of the region north of 60 degrees north latitude and the region south of 60 degrees south latitude.
enumeration	NearSurface.SouthAtlanticMagneticRegion	The Earth's inner van Allen radiation belt makes its closest approach to the planets surface. The result is that, for a given altitude, the radiation intensity is higher over this region than elsewhere.
enumeration	NearSurface.Stratosphere	The layer of the atmosphere that extends from the troposphere to about 30 km, temperature increases with height. The stratosphere contains the ozone layer.
enumeration	NearSurface.Thermosphere	The layer of the atmosphere that extends from the Mesosphere to 640+ km, temperature increasing with height.
enumeration	NearSurface.Troposphere	The lowest layer of the atmosphere which begins at the surface and extends to between 7 km (4.4 mi) at the poles and 17 km (10.6 mi) at the equator, with some variation due to weather factors.
enumeration	Surface	The outermost area of a solid object.
Source	<pre><xsd:simpleType name="enumEarth"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the regions surrounding the Earth.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Magnetsheath"> <xsd:annotation> <xsd:documentation xml:lang="en">The region between the bow shock and the magnetopause, characterized by very turbulent plasma.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Magnetosphere"> <xsd:annotation> <xsd:documentation xml:lang="en">The region of space above the atmosphere or surface of the planet, and bounded by the magnetopause, that is under the direct influence of the planet's magnetic field.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Magnetosphere.Magnetotail"> <xsd:annotation> <xsd:documentation xml:lang="en">The region on the night side of the body where the magnetic field is stretched backwards by the force of the solar wind. For Earth, the magnetotail begins at a night-side radial distance of 10 Re (X > -10Re).</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>	

```

        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="Magnetosphere.Main">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">The region of the magnetosphere where the
                magnetic field lines are closed, but does
                not include the gaseous region gravitationally
                bound to the body.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="Magnetosphere.Polar">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">The region near the pole of a body. For a
                magnetosphere the polar region is the area
                where magnetic field lines are open and includes
                the auroral zone.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="Magnetosphere.RadiationBelt">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">The region within a magnetosphere where high-
                energy
                    particles could potentially be trapped in
                    a magnetic field.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="NearSurface">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">The gaseous and possibly ionized environment
                of a body extending from the surface to some
                specified altitude. For the Earth, this altitude
                is 2000 km.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="NearSurface.Atmosphere">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">The neutral gases surrounding a body that
                extends from the surface and is bound to the
                body by virtue of the gravitational attraction.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="NearSurface.AuroralRegion">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">The region in the atmospheric where electrically-
                charged
                    particles bombarding the upper atmosphere
                    of a planet in the presence of a magnetic
                    field produce an optical phenomenon.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="NearSurface.EquatorialRegion">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">A region centered on the equator and limited
                in latitude by approximately 23 degrees north
                and south of the equator.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="NearSurface.Ionosphere">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">The charged or ionized gases surrounding a
                body that are nominally bound to the body
                by virtue of the gravitational attraction.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="NearSurface.Ionosphere.DRegion">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">The layer of the ionosphere that exists
                approximately
                    50 to 95 km above the surface of the Earth.
                    One of several layers in the ionosphere.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="NearSurface.Ionosphere.ERegion">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">A layer of ionised gas occurring at 90-150km
                above the ground. One of several layers in
                the ionosphere. Also called the The Kennelly-Heaviside
                layer.</xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="NearSurface.Ionosphere.FRegion">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">A layer that contains ionized gases at a height

```

```

of around 150-800 km above sea level, placing
it in the thermosphere. the F region has the
highest concentration of free electrons and
ions anywhere in the atmosphere. It may be
thought of as comprising two layers, the F1-and
F2-layers. One of several layers in the ionosphere.
Also known as the Appleton layer.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="NearSurface.Ionosphere.Topside">
<xsd:annotation>
<xsd:documentation xml:lang="en">The region at the upper most areas of the
ionosphere.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="NearSurface.Mesosphere">
<xsd:annotation>
<xsd:documentation xml:lang="en">The layer of the atmosphere that extends from
the Stratosphere to a range of 80 km to 85
km, temperature decreasing with height.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="NearSurface.Plasmasphere">
<xsd:annotation>
<xsd:documentation xml:lang="en">A region of the magnetosphere consisting of
low energy (cool) plasma. It is located above
the ionosphere. The outer boundary of the
plasmasphere is known as the plasmapause,
which is defined by an order of magnitude
drop in plasma density.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="NearSurface.PolarCap">
<xsd:annotation>
<xsd:documentation xml:lang="en">The areas of the globe surrounding the poles
and consisting of the region north of 60 degrees
north latitude an the region south of 60 degrees
south latitude.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="NearSurface.SouthAtlanticAnomalyRegion">
<xsd:annotation>
<xsd:documentation xml:lang="en">The region where the Earth's inner van Allen
radiation belt makes its closest approach
to the planet's surface. The result is that,
for a given altitude, the radiation intensity
is higher over this region than elsewhere.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="NearSurface.Stratosphere">
<xsd:annotation>
<xsd:documentation xml:lang="en">The layer of the atmosphere that extends from
the troposphere to about 30 km, temperature
increases with height. The stratosphere contains
the ozone layer.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="NearSurface.Thermosphere">
<xsd:annotation>
<xsd:documentation xml:lang="en">The layer of the atmosphere that extends from
the Mesosphere to 640+ km, temperature increasing
with height.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="NearSurface.Troposphere">
<xsd:annotation>
<xsd:documentation xml:lang="en">The lowest layer of the atmosphere which begins
at the surface and extends to between 7 km
(4.4 mi) at the poles and 17 km (10.6 mi)
at the equator, with some variation due to
weather factors.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Surface">
<xsd:annotation>
<xsd:documentation xml:lang="en">The outermost area of a solid object.</
xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
</xsd:restriction>
</xsd:simpleType>

```

Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd
-----------------	---

Simple Type enumHardcopy

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for permanent reproductions, or copy in the form of a physical object, of any media suitable for direct use by a person.		
Diagram	<pre> classDiagram class enumHardcopy { <<Identifiers for permanent reproductions, or copy in the form of a physical object, of any media suitable for direct use by a person.>> } class xsdString { <<xsd:string>> } enumHardcopy < -- xsdString </pre>		
Type	restriction of xsd:string		
Facets	enumeration	Film	An image recording medium on which usually a "negative" analog image is registered. A "positive" image can be recovered or reproduced from film, which is usually made of flexible materials for ease of storage and transportation.
	enumeration	Microfiche	A sheet of microfilm on which many pages of material have been photographed; a magnification system is used to read the material.
	enumeration	Microfilm	Film rolls on which materials are photographed at greatly reduced size; a magnification system is used to read the material.
	enumeration	Photograph	An image (positive or negative) registered on a piece of photo-sensitive paper
	enumeration	PhotographicPlate	A rigid (typically glass) medium that functions like film. Its rigidity is for guarding against image distortion due to medium deformation (caused by heat and humidity). Photographic plates are often used for astronomical photography.
	enumeration	Print	A sheet of any written or printed material which may include notes or graphics. Multiple printed pages may be bound into a manuscript or book.
Source	<pre> <xsd:simpleType name="enumHardcopy"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for permanent reproductions, or copy in the form of a physical object, of any media suitable for direct use by a person.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Film"> <xsd:annotation> <xsd:documentation xml:lang="en">An image recording medium on which usually a "negative" analog image is registered. A "positive" image can be recovered or reproduced from film, which is usually made of flexible materials for ease of storage and transportation.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Microfiche"> <xsd:annotation> <xsd:documentation xml:lang="en">A sheet of microfilm on which many pages of material have been photographed; a magnification system is used to read the material.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Microfilm"> <xsd:annotation> <xsd:documentation xml:lang="en">Film rolls on which materials are photographed at greatly reduced size; a magnification system is used to read the material.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Photograph"> <xsd:annotation> <xsd:documentation xml:lang="en">An image (positive or negative) registered on a piece of photo-sensitive paper</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>		

	<pre> <xsd:enumeration value="PhotographicPlate"> <xsd:annotation> <xsd:documentation xml:lang="en">A rigid (typically glass) medium that functions like film. Its rigidity is for guarding against image distortion due to medium deformation (caused by heat and humidity). Photographic plates are often used for astronomical photography.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Print"> <xsd:annotation> <xsd:documentation xml:lang="en">A sheet of any written or printed material which may include notes or graphics. Multiple printed pages may be bound into a manuscript or book.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumHeliosphere

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for regions of the solar atmosphere which extends roughly from the inner corona to the edge of the solar plasma at the heliopause separating primarily solar plasma from interstellar plasma.		
Diagram			
Type	restriction of xsd:string		
Facets	enumeration	Heliosheath	The region extending radially outward from the heliospheric termination shock and in which the decelerated solar wind plasma is still significant.
	enumeration	Inner	The region of the heliosphere extending radially outward from the solar coronal base to just inside 1 AU.
	enumeration	NearEarth	The heliospheric region near the Earth which extends to and includes the area near the L1 and L2 Lagrange point.
	enumeration	Outer	The region of the heliosphere extending radially outward from just outside 1 AU to the heliospheric termination shock.
	enumeration	Remote1AU	A roughly toroidal region that includes the Earth's orbit, but exclusive of the region near the Earth.
Source	<pre> <xsd:simpleType name="enumHeliosphere"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for regions of the solar atmosphere which extends roughly from the inner corona to the edge of the solar plasma at the heliopause separating primarily solar plasma from interstellar plasma.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Heliosheath"> <xsd:annotation> <xsd:documentation xml:lang="en">The region extending radially outward from the heliospheric termination shock and in which the decelerated solar wind plasma is still significant.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Inner"> <xsd:annotation> <xsd:documentation xml:lang="en">The region of the heliosphere extending radially outward from the solar coronal base to just inside 1 AU.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="NearEarth"> <xsd:annotation> <xsd:documentation xml:lang="en">The heliospheric region near the Earth which extends to and includes the area near the L1 and L2 Lagrange point.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Outer"> <xsd:annotation> <xsd:documentation xml:lang="en">The region of the heliosphere extending radially outward from just outside 1 AU to the heliospheric termination shock.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Remote1AU"> <xsd:annotation> <xsd:documentation xml:lang="en">A roughly toroidal region that includes the Earth's orbit, but exclusive of the region near the Earth.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>		

	<pre> <xsd:annotation> <xsd:documentation xml:lang="en">The heliospheric region near the Earth which extends to and includes the area near the L1 and L2 Lagrange point.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Outer"> <xsd:annotation> <xsd:documentation xml:lang="en">The region of the heliosphere extending radially outward from just outside 1 AU to the heliospheric termination shock.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Remote1AU"> <xsd:annotation> <xsd:documentation xml:lang="en">A roughly toroidal region that includes the Earth&#39;s orbit, but exclusive of the region near the Earth.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumIntegral

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for values above a given threshold and over area or solid-angle range.		
Diagram	<pre> classDiagram class enumIntegral { <<restriction of xsd:string>> <<enumeration value="Area">> <<enumeration value="Bandwidth">> <<enumeration value="SolidAngle">> } </pre>		
Type	restriction of xsd:string		
Facets	enumeration	Area	Integration over the extent of a planar region, or of the surface of a solid.
	enumeration	Bandwidth	Integration over the width a frequency band.
	enumeration	SolidAngle	Integration over the angle in three-dimensional space that an object subtends at a point.
Source	<pre> <xsd:simpleType name="enumIntegral"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for values above a given threshold and over area or solid-angle range.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Area"> <xsd:annotation> <xsd:documentation xml:lang="en">Integration over the extent of a planar region, or of the surface of a solid.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Bandwidth"> <xsd:annotation> <xsd:documentation xml:lang="en">Integration over the width a frequency band.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="SolidAngle"> <xsd:annotation> <xsd:documentation xml:lang="en">Integration over the angle in three-dimensional space that an object subtends at a point.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>		
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd		

Simple Type enumIonosphere

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for ionospheric regions.		
Diagram	<pre> classDiagram class enumIonosphere { <<restriction of xsd:string>> } </pre>		

Type	restriction of xsd:string		
Facets	enumeration	DRegion	The layer of the ionosphere that exists approximately 50 to 95 km above the surface of the Earth. One of several layers in the ionosphere.
	enumeration	ERegion	A layer of ionised gas occurring at 90-150km above the ground. One of several layers in the ionosphere. Also called the The Kennelly-Heaviside layer.
	enumeration	FRegion	A layer that contains ionized gases at a height of around 150-800 km above sea level, placing it in the thermosphere. the F region has the highest concentration of free electrons and ions anywhere in the atmosphere. It may be thought of as comprising two layers, the F1-and F2-layers. One of several layers in the ionosphere. Also known as the Appleton layer.
	enumeration	Topside	The region at the upper most areas of the ionosphere.
Source	<pre> <xsd:simpleType name="enumIonosphere"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for ionospheric regions.</ xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="DRegion"> <xsd:annotation> <xsd:documentation xml:lang="en">The layer of the ionosphere that exists approximately 50 to 95 km above the surface of the Earth. One of several layers in the ionosphere.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="ERegion"> <xsd:annotation> <xsd:documentation xml:lang="en">A layer of ionised gas occurring at 90-150km above the ground. One of several layers in the ionosphere. Also called the The Kennelly-Heaviside layer.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="FRegion"> <xsd:annotation> <xsd:documentation xml:lang="en">A layer that contains ionized gases at a height of around 150-800 km above sea level, placing it in the thermosphere. the F region has the highest concentration of free electrons and ions anywhere in the atmosphere. It may be thought of as comprising two layers, the F1-and F2-layers. One of several layers in the ionosphere. Also known as the Appleton layer.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Topside"> <xsd:annotation> <xsd:documentation xml:lang="en">The region at the upper most areas of the ionosphere.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>		
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd		

Simple Type enumMagnetosphere

Namespace	http://www.spase-group.org/data/schema
Annotations	Identifiers for the region of space above the atmosphere or surface of the planet, and bounded by the magnetopause, that is under the direct influence of planets magnetic field.

Diagram	<pre> classDiagram enumMagnetosphere < -- xsd:string </pre>		
Type	restriction of xsd:string		
Facets	enumeration	Magnetotail	The region on the night side of the body where the magnetic field is stretched backwards by the force of the solar wind. For Earth, the magnetotail begins at a night-side radial distance of 10 Re ($X > -10Re$).
	enumeration	Main	The region of the magnetosphere where the magnetic field lines are closed, but does not include the gaseous region gravitationally bound to the body.
	enumeration	Polar	The region near the pole of a body. For a magnetosphere the polar region is the area where magnetic field lines are open and includes the auroral zone.
	enumeration	RadiationBelt	The region within a magnetosphere where high-energy particles could potentially be trapped in a magnetic field.
Source	<pre> <xsd:simpleType name="enumMagnetosphere"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the region of space above the atmosphere or surface of the planet, and bounded by the magnetopause, that is under the direct influence of planet's magnetic field.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Magnetotail"> <xsd:annotation> <xsd:documentation xml:lang="en">The region on the night side of the body where the magnetic field is stretched backwards by the force of the solar wind. For Earth, the magnetotail begins at a night-side radial distance of 10 Re ($X > -10Re$).</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Main"> <xsd:annotation> <xsd:documentation xml:lang="en">The region of the magnetosphere where the magnetic field lines are closed, but does not include the gaseous region gravitationally bound to the body.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Polar"> <xsd:annotation> <xsd:documentation xml:lang="en">The region near the pole of a body. For a magnetosphere the polar region is the area where magnetic field lines are open and includes the auroral zone.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="RadiationBelt"> <xsd:annotation> <xsd:documentation xml:lang="en">The region within a magnetosphere where high-energy particles could potentially be trapped in a magnetic field.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>		
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd		

Simple Type enumNearSurface

Namespace	http://www.spase-group.org/data/schema
Annotations	Identifiers for regions of the gaseous and possibly ionized environment of a body extending from the surface to some specified altitude.

Diagram	<pre> classDiagram enumNearSurface < -- xsd:string </pre>	
Type	restriction of xsd:string	
Facets	enumeration	Atmosphere The neutral gases surrounding a body that extends from the surface and is bound to the body by virtue of the gravitational attraction.
	enumeration	AuroralRegion The region in the atmospheric where electrically-charged particles bombarding the upper atmosphere of a planet in the presence of a magnetic field produce an optical phenomenon.
	enumeration	EquatorialRegion A region centered on the equator and limited in latitude by approximately 23 degrees north and south of the equator.
	enumeration	Ionosphere The charged or ionized gases surrounding a body that are nominally bound to the body by virtue of the gravitational attraction.
	enumeration	Ionosphere.DRegion The layer of the ionosphere that exists approximately 50 to 95 km above the surface of the Earth. One of several layers in the ionosphere.
	enumeration	Ionosphere.ERegion A layer of ionised gas occurring at 90-150km above the ground. One of several layers in the ionosphere. Also called the The Kennelly-Heaviside layer.
	enumeration	Ionosphere.FRegion A layer that contains ionized gases at a height of around 150-800 km above sea level, placing it in the thermosphere. the F region has the highest concentration of free electrons and ions anywhere in the atmosphere. It may be thought of as comprising two layers, the F1- and F2-layers. One of several layers in the ionosphere. Also known as the Appleton layer.
	enumeration	Ionosphere.Topside The region at the upper most areas of the ionosphere.
	enumeration	Mesosphere The layer of the atmosphere that extends from the Stratosphere to a range of 80 km to 85 km, temperature decreasing with height.
	enumeration	Plasmasphere A region of the magnetosphere consisting of low energy (cool) plasma. It is located above the ionosphere. The outer boundary of the plasmasphere is known as the plasmapause, which is defined by an order of magnitude drop in plasma density.
	enumeration	PolarCap The areas of the globe surrounding the poles and consisting of the region north of 60 degrees north latitude an the region south of 60 degrees south latitude.
	enumeration	SouthAtlanticAnomalyRegion The region where the Earths inner van Allen radiation belt makes its closest approach to the planets surface. The result is that, for a given altitude, the radiation intensity is higher over this region than elsewhere.
	enumeration	Stratosphere The layer of the atmosphere that extends from the troposphere to about 30 km, temperature increases with height. The stratosphere contains the ozone layer.
	enumeration	Thermosphere The layer of the atmosphere that extends from

		the Mesosphere to 640+ km, temperature increasing with height.	
	enumeration	Troposphere	
Source	<pre> <xsd:simpleType name="enumNearSurface"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for regions of the gaseous and possibly ionized environment of a body extending from the surface to some specified altitude.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Atmosphere"> <xsd:annotation> <xsd:documentation xml:lang="en">The neutral gases surrounding a body that extends from the surface and is bound to the body by virtue of the gravitational attraction.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="AuroralRegion"> <xsd:annotation> <xsd:documentation xml:lang="en">The region in the atmospheric where electrically-charged particles bombarding the upper atmosphere of a planet in the presence of a magnetic field produce an optical phenomenon.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="EquatorialRegion"> <xsd:annotation> <xsd:documentation xml:lang="en">A region centered on the equator and limited in latitude by approximately 23 degrees north and south of the equator.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Ionosphere"> <xsd:annotation> <xsd:documentation xml:lang="en">The charged or ionized gases surrounding a body that are nominally bound to the body by virtue of the gravitational attraction.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Ionosphere.DRegion"> <xsd:annotation> <xsd:documentation xml:lang="en">The layer of the ionosphere that exists approximately 50 to 95 km above the surface of the Earth. One of several layers in the ionosphere.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Ionosphere.ERegion"> <xsd:annotation> <xsd:documentation xml:lang="en">A layer of ionised gas occurring at 90-150km above the ground. One of several layers in the ionosphere. Also called the The Kennelly-Heaviside layer.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Ionosphere.FRegion"> <xsd:annotation> <xsd:documentation xml:lang="en">A layer that contains ionized gases at a height of around 150-800 km above sea level, placing it in the thermosphere. the F region has the highest concentration of free electrons and ions anywhere in the atmosphere. It may be thought of as comprising two layers, the F1-and F2-layers. One of several layers in the ionosphere. Also known as the Appleton layer.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Ionosphere.Topside"> <xsd:annotation> <xsd:documentation xml:lang="en">The region at the upper most areas of the ionosphere.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Mesosphere"></pre>	<p>The lowest layer of the atmosphere which begins at the surface and extends to between 7 km (4.4 mi) at the poles and 17 km (10.6 mi) at the equator, with some variation due to weather factors.</p>	

```

<xsd:annotation>
  <xsd:documentation xml:lang="en">The layer of the atmosphere that extends from
    the Stratosphere to a range of 80 km to 85
    km, temperature decreasing with height.</xsd:documentation>
</xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Plasmasphere">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">A region of the magnetosphere consisting of
      low energy (cool) plasma. It is located above
      the ionosphere. The outer boundary of the
      plasmasphere is known as the plasmapause,
      which is defined by an order of magnitude
      drop in plasma density.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="PolarCap">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">The areas of the globe surrounding the poles
      and consisting of the region north of 60 degrees
      north latitude and the region south of 60 degrees
      south latitude.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="SouthAtlanticAnomalyRegion">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">The region where the Earth's inner van Allen
      radiation belt makes its closest approach
      to the planet's surface. The result is that,
      for a given altitude, the radiation intensity
      is higher over this region than elsewhere.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Stratosphere">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">The layer of the atmosphere that extends from
      the troposphere to about 30 km, temperature
      increases with height. The stratosphere contains
      the ozone layer.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Thermosphere">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">The layer of the atmosphere that extends from
      the Mesosphere to 640+ km, temperature increasing
      with height.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
<xsd:enumeration value="Troposphere">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">The lowest layer of the atmosphere which begins
      at the surface and extends to between 7 km
      (4.4 mi) at the poles and 17 km (10.6 mi)
      at the equator, with some variation due to
      weather factors.</xsd:documentation>
  </xsd:annotation>
</xsd:enumeration>
</xsd:restriction>
</xsd:simpleType>

```

Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd
-----------------	---

Simple Type enumProjecn

		plane of the coordinate system.
	enumeration JK	A measure of the length of a position or measured vector projected into the j-k (typically Y-Z) plane of the coordinate system.
Source	<pre> <xsd:simpleType name="enumProjection"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers to projections into a coordinate system.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="IJ"> <xsd:annotation> <xsd:documentation xml:lang="en">A measure of the length of a position or measured vector projected into the i-j (typically X-Y) plane of the coordinate system.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="IK"> <xsd:annotation> <xsd:documentation xml:lang="en">A measure of the length of a position or measured vector projected into the i-k (typically X-Z) plane of the coordinate system.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="JK"> <xsd:annotation> <xsd:documentation xml:lang="en">A measure of the length of a position or measured vector projected into the j-k (typically Y-Z) plane of the coordinate system.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType></pre>	
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd	

Simple Type enumSun

Namespace	http://www.spase-group.org/data/schema
Annotations	Identifiers for regions of the star upon which our solar system is centered.
—	—

```

<xsd:annotation>
  <xsd:documentation xml:lang="en">Identifiers for regions of the star upon which
    our solar system is centered.</xsd:documentation>
</xsd:annotation>
<xsd:restriction base="xsd:string">
  <xsd:enumeration value="Chromosphere">
    <xsd:annotation>
      <xsd:documentation xml:lang="en">The region of the Sun's (or a star's) atmosphere
        above the temperature minimum and below the
        Transition Region. The solar chromosphere
        is approximately 400 km to 2100 km above the
        photosphere, and characterized by temperatures
        from 4500 - 28000 K.</xsd:documentation>
    </xsd:annotation>
  </xsd:enumeration>
  <xsd:enumeration value="Corona">
    <xsd:annotation>
      <xsd:documentation xml:lang="en">The outermost atmospheric region of the Sun
        or a star, characterized by ionization temperatures
        above 10^5 K. The solar corona starts at about
        2100 km above the photosphere; there is no
        generally defined upper limit.</xsd:documentation>
    </xsd:annotation>
  </xsd:enumeration>
  <xsd:enumeration value="Interior">
    <xsd:annotation>
      <xsd:documentation xml:lang="en">The region inside the body which is not visible
        from outside the body.</xsd:documentation>
    </xsd:annotation>
  </xsd:enumeration>
  <xsd:enumeration value="Photosphere">
    <xsd:annotation>
      <xsd:documentation xml:lang="en">The atmospheric layer of the Sun or a star
        from which continuum radiation, especially
        optical, is emitted to space. For the Sun,
        the photosphere is about 500 km thick.</xsd:documentation>
    </xsd:annotation>
  </xsd:enumeration>
  <xsd:enumeration value="TransitionRegion">
    <xsd:annotation>
      <xsd:documentation xml:lang="en">A very narrow (<100 km) layer between the
        chromosphere and the corona where the temperature
        rises abruptly from about 8000 to about 500,000
        K.</xsd:documentation>
    </xsd:annotation>
  </xsd:enumeration>
</xsd:restriction>
</xsd:simpleType>

```

Schema location file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd

Simple Type enumText

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for the encoding of sequences of characters.		
Diagram			
Type	restriction of xsd:string		
Facets	enumeration	ASCII	A sequence of characters that adheres to American Standard Code for Information Interchange (ASCII) which is an 7-bit character-coding scheme.
	enumeration	Unicode	Text in multi-byte Unicode format.
Source	<pre> <xsd:simpleType name="enumText"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for the encoding of sequences of characters.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="ASCII"> <xsd:annotation> <xsd:documentation xml:lang="en">A sequence of characters that adheres to American Standard Code for Information Interchange (ASCII) which is an 7-bit character-coding scheme.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>		

```

        </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="Unicode">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">Text in multi-byte Unicode format.</
xsd:documentation>
        </xsd:annotation>
    </xsd:enumeration>
</xsd:restriction>
</xsd:simpleType>

```

Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd
-----------------	---

Simple Type enumWaves

Namespace	http://www.spase-group.org/data/schema		
Annotations	Identifiers for experimental and natural wave phenomena.		
Diagram			
Type	restriction of xsd:string		
Facets	enumeration	Active	Exerting an influence or producing a change or effect. An active measurement is one which produces a transmission or excitation as a part of the measurement cycle.
	enumeration	Passive	Movement or effect produced by outside influence. A passive measurement is one which does not produce a transmission or excitation as a part of the measurement cycle.
Source	<pre> <xsd:simpleType name="enumWaves"> <xsd:annotation> <xsd:documentation xml:lang="en">Identifiers for experimental and natural wave phenomena.</xsd:documentation> </xsd:annotation> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Active"> <xsd:annotation> <xsd:documentation xml:lang="en">Exerting an influence or producing a change or effect. An active measurement is one which produces a transmission or excitation as a part of the measurement cycle.</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="Passive"> <xsd:annotation> <xsd:documentation xml:lang="en">Movement or effect produced by outside influence. A passive measurement is one which does not produce a transmission or excitation as a part of the measurement cycle.</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>		
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd		

Namespace: ""

Attributes

Attribute Spase / @lang

Namespace	No namespace
Type	xsd:string
Properties	default: en
Used by	Complex Type Spase
Source	<xsd:attribute name="lang" type="xsd:string" default="en"/>
Schema location	file:/var/www/spase/site/root/data/schema/spase-2_2_0.xsd