



Alexandru Calotoiu

DaFIEEx



C2DaCe challenges

- **Classes**
 - Inheritance
 - Contexts
- **Recursions**
 - Tail recursion
 - Indirect recursion
- **Pointers**
 - Unrestricted arithmetic
- **Stateful library calls**
 - Automatic assessment
- **Template programming**
- **Library nodes**
- **Encapsulation**

F2DaCe challenges

- **Generalized views**
- **Vector operations**
- **Labels & GoTo's**
- **Intrinsic function coverage**
- **Modern Fortran**

DaCe challenges

- **Application-level ToGPU transform**
 - + Associated transforms

Engineering efforts

Research efforts

Collaboration?

Application-level ToGPU transform

- **Schedule tree representation**
 - New IR
 - Allows for different transformation to happen efficiently
 - Work in Progress

```
map i in [0:N]: __tmp2[0:5, 0:5] = library MatMul[alpha=1, beta=0](A[i, 0:5, 0:5], B[i, 0:5, 0:5]) map __i0, __i1 in [0:5, 0:5]:  
__return[i, __i0, __i1] = tasklet(cst[0], __tmp2[__i0, __i1])
```

Other topics

- **Merging Fortran frontend**
 - (almost finished)
- **Snitch backend**
 - Development in progress
 - Basic C works
 - Snitch extensions not finished
- **Read the docs:**
 - <https://spcl.dace.readthedocs.io/en/latest/>




IR Lemmas

If there exists a bi-directional transformation with no loss of information between two representations, then any transformation that is possible in one, must be possible in the other

Corollary: if the engineering or runtime complexity of a transformation in one representation is larger than translating back and forth and applying the transformation in another representation, it should be done there.

Code example

```
@dace.program
def dace_azimint_naive(data: dace.float64[N], radius:
dace.float64[N]):
    rmax = np.amax(radius)
    res = np.zeros((npt, ), dtype=np.float64)
    for i in range(npt):
        r1 = rmax * i / npt
        r2 = rmax * (i + 1) / npt
        mask_r12 = np.logical_and((r1 <= radius), (radius < r2))
        on_values = 0
        tmp = np.float64(0)
        for j in dace.map[0:N]:
            if mask_r12[j]:
                tmp += data[j]
                on_values += 1
        res[i] = tmp / on_values
    return res
```



```
@dace.program
def dace_azimint_naive(data: dace.float64[N], radius:
dace.float64[N]):
    rmax = np.amax(radius)
    res = np.zeros((npt, ), dtype=np.float64)
    for i in range(npt):
        1 r1 = rmax * i / npt
        2 r2 = rmax * (i + 1) / npt
        3 mask_r12 = np.logical_and((r1 <= radius), (radius <
r2))

        4 on_values = 0
        5 tmp = np.float64(0)
        6 for j in dace.map[0:N]:
            if mask_r12[j]:
                tmp += data[j]
                on_values += 1
        res[i] = tmp / on_values
    return res
```

It is good for maps that have (a) the same range and (b) can pipe the output of one to the input of another to be together.

State Fusion and WCR Edge Representation

- Change Map representation
- Add input wcr-style edge
- Increase “fusibility”