
Python Basics Cheatsheet

1. Basic Calculation Operations

```
5 + 3    # 8
5 - 3    # 2
5 * 3    # 15
5 ** 3   # 125

5 / 3    # 1.66...
5 // 3   # 1
5 % 3    # 2
```

```
# Rounding
round(1.6667)    # 2
round(1.6667, 2) # 1.67
int(1.6667)      # 1
```

Math

(you cannot use math functions during exam)

```
import math
```

```
# Constants
math.pi    # 3.14159...
math.e      # 2.718...
```

```
# Power and Roots
math.sqrt(16)    # 4
math.pow(2, 3)   # 8
math.exp(1)      # e^1
math.log(10)     # log(10) base e
math.log(100, 10) # log(10) base 10
```

Trigonometric Functions

```
math.sin(math.pi / 2) # 1
math.cos(0)           # 1
math.tan(math.pi / 4) # 1
```

Inverse Trigonometric Functions

```
math.asin(1)    # pi/2
math.acos(1)    # 0
math.atan(1)    # pi/4
```

Rounding

```
math.floor(3.7) # 3
math.ceil(3.2)  # 4
```

3. Basic Type Conversions

```
int("42")      # String to int
float("3.14")   # String to float
str(42)        # Int to string
list("abcd")    # String to list
```

4. Lists

```
# Create a list
my_list = [3, 2, 1]

# Operations
item = my_list[2]    # 1 - element at index 2
my_list.append(3)    # [3, 2, 1, 3]
new_list = my_list + [5, 6] # [3, 2, 1, 3, 5, 6]
x = len(new_list)    # 6 - length of list
"Apple" in new_list  # False
```

```
# Looping 1
for item in my_list:
    print(item)
```

```
# Looping 2
for i in range(len(my_list)):
    item = my_list[i]
    print(item)
```

```
# Methods
new_list.sort()      # [1, 2, 3, 3, 5, 6]
new_list.insert(2, 10) # [1, 2, 10, 3, 3, 5, 6]
new_list.remove(3)    # [1, 2, 10, 3, 5, 6]
i = new_list.index(10) # 2 (↑ index of 10: 2)
```

```
# Slicing
lst = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
lst[2:5]    # [2, 3, 4] (from 2 to 4)
lst[:3]     # [0, 1, 2] (from start to 2)
lst[7:]     # [7, 8, 9] (from 7 to end)
lst[-3:]    # [7, 8, 9] (last 3)
lst[::-2]   # [0, 2, 4, 6, 8] (every 2nd)
lst[1:8:3]  # [1, 4, 7] (from 1 to 7 step 3)
lst[::-1]   # [9, 8, ...] (reverses list)
lst[8:2:-2] # [8, 6, 4] (from 8 to 3 step -2)
```

5. Strings

```
# Strings
my_str = "Hello, World!"

my_str.lower()    # Convert to lowercase
my_str.upper()    # Convert to uppercase
my_str.capitalize() # Only first char uppercase
my_str.lstrip()   # Remove leading whitespace
my_str.rstrip()   # Remove trailing whitespace
my_str.strip()    # Combined lstrip and rstrip
my_str.isalpha()  # all characters alphabetic?
my_str.isdigit()  # all characters digits?
my_str.islower()  # all characters lowercase?
my_str.isupper()  # all characters uppercase?
my_str.split(" ") # split string on spaces
```

```
# Looping through characters 1
for char in my_str:
    print(char)
```

```
# Looping through characters 2
for i in range(len(my_str)):
    char = my_str[i]
    print(char)
```

6. Reading files

```
# Open and read whole file
file = open("file.txt", "r")
content = file.read()
print(content)
file.close()
```

```
# Open and read line by line
file = open("file.txt", "r")
for line in file:
    print(line)
file.close()
```

```
# Alternative method: with open
with open("file.txt", "r") as file:
    for line in file:
        print(line)
```

Dictionaries, Sets and Classes

1. Dictionaries

```
# Create a dictionary: key -> value
ages = {"Ann": 28, "Bob": 24}
```

```
# Look up, add and change
ages["Ann"]          # 28
ages["Cem"] = 35      # add a new key
ages["Ann"] = 29      # change a value
ages["Dan"]          # KeyError!
ages.get("Dan", 0)    # 0 (default if missing)
"Bob" in ages         # True (checks keys)
len(ages)             # 3
del ages["Bob"]       # remove a key
ages.pop("Cem")       # remove, returns 35
```

```
# Looping 1: over the keys
for name in ages:
    print(name, ages[name])
```

```
# Looping 2: over key-value pairs
for name, age in ages.items():
    print(name, age)
```

```
list(ages.values())   # all values as a list
```

2. Sets

```
# Create a set: unique elements, no order
s = {3, 1, 4}
empty = set()          # not {}: that is a dict!
list(set(my_list))     # remove duplicates
```

```
# Operations
s.add(5)               # add (no duplicates)
s.remove(3)            # KeyError if missing
s.discard(9)           # no error if missing
4 in s                 # True
len(s)                 # 3
s[0]                   # TypeError: no index!
```

```
# Set operations
a = {1, 2, 3, 4}
b = {3, 4, 5}
a | b                  # {1, 2, 3, 4, 5} a.union(b)
a & b                  # {3, 4}          a.intersection(b)
a - b                  # {1, 2}          a.difference(b)
b.issubset(a)          # False
```

3. Tuples

```
# Create a tuple: like a list, but immutable
t = (42, "hello", 3.14)
t[1]                   # "hello"
len(t)                 # 3
t[1] = 9               # TypeError: immutable!
t.append(7)            # AttributeError!
tuple(my_list)         # list to tuple
```

```
# Unpacking
a, b, c = t             # a = 42, b = "hello", ...
a, b = t                # ValueError: too many
```

4. Classes

```
class MyClass:
    # Initializer: runs when creating an object
    def __init__(self, x):
        self.x = x

    # a method without parameters
    def method1(self):
        ...

    # a method with a parameters
    def method2(self, a):
        ...

    ...

r = MyClass(42)        # calls __init__ with x -> 42
r.method1()             # (method call)
r.method2("foo")        # (method call with parameter)
```

self is the object itself. A name starting with `_`, like `self._cards`, is private to the class.

5. Inheritance

```
class MyParentClass:
    def __init__(self, x):
        self.x = x
    ...

class MyChildClass(MyParentClass):
    def __init__(self, x):
        super().__init__(x)
    ...
```
