

# EE 3233 System Programming for Engineers - Summer 2025

## Exam 1


(Monday, June 16)

Name: \_\_\_\_\_

Score: \_\_\_\_\_/120

### I. Multiple Choice (Each 10 points)

1. Choose one, which is NOT a task performed by the kernel.
  - a. Memory management
  - b. Creation and termination of process
  - c. Compilation of program
  - d. Provision of a file system
2. Following figure shows the steps in the execution of a system call, `execve()`. In which step the actual `execve()` is executed?
  - a. (1)
  - b. (2)
  - c. (3)
  - d. (4)



3. Which statement about the `clearenv()` function is true?
  - a. It retrieves the value of all environment variables.
  - b. It adds a new environment variable.
  - c. It removes a specific environment variable.
  - d. It erases all environment variables.

4. Choose an INCORRECT statement about the memory layout.
- a. 'Text' segment contains machine-language instructions of the program
  - b. 'Data' segment contains global and static variables
  - c. 'Stack' segment dynamically grows and shrinks
  - d. 'Heap' segment is used to allocate memory at compile time

II. Choose [T] for True or [F] for False [F] (Each 5 points)

1. When running in Kernel MODE, a CPU can access memory that is marked as userspace. [T] [F]
2. A **process** is an instance of an executed program. [T] [F]
3. Two **processes** typically use the same memory space? [T] [F]
4. A function contains more than one stack frame? [T] [F]
5. The advantage of separating the virtual address space from the physical address space is isolating processes from one another to prevent one process from accessing the memory of another process. [T] [F]
6. ***void free(void \*ptr)*** deallocates the block of memory pointed to by ***ptr*** and adds the block of memory to a list of free blocks for re-use. [T] [F]
7. When ***malloc()*** allocates the block, it allocates extra bytes to hold the size of the block [T] [F]
8. The expected output when you run the following **Python** script is [(2,3), 'xy'].

```
>>> t=[3,4.1,(2,3),'xy']
>>> print(t[2:])
```

[T] [F]

III. Fill in the blank(s) in each statement.

1. Each time a function calls another function, stack frame or activation record is pushed onto the stack. This entry contains ( ) to go back to its caller, and ( ) and ( ) – 10 points
2. On x86\_64 the stack grows in a ( ) direction and the heap grows in a ( ) direction – 10 points