


JSTL Core Tag - `<forEach>`



JSP Standard Tag Library (JSTL)

Core

**Messages
Formatting
I18N**

Functions

XML

SQL

Core Tags

Tag Summary	
<u>catch</u>	Catches any Throwable that occurs in its body and optionally exposes it.
<u>choose</u>	Simple conditional tag that establishes a context for mutually exclusive conditional operations, marked by <when> and <otherwise>
<u>if</u>	Simple conditional tag, which evalutes its body if the supplied condition is true and optionally exposes a Boolean scripting variable representing the evaluation of this condition
<u>import</u>	Retrieves an absolute or relative URL and exposes its contents to either the page, a String in 'var', or a Reader in 'varReader'.
<u>forEach</u>	The basic iteration tag, accepting many different collection types and supporting subsetting and other functionality
<u>forTokens</u>	Iterates over tokens, separated by the supplied delimiters
<u>out</u>	Like <%= ... >, but for expressions.
<u>otherwise</u>	Subtag of <choose> that follows <when> tags and runs only if all of the prior conditions evaluated to 'false'
<u>param</u>	Adds a parameter to a containing 'import' tag's URL.
<u>redirect</u>	Redirects to a new URL.
<u>remove</u>	Removes a scoped variable (from a particular scope, if specified).
<u>set</u>	Sets the result of an expression evaluation in a 'scope'
<u>url</u>	Creates a URL with optional query parameters.
<u>when</u>	Subtag of <choose> that includes its body if its condition evalutes to 'true'

JSP Core Taglib Reference

- Every page that uses the Core tags must include this reference:

```
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>
```


<%

// just create some sample data ... normally provided by MVC

String[] cities = {"Mumbai", "Singapore", "Philadelphia"};

pageContext.setAttribute("myCities", cities);

%>

<body>

<c:forEach var="tempCity" items="\${myCities}">

 \${tempCity}

</c:forEach>

</body>

Mumbai
Singapore
Philadelphia

<%

// just create some sample data ... normally provided by MVC

String[] cities = {"Mumbai", "Singapore", "Philadelphia"};

pageContext.setAttribute("myCities", cities);

%>

<body>

<c:forEach var="tempCity" items="\${myCities}">

 \${tempCity}

</c:forEach>

</body>

Resources

Name	Website
JSP Custom Tags Tutorial	<u>www.luv2code.com/tag-tutorial</u>
JSTL Tutorial	<u>www.luv2code.com/jstl-tutorial</u>
JSTL JavaDoc	<u>www.luv2code.com/jstl-javadoc</u>
JSTL Specification PDF	<u>www.luv2code.com/jstl-pdf</u>

JSTL Core Tag - `<forEach>`

