System Verification and Validation Plan for Software Engineering

Team 13, Speech Buddies
Mazen Youssef
Rawan Mahdi
Luna Aljammal
Kelvin Yu

April 5, 2026

Revision History

Date	Version	Notes
Oct 26, 2025	1.0	Added Section 3
Oct 27, 2025	1.0	Added Sections 1,2, and 4.1
Oct 27, 2025	1.0	Added Sections 4.2, 4.3, and 4.4
Dec 20, 2025	1.1	Implemented TA feedback
Dec 25, 2025	1.2	Implemented Peer feedback in Sections 2.2 and 2.3
Apr 5, 2026	2.0	Added FR6, updated symbols table, corrected stretch-goal status for test-PF-3, fixed traceability table

Contents

1 Symbols, Abbreviations, and Acronyms **1**

2 General Information **2**
- 2.1 Summary . . . 2
- 2.2 Objectives . . . 2
- 2.3 Objectives . . . 2
- 2.4 Challenge Level . . . 3
- 2.5 Relevant Documentation . . . 3

3 Plan **4**
- 3.1 Verification and Validation Team . . . 4
- 3.2 SRS Verification . . . 4
- 3.3 Design Verification . . . 6
- 3.4 Verification and Validation Plan Verification . . . 7
- 3.5 Implementation Verification . . . 8
- 3.6 Automated Testing and Verification Tools . . . 9
- 3.7 Software Validation . . . 10

4 System Tests **10**
- 4.1 Tests for Functional Requirements . . . 11
  - 4.1.1 Tests for FR1 — Accept Speech Audio via Microphone 11
  - 4.1.2 Tests for FR2 — Convert Impaired Speech to Text at ≥80% Accuracy . . . 12
  - 4.1.3 FR3 — Display Transcription for Verification . . . 13
  - 4.1.4 FR4 — Map Text to Arbitrary Device Commands . . . 14
  - 4.1.5 FR5 — Execute Commands on the Host Device . . . 15
  - 4.1.6 FR6 — Handle Security Software Interference . . . 16
- 4.2 Tests for Nonfunctional Requirements . . . 17
  - 4.2.1 Look & Feel . . . 17
  - 4.2.2 Usability & Humanity . . . 18
  - 4.2.3 Performance . . . 20
  - 4.2.4 Operational & Environmental . . . 22
  - 4.2.5 Maintainability & Support . . . 23
  - 4.2.6 Security . . . 24
  - 4.2.7 Cultural . . . 26
  - 4.2.8 Compliance . . . 26

4.3 Traceability Between Test Cases and Requirements 27

5 Unit Test Description **29**
5.1 Unit Testing Scope 29
5.2 Tests for Functional Requirements 30
5.2.1 Module M4: Speech-to-Text Engine 30
5.2.2 Module M5: Command Orchestrator 32
5.2.3 Module M7: Browser Orchestrator 34
5.2.4 Module M8: Session Manager 35
5.2.5 Module M15: Real-time Audio Capture 36
5.2.6 Module M20: Feedback Module 38
5.3 Traceability Between Unit Tests and Modules 40
5.4 Traceability Between Unit Tests and Modules 41

List of Tables

1 SRS Verification Checklist 6
2 Design Verification Checklist 7
3 V&V Plan Verification Checklist 8
4 Automated Testing and Verification Tools 9
5 Traceability Between Unit Tests and MIS Modules 41
6 Traceability Between Unit Tests and MIS Modules 42

1 Symbols, Abbreviations, and Acronyms

Symbol / Acronym	Description
T	Test
ASR	Automatic Speech Recognition
UI	User Interface
NFR	Non-Functional Requirement
FR	Functional Requirement
WER	Word Error Rate
SNR	Signal-to-Noise Ratio
WCAG	Web Content Accessibility Guidelines
LoRA	Low-Rank Adaptation
OOD	Out-of-Domain: input or data that falls outside the system's trained or expected domain.
V&V	Verification and Validation: processes to ensure a system meets requirements and fulfills its intended purpose.

2 General Information

2.1 Summary

The V&V (Verification and Validation) plan described in this document applies to the VoiceBridge application. VoiceBridge is an accessibility tool that is built around speech-to-text, designed for individuals with impaired or atypical speech caused by neurological or motor speech disorders. Using a customizable model, it converts slurred or non-standard speech into accurate text and control commands on standard consumer devices. The system integrates seamlessly with commonly used technology, including web browsers, enabling open-ended, customizable control for tasks such as online shopping, browsing, and digital communication. By allowing users to operate everyday applications with their own speech patterns, the product promotes greater autonomy, accessibility, and independence.

2.2 Objectives

2.3 Objectives

The primary objective of VoiceBridge is to accurately capture and interpret the intended meaning of speech from users with impaired or atypical articulation, ensuring that spoken input is reliably translated into correct text or device actions. From a verification and validation (V&V) perspective, this objective is met only if the system's key qualities, including accuracy, safety, reliability, and usability, can be objectively measured and confirmed through testing.

To support this objective, the V&V plan will define clear test procedures and measurable success criteria to validate the system's ability to transcribe impaired speech with acceptable accuracy, correctly map recognized text to intended commands, and prevent unsafe or unintended actions through confirmation and safeguard mechanisms. Transcription accuracy will be evaluated using controlled speech datasets, while command execution will be validated through scenario-based tests under both normal and error-prone conditions.

A critical focus of validation is the safe mapping of user intent when controlling web browsers and other general-purpose software, where unintended actions could have significant consequences. Because VoiceBridge relies on

non-deterministic AI models, the V&V activities will assess whether validation layers, confirmation prompts, and fallback behaviors reduce misinterpretation and unsafe execution.

Usability and accessibility are also treated as verifiable objectives. The system must demonstrate that users can complete core tasks with minimal effort on standard consumer hardware and receive clear feedback during both successful and failed interactions. The goal of empowering users with meaningful autonomy is validated by showing that users can reliably and safely achieve intended outcomes using VoiceBridge without external assistance.

2.4 Challenge Level

In addition to baseline verification and validation activities, limited challenge-level evaluations may be performed to further assess system robustness. These may include performance testing under increased background noise, basic accessibility checks using assistive tools, and exploratory evaluation of safeguard behavior under ambiguous or low-confidence inputs.

These challenge-level activities are optional and intended to provide additional insight into system behavior beyond baseline validation.

2.5 Relevant Documentation

Below is a list of documents that can be referenced for further information, as well as short descriptions highlighting their relevance to V&V

- Problem Statement & Goals: This document summarizes the core objectives of VoiceBridge and the problem it aims to address. These initial goals lay the foundation for the subsequent requirements that the V&V aims to ensure.

- Software Requirements Specification: This document goes into depth about the project specifications (user identification, business cases) as well as the functional and non-functional requirements that the V&V validates through the outlined testing plan.

- Design Document (To be written): This document will summarize the core modules of VoiceBridge, highlighting the components that needed to be directly and indirectly tested, as defined in the V&V.

3 Plan

This section describes how the VoiceBridge team will verify and validate the system throughout its lifecycle. It outlines responsibilities, reviews, and testing activities that ensure each stage, from the SRS to it's implementation. The plan emphasizes practical verification aligned with our project scope.

3.1 Verification and Validation Team

- **Kelvin Yu:** Lead Tester. Coordinates overall V&V activities and integration testing across the ASR, intent mapping, and browser components.
- **Mazen Youssef:** Functional Tester. Verifies core functional requirements (FR1–FR6) including audio capture, transcription, command execution, and security software interference handling.
- **Rawan Mahdi:** UI and Usability Tester. Tests the front-end interface for accessibility, feedback clarity, and overall user experience.
- **Luna Aljammal:** Non-Functional Tester. Assesses performance, latency, and privacy compliance; maintains testing documentation and traceability.
- **Dr. Christian Brodbeck (Supervisor):** Oversees the V&V process, providing feedback on testing and alignment with project goals.

3.2 SRS Verification

3.2.1 Requirements Validation

Each functional and non-functional requirement will be verified for clarity, feasibility, and measurability. A formal SRS Review Checklist will be applied to Sections 10–16 of the SRS document, focusing on fit criteria, ambiguity, and traceability. Automated verification will be performed for measurable criteria (e.g., transcription latency, confidence scores) using `PyTest`, while manual validation will confirm qualitative attributes such as user feedback clarity.

3.2.2 Supervisor Review

A structured review session will be held with Dr. Christian Brodbeck. The meeting will consist of:

1. A concise summary of all functional and safety-related requirements.
2. System and use case diagrams for visual reference.
3. Specific discussion prompts on potentially ambiguous or high-risk requirements.

During the meeting, we will assess correctness, feasibility, and alignment with user needs. All comments will be logged as GitHub issues and tracked under the *SRS Verification* label for resolution.

3.2.3 Prototype-Based Validation

A low-fidelity prototype of VoiceBridge's transcription interface and feedback module will be used to validate usability-related requirements (e.g., accessibility of controls, clarity of feedback, and response timing). Test participants will perform scripted scenarios derived from core functional requirements, such as initiating live transcription, adjusting speech sensitivity, and reviewing transcript accuracy.Results will be compared against defined success metrics (e.g., *task completion within 5 seconds* or *90% accuracy threshold*).

3.2.4 Continuous Verification

To ensure ongoing alignment between the SRS and the evolving design, biweekly verification reviews will be conducted. These sessions will:

- Assess the impact of requirement modifications.
- Re-verify modified requirements using the checklist to confirm consistency and completeness.

Table 1: SRS Verification Checklist

Criteria	**Verification Activities**
Requirements Validation	☐ Apply checklist to all SRS sections ☐ Execute automated + manual verifications
Supervisor Review	☐ Prepare and distribute review materials ☐ Conduct formal walkthrough ☐ Record findings as GitHub issues
Prototype-Based Validation	☐ Develop interactive prototype ☐ Run scenario-based usability tests ☐ Compare results against success metrics
Continuous Verification	☐ Hold biweekly review meetings ☐ Update documentation and traceability records ☐ Re-inspect modified requirements

3.3 Design Verification

Design verification (including MIS and MG documents) confirms that the VoiceBridge architecture and modules meet all verified requirements from the SRS. Planned Verification Activities:

- Design Review Meeting:
  Conduct a structured walkthrough of the Module Interface Specification with Dr. Brodbeck. Each module will be checked against SRS FR1–FR6 and non-functional requirements. Findings will be documented and tracked in GitHub under *Design Verification*.

- Checklist Inspection:
  Verify that data flows align with the SRS Data Dictionary and that control logic matches the Business Use Cases. Confirm consistency in naming, data handling, and error management.

- Interface Validation:
  Use UI mock-ups to confirm compliance with Accessibility and Safety-Critical requirements. Validate color contrast, keyboard navigation, and error feedback clarity.

Table 2: Design Verification Checklist

Criteria	Verification Activities
Design Review	☐ Cross-check each module with SRS requirements ☐ Log findings in GitHub
Checklist Inspection	☐ Validate data flows and logic consistency ☐ Check naming and error handling
Interface Validation	☐ Review mock-ups for accessibility and safety compliance

3.4 Verification and Validation Plan Verification

The Verification and Validation (V&V) Plan will undergo its own verification process to ensure that it is accurate, complete, and consistent with project standards. Planned Verification Activities:

- Peer Inspection:
  All team members will review the plan using a standardized checklist to evaluate completeness of scope, requirement traceability, and feasibility of proposed activities.

- Supervisor Approval:
  The finalized document will be submitted to Dr. Brodbeck for formal review. Feedback will confirm that verification procedures align with course and project expectations.

- Issue Logging and Revision Tracking:
  Any missing information, inconsistencies, or suggested improvements will be logged as GitHub issues. Updates will be reviewed and approved before submission.

Table 3: V&V Plan Verification Checklist

Criteria	Verification Activities
Peer Inspection	☐ Verify traceability and feasibility ☐ Review plan scope, objectives, and completeness
Supervisor Approval	☐ Submit plan for instructor feedback ☐ Incorporate required revisions
Issue Logging and Tracking	☐ Record suggested updates in GitHub ☐ Confirm all revisions are reviewed and approved

3.5 Implementation Verification

Implementation verification ensures that VoiceBridge's source code correctly implements the approved design and satisfies all verified requirements. Planned Verification Activities:

- Unit and Integration Testing:
  Automated tests will verify core functional requirements (SRS §10, FR1–FR6), covering audio input, speech-to-text, intent mapping, command execution, and security software interference handling. End-to-end PUC flows (SRS §8.2) will be validated through CI pipelines with coverage tracking.

- Static Analysis and Peer Review:
  Code reviews will check compliance with maintainability and security requirements (SRS §15–16) and confirm mitigation of hazards listed in the Hazard Analysis (e.g., IR1, IMR1–IMR3). Issues will be tracked on GitHub for traceability.

- Automated Code Quality Tools:
  PEP 8 and ESLint will enforce code quality and consistency, supporting maintainability goals (SRS §15.1).

Criteria	Verification Activities
Unit & Integration Testing	☐ Track coverage and test results ☐ Develop automated test suites for all modules
Static Analysis & Peer Review	☐ Conduct code inspections ☐ Log and resolve defects in GitHub
Code Quality Tools	☐ Enforce style rules with PEP 8 and ESLint ☐ Verify consistent formatting and documentation

3.6 Automated Testing and Verification Tools

To support consistent and repeatable verification, the following tools will be used.

Table 4: Automated Testing and Verification Tools

Tool	Purpose
PyTest / unittest	Automated unit tests for ASR and intent mapping modules (Python).
GitHub Actions	Continuous integration pipeline executing test suites on each commit.
ESLint / Prettier	Enforces style and code quality standards for JavaScript/TypeScript.
pytest-cov / Codecov	Collects and reports test coverage metrics; uploads reports per build.
WAVE / axe Accessibility Scanner	Evaluates UI compliance with WCAG 2.1 AA.
Static Code Review (Peer Review)	Manual inspection of code by team members before merging; ensures readability, maintainability, and adherence to design standards.
Document Review Meetings	Scheduled reviews for major deliverables (SRS, V&V Plan, Hazard Analysis, etc.) by all team members to verify completeness and traceability.

Coverage and Linting Summary

- `pytest-cov` will generate line and branch coverage reports.
- Coverage summaries will appear on pull requests and weekly trend reports in the repository.
- Linters (`ruff`, `eslint`, and `prettier`) will ensure consistent style and catch syntax or accessibility issues before merging.

3.7 Software Validation

Validation confirms that VoiceBridge meets user needs and operates as intended in real-world conditions. Approaches:

- Stakeholder Feedback and Demo Validation:
  Rev 0 and Rev 1 demos will be used to validate against user personas and supervisor expectations.
- User Testing:
  Collect feedback from two target users performing three core tasks (speak command, observe transcription, confirm command) with success metrics on accuracy and ease of use.
- Functional Testing:
  Validate VoiceBridge's performance and behavior against comparable open-source Python speech-processing projects to confirm functional correctness.
- Code and Documentation Review Validation:
  Include scheduled reviews of code quality, module-level documentation, and user guides to ensure consistency with standards and maintainability expectations.

4 System Tests

This section defines the system-level tests for *VoiceBridge*. It follows the course template: each heading includes connective text, and each test case includes the control/type, initial state, inputs/conditions, expected outputs/results,

a brief test-case derivation (where applicable), and how the test will be performed. The functional tests map directly to SRS Functional Requirements (FR1–FR5). The nonfunctional tests map to SRS Nonfunctional Requirements (LFR, UHR, PRF, OER, MSR, SCR, CLR, CPR). A traceability table linking tests to requirements is provided at the end of this section.

4.1 Tests for Functional Requirements

The subsections below outline tests corresponding to the SRS Functional Requirements (FR1–FR6). Each test has a unique ID and clear execution steps.

4.1.1 Tests for FR1 — Accept Speech Audio via Microphone

Goal: Verify live microphone capture across platforms at ≥16 kHz.

1. test-FR1-MIC-1
   Control: Manual

   Initial State: App installed; permissions not yet granted.

   Input: Speak a short phrase (*"Testing one two three"*) into the default OS microphone on a Windows laptop.

   Output: App requests microphone permission; once granted, waveform/level indicator appears and raw audio frames are buffered at ≥16 kHz.

   How test will be performed: Launch app → start capture → verify UI level meter moves; export a short recording and inspect metadata (sample rate ≥16 kHz).

1. test-FR1-MIC-2
   Control: Manual

   Initial State: App freshly installed on iOS and Android.

   Input: First-time launch and attempt to record.

   Output: OS permission prompt shown; after approval, capture begins; denial shows friendly error and retry path.

   How test will be performed: Deny once (expect error + guidance), then allow (expect capture + levels).

1. test-FR1-MIC-3
   Control: Manual

   Initial State: Multiple audio devices present (laptop microphone + USB microphone).

   Input: Unplug/plug devices while capturing.

   Output: The system selects the current default audio input device. If the device disconnects, it automatically falls back to another available microphone and notifies the user. If it cannot find any, it shows an error.

   How test will be performed: Start capture → unplug active microphone → observe fallback notice → confirm continued capture.

4.1.2 Tests for FR2 — Convert Impaired Speech to Text at ≥80% Accuracy

test-FR2-ASR-1 Dataset Evaluation vs Baseline

1. test-FR2-ASR-1
   Control: Automated (batch evaluation)

   Initial State: Curated impaired-speech test set with references; chosen baseline model.

   Input: Run system and baseline over full test set.

   Output: System achieves ≥80% WER reduction vs baseline **or** meets defined WER delta per SRS; report includes per-speaker metrics.

   Test Case Derivation: Directly tests Fit Criterion's WER reduction expectation.

   How test will be performed: Evaluation script computes WER, CER; export CSV; assert threshold met.

test-FR2-ASR-2 Common Command Recognition (Acceptance Threshold)

1. test-FR2-ASR-2
   Control: Automated (scripted playback)

   Initial State: Command list of 50+ common intents; audio variants (different speakers/noise).

Input: Play each command sample to the system.

Output: System produces an acceptable transcription for each command (exact or accepted synonyms); overall acceptance threshold ≥80% on the command set.

Test Case Derivation: Meets "≥80% accuracy for common commands."

How test will be performed: Align decoded text with ground truth (string/intent match); assert ≥80% pass rate.

4.1.3 FR3 — Display Transcription for Verification

test-FR3-UI-1 Real-Time Display Latency

1. test-FR3-UI-1
   Control: Automated (instrumented)

   Initial State: Logging timestamps at (a) audio frame arrival, (b) first token shown.

   Input: 100 short utterances across platforms.

   Output: Time-to-first-text ≤2 s in ≥95% of trials.

   Test Case Derivation: Direct Fit Criterion.

   How test will be performed: Run scripted playback or live reads with a timer, store successful and unsuccessful trials and calculate percentage.

test-FR3-UI-2 Continuous Update & Finalization

1. test-FR3-UI-2
   Control: Manual

   Initial State: Streaming UI enabled.

   Input: Speak a 10–15 s sentence; include pauses and restarts.

   Output: UI shows incremental textas it is transcribed; final text locks with a small visual cue; no flickering or text loss occurs.

   Test Case Derivation: Ensures transparency/trust via visible updates (FR3).

   How test will be performed: Observe display during input; record the session on video; verify that the text updates smoothly and that the finalization cue appears.

4.1.4 FR4 — Map Text to Arbitrary Device Commands

test-FR4-MAP-1 Canonical Command Set Accuracy

1. test-FR4-MAP-1
   Control: Automated

   Initial State: 50 predefined commands with canonical phrasings and expected command representations (API/CLI/accessibility).

   Input: Exact text phrases.

   Output: ≥90% correct mapping to the expected command representation.

   Test Case Derivation: Direct Fit Criterion.

   How test will be performed: Feed text into intent mapper; compare output to expected representations for accuracy.

test-FR4-MAP-2 Paraphrase & Synonym Robustness

1. test-FR4-MAP-2
   Control: Automated

   Initial State: Same 50 intents with 2–3 paraphrases each.

   Input: Paraphrased commands (e.g., "launch mail app" for "open email").

   Output: Maintains ≥90% accuracy across the combined set or recorded separately for robustness.

   Test Case Derivation: Realistic language coverage (FR4 rationale).

   How test will be performed: Evaluate precision/recall across the set and calculate percentage.

test-FR4-MAP-3 Ambiguity & Disambiguation

1. test-FR4-MAP-3
   Control: Manual

   Initial State: Commands with ambiguous target ("open Amazon" vs "open Amazon.ca").

   Input: Ambiguous phrasing.

Output: System asks a brief clarifying question before mapping; no unsafe default.

Test Case Derivation: Safe mapping for independence without surprises (FR4).

How test will be performed: Provide ambiguous text; verify clarification prompt and final mapping.

test-FR4-MAP-4 Out-of-Domain Commands

1. test-FR4-MAP-4
   Control: Manual

   Initial State: Intent catalog fixed; user requests unsupported app/action.

   Input: "Turn on bedroom lights" (if smart-home unsupported).

   Output: Clear feedback: unsupported command + suggestion (link/alternative).

   Test Case Derivation: Graceful handling of arbitrary requests (FR4).

   How test will be performed: Issue out-of-domain (OOD) text; verify messaging and no execution.

4.1.5 FR5 — Execute Commands on the Host Device

test-FR5-EXEC-1 End-to-End Execution Latency & Reliability

1. test-FR5-EXEC-1
   Control: Automated (instrumented E2E)

   Initial State: Known-good mappings for a 50-command set.

   Input: Trigger each command (text or speech $\rightarrow$ text).

   Output: Visible system action completes with an overall success rate of $\geq$90% across the command set.

   Test Case Derivation: Direct Fit Criterion.

   How test will be performed: Timestamp intent and effect (e.g., window focus/app open), calculate success rate over the 50-command set.

test-FR5-EXEC-2 Accessibility/API Fallback Paths

1. test-FR5-EXEC-2
   Control: Manual/Automated

   Initial State: Primary API disabled (simulate outage).

   Input: Execute commands that have both accessibility and API paths.

   Output: System selects fallback path, still within target latency where feasible, or reports partial degradation.

   Test Case Derivation: Ensures robust execution loop (FR5 rationale).

   How test will be performed: Toggle feature flags/mocks; verify fallback invocation.

test-FR5-EXEC-3 Safety & Confirmation for Destructive Actions

1. test-FR5-EXEC-3
   Control: Manual

   Initial State: Commands include potentially destructive actions (e.g., "delete email").

   Input: Issue destructive command.

   Output: Confirmation prompt appears; execution only after explicit confirmation.

   Test Case Derivation: Safe device control (FR5).

   How test will be performed: Attempt action, • verify prompt appears and execution is blocked if canceled.

4.1.6 FR6 — Handle Security Software Interference

Goal: Verify that the system detects when browser, operating system, or antivirus security controls block or restrict automated actions and provides clear feedback to the user, including the affected command and available fallback options.

No dedicated test cases are defined for FR6 in this plan. FR6 behavior is evaluated through scenario-based testing conducted during the FR5 execution tests (test-FR5-EXEC-1 through test-FR5-EXEC-3). Any blocking events observed during those tests are recorded and their feedback quality

assessed. This approach is documented here to preserve traceability between the V&V Plan and the V&V Report.

4.2 Tests for Nonfunctional Requirements

This section covers system tests for the Non-Functional Requirements (NFR) in the SRS. Each test ties back to one or more NFRs (see "Covers" field). NFRs not explicitly tested here are covered by functional or unit tests and are referenced in the traceability matrix.

4.2.1 Look & Feel

Note: The tests in this subsection (test-LF-1 and test-LF-2) were not conducted during the current project cycle and are deferred to future work. Usability and visual design were partially assessed through the user testing sessions documented in the Usability & Humanity subsection.

test-LF-1 UI Browser Overlay Coverage

1. test-LF-1
   Type: Non-Functional, Manual, Survey-based

   Test Case Derivation: LFR-11.1

   Initial State: VoiceBridge extension/app active on common pages (docs, dashboards, news).

   Input/Condition: Idle state; listening state; confirmation state.

   Output/Result: Browser is full visible, browser is fully visible with indication that in listening state, interface confirms action and user confirms.

   How test will be performed: Usability survey is performed with users indicating how well they were able to see the content while running the interface on a scale from 1-5 with 5 being the clearest. Manual spot-checks confirm no critical content is masked.

test-LF-2 Visual Consistency & Minimalism Heuristic Review

1. test-LF-2
   Type: Heuristic Inspection (Design QA)

Test Case Derivation: LFR-11.1, LFR-11.2

Initial State: Latest build with UI design with spacing/typography/colors.

Input/Condition: Inspect primary screens & dialogs.

Output/Result: Checklist rating and noting consistent spacing scale, typography hierarchy, color roles, icon style.

How test will be performed: 10-item checklist scored by two reviewers done at separate times to prevent bias, ratings are review and consolidated to make necessary fixes.

4.2.2 Usability & Humanity

test-UH-1 Core Task Ease of Use

1. test-UH-1
   Type: User Testing, Instrumented

   Test Case Derivation: UHR-12.1

   Initial State: Tasks prepared (speak command, observe transcription, confirm command).

   Input/Condition: $n = 2$ participants (target users).

   Output/Result: Both participants complete each task in ≤ 4 interactions; success feedback observed within 1s of action.

   How test will be performed: Users interact with the interface through their browser and go through the prepared tasks, observers verify timing/task success rate/feedback time.

test-UH-2 Onboarding Learnability & First-Try Success

1. test-UH-2
   Type: User Testing + Survey

   Test Case Derivation: UHR-12.3

   Initial State: Fresh profile; no dedicated onboarding tutorial. The UI provides instructional cues via labelled controls, status messages, and contextual prompts.

Input/Condition: Participants ($n = 2$) are given only a general description of VoiceBridge's purpose and then complete the full core interaction sequence without any further guidance.

Output/Result: $\geq 85\%$ complete all core tasks on first attempt; onboarding time ≤ 10 minutes on average.

How test will be performed: Time-on-task success percentage, rating documentation out of 5 with feedback on what they liked/disliked.

test-UH-3 Personalization Ability

1. test-UH-3
   Type: Manual, Dynamic

   Test Case Derivation: UHR-12.2

   Initial State: User has a defined preference profile (language, mic, confirmation style).

   Input/Condition: Switch browser profile, sign-out/in.

   Output/Result: Personalized interaction remains consistent and predictable after re-authentication (no unexpected resets; confirmation style/language match the user's expected configuration).

   How test will be performed: Configure preferences $\rightarrow$ log out $\rightarrow$ log in elsewhere $\rightarrow$ confirm the system's interaction style matches expectations and loads without confusing changes or delays.

test-UH-4 Message Clarity & Politeness

1. test-UH-4
   Type: Survey-Based Language Review

   Test Case Derivation: UHR-12.4

   Initial State: Library of 8 representative system messages covering the full range of interaction states (listening, confirmation, error, clarification).

   Input/Condition: $n = 2$ participants rate each message on two separate 1–5 Likert scales: clarity (1 = very unclear, 5 = very clear) and tone (1 = impolite or unhelpful, 5 = appropriate and supportive).

Output/Result: $\geq 90\%$ of clarity ratings $\geq 4/5$; $\geq 90\%$ of tone ratings $\geq 4/5$; comments reviewed.

How test will be performed: Run a survey with $n = 2$ participants rating 8 system messages out of 5 on both clarity and tone scales, with an option to leave specific feedback at the end of the survey.

test-UH-5 Assistive Navigation

1. test-UH-5
   Type: Manual Keyboard Testing

   Test Case Derivation: UHR-12.5

   Initial State: Keyboard navigation enabled; all currently accessible interactive elements available (light/dark mode toggle, visible confirmation toggle).

   Input/Condition: Navigate all present interactive elements via keyboard (Tab to reach, Enter/Space to activate); confirm visual focus is clearly indicated throughout.

   Output/Result: All interactive elements reachable and operable via keyboard; visual focus indicator present on all elements.

   How test will be performed: Perform keyboard-only navigation following WCAG keyboard accessibility principles; verify each element is reachable via Tab and activatable with Enter or Space. No automated accessibility audit is required for the current scope.

4.2.3 Performance

test-PF-1 ASR Latency Benchmark

1. test-PF-1
   Type: Automated, Dynamic

   Test Case Derivation: PRF-13.1

   Initial State: ASR service with a ready test audio set that is from various speakers.

   Input/Condition: Feed audio with marked end-of-speech.

   Output/Result: latency ≤ 5 s from end-of-speech to transcript availability.

How test will be performed: Measure timestamps from End of Audio to getting transcript, repeat over 20 different audio samples and calculate average latency.

test-PF-2 Command Pipeline Latency

1. test-PF-2
   Type: Automated, Dynamic

   Test Case Derivation: PRF-13.2

   Initial State: Full app pipeline (NLP $\rightarrow$ action planning $\rightarrow$ execution).

   Input/Condition: Standard command set (e.g., "summarize page", "reply to this email").

   Output/Result: Average $\leq$ 15 s from transcript ready to command result.

   How test will be performed: Measure timestamps from End of Audio to command set being performed, repeat over 20 different audio samples and calculate average latency.

test-PF-3 Accuracy & Precision (Stationary Noise) — Stretch Goal

1. test-PF-3
   Type: Offline Evaluation

   Note: This test is classified as a **stretch goal** and is not required for the baseline validation of the system. It is deferred beyond the current project scope. Evaluation under stationary noise conditions remains future work.

   Test Case Derivation: PRF-13.1, PRF-13.2

   Initial State: Labeled impaired-speech with a command set with stationary background noise (AC/fan) mixed at 20/10/5 dB.

   Input/Condition: Run ASR with the intent/command classifier.

   Output/Result: WER meets $\geq$ 70% accuracy; command precision $\geq$ 80% at SNR less than or equal to 20 dB.

   How test will be performed: Run sample audios with the different levels of background noise, calculate accuracy and command recognition

against the what was actually meant from the audio sample, then calculate percentages of accuracy and precision.

Unnecessary Tests and Justifications

- **PRF-13.5 Capacity ($\geq$ 20 concurrent users) — Out of Scope (PoC)**
  Why not tested now: The PoC targets **single-user** evaluation focused on correctness and latency. It is infeasible at this stage to run a system test that scales over 20 users and adds significant load and costs.

- **PRF-13.6 Scalability/Extensibility (Horizontal scaling; modular extensions) — Out of Scope (PoC)**
  Why not tested now: Horizontal scaling is an **infrastructure** concern that isn't meaningfully exercised without real or simulated multi-tenant traffic. Extensibility is largely an **architecture/code-structure** attribute rather than a runtime metric.
  How it's handled instead: Verified via **architecture/code review** and maintainability checks (see **test-MS-1** for modularity and extension points).

- **PRF-13.7 Longevity (reliable operations $\geq$ 5 years) — Out of Scope (PoC)**
  Why not tested now: Longevity cannot be validated with a short-cycle **system test**; it requires years of operation data. Running a 5-year endurance test is infeasible at this stage.

4.2.4 Operational & Environmental

test-OER-1 Cross-Platform Browser Compatibility

1. test-OER-1
   Type: Manual + Automated

   Test Case Derivation: OER-14.1, OER-14.2, MSR-15.3

   Initial State: Windows 10+, macOS 12+, Ubuntu 20.04+; Chrome/Edge/Firefox/Safari (latest two versions).

   Input/Condition: Run flow test.

   Output/Result: All flows pass, no OS tweaks/extensions beyond product install.

How test will be performed: Run same flow test through each browser, validate that each runs as expected regardless of browser used.

test-OER-2 Update & Backward Compatibility

1. test-OER-2
   Type: Manual + Automated Regression

   Test Case Derivation: OER-14.4, OER-14.5

   Initial State: Real user profile with data/preferences.

   Input/Condition: Apply minor and major updates.

   Output/Result: No data loss. preferences retained; ¡1 minute downtime perceived.

   How test will be performed: Update then validate data and features are saved simulate rollback and check the same conditions.

Unnecessary Tests and Justifications

- **OER-14.3 Adjacent systems & OSS compatibility — Out of Scope (PoC)**
  Why not tested now: No concrete adjacent systems are defined for the PoC, runtime end to end integration would be speculative and low-value. Compatibility is sufficiently covered via CI dependency/license checks and mock contract tests at this stage.

4.2.5 Maintainability & Support

test-MS-1 Codebase Maintainability Review

1. test-MS-1
   Type: Static Analysis + Doc Review

   Test Case Derivation: MSR-15.1

   Initial State: Final repo & docs.

   Input/Condition: Evaluate architecture, boundaries, test coverage, comments, READMEs.

   Output/Result: Checklist score $\geq$ 85%, new dev completes a small change in $\leq$ 0.5 day using docs.

How test will be performed: Two new reviewers/devs score the documentation and the code, they attempt to make a change to the code and rate how easily they were able to perform the task.

test-MS-2 Support Assets Accessibility

1. test-MS-2
   Type: Manual + Automated Accessibility Checks

   Test Case Derivation: MSR-15.2

   Initial State: Help/FAQ pages built.

   Input/Condition: Audit contrast and readability and media aids.

   Output/Result: Pass high-contrast checks with captions/alt text present.

   How test will be performed: Run a contrast tool on the page and manual spot-checks to ensure captions and alt text is present.

4.2.6 Security

test-SEC-1 Role-Based Access Control (RBAC)

1. test-SEC-1
   Type: Manual + Automated Security Tests

   Test Case Derivation: SCR-16.1

   Initial State: Accounts for primary/secondary/tertiary roles.

   Input/Condition: Attempt in-role and out-of-role actions.

   Output/Result: Least-privilege enforced, unauthorized actions blocked and logged.

   How test will be performed: Test privileges of each of the 3 users, run through a checklist of what they can and cannot access and make sure they are able to do all actions they have permissions to do and are blocked out of actions they are unauthorized to do.

test-SEC-2 Command Confirmation & Intent Match

1. test-SEC-2
   Type: Manual, Dynamic

Test Case Derivation: SCR-16.2

Initial State: Confirmation UI enabled.

Input/Condition: Ambiguous/noisy commands; potentially disruptive actions.

Output/Result: System requires user validation and shows warnings with no unintended execution.

How test will be performed: Run with a script of commands and verify confirmation flow.

test-SEC-3 Consent & Data Handling

1. test-SEC-3
   Type: Static Review + Manual Flow

   Test Case Derivation: SCR-16.3

   Initial State: Fresh user; data policy active.

   Input/Condition: Onboarding consent and option to opt-in for model improvement.

   Output/Result: Explicit consent captured and a decline path respected with data anonymized before training.

   How test will be performed: Review code/config plus run onboarding with a new user, inspect data pipeline & backup config to ensure user consent is respected.

Unnecessary Tests and Justifications

- **SCR-16.4 Secure logging (audit integrity & retention) — Out of Scope (Unit tests)**
  Why not tested now: Best validated via code-level/unit tests and static review. Duplicating with system tests in the PoC adds little value.

- **SCR-16.5 Immunity to misuse (robust to noise/rate limits) — Out of Scope (Unit tests)**
  Why not tested now: Requires targeted fault injection/adversarial unit tests (e.g., noisy inputs, burst traffic) and contract tests for rate limiting. Portions are indirectly covered by existing flows; full coverage deferred to unit/integration tests.

4.2.7 Cultural

test-CUL-1 Tone, Bias & Harm Guardrails Review

1. test-CUL-1
   Type: Static and Scenario-Based Testing

   Test Case Derivation: CLR-17.1

   Initial State: Prompt templates and moderation/guardrail rules configured.

   Input/Condition: Run scenarios across diverse names with edge cases.

   Output/Result: Neutral tone; harmful/biased outputs blocked with safe messaging; escalation path provided.

   How test will be performed: Run a curated scenario set and have a reviewer checklist how the output tone is and if guardrails are deployed against harmful content.

4.2.8 Compliance

test-CPL-1 PIPEDA Compliance Audit

1. test-CPL-1
   Type: Documentation & Process Audit

   Test Case Derivation: CPR-18.1

   Initial State: Data inventory, consent records, retention policy, DSAR process.

   Input/Condition: Auditor reviews artifacts & simulates data access/deletion request.

   Output/Result: Pass checklist; DSAR fulfilled within policy timelines; lawful basis documented.

   How test will be performed: Map data flows and verify consent & retention.

test-CPL-2 WCAG 2.0 AA Spot-Compliance

1. test-CPL-2
   Type: Automated and Manual Accessibility Testing

   Test Case Derivation: CPR-18.2

   Initial State: UI build with accessibility tooling integrated.

   Input/Condition: Run automated audit; manual keyboard/screen reader checks on critical paths.

   Output/Result: No critical AA violations on core flows; issues tracked with remediation plan.

   How test will be performed: Automated scan and manual verification on forms.

4.3 Traceability Between Test Cases and Requirements

The table below maps each test case to the SRS requirements it supports.

Test ID	Requirement(s)
test-FR1-MIC-1	FR1
test-FR1-MIC-2	FR1
test-FR1-MIC-3	FR1
test-FR2-ASR-1	FR2
test-FR2-ASR-2	FR2
test-FR3-UI-1	FR3
test-FR3-UI-2	FR3
test-FR4-MAP-1	FR4
test-FR4-MAP-2	FR4
test-FR4-MAP-3	FR4
test-FR4-MAP-4	FR4
test-FR5-EXEC-1	FR5
test-FR5-EXEC-2	FR5
test-FR5-EXEC-3	FR5
FR6 (Scenario-based, via FR5 tests)	FR6
test-LF-1	LFR-11.1
test-LF-2	LFR-11.1, LFR-11.2
test-UH-1	UHR-12.1
test-UH-2	UHR-12.3
test-UH-3	UHR-12.2
test-UH-4	UHR-12.4
test-UH-5	UHR-12.5
test-PF-1	PRF-13.1
test-PF-2	PRF-13.2
test-PF-3	PRF-13.1, PRF-13.2
test-OER-1	OER-14.1, OER-14.2, MSR-15.3
test-OER-2	OER-14.4, OER-14.5
test-MS-1	MSR-15.1
test-MS-2	MSR-15.2
test-SEC-1	SCR-16.1
test-SEC-2	SCR-16.2
test-SEC-3	SCR-16.3
test-CUL-1	CLR-17.1
test-CPL-1	CPR-18.1
test-CPL-2	CPR-18.2

5 Unit Test Description

The unit tests for *VoiceBridge* are designed to exercise the core modules defined in the Module Interface Specification (MIS), with a focus on the control and data-flow responsibilities of each module. Our overall philosophy is:

- treat each module as a black box at its public interface (access routines) while also covering important white-box behaviours such as error paths, boundary conditions, and internal state transitions;
- isolate heavy or external dependencies (e.g., LLM clients, browser automation, sound hardware, ASR models) using test doubles so that unit tests remain deterministic and fast; and
- organise tests into small, readable cases whose names document the behaviour under test (for example, `test_transcribe_returns_transcript_text` or `test_start_session_already_running_returns_message`).

Concretely, the unit testing strategy follows this pattern for each module:

1. At least one test for normal behaviour of each public access routine.
2. Additional tests for invalid inputs, misconfiguration, and exceptional conditions.
3. Tests that exercise important internal state transitions where applicable (for example, audio capture state or session lifecycle).
4. Integration-style unit tests that verify the full happy-path pipeline for the module with all collaborators mocked.

The detailed inputs and outputs for each case are documented directly in the Python test code under the `test/` directory. This section summarises the implemented tests and how they relate to the MIS modules.

5.1 Unit Testing Scope

The core modules that have been implemented to satisfy the application's functional requirements will be the focus of unit testing. That includes the following modules:

- (M4) Speech-to-Text Engine
- (M5) Command Orchestrator
- (M7) Browser Orchestrator
- (M8) Session Manager
- (M15) Audio Capture Module
- (M20) Feedback Module

Note that though the modules in the presentation layer are core to the application functionality, as they supply the user interface, they will be excluded. Given the simplicity of our UI, we have chosen to forgo unit tests in favor of end-to-end (E2E) and backend integration tests. With minimal frontend logic and no complex state management, unit tests would largely just verify that components render, offering little confidence in actual user outcomes. E2E tests give us far greater coverage per test by validating complete user flows, and backend integration tests ensure the data layer behaves correctly.

The remaining modules not mentioned in the above list are considered out of scope for the current MVP phase of the project; therefore, we will not populate unit test descriptions for them.

5.2 Tests for Functional Requirements

Most of the verification of functional behaviour is performed through automated unit tests using `pytest`. For each module, we define a small number of representative test groups that collectively exercise the normal path, error handling, and edge conditions. Below we summarise the implemented tests and how they relate to the MIS modules and SRS functional requirements (FR1–FR6). For full details, including exact inputs and assertions, see the test code under `test/`.

5.2.1 Module M4: Speech-to-Text Engine

The Speech-to-Text Engine is implemented in `app.speech_to_text_engine` and is verified by `test/test_app/test_stt.py`. The tests cover construction, audio format validation, model readiness, conversion of raw bytes to

audio streams, the asynchronous transcription pipeline, buffering of streaming audio, and optional personalization.

1. `TestInit` and `TestValidateModelReady`
   Type: Automatic

   Initial State: A `SpeechToTextEngine` instance constructed with a fully mocked `WhisperLoraAsrModel`.

   Input: Different constructor arguments (with/without noise filter and personalization store) and model readiness configurations (valid, invalid, or missing model).

   Output: The engine stores configuration correctly, initialises an internal model when the checkpoint is valid, and raises `InitializationError` or `ModelValidationError` when initialisation or validation fails.

   Test Case Derivation: These cases directly enforce the MIS contracts for engine construction and readiness checks, ensuring that the ASR pipeline cannot be used when its dependencies are misconfigured.

   How test will be performed: Instantiate the engine under different conditions and assert internal attributes and raised exceptions using the tests in the `TestInit` and `TestValidateModelReady` classes.

2. `TestValidateAudioFormat` and `TestBytesToAudioStream`
   Type: Automatic

   Initial State: A `SpeechToTextEngine` with default configuration.

   Input: `AudioStream` instances and raw PCM byte buffers at various sample rates and amplitudes.

   Output: `validateAudioFormat` correctly accepts 16 kHz audio and rejects unsupported rates; `_bytes_to_audio_stream` produces `AudioStream` objects with the expected length, sample rate, and normalised `float32` samples.

   Test Case Derivation: These tests validate the preconditions for FR2 (accurate transcription) by ensuring that only well-formed audio enters the ASR model and that conversion from bytes to internal representation is correct.

   How test will be performed: Call the relevant methods with synthetic audio produced in helpers such as `_make_audio_bytes` and `_make_audio_stream`, then assert boolean return values and array properties.

3. `TestTranscribe`, `TestApplyPersonalization`, and `TestTranscribeIntegration`
   Type: Automatic

   Initial State: A mocked ASR model whose `extract_features` and `decode` methods can succeed or raise errors; optional noise filter and personalization store.

   Input: Valid and invalid audio bytes, with toggled noise filtering and personalization behaviour, and injected failures in feature extraction, filtering, or decoding.

   Output: On valid input, `transcribe` returns the expected transcript string; on invalid audio or model failures, it raises a runtime error with a "Failed to transcribe" message; when personalization is configured, profile metadata is attached to transcripts via `_apply_personalization`.

   Test Case Derivation: These tests exercise the full unit-level ASR pipeline corresponding to FR2, including both happy path and failure modes.

   How test will be performed: Use asynchronous `pytest.mark.asyncio` tests to call `transcribe`, assert return values or exceptions, and verify that collaborators (noise filter, model, personalization store) are invoked in the correct order.

5.2.2 Module M5: Command Orchestrator

The Command Orchestrator is implemented in `command_orchestrator` and verified by `test/test_app/test_command_orchestrator.py`. The unit tests stub the external `google.genai` client and exercise dataclasses, custom exceptions, prompt construction, LLM interaction, response parsing, guardrails, and the high-level `process` method.

1. `TestOrchestratorResponse` and `TestExceptions`
   Type: Automatic

   Initial State: No external state; only the `OrchestratorResponse` dataclass and custom exception hierarchy.

   Input: Various combinations of constructor arguments and raised exceptions.

Output: Fields such as `needs_clarification`, `user_prompt`, and `metadata` are stored as specified, and `InitializationError` and `InferenceError` behave as specialisations of `OrchestratorError`.

Test Case Derivation: These tests enforce the basic contracts used by higher-level orchestration logic and ensure that error handling is traceable and type-safe.

How test will be performed: Instantiate dataclasses and raise exceptions inside `pytest.raises` blocks, checking attributes and messages.

2. `TestCommandOrchestratorInit` and `TestGetDefaultSystemPrompt`
   Type: Automatic

   Initial State: Environment variables may or may not define `GEMINI_API_KEY`; prompt files may or may not exist; `google.genai.Client` may succeed or fail.

   Input: Different combinations of explicit API keys, environment configuration, model IDs, and prompt file paths.

   Output: The orchestrator selects the correct API key source, stores the configured model ID, loads system prompts from file when available (or falls back to a default prompt containing all required keys), and propagates initialisation failures as `InitializationError`.

   Test Case Derivation: These tests ensure that the module is robust to missing configuration and that default behaviour matches the MIS design for orchestration initialisation.

   How test will be performed: Use `patch.dict` and `MagicMock` to control environment variables and the `Client` constructor, then assert internal attributes and exceptions.

3. `TestParseResponse`, `TestCallLlm`, `TestProcess`, `TestApplyGuardrails`, and `TestMultiTurnFlow`
   Type: Automatic

   Initial State: A `CommandOrchestrator` instance with a mocked LLM client; optional conversation history.

   Input: Raw LLM responses that are valid JSON, code blocks wrapped in Markdown fences, completely invalid JSON, and payloads indicating clarification or direct commands; user inputs that should be allowed or blocked by guardrails; single-turn and multi-turn conversation contexts.

Output: _parse_response returns OrchestratorResponse objects with correct clarification flags, prompts, commands, reasoning, and metadata; _call_llm forwards messages and system prompts with the right roles and model ID and raises InferenceError on API failures; process handles ambiguous commands via clarification, propagates conversation context, and wraps bad JSON gracefully; apply_guardrails allows benign commands and blocks dangerous ones with an explanatory message.

Test Case Derivation: These tests directly support FR4 and FR5 by ensuring that textual commands are clarified, normalised, and screened for safety before execution, and that the orchestrator behaves predictably even when the LLM returns malformed responses.

How test will be performed: Use mocked generate_content calls to inject specific raw response text, run asynchronous tests for _call_llm and process, and assert both returned objects and interactions with the LLM client.

5.2.3 Module M7: Browser Orchestrator

The Browser Orchestrator module (browser_orchestrator) is responsible for delegating high-level textual commands to a browser automation agent. It is verified by test/test_control/test_browser_controller.py, which stubs the external browser_use package.

1. TestRunCommand
   Type: Automatic

   Initial State: A stubbed browser_use environment; no active browser agent.

   Input: Various task strings (normal commands, empty strings) and a mocked Browser instance.

   Output: The asynchronous run_command function constructs a ChatBrowserUse instance and an Agent with the correct task and browser arguments, awaits agent.run() exactly once, returns the resulting history object, and propagates exceptions raised by the agent.

   Test Case Derivation: These tests verify the MIS contract that the orchestrator translates textual tasks into browser operations without embedding browser logic itself, aligning with FR5 execution behaviour.

How test will be performed: Use `patch` to mock `ChatBrowserUse` and `Agent`, run `run_command` under `pytest.mark.asyncio`, and assert constructor arguments, awaited calls, and returned objects.

2. `TestEnvironmentSetup`
   Type: Automatic

   Initial State: The module-level environment is reloaded with and without a `BROWSER_USE_API_KEY`; the platform may be Windows.

   Input: Environment variable dictionaries and a module reload via `importlib.reload`.

   Output: The module computes `ENV_PATH` pointing to a `.env` file two levels above, reads the API key from the environment, and (on Windows) configures the event loop policy as `WindowsProactorEventLoopPolicy`.

   Test Case Derivation: These tests ensure that browser orchestration can be configured reliably across environments and platforms.

   How test will be performed: Reload the module under controlled environment settings, then assert module-level constants and, on Windows, the configured event loop policy.

5.2.4 Module M8: Session Manager

The Session Manager (`session_manager`) manages the lifecycle of a long-lived browser session. It is tested in `test/test_control/test_session_manager.py`, which focuses on the behaviour of `start_session`, `stop_session`, and `get_browser`.

1. `TestStartSession` and `TestStopSession`
   Type: Automatic

   Initial State: A module-level browser reference that may be `None` or an active mocked Browser instance.

   Input: Calls to `start_session()` and `stop_session()` in different orders (first start, repeated start, stop without start, start after stop).

   Output: `start_session` creates a Browser with `keep_alive = True`, calls `browser.start()` exactly once, sets the global browser reference, and returns either "Browser started" or "Browser already running"; `stop_session` awaits `browser.stop()`, clears the global reference, and

returns "Browser stopped" or "Browser already stopped" without raising when no browser exists.

Test Case Derivation: These tests validate that the session lifecycle is robust and idempotent, matching the MIS design for shared browser resources and supporting FR5.

How test will be performed: Use `patch` to replace `Browser` with an async-mocked instance, invoke the lifecycle functions under `pytest.mark.asyncio`, and check both messages and side effects on the global browser variable.

2. `TestGetBrowser` and `TestSessionLifecycle`
   Type: Automatic

   Initial State: Different configurations of the global browser reference before and after lifecycle calls.

   Input: Calls to `get_browser()` in each state and sequences of `start_session` and `stop_session`.

   Output: `get_browser` returns the current Browser object when running and `None` otherwise, without modifying state; a full start–stop–start cycle results in a fresh Browser instance and leaves the module in a consistent state.

   Test Case Derivation: These tests ensure that code which depends on the shared browser can safely query it and that repeated lifecycle operations do not leak or reuse invalid resources.

   How test will be performed: Manipulate the module-level browser reference directly in tests, call the public functions, and assert return values and instance identity.

5.2.5 Module M15: Real-time Audio Capture

The Real-time Audio Capture module (`audio_capture`) implements microphone capture, VAD-based speech detection, and buffering before transcription. It is tested in `test/test_inputs/test_audio_capture.py`, which stubs out hardware and VAD dependencies.

1. `TestAudioConfig`, `TestAudioState`, and `TestRealtimeAudioCaptureInit`
   Type: Automatic

Initial State: No external audio devices required; configuration and state classes only.

Input: Different constructor arguments for `AudioConfig` (sample rate, chunk duration, pre-buffer and silence durations, device selection, energy thresholds) and for `RealtimeAudioCapture`.

Output: Derived fields such as `chunk_size`, `pre_buffer_chunks`, and `silence_chunks` are computed correctly; invalid configurations raise `ValueError`; initial capture state is `IDLE` with empty statistics and correctly sized pre-buffer.

Test Case Derivation: These tests confirm that configuration constraints for FR1 (audio capture) are enforced and that state machines start from a known baseline.

How test will be performed: Instantiate configuration and capture objects with different parameters and assert field values and exceptions.

2. `TestIsSpeech`, `TestProcessAudioChunk`, `TestStartRecording`, and `TestEndRecording`
   Type: Automatic

   Initial State: A `RealtimeAudioCapture` instance with a mocked VAD and (optionally) an `on_audio_ready` callback.

   Input: Synthetic audio chunks representing silence and speech, with varying energy levels, delivered while the capture state machine is in `LISTENING`, `SPEECH_DETECTED`, or `RECORDING`.

   Output: `_is_speech` combines VAD output and energy thresholds to classify chunks and increments error counters on VAD failures; `_process_audio_chunk` manages state transitions, pre-buffering, recording buffers, silence counters, and maximum duration enforcement; `_start_recording` copies pre-buffered audio and resets counters; `_end_recording` converts buffered chunks into a normalised `float32` array, computes metadata (duration, sample rate, timestamp), updates stats, invokes callbacks once per utterance, and returns to the listening state even when callbacks raise exceptions.

   Test Case Derivation: These tests correspond directly to FR1 by ensuring that the capture module correctly detects speech, segments utterances, and prepares audio for downstream processing under realistic noise and timing conditions.

How test will be performed: Drive the private methods with synthetic chunks in different states, then assert state, buffer contents, error counters, statistics, and callback invocations.

3. `TestAudioCallback`, `TestStartStop`, `TestGetStats`, `TestListAudioDevices`, and `TestFullFlow`
   Type: Automatic

   Initial State: A capture instance with its internal stream mocked via `sounddevice.InputStream`, and optional callbacks to capture utterances.

   Input: Calls to `start()`, `stop()`, and `_audio_callback` under different conditions (already running, stream errors, stopped state), as well as simulated full utterances of speech followed by sufficient silence to trigger recording end.

   Output: The capture object transitions between `IDLE`, `LISTENING`, `RECORDING`, and `STOPPED` as specified; stream errors are counted without crashing; stats dictionaries are returned as defensive copies; `list_audio_devices` filters only input-capable devices; and the full flow produces one callback per utterance with the expected audio data and metadata.

   Test Case Derivation: These tests ensure that the module behaves correctly when integrated with the OS audio stack and that repeated start/stop operations and error conditions do not leave it in an inconsistent state.

   How test will be performed: Use `patch` to replace `sounddevice.InputStream`, simulate callback invocations, and run integration-style flows that mimic real speech followed by silence while asserting resulting callbacks and stats.

5.2.6 Module M20: Feedback Module

The Feedback Module is implemented in `feedback_store` and is verified by `test/test_data/test_feedback_module.py`. These tests focus on reliable, structured recording of user feedback about executed commands (for example, ratings and satisfaction signals) and on robustness under concurrent writes and I/O errors.

1. `TestInit`
   Type: Automatic

   Initial State: No prior feedback log; optional explicit or default log path.

   Input: Different constructor arguments for `FeedbackStore`, including explicit `log_path` values (as strings and `Path` objects) and the no-argument default.

   Output: The store always normalises `log_path` to a `Path` object, chooses a default `feedback_log.jsonl` file in the module directory when no path is provided, and initialises a re-entrant lock for thread-safe writes.

   Test Case Derivation: These tests ensure that initialisation is predictable across environments and that the module is safe to use concurrently from different parts of the system.

   How test will be performed: Instantiate `FeedbackStore` with various arguments and assert properties of `log_path` and `_lock`.

2. `TestRecordStructure` and `TestSourceAutoDetection`
   Type: Automatic

   Initial State: A store whose log file is backed by a temporary directory.

   Input: Calls to `log_feedback` with different command IDs, feedback types, values, optional command text, and optional explicit sources.

   Output: Each written JSON record contains all required keys (`uuid`, `command_id`, `command_text`, `type`, `value`, `source`, `timestamp`); UUIDs are valid version 4 strings and unique per record; timestamps are valid ISO-8601 values ending in `Z`; sources are automatically classified as `verbal`, `ui`, or `unknown` based on the value, unless an explicit source is provided (which is preserved as-is).

   Test Case Derivation: These tests enforce the data schema used for offline analysis of user feedback and ensure that automatic source classification behaves as intended.

   How test will be performed: Log feedback events, read back lines from the JSONL log, and assert field presence, formats, and classification logic.

3. `TestFileWriting` and `TestErrorHandling`
   Type: Automatic

   Initial State: A store with an existing or non-existing log file path.

   Input: Single and repeated calls to `log_feedback`, with and without simulated I/O failures (for example, by patching `Path.open` to raise `IOError`).

   Output: Each call appends a single valid JSON object on its own line without overwriting previous records; log files are created on demand if missing; transient write errors are swallowed so that callers are not interrupted, and such errors are reported via the module logger; subsequent calls after an error still succeed and produce valid records.

   Test Case Derivation: These tests provide confidence that feedback collection is resilient to partial disk failures and that logging cannot crash the main application.

   How test will be performed: Inspect the contents of the log file after different sequences of writes and use `patch` to inject controlled I/O failures while asserting logger calls.

4. `TestThreadSafety`
   Type: Automatic

   Initial State: A store with an empty log file.

   Input: Concurrent calls to `log_feedback` from multiple threads.

   Output: All attempted writes succeed without raising exceptions; the resulting log file contains exactly one record per attempted write, each with a unique UUID.

   Test Case Derivation: These tests validate that the internal locking strategy of the Feedback Module is sufficient to prevent lost updates or corrupted records under concurrent usage.

   How test will be performed: Spawn multiple threads that call `log_feedback` in parallel, then read back all records and assert count equality and UUID uniqueness.

5.3 Traceability Between Unit Tests and Modules

Table 6 summarises which test files cover each in-scope MIS module.

Table 5: Traceability Between Unit Tests and MIS Modules

MIS Module	**Primary Responsibilities**	**Unit Test File(s)**
M4 Speech-to-Text Engine	Audio format validation, ASR model integration, transcription pipeline, personalization	`test/test_app/ test_stt.py`
M5 Command Orchestrator	LLM prompt construction, response parsing, clarification handling, safety guardrails	`test/test_app/ test_command_orchestrator.py`
M7 Browser Orchestrator	Delegating textual tasks to browser automation agent	`test/test_control/ test_browser_controller.py`
M8 Session Manager	Lifecycle of shared browser session (start/stop/get)	`test/test_control/ test_session_manager.py`
M15 Audio Capture Module	Microphone capture, VAD-based speech detection, utterance segmentation, audio statistics	`test/test_inputs/ test_audio_capture.py`
M20 Feedback Module	Persistent storage of structured command feedback records	`test/test_data/ test_feedback_module.py`

5.4 Traceability Between Unit Tests and Modules

Table 6 summarises which test files cover each in-scope MIS module.

Table 6: Traceability Between Unit Tests and MIS Modules

MIS Module	**Primary Responsibilities**	**Unit Test File(s)**
M4 Speech-to-Text Engine	Audio format validation, ASR model integration, transcription pipeline, personalization	`test/test_app/ test_stt.py`
M5 Command Orchestrator	LLM prompt construction, response parsing, clarification handling, safety guardrails	`test/test_app/ test_command_orchestrator.py`
M7 Browser Orchestrator	Delegating textual tasks to browser automation agent	`test/test_control/ test_browser_controller.py`
M8 Session Manager	Lifecycle of shared browser session (start/stop/get)	`test/test_control/ test_session_manager.py`
M15 Audio Capture Module	Microphone capture, VAD-based speech detection, utterance segmentation, audio statistics	`test/test_inputs/ test_audio_capture.py`

Appendix — Reflection

The information in this section will be used to evaluate the team members on the graduate attribute of Lifelong Learning.

1. **What went well while writing this deliverable?**
   The writing process went smoothly because there was strong alignment between the project requirements and the testing approach. Breaking down each functional requirement into specific, well-defined tests helped focus the effort and ensured completeness. The collaboration within the team was productive, allowing us to clarify assumptions and verify tool use early on. Being able to connect test cases directly to the requirements and think through measurable success criteria gave the plan a solid foundation.

2. **What pain points did you experience during this deliverable, and how did you resolve them?**
   A major difficulty was ensuring that all planned tests were realistically feasible given our current toolset, resources, and project timeline. Some initial test ideas were technically interesting but would have required tools or integrations we didn't yet have, or would have taken more time than we could allocate. To address this, we carefully reviewed past project documentation and assessed our CI/CD and automation capabilities to see what was immediately implementable. We then adjusted the scope of certain tests, streamlining some, combining others, and prioritizing high-impact cases, so that every test included in the plan was both practical and meaningful. This approach allowed us to maintain ambitious coverage without overcommitting, ensuring that the V&V plan is actionable, realistic, and aligned with project constraints.

3. **What knowledge and skills will the team collectively need to acquire to successfully complete the verification and validation of your project?**
   To successfully complete the verification and validation of the VoiceBridge project, the team will need to acquire a combination of technical, ethical, and user-centered skills. This includes understanding speech data quality standards to verify the clarity, consistency, and accuracy of dysarthric speech recordings, along with proficiency in labeling and

annotation tools to ensure reliable datasets. The team must also develop skills in machine learning verification techniques, such as cross-validation, confusion matrix analysis, and bias detection, to evaluate model performance objectively. Knowledge of accessibility and ethical guidelines will be essential to ensure responsible data collection, participant consent, and inclusivity for users with speech impairments. In addition, team members should strengthen their understanding of software testing practices, including unit, integration, and system testing, to verify code reliability. Finally, the ability to conduct usability testing and analyze user feedback will be crucial for validating the system's real-world effectiveness and ensuring that VoiceBridge genuinely improves accessibility and communication support for its intended users.