Percentages keep the proportions

The columns are declared as 20%, 16%, *, 8% and 12%. The star column gets the remaining 44%.

Article no.	Size	Application	PU	Price €
CS-3012	3.0 × 12	Fine work in chipboard and MDF	1000	4.90
CS-4030	4.0 × 30	Universal screw for wood and chipboard, no pre-drilling required	500	4.90
CS-4050	4.0 × 50	Universal screw for wood and chipboard, no pre-drilling required	500	6.70
CS-5070	5.0 × 70	Load-bearing timber connections, pre-drill in hardwood	200	5.90
CS-6080	6.0 × 80	Heavy-duty connections in solid timber	100	5.00
CS-60120	6.0 × 120	Heavy-duty connections, requires pre-drilling near edges	100	7.30

The same declaration in two tables of half the width: all columns shrink in the same ratio.

Article no.	Size	Application	PU	Price €
CS-3012	3.0 × 12	Fine work in chipboard and MDF	1000	4.90
CS-4030	4.0 × 30	Universal screw for wood and chipboard, no pre-drilling required	500	4.90
CS-4050	4.0 × 50	Universal screw for wood and chipboard, no pre-drilling required	500	6.70

Article no.	Size	Application	PU	Price €
CS-5070	5.0 × 70	Load-bearing timber connections, pre-drill in hardwood	200	5.90
CS-6080	6.0 × 80	Heavy-duty connections in solid timber	100	5.00
CS-60120	6.0 × 120	Heavy-duty connections, requires pre-drilling near edges	100	7.30

Star widths may have decimals, a star on its own means 1*. The remaining width is shared in the ratio 1 : 1.5 : 2.5.

30mm	*	1.5*	2.5*

Widths from the content

max: the columns get the natural width of their content, the star column gets the rest. The size column has minwidth="25mm".

Article no.	Size	Application	PU	Price €
CS-3012	3.0 × 12	Fine work in chipboard and MDF	1000	4.90
CS-4030	4.0 × 30	Universal screw for wood and chipboard, no pre-drilling required	500	4.90
CS-4050	4.0 × 50	Universal screw for wood and chipboard, no pre-drilling required	500	6.70
CS-5070	5.0 × 70	Load-bearing timber connections, pre-drill in hardwood	200	5.90
CS-6080	6.0 × 80	Heavy-duty connections in solid timber	100	5.00
CS-60120	6.0 × 120	Heavy-duty connections, requires pre-drilling near edges	100	7.30

min: the column is as narrow as its widest word (here without hyphenation). minwidth sets a lower bound (for all kinds of widths), the star column gets the rest.

min: load-bearing timber connections	min, minwidth="40mm": load-bearing timber connections	*: load-bearing timber connections

?: after the fixed first column (30mm), the ?-columns share the rest in the ratio of their natural widths (stretch="max"). Without stretch="max" they get their natural width.

Article no. (30mm)	Size (?)	Application (?)
CS-3012	3.0 × 12	Fine work in chipboard and MDF
CS-4030	4.0 × 30	Universal screw for wood and chipboard, no pre-drilling required
CS-4050	4.0 × 50	Universal screw for wood and chipboard, no pre-drilling required