IEEE Std 1003.1™, 2004 Edition

The Open Group Technical Standard
Base Specifications, Issue 6

Includes IEEE Std 1003.1™-2001, IEEE Std 1003.1™-2001/Cor 1-2002
and IEEE Std 1003.1™-2001/Cor 2-2004

Standard for Information Technology—
Portable Operating System Interface (POSIX®)

Base Definitions

Sponsor

Portable Applications Standards Committee
of the
IEEE Computer Society

and

The Open Group

[This page intentionally left blank]

Abstract

This standard is simultaneously ISO/IEC 9945, IEEE Std 1003.1, and forms the core of the Single UNIX Specification, Version 3.

This 2004 Edition includes IEEE Std 1003.1-2001/Cor 1-2002 and IEEE Std 1003.1-2001/Cor 2-2004 incorporated into IEEE Std 1003.1-2001 (the base document). The two Corrigenda address problems discovered since the approval of IEEE Std 1003.1-2001. These changes are mainly due to resolving integration issues raised by the merger of the base documents that were incorporated into IEEE Std 1003.1-2001, which is the single common revision to IEEE Std 1003.1™-1996, IEEE Std 1003.2™-1992, ISO/IEC 9945-1:1996, ISO/IEC 9945-2:1993, and the Base Specifications of The Open Group Single UNIX® Specification, Version 2.

This standard defines a standard operating system interface and environment, including a command interpreter (or ''shell''), and common utility programs to support applications portability at the source code level. This standard is intended to be used by both applications developers and system implementors and comprises four major components (each in an associated volume):

- General terms, concepts, and interfaces common to all volumes of this standard, including utility conventions and C-language header definitions, are included in the Base Definitions volume.
- Definitions for system service functions and subroutines, language-specific system services for the C programming language, function issues, including portability, error handling, and error recovery, are included in the System Interfaces volume.
- Definitions for a standard source code-level interface to command interpretation services (a ''shell'') and common utility programs for application programs are included in the Shell and Utilities volume.
- Extended rationale that did not fit well into the rest of the document structure, which contains historical information concerning the contents of this standard and why features were included or discarded by the standard developers, is included in the Rationale (Informative) volume.

The following areas are outside the scope of this standard:

- Graphics interfaces
- Database management system interfaces
- Record I/O considerations
- Object or binary code portability
- System configuration and resource availability

This standard describes the external characteristics and facilities that are of importance to applications developers, rather than the internal construction techniques employed to achieve these capabilities. Special emphasis is placed on those functions and facilities that are needed in a wide variety of commercial applications.

Keywords

application program interface (API), argument, asynchronous, basic regular expression (BRE), batch job, batch system, built-in utility, byte, child, command language interpreter, CPU, extended regular expression (ERE), FIFO, file access control mechanism, input/output (I/O), job control, network, portable operating system interface (POSIX®), parent, shell, stream, string, synchronous, system, thread, X/Open System Interface (XSI)

Base Definitions, Issue 6

Published 30 April 2004 by the Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, U.S.A.
ISBN: 0-7381-4039-2 / SH95234 PDF 0-7381-4040-6 / SS95234
Printed in the United States of America by the IEEE.

Published 30 April 2004 by The Open Group
Apex Plaza, Forbury Road, Reading, Berkshire RG1 1AX, U.K.
Document Number: C046
ISBN: 1-931624-43-7
Printed in the U.K. by The Open Group.

Feedback

This standard has been prepared by the Austin Group. Feedback relating to the material contained in this standard may be submitted using the Austin Group web site at *www.opengroup.org/austin/defectform.html*.

IEEE

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

Use of an IEEE Standard is wholly voluntary. The IEEE disclaims liability for any personal injury, property, or other damage, of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, or reliance upon this, or any other IEEE Standard document.

The IEEE does not warrant or represent the accuracy or content of the material contained herein, and expressly disclaims any express or implied warranty, including any implied warranty of merchantability or fitness for a specific purpose, or that the use of the material contained herein is free from patent infringement. IEEE Standards documents are supplied "AS IS".

The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE Standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard. Every IEEE Standard is subjected to review at least every five years for revision or reaffirmation. When a document is more than five years old and has not been reaffirmed, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE Standard.

In publishing and making this document available, the IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity. Nor is the IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing this, and any other IEEE Standards document, should rely upon the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

Interpretations: Occasionally questions may arise regarding the meaning of portions of standards as they relate to specific applications. When the need for interpretations is brought to the attention of the IEEE, the Institute will initiate action to prepare appropriate responses. Since IEEE Standards represent a consensus of concerned interests, it is important to ensure that any interpretation has also received the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to interpretation requests except in those cases where the matter has previously received formal consideration. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position, explanation, or interpretation of the IEEE. Current interpretations can be accessed at *http://standards.ieee.org/reading/ieee/interp/index.html*.

Errata, if any, for this and all other standards can be accessed at *http://standards.ieee.org/reading/ieee/updates/errata/index.html*. Users are encouraged to check this URL for errata periodically.

Comments for revision of IEEE Standards are welcome from any interested party, regardless of membership affiliation with the IEEE.[1] Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Comments on standards and requests for interpretations should be addressed to:

Secretary, IEEE-SA Standards Board, 445 Hoes Lane, P.O. Box 1331, Piscataway, NJ 08855-1331, U.S.A.

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. The IEEE shall not be responsible for identifying patents for which a license may be required by an IEEE Standard or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

A patent holder has filed a statement of assurance that it will grant licenses under these rights without compensation or under reasonable rates and non-discriminatory, reasonable terms and conditions to all applicants desiring to obtain such licenses. The IEEE makes no representation as to the reasonableness of rates and/or terms and conditions of the license agreements offered by patent holders. Further information may be obtained from the IEEE Standards Department.

Authorization to photocopy portions of any individual standard for internal or personal use is granted in the U.S. by the Institute of Electrical and Electronics Engineers, Inc., provided that the appropriate fee is paid to the Copyright Clearance Center.[2] Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center. To arrange for payment of the licensing fee, please contact:

Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923, U.S.A., Tel.: +1 978 750 8400

Amendments, corrigenda, and interpretations for this standard, or information about the IEEE standards development process, may be found at *http://standards.ieee.org*.

The IEEE publications catalog and ordering information are available at *http://shop.ieee.org/store*.

---

1. For this standard, please send comments via the Austin Group as requested on page ii.
2. Please refer to the special provisions for this standard on page ii concerning permissions from both copyright holders and arrangements to cover photocopying and reproduction across the world, as well as by commercial organizations wishing to license the material for use in product documentation.

The Open Group

The Open Group is a vendor-neutral and technology-neutral consortium, whose vision of Boundaryless Information Flow will enable access to integrated information within and between enterprises based on open standards and global interoperability. The Open Group works with customers, suppliers, consortia, and other standards bodies. Its role is to capture, understand, and address current and emerging requirements, establish policies, and share best practices; to facilitate interoperability, develop consensus, and evolve and integrate specifications and Open Source technologies; to offer a comprehensive set of services to enhance the operational efficiency of consortia; and to operate the industry's premier certification service, including UNIX certification.

Further information on The Open Group is available at *www.opengroup.org*.

The Open Group has over 15 years' experience in developing and operating certification programs and has extensive experience developing and facilitating industry adoption of test suites used to validate conformance to an open standard or specification. The Open Group portfolio of test suites includes the *Westwood* family of tests for this standard and the associated certification program for Version 3 of the Single UNIX Specification, as well tests for CDE, CORBA, Motif, Linux, LDAP, POSIX.1, POSIX.2, POSIX Realtime, Sockets, UNIX, XPG4, XNFS, XTI, and X11. The Open Group test tools are essential for proper development and maintenance of standards-based products, ensuring conformance of products to industry-standard APIs, applications portability, and interoperability. In-depth testing identifies defects at the earliest possible point in the development cycle, saving costs in development and quality assurance.

More information is available at *www.opengroup.org/testing*.

The Open Group publishes a wide range of technical documentation, the main part of which is focused on development of Technical and Product Standards and Guides, but which also includes white papers, technical studies, branding and testing documentation, and business titles. Full details and a catalog are available at *www.opengroup.org/pubs*.

As with all *live* documents, Technical Standards and Specifications require revision to align with new developments and associated international standards. To distinguish between revised specifications which are fully backwards compatible and those which are not:

- A new *Version* indicates there is no change to the definitive information contained in the previous publication of that title, but additions/extensions are included. As such, it *replaces* the previous publication.
- A new *Issue* indicates there is substantive change to the definitive information contained in the previous publication of that title, and there may also be additions/extensions. As such, both previous and new documents are maintained as current publications.

Readers should note that Corrigenda may apply to any publication. Corrigenda information is published at *www.opengroup.org/corrigenda*.

The Open Group publications catalog and ordering information are available at *www.opengroup.org/pubs*.

Contents

List of Tables

Foreword

Structure of the Standard

This standard was originally developed by the Austin Group, a joint working group of members of the IEEE, members of The Open Group, and members of ISO/IEC Joint Technical Committee 1, as one of the four volumes of IEEE Std 1003.1-2001. The standard was approved by ISO and IEC and published in four parts, correlating to the original volumes.

A mapping of the parts to the volumes is shown below:

ISO/IEC 9945 Part	IEEE Std 1003.1 Volume	Description
9945-1	Base Definitions	Includes general terms, concepts, and interfaces common to all parts of ISO/IEC 9945, including utility conventions and C-language header definitions.
9945-2	System Interfaces	Includes definitions for system service functions and subroutines, language-specific system services for the C programming language, function issues, including portability, error handling, and error recovery.
9945-3	Shell and Utilities	Includes definitions for a standard source code-level interface to command interpretation services (a ''shell'') and common utility programs for application programs.
9945-4	Rationale	Includes extended rationale that did not fit well into the rest of the document structure, containing historical information concerning the contents of ISO/IEC 9945 and why features were included or discarded by the standard developers.

All four parts comprise the entire standard, and are intended to be used together to accommodate significant internal referencing among them. POSIX-conforming systems are required to support all four parts.

Introduction

Note: This introduction is not part of IEEE Std 1003.1-2001, Standard for Information Technology — Portable Operating System Interface (POSIX).

This standard has been jointly developed by the IEEE and The Open Group. It is simultaneously an IEEE Standard, an ISO/IEC Standard, and an Open Group Technical Standard.

The Austin Group

This standard was developed, and is maintained, by a joint working group of members of the IEEE Portable Applications Standards Committee, members of The Open Group, and members of ISO/IEC Joint Technical Committee 1. This joint working group is known as the Austin Group.[3] The Austin Group arose out of discussions amongst the parties which started in early 1998, leading to an initial meeting and formation of the group in September 1998. The purpose of the Austin Group has been to revise, combine, and update the following standards: ISO/IEC 9945-1, ISO/IEC 9945-2, IEEE Std 1003.1, IEEE Std 1003.2, and the Base Specifications of The Open Group Single UNIX Specification.

After two initial meetings, an agreement was signed in July 1999 between The Open Group and the Institute of Electrical and Electronics Engineers (IEEE), Inc., to formalize the project with the first draft of the revised specifications being made available at the same time. Under this agreement, The Open Group and IEEE agreed to share joint copyright of the resulting work. The Open Group has provided the chair and secretariat for the Austin Group.

The base document for the revision was The Open Group's Base volumes of its Single UNIX Specification, Version 2. These were selected since they were a superset of the existing POSIX.1 and POSIX.2 specifications and had some organizational aspects that would benefit the audience for the new revision.

The approach to specification development has been one of ''write once, adopt everywhere'', with the deliverables being a set of specifications that carry the IEEE POSIX designation, The Open Group's Technical Standard designation, and an ISO/IEC designation. This set of specifications forms the core of the Single UNIX Specification, Version 3.

This unique development has combined both the industry-led efforts and the formal standardization activities into a single initiative, and included a wide spectrum of participants. The Austin Group continues as the maintenance body for this document.

Anyone wishing to participate in the Austin Group should contact the chair with their request. There are no fees for participation or membership. You may participate as an observer or as a contributor. You do not have to attend face-to-face meetings to participate; electronic participation is most welcome. For more information on the Austin Group and how to participate, see *http://www.opengroup.org/austin*.

---

3. The Austin Group is named after the location of the inaugural meeting held at the IBM facility in Austin, Texas in September 1998.

Background

The developers of this standard represent a cross section of hardware manufacturers, vendors of operating systems and other software development tools, software designers, consultants, academics, authors, applications programmers, and others.

Conceptually, this standard describes a set of fundamental services needed for the efficient construction of application programs. Access to these services has been provided by defining an interface, using the C programming language, a command interpreter, and common utility programs that establish standard semantics and syntax. Since this interface enables application writers to write portable applications—it was developed with that goal in mind—it has been designated POSIX,[4] an acronym for Portable Operating System Interface.

Although originated to refer to the original IEEE Std 1003.1-1988, the name POSIX more correctly refers to a *family* of related standards: IEEE Std 1003.*n* and the parts of ISO/IEC 9945. In earlier editions of the IEEE standard, the term POSIX was used as a synonym for IEEE Std 1003.1-1988. A preferred term, POSIX.1, emerged. This maintained the advantages of readability of the symbol ''POSIX'' without being ambiguous with the POSIX family of standards.

Audience

The intended audience for this standard is all persons concerned with an industry-wide standard operating system based on the UNIX system. This includes at least four groups of people:

1. Persons buying hardware and software systems
2. Persons managing companies that are deciding on future corporate computing directions
3. Persons implementing operating systems, and especially
4. Persons developing applications where portability is an objective

Purpose

Several principles guided the development of this standard:

- Application-Oriented

  The basic goal was to promote portability of application programs across UNIX system environments by developing a clear, consistent, and unambiguous standard for the interface specification of a portable operating system based on the UNIX system documentation. This standard codifies the common, existing definition of the UNIX system.

- Interface, Not Implementation

  This standard defines an interface, not an implementation. No distinction is made between library functions and system calls; both are referred to as functions. No details of the implementation of any function are given (although historical practice is sometimes indicated in the RATIONALE section). Symbolic names are given for constants (such as signals and error numbers) rather than numbers.

---

4. The name POSIX was suggested by Richard Stallman. It is expected to be pronounced *pahz-icks*, as in *positive*, not *poh-six*, or other variations. The pronunciation has been published in an attempt to promulgate a standardized way of referring to a standard operating system interface.

- Source, Not Object, Portability

  This standard has been written so that a program written and translated for execution on one conforming implementation may also be translated for execution on another conforming implementation. This standard does not guarantee that executable (object or binary) code will execute under a different conforming implementation than that for which it was translated, even if the underlying hardware is identical.

- The C Language

  The system interfaces and header definitions are written in terms of the standard C language as specified in the ISO C standard.

- No Superuser, No System Administration

  There was no intention to specify all aspects of an operating system. System administration facilities and functions are excluded from this standard, and functions usable only by the superuser have not been included. Still, an implementation of the standard interface may also implement features not in this standard. This standard is also not concerned with hardware constraints or system maintenance.

- Minimal Interface, Minimally Defined

  In keeping with the historical design principles of the UNIX system, the mandatory core facilities of this standard have been kept as minimal as possible. Additional capabilities have been added as optional extensions.

- Broadly Implementable

  The developers of this standard endeavored to make all specified functions implementable across a wide range of existing and potential systems, including:

  1. All of the current major systems that are ultimately derived from the original UNIX system code (Version 7 or later)
  2. Compatible systems that are not derived from the original UNIX system code
  3. Emulations hosted on entirely different operating systems
  4. Networked systems
  5. Distributed systems
  6. Systems running on a broad range of hardware

  No direct references to this goal appear in this standard, but some results of it are mentioned in the Rationale (Informative) volume.

- Minimal Changes to Historical Implementations

  When the original version of IEEE Std 1003.1-2001/Cor 2-2004 was published, there were no known historical implementations that did not have to change. However, there was a broad consensus on a set of functions, types, definitions, and concepts that formed an interface that was common to most historical implementations.

  The adoption of the 1988 and 1990 IEEE system interface standards, the 1992 IEEE shell and utilities standard, the various Open Group (formerly X/Open) specifications, and the subsequent revisions and addenda to all of them have consolidated this consensus, and this revision reflects the significantly increased level of consensus arrived at since the original versions. The earlier standards and their modifications specified a number of areas where consensus had not been reached before, and these are now reflected in this revision. The authors of the original versions tried, as much as possible, to follow the principles below

when creating new specifications:

1. By standardizing an interface like one in an historical implementation; for example, directories
2. By specifying an interface that is readily implementable in terms of, and backwards-compatible with, historical implementations, such as the extended *tar* format defined in the *pax* utility
3. By specifying an interface that, when added to an historical implementation, will not conflict with it; for example, the *sigaction*( ) function

This revision tries to minimize the number of changes required to implementations which conform to the earlier versions of the approved standards to bring them into conformance with the current standard. Specifically, the scope of this work excluded doing any ''new'' work, but rather collecting into a single document what had been spread across a number of documents, and presenting it in what had been proven in practice to be a more effective way. Some changes to prior conforming implementations were unavoidable, primarily as a consequence of resolving conflicts found in prior revisions, or which became apparent when bringing the various pieces together.

However, since it references the 1999 version of the ISO C standard, and no longer supports ''Common Usage C'', there are a number of unavoidable changes. Applications portability is similarly affected.

This standard is specifically not a codification of a particular vendor's product.

It should be noted that implementations will have different kinds of extensions. Some will reflect ''historical usage'' and will be preserved for execution of pre-existing applications. These functions should be considered ''obsolescent'' and the standard functions used for new applications. Some extensions will represent functions beyond the scope of this standard. These need to be used with careful management to be able to adapt to future extensions of this standard and/or port to implementations that provide these services in a different manner.

- Minimal Changes to Existing Application Code

  A goal of this standard was to minimize additional work for the developers of applications. However, because every known historical implementation will have to change at least slightly to conform, some applications will have to change.

This Standard

This standard defines the Portable Operating System Interface (POSIX) requirements and consists of the following volumes:

- Base Definitions (this volume)
- Shell and Utilities
- System Interfaces
- Rationale (Informative)

This Volume

The Base Definitions volume provides common definitions for this standard, therefore readers should be familiar with it before using the other volumes.

This volume is structured as follows:

- Chapter 1 is an introduction.
- Chapter 2 defines the conformance requirements.
- Chapter 3 defines general terms used.
- Chapter 4 describes general concepts used.
- Chapter 5 describes the notation used to specify file input and output formats in this volume and the Shell and Utilities volume.
- Chapter 6 describes the portable character set and the process of character set definition.
- Chapter 7 describes the syntax for defining internationalization locales as well as the POSIX locale provided on all systems.
- Chapter 8 describes the use of environment variables for internationalization and other purposes.
- Chapter 9 describes the syntax of pattern matching using regular expressions employed by many utilities and matched by the *regcomp*( ) and *regexec*( ) functions.
- Chapter 10 describes files and devices found on all systems.
- Chapter 11 describes the asynchronous terminal interface for many of the functions in the System Interfaces volume and the *stty* utility in the Shell and Utilities volume.
- Chapter 12 describes the policies for command line argument construction and parsing.
- Chapter 13 defines the contents of headers which declare constants, macros, and data structures that are needed by programs using the services provided by the System Interfaces volume.

Comprehensive references are available in the index.

Typographical Conventions

The following typographical conventions are used throughout this standard. In the text, this standard is referred to as IEEE Std 1003.1-2001, which is technically identical to The Open Group Base Specifications, Issue 6.

The typographical conventions listed here are for ease of reading only. Editorial inconsistencies in the use of typography are unintentional and have no normative meaning in this standard.

Reference	Example	Notes
C-Language Data Structure	**aiocb**	
C-Language Data Structure Member	*aio_lio_opcode*	
C-Language Data Type	**long**	
C-Language External Variable	*errno*	
C-Language Function	*system*( )	

Reference	Example	Notes
C-Language Function Argument	*arg1*	
C-Language Function Family	*exec*	
C-Language Header	**<sys/stat.h>**	
C-Language Keyword	**return**	
C-Language Macro with Argument	*assert*( )	
C-Language Macro with No Argument	INET_ADDRSTRLEN	
C-Language Preprocessing Directive	**#define**	
Commands within a Utility	**a**, **c**	
Conversion Specification, Specifier / Modifier Character	%A, g, E	1
Environment Variable	*PATH*	
Error Number	[EINTR]	
Example Output	**Hello, World**	
Filename	**/tmp**	
Literal Character	'c', '\r', '\'	2
Literal String	"abcde"	2
Optional Items in Utility Syntax	**[ ]**	
Parameter	<*directory pathname*>	
Special Character	<newline>	3
Symbolic Constant	_POSIX_VDISABLE	
Symbolic Limit, Configuration Value	{LINE_MAX}	4
Syntax	#include <sys/stat.h>	
User Input and Example Code	echo Hello, World	5
Utility Name	*awk*	
Utility Operand	*file_name*	
Utility Option	**–c**	
Utility Option with Option-Argument	**–w** *width*	

Notes:

1. Conversion specifications, specifier characters, and modifier characters are used primarily in date-related functions and utilities and the *fprintf* and *fscanf* formatting functions.
2. Unless otherwise noted, the quotes shall not be used as input or output. When used in a list item, the quotes are omitted. For literal characters, '\' (or any of the other sequences such as ''') is the same as the C constant '\\' (or '\'').
3. The style selected for some of the special characters, such as <newline>, matches the form of the input given to the *localedef* utility. Generally, the characters selected for this special treatment are those that are not visually distinct, such as the control characters <tab> or <newline>.
4. Names surrounded by braces represent symbolic limits or configuration values which may be declared in appropriate headers by means of the C **#define** construct.
5. Brackets shown in this font, "[ ]", are part of the syntax and do *not* indicate optional items. In syntax the '|' symbol is used to separate alternatives, and ellipses ("...") are used to show that additional arguments are optional.

Shading is used to identify extensions and options; see Section 1.5.1 (on page 6).

Footnotes and notes within the body of the normative text are for information only (informative).

Informative sections (such as Rationale, Change History, Application Usage, and so on) are denoted by continuous shading bars in the margins.

Ranges of values are indicated with parentheses or brackets as follows:

- (*a*,*b*) means the range of all values from *a* to *b*, including neither *a* nor *b*.
- [*a*,*b*] means the range of all values from *a* to *b*, including *a* and *b*.
- [*a*,*b*) means the range of all values from *a* to *b*, including *a*, but not *b*.
- (*a*,*b*] means the range of all values from *a* to *b*, including *b*, but not *a*.

Note: A symbolic limit beginning with POSIX is treated differently, depending on context. In a C-language header, the symbol POSIX*string* (where *string* may contain underscores) is represented by the C identifier _POSIX*string*, with a leading underscore required to prevent ISO C standard name space pollution. However, in other contexts, such as languages other than C, the leading underscore is not used because this requirement does not exist.

Participants

IEEE Std 1003.1-2001 was prepared by the Austin Group, sponsored by the Portable Applications Standards Committee of the IEEE Computer Society, The Open Group, and ISO / SC22 WG15.

The Austin Group

At the time of approval, the membership of the Austin Group was as follows:

Andrew Josey, Chair
Donald W. Cragun, Organizational Representative, IEEE PASC
Nicholas Stoughton, Organizational Representative, ISO / SC22 WG15
Mark Brown, Organizational Representative, The Open Group
Cathy Hughes, Technical Editor

Austin Group Technical Reviewers

Peter Anvin
Bouazza Bachar
Theodore P. Baker
Walter Briscoe
Mark Brown
Dave Butenhof
Geoff Clare
Donald W. Cragun
Lee Damico
Ulrich Drepper
Paul Eggert
Joanna Farley
Clive D.W. Feather
Andrew Gollan
Michael Gonzalez
Joseph M. Gwinn
Jon Hitchcock
Yvette Ho Sang
Cathy Hughes
Lowell G. Johnson
Andrew Josey
Michael Kavanaugh
David Korn
Marc Aurele La France
Jim Meyering
Gary Miller
Finnbarr P. Murphy
Joseph S. Myers
Sandra O'Donnell
Frank Prindle
Curtis Royster Jr.
Glen Seeds
Keld Jorn Simonsen
Raja Srinivasan
Nicholas Stoughton
Donn S. Terry
Fred Tydeman
Peter Van Der Veen
James Youngman
Jim Zepeda
Jason Zions

Austin Group Working Group Members

Harold C. Adams
Peter Anvin
Pierre-Jean Arcos
Jay Ashford
Bouazza Bachar
Theodore P. Baker
Robert Barned
Joel Berman
David J. Blackwood
Shirley Bockstahler-Brandt
James Bottomley
Walter Briscoe
Andries Brouwer
Mark Brown
Eric W. Burger
Alan Burns
Andries Brouwer
Dave Butenhof
Keith Chow
Geoff Clare
Donald W. Cragun
Lee Damico
Juan Antonio De La Puente
Ming De Zhou
Steven J. Dovich
Richard P. Draves
Ulrich Drepper
Paul Eggert
Philip H. Enslow
Joanna Farley
Clive D.W. Feather
Pete Forman
Mark Funkenhauser
Lois Goldthwaite
Andrew Gollan
Michael Gonzalez
Karen D. Gordon
Joseph M. Gwinn
Steven A. Haaser
Charles E. Hammons
Chris J. Harding
Barry Hedquist
Vincent E. Henley
Karl Heubaum
Jon Hitchcock
Yvette Ho Sang
Niklas Holsti
Thomas Hosmer
Cathy Hughes
Jim D. Isaak
Lowell G. Johnson
Michael B. Jones
Andrew Josey
Michael J. Karels
Michael Kavanaugh
David Korn
Steven Kramer
Thomas M. Kurihara
Marc Aurele La France
C. Douglass Locke
Nick Maclaren
Roger J. Martin
Craig H. Meyer
Jim Meyering
Gary Miller
Finnbarr P. Murphy
Joseph S. Myers
John Napier
Peter E. Obermayer
James T. Oblinger
Sandra O'Donnell
Frank Prindle
Francois Riche
John D. Riley
Andrew K. Roach
Helmut Roth
Jaideep Roy
Curtis Royster Jr.
Stephen C. Schwarm
Glen Seeds
Richard Seibel
David L. Shroads Jr.
W. Olin Sibert
Keld Jorn Simonsen
Curtis Smith
Raja Srinivasan
Nicholas Stoughton
Marc J. Teller
Donn S. Terry
Fred Tydeman
Mark-Rene Uchida
Scott A. Valcourt
Peter Van Der Veen
Michael W. Vannier
Eric Vought
Frederick N. Webb
Paul A.T. Wolfgang
Garrett A. Wollman
James Youngman
Oren Yuen
Janusz Zalewski
Jim Zepeda
Jason Zions

The Open Group

When The Open Group approved the Base Specifications, Issue 6 on 12 September 2001, the membership of The Open Group Base Working Group was as follows:

Andrew Josey, Chair
Finnbarr P. Murphy, Vice-Chair
Mark Brown, Austin Group Liaison
Cathy Hughes, Technical Editor

Base Working Group Members

Bouazza Bachar
Mark Brown
Dave Butenhof
Donald W. Cragun
Larry Dwyer
Joanna Farley
Andrew Gollan
Karen D. Gordon
Gary Miller
Finnbarr P. Murphy
Frank Prindle
Andrew K. Roach
Curtis Royster Jr.
Nicholas Stoughton
Kenjiro Tsuji

IEEE

When the IEEE Standards Board approved IEEE Std 1003.1-2001 on 6 December 2001, the membership of the committees was as follows:

Portable Applications Standards Committee (PASC)

Lowell G. Johnson, Chair
Joseph M. Gwinn, Vice-Chair
Jay Ashford, Functional Chair
Andrew Josey, Functional Chair
Curtis Royster Jr., Functional Chair
Nicholas Stoughton, Secretary

Balloting Committee

The following members of the balloting committee voted on IEEE Std 1003.1-2001. Balloters may have voted for approval, disapproval, or abstention:

Harold C. Adams
Pierre-Jean Arcos
Jay Ashford
Theodore P. Baker
Robert Barned
David J. Blackwood
Shirley Bockstahler-Brandt
James Bottomley
Mark Brown
Eric W. Burger
Alan Burns
Dave Butenhof
Keith Chow
Donald W. Cragun
Juan Antonio De La Puente
Ming De Zhou
Steven J. Dovich
Richard P. Draves
Philip H. Enslow
Michael Gonzalez
Karen D. Gordon
Joseph M. Gwinn
Steven A. Haaser
Charles E. Hammons
Chris J. Harding
Barry Hedquist
Vincent E. Henley
Karl Heubaum
Niklas Holsti
Thomas Hosmer
Jim D. Isaak
Lowell G. Johnson
Michael B. Jones
Andrew Josey
Michael J. Karels
Steven Kramer
Thomas M. Kurihara
C. Douglass Locke
Roger J. Martin
Craig H. Meyer
Finnbarr P. Murphy
John Napier
Peter E. Obermayer
James T. Oblinger
Frank Prindle
Francois Riche
John D. Riley
Andrew K. Roach
Helmut Roth
Jaideep Roy
Curtis Royster Jr.
Stephen C. Schwarm
Richard Seibel
David L. Shroads Jr.
W. Olin Sibert
Keld Jorn Simonsen
Nicholas Stoughton
Donn S. Terry
Mark-Rene Uchida
Scott A. Valcourt
Michael W. Vannier
Frederick N. Webb
Paul A.T. Wolfgang
Oren Yuen
Janusz Zalewski

The following organizational representative voted on this standard:

Andrew Josey, X/Open Company Ltd.

IEEE-SA Standards Board

When the IEEE-SA Standards Board approved IEEE Std 1003.1-2001 on 6 December 2001, it had the following membership:

Donald N. Heirman, Chair
James T. Carlo, Vice-Chair
Judith Gorman, Secretary

Satish K. Aggarwal	James H. Gurney	James W. Moore
Mark D. Bowman	Richard J. Holleman	Robert F. Munzner
Gary R. Engmann	Lowell G. Johnson	Ronald C. Petersen
Harold E. Epstein	Robert J. Kennelly	Gerald H. Peterson
H. Landis Floyd	Joseph L. Koepfinger*	John B. Posey
Jay Forster*	Peter H. Lips	Gary S. Robinson
Howard M. Frazier	L. Bruce McClung	Akio Tojo
Ruben D. Garzon	Daleep C. Mohla	Donald W. Zipse

Also included are the following non-voting IEEE-SA Standards Board liaisons:

Alan Cookson, NIST Representative
Donald R. Volzka, TAB Representative
Yvette Ho Sang, **Don Messina**, **Savoula Amanatidis**, IEEE Project Editors

* Member Emeritus

IEEE Std 1003.1-2001/Cor 1-2002 was prepared by the Austin Group, sponsored by the Portable Applications Standards Committee of the IEEE Computer Society, The Open Group, and ISO/IEC JTC 1/SC22/WG15.

The Austin Group

At the time of approval, the membership of the Austin Group was as follows:

Andrew Josey, Chair
Donald W. Cragun, Organizational Representative, IEEE PASC
Nicholas Stoughton, Organizational Representative, ISO/IEC JTC 1/SC22/WG15
Mark Brown, Organizational Representative, The Open Group
Cathy Fox, Technical Editor

Austin Group Technical Reviewers

Theodore P. Baker
Julian Blake
Andries Brouwer
Mark Brown
Dave Butenhof
Geoff Clare
Donald W. Cragun
Ken Dawson
Ulrich Drepper
Larry Dwyer
Paul Eggert
Joanna Farley
Clive D.W. Feather
Cathy Fox
Mark Funkenhauser
Lois Goldthwaite
Andrew Gollan
Michael Gonzalez
Bruno Haible
Ben Harris
Jon Hitchcock
Andreas Jaeger
Andrew Josey
Jonathan Lennox
Nick Maclaren
Jack McCann
Wilhelm Mueller
Joseph S. Myers
Frank Prindle
Kenneth Raeburn
Tim Robbins
Glen Seeds
Matthew Seitz
Keld Jorn Simonsen
Nicholas Stoughton
Alexander Terekhov
Donn S. Terry
Mike Wilson
Garrett A. Wollman
Mark Ziegast

Austin Group Working Group Members

Harold C. Adams
Alejandro Alonso
Jay Ashford
Theodore P. Baker
David J. Blackwood
Julian Blake
Mitchell Bonnett
Andries Brouwer
Mark Brown
Eric W. Burger
Alan Burns
Dave Butenhof
Keith Chow
Geoff Clare
Luis Cordova
Donald W. Cragun
Dragan Cvetkovic
Lee Damico
Ken Dawson
Jeroen Dekkers
Juan Antonio De La Puente
Steven J. Dovich
Ulrich Drepper
Dr. Sourav Dutta
Larry Dwyer
Paul Eggert
Joanna Farley
Clive D.W. Feather
Yaacov Fenster
Cathy Fox
Mark Funkenhauser
Lois Goldthwaite
Andrew Gollan
Michael Gonzalez
Karen D. Gordon
Scott Gudgel
Joseph M. Gwinn
Steven A. Haaser
Bruno Haible
Charles E. Hammons
Bryan Harold
Ben Harris
Barry Hedquist
Karl Heubaum
Jon Hitchcock
Andreas Jaeger
Andrew Josey
Kenneth Lang
Pi-Cheng Law
Jonathan Lennox
Nick Maclaren
Roger J. Martin
Jack McCann
George Miao
Wilhelm Mueller
Finnbarr P. Murphy
Joseph S. Myers
Alexey Neyman
Charles Ngethe
Peter Petrov
Frank Prindle
Vikram Punj
Kenneth Raeburn
Francois Riche
Tim Robbins
Curtis Royster Jr.
Diane Schleicher
Gil Shultz
Stephen C. Schwarm
Glen Seeds
Matthew Seitz
Keld Jorn Simonsen
Doug Stevenson
Nicholas Stoughton
Alexander Terekhov
Donn S. Terry
Mike Wilson
Garrett A. Wollman
Oren Yuen
Mark Ziegast

The Open Group

When The Open Group approved the Base Specifications, Issue 6, Technical Corrigendum 1 on 7 February 2003, the membership of The Open Group Base Working Group was as follows:

Andrew Josey, Chair
Finnbarr P. Murphy, Vice-Chair
Mark Brown, Austin Group Liaison
Cathy Fox, Technical Editor

Base Working Group Members

Mark Brown
Dave Butenhof
Donald W. Cragun
Larry Dwyer
Ulrich Drepper
Joanna Farley
Andrew Gollan
Finnbarr P. Murphy
Frank Prindle
Andrew K. Roach
Curtis Royster Jr.
Nicholas Stoughton
Kenjiro Tsuji

IEEE

When the IEEE Standards Board approved IEEE Std 1003.1-2001/Cor 1-2002 on 11 December 2002, the membership of the committees was as follows:

Portable Applications Standards Committee (PASC)

Lowell G. Johnson, Chair
Joseph M. Gwinn, Vice-Chair
Jay Ashford, Functional Chair
Andrew Josey, Functional Chair
Curtis Royster Jr., Functional Chair
Nicholas Stoughton, Secretary

Balloting Committee

The following members of the balloting committee voted on IEEE Std 1003.1-2001/Cor 1-2002. Balloters may have voted for approval, disapproval, or abstention:

Alejandro Alonso
Jay Ashford
David J. Blackwood
Julian Blake
Mitchell Bonnett
Mark Brown
Dave Butenhof
Keith Chow
Luis Cordova
Donald W. Cragun
Steven J. Dovich
Dr. Sourav Dutta
Yaacov Fenster
Michael Gonzalez
Scott Gudgel
Charles E. Hammons
Bryan Harold
Barry Hedquist
Karl Heubaum
Lowell G. Johnson
Andrew Josey
Kenneth Lang
Pi-Cheng Law
George Miao
Roger J. Martin
Finnbarr P. Murphy
Charles Ngethe
Peter Petrov
Frank Prindle
Vikram Punj
Francois Riche
Curtis Royster Jr.
Diane Schleicher
Stephen C. Schwarm
Gil Shultz
Nicholas Stoughton
Donn S. Terry
Oren Yuen
Juan A. de la Puente

IEEE-SA Standards Board

When the IEEE-SA Standards Board approved IEEE Std 1003.1-2001/Cor 1-2002 on 11 December 2002, the membership was as follows:

James T. Carlo, Chair
James H. Gurney, Vice-Chair
Judith Gorman, Secretary

Sid Bennett	Arnold M. Greenspan	Daleep C. Mohla
H. Stephen Berger	Raymond Hapeman	William J. Moylan
Clyde R. Camp	Donald M. Heirman	Malcolm V. Thaden
Richard DeBlasio	Richard H. Hulett	Geoffrey O. Thompson
Harold E. Epstein	Lowell G. Johnson	Howard L. Wolfman
Julian Forster*	Joseph L. Koepfinger*	Don Wright
Howard M. Frazier	Peter H. Lips	
Toshio Fukuda	Nader Mehravari	

Also included are the following non-voting IEEE-SA Standards Board liaisons:

Alan Cookson, NIST Representative
Satish K. Aggarwal, NRC Representative
Savoula Amanatidis, IEEE Standards Managing Editor

* Member Emeritus

IEEE Std 1003.1-2001/Cor 2-2004 was prepared by the Austin Group, sponsored by the Portable Applications Standards Committee of the IEEE Computer Society, The Open Group, and ISO/IEC JTC 1/SC22/WG15.

The Austin Group

At the time of approval, the membership of the Austin Group was as follows:

Andrew Josey, Chair
Donald W. Cragun, Organizational Representative, IEEE PASC
Nicholas Stoughton, Organizational Representative, ISO/IEC JTC 1/SC22/WG15
Mark Brown, Organizational Representative, The Open Group

Cathy Fox, Technical Editor

Austin Group Technical Reviewers

Jay Ashford
Julian Blake
Mitchell Bonnett
Andries Brouwer
Mark Brown
Paul Buerger
Dave Butenhof
Keith Chow
Geoff Clare
Donald W. Cragun
Lee Damico
Maulik Dave
Juan A. de la Puente
Guru Dutt Dhingra
Loic Domaigne
Ulrich Drepper
Sourav Dutta
Larry Dwyer
Paul Eggert
Joanna Farley
Clive D.W. Feather
Yaacov Fenster
Mark Funkenhauser
Ernesto Garcia
Andrew Gollan
Michael Gonzalez
Jean-Denis Gorin
Matthew Gream
Scott Gudgel
Bruno Haible
Charles Hammons
Barry Hedquist
Jon Hitchcock
Lowell G. Johnson
Andrew Josey
Piotr Karocki
David Leciston
Ryan Madron
Roger J. Martin
George Miao
Rajesh Moorkath
Peter Petrov
Franklin Prindle
Vikram Punj
Eusebio Rufian-Zilbermann
Joerg Schilling
Stephen Schwarm
Gil Shultz
Keld Simonsen
Nicholas Stoughton
Alexander Terekhov
Donn Terry
Mark-Rene Uchida
Thomas Unsicker
Scott Valcourt
Mats Wichmann
Garrett A. Wollman
Oren Yuen
Mark Ziegast

Austin Group Working Group Members

Harold C. Adams
Jay Ashford
Theodore P. Baker
David J. Blackwood
Julian Blake
Mitchell Bonnett
Andries Brouwer
Mark Brown
Paul Buerger
Alan Burns
Dave Butenhof
Keith Chow
Geoff Clare
Donald W. Cragun
Dragan Cvetkovic
Lee Damico
Maulik Dave
Juan A. de la Puente
Loic Domaigne
Steven J. Dovich
Ulrich Drepper
Guru Dutt Dhingra
Sourav Dutta
Larry Dwyer
Paul Eggert
Joanna Farley
Clive D.W. Feather
Yaacov Fenster
Mark Funkenhauser
Ernesto Garcia
Lois Goldthwaite
Andrew Gollan
Michael Gonzalez
Karen D. Gordon
Jean-Denis Gorin
Matthew Gream
Scott Gudgel
Joseph M. Gwinn
Steven A. Haaser
Charles Hammons
Ben Harris
Barry Hedquist
Karl Heubaum
Jon Hitchcock
Andreas Jaeger
Lowell G. Johnson
Andrew Josey
Piotr Karocki
Kenneth Lang
Pi-Cheng Law
David Leciston
Wojtek Lerch
Jonathan Lennox
Nick Maclaren
Ryan Madron
Roger J. Martin
George Miao
Rajesh Moorkath
Vilhelm Mueller
Joseph S. Myers
Peter Petrov
Franklin Prindle
Vikram Punj
Kenneth Raeburn
Tim Robbins
Curtis Royster Jr.
Eusebio Rufian-Zilbermann
Joerg Schilling
Stephen Schwarm
Glen Seeds
Gil Shultz
Keld Simonsen
Nicholas Stoughton
Alexander Terekhov
Donn Terry
Mark-Rene Uchida
Thomas Unsicker
Scott Valcourt
Mats Wichmann
Mike Wilson
Garrett A. Wollman
Oren Yuen
Mark Ziegast
Jason Zions

The Open Group

When The Open Group approved the Base Specifications, Issue 6, Technical Corrigendum 2 on 18 December 2003, the membership of The Open Group Base Working Group was as follows:

Andrew Josey, Chair
Mark Brown, Austin Group Liaison

Cathy Fox, Technical Editor

Base Working Group Members

Mark Brown	IBM Corporation
Dave Butenhof	Hewlett-Packard Company
Donald W. Cragun	Sun Microsystems, Inc.
Larry Dwyer	Hewlett-Packard Company
Ulrich Drepper	Red Hat, Inc.
Joanna Farley	Sun Microsystems, Inc.
Andrew Gollan	Sun Microsystems, Inc.
Andrew K. Roach	Sun Microsystems, Inc.
Curtis Royster Jr.	US DoD DISA
Nicholas Stoughton	USENIX Association
Kenjiro Tsuji	Sun Microsystems, Inc.

IEEE

When the IEEE Standards Board approved IEEE Std 1003.1-2001/Cor 2-2004 on 9 February 2004, the membership of the committees was as follows:

Portable Applications Standards Committee (PASC)

Lowell G. Johnson, Chair
Joseph M. Gwinn, Vice-Chair
Jay Ashford, Functional Chair
Andrew Josey, Functional Chair
Curtis Royster Jr., Functional Chair
Nicholas Stoughton, Secretary

Balloting Committee

The following members of the balloting committee voted on IEEE Std 1003.1-2001/Cor 2-2004. Balloters may have voted for approval, disapproval, or abstention:

Jay Ashford
Julian Blake
Mark Brown
Keith Chow
Donald W. Cragun
Juan A. de la Puente
Guru Dutt Dhingra
Ernesto Garcia
Michael Gonzalez
Jean-Denis Gorin
Matthew Gream
Scott Gudgel
Charles Hammons
Barry Hedquist
Andrew Josey
Piotr Karocki
David Leciston
Ryan Madron
Roger J. Martin
George Miao
Rajesh Moorkath
Peter Petrov
Vikram Punj
Eusebio Rufian-Zilbermann
Stephen Schwarm
Gil Shultz
Mark-Rene Uchida
Thomas Unsicker
Scott Valcourt
Oren Yuen

IEEE-SA Standards Board

When the IEEE-SA Standards Board approved IEEE Std 1003.1-2001/Cor 2-2004 on 9 February 2004, the membership was as follows:

Don Wright, Chair
Judith Gorman, Secretary

Chuck Adams	Raymond Hapeman	Paul Nikolich
H. Stephen Berger	Richard J. Holleman	T. W. Olsen
Mark D. Bowman	Richard H. Hulett	Ronald C. Petersen
Joseph A. Bruder	Lowell G. Johnson	Gary S. Robinson
Bob Davis	Hermann Koch	Frank Stone
Roberto de Boisson	Joseph L. Koepfinger*	Malcolm V. Thaden
Julian Forster*	Thomas J. McGean	Doug Topping
Arnold M. Greenspan	Steve M. Mills	Joe D. Watson
Mark S. Halpin	Daleep C. Mohla	

Also included are the following non-voting IEEE-SA Standards Board liaisons:

Satish K. Aggarwal, NRC Representative
Richard DeBlasio, DOE Representative
Alan Cookson, NIST Representative

Savoula Amanatidis, IEEE Standards Managing Editor

* Member Emeritus

Trademarks

The following information is given for the convenience of users of this standard and does not constitute endorsement of these products by The Open Group or the IEEE. There may be other products mentioned in the text that might be covered by trademark protection and readers are advised to verify them independently.

1003.1™ is a trademark of the Institute of Electrical and Electronic Engineers, Inc.

AIX® is a registered trademark of IBM Corporation.

AT&T® is a registered trademark of AT&T in the U.S.A. and other countries.

BSD™ is a trademark of the University of California, Berkeley, U.S.A.

Hewlett-Packard®, HP®, and HP-UX® are registered trademarks of Hewlett-Packard Company.

IBM® is a registered trademark of International Business Machines Corporation.

Boundaryless Information Flow is a trademark and UNIX and The Open Group are registered trademarks of The Open Group in the United States and other countries.

All other trademarks are the property of their respective owners.

POSIX® is a registered trademark of the Institute of Electrical and Electronic Engineers, Inc.

Sun® and Sun Microsystems® are registered trademarks of Sun Microsystems, Inc.

/usr/group® is a registered trademark of UniForum, the International Network of UNIX System Users.

Acknowledgements

The contributions of the following organizations to the development of IEEE Std 1003.1-2001 are gratefully acknowledged:

- AT&T for permission to reproduce portions of its copyrighted System V Interface Definition (SVID) and material from the UNIX System V Release 2.0 documentation.
- The SC22 WG14 Committees.

This standard was prepared by the Austin Group, a joint working group of the IEEE, The Open Group, and ISO SC22 WG15.

Referenced Documents

Normative References

Normative references for this standard are defined in Section 1.3 (on page 4).

Informative References

The following documents are referenced in this standard:

1984 /usr/group Standard
/usr/group Standards Committee, Santa Clara, CA, UniForum 1984.

Almasi and Gottlieb
George S. Almasi and Allan Gottlieb, *Highly Parallel Computing*, The Benjamin/Cummings Publishing Company, Inc., 1989, ISBN: 0-8053-0177-1.

ANSI C
American National Standard for Information Systems: Standard X3.159-1989, Programming Language C.

ANSI X3.226-1994
American National Standard for Information Systems: Standard X3.226-1994, Programming Language Common LISP.

Brawer
Steven Brawer, *Introduction to Parallel Programming*, Academic Press, 1989, ISBN: 0-12-128470-0.

DeRemer and Pennello Article
DeRemer, Frank and Pennello, Thomas J., *Efficient Computation of LALR(1) Look-Ahead Sets*, SigPlan Notices, Volume 15, No. 8, August 1979.

Draft ANSI X3J11.1
IEEE Floating Point draft report of ANSI X3J11.1 (NCEG).

FIPS 151-1
Federal Information Procurement Standard (FIPS) 151-1. Portable Operating System Interface (POSIX)—Part 1: System Application Program Interface (API) [C Language].

FIPS 151-2
Federal Information Procurement Standards (FIPS) 151-2, Portable Operating System Interface (POSIX)— Part 1: System Application Program Interface (API) [C Language].

HP-UX Manual
Hewlett-Packard HP-UX Release 9.0 Reference Manual, Third Edition, August 1992.

IEC 60559: 1989
IEC 60559: 1989, Binary Floating-Point Arithmetic for Microprocessor Systems (previously designated IEC 559: 1989).

IEEE Std 754-1985
IEEE Std 754-1985, IEEE Standard for Binary Floating-Point Arithmetic.

IEEE Std 854-1987
IEEE Std 854-1987, IEEE Standard for Radix-Independent Floating-Point Arithmetic.

IEEE Std 1003.9-1992
IEEE Std 1003.9-1992, IEEE Standard for Information Technology — POSIX FORTRAN 77 Language Interfaces — Part 1: Binding for System Application Program Interface API.

IETF RFC 791
Internet Protocol, Version 4 (IPv4), September 1981.

IETF RFC 819
The Domain Naming Convention for Internet User Applications, Z. Su, J. Postel, August 1982.

IETF RFC 822
Standard for the Format of ARPA Internet Text Messages, D.H. Crocker, August 1982.

IETF RFC 919
Broadcasting Internet Datagrams, J. Mogul, October 1984.

IETF RFC 920
Domain Requirements, J. Postel, J. Reynolds, October 1984.

IETF RFC 921
Domain Name System Implementation Schedule, J. Postel, October 1984.

IETF RFC 922
Broadcasting Internet Datagrams in the Presence of Subnets, J. Mogul, October 1984.

IETF RFC 1034
Domain Names — Concepts and Facilities, P. Mockapetris, November 1987.

IETF RFC 1035
Domain Names — Implementation and Specification, P. Mockapetris, November 1987.

IETF RFC 1123
Requirements for Internet Hosts — Application and Support, R. Braden, October 1989.

IETF RFC 1886
DNS Extensions to Support Internet Protocol, Version 6 (IPv6), C. Huitema, S. Thomson, December 1995.

IETF RFC 2045
Multipurpose Internet Mail Extensions (MIME), Part 1: Format of Internet Message Bodies, N. Freed, N. Borenstein, November 1996.

IETF RFC 2181
Clarifications to the DNS Specification, R. Elz, R. Bush, July 1997.

IETF RFC 2373
Internet Protocol, Version 6 (IPv6) Addressing Architecture, S. Deering, R. Hinden, July 1998.

IETF RFC 2460
Internet Protocol, Version 6 (IPv6), S. Deering, R. Hinden, December 1998.

Internationalisation Guide
Guide, July 1993, Internationalisation Guide, Version 2 (ISBN: 1-859120-02-4, G304), published by The Open Group.

ISO C (1990)
ISO/IEC 9899:1990, Programming Languages — C, including Amendment 1:1995 (E), C Integrity (Multibyte Support Extensions (MSE) for ISO C).

ISO 2375: 1985
ISO 2375: 1985, Data Processing — Procedure for Registration of Escape Sequences.

ISO 8652: 1987
ISO 8652: 1987, Programming Languages — Ada (technically identical to ANSI standard 1815A-1983).

ISO / IEC 1539: 1990
ISO / IEC 1539: 1990, Information Technology — Programming Languages — Fortran (technically identical to the ANSI X3.9-1978 standard [FORTRAN 77]).

ISO / IEC 4873: 1991
ISO / IEC 4873: 1991, Information Technology — ISO 8-bit Code for Information Interchange — Structure and Rules for Implementation.

ISO / IEC 6429: 1992
ISO / IEC 6429: 1992, Information Technology — Control Functions for Coded Character Sets.

ISO / IEC 6937: 1994
ISO / IEC 6937: 1994, Information Technology — Coded Character Set for Text Communication — Latin Alphabet.

ISO / IEC 8802-3: 1996
ISO / IEC 8802-3: 1996, Information Technology — Telecommunications and Information Exchange Between Systems — Local and Metropolitan Area Networks — Specific Requirements — Part 3: Carrier Sense Multiple Access with Collision Detection (CSMA / CD) Access Method and Physical Layer Specifications.

ISO / IEC 8859
ISO / IEC 8859, Information Technology — 8-Bit Single-Byte Coded Graphic Character Sets:

Part 1: Latin Alphabet No. 1
Part 2: Latin Alphabet No. 2
Part 3: Latin Alphabet No. 3
Part 4: Latin Alphabet No. 4
Part 5: Latin / Cyrillic Alphabet
Part 6: Latin / Arabic Alphabet
Part 7: Latin / Greek Alphabet
Part 8: Latin / Hebrew Alphabet
Part 9: Latin Alphabet No. 5
Part 10: Latin Alphabet No. 6
Part 11: Latin / Thai Alphabet
Part 13: Latin Alphabet No. 7
Part 14: Latin Alphabet No. 8
Part 15: Latin Alphabet No. 9
Part 16: Latin Alphabet No. 10

ISO POSIX-1: 1996
ISO / IEC 9945-1: 1996, Information Technology — Portable Operating System Interface (POSIX) — Part 1: System Application Program Interface (API) [C Language] (identical to ANSI / IEEE Std 1003.1-1996). Incorporating ANSI / IEEE Stds 1003.1-1990, 1003.1b-1993, 1003.1c-1995, and 1003.1i-1995.

ISO POSIX-2: 1993
ISO / IEC 9945-2: 1993, Information Technology — Portable Operating System Interface (POSIX) — Part 2: Shell and Utilities (identical to ANSI / IEEE Std 1003.2-1992, as amended

by ANSI/IEEE Std 1003.2a-1992).

Issue 1
X/Open Portability Guide, July 1985 (ISBN: 0-444-87839-4).

Issue 2
X/Open Portability Guide, January 1987:

- Volume 1: XVS Commands and Utilities (ISBN: 0-444-70174-5)
- Volume 2: XVS System Calls and Libraries (ISBN: 0-444-70175-3)

Issue 3
X/Open Specification, 1988, 1989, February 1992:

- Commands and Utilities, Issue 3 (ISBN: 1-872630-36-7, C211); this specification was formerly X/Open Portability Guide, Issue 3, Volume 1, January 1989, XSI Commands and Utilities (ISBN: 0-13-685835-X, XO/XPG/89/002)
- System Interfaces and Headers, Issue 3 (ISBN: 1-872630-37-5, C212); this specification was formerly X/Open Portability Guide, Issue 3, Volume 2, January 1989, XSI System Interface and Headers (ISBN: 0-13-685843-0, XO/XPG/89/003)
- Curses Interface, Issue 3, contained in Supplementary Definitions, Issue 3 (ISBN: 1-872630-38-3, C213), Chapters 9 to 14 inclusive; this specification was formerly X/Open Portability Guide, Issue 3, Volume 3, January 1989, XSI Supplementary Definitions (ISBN: 0-13-685850-3, XO/XPG/89/004)
- Headers Interface, Issue 3, contained in Supplementary Definitions, Issue 3 (ISBN: 1-872630-38-3, C213), Chapter 19, Cpio and Tar Headers; this specification was formerly X/Open Portability Guide Issue 3, Volume 3, January 1989, XSI Supplementary Definitions (ISBN: 0-13-685850-3, XO/XPG/89/004)

Issue 4
CAE Specification, July 1992, published by The Open Group:

- System Interface Definitions (XBD), Issue 4 (ISBN: 1-872630-46-4, C204)
- Commands and Utilities (XCU), Issue 4 (ISBN: 1-872630-48-0, C203)
- System Interfaces and Headers (XSH), Issue 4 (ISBN: 1-872630-47-2, C202)

Issue 4, Version 2
CAE Specification, August 1994, published by The Open Group:

- System Interface Definitions (XBD), Issue 4, Version 2 (ISBN: 1-85912-036-9, C434)
- Commands and Utilities (XCU), Issue 4, Version 2 (ISBN: 1-85912-034-2, C436)
- System Interfaces and Headers (XSH), Issue 4, Version 2 (ISBN: 1-85912-037-7, C435)

Issue 5
Technical Standard, February 1997, published by The Open Group:

- System Interface Definitions (XBD), Issue 5 (ISBN: 1-85912-186-1, C605)
- Commands and Utilities (XCU), Issue 5 (ISBN: 1-85912-191-8, C604)
- System Interfaces and Headers (XSH), Issue 5 (ISBN: 1-85912-181-0, C606)

Knuth Article
Knuth, Donald E., *On the Translation of Languages from Left to Right*, Information and Control, Volume 8, No. 6, October 1965.

KornShell
: Bolsky, Morris I. and Korn, David G., *The New KornShell Command and Programming Language*, March 1995, Prentice Hall.

MSE Working Draft
: Working draft of ISO/IEC 9899:1990/Add3:Draft, Addendum 3 — Multibyte Support Extensions (MSE) as documented in the ISO Working Paper SC22/WG14/N205 dated 31 March 1992.

POSIX.0:1995
: IEEE Std 1003.0-1995, IEEE Guide to the POSIX Open System Environment (OSE) (identical to ISO/IEC TR 14252).

POSIX.1:1988
: IEEE Std 1003.1-1988, IEEE Standard for Information Technology — Portable Operating System Interface (POSIX) — Part 1: System Application Program Interface (API) [C Language].

POSIX.1:1990
: IEEE Std 1003.1-1990, IEEE Standard for Information Technology — Portable Operating System Interface (POSIX) — Part 1: System Application Program Interface (API) [C Language].

POSIX.1a
: P1003.1a, Standard for Information Technology — Portable Operating System Interface (POSIX) — Part 1: System Application Program Interface (API) — (C Language) Amendment.

POSIX.1d:1999
: IEEE Std 1003.1d-1999, IEEE Standard for Information Technology — Portable Operating System Interface (POSIX) — Part 1: System Application Program Interface (API) — Amendment 4: Additional Realtime Extensions [C Language].

POSIX.1g:2000
: IEEE Std 1003.1g-2000, IEEE Standard for Information Technology — Portable Operating System Interface (POSIX) — Part 1: System Application Program Interface (API) — Amendment 6: Protocol-Independent Interfaces (PII).

POSIX.1j:2000
: IEEE Std 1003.1j-2000, IEEE Standard for Information Technology — Portable Operating System Interface (POSIX) — Part 1: System Application Program Interface (API) — Amendment 5: Advanced Realtime Extensions [C Language].

POSIX.1q:2000
: IEEE Std 1003.1q-2000, IEEE Standard for Information Technology — Portable Operating System Interface (POSIX) — Part 1: System Application Program Interface (API) — Amendment 7: Tracing [C Language].

POSIX.2b
: P1003.2b, Standard for Information Technology — Portable Operating System Interface (POSIX) — Part 2: Shell and Utilities — Amendment.

POSIX.2d:-1994
: IEEE Std 1003.2d-1994, IEEE Standard for Information Technology — Portable Operating System Interface (POSIX) — Part 2: Shell and Utilities — Amendment 1: Batch Environment.

POSIX.13:-1998

IEEE Std 1003.13:1998, IEEE Standard for Information Technology — Standardized Application Environment Profile (AEP) — POSIX Realtime Application Support.

Sarwate Article

Sarwate, Dilip V., *Computation of Cyclic Redundancy Checks via Table Lookup*, Communications of the ACM, Volume 30, No. 8, August 1988.

Sprunt, Sha, and Lehoczky

Sprunt, B., Sha, L., and Lehoczky, J.P., *Aperiodic Task Scheduling for Hard Real-Time Systems*, The Journal of Real-Time Systems, Volume 1, 1989, Pages 27-60.

SVID, Issue 1

American Telephone and Telegraph Company, System V Interface Definition (SVID), Issue 1; Morristown, NJ, UNIX Press, 1985.

SVID, Issue 2

American Telephone and Telegraph Company, System V Interface Definition (SVID), Issue 2; Morristown, NJ, UNIX Press, 1986.

SVID, Issue 3

American Telephone and Telegraph Company, System V Interface Definition (SVID), Issue 3; Morristown, NJ, UNIX Press, 1989.

The AWK Programming Language

Aho, Alfred V., Kernighan, Brian W., and Weinberger, Peter J., *The AWK Programming Language*, Reading, MA, Addison-Wesley 1988.

UNIX Programmer's Manual

American Telephone and Telegraph Company, *UNIX Time-Sharing System: UNIX Programmer's Manual*, 7th Edition, Murray Hill, NJ, Bell Telephone Laboratories, January 1979.

XNS, Issue 4

CAE Specification, August 1994, Networking Services, Issue 4 (ISBN: 1-85912-049-0, C438), published by The Open Group.

XNS, Issue 5

CAE Specification, February 1997, Networking Services, Issue 5 (ISBN: 1-85912-165-9, C523), published by The Open Group.

XNS, Issue 5.2

Technical Standard, January 2000, Networking Services (XNS), Issue 5.2 (ISBN: 1-85912-241-8, C808), published by The Open Group.

X/Open Curses, Issue 4, Version 2

CAE Specification, May 1996, X/Open Curses, Issue 4, Version 2 (ISBN: 1-85912-171-3, C610), published by The Open Group.

Yacc

Yacc: Yet Another Compiler Compiler, Stephen C. Johnson, 1978.

Source Documents

Parts of the following documents were used to create the base documents for this standard:

AIX 3.2 Manual

AIX Version 3.2 For RISC System/6000, Technical Reference: Base Operating System and Extensions, 1990, 1992 (Part No. SC23-2382-00).

OSF/1

OSF/1 Programmer's Reference, Release 1.2 (ISBN: 0-13-020579-6).

OSF AES

Application Environment Specification (AES) Operating System Programming Interfaces Volume, Revision A (ISBN: 0-13-043522-8).

System V Release 2.0

— UNIX System V Release 2.0 Programmer's Reference Manual (April 1984 - Issue 2).

— UNIX System V Release 2.0 Programming Guide (April 1984 - Issue 2).

System V Release 4.2

Operating System API Reference, UNIX SVR4.2 (1992) (ISBN: 0-13-017658-3).

Chapter 1

Introduction

1.1 Scope

IEEE Std 1003.1-2001 defines a standard operating system interface and environment, including a command interpreter (or ‘‘shell’’), and common utility programs to support applications portability at the source code level. It is intended to be used by both applications developers and system implementors.

IEEE Std 1003.1-2001 comprises four major components (each in an associated volume):

1. General terms, concepts, and interfaces common to all volumes of IEEE Std 1003.1-2001, including utility conventions and C-language header definitions, are included in the Base Definitions volume of IEEE Std 1003.1-2001.
2. Definitions for system service functions and subroutines, language-specific system services for the C programming language, function issues, including portability, error handling, and error recovery, are included in the System Interfaces volume of IEEE Std 1003.1-2001.
3. Definitions for a standard source code-level interface to command interpretation services (a ‘‘shell’’) and common utility programs for application programs are included in the Shell and Utilities volume of IEEE Std 1003.1-2001.
4. Extended rationale that did not fit well into the rest of the document structure, containing historical information concerning the contents of IEEE Std 1003.1-2001 and why features were included or discarded by the standard developers, is included in the Rationale (Informative) volume of IEEE Std 1003.1-2001.

The following areas are outside of the scope of IEEE Std 1003.1-2001:

- Graphics interfaces
- Database management system interfaces
- Record I/O considerations
- Object or binary code portability
- System configuration and resource availability

IEEE Std 1003.1-2001 describes the external characteristics and facilities that are of importance to applications developers, rather than the internal construction techniques employed to achieve these capabilities. Special emphasis is placed on those functions and facilities that are needed in a wide variety of commercial applications.

The facilities provided in IEEE Std 1003.1-2001 are drawn from the following base documents:

- IEEE Std 1003.1-1996 (POSIX-1) (incorporating IEEE Stds 1003.1-1990, 1003.1b-1993, 1003.1c-1995, and 1003.1i-1995)
- The following amendments to the POSIX.1-1990 standard:
  - IEEE P1003.1a draft standard (Additional System Services)
  - IEEE Std 1003.1d-1999 (Additional Realtime Extensions)

— IEEE Std 1003.1g-2000 (Protocol-Independent Interfaces (PII))

— IEEE Std 1003.1j-2000 (Advanced Realtime Extensions)

— IEEE Std 1003.1q-2000 (Tracing)

- IEEE Std 1003.2-1992 (POSIX-2) (includes IEEE Std 1003.2a-1992)
- The following amendments to the ISO POSIX-2: 1993 standard:

  — IEEE P1003.2b draft standard (Additional Utilities)

  — IEEE Std 1003.2d-1994 (Batch Environment)

- Open Group Technical Standard, February 1997, System Interface Definitions, Issue 5 (XBD5) (ISBN: 1-85912-186-1, C605)
- Open Group Technical Standard, February 1997, Commands and Utilities, Issue 5 (XCU5) (ISBN: 1-85912-191-8, C604)
- Open Group Technical Standard, February 1997, System Interfaces and Headers, Issue 5 (XSH5) (in 2 Volumes) (ISBN: 1-85912-181-0, C606)

  Note: XBD5, XCU5, and XSH5 are collectively referred to as the *Base Specifications*.

- Open Group Technical Standard, January 2000, Networking Services, Issue 5.2 (XNS5.2) (ISBN: 1-85912-241-8, C808)
- ISO / IEC 9899: 1999, Programming Languages — C.

IEEE Std 1003.1-2001 uses the Base Specifications as its organizational basis and adds the following additional functionality to them, drawn from the base documents above:

- Normative text from the ISO POSIX-1: 1996 standard and the ISO POSIX-2: 1993 standard not included in the Base Specifications
- The amendments to the POSIX.1-1990 standard and the ISO POSIX-2: 1993 standard listed above, except for parts of IEEE Std 1003.1g-2000
- Portability Considerations
- Additional rationale and notes

The following features, marked legacy or obsolescent in the base documents, are not carried forward into IEEE Std 1003.1-2001. Other features from the base documents marked legacy or obsolescent are carried forward unless otherwise noted.

From XSH5, the following legacy interfaces, headers, and external variables are not carried forward:

advance( ), *brk*( ), *chroot*( ), *compile*( ), *cuserid*( ), *gamma*( ), *getdtablesize*( ), *getpagesize*( ), *getpass*( ), *getw*( ), *putw*( ), *re_comp*( ), *re_exec*( ), *regcmp*( ), *regex*( ), *sbrk*( ), *sigstack*( ), *step*( ), *ttyslot*( ), *valloc*( ), *wait3*( ), **<re_comp.h>**, **<regexp.h>**, **<varargs.h>**, *loc1*, *__loc1*, *loc2*, *locs*

From XCU5, the following legacy utilities are not carried forward:

calendar, *cancel*, *cc*, *col*, *cpio*, *cu*, *dircmp*, *dis*, *egrep*, *fgrep*, *line*, *lint*, *lpstat*, *mail*, *pack*, *pcat*, *pg*, *spell*, *sum*, *tar*, *unpack*, *uulog*, *uuname*, *uupick*, *uuto*

In addition, legacy features within non-legacy reference pages (for example, headers) are not carried forward.

From the ISO POSIX-1: 1996 standard, the following obsolescent features are not carried forward:

Page 112, CLK_TCK
Page 197 *tcgetattr*( ) rate returned option

From the ISO POSIX-2: 1993 standard, obsolescent features within the following pages are not carried forward:

Page 75, zero-length prefix within *PATH*
Page 156, 159 *set*
Page 178, *awk*, use of no argument and no parentheses with length
Page 259, *ed*
Page 272, *env*
Page 282, *find* –**perm**[–]*onum*
Page 295-296, *egrep*
Page 299-300, *head*
Page 305-306, *join*
Page 309-310, *kill*
Page 431-433, 435-436, *sort*
Page 444-445, *tail*
Page 453, 455-456, *touch*
Page 464-465, *tty*
Page 472, *uniq*
Page 515-516, *ex*
Page 542-543, *expand*
Page 563-565, *more*
Page 574-576, *newgrp*
Page 578, *nice*
Page 594-596, *renice*
Page 597-598, *split*
Page 600-601, *strings*
Page 624-625, *vi*
Page 693, *lex*

The *c89* utility (which specified a compiler for the C Language specified by the ISO / IEC 9899: 1990 standard) has been replaced by a *c99* utility (which specifies a compiler for the C Language specified by the ISO / IEC 9899: 1999 standard).

From XSH5, text marked OH (Optional Header) has been reviewed on a case-by-case basis and removed where appropriate. The XCU5 text marked OF (Output Format Incompletely Specified) and UN (Possibly Unsupportable Feature) has been reviewed on a case-by-case basis and removed where appropriate.

For the networking interfaces, the base document is the XNS, Issue 5.2 specification. The following parts of the XNS, Issue 5.2 specification are out of scope and not included in IEEE Std 1003.1-2001:

- Part 3 (XTI)
- Part 4 (Appendixes)

Since there is much duplication between the XNS, Issue 5.2 specification and IEEE Std 1003.1g-2000, material only from the following sections of IEEE Std 1003.1g-2000 has been included:

- General terms related to sockets (Section 2.2.2)
- Socket concepts (Sections 5.1 through 5.3, inclusive)

- The *pselect*( ) function (Sections 6.2.2.1 and 6.2.3)
- The *sockatmark*( ) function (Section 5.4.13)
- The **<sys/select.h>** header (Section 6.2)

Emphasis is placed on standardizing existing practice for existing users, with changes and additions limited to correcting deficiencies in the following areas:

- Issues raised by IEEE or ISO / IEC Interpretations against IEEE Std 1003.1 and IEEE Std 1003.2
- Issues raised in corrigenda for the Base Specifications and working group resolutions from The Open Group
- Corrigenda and resolutions passed by The Open Group for the XNS, Issue 5.2 specification
- Changes to make the text self-consistent with the additional material merged
- A reorganization of the options in order to facilitate profiling, both for smaller profiles such as IEEE Std 1003.13, and larger profiles such as the Single UNIX Specification
- Alignment with the ISO / IEC 9899: 1999 standard

1.2 Conformance

Conformance requirements for IEEE Std 1003.1-2001 are defined in Chapter 2 (on page 17).

1.3 Normative References

The following standards contain provisions which, through references in IEEE Std 1003.1-2001, constitute provisions of IEEE Std 1003.1-2001. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on IEEE Std 1003.1-2001 are encouraged to investigate the possibility of applying the most recent editions of the standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

ANS X3.9-1978
: (Reaffirmed 1989) American National Standard for Information Systems: Standard X3.9-1978, Programming Language FORTRAN.[1]

ISO / IEC 646: 1991
: ISO / IEC 646: 1991, Information Processing — ISO 7-Bit Coded Character Set for Information Interchange.[2]

ISO 4217: 2001
: ISO 4217: 2001, Codes for the Representation of Currencies and Funds.

ISO 8601: 2000
: ISO 8601: 2000, Data Elements and Interchange Formats — Information Interchange —

1. ANSI documents can be obtained from the Sales Department, American National Standards Institute, 1430 Broadway, New York, NY 10018, U.S.A.
2. ISO / IEC documents can be obtained from the ISO office: 1 Rue de Varembé, Case Postale 56, CH-1211, Genève 20, Switzerland / Suisse

Representation of Dates and Times.

ISO C (1999)
ISO/IEC 9899:1999, Programming Languages — C, including Technical Corrigendum 1.

ISO/IEC 10646-1:2000
ISO/IEC 10646-1:2000, Information Technology — Universal Multiple-Octet Coded Character Set (UCS) — Part 1: Architecture and Basic Multilingual Plane.

1.4 Terminology

For the purposes of IEEE Std 1003.1-2001, the following terminology definitions apply:

can
Describes a permissible optional feature or behavior available to the user or application. The feature or behavior is mandatory for an implementation that conforms to IEEE Std 1003.1-2001. An application can rely on the existence of the feature or behavior.

implementation-defined
Describes a value or behavior that is not defined by IEEE Std 1003.1-2001 but is selected by an implementor. The value or behavior may vary among implementations that conform to IEEE Std 1003.1-2001. An application should not rely on the existence of the value or behavior. An application that relies on such a value or behavior cannot be assured to be portable across conforming implementations.

The implementor shall document such a value or behavior so that it can be used correctly by an application.

legacy
Describes a feature or behavior that is being retained for compatibility with older applications, but which has limitations which make it inappropriate for developing portable applications. New applications should use alternative means of obtaining equivalent functionality.

may
Describes a feature or behavior that is optional for an implementation that conforms to IEEE Std 1003.1-2001. An application should not rely on the existence of the feature or behavior. An application that relies on such a feature or behavior cannot be assured to be portable across conforming implementations.

To avoid ambiguity, the opposite of *may* is expressed as *need not*, instead of *may not*.

shall
For an implementation that conforms to IEEE Std 1003.1-2001, describes a feature or behavior that is mandatory. An application can rely on the existence of the feature or behavior.

For an application or user, describes a behavior that is mandatory.

should
For an implementation that conforms to IEEE Std 1003.1-2001, describes a feature or behavior that is recommended but not mandatory. An application should not rely on the existence of the feature or behavior. An application that relies on such a feature or behavior cannot be assured to be portable across conforming implementations.

For an application, describes a feature or behavior that is recommended programming practice for optimum portability.

undefined

Describes the nature of a value or behavior not defined by IEEE Std 1003.1-2001 which results from use of an invalid program construct or invalid data input.

The value or behavior may vary among implementations that conform to IEEE Std 1003.1-2001. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

unspecified

Describes the nature of a value or behavior not specified by IEEE Std 1003.1-2001 which results from use of a valid program construct or valid data input.

The value or behavior may vary among implementations that conform to IEEE Std 1003.1-2001. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

1.5 Portability

Some of the utilities in the Shell and Utilities volume of IEEE Std 1003.1-2001 and functions in the System Interfaces volume of IEEE Std 1003.1-2001 describe functionality that might not be fully portable to systems meeting the requirements for POSIX conformance (see the Base Definitions volume of IEEE Std 1003.1-2001, Chapter 2, Conformance).

Where optional, enhanced, or reduced functionality is specified, the text is shaded and a code in the margin identifies the nature of the option, extension, or warning (see Section 1.5.1). For maximum portability, an application should avoid such functionality.

Unless the primary task of a utility is to produce textual material on its standard output, application developers should not rely on the format or content of any such material that may be produced. Where the primary task *is* to provide such material, but the output format is incompletely specified, the description is marked with the OF margin code and shading. Application developers are warned not to expect that the output of such an interface on one system is any guide to its behavior on another system.

1.5.1 Codes

The codes and their meanings are as follows. See also Section 1.5.2 (on page 14).

ADV Advisory Information

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the ADV margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the ADV margin legend.

AIO Asynchronous Input and Output

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the AIO margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the AIO margin legend.

BAR Barriers

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the BAR margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the BAR margin legend.

BE Batch Environment Services and Utilities

The functionality described is optional.

Where applicable, utilities are marked with the BE margin legend in the SYNOPSIS section. Where additional semantics apply to a utility, the material is identified by use of the BE margin legend.

CD C-Language Development Utilities

The functionality described is optional.

Where applicable, utilities are marked with the CD margin legend in the SYNOPSIS section. Where additional semantics apply to a utility, the material is identified by use of the CD margin legend.

CPT Process CPU-Time Clocks

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the CPT margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the CPT margin legend.

CS Clock Selection

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the CS margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the CS margin legend.

CX Extension to the ISO C standard

The functionality described is an extension to the ISO C standard. Application writers may make use of an extension as it is supported on all IEEE Std 1003.1-2001-conforming systems.

With each function or header from the ISO C standard, a statement to the effect that ‘‘any conflict is unintentional’’ is included. That is intended to refer to a direct conflict. IEEE Std 1003.1-2001 acts in part as a profile of the ISO C standard, and it may choose to further constrain behaviors allowed to vary by the ISO C standard. Such limitations are not considered conflicts.

Where additional semantics apply to a function or header, the material is identified by use of the CX margin legend.

FD FORTRAN Development Utilities

The functionality described is optional.

Where applicable, utilities are marked with the FD margin legend in the SYNOPSIS section. Where additional semantics apply to a utility, the material is identified by use of the FD margin legend.

FR FORTRAN Runtime Utilities

The functionality described is optional.

Where applicable, utilities are marked with the FR margin legend in the SYNOPSIS section. Where additional semantics apply to a utility, the material is identified by use of the FR margin legend.

FSC File Synchronization
The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the FSC margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the FSC margin legend.

IP6 IPV6
The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the IP6 margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the IP6 margin legend.

MC1 Advisory Information and either Memory Mapped Files or Shared Memory Objects
The functionality described is optional. The functionality described is also an extension to the ISO C standard.

This is a shorthand notation for combinations of multiple option codes.

Where applicable, functions are marked with the MC1 margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the MC1 margin legend.

Refer to Section 1.5.2 (on page 14).

MC2 Memory Mapped Files, Shared Memory Objects, or Memory Protection
The functionality described is optional. The functionality described is also an extension to the ISO C standard.

This is a shorthand notation for combinations of multiple option codes.

Where applicable, functions are marked with the MC2 margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the MC2 margin legend.

Refer to Section 1.5.2 (on page 14).

MC3 Memory Mapped Files, Shared Memory Objects, or Typed Memory Objects
The functionality described is optional. The functionality described is also an extension to the ISO C standard.

This is a shorthand notation for combinations of multiple option codes.

Where applicable, functions are marked with the MC3 margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the MC3 margin legend.

Refer to Section 1.5.2 (on page 14).

MF Memory Mapped Files
The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the MF margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the MF margin legend.

ML Process Memory Locking

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the ML margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the ML margin legend.

MLR Range Memory Locking

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the MLR margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the MLR margin legend.

MON Monotonic Clock

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the MON margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the MON margin legend.

MPR Memory Protection

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the MPR margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the MPR margin legend.

MSG Message Passing

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the MSG margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the MSG margin legend.

MX IEC 60559 Floating-Point Option

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the MX margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the MX margin legend.

OB Obsolescent

The functionality described may be withdrawn in a future version of this volume of IEEE Std 1003.1-2001. Strictly Conforming POSIX Applications and Strictly Conforming XSI Applications shall not use obsolescent features.

Where applicable, the material is identified by use of the OB margin legend.

OF Output Format Incompletely Specified

The functionality described is an XSI extension. The format of the output produced by the utility is not fully specified. It is therefore not possible to post-process this output in a consistent fashion. Typical problems include unknown length of strings and unspecified field delimiters.

Where applicable, the material is identified by use of the OF margin legend.

OH Optional Header

In the SYNOPSIS section of some interfaces in the System Interfaces volume of IEEE Std 1003.1-2001 an included header is marked as in the following example:

OH
```
#include <sys/types.h>
#include <grp.h>
struct group *getgrnam(const char *name);
```

The OH margin legend indicates that the marked header is not required on XSI-conformant systems.

PIO Prioritized Input and Output

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the PIO margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the PIO margin legend.

PS Process Scheduling

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the PS margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the PS margin legend.

RS Raw Sockets

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the RS margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the RS margin legend.

RTS Realtime Signals Extension

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the RTS margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the RTS margin legend.

SD Software Development Utilities

The functionality described is optional.

Where applicable, utilities are marked with the SD margin legend in the SYNOPSIS section. Where additional semantics apply to a utility, the material is identified by use of the SD margin legend.

SEM Semaphores

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the SEM margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the SEM margin legend.

SHM Shared Memory Objects

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the SHM margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the SHM margin legend.

SIO Synchronized Input and Output

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the SIO margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the SIO margin legend.

SPI Spin Locks

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the SPI margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the SPI margin legend.

SPN Spawn

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the SPN margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the SPN margin legend.

SS Process Sporadic Server

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the SS margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the SS margin legend.

TCT Thread CPU-Time Clocks

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TCT margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TCT margin legend.

TEF Trace Event Filter

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TEF margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TEF margin legend.

THR **Threads**

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the THR margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the THR margin legend.

TMO **Timeouts**

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TMO margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TMO margin legend.

TMR **Timers**

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TMR margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TMR margin legend.

TPI **Thread Priority Inheritance**

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TPI margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TPI margin legend.

TPP **Thread Priority Protection**

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TPP margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TPP margin legend.

TPS **Thread Execution Scheduling**

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TPS margin legend for the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TPS margin legend.

TRC **Trace**

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TRC margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TRC margin legend.

TRI **Trace Inherit**

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TRI margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TRI margin legend.

TRL Trace Log

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TRL margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TRL margin legend.

TSA Thread Stack Address Attribute

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TSA margin legend for the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TSA margin legend.

TSF Thread-Safe Functions

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TSF margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TSF margin legend.

TSH Thread Process-Shared Synchronization

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TSH margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TSH margin legend.

TSP Thread Sporadic Server

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TSP margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TSP margin legend.

TSS Thread Stack Size Attribute

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TSS margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TSS margin legend.

TYM Typed Memory Objects

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the TYM margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the TYM margin legend.

UP User Portability Utilities
The functionality described is optional.

Where applicable, utilities are marked with the UP margin legend in the SYNOPSIS section. Where additional semantics apply to a utility, the material is identified by use of the UP margin legend.

XSI Extension
The functionality described is an XSI extension. Functionality marked XSI is also an extension to the ISO C standard. Application writers may confidently make use of an extension on all systems supporting the X/Open System Interfaces Extension.

If an entire SYNOPSIS section is shaded and marked XSI, all the functionality described in that reference page is an extension. See Section 2.1.4 (on page 21).

XSR XSI STREAMS
The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the XSR margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the XSR margin legend.

1.5.2 Margin Code Notation

Some of the functionality described in IEEE Std 1003.1-2001 depends on support of more than one option, or independently may depend on several options. The following notation for margin codes is used to denote the following cases.

A Feature Dependent on One or Two Options

In this case, margin codes have a <space> separator; for example:

MF This feature requires support for only the Memory Mapped Files option.

MF SHM This feature requires support for both the Memory Mapped Files and the Shared Memory Objects options; that is, an application which uses this feature is portable only between implementations that provide both options.

A Feature Dependent on Either of the Options Denoted

In this case, margin codes have a '|' separator to denote the logical OR; for example:

MF|SHM This feature is dependent on support for either the Memory Mapped Files option or the Shared Memory Objects option; that is, an application which uses this feature is portable between implementations that provide any (or all) of the options.

A Feature Dependent on More than Two Options

The following shorthand notations are used:

MC1 The MC1 margin code is shorthand for ADV (MF|SHM). Features which are shaded with this margin code require support of the Advisory Information option and either the Memory Mapped Files or Shared Memory Objects option.

MC2 The MC2 margin code is shorthand for MF|SHM|MPR. Features which are shaded with this margin code require support of either the Memory Mapped Files, Shared Memory Objects, or Memory Protection options.

MC3 The MC3 margin code is shorthand for MF|SHM|TYM. Features which are shaded with this margin code require support of either the Memory Mapped Files, Shared Memory Objects, or Typed Memory Objects options.

Large Sections Dependent on an Option

Where large sections of text are dependent on support for an option, a lead-in text block is provided and shaded accordingly; for example:

TRC This section describes extensions to support tracing of user applications. This functionality is dependent on support of the Trace option (and the rest of this section is not further shaded for this option).

606 Chapter 2

Conformance

607 ## 2.1 Implementation Conformance

608 ### 2.1.1 Requirements

609 A *conforming implementation* shall meet all of the following criteria:

610 1. The system shall support all utilities, functions, and facilities defined within
611 IEEE Std 1003.1-2001 that are required for POSIX conformance (see Section 2.1.3 (on page
612 18)). These interfaces shall support the functional behavior described herein.

613 2. The system may support one or more options as described under Section 2.1.5 (on page
614 22). When an implementation claims that an option is supported, all of its constituent
615 parts shall be provided.

616 3. The system may support the X/Open System Interface Extension (XSI) as described under
617 Section 2.1.4 (on page 21).

618 4. The system may provide additional utilities, functions, or facilities not required by
619 IEEE Std 1003.1-2001. Non-standard extensions of the utilities, functions, or facilities
620 specified in IEEE Std 1003.1-2001 should be identified as such in the system
621 documentation. Non-standard extensions, when used, may change the behavior of utilities,
622 functions, or facilities defined by IEEE Std 1003.1-2001. The conformance document shall
623 define an environment in which an application can be run with the behavior specified by
624 IEEE Std 1003.1-2001. In no case shall such an environment require modification of a
625 Strictly Conforming POSIX Application (see Section 2.2.1 (on page 31)).

626 ### 2.1.2 Documentation

627 A conformance document with the following information shall be available for an
628 implementation claiming conformance to IEEE Std 1003.1-2001. The conformance document
629 shall have the same structure as IEEE Std 1003.1-2001, with the information presented in the
630 appropriate sections and subsections. Sections and subsections that consist solely of subordinate
631 section titles, with no other information, are not required. The conformance document shall not
632 contain information about extended facilities or capabilities outside the scope of
633 IEEE Std 1003.1-2001.

634 The conformance document shall contain a statement that indicates the full name, number, and
635 date of the standard that applies. The conformance document may also list international
636 software standards that are available for use by a Conforming POSIX Application. Applicable
637 characteristics where documentation is required by one of these standards, or by standards of
638 government bodies, may also be included.

639 The conformance document shall describe the limit values found in the headers **<limits.h>** (on
640 page 249) and **<unistd.h>** (on page 403), stating values, the conditions under which those values
641 may change, and the limits of such variations, if any.

642 The conformance document shall describe the behavior of the implementation for all
643 implementation-defined features defined in IEEE Std 1003.1-2001. This requirement shall be met
644 by listing these features and providing either a specific reference to the system documentation or
645 providing full syntax and semantics of these features. When the value or behavior in the

implementation is designed to be variable or customized on each instantiation of the system, the implementation provider shall document the nature and permissible ranges of this variation.

The conformance document may specify the behavior of the implementation for those features where IEEE Std 1003.1-2001 states that implementations may vary or where features are identified as undefined or unspecified.

The conformance document shall not contain documentation other than that specified in the preceding paragraphs except where such documentation is specifically allowed or required by other provisions of IEEE Std 1003.1-2001.

The phrases ‘‘shall document’’ or ‘‘shall be documented’’ in IEEE Std 1003.1-2001 mean that documentation of the feature shall appear in the conformance document, as described previously, unless there is an explicit reference in the conformance document to show where the information can be found in the system documentation.

The system documentation should also contain the information found in the conformance document.

2.1.3 POSIX Conformance

A conforming implementation shall meet the following criteria for POSIX conformance.

2.1.3.1 POSIX System Interfaces

- The system shall support all the mandatory functions and headers defined in IEEE Std 1003.1-2001, and shall set the symbolic constant _POSIX_VERSION to the value 200112L.
- Although all implementations conforming to IEEE Std 1003.1-2001 support all the features described below, there may be system-dependent or file system-dependent configuration procedures that can remove or modify any or all of these features. Such configurations should not be made if strict compliance is required.

  The following symbolic constants shall either be undefined or defined with a value other than −1. If a constant is undefined, an application should use the *sysconf*( ), *pathconf*( ), or *fpathconf*( ) functions, or the *getconf* utility, to determine which features are present on the system at that time or for the particular pathname in question.

  — _POSIX_CHOWN_RESTRICTED

  The use of *chown*( ) is restricted to a process with appropriate privileges, and to changing the group ID of a file only to the effective group ID of the process or to one of its supplementary group IDs.

  — _POSIX_NO_TRUNC

  Pathname components longer than {NAME_MAX} generate an error.
- The following symbolic constants shall be defined as follows:
  - _POSIX_JOB_CONTROL shall have a value greater than zero.
  - _POSIX_SAVED_IDS shall have a value greater than zero.
  - _POSIX_VDISABLE shall have a value other than −1.

Note: The symbols above represent historical options that are no longer allowed as options, but are retained here for backwards-compatibility of applications.

- The system may support one or more options (see Section 2.1.6 (on page 28)) denoted by the following symbolic constants:
  - — _POSIX_ADVISORY_INFO
  - — _POSIX_ASYNCHRONOUS_IO
  - — _POSIX_BARRIERS
  - — _POSIX_CLOCK_SELECTION
  - — _POSIX_CPUTIME
  - — _POSIX_FSYNC
  - — _POSIX_IPV6
  - — _POSIX_MAPPED_FILES
  - — _POSIX_MEMLOCK
  - — _POSIX_MEMLOCK_RANGE
  - — _POSIX_MEMORY_PROTECTION
  - — _POSIX_MESSAGE_PASSING
  - — _POSIX_MONOTONIC_CLOCK
  - — _POSIX_PRIORITIZED_IO
  - — _POSIX_PRIORITY_SCHEDULING
  - — _POSIX_RAW_SOCKETS
  - — _POSIX_REALTIME_SIGNALS
  - — _POSIX_SEMAPHORES
  - — _POSIX_SHARED_MEMORY_OBJECTS
  - — _POSIX_SPAWN
  - — _POSIX_SPIN_LOCKS
  - — _POSIX_SPORADIC_SERVER
  - — _POSIX_SYNCHRONIZED_IO
  - — _POSIX_THREAD_ATTR_STACKADDR
  - — _POSIX_THREAD_CPUTIME
  - — _POSIX_THREAD_ATTR_STACKSIZE
  - — _POSIX_THREAD_PRIO_INHERIT
  - — _POSIX_THREAD_PRIO_PROTECT
  - — _POSIX_THREAD_PRIORITY_SCHEDULING
  - — _POSIX_THREAD_PROCESS_SHARED
  - — _POSIX_THREAD_SAFE_FUNCTIONS
  - — _POSIX_THREAD_SPORADIC_SERVER
  - — _POSIX_THREADS

— _POSIX_TIMEOUTS

— _POSIX_TIMERS

— _POSIX_TRACE

— _POSIX_TRACE_EVENT_FILTER

— _POSIX_TRACE_INHERIT

— _POSIX_TRACE_LOG

— _POSIX_TYPED_MEMORY_OBJECTS

If any of the symbolic constants _POSIX_TRACE_EVENT_FILTER, _POSIX_TRACE_LOG, or _POSIX_TRACE_INHERIT is defined to have a value other than –1, then the symbolic constant _POSIX_TRACE shall also be defined to have a value other than –1.

XSI • The system may support the XSI extensions (see Section 2.1.5.2 (on page 24)) denoted by the following symbolic constants:

— _XOPEN_CRYPT

— _XOPEN_LEGACY

— _XOPEN_REALTIME

— _XOPEN_REALTIME_THREADS

— _XOPEN_UNIX

2.1.3.2 POSIX Shell and Utilities

- The system shall provide all the mandatory utilities in the Shell and Utilities volume of IEEE Std 1003.1-2001 with all the functional behavior described therein.
- The system shall support the Large File capabilities described in the Shell and Utilities volume of IEEE Std 1003.1-2001.
- The system may support one or more options (see Section 2.1.6 (on page 28)) denoted by the following symbolic constants. (The literal names below apply to the *getconf* utility.)

— POSIX2_C_DEV

— POSIX2_CHAR_TERM

— POSIX2_FORT_DEV

— POSIX2_FORT_RUN

— POSIX2_LOCALEDEF

— POSIX2_PBS

— POSIX2_PBS_ACCOUNTING

— POSIX2_PBS_LOCATE

— POSIX2_PBS_MESSAGE

— POSIX2_PBS_TRACK

— POSIX2_SW_DEV

— POSIX2_UPE

- The system may support the XSI extensions (see Section 2.1.4).

Additional language bindings and development utility options may be provided in other related standards or in a future version of IEEE Std 1003.1-2001. In the former case, additional symbolic constants of the same general form as shown in this subsection should be defined by the related standard document and made available to the application without requiring IEEE Std 1003.1-2001 to be updated.

2.1.4 XSI Conformance

XSI This section describes the criteria for implementations conforming to the XSI extension (see Section 3.439 (on page 95)). This functionality is dependent on the support of the XSI extension (and the rest of this section is not further shaded).

IEEE Std 1003.1-2001 describes utilities, functions, and facilities offered to application programs by the X/Open System Interface (XSI). An XSI-conforming implementation shall meet the criteria for POSIX conformance and the following requirements.

2.1.4.1 XSI System Interfaces

- The system shall support all the functions and headers defined in IEEE Std 1003.1-2001 as part of the XSI extension denoted by the symbolic constant _XOPEN_UNIX and any extensions marked with the XSI extension marking (see Section 1.5.1 (on page 6)).
- The system shall support the *mmap*( ), *munmap*( ), and *msync*( ) functions.
- The system shall support the following options defined within IEEE Std 1003.1-2001 (see Section 2.1.6 (on page 28)):
  - — _POSIX_FSYNC
  - — _POSIX_MAPPED_FILES
  - — _POSIX_MEMORY_PROTECTION
  - — _POSIX_THREAD_ATTR_STACKADDR
  - — _POSIX_THREAD_ATTR_STACKSIZE
  - — _POSIX_THREAD_PROCESS_SHARED
  - — _POSIX_THREAD_SAFE_FUNCTIONS
  - — _POSIX_THREADS
- The system may support the following XSI Option Groups (see Section 2.1.5.2 (on page 24)) defined within IEEE Std 1003.1-2001:
  - — Encryption
  - — Realtime
  - — Advanced Realtime
  - — Realtime Threads
  - — Advanced Realtime Threads
  - — Tracing
  - — XSI STREAMS
  - — Legacy

795 *2.1.4.2 XSI Shell and Utilities Conformance*

796 • The system shall support all the utilities defined in the Shell and Utilities volume of
797 IEEE Std 1003.1-2001 as part of the XSI extension denoted by the XSI marking in the
798 SYNOPSIS section, and any extensions marked with the XSI extension marking (see Section
799 1.5.1 (on page 6)) within the text.

800 • The system shall support the User Portability Utilities option.

801 • The system shall support creation of locales (see Chapter 7 (on page 123)).

802 • The C-language Development utility *c99* shall be supported.

803 • The XSI Development Utilities option may be supported. It consists of the following software
804 development utilities:

805 *admin* *delta* *prs* *unget* 1
806 *cflow* *get* *rmdel* *val* 1
807 *ctags* *m4* *sact* *what*
808 *cxref* *nm* *sccs* 1

809 • Within the utilities that are provided, functionality marked by the code OF (see Section 1.5.1
810 (on page 6)) need not be provided.

811 ## 2.1.5 Option Groups

812 An Option Group is a group of related functions or options defined within the System Interfaces
813 volume of IEEE Std 1003.1-2001.

814 If an implementation supports an Option Group, then the system shall support the functional
815 behavior described herein.

816 If an implementation does not support an Option Group, then the system need not support the
817 functional behavior described herein.

818 *2.1.5.1 Subprofiling Considerations*

819 Profiling standards supporting functional requirements less than that required in
820 IEEE Std 1003.1-2001 may subset both mandatory and optional functionality required for POSIX
821 Conformance (see Section 2.1.3 (on page 18)) or XSI Conformance (see Section 2.1.4 (on page
822 21)). Such profiles shall organize the subsets into Subprofiling Option Groups.

823 The Rationale (Informative) volume of IEEE Std 1003.1-2001, Appendix E, Subprofiling
824 Considerations (Informative) describes a representative set of such Subprofiling Option Groups
825 for use by profiles applicable to specialized realtime systems. IEEE Std 1003.1-2001 does not
826 require that the presence of Subprofiling Option Groups be testable at compile-time (as symbols
827 defined in any header) or at runtime (via *sysconf*( ) or *getconf*).

828 A Subprofiling Option Group may provide basic system functionality that other Subprofiling
829 Option Groups and other options depend upon.[3] If a profile of IEEE Std 1003.1-2001 does not

830 ———————

831 3. As an example, the File System profiling option group provides underlying support for pathname resolution and file creation
832 which are needed by any interface in IEEE Std 1003.1-2001 that parses a *path* argument. If a profile requires support for the
833 Device Input and Output profiling option group but does not require support for the File System profiling option group, the
834 profile must specify how pathname resolution is to behave in that profile, how the O_CREAT flag to *open*( ) is to be handled (and
835 the use of the character `'a'` in the *mode* argument of *fopen*( ) when a filename argument names a file that does not exist), and
836 specify lots of other details.

require an implementation to provide a Subprofiling Option Group that provides features utilized by a required Subprofiling Option Group (or option),[4] the profile shall specify[5] all of the following:

- Restricted or altered behavior of interfaces defined in IEEE Std 1003.1-2001 that may differ on an implementation of the profile
- Additional behaviors that may produce undefined or unspecified results
- Additional implementation-defined behavior that implementations shall be required to document in the profile's conformance document

if any of the above is a result of the profile not requiring an interface required by IEEE Std 1003.1-2001.

The following additional rules shall apply to all profiles of IEEE Std 1003.1-2001:

- Any application that conforms to that profile shall also conform to IEEE Std 1003.1-2001 (that is, a profile shall not require restricted, altered, or extended behaviors of an implementation of IEEE Std 1003.1-2001).
- Profiles are permitted to add additional requirements to the limits defined in **<limits.h>** and **<stdint.h>**, subject to the following:

  For the limits in **<limits.h>** and **<stdint.h>**:

  — If the limit is specified as having a fixed value, it shall not be changed by a profile.

  — If a limit is specified as having a minimum or maximum acceptable value, it may be changed by a profile as follows:

    — A profile may increase a minimum acceptable value, but shall not make a minimum acceptable value smaller.

    — A profile may reduce a maximum acceptable value, but shall not make a maximum acceptable value larger.

- A profile shall not change a limit specified as having a minimum or maximum value into a limit specified as having a fixed value.
- A profile shall not create new limits.
- Any implementation that conforms to IEEE Std 1003.1-2001 (including all options and extended limits required by the profile) shall also conform to that profile.

---

4. As an example, IEEE Std 1003.1-2001 requires that implementations claiming to support the Range Memory Locking option also support the Process Memory Locking option. A profile could require that the Range Memory Locking option had to be supplied without requiring that the Process Memory Locking option be supplied as long as the profile specifies everything an application writer or system implementor would have to know to build an application or implementation conforming to the profile.
5. Note that the profile could just specify that any use of the features not specified by the profile would produce undefined or unspecified results.

873 *2.1.5.2 XSI Option Groups*

874 XSI This section describes Option Groups to support the definition of XSI conformance within the
875 System Interfaces volume of IEEE Std 1003.1-2001. This functionality is dependent on the
876 support of the XSI extension (and the rest of this section is not further shaded).

877 The following Option Groups are defined.

878 **Encryption**

879 The Encryption Option Group is denoted by the symbolic constant _XOPEN_CRYPT. It includes
880 the following functions:

881 *crypt*( ), *encrypt*( ), *setkey*( )

882 These functions are marked CRYPT.

883 Due to export restrictions on the decoding algorithm in some countries, implementations may be
884 restricted in making these functions available. All the functions in the Encryption Option Group
885 may therefore return [ENOSYS] or, alternatively, *encrypt*( ) shall return [ENOSYS] for the
886 decryption operation.

887 An implementation that claims conformance to this Option Group shall set _XOPEN_CRYPT to
888 a value other than –1.

889 **Realtime**

890 The Realtime Option Group is denoted by the symbolic constant _XOPEN_REALTIME.

891 This Option Group includes a set of realtime functions drawn from options within
892 IEEE Std 1003.1-2001 (see Section 2.1.6 (on page 28)).

893 Where entire functions are included in the Option Group, the NAME section is marked with
894 REALTIME. Where additional semantics have been added to existing pages, the new material is
895 identified by use of the appropriate margin legend for the underlying option defined within
896 IEEE Std 1003.1-2001.

897 An implementation that claims conformance to this Option Group shall set
898 _XOPEN_REALTIME to a value other than –1.

899 This Option Group consists of the set of the following options from within IEEE Std 1003.1-2001
900 (see Section 2.1.6 (on page 28)):

901 _POSIX_ASYNCHRONOUS_IO
902 _POSIX_FSYNC
903 _POSIX_MAPPED_FILES
904 _POSIX_MEMLOCK
905 _POSIX_MEMLOCK_RANGE
906 _POSIX_MEMORY_PROTECTION
907 _POSIX_MESSAGE_PASSING
908 _POSIX_PRIORITIZED_IO
909 _POSIX_PRIORITY_SCHEDULING
910 _POSIX_REALTIME_SIGNALS
911 _POSIX_SEMAPHORES
912 _POSIX_SHARED_MEMORY_OBJECTS
913 _POSIX_SYNCHRONIZED_IO
914 _POSIX_TIMERS

If the symbolic constant _XOPEN_REALTIME is defined to have a value other than –1, then the following symbolic constants shall be defined by the implementation to have the value 200112L:

- _POSIX_ASYNCHRONOUS_IO
- _POSIX_MEMLOCK
- _POSIX_MEMLOCK_RANGE
- _POSIX_MESSAGE_PASSING
- _POSIX_PRIORITY_SCHEDULING
- _POSIX_REALTIME_SIGNALS
- _POSIX_SEMAPHORES
- _POSIX_SHARED_MEMORY_OBJECTS
- _POSIX_SYNCHRONIZED_IO
- _POSIX_TIMERS

The functionality associated with _POSIX_MAPPED_FILES, _POSIX_MEMORY_PROTECTION, and _POSIX_FSYNC is always supported on XSI-conformant systems.

Support of _POSIX_PRIORITIZED_IO on XSI-conformant systems is optional. If this functionality is supported, then _POSIX_PRIORITIZED_IO shall be set to a value other than –1. Otherwise, it shall be undefined.

If _POSIX_PRIORITIZED_IO is supported, then asynchronous I/O operations performed by *aio_read*( ), *aio_write*( ), and *lio_listio*( ) shall be submitted at a priority equal to the scheduling priority equal to a base scheduling priority minus *aiocbp->aio_reqprio*. If Thread Execution Scheduling is not supported, then the base scheduling priority is that of the calling process; otherwise, the base scheduling priority is that of the calling thread. The implementation shall also document for which files I/O prioritization is supported.

Advanced Realtime

An implementation that claims conformance to this Option Group shall also support the Realtime Option Group.

Where entire functions are included in the Option Group, the NAME section is marked with ADVANCED REALTIME. Where additional semantics have been added to existing pages, the new material is identified by use of the appropriate margin legend for the underlying option defined within IEEE Std 1003.1-2001.

This Option Group consists of the set of the following options from within IEEE Std 1003.1-2001 (see Section 2.1.6 (on page 28)):

- _POSIX_ADVISORY_INFO
- _POSIX_CLOCK_SELECTION
- _POSIX_CPUTIME
- _POSIX_MONOTONIC_CLOCK
- _POSIX_SPAWN
- _POSIX_SPORADIC_SERVER
- _POSIX_TIMEOUTS
- _POSIX_TYPED_MEMORY_OBJECTS

If the implementation supports the Advanced Realtime Option Group, then the following symbolic constants shall be defined by the implementation to have the value 200112L:

957 _POSIX_ADVISORY_INFO
958 _POSIX_CLOCK_SELECTION
959 _POSIX_CPUTIME
960 _POSIX_MONOTONIC_CLOCK
961 _POSIX_SPAWN
962 _POSIX_SPORADIC_SERVER
963 _POSIX_TIMEOUTS
964 _POSIX_TYPED_MEMORY_OBJECTS

965 If the symbolic constant _POSIX_SPORADIC_SERVER is defined, then the symbolic constant
966 _POSIX_PRIORITY_SCHEDULING shall also be defined by the implementation to have the
967 value 200112L.

968 If the symbolic constant _POSIX_CPUTIME is defined, then the symbolic constant
969 _POSIX_TIMERS shall also be defined by the implementation to have the value 200112L.

970 If the symbolic constant _POSIX_MONOTONIC_CLOCK is defined, then the symbolic constant
971 _POSIX_TIMERS shall also be defined by the implementation to have the value 200112L.

972 If the symbolic constant _POSIX_CLOCK_SELECTION is defined, then the symbolic constant
973 _POSIX_TIMERS shall also be defined by the implementation to have the value 200112L.

974 **Realtime Threads**

975 The Realtime Threads Option Group is denoted by the symbolic constant
976 _XOPEN_REALTIME_THREADS.

977 This Option Group consists of the set of the following options from within IEEE Std 1003.1-2001
978 (see Section 2.1.6 (on page 28)):

979 _POSIX_THREAD_PRIO_INHERIT
980 _POSIX_THREAD_PRIO_PROTECT
981 _POSIX_THREAD_PRIORITY_SCHEDULING

982 Where applicable, whole pages are marked REALTIME THREADS, together with the
983 appropriate option margin legend for the SYNOPSIS section (see Section 1.5.1 (on page 6)).

984 An implementation that claims conformance to this Option Group shall set
985 _XOPEN_REALTIME_THREADS to a value other than –1.

986 If the symbol _XOPEN_REALTIME_THREADS is defined to have a value other than –1, then the
987 following options shall also be defined by the implementation to have the value 200112L:

988 _POSIX_THREAD_PRIO_INHERIT
989 _POSIX_THREAD_PRIO_PROTECT
990 _POSIX_THREAD_PRIORITY_SCHEDULING

991 **Advanced Realtime Threads**

992 An implementation that claims conformance to this Option Group shall also support the
993 Realtime Threads Option Group.

994 Where entire functions are included in the Option Group, the NAME section is marked with
995 ADVANCED REALTIME THREADS. Where additional semantics have been added to existing
996 pages, the new material is identified by use of the appropriate margin legend for the underlying
997 option defined within IEEE Std 1003.1-2001.

998 This Option Group consists of the set of the following options from within IEEE Std 1003.1-2001
999 (see Section 2.1.6 (on page 28)):

1000 _POSIX_BARRIERS
1001 _POSIX_SPIN_LOCKS
1002 _POSIX_THREAD_CPUTIME
1003 _POSIX_THREAD_SPORADIC_SERVER

1004 If the symbolic constant _POSIX_THREAD_SPORADIC_SERVER is defined to have the value
1005 200112L, then the symbolic constant _POSIX_THREAD_PRIORITY_SCHEDULING shall also be
1006 defined by the implementation to have the value 200112L.

1007 If the symbolic constant _POSIX_THREAD_CPUTIME is defined to have the value 200112L,
1008 then the symbolic constant _POSIX_TIMERS shall also be defined by the implementation to have
1009 the value 200112L.

1010 If the symbolic constant _POSIX_BARRIERS is defined to have the value 200112L, then the
1011 symbolic constants _POSIX_THREADS and _POSIX_THREAD_SAFE_FUNCTIONS shall also
1012 be defined by the implementation to have the value 200112L.

1013 If the symbolic constant _POSIX_SPIN_LOCKS is defined to have the value 200112L, then the
1014 symbolic constants _POSIX_THREADS and _POSIX_THREAD_SAFE_FUNCTIONS shall also
1015 be defined by the implementation to have the value 200112L.

1016 If the implementation supports the Advanced Realtime Threads Option Group, then the
1017 following symbolic constants shall be defined by the implementation to have the value 200112L:

1018 _POSIX_BARRIERS
1019 _POSIX_SPIN_LOCKS
1020 _POSIX_THREAD_CPUTIME
1021 _POSIX_THREAD_SPORADIC_SERVER

1022 **Tracing**

1023 This Option Group includes a set of tracing functions drawn from options within
1024 IEEE Std 1003.1-2001 (see Section 2.1.6 (on page 28)).

1025 Where entire functions are included in the Option Group, the NAME section is marked with
1026 TRACING. Where additional semantics have been added to existing pages, the new material is
1027 identified by use of the appropriate margin legend for the underlying option defined within
1028 IEEE Std 1003.1-2001.

1029 This Option Group consists of the set of the following options from within IEEE Std 1003.1-2001
1030 (see Section 2.1.6 (on page 28)):

1031 _POSIX_TRACE
1032 _POSIX_TRACE_EVENT_FILTER
1033 _POSIX_TRACE_LOG
1034 _POSIX_TRACE_INHERIT

1035 If the implementation supports the Tracing Option Group, then the following symbolic
1036 constants shall be defined by the implementation to have the value 200112L:

1037 _POSIX_TRACE
1038 _POSIX_TRACE_EVENT_FILTER
1039 _POSIX_TRACE_LOG
1040 _POSIX_TRACE_INHERIT

XSI STREAMS

The XSI STREAMS Option Group is denoted by the symbolic constant _XOPEN_STREAMS.

This Option Group includes functionality related to STREAMS, a uniform mechanism for implementing networking services and other character-based I/O as described in the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.6, STREAMS.

It includes the following functions:

fattach( ), *fdetach*( ), *getmsg*( ), *getpmsg*( ), *ioctl*( ), *isastream*( ), *putmsg*( ), *putpmsg*( )

and the **<stropts.h>** header.

Where applicable, whole pages are marked STREAMS, together with the appropriate option margin legend for the SYNOPSIS section (see Section 1.5.1 (on page 6)). Where additional semantics have been added to existing pages, the new material is identified by use of the appropriate margin legend for the underlying option defined within IEEE Std 1003.1-2001.

An implementation that claims conformance to this Option Group shall set _XOPEN_STREAMS to a value other than –1.

Legacy

The Legacy Option Group is denoted by the symbolic constant _XOPEN_LEGACY.

The Legacy Option Group includes the functions and headers which were mandatory in previous versions of IEEE Std 1003.1-2001 but are optional in this version.

These functions and headers are retained in IEEE Std 1003.1-2001 because of their widespread use. Application writers should not rely on the existence of these functions or headers in new applications, but should follow the migration path detailed in the APPLICATION USAGE sections of the relevant pages.

Various factors may have contributed to the decision to mark a function or header LEGACY. In all cases, the specific reasons for the withdrawal of a function or header are documented on the relevant pages.

Once a function or header is marked LEGACY, no modifications are made to the specifications of such functions or headers other than to the APPLICATION USAGE sections of the relevant pages.

The functions and headers which form this Option Group are as follows:

bcmp( ), *bcopy*( ), *bzero*( ), *ecvt*( ), *fcvt*( ), *ftime*( ), *gcvt*( ), *getwd*( ), *index*( ), *mktemp*( ), *rindex*( ), *utimes*( ), *wcswcs*( )

An implementation that claims conformance to this Option Group shall set _XOPEN_LEGACY to a value other than –1.

2.1.6 Options

The symbolic constants defined in **<unistd.h>**, **Constants for Options and Option Groups** (on page 403) reflect implementation options for IEEE Std 1003.1-2001. These symbols can be used by the application to determine which optional facilities are present on the implementation. The *sysconf*( ) function defined in the System Interfaces volume of IEEE Std 1003.1-2001 or the *getconf* utility defined in the Shell and Utilities volume of IEEE Std 1003.1-2001 can be used to retrieve the value of each symbol on each specific implementation to determine whether the option is supported.

Where an option is not supported, the associated utilities, functions, or facilities need not be present.

Margin codes are defined for each option (see Section 1.5.1 (on page 6)).

2.1.6.1 *System Interfaces*

Refer to **<unistd.h>**, **Constants for Options and Option Groups** (on page 403) for the list of options.

2.1.6.2 *Shell and Utilities*

Each of these symbols shall be considered valid names by the implementation. Refer to **<unistd.h>**, **Constants for Options and Option Groups** (on page 403).

The literal names shown below apply only to the *getconf* utility.

CD POSIX2_C_DEV

The system supports the C-Language Development Utilities option.

The utilities in the C-Language Development Utilities option are used for the development of C-language applications, including compilation or translation of C source code and complex program generators for simple lexical tasks and processing of context-free grammars.

The utilities listed below may be provided by a conforming system; however, any system claiming conformance to the C-Language Development Utilities option shall provide all of the utilities listed.

c99
lex
yacc

POSIX2_CHAR_TERM

The system supports the Terminal Characteristics option. This value need not be present on a system not supporting the User Portability Utilities option.

Where applicable, the dependency is noted within the description of the utility.

This option applies only to systems supporting the User Portability Utilities option. If supported, then the system supports at least one terminal type capable of all operations described in IEEE Std 1003.1-2001; see Section 10.2 (on page 185).

FD POSIX2_FORT_DEV

The system supports the FORTRAN Development Utilities option.

The *fort77* FORTRAN compiler is the only utility in the FORTRAN Development Utilities option. This is used for the development of FORTRAN language applications, including compilation or translation of FORTRAN source code.

The *fort77* utility may be provided by a conforming system; however, any system claiming conformance to the FORTRAN Development Utilities option shall provide the *fort77* utility.

FR POSIX2_FORT_RUN

The system supports the FORTRAN Runtime Utilities option.

The *asa* utility is the only utility in the FORTRAN Runtime Utilities option.

The *asa* utility may be provided by a conforming system; however, any system claiming conformance to the FORTRAN Runtime Utilities option shall provide the *asa* utility.

POSIX2_LOCALEDEF

The system supports the Locale Creation Utilities option.

If supported, the system supports the creation of locales as described in the *localedef* utility.

The *localedef* utility may be provided by a conforming system; however, any system claiming conformance to the Locale Creation Utilities option shall provide the *localedef* utility.

BE POSIX2_PBS

The system supports the Batch Environment Services and Utilities option (see the Shell and Utilities volume of IEEE Std 1003.1-2001, Chapter 3, Batch Environment Services).

Note: The Batch Environment Services and Utilities option is a combination of mandatory and optional batch services and utilities. The POSIX_PBS symbolic constant implies the system supports all the mandatory batch services and utilities.

POSIX2_PBS_ACCOUNTING

The system supports the Batch Accounting option.

POSIX2_PBS_CHECKPOINT

The system supports the Batch Checkpoint/Restart option.

POSIX2_PBS_LOCATE

The system supports the Locate Batch Job Request option.

POSIX2_PBS_MESSAGE

The system supports the Batch Job Message Request option.

POSIX2_PBS_TRACK

The system supports the Track Batch Job Request option.

SD POSIX2_SW_DEV

The system supports the Software Development Utilities option.

The utilities in the Software Development Utilities option are used for the development of applications, including compilation or translation of source code, the creation and maintenance of library archives, and the maintenance of groups of inter-dependent programs.

The utilities listed below may be provided by the conforming system; however, any system claiming conformance to the Software Development Utilities option shall provide all of the utilities listed here.

ar
make
nm
strip

UP POSIX2_UPE

The system supports the User Portability Utilities option.

The utilities in the User Portability Utilities option shall be implemented on all systems that claim conformance to this option. Certain utilities are noted as having features that cannot be implemented on all terminal types; if the POSIX2_CHAR_TERM option is supported, the system shall support all such features on at least one terminal type; see Section 10.2 (on page 185).

Some of the utilities are required only on systems that also support the Software Development Utilities option, or the character-at-a-time terminal option (see Section 10.2 (on page 185)); such utilities have this noted in their DESCRIPTION sections. All of the

other utilities listed are required only on systems that claim conformance to the User Portability Utilities option.

alias	*expand*	*nm*	*unalias*
at	*fc*	*patch*	*unexpand*
batch	*fg*	*ps*	*uudecode*
bg	*file*	*renice*	*uuencode*
crontab	*jobs*	*split*	*vi*
split	*man*	*strings*	*who*
ctags	*mesg*	*tabs*	*write*
df	*more*	*talk*	
du	*newgrp*	*time*	
ex	*nice*	*tput*	

2.2 Application Conformance

All applications claiming conformance to IEEE Std 1003.1-2001 shall use only language-dependent services for the C programming language described in Section 2.3 (on page 33), shall use only the utilities and facilities defined in the Shell and Utilities volume of IEEE Std 1003.1-2001, and shall fall within one of the following categories.

2.2.1 Strictly Conforming POSIX Application

A Strictly Conforming POSIX Application is an application that requires only the facilities described in IEEE Std 1003.1-2001. Such an application:

1. Shall accept any implementation behavior that results from actions it takes in areas described in IEEE Std 1003.1-2001 as *implementation-defined* or *unspecified*, or where IEEE Std 1003.1-2001 indicates that implementations may vary
2. Shall not perform any actions that are described as producing *undefined* results
3. For symbolic constants, shall accept any value in the range permitted by IEEE Std 1003.1-2001, but shall not rely on any value in the range being greater than the minimums listed or being less than the maximums listed in IEEE Std 1003.1-2001
4. Shall not use facilities designated as *obsolescent*
5. Is required to tolerate and permitted to adapt to the presence or absence of optional facilities whose availability is indicated by Section 2.1.3 (on page 18)
6. For the C programming language, shall not produce any output dependent on any behavior described in the ISO/IEC 9899:1999 standard as *unspecified*, *undefined*, or *implementation-defined*, unless the System Interfaces volume of IEEE Std 1003.1-2001 specifies the behavior
7. For the C programming language, shall not exceed any minimum implementation limit defined in the ISO/IEC 9899:1999 standard, unless the System Interfaces volume of IEEE Std 1003.1-2001 specifies a higher minimum implementation limit
8. For the C programming language, shall define _POSIX_C_SOURCE to be 200112L before any header is included

Within IEEE Std 1003.1-2001, any restrictions placed upon a Conforming POSIX Application shall restrict a Strictly Conforming POSIX Application.

2.2.2 Conforming POSIX Application

2.2.2.1 ISO/IEC Conforming POSIX Application

An ISO/IEC Conforming POSIX Application is an application that uses only the facilities described in IEEE Std 1003.1-2001 and approved Conforming Language bindings for any ISO or IEC standard. Such an application shall include a statement of conformance that documents all options and limit dependencies, and all other ISO or IEC standards used.

2.2.2.2 <National Body> Conforming POSIX Application

A <National Body> Conforming POSIX Application differs from an ISO/IEC Conforming POSIX Application in that it also may use specific standards of a single ISO/IEC member body referred to here as *<National Body>*. Such an application shall include a statement of conformance that documents all options and limit dependencies, and all other <National Body> standards used.

2.2.3 Conforming POSIX Application Using Extensions

A Conforming POSIX Application Using Extensions is an application that differs from a Conforming POSIX Application only in that it uses non-standard facilities that are consistent with IEEE Std 1003.1-2001. Such an application shall fully document its requirements for these extended facilities, in addition to the documentation required of a Conforming POSIX Application. A Conforming POSIX Application Using Extensions shall be either an ISO/IEC Conforming POSIX Application Using Extensions or a <National Body> Conforming POSIX Application Using Extensions (see Section 2.2.2.1 and Section 2.2.2.2).

2.2.4 Strictly Conforming XSI Application

A Strictly Conforming XSI Application is an application that requires only the facilities described in IEEE Std 1003.1-2001. Such an application:

1. Shall accept any implementation behavior that results from actions it takes in areas described in IEEE Std 1003.1-2001 as *implementation-defined* or *unspecified*, or where IEEE Std 1003.1-2001 indicates that implementations may vary
2. Shall not perform any actions that are described as producing *undefined* results
3. For symbolic constants, shall accept any value in the range permitted by IEEE Std 1003.1-2001, but shall not rely on any value in the range being greater than the minimums listed or being less than the maximums listed in IEEE Std 1003.1-2001
4. Shall not use facilities designated as *obsolescent*
5. Is required to tolerate and permitted to adapt to the presence or absence of optional facilities whose availability is indicated by Section 2.1.4 (on page 21)
6. For the C programming language, shall not produce any output dependent on any behavior described in the ISO C standard as *unspecified*, *undefined*, or *implementation-defined*, unless the System Interfaces volume of IEEE Std 1003.1-2001 specifies the behavior
7. For the C programming language, shall not exceed any minimum implementation limit defined in the ISO C standard, unless the System Interfaces volume of IEEE Std 1003.1-2001 specifies a higher minimum implementation limit
8. For the C programming language, shall define _XOPEN_SOURCE to be 600 before any header is included

Within IEEE Std 1003.1-2001, any restrictions placed upon a Conforming POSIX Application shall restrict a Strictly Conforming XSI Application.

2.2.5 Conforming XSI Application Using Extensions

A Conforming XSI Application Using Extensions is an application that differs from a Strictly Conforming XSI Application only in that it uses non-standard facilities that are consistent with IEEE Std 1003.1-2001. Such an application shall fully document its requirements for these extended facilities, in addition to the documentation required of a Strictly Conforming XSI Application.

2.3 Language-Dependent Services for the C Programming Language

Implementors seeking to claim conformance using the ISO C standard shall claim POSIX conformance as described in Section 2.1.3 (on page 18).

2.4 Other Language-Related Specifications

IEEE Std 1003.1-2001 is currently specified in terms of the shell command language and ISO C. Bindings to other programming languages are being developed.

If conformance to IEEE Std 1003.1-2001 is claimed for implementation of any programming language, the implementation of that language shall support the use of external symbols distinct to at least 31 bytes in length in the source program text. (That is, identifiers that differ at or before the thirty-first byte shall be distinct.) If a national or international standard governing a language defines a maximum length that is less than this value, the language-defined maximum shall be supported. External symbols that differ only by case shall be distinct when the character set in use distinguishes uppercase and lowercase characters and the language permits (or requires) uppercase and lowercase characters to be distinct in external symbols.

1272

1273 *Chapter 3*

Definitions

1274 For the purposes of IEEE Std 1003.1-2001, the terms and definitions given in Chapter 3 apply.

1275 **Note:** No shading to denote extensions or options occurs in this chapter. Where the terms and
1276 definitions given in this chapter are used elsewhere in text related to extensions and options,
1277 they are shaded as appropriate.

1278 3.1 Abortive Release

1279 An abrupt termination of a network connection that may result in the loss of data.

1280 3.2 Absolute Pathname

1281 A pathname beginning with a single or more than two slashes; see also Section 3.266 (on page
1282 72).

1283 **Note:** Pathname Resolution is defined in detail in Section 4.11 (on page 100).

1284 3.3 Access Mode

1285 A particular form of access permitted to a file.

1286 3.4 Additional File Access Control Mechanism

1287 An implementation-defined mechanism that is layered upon the access control mechanisms
1288 defined here, but which do not grant permissions beyond those defined herein, although they
1289 may further restrict them.

1290 **Note:** File Access Permissions are defined in detail in Section 4.4 (on page 97).

1291 3.5 Address Space

1292 The memory locations that can be referenced by a process or the threads of a process.

1293 3.6 Advisory Information

1294 An interface that advises the implementation on (portable) application behavior so that it can
1295 optimize the system.

3.7 Affirmative Response

An input string that matches one of the responses acceptable to the *LC_MESSAGES* category keyword **yesexpr**, matching an extended regular expression in the current locale.

Note: The *LC_MESSAGES* category is defined in detail in Section 7.3.6 (on page 152).

3.8 Alert

To cause the user's terminal to give some audible or visual indication that an error or some other event has occurred. When the standard output is directed to a terminal device, the method for alerting the terminal user is unspecified. When the standard output is not directed to a terminal device, the alert is accomplished by writing the <alert> to standard output (unless the utility description indicates that the use of standard output produces undefined results in this case).

3.9 Alert Character (<alert>)

A character that in the output stream should cause a terminal to alert its user via a visual or audible notification. It is the character designated by `'\a'` in the C language. It is unspecified whether this character is the exact sequence transmitted to an output device by the system to accomplish the alert function.

3.10 Alias Name

In the shell command language, a word consisting solely of underscores, digits, and alphabetics from the portable character set and any of the following characters: `'!'`, `'%'`, `','`, `'@'`.

Implementations may allow other characters within alias names as an extension.

Note: The Portable Character Set is defined in detail in Section 6.1 (on page 113).

3.11 Alignment

A requirement that objects of a particular type be located on storage boundaries with addresses that are particular multiples of a byte address.

Note: See also the ISO C standard, Section B3.

3.12 Alternate File Access Control Mechanism

An implementation-defined mechanism that is independent of the access control mechanisms defined herein, and which if enabled on a file may either restrict or extend the permissions of a given user. IEEE Std 1003.1-2001 defines when such mechanisms can be enabled and when they are disabled.

Note: File Access Permissions are defined in detail in Section 4.4 (on page 97).

3.13 Alternate Signal Stack

Memory associated with a thread, established upon request by the implementation for a thread, separate from the thread signal stack, in which signal handlers responding to signals sent to that thread may be executed.

3.14 Ancillary Data

Protocol-specific, local system-specific, or optional information. The information can be both local or end-to-end significant, header information, part of a data portion, protocol-specific, and implementation or system-specific.

3.15 Angle Brackets

The characters '<' (left-angle-bracket) and '>' (right-angle-bracket). When used in the phrase ''enclosed in angle brackets'', the symbol '<' immediately precedes the object to be enclosed, and '>' immediately follows it. When describing these characters in the portable character set, the names <less-than-sign> and <greater-than-sign> are used.

3.16 Application

A computer program that performs some desired function.

3.17 Application Address

Endpoint address of a specific application.

3.18 Application Program Interface (API)

The definition of syntax and semantics for providing computer system services.

3.19 Appropriate Privileges

An implementation-defined means of associating privileges with a process with regard to the function calls, function call options, and the commands that need special privileges. There may be zero or more such means. These means (or lack thereof) are described in the conformance document.

Note: Function calls are defined in the System Interfaces volume of IEEE Std 1003.1-2001, and commands are defined in the Shell and Utilities volume of IEEE Std 1003.1-2001.

3.20 Argument

In the shell command language, a parameter passed to a utility as the equivalent of a single string in the *argv* array created by one of the *exec* functions. An argument is one of the options, option-arguments, or operands following the command name.

Note: The Utility Argument Syntax is defined in detail in Section 12.1 (on page 201) and the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.9.1.1, Command Search and Execution.

In the C language, an expression in a function call expression or a sequence of preprocessing tokens in a function-like macro invocation.

3.21 Arm (a Timer)

To start a timer measuring the passage of time, enabling notifying a process when the specified time or time interval has passed.

3.22 Asterisk

The character '*'.

3.23 Async-Cancel-Safe Function

A function that may be safely invoked by an application while the asynchronous form of cancellation is enabled. No function is async-cancel-safe unless explicitly described as such.

3.24 Asynchronous Events

Events that occur independently of the execution of the application.

3.25 Asynchronous Input and Output

A functionality enhancement to allow an application process to queue data input and output commands with asynchronous notification of completion.

3.26 Async-Signal-Safe Function

A function that may be invoked, without restriction, from signal-catching functions. No function is async-signal-safe unless explicitly described as such.

3.27 Asynchronously-Generated Signal

A signal that is not attributable to a specific thread. Examples are signals sent via *kill*( ), signals sent from the keyboard, and signals delivered to process groups. Being asynchronous is a property of how the signal was generated and not a property of the signal number. All signals may be generated asynchronously.

Note: The *kill*( ) function is defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.28 Asynchronous I/O Completion

For an asynchronous read or write operation, when a corresponding synchronous read or write would have completed and when any associated status fields have been updated.

3.29 Asynchronous I/O Operation

An I/O operation that does not of itself cause the thread requesting the I/O to be blocked from further use of the processor.

This implies that the process and the I/O operation may be running concurrently.

3.30 Authentication

The process of validating a user or process to verify that the user or process is not a counterfeit.

3.31 Authorization

The process of verifying that a user or process has permission to use a resource in the manner requested.

To ensure security, the user or process would also need to be authenticated before granting access.

3.32 Background Job

See *Background Process Group* in Section 3.34.

3.33 Background Process

A process that is a member of a background process group.

3.34 Background Process Group (or Background Job)

Any process group, other than a foreground process group, that is a member of a session that has established a connection with a controlling terminal.

3.35 Backquote

The character '`', also known as a grave accent.

3.36 Backslash

The character '\', also known as a reverse solidus.

3.37 Backspace Character (<backspace>)

A character that, in the output stream, should cause printing (or displaying) to occur one column position previous to the position about to be printed. If the position about to be printed is at the beginning of the current line, the behavior is unspecified. It is the character designated by '\b' in the C language. It is unspecified whether this character is the exact sequence transmitted to an output device by the system to accomplish the backspace function. The <backspace> defined here is not necessarily the ERASE special character.

Note: Special Characters are defined in detail in Section 11.1.9 (on page 191).

3.38 Barrier

A synchronization object that allows multiple threads to synchronize at a particular point in their execution.

3.39 Base Character

One of the set of characters defined in the Latin alphabet. In Western European languages other than English, these characters are commonly used with diacritical marks (accents, cedilla, and so on) to extend the range of characters in an alphabet.

3.40 Basename

The final, or only, filename in a pathname.

3.41 Basic Regular Expression (BRE)

A regular expression (see Section 3.316 (on page 79)) used by the majority of utilities that select strings from a set of character strings.

Note: Basic Regular Expressions are described in detail in Section 9.3 (on page 171).

3.42 Batch Access List

A list of user IDs and group IDs of those users and groups authorized to place batch jobs in a batch queue.

A batch access list is associated with a batch queue. A batch server uses the batch access list of a batch queue as one of the criteria in deciding to put a batch job in a batch queue.

3.43 Batch Administrator

A user that is authorized to modify all the attributes of queues and jobs and to change the status of a batch server.

3.44 Batch Client

A computational entity that utilizes batch services by making requests of batch servers.

Batch clients often provide the means by which users access batch services, although a batch server may act as a batch client by virtue of making requests of another batch server.

3.45 Batch Destination

The batch server in a batch system to which a batch job should be sent for processing.

Acceptance of a batch job at a batch destination is the responsibility of a receiving batch server. A batch destination may consist of a batch server-specific portion, a network-wide portion, or both. The batch server-specific portion is referred to as the ‘‘batch queue’’. The network-wide portion is referred to as a ‘‘batch server name’’.

3.46 Batch Destination Identifier

A string that identifies a specific batch destination.

A string of characters in the portable character set used to specify a particular batch destination.

Note: The Portable Character Set is defined in detail in Section 6.1 (on page 113).

3.47 Batch Directive

A line from a file that is interpreted by the batch server. The line is usually in the form of a comment and is an additional means of passing options to the *qsub* utility.

Note: The *qsub* utility is defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001.

3.48 Batch Job

A set of computational tasks for a computing system.

Batch jobs are managed by batch servers.

Once created, a batch job may be executing or pending execution. A batch job that is executing has an associated session leader (a process) that initiates and monitors the computational tasks of the batch job.

3.49 Batch Job Attribute

A named data type whose value affects the processing of a batch job.

The values of the attributes of a batch job affect the processing of that job by the batch server that manages the batch job.

3.50 Batch Job Identifier

A unique name for a batch job. A name that is unique among all other batch job identifiers in a batch system and that identifies the batch server to which the batch job was originally submitted.

3.51 Batch Job Name

A label that is an attribute of a batch job. The batch job name is not necessarily unique.

3.52 Batch Job Owner

The *username@hostname* of the user submitting the batch job, where *username* is a user name (see also Section 3.426 (on page 93)) and *hostname* is a network host name.

3.53 Batch Job Priority

A value specified by the user that may be used by an implementation to determine the order in which batch jobs are selected to be executed. Job priority has a numeric value in the range –1 024 to 1 023.

Note: The batch job priority is not the execution priority (nice value) of the batch job.

3.54 Batch Job State

An attribute of a batch job which determines the types of requests that the batch server that manages the batch job can accept for the batch job. Valid states include QUEUED, RUNNING, HELD, WAITING, EXITING, and TRANSITING.

3.55 Batch Name Service

A service that assigns batch names that are unique within the batch name space, and that can translate a unique batch name into the location of the named batch entity.

3.56 Batch Name Space

The environment within which a batch name is known to be unique.

3.57 Batch Node

A host containing part or all of a batch system.

A batch node is a host meeting at least one of the following conditions:

- Capable of executing a batch client
- Contains a routing batch queue
- Contains an execution batch queue

3.58 Batch Operator

A user that is authorized to modify some, but not all, of the attributes of jobs and queues, and may change the status of the batch server.

3.59 Batch Queue

A manageable object that represents a set of batch jobs and is managed by a single batch server.

Note: A set of batch jobs is called a batch queue largely for historical reasons. Jobs are selected from the batch queue for execution based on attributes such as priority, resource requirements, and hold conditions.

See also the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 3.1.2, Batch Queues.

3.60 Batch Queue Attribute

A named data type whose value affects the processing of all batch jobs that are members of the batch queue.

A batch queue has attributes that affect the processing of batch jobs that are members of the batch queue.

3.61 Batch Queue Position

The place, relative to other jobs in the batch queue, occupied by a particular job in a batch queue. This is defined in part by submission time and priority; see also Section 3.62.

3.62 Batch Queue Priority

The maximum job priority allowed for any batch job in a given batch queue.

The batch queue priority is set and may be changed by users with appropriate privilege. The priority is bounded in an implementation-defined manner.

3.63 Batch Rerunability

An attribute of a batch job indicating that it may be rerun after an abnormal termination from the beginning without affecting the validity of the results.

3.64 Batch Restart

The action of resuming the processing of a batch job from the point of the last checkpoint. Typically, this is done if the batch job has been interrupted because of a system failure.

3.65 Batch Server

A computational entity that provides batch services.

3.66 Batch Server Name

A string of characters in the portable character set used to specify a particular server in a network.

Note: The Portable Character Set is defined in detail in Section 6.1 (on page 113).

3.67 Batch Service

Computational and organizational services performed by a batch system on behalf of batch jobs.

Batch services are of two types: requested and deferred.

Note: Batch Services are listed in the Shell and Utilities volume of IEEE Std 1003.1-2001, Table 3-5, Batch Services Summary.

3.68 Batch Service Request

A solicitation of services from a batch client to a batch server.

A batch service request may entail the exchange of any number of messages between the batch client and the batch server.

When naming specific types of service requests, the term ‘‘request’’ is qualified by the type of request, as in *Queue Batch Job Request* and *Delete Batch Job Request*.

3.69 Batch Submission

The process by which a batch client requests that a batch server create a batch job via a *Queue Job Request* to perform a specified computational task.

3.70 Batch System

A collection of one or more batch servers.

3.71 Batch Target User

The name of a user on the batch destination batch server.

The target user is the user name under whose account the batch job is to execute on the destination batch server.

3.72 Batch User

A user who is authorized to make use of batch services.

3.73 Bind

The process of assigning a network address to an endpoint.

3.74 Blank Character (<blank>)

One of the characters that belong to the **blank** character class as defined via the *LC_CTYPE* category in the current locale. In the POSIX locale, a <blank> is either a <tab> or a <space>.

3.75 Blank Line

A line consisting solely of zero or more <blank>s terminated by a <newline>; see also Section 3.144 (on page 55).

3.76 Blocked Process (or Thread)

A process (or thread) that is waiting for some condition (other than the availability of a processor) to be satisfied before it can continue execution.

3.77 Blocking

A property of an open file description that causes function calls associated with it to wait for the requested action to be performed before returning.

3.78 Block-Mode Terminal

A terminal device operating in a mode incapable of the character-at-a-time input and output operations described by some of the standard utilities.

Note: Output Devices and Terminal Types are defined in detail in Section 10.2 (on page 185).

3.79 Block Special File

A file that refers to a device. A block special file is normally distinguished from a character special file by providing access to the device in a manner such that the hardware characteristics of the device are not visible.

3.80 Braces

The characters '{' (left brace) and '}' (right brace), also known as curly braces. When used in the phrase ''enclosed in (curly) braces'' the symbol '{' immediately precedes the object to be enclosed, and '}' immediately follows it. When describing these characters in the portable character set, the names <left-brace> and <right-brace> are used.

3.81 Brackets

The characters '[' (left-bracket) and ']' (right-bracket), also known as square brackets. When used in the phrase ''enclosed in (square) brackets'' the symbol '[' immediately precedes the object to be enclosed, and ']' immediately follows it. When describing these characters in the portable character set, the names <left-square-bracket> and <right-square-bracket> are used.

3.82 Broadcast

The transfer of data from one endpoint to several endpoints, as described in RFC 919 and RFC 922.

3.83 Built-In Utility (or Built-In)

A utility implemented within a shell. The utilities referred to as special built-ins have special qualities. Unless qualified, the term ''built-in'' includes the special built-in utilities. Regular built-ins are not required to be actually built into the shell on the implementation, but they do have special command-search qualities.

Note: Special Built-In Utilities are defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.14, Special Built-In Utilities.

Regular Built-In Utilities are defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.9.1.1, Command Search and Execution.

3.84 Byte

An individually addressable unit of data storage that is exactly an octet, used to store a character or a portion of a character; see also Section 3.87 (on page 47). A byte is composed of a contiguous sequence of 8 bits. The least significant bit is called the ''low-order'' bit; the most significant is called the ''high-order'' bit.

Note: The definition of byte from the ISO C standard is broader than the above and might accommodate hardware architectures with different sized addressable units than octets.

3.85 Byte Input/Output Functions

The functions that perform byte-oriented input from streams or byte-oriented output to streams: *fgetc*( ), *fgets*( ), *fprintf*( ), *fputc*( ), *fputs*( ), *fread*( ), *fscanf*( ), *fwrite*( ), *getc*( ), *getchar*( ), *gets*( ), *printf*( ), *putc*( ), *putchar*( ), *puts*( ), *scanf*( ), *ungetc*( ), *vfprintf*( ), and *vprintf*( ).

Note: Functions are defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.86 Carriage-Return Character (<carriage-return>)

A character that in the output stream indicates that printing should start at the beginning of the same physical line in which the <carriage-return> occurred. It is the character designated by `'\r'` in the C language. It is unspecified whether this character is the exact sequence transmitted to an output device by the system to accomplish the movement to the beginning of the line.

3.87 Character

A sequence of one or more bytes representing a single graphic symbol or control code.

Note: This term corresponds to the ISO C standard term multi-byte character, where a single-byte character is a special case of a multi-byte character. Unlike the usage in the ISO C standard, *character* here has no necessary relationship with storage space, and *byte* is used when storage space is discussed.

See the definition of the portable character set in Section 6.1 (on page 113) for a further explanation of the graphical representations of (abstract) characters, as opposed to character encodings.

3.88 Character Array

An array of elements of type **char**.

3.89 Character Class

A named set of characters sharing an attribute associated with the name of the class. The classes and the characters that they contain are dependent on the value of the *LC_CTYPE* category in the current locale.

Note: The *LC_CTYPE* category is defined in detail in Section 7.3.1 (on page 126).

3.90 Character Set

A finite set of different characters used for the representation, organization, or control of data.

3.91 Character Special File

A file that refers to a device. One specific type of character special file is a terminal device file.

Note: The General Terminal Interface is defined in detail in Chapter 11 (on page 187).

3.92 Character String

A contiguous sequence of characters terminated by and including the first null byte.

3.93 Child Process

A new process created (by *fork*(), *posix_spawn*(), *posix_spawnp*(), or *vfork*()) by a given process. A child process remains the child of the creating process as long as both processes continue to exist.

Note: The *fork*(), *posix_spawn*(), *posix_spawnp*(), and *vfork*() functions are defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.94 Circumflex

The character '^'.

3.95 Clock

A software or hardware object that can be used to measure the apparent or actual passage of time.

The current value of the time measured by a clock can be queried and, possibly, set to a value within the legal range of the clock.

3.96 Clock Jump

The difference between two successive distinct values of a clock, as observed from the application via one of the ''get time'' operations.

3.97 Clock Tick

An interval of time; an implementation-defined number of these occur each second. Clock ticks are one of the units that may be used to express a value found in type **clock_t**.

3.98 Coded Character Set

A set of unambiguous rules that establishes a character set and the one-to-one relationship between each character of the set and its bit representation.

3.99 Codeset

The result of applying rules that map a numeric code value to each element of a character set. An element of a character set may be related to more than one numeric code value but the reverse is not true. However, for state-dependent encodings the relationship between numeric code values and elements of a character set may be further controlled by state information. The character set may contain fewer elements than the total number of possible numeric code values; that is, some code values may be unassigned.

Note: Character Encoding is defined in detail in Section 6.2 (on page 116).

3.100 Collating Element

The smallest entity used to determine the logical ordering of character or wide-character strings; see also Section 3.102. A collating element consists of either a single character, or two or more characters collating as a single entity. The value of the *LC_COLLATE* category in the current locale determines the current set of collating elements.

3.101 Collation

The logical ordering of character or wide-character strings according to defined precedence rules. These rules identify a collation sequence between the collating elements, and such additional rules that can be used to order strings consisting of multiple collating elements.

3.102 Collation Sequence

The relative order of collating elements as determined by the setting of the *LC_COLLATE* category in the current locale. The collation sequence is used for sorting and is determined from the collating weights assigned to each collating element. In the absence of weights, the collation sequence is the order in which collating elements are specified between **order_start** and **order_end** keywords in the *LC_COLLATE* category.

Multi-level sorting is accomplished by assigning elements one or more collation weights, up to the limit {COLL_WEIGHTS_MAX}. On each level, elements may be given the same weight (at the primary level, called an equivalence class; see also Section 3.150 (on page 55)) or be omitted from the sequence. Strings that collate equally using the first assigned weight (primary ordering) are then compared using the next assigned weight (secondary ordering), and so on.

Note: {COLL_WEIGHTS_MAX} is defined in detail in **<limits.h>**.

3.103 Column Position

A unit of horizontal measure related to characters in a line.

It is assumed that each character in a character set has an intrinsic column width independent of any output device. Each printable character in the portable character set has a column width of one. The standard utilities, when used as described in IEEE Std 1003.1-2001, assume that all characters have integral column widths. The column width of a character is not necessarily related to the internal representation of the character (numbers of bits or bytes).

The column position of a character in a line is defined as one plus the sum of the column widths of the preceding characters in the line. Column positions are numbered starting from 1.

3.104 Command

A directive to the shell to perform a particular task.

Note: Shell Commands are defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.9, Shell Commands.

3.105 Command Language Interpreter

An interface that interprets sequences of text input as commands. It may operate on an input stream or it may interactively prompt and read commands from a terminal. It is possible for applications to invoke utilities through a number of interfaces, which are collectively considered to act as command interpreters. The most obvious of these are the *sh* utility and the *system*( ) function, although *popen*( ) and the various forms of *exec* may also be considered to behave as interpreters.

Note: The *sh* utility is defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001.

The *system*( ), *popen*( ), and *exec* functions are defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.106 Composite Graphic Symbol

A graphic symbol consisting of a combination of two or more other graphic symbols in a single character position, such as a diacritical mark and a base character.

3.107 Condition Variable

A synchronization object which allows a thread to suspend execution, repeatedly, until some associated predicate becomes true. A thread whose execution is suspended on a condition variable is said to be blocked on the condition variable.

3.108 Connection

An association established between two or more endpoints for the transfer of data

3.109 Connection Mode

The transfer of data in the context of a connection; see also Section 3.110.

3.110 Connectionless Mode

The transfer of data other than in the context of a connection; see also Section 3.109 and Section 3.123 (on page 52).

3.111 Control Character

A character, other than a graphic character, that affects the recording, processing, transmission, or interpretation of text.

3.112 Control Operator

In the shell command language, a token that performs a control function. It is one of the following symbols:

```
&    &&    (    )    ;    ;;    newline    |    ||
```

The end-of-input indicator used internally by the shell is also considered a control operator.

Note: Token Recognition is defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.3, Token Recognition.

3.113 Controlling Process

The session leader that established the connection to the controlling terminal. If the terminal subsequently ceases to be a controlling terminal for this session, the session leader ceases to be the controlling process.

3.114 Controlling Terminal

A terminal that is associated with a session. Each session may have at most one controlling terminal associated with it, and a controlling terminal is associated with exactly one session. Certain input sequences from the controlling terminal cause signals to be sent to all processes in the process group associated with the controlling terminal.

Note: The General Terminal Interface is defined in detail in Chapter 11 (on page 187).

3.115 Conversion Descriptor

A per-process unique value used to identify an open codeset conversion.

3.116 Core File

A file of unspecified format that may be generated when a process terminates abnormally.

3.117 CPU Time (Execution Time)

The time spent executing a process or thread, including the time spent executing system services on behalf of that process or thread. If the Threads option is supported, then the value of the CPU-time clock for a process is implementation-defined. With this definition the sum of all the execution times of all the threads in a process might not equal the process execution time, even in a single-threaded process, because implementations may differ in how they account for time during context switches or for other reasons.

3.118 CPU-Time Clock

A clock that measures the execution time of a particular process or thread.

3.119 CPU-Time Timer

A timer attached to a CPU-time clock.

3.120 Current Job

In the context of job control, the job that will be used as the default for the *fg* or *bg* utilities. There is at most one current job; see also Section 3.203 (on page 63).

3.121 Current Working Directory

See *Working Directory* in Section 3.436 (on page 95).

3.122 Cursor Position

The line and column position on the screen denoted by the terminal's cursor.

3.123 Datagram

A unit of data transferred from one endpoint to another in connectionless mode service.

3.124 Data Segment

Memory associated with a process, that can contain dynamically allocated data.

3.125 Deferred Batch Service

A service that is performed as a result of events that are asynchronous with respect to requests.

Note: Once a batch job has been created, it is subject to deferred services.

3.126 Device

A computer peripheral or an object that appears to the application as such.

3.127 Device ID

A non-negative integer used to identify a device.

3.128 Directory

A file that contains directory entries. No two directory entries in the same directory have the same name.

3.129 Directory Entry (or Link)

An object that associates a filename with a file. Several directory entries can associate names with the same file.

3.130 Directory Stream

A sequence of all the directory entries in a particular directory. An open directory stream may be implemented using a file descriptor.

3.131 Disarm (a Timer)

To stop a timer from measuring the passage of time, disabling any future process notifications (until the timer is armed again).

3.132 Display

To output to the user's terminal. If the output is not directed to a terminal, the results are undefined.

3.133 Display Line

A line of text on a physical device or an emulation thereof. Such a line will have a maximum number of characters which can be presented.

Note: This may also be written as ''line on the display''.

3.134 Dollar Sign

The character '$'.

3.135 Dot

In the context of naming files, the filename consisting of a single dot character ('.').

Note: In the context of shell special built-in utilities, see *dot* in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.14, Special Built-In Utilities.

Pathname Resolution is defined in detail in Section 4.11 (on page 100).

3.136 Dot-Dot

The filename consisting solely of two dot characters ("..").

Note: Pathname Resolution is defined in detail in Section 4.11 (on page 100).

3.137 Double-Quote

The character '"', also known as quotation-mark.

Note: The ''double'' adjective in this term refers to the two strokes in the character glyph. IEEE Std 1003.1-2001 never uses the term ''double-quote'' to refer to two apostrophes or quotation marks.

3.138 Downshifting

The conversion of an uppercase character that has a single-character lowercase representation into this lowercase representation.

3.139 Driver

A module that controls data transferred to and received from devices.

Note: Drivers are traditionally written to be a part of the system implementation, although they are frequently written separately from the writing of the implementation. A driver may contain processor-specific code, and therefore be non-portable.

3.140 Effective Group ID

An attribute of a process that is used in determining various permissions, including file access permissions; see also Section 3.188 (on page 61).

3.141 Effective User ID

An attribute of a process that is used in determining various permissions, including file access permissions; see also Section 3.425 (on page 93).

3.142 Eight-Bit Transparency

The ability of a software component to process 8-bit characters without modifying or utilizing any part of the character in a way that is inconsistent with the rules of the current coded character set.

3.143 Empty Directory

A directory that contains, at most, directory entries for dot and dot-dot, and has exactly one link to it, in dot-dot. No other links to the directory may exist. It is unspecified whether an implementation can ever consider the root directory to be empty.

3.144 Empty Line

A line consisting of only a <newline>; see also Section 3.75 (on page 45).

3.145 Empty String (or Null String)

A string whose first byte is a null byte.

3.146 Empty Wide-Character String

A wide-character string whose first element is a null wide-character code.

3.147 Encoding Rule

The rules used to convert between wide-character codes and multi-byte character codes.

Note: Stream Orientation and Encoding Rules are defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.5.2, Stream Orientation and Encoding Rules.

3.148 Entire Regular Expression

The concatenated set of one or more basic regular expressions or extended regular expressions that make up the pattern specified for string selection.

Note: Regular Expressions are defined in detail in Chapter 9 (on page 169).

3.149 Epoch

The time zero hours, zero minutes, zero seconds, on January 1, 1970 Coordinated Universal Time (UTC).

Note: See also Seconds Since the Epoch defined in Section 4.14 (on page 102).

3.150 Equivalence Class

A set of collating elements with the same primary collation weight.

Elements in an equivalence class are typically elements that naturally group together, such as all accented letters based on the same base letter.

The collation order of elements within an equivalence class is determined by the weights assigned on any subsequent levels after the primary weight.

3.151 Era

A locale-specific method for counting and displaying years.

Note: The *LC_TIME* category is defined in detail in Section 7.3.5 (on page 147).

3.152 Event Management

The mechanism that enables applications to register for and be made aware of external events such as data becoming available for reading.

3.153 Executable File

A regular file acceptable as a new process image file by the equivalent of the *exec* family of functions, and thus usable as one form of a utility. The standard utilities described as compilers can produce executable files, but other unspecified methods of producing executable files may also be provided. The internal format of an executable file is unspecified, but a conforming application cannot assume an executable file is a text file.

3.154 Execute

To perform command search and execution actions, as defined in the Shell and Utilities volume of IEEE Std 1003.1-2001; see also Section 3.200 (on page 62).

Note: Command Search and Execution is defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.9.1.1, Command Search and Execution.

3.155 Execution Time

See *CPU Time* in Section 3.117 (on page 51).

3.156 Execution Time Monitoring

A set of execution time monitoring primitives that allow online measuring of thread and process execution times.

3.157 Expand

In the shell command language, when not qualified, the act of applying word expansions.

Note: Word Expansions are defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.6, Word Expansions.

3.158 Extended Regular Expression (ERE)

A regular expression (see also Section 3.316 (on page 79)) that is an alternative to the Basic Regular Expression using a more extensive syntax, occasionally used by some utilities.

Note: Extended Regular Expressions are described in detail in Section 9.4 (on page 175).

3.159 Extended Security Controls

Implementation-defined security controls allowed by the file access permission and appropriate privilege (see also Section 3.19 (on page 37)) mechanisms, through which an implementation can support different security policies from those described in IEEE Std 1003.1-2001.

Note: See also Extended Security Controls defined in Section 4.3 (on page 97).

File Access Permissions are defined in detail in Section 4.4 (on page 97).

3.160 Feature Test Macro

A macro used to determine whether a particular set of features is included from a header.

Note: See also the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.2, The Compilation Environment.

3.161 Field

In the shell command language, a unit of text that is the result of parameter expansion, arithmetic expansion, command substitution, or field splitting. During command processing, the resulting fields are used as the command name and its arguments.

Note: Parameter Expansion is defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.6.2, Parameter Expansion.

Arithmetic Expansion is defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.6.4, Arithmetic Expansion.

Command Substitution is defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.6.3, Command Substitution.

Field Splitting is defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.6.5, Field Splitting.

For further information on command processing, see the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.9.1, Simple Commands.

3.162 FIFO Special File (or FIFO)

A type of file with the property that data written to such a file is read on a first-in-first-out basis.

Note: Other characteristics of FIFOs are described in the System Interfaces volume of IEEE Std 1003.1-2001, *lseek*( ), *open*( ), *read*( ), and *write*( ).

3.163 File

An object that can be written to, or read from, or both. A file has certain attributes, including access permissions and type. File types include regular file, character special file, block special file, FIFO special file, symbolic link, socket, and directory. Other types of files may be supported by the implementation.

3.164 File Description

See *Open File Description* in Section 3.253 (on page 70).

3.165 File Descriptor

A per-process unique, non-negative integer used to identify an open file for the purpose of file access. The value of a file descriptor is from zero to {OPEN_MAX}. A process can have no more than {OPEN_MAX} file descriptors open simultaneously. File descriptors may also be used to implement message catalog descriptors and directory streams; see also Section 3.253 (on page 70).

Note: {OPEN_MAX} is defined in detail in **<limits.h>**.

3.166 File Group Class

The property of a file indicating access permissions for a process related to the group identification of a process. A process is in the file group class of a file if the process is not in the file owner class and if the effective group ID or one of the supplementary group IDs of the process matches the group ID associated with the file. Other members of the class may be implementation-defined.

3.167 File Mode

An object containing the file mode bits and file type of a file.

Note: File mode bits and file types are defined in detail in **<sys/stat.h>**.

3.168 File Mode Bits

A file's file permission bits: set-user-ID-on-execution bit (S_ISUID), set-group-ID-on-execution bit (S_ISGID), and, on directories, the restricted deletion flag bit (S_ISVTX).

Note: File Mode Bits are defined in detail in **<sys/stat.h>**.

3.169 Filename

A name consisting of 1 to {NAME_MAX} bytes used to name a file. The characters composing the name may be selected from the set of all character values excluding the slash character and the null byte. The filenames dot and dot-dot have special meaning. A filename is sometimes referred to as a ''pathname component''.

Note: Pathname Resolution is defined in detail in Section 4.11 (on page 100).

3.170 Filename Portability

Filenames should be constructed from the portable filename character set because the use of other characters can be confusing or ambiguous in certain contexts. (For example, the use of a colon (':') in a pathname could cause ambiguity if that pathname were included in a *PATH* definition.)

3.171 File Offset

The byte position in the file where the next I/O operation begins. Each open file description associated with a regular file, block special file, or directory has a file offset. A character special file that does not refer to a terminal device may have a file offset. There is no file offset specified for a pipe or FIFO.

3.172 File Other Class

The property of a file indicating access permissions for a process related to the user and group identification of a process. A process is in the file other class of a file if the process is not in the file owner class or file group class.

3.173 File Owner Class

The property of a file indicating access permissions for a process related to the user identification of a process. A process is in the file owner class of a file if the effective user ID of the process matches the user ID of the file.

3.174 File Permission Bits

Information about a file that is used, along with other information, to determine whether a process has read, write, or execute/search permission to a file. The bits are divided into three parts: owner, group, and other. Each part is used with the corresponding file class of processes. These bits are contained in the file mode.

Note: File modes are defined in detail in **<sys/stat.h>**.

File Access Permissions are defined in detail in Section 4.4 (on page 97).

3.175 File Serial Number

A per-file system unique identifier for a file.

3.176 File System

A collection of files and certain of their attributes. It provides a name space for file serial numbers referring to those files.

3.177 File Type

See *File* in Section 3.163 (on page 57).

3.178 Filter

A command whose operation consists of reading data from standard input or a list of input files and writing data to standard output. Typically, its function is to perform some transformation on the data stream.

3.179 First Open (of a File)

When a process opens a file that is not currently an open file within any process.

3.180 Flow Control

The mechanism employed by a communications provider that constrains a sending entity to wait until the receiving entities can safely receive additional data without loss.

3.181 Foreground Job

See *Foreground Process Group* in Section 3.183.

3.182 Foreground Process

A process that is a member of a foreground process group.

3.183 Foreground Process Group (or Foreground Job)

A process group whose member processes have certain privileges, denied to processes in background process groups, when accessing their controlling terminal. Each session that has established a connection with a controlling terminal has at most one process group of the session as the foreground process group of that controlling terminal.

Note: The General Terminal Interface is defined in detail in Chapter 11.

3.184 Foreground Process Group ID

The process group ID of the foreground process group.

3.185 Form-Feed Character (<form-feed>)

A character that in the output stream indicates that printing should start on the next page of an output device. It is the character designated by `'\f'` in the C language. If the <form-feed> is not the first character of an output line, the result is unspecified. It is unspecified whether this character is the exact sequence transmitted to an output device by the system to accomplish the movement to the next page.

3.186 Graphic Character

A member of the **graph** character class of the current locale.

Note: The **graph** character class is defined in detail in Section 7.3.1 (on page 126).

3.187 Group Database

A system database that contains at least the following information for each group ID: 2

- Group name
- Numerical group ID
- List of users allowed in the group

The list of users allowed in the group is used by the *newgrp* utility.

Note: The *newgrp* utility is defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001.

3.188 Group ID

A non-negative integer, which can be contained in an object of type **gid_t**, that is used to identify a group of system users. Each system user is a member of at least one group. When the identity of a group is associated with a process, a group ID value is referred to as a real group ID, an effective group ID, one of the supplementary group IDs, or a saved set-group-ID.

3.189 Group Name

A string that is used to identify a group; see also Section 3.187. To be portable across conforming systems, the value is composed of characters from the portable filename character set. The hyphen should not be used as the first character of a portable group name.

3.190 Hard Limit

A system resource limitation that may be reset to a lesser or greater limit by a privileged process. A non-privileged process is restricted to only lowering its hard limit.

3.191 Hard Link

The relationship between two directory entries that represent the same file; see also Section 3.129 (on page 53). The result of an execution of the *ln* utility (without the **–s** option) or the *link*( ) function. This term is contrasted against symbolic link; see also Section 3.372 (on page 86).

3.192 Home Directory

The directory specified by the *HOME* environment variable.

3.193 Host Byte Order

The arrangement of bytes in any integer type when using a specific machine architecture.

Note: Two common methods of byte ordering are big-endian and little-endian. Big-endian is a format for storage of binary data in which the most significant byte is placed first, with the rest in descending order. Little-endian is a format for storage or transmission of binary data in which the least significant byte is placed first, with the rest in ascending order. See also Section 4.8 (on page 99).

3.194 Incomplete Line

A sequence of one or more non-<newline>s at the end of the file.

3.195 Inf

A value representing +infinity or a value representing –infinity that can be stored in a floating type. Not all systems support the Inf values.

3.196 Instrumented Application

An application that contains at least one call to the trace point function *posix_trace_event*( ). Each process of an instrumented application has a mapping of trace event names to trace event type identifiers. This mapping is used by the trace stream that is created for that process.

3.197 Interactive Shell

A processing mode of the shell that is suitable for direct user interaction.

3.198 Internationalization

The provision within a computer program of the capability of making itself adaptable to the requirements of different native languages, local customs, and coded character sets.

3.199 Interprocess Communication

A functionality enhancement to add a high-performance, deterministic interprocess communication facility for local communication.

3.200 Invoke

To perform command search and execution actions, except that searching for shell functions and special built-in utilities is suppressed; see also Section 3.154 (on page 56).

Note: Command Search and Execution is defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.9.1.1, Command Search and Execution.

3.201 Job

A set of processes, comprising a shell pipeline, and any processes descended from it, that are all in the same process group.

Note: See also the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.9.2, Pipelines.

3.202 Job Control

A facility that allows users selectively to stop (suspend) the execution of processes and continue (resume) their execution at a later point. The user typically employs this facility via the interactive interface jointly supplied by the terminal I/O driver and a command interpreter.

3.203 Job Control Job ID

A handle that is used to refer to a job. The job control job ID can be any of the forms shown in the following table:

Table 3-1 Job Control Job ID Formats

Job Control Job ID	Meaning
%%	Current job.
%+	Current job.
%–	Previous job.
%*n*	Job number *n*.
%*string*	Job whose command begins with *string*.
%?*string*	Job whose command contains *string*.

3.204 Last Close (of a File)

When a process closes a file, resulting in the file not being an open file within any process.

3.205 Line

A sequence of zero or more non-<newline>s plus a terminating <newline>.

3.206 Linger

A period of time before terminating a connection, to allow outstanding data to be transferred.

3.207 Link

See *Directory Entry* in Section 3.129 (on page 53).

3.208 Link Count

The number of directory entries that refer to a particular file.

3.209 Local Customs

The conventions of a geographical area or territory for such things as date, time, and currency formats.

3.210 Local Interprocess Communication (Local IPC)

The transfer of data between processes in the same system.

3.211 Locale

The definition of the subset of a user's environment that depends on language and cultural conventions.

Note: Locales are defined in detail in Chapter 7 (on page 123).

3.212 Localization

The process of establishing information within a computer system specific to the operation of particular native languages, local customs, and coded character sets.

3.213 Login

The unspecified activity by which a user gains access to the system. Each login is associated with exactly one login name.

3.214 Login Name

A user name that is associated with a login.

3.215 Map

To create an association between a page-aligned range of the address space of a process and some memory object, such that a reference to an address in that range of the address space results in a reference to the associated memory object. The mapped memory object is not necessarily memory-resident.

3.216 Marked Message

A STREAMs message on which a certain flag is set. Marking a message gives the application protocol-specific information. An application can use *ioctl*( ) to determine whether a given message is marked.

Note: The *ioctl*( ) function is defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.217 Matched

A state applying to a sequence of zero or more characters when the characters in the sequence correspond to a sequence of characters defined by a basic regular expression or extended regular expression pattern.

Note: Regular Expressions are defined in detail in Chapter 9 (on page 169).

3.218 Memory Mapped Files

A facility to allow applications to access files as part of the address space.

3.219 Memory Object

One of:

- A file (see Section 3.163 (on page 57))
- A shared memory object (see Section 3.340 (on page 82))
- A typed memory object (see Section 3.418 (on page 92))

When used in conjunction with *mmap*( ), a memory object appears in the address space of the calling process.

Note: The *mmap*( ) function is defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.220 Memory-Resident

The process of managing the implementation in such a way as to provide an upper bound on memory access times.

3.221 Message

In the context of programmatic message passing, information that can be transferred between processes or threads by being added to and removed from a message queue. A message consists of a fixed-size message buffer.

3.222 Message Catalog

In the context of providing natural language messages to the user, a file or storage area containing program messages, command prompts, and responses to prompts for a particular native language, territory, and codeset.

3.223 Message Catalog Descriptor

In the context of providing natural language messages to the user, a per-process unique value used to identify an open message catalog. A message catalog descriptor may be implemented using a file descriptor.

3.224 Message Queue

In the context of programmatic message passing, an object to which messages can be added and removed. Messages may be removed in the order in which they were added or in priority order.

3.225 Mode

A collection of attributes that specifies a file's type and its access permissions.

Note: File Access Permissions are defined in detail in Section 4.4 (on page 97).

3.226 Monotonic Clock

A clock whose value cannot be set via *clock_settime*( ) and which cannot have negative clock jumps.

3.227 Mount Point

Either the system root directory or a directory for which the *st_dev* field of structure **stat** differs from that of its parent directory.

Note: The **stat** structure is defined in detail in **<sys/stat.h>**.

3.228 Multi-Character Collating Element

A sequence of two or more characters that collate as an entity. For example, in some coded character sets, an accented character is represented by a non-spacing accent, followed by the letter. Other examples are the Spanish elements *ch* and *ll*.

3.229 Mutex

A synchronization object used to allow multiple threads to serialize their access to shared data. The name derives from the capability it provides; namely, mutual-exclusion. The thread that has locked a mutex becomes its owner and remains the owner until that same thread unlocks the mutex.

3.230 Name

In the shell command language, a word consisting solely of underscores, digits, and alphabetics from the portable character set. The first character of a name is not a digit.

Note: The Portable Character Set is defined in detail in Section 6.1 (on page 113).

3.231 Named STREAM

A STREAMS-based file descriptor that is attached to a name in the file system name space. All subsequent operations on the named STREAM act on the STREAM that was associated with the file descriptor until the name is disassociated from the STREAM.

3.232 NaN (Not a Number)

A set of values that may be stored in a floating type but that are neither Inf nor valid floating-point numbers. Not all systems support NaN values.

3.233 Native Language

A computer user's spoken or written language, such as American English, British English, Danish, Dutch, French, German, Italian, Japanese, Norwegian, or Swedish.

3.234 Negative Response

An input string that matches one of the responses acceptable to the *LC_MESSAGES* category keyword **noexpr**, matching an extended regular expression in the current locale.

Note: The *LC_MESSAGES* category is defined in detail in Section 7.3.6 (on page 152).

3.235 Network

A collection of interconnected hosts.

Note: The term ''network'' in IEEE Std 1003.1-2001 is used to refer to the network of hosts. The term ''batch system'' is used to refer to the network of batch servers.

3.236 Network Address

A network-visible identifier used to designate specific endpoints in a network. Specific endpoints on host systems have addresses, and host systems may also have addresses.

3.237 Network Byte Order

The way of representing any integer type such that, when transmitted over a network via a network endpoint, the **int** type is transmitted as an appropriate number of octets with the most significant octet first, followed by any other octets in descending order of significance.

Note: This order is more commonly known as big-endian ordering. See also Section 4.8 (on page 99).

3.238 Newline Character (<newline>)

A character that in the output stream indicates that printing should start at the beginning of the next line. It is the character designated by `'\n'` in the C language. It is unspecified whether this character is the exact sequence transmitted to an output device by the system to accomplish the movement to the next line.

3.239 Nice Value

A number used as advice to the system to alter process scheduling. Numerically smaller values give a process additional preference when scheduling a process to run. Numerically larger values reduce the preference and make a process less likely to run. Typically, a process with a smaller nice value runs to completion more quickly than an equivalent process with a higher nice value. The symbol {NZERO} specifies the default nice value of the system.

3.240 Non-Blocking

A property of an open file description that causes function calls involving it to return without delay when it is detected that the requested action associated with the function call cannot be completed without unknown delay.

Note: The exact semantics are dependent on the type of file associated with the open file description. For data reads from devices such as ttys and FIFOs, this property causes the read to return immediately when no data was available. Similarly, for writes, it causes the call to return immediately when the thread would otherwise be delayed in the write operation; for example, because no space was available. For networking, it causes functions not to await protocol events (for example, acknowledgements) to occur. See also the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.10.7, Socket I/O Mode.

3.241 Non-Spacing Characters

A character, such as a character representing a diacritical mark in the ISO/IEC 6937:2001 standard coded character set, which is used in combination with other characters to form composite graphic symbols. 2

3.242 NUL

A character with all bits set to zero.

3.243 Null Byte

A byte with all bits set to zero.

3.244 Null Pointer

The value that is obtained by converting the number 0 into a pointer; for example, (**void** *) 0. The C language guarantees that this value does not match that of any legitimate pointer, so it is used by many functions that return pointers to indicate an error.

3.245 Null String

See *Empty String* in Section 3.145 (on page 55).

3.246 Null Wide-Character Code

A wide-character code with all bits set to zero.

3.247 Number Sign

The character '#', also known as hash sign.

3.248 Object File

A regular file containing the output of a compiler, formatted as input to a linkage editor for linking with other object files into an executable form. The methods of linking are unspecified and may involve the dynamic linking of objects at runtime. The internal format of an object file is unspecified, but a conforming application cannot assume an object file is a text file.

3.249 Octet

Unit of data representation that consists of eight contiguous bits.

3.250 Offset Maximum

An attribute of an open file description representing the largest value that can be used as a file offset.

3.251 Opaque Address

An address such that the entity making use of it requires no details about its contents or format.

3.252 Open File

A file that is currently associated with a file descriptor.

3.253 Open File Description

A record of how a process or group of processes is accessing a file. Each file descriptor refers to exactly one open file description, but an open file description can be referred to by more than one file descriptor. The file offset, file status, and file access modes are attributes of an open file description.

3.254 Operand

An argument to a command that is generally used as an object supplying information to a utility necessary to complete its processing. Operands generally follow the options in a command line.

Note: Utility Argument Syntax is defined in detail in Section 12.1 (on page 201).

3.255 Operator

In the shell command language, either a control operator or a redirection operator.

3.256 Option

An argument to a command that is generally used to specify changes in the utility's default behavior.

Note: Utility Argument Syntax is defined in detail in Section 12.1 (on page 201).

3.257 Option-Argument

A parameter that follows certain options. In some cases an option-argument is included within the same argument string as the option—in most cases it is the next argument.

Note: Utility Argument Syntax is defined in detail in Section 12.1 (on page 201).

3.258 Orientation

A stream has one of three orientations: unoriented, byte-oriented, or wide-oriented.

Note: For further information, see the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.5.2, Stream Orientation and Encoding Rules.

3.259 Orphaned Process Group

A process group in which the parent of every member is either itself a member of the group or is not a member of the group's session.

3.260 Page

The granularity of process memory mapping or locking.

Physical memory and memory objects can be mapped into the address space of a process on page boundaries and in integral multiples of pages. Process address space can be locked into memory (made memory-resident) on page boundaries and in integral multiples of pages.

3.261 Page Size

The size, in bytes, of the system unit of memory allocation, protection, and mapping. On systems that have segment rather than page-based memory architectures, the term ‘‘page’’ means a segment.

3.262 Parameter

In the shell command language, an entity that stores values. There are three types of parameters: variables (named parameters), positional parameters, and special parameters. Parameter expansion is accomplished by introducing a parameter with the `'$'` character.

Note: See also the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.5, Parameters and Variables.

In the C language, an object declared as part of a function declaration or definition that acquires a value on entry to the function, or an identifier following the macro name in a function-like macro definition.

3.263 Parent Directory

When discussing a given directory, the directory that both contains a directory entry for the given directory and is represented by the pathname dot-dot in the given directory.

When discussing other types of files, a directory containing a directory entry for the file under discussion.

This concept does not apply to dot and dot-dot.

3.264 Parent Process

The process which created (or inherited) the process under discussion.

3.265 Parent Process ID

An attribute of a new process identifying the parent of the process. The parent process ID of a process is the process ID of its creator, for the lifetime of the creator. After the creator’s lifetime has ended, the parent process ID is the process ID of an implementation-defined system process.

3.266 Pathname

A character string that is used to identify a file. In the context of IEEE Std 1003.1-2001, a pathname consists of, at most, {PATH_MAX} bytes, including the terminating null byte. It has an optional beginning slash, followed by zero or more filenames separated by slashes. A pathname may optionally contain one or more trailing slashes. Multiple successive slashes are considered to be the same as one slash.

Note: Pathname Resolution is defined in detail in Section 4.11 (on page 100).

3.267 Pathname Component

See *Filename* in Section 3.169 (on page 58).

3.268 Path Prefix

A pathname, with an optional ending slash, that refers to a directory.

3.269 Pattern

A sequence of characters used either with regular expression notation or for pathname expansion, as a means of selecting various character strings or pathnames, respectively.

Note: Regular Expressions are defined in detail in Chapter 9 (on page 169).

See also the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.6.6, Pathname Expansion.

The syntaxes of the two types of patterns are similar, but not identical; IEEE Std 1003.1-2001 always indicates the type of pattern being referred to in the immediate context of the use of the term.

3.270 Period

The character '.'. The term ''period'' is contrasted with dot (see also Section 3.135 (on page 53)), which is used to describe a specific directory entry.

3.271 Permissions

Attributes of an object that determine the privilege necessary to access or manipulate the object.

Note: File Access Permissions are defined in detail in Section 4.4 (on page 97).

3.272 Persistence

A mode for semaphores, shared memory, and message queues requiring that the object and its state (including data, if any) are preserved after the object is no longer referenced by any process.

Persistence of an object does not imply that the state of the object is maintained across a system crash or a system reboot.

3.273 Pipe

An object accessed by one of the pair of file descriptors created by the *pipe*( ) function. Once created, the file descriptors can be used to manipulate it, and it behaves identically to a FIFO special file when accessed in this way. It has no name in the file hierarchy.

Note: The *pipe*( ) function is defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.274 Polling

A scheduling scheme whereby the local process periodically checks until the pre-specified events (for example, read, write) have occurred.

3.275 Portable Character Set

The collection of characters that are required to be present in all locales supported by conforming systems.

Note: The Portable Character Set is defined in detail in Section 6.1 (on page 113).

This term is contrasted against the smaller portable filename character set; see also Section 3.276.

3.276 Portable Filename Character Set

The set of characters from which portable filenames are constructed.

```
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
a b c d e f g h i j k l m n o p q r s t u v w x y z
0 1 2 3 4 5 6 7 8 9 . _ -
```

The last three characters are the period, underscore, and hyphen characters, respectively.

3.277 Positional Parameter

In the shell command language, a parameter denoted by a single digit or one or more digits in curly braces.

Note: For further information, see the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.5.1, Positional Parameters.

3.278 Preallocation

The reservation of resources in a system for a particular use.

Preallocation does not imply that the resources are immediately allocated to that use, but merely indicates that they are guaranteed to be available in bounded time when needed.

3.279 Preempted Process (or Thread)

A running thread whose execution is suspended due to another thread becoming runnable at a higher priority.

3.280 Previous Job

In the context of job control, the job that will be used as the default for the *fg* or *bg* utilities if the current job exits. There is at most one previous job; see also Section 3.203 (on page 63).

3.281 Printable Character

One of the characters included in the **print** character classification of the *LC_CTYPE* category in the current locale.

Note: The *LC_CTYPE* category is defined in detail in Section 7.3.1 (on page 126).

3.282 Printable File

A text file consisting only of the characters included in the **print** and **space** character classifications of the *LC_CTYPE* category and the <backspace>, all in the current locale.

Note: The *LC_CTYPE* category is defined in detail in Section 7.3.1 (on page 126).

3.283 Priority

A non-negative integer associated with processes or threads whose value is constrained to a range defined by the applicable scheduling policy. Numerically higher values represent higher priorities.

3.284 Priority Band

The queuing order applied to normal priority STREAMS messages. High priority STREAMS messages are not grouped by priority bands. The only differentiation made by the STREAMS mechanism is between zero and non-zero bands, but specific protocol modules may differentiate between priority bands.

3.285 Priority Inversion

A condition in which a thread that is not voluntarily suspended (waiting for an event or time delay) is not running while a lower priority thread is running. Such blocking of the higher priority thread is often caused by contention for a shared resource.

3.286 Priority Scheduling

A performance and determinism improvement facility to allow applications to determine the order in which threads that are ready to run are granted access to processor resources.

3.287 Priority-Based Scheduling

Scheduling in which the selection of a running thread is determined by the priorities of the runnable processes or threads.

3.288 Privilege

See *Appropriate Privileges* in Section 3.19 (on page 37).

3.289 Process

An address space with one or more threads executing within that address space, and the required system resources for those threads.

Note: Many of the system resources defined by IEEE Std 1003.1-2001 are shared among all of the threads within a process. These include the process ID, the parent process ID, process group ID, session membership, real, effective, and saved set-user-ID, real, effective, and saved set-group-ID, supplementary group IDs, current working directory, root directory, file mode creation mask, and file descriptors.

3.290 Process Group

A collection of processes that permits the signaling of related processes. Each process in the system is a member of a process group that is identified by a process group ID. A newly created process joins the process group of its creator.

3.291 Process Group ID

The unique positive integer identifier representing a process group during its lifetime.

Note: See also Process Group ID Reuse defined in Section 4.12 (on page 101).

3.292 Process Group Leader

A process whose process ID is the same as its process group ID.

3.293 Process Group Lifetime

A period of time that begins when a process group is created and ends when the last remaining process in the group leaves the group, due either to the end of the last process' lifetime or to the last remaining process calling the *setsid*( ) or *setpgid*( ) functions.

Note: The *setsid*( ) and *setpgid*( ) functions are defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.294 Process ID

The unique positive integer identifier representing a process during its lifetime.

Note: See also Process ID Reuse defined in Section 4.12 (on page 101).

3.295 Process Lifetime

The period of time that begins when a process is created and ends when its process ID is returned to the system. After a process is created by *fork*( ), *posix_spawn*( ), *posix_spawnp*( ), or *vfork*( ), it is considered active. At least one thread of control and address space exist until it terminates. It then enters an inactive state where certain resources may be returned to the system, although some resources, such as the process ID, are still in use. When another process executes a *wait*( ), *waitid*( ), or *waitpid*( ) function for an inactive process, the remaining resources are returned to the system. The last resource to be returned to the system is the process ID. At this time, the lifetime of the process ends.

Note: The *fork*( ), *posix_spawn*( ), *posix_spawnp*( ), *vfork*( ), *wait*( ), *waitid*( ), and *waitpid*( ) functions are defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.296 Process Memory Locking

A performance improvement facility to bind application programs into the high-performance random access memory of a computer system. This avoids potential latencies introduced by the operating system in storing parts of a program that were not recently referenced on secondary memory devices.

3.297 Process Termination

There are two kinds of process termination:

1. Normal termination occurs by a return from *main*( ), when requested with the *exit*( ), *_exit*( ), or *_Exit*( ) functions; or when the last thread in the process terminates by returning from its start function, by calling the *pthread_exit*( ) function, or through cancellation.
2. Abnormal termination occurs when requested by the *abort*( ) function or when some signals are received.

Note: The *_exit*( ), *_Exit*( ), *abort*( ), and *exit*( ) functions are defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.298 Process-To-Process Communication

The transfer of data between processes.

3.299 Process Virtual Time

The measurement of time in units elapsed by the system clock while a process is executing.

3.300 Program

A prepared sequence of instructions to the system to accomplish a defined task. The term ''program'' in IEEE Std 1003.1-2001 encompasses applications written in the Shell Command Language, complex utility input languages (for example, *awk*, *lex*, *sed*, and so on), and high-level languages.

3.301 Protocol

A set of semantic and syntactic rules for exchanging information.

3.302 Pseudo-Terminal

A facility that provides an interface that is identical to the terminal subsystem. A pseudo-terminal is composed of two devices: the ''master device'' and a ''slave device''. The slave device provides processes with an interface that is identical to the terminal interface, although there need not be hardware behind that interface. Anything written on the master device is presented to the slave as an input and anything written on the slave device is presented as an input on the master side.

3.303 Radix Character

The character that separates the integer part of a number from the fractional part.

3.304 Read-Only File System

A file system that has implementation-defined characteristics restricting modifications.

Note: File Times Update is described in detail in Section 4.7 (on page 98).

3.305 Read-Write Lock

Multiple readers, single writer (read-write) locks allow many threads to have simultaneous read-only access to data while allowing only one thread to have write access at any given time. They are typically used to protect data that is read-only more frequently than it is changed.

Read-write locks can be used to synchronize threads in the current process and other processes if they are allocated in memory that is writable and shared among the cooperating processes and have been initialized for this behavior.

3.306 Real Group ID

The attribute of a process that, at the time of process creation, identifies the group of the user who created the process; see also Section 3.188 (on page 61).

3.307 Real Time

Time measured as total units elapsed by the system clock without regard to which thread is executing.

3.308 Realtime Signal Extension

A determinism improvement facility to enable asynchronous signal notifications to an application to be queued without impacting compatibility with the existing signal functions.

3.309 Real User ID

The attribute of a process that, at the time of process creation, identifies the user who created the process; see also Section 3.425 (on page 93).

3.310 Record

A collection of related data units or words which is treated as a unit.

3.311 Redirection

In the shell command language, a method of associating files with the input or output of commands.

Note: For further information, see the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.7, Redirection.

3.312 Redirection Operator

In the shell command language, a token that performs a redirection function. It is one of the following symbols:

< > >| << >> <& >& <<– <>

3.313 Reentrant Function

A function whose effect, when called by two or more threads, is guaranteed to be as if the threads each executed the function one after another in an undefined order, even if the actual execution is interleaved.

3.314 Referenced Shared Memory Object

A shared memory object that is open or has one or more mappings defined on it.

3.315 Refresh

To ensure that the information on the user's terminal screen is up-to-date.

3.316 Regular Expression

A pattern that selects specific strings from a set of character strings.

Note: Regular Expressions are described in detail in Chapter 9 (on page 169).

3.317 Region

In the context of the address space of a process, a sequence of addresses.

In the context of a file, a sequence of offsets.

3.318 Regular File

A file that is a randomly accessible sequence of bytes, with no further structure imposed by the system.

3.319 Relative Pathname

A pathname not beginning with a slash.

Note: Pathname Resolution is defined in detail in Section 4.11 (on page 100).

3.320 Relocatable File

A file holding code or data suitable for linking with other object files to create an executable or a shared object file.

3.321 Relocation

The process of connecting symbolic references with symbolic definitions. For example, when a program calls a function, the associated call instruction transfers control to the proper destination address at execution.

3.322 Requested Batch Service

A service that is either rejected or performed prior to a response from the service to the requester.

3.323 (Time) Resolution

The minimum time interval that a clock can measure or whose passage a timer can detect.

3.324 Root Directory

A directory, associated with a process, that is used in pathname resolution for pathnames that begin with a slash.

3.325 Runnable Process (or Thread)

A thread that is capable of being a running thread, but for which no processor is available.

3.326 Running Process (or Thread)

A thread currently executing on a processor. On multi-processor systems there may be more than one such thread in a system at a time.

3.327 Saved Resource Limits

An attribute of a process that provides some flexibility in the handling of unrepresentable resource limits, as described in the *exec* family of functions and *setrlimit*( ).

Note: The *exec* and *setrlimit*( ) functions are defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.328 Saved Set-Group-ID

An attribute of a process that allows some flexibility in the assignment of the effective group ID attribute, as described in the *exec* family of functions and *setgid*( ).

Note: The *exec* and *setgid*( ) functions are defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.329 Saved Set-User-ID

An attribute of a process that allows some flexibility in the assignment of the effective user ID attribute, as described in the *exec* family of functions and *setuid*( ).

Note: The *exec* and *setuid*( ) functions are defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.330 Scheduling

The application of a policy to select a runnable process or thread to become a running process or thread, or to alter one or more of the thread lists.

3.331 Scheduling Allocation Domain

The set of processors on which an individual thread can be scheduled at any given time.

3.332 Scheduling Contention Scope

A property of a thread that defines the set of threads against which that thread competes for resources.

For example, in a scheduling decision, threads sharing scheduling contention scope compete for processor resources. In IEEE Std 1003.1-2001, a thread has scheduling contention scope of either PTHREAD_SCOPE_SYSTEM or PTHREAD_SCOPE_PROCESS.

3.333 Scheduling Policy

A set of rules that is used to determine the order of execution of processes or threads to achieve some goal.

Note: Scheduling Policy is defined in detail in Section 4.13 (on page 101).

3.334 Screen

A rectangular region of columns and lines on a terminal display. A screen may be a portion of a physical display device or may occupy the entire physical area of the display device.

3.335 Scroll

To move the representation of data vertically or horizontally relative to the terminal screen. There are two types of scrolling:

1. The cursor moves with the data.
2. The cursor remains stationary while the data moves.

3.336 Semaphore

A minimum synchronization primitive to serve as a basis for more complex synchronization mechanisms to be defined by the application program.

Note: Semaphores are defined in detail in Section 4.15 (on page 102).

3.337 Session

A collection of process groups established for job control purposes. Each process group is a member of a session. A process is considered to be a member of the session of which its process group is a member. A newly created process joins the session of its creator. A process can alter its session membership; see *setsid*( ). There can be multiple process groups in the same session.

Note: The *setsid*( ) function is defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.338 Session Leader

A process that has created a session.

Note: For further information, see the *setsid*( ) function defined in the System Interfaces volume of IEEE Std 1003.1-2001.

3.339 Session Lifetime

The period between when a session is created and the end of the lifetime of all the process groups that remain as members of the session.

3.340 Shared Memory Object

An object that represents memory that can be mapped concurrently into the address space of more than one process.

3.341 Shell

A program that interprets sequences of text input as commands. It may operate on an input stream or it may interactively prompt and read commands from a terminal.

3.342 Shell, the

The Shell Command Language Interpreter; a specific instance of a shell.

Note: For further information, see the *sh* utility defined in the Shell and Utilities volume of IEEE Std 1003.1-2001.

3.343 Shell Script

A file containing shell commands. If the file is made executable, it can be executed by specifying its name as a simple command. Execution of a shell script causes a shell to execute the commands within the script. Alternatively, a shell can be requested to execute the commands in a shell script by specifying the name of the shell script as the operand to the *sh* utility.

Note: Simple Commands are defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.9.1, Simple Commands.

The *sh* utility is defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001.

3.344 Signal

A mechanism by which a process or thread may be notified of, or affected by, an event occurring in the system. Examples of such events include hardware exceptions and specific actions by processes. The term signal is also used to refer to the event itself.

3.345 Signal Stack

Memory established for a thread, in which signal handlers catching signals sent to that thread are executed.

3.346 Single-Quote

The character ''', also known as apostrophe.

3.347 Slash

The character '/', also known as solidus.

3.348 Socket

A file of a particular type that is used as a communications endpoint for process-to-process communication as described in the System Interfaces volume of IEEE Std 1003.1-2001.

3.349 Socket Address

An address associated with a socket or remote endpoint, including an address family identifier and addressing information specific to that address family. The address may include multiple parts, such as a network address associated with a host system and an identifier for a specific endpoint.

3.350 Soft Limit

A resource limitation established for each process that the process may set to any value less than or equal to the hard limit.

3.351 Source Code

When dealing with the Shell Command Language, input to the command language interpreter. The term ''shell script'' is synonymous with this meaning.

When dealing with an ISO/IEC-conforming programming language, source code is input to a compiler conforming to that ISO/IEC standard.

Source code also refers to the input statements prepared for the following standard utilities: *awk*, *bc*, *ed*, *lex*, *localedef*, *make*, *sed*, and *yacc*.

Source code can also refer to a collection of sources meeting any or all of these meanings.

Note: The *awk*, *bc*, *ed*, *lex*, *localedef*, *make*, *sed*, and *yacc* utilities are defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001.

3.352 Space Character (<space>)

The character defined in the portable character set as <space>. The <space> is a member of the **space** character class of the current locale, but represents the single character, and not all of the possible members of the class; see also Section 3.431 (on page 94).

3.353 Spawn

A process creation primitive useful for systems that have difficulty with *fork*( ) and as an efficient replacement for *fork*( )/*exec*.

3.354 Special Built-In

See *Built-In Utility* in Section 3.83 (on page 46).

3.355 Special Parameter

In the shell command language, a parameter named by a single character from the following list:

```
*   @   #   ?   !   –   $   0
```

Note: For further information, see the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.5.2, Special Parameters.

3.356 Spin Lock

A synchronization object used to allow multiple threads to serialize their access to shared data.

3.357 Sporadic Server

A scheduling policy for threads and processes that reserves a certain amount of execution capacity for processing aperiodic events at a given priority level.

3.358 Standard Error

An output stream usually intended to be used for diagnostic messages.

3.359 Standard Input

An input stream usually intended to be used for primary data input.

3.360 Standard Output

An output stream usually intended to be used for primary data output.

3.361 Standard Utilities

The utilities described in the Shell and Utilities volume of IEEE Std 1003.1-2001.

3.362 Stream

Appearing in lowercase, a stream is a file access object that allows access to an ordered sequence of characters, as described by the ISO C standard. Such objects can be created by the *fdopen*( ), *fopen*( ), or *popen*( ) functions, and are associated with a file descriptor. A stream provides the additional services of user-selectable buffering and formatted input and output; see also Section 3.363.

Note: For further information, see the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.5, Standard I/O Streams.

The *fdopen*( ), *fopen*( ), or *popen*( ) functions are defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.363 STREAM

Appearing in uppercase, STREAM refers to a full-duplex connection between a process and an open device or pseudo-device. It optionally includes one or more intermediate processing modules that are interposed between the process end of the STREAM and the device driver (or pseudo-device driver) end of the STREAM; see also Section 3.362.

Note: For further information, see the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.6, STREAMS.

3.364 STREAM End

The STREAM end is the driver end of the STREAM and is also known as the downstream end of the STREAM.

3.365 STREAM Head

The STREAM head is the beginning of the STREAM and is at the boundary between the system and the application process. This is also known as the upstream end of the STREAM.

3.366 STREAMS Multiplexor

A driver with multiple STREAMS connected to it. Multiplexing with STREAMS connected above is referred to as N-to-1, or ‘‘upper multiplexing’’. Multiplexing with STREAMS connected below is referred to as 1-to-N or ‘‘lower multiplexing’’.

3.367 String

A contiguous sequence of bytes terminated by and including the first null byte.

3.368 Subshell

A shell execution environment, distinguished from the main or current shell execution environment.

Note: For further information, see the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.12, Shell Execution Environment.

3.369 Successfully Transferred

For a write operation to a regular file, when the system ensures that all data written is readable on any subsequent open of the file (even one that follows a system or power failure) in the absence of a failure of the physical storage medium.

For a read operation, when an image of the data on the physical storage medium is available to the requesting process.

3.370 Supplementary Group ID

An attribute of a process used in determining file access permissions. A process has up to {NGROUPS_MAX} supplementary group IDs in addition to the effective group ID. The supplementary group IDs of a process are set to the supplementary group IDs of the parent process when the process is created.

3.371 Suspended Job

A job that has received a SIGSTOP, SIGTSTP, SIGTTIN, or SIGTTOU signal that caused the process group to stop. A suspended job is a background job, but a background job is not necessarily a suspended job.

3.372 Symbolic Link

A type of file with the property that when the file is encountered during pathname resolution, a string stored by the file is used to modify the pathname resolution. The stored string has a length of {SYMLINK_MAX} bytes or fewer.

Note: Pathname Resolution is defined in detail in Section 4.11 (on page 100).

3.373 Synchronized Input and Output

A determinism and robustness improvement mechanism to enhance the data input and output mechanisms, so that an application can ensure that the data being manipulated is physically present on secondary mass storage devices.

3.374 Synchronized I/O Completion

The state of an I/O operation that has either been successfully transferred or diagnosed as unsuccessful.

3.375 Synchronized I/O Data Integrity Completion

For read, when the operation has been completed or diagnosed if unsuccessful. The read is complete only when an image of the data has been successfully transferred to the requesting process. If there were any pending write requests affecting the data to be read at the time that the synchronized read operation was requested, these write requests are successfully transferred prior to reading the data.

For write, when the operation has been completed or diagnosed if unsuccessful. The write is complete only when the data specified in the write request is successfully transferred and all file system information required to retrieve the data is successfully transferred.

File attributes that are not necessary for data retrieval (access time, modification time, status change time) need not be successfully transferred prior to returning to the calling process.

3.376 Synchronized I/O File Integrity Completion

Identical to a synchronized I/O data integrity completion with the addition that all file attributes relative to the I/O operation (including access time, modification time, status change time) are successfully transferred prior to returning to the calling process.

3.377 Synchronized I/O Operation

An I/O operation performed on a file that provides the application assurance of the integrity of its data and files.

3.378 Synchronous I/O Operation

An I/O operation that causes the thread requesting the I/O to be blocked from further use of the processor until that I/O operation completes.

Note: A synchronous I/O operation does not imply synchronized I/O data integrity completion or synchronized I/O file integrity completion.

3.379 Synchronously-Generated Signal

A signal that is attributable to a specific thread.

For example, a thread executing an illegal instruction or touching invalid memory causes a synchronously-generated signal. Being synchronous is a property of how the signal was generated and not a property of the signal number.

3.380 System

An implementation of IEEE Std 1003.1-2001.

3.381 System Crash

An interval initiated by an unspecified circumstance that causes all processes (possibly other than special system processes) to be terminated in an undefined manner, after which any changes to the state and contents of files created or written to by an application prior to the interval are undefined, except as required elsewhere in IEEE Std 1003.1-2001.

3.382 System Console

A device that receives messages sent by the *syslog*( ) function, and the *fmtmsg*( ) function when the MM_CONSOLE flag is set.

Note: The *syslog*( ) and *fmtmsg*( ) functions are defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.383 System Databases

An implementation provides two system databases: the ‘‘group database’’ (see also Section 3.187 (on page 61)) and the ‘‘user database’’ (see also Section 3.424 (on page 93)).

3.384 System Documentation

All documentation provided with an implementation except for the conformance document. Electronically distributed documents for an implementation are considered part of the system documentation.

3.385 System Process

An object other than a process executing an application, that is provided by the system and has a process ID.

3.386 System Reboot

An unspecified sequence of events that may result in the loss of transitory data; that is, data that is not saved in permanent storage. For example, message queues, shared memory, semaphores, and processes.

3.387 System Trace Event

A trace event that is generated by the implementation, in response either to a system-initiated action or to an application-requested action, except for a call to *posix_trace_event*( ). When supported by the implementation, a system-initiated action generates a process-independent system trace event and an application-requested action generates a process-dependent system trace event. For a system trace event not defined by IEEE Std 1003.1-2001, the associated trace event type identifier is derived from the implementation-defined name for this trace event, and the associated data is of implementation-defined content and length.

3.388 System-Wide

Pertaining to events occurring in all processes existing in an implementation at a given point in time.

3.389 Tab Character (<tab>)

A character that in the output stream indicates that printing or displaying should start at the next horizontal tabulation position on the current line. It is the character designated by `'\t'` in the C language. If the current position is at or past the last defined horizontal tabulation position, the behavior is unspecified. It is unspecified whether this character is the exact sequence transmitted to an output device by the system to accomplish the tabulation.

3.390 Terminal (or Terminal Device)

A character special file that obeys the specifications of the general terminal interface.

Note: The General Terminal Interface is defined in detail in Chapter 11 (on page 187).

3.391 Text Column

A roughly rectangular block of characters capable of being laid out side-by-side next to other text columns on an output page or terminal screen. The widths of text columns are measured in column positions.

3.392 Text File

A file that contains characters organized into one or more lines. The lines do not contain NUL characters and none can exceed {LINE_MAX} bytes in length, including the <newline>. Although IEEE Std 1003.1-2001 does not distinguish between text files and binary files (see the ISO C standard), many utilities only produce predictable or meaningful output when operating on text files. The standard utilities that have such restrictions always specify ‘‘text files’’ in their STDIN or INPUT FILES sections.

3.393 Thread

A single flow of control within a process. Each thread has its own thread ID, scheduling priority and policy, *errno* value, thread-specific key/value bindings, and the required system resources to support a flow of control. Anything whose address may be determined by a thread, including but not limited to static variables, storage obtained via *malloc*(), directly addressable storage obtained through implementation-defined functions, and automatic variables, are accessible to all threads in the same process.

Note: The *malloc*() function is defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.394 Thread ID

Each thread in a process is uniquely identified during its lifetime by a value of type **pthread_t** called a thread ID.

3.395 Thread List

An ordered set of runnable threads that all have the same ordinal value for their priority.

The ordering of threads on the list is determined by a scheduling policy or policies. The set of thread lists includes all runnable threads in the system.

3.396 Thread-Safe

A function that may be safely invoked concurrently by multiple threads. Each function defined in the System Interfaces volume of IEEE Std 1003.1-2001 is thread-safe unless explicitly stated otherwise. Examples are any ''pure'' function, a function which holds a mutex locked while it is accessing static storage, or objects shared among threads.

3.397 Thread-Specific Data Key

A process global handle of type **pthread_key_t** which is used for naming thread-specific data.

Although the same key value may be used by different threads, the values bound to the key by *pthread_setspecific*( ) and accessed by *pthread_getspecific*( ) are maintained on a per-thread basis and persist for the life of the calling thread.

Note: The *pthread_getspecific*( ) and *pthread_setspecific*( ) functions are defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.398 Tilde

The character '~'.

3.399 Timeouts

A method of limiting the length of time an interface will block; see also Section 3.76 (on page 45).

3.400 Timer

A mechanism that can notify a thread when the time as measured by a particular clock has reached or passed a specified value, or when a specified amount of time has passed.

3.401 Timer Overrun

A condition that occurs each time a timer, for which there is already an expiration signal queued to the process, expires.

3.402 Token

In the shell command language, a sequence of characters that the shell considers as a single unit when reading input. A token is either an operator or a word.

Note: The rules for reading input are defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.3, Token Recognition.

3.403 Trace Analyzer Process

A process that extracts trace events from a trace stream to retrieve information about the behavior of an application.

3.404 Trace Controller Process

A process that creates a trace stream for tracing a process.

3.405 Trace Event

A data object that represents an action executed by the system, and that is recorded in a trace stream.

3.406 Trace Event Type

A data object type that defines a class of trace event.

3.407 Trace Event Type Mapping

A one-to-one mapping between trace event types and trace event names.

3.408 Trace Filter

A filter that allows the trace controller process to specify those trace event types that are to be ignored; that is, not generated.

3.409 Trace Generation Version

A data object that is an implementation-defined character string, generated by the trace system and describing the origin and version of the trace system.

3.410 Trace Log

The flushed image of a trace stream, if the trace stream is created with a trace log.

3.411 Trace Point

An action that may cause a trace event to be generated.

3.412 Trace Stream

An opaque object that contains trace events plus internal data needed to interpret those trace events.

3.413 Trace Stream Identifier

A handle to manage tracing operations in a trace stream.

3.414 Trace System

A system that allows both system and user trace events to be generated into a trace stream. These trace events can be retrieved later.

3.415 Traced Process

A process for which at least one trace stream has been created. A traced process is also called a target process.

3.416 Tracing Status of a Trace Stream

A status that describes the state of an active trace stream. The tracing status of a trace stream can be retrieved from the trace stream attributes. An active trace stream can be in one of two states: running or suspended.

3.417 Typed Memory Name Space

A system-wide name space that contains the names of the typed memory objects present in the system. It is configurable for a given implementation.

3.418 Typed Memory Object

A combination of a typed memory pool and a typed memory port. The entire contents of the pool are accessible from the port. The typed memory object is identified through a name that belongs to the typed memory name space.

3.419 Typed Memory Pool

An extent of memory with the same operational characteristics. Typed memory pools may be contained within each other.

3.420 Typed Memory Port

A hardware access path to one or more typed memory pools.

3.421 Unbind

Remove the association between a network address and an endpoint.

3.422 Unit Data

See *Datagram* in Section 3.123 (on page 52).

3.423 Upshifting

The conversion of a lowercase character that has a single-character uppercase representation into this uppercase representation.

3.424 User Database

A system database that contains at least the following information for each user ID:

- User name
- Numerical user ID
- Initial numerical group ID
- Initial working directory
- Initial user program

The initial numerical group ID is used by the *newgrp* utility. Any other circumstances under which the initial values are operative are implementation-defined.

If the initial user program field is null, an implementation-defined program is used.

If the initial working directory field is null, the interpretation of that field is implementation-defined.

Note: The *newgrp* utility is defined in detail in the Shell and Utilities volume of IEEE Std 1003.1-2001.

3.425 User ID

A non-negative integer that is used to identify a system user. When the identity of a user is associated with a process, a user ID value is referred to as a real user ID, an effective user ID, or a saved set-user-ID.

3.426 User Name

A string that is used to identify a user; see also Section 3.424. To be portable across systems conforming to IEEE Std 1003.1-2001, the value is composed of characters from the portable filename character set. The hyphen should not be used as the first character of a portable user

name.

3.427 User Trace Event

A trace event that is generated explicitly by the application as a result of a call to *posix_trace_event*( ).

3.428 Utility

A program, excluding special built-in utilities provided as part of the Shell Command Language, that can be called by name from a shell to perform a specific task, or related set of tasks.

Note: For further information on special built-in utilities, see the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.14, Special Built-In Utilities.

3.429 Variable

In the shell command language, a named parameter.

Note: For further information, see the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.5, Parameters and Variables.

3.430 Vertical-Tab Character (<vertical-tab>)

A character that in the output stream indicates that printing should start at the next vertical tabulation position. It is the character designated by '\v' in the C language. If the current position is at or past the last defined vertical tabulation position, the behavior is unspecified. It is unspecified whether this character is the exact sequence transmitted to an output device by the system to accomplish the tabulation.

3.431 White Space

A sequence of one or more characters that belong to the **space** character class as defined via the *LC_CTYPE* category in the current locale.

In the POSIX locale, white space consists of one or more <blank>s (<space>s and <tab>s), <newline>s, <carriage-return>s, <form-feed>s, and <vertical-tab>s.

3.432 Wide-Character Code (C Language)

An integer value corresponding to a single graphic symbol or control code.

Note: C Language Wide-Character Codes are defined in detail in Section 6.3 (on page 117).

3.433 Wide-Character Input/Output Functions

The functions that perform wide-oriented input from streams or wide-oriented output to streams: *fgetwc*( ), *fgetws*( ), *fputwc*( ), *fputws*( ), *fwprintf*( ), *fwscanf*( ), *getwc*( ), *getwchar*( ), *putwc*( ),

putwchar( ), *ungetwc*( ), *vfwprintf*( ), *vfwscanf*( ), *vwprintf*( ), *vwscanf*( ), *wprintf*( ), and *wscanf*( ).

Note: These functions are defined in detail in the System Interfaces volume of IEEE Std 1003.1-2001.

3.434 Wide-Character String

A contiguous sequence of wide-character codes terminated by and including the first null wide-character code.

3.435 Word

In the shell command language, a token other than an operator. In some cases a word is also a portion of a word token: in the various forms of parameter expansion, such as ${*name–word*}, and variable assignment, such as *name*=*word*, the word is the portion of the token depicted by *word*. The concept of a word is no longer applicable following word expansions—only fields remain.

Note: For further information, see the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.6.2, Parameter Expansion and the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.6, Word Expansions.

3.436 Working Directory (or Current Working Directory)

A directory, associated with a process, that is used in pathname resolution for pathnames that do not begin with a slash.

3.437 Worldwide Portability Interface

Functions for handling characters in a codeset-independent manner.

3.438 Write

To output characters to a file, such as standard output or standard error. Unless otherwise stated, standard output is the default output destination for all uses of the term ‘‘write’’; see the distinction between display and write in Section 3.132 (on page 53).

3.439 XSI

The X/Open System Interface is the core application programming interface for C and *sh* programming for systems conforming to the Single UNIX Specification. This is a superset of the mandatory requirements for conformance to IEEE Std 1003.1-2001.

3.440 XSI-Conformant

A system which allows an application to be built using a set of services that are consistent across all systems that conform to IEEE Std 1003.1-2001 and that support the XSI extension.

Note: See also Chapter 2 (on page 17).

3.441 Zombie Process

A process that has terminated and that is deleted when its exit status has been reported to another process which is waiting for that process to terminate.

3.442 ±0

The algebraic sign provides additional information about any variable that has the value zero when the representation allows the sign to be determined.

Chapter 4

General Concepts

For the purposes of IEEE Std 1003.1-2001, the general concepts given in Chapter 4 apply.

Note: No shading to denote extensions or options occurs in this chapter. Where the terms and definitions given in this chapter are used elsewhere in text related to extensions and options, they are shaded as appropriate.

4.1 Concurrent Execution

Functions that suspend the execution of the calling thread shall not cause the execution of other threads to be indefinitely suspended.

4.2 Directory Protection

If a directory is writable and the mode bit S_ISVTX is set on the directory, a process may remove or rename files within that directory only if one or more of the following is true:

- The effective user ID of the process is the same as that of the owner ID of the file.
- The effective user ID of the process is the same as that of the owner ID of the directory.
- The process has appropriate privileges.

If the S_ISVTX bit is set on a non-directory file, the behavior is unspecified.

4.3 Extended Security Controls

An implementation may provide implementation-defined extended security controls (see Section 3.159 (on page 57)). These permit an implementation to provide security mechanisms to implement different security policies than those described in IEEE Std 1003.1-2001. These mechanisms shall not alter or override the defined semantics of any of the interfaces in IEEE Std 1003.1-2001.

4.4 File Access Permissions

The standard file access control mechanism uses the file permission bits, as described below.

Implementations may provide *additional* or *alternate* file access control mechanisms, or both. An additional access control mechanism shall only further restrict the access permissions defined by the file permission bits. An alternate file access control mechanism shall:

- Specify file permission bits for the file owner class, file group class, and file other class of that file, corresponding to the access permissions.
- Be enabled only by explicit user action, on a per-file basis by the file owner or a user with the appropriate privilege.
- Be disabled for a file after the file permission bits are changed for that file with *chmod*( ). The disabling of the alternate mechanism need not disable any additional mechanisms supported

by an implementation.

Whenever a process requests file access permission for read, write, or execute/search, if no additional mechanism denies access, access shall be determined as follows:

- If a process has the appropriate privilege:
  - — If read, write, or directory search permission is requested, access shall be granted.
  - — If execute permission is requested, access shall be granted if execute permission is granted to at least one user by the file permission bits or by an alternate access control mechanism; otherwise, access shall be denied.
- Otherwise:
  - — The file permission bits of a file contain read, write, and execute/search permissions for the file owner class, file group class, and file other class.
  - — Access shall be granted if an alternate access control mechanism is not enabled and the requested access permission bit is set for the class (file owner class, file group class, or file other class) to which the process belongs, or if an alternate access control mechanism is enabled and it allows the requested access; otherwise, access shall be denied.

4.5 File Hierarchy

Files in the system are organized in a hierarchical structure in which all of the non-terminal nodes are directories and all of the terminal nodes are any other type of file. Since multiple directory entries may refer to the same file, the hierarchy is properly described as a ‘‘directed graph’’.

4.6 Filenames

For a filename to be portable across implementations conforming to IEEE Std 1003.1-2001, it shall consist only of the portable filename character set as defined in Section 3.276 (on page 73).

The hyphen character shall not be used as the first character of a portable filename. Uppercase and lowercase letters shall retain their unique identities between conforming implementations. In the case of a portable pathname, the slash character may also be used.

4.7 File Times Update

Each file has three distinct associated time values: *st_atime*, *st_mtime*, and *st_ctime*. The *st_atime* field is associated with the times that the file data is accessed; *st_mtime* is associated with the times that the file data is modified; and *st_ctime* is associated with the times that the file status is changed. These values are returned in the file characteristics structure, as described in **<sys/stat.h>**.

Each function or utility in IEEE Std 1003.1-2001 that reads or writes data or changes file status indicates which of the appropriate time-related fields shall be ‘‘marked for update’’. If an implementation of such a function or utility marks for update a time-related field not specified by IEEE Std 1003.1-2001, this shall be documented, except that any changes caused by pathname resolution need not be documented. For the other functions or utilities in IEEE Std 1003.1-2001 (those that are not explicitly required to read or write file data or change file status, but that in some implementations happen to do so), the effect is unspecified.

An implementation may update fields that are marked for update immediately, or it may update such fields periodically. At an update point in time, any marked fields shall be set to the current time and the update marks shall be cleared. All fields that are marked for update shall be updated when the file ceases to be open by any process, or when a *stat*( ), *fstat*( ), or *lstat*( ) is performed on the file. Other times at which updates are done are unspecified. Marks for update, and updates themselves, are not done for files on read-only file systems; see Section 3.304 (on page 77).

4.8 Host and Network Byte Orders

When data is transmitted over the network, it is sent as a sequence of octets (8-bit unsigned values). If an entity (such as an address or a port number) can be larger than 8 bits, it needs to be stored in several octets. The convention is that all such values are stored with 8 bits in each octet, and with the first (lowest-addressed) octet holding the most-significant bits. This is called ''network byte order''.

Network byte order may not be convenient for processing actual values. For this, it is more sensible for values to be stored as ordinary integers. This is known as ''host byte order''. In host byte order:

- The most significant bit might not be stored in the first byte in address order.
- Bits might not be allocated to bytes in any obvious order at all.

8-bit values stored in **uint8_t** objects do not require conversion to or from host byte order, as they have the same representation. 16 and 32-bit values can be converted using the *htonl*( ), *htons*( ), *ntohl*( ), and *ntohs*( ) functions. When reading data that is to be converted to host byte order, it should either be received directly into a **uint16_t** or **uint32_t** object or should be copied from an array of bytes using *memcpy*( ) or similar. Passing the data through other types could cause the byte order to be changed. Similar considerations apply when sending data.

4.9 Measurement of Execution Time

The mechanism used to measure execution time shall be implementation-defined. The implementation shall also define to whom the CPU time that is consumed by interrupt handlers and system services on behalf of the operating system will be charged. See Section 3.117 (on page 51).

4.10 Memory Synchronization

Applications shall ensure that access to any memory location by more than one thread of control (threads or processes) is restricted such that no thread of control can read or modify a memory location while another thread of control may be modifying it. Such access is restricted using functions that synchronize thread execution and also synchronize memory with respect to other threads. The following functions synchronize memory with respect to other threads:

fork( )	*pthread_mutex_timedlock*( )	*pthread_rwlock_tryrdlock*( )
pthread_barrier_wait( )	*pthread_mutex_trylock*( )	*pthread_rwlock_trywrlock*( )
pthread_cond_broadcast( )	*pthread_mutex_unlock*( )	*pthread_rwlock_unlock*( )
pthread_cond_signal( )	*pthread_spin_lock*( )	*pthread_rwlock_wrlock*( )
pthread_cond_timedwait( )	*pthread_spin_trylock*( )	*sem_post*( )
pthread_cond_wait( )	*pthread_spin_unlock*( )	*sem_trywait*( )
pthread_create( )	*pthread_rwlock_rdlock*( )	*sem_wait*( )
pthread_join( )	*pthread_rwlock_timedrdlock*( )	*wait*( )
pthread_mutex_lock( )	*pthread_rwlock_timedwrlock*( )	*waitpid*( )

The *pthread_once*( ) function shall synchronize memory for the first call in each thread for a given **pthread_once_t** object.

Unless explicitly stated otherwise, if one of the above functions returns an error, it is unspecified whether the invocation causes memory to be synchronized.

Applications may allow more than one thread of control to read a memory location simultaneously.

4.11 Pathname Resolution

Pathname resolution is performed for a process to resolve a pathname to a particular file in a file hierarchy. There may be multiple pathnames that resolve to the same file.

Each filename in the pathname is located in the directory specified by its predecessor (for example, in the pathname fragment **a/b**, file **b** is located in directory **a**). Pathname resolution shall fail if this cannot be accomplished. If the pathname begins with a slash, the predecessor of the first filename in the pathname shall be taken to be the root directory of the process (such pathnames are referred to as ‘‘absolute pathnames’’). If the pathname does not begin with a slash, the predecessor of the first filename of the pathname shall be taken to be the current working directory of the process (such pathnames are referred to as ‘‘relative pathnames’’).

The interpretation of a pathname component is dependent on the value of {NAME_MAX} and _POSIX_NO_TRUNC associated with the path prefix of that component. If any pathname component is longer than {NAME_MAX}, the implementation shall consider this an error.

A pathname that contains at least one non-slash character and that ends with one or more trailing slashes shall be resolved as if a single dot character (’.’) were appended to the pathname.

If a symbolic link is encountered during pathname resolution, the behavior shall depend on whether the pathname component is at the end of the pathname and on the function being performed. If all of the following are true, then pathname resolution is complete:

1. This is the last pathname component of the pathname.
2. The pathname has no trailing slash.

3. The function is required to act on the symbolic link itself, or certain arguments direct that the function act on the symbolic link itself.

In all other cases, the system shall prefix the remaining pathname, if any, with the contents of the symbolic link. If the combined length exceeds {PATH_MAX}, and the implementation considers this to be an error, *errno* shall be set to [ENAMETOOLONG] and an error indication shall be returned. Otherwise, the resolved pathname shall be the resolution of the pathname just created. If the resulting pathname does not begin with a slash, the predecessor of the first filename of the pathname is taken to be the directory containing the symbolic link.

If the system detects a loop in the pathname resolution process, it shall set *errno* to [ELOOP] and return an error indication. The same may happen if during the resolution process more symbolic links were followed than the implementation allows. This implementation-defined limit shall not be smaller than {SYMLOOP_MAX}.

The special filename dot shall refer to the directory specified by its predecessor. The special filename dot-dot shall refer to the parent directory of its predecessor directory. As a special case, in the root directory, dot-dot may refer to the root directory itself.

A pathname consisting of a single slash shall resolve to the root directory of the process. A null pathname shall not be successfully resolved. A pathname that begins with two successive slashes may be interpreted in an implementation-defined manner, although more than two leading slashes shall be treated as a single slash.

4.12 Process ID Reuse

A process group ID shall not be reused by the system until the process group lifetime ends.

A process ID shall not be reused by the system until the process lifetime ends. In addition, if there exists a process group whose process group ID is equal to that process ID, the process ID shall not be reused by the system until the process group lifetime ends. A process that is not a system process shall not have a process ID of 1.

4.13 Scheduling Policy

A scheduling policy affects process or thread ordering:

- When a process or thread is a running thread and it becomes a blocked thread
- When a process or thread is a running thread and it becomes a preempted thread
- When a process or thread is a blocked thread and it becomes a runnable thread
- When a running thread calls a function that can change the priority or scheduling policy of a process or thread
- In other scheduling policy-defined circumstances

Conforming implementations shall define the manner in which each of the scheduling policies may modify the priorities or otherwise affect the ordering of processes or threads at each of the occurrences listed above. Additionally, conforming implementations shall define in what other circumstances and in what manner each scheduling policy may modify the priorities or affect the ordering of processes or threads.

4.14 Seconds Since the Epoch

A value that approximates the number of seconds that have elapsed since the Epoch. A Coordinated Universal Time name (specified in terms of seconds (*tm_sec*), minutes (*tm_min*), hours (*tm_hour*), days since January 1 of the year (*tm_yday*), and calendar year minus 1900 (*tm_year*)) is related to a time represented as seconds since the Epoch, according to the expression below.

If the year is <1970 or the value is negative, the relationship is undefined. If the year is ≥1970 and the value is non-negative, the value is related to a Coordinated Universal Time name according to the C-language expression, where *tm_sec*, *tm_min*, *tm_hour*, *tm_yday*, and *tm_year* are all integer types:

```
tm_sec + tm_min*60 + tm_hour*3600 + tm_yday*86400 +
    (tm_year–70)*31536000 + ((tm_year–69)/4)*86400 –
    ((tm_year–1)/100)*86400 + ((tm_year+299)/400)*86400
```

The relationship between the actual time of day and the current value for seconds since the Epoch is unspecified.

How any changes to the value of seconds since the Epoch are made to align to a desired relationship with the current actual time is implementation-defined. As represented in seconds since the Epoch, each and every day shall be accounted for by exactly 86 400 seconds.

Note: The last three terms of the expression add in a day for each year that follows a leap year starting with the first leap year since the Epoch. The first term adds a day every 4 years starting in 1973, the second subtracts a day back out every 100 years starting in 2001, and the third adds a day back in every 400 years starting in 2001. The divisions in the formula are integer divisions; that is, the remainder is discarded leaving only the integer quotient.

4.15 Semaphore

A minimum synchronization primitive to serve as a basis for more complex synchronization mechanisms to be defined by the application program.

For the semaphores associated with the Semaphores option, a semaphore is represented as a shareable resource that has a non-negative integer value. When the value is zero, there is a (possibly empty) set of threads awaiting the availability of the semaphore.

For the semaphores associated with the X/Open System Interface Extension (XSI), a semaphore is a positive integer (0 through 32767). The *semget*( ) function can be called to create a set or array of semaphores. A semaphore set can contain one or more semaphores up to an implementation-defined value.

Semaphore Lock Operation

An operation that is applied to a semaphore. If, prior to the operation, the value of the semaphore is zero, the semaphore lock operation shall cause the calling thread to be blocked and added to the set of threads awaiting the semaphore; otherwise, the value shall be decremented.

Semaphore Unlock Operation

An operation that is applied to a semaphore. If, prior to the operation, there are any threads in the set of threads awaiting the semaphore, then some thread from that set shall be removed from the set and becomes unblocked; otherwise, the semaphore value shall be incremented.

4.16 Thread-Safety

Refer to the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.9, Threads.

4.17 Tracing

The trace system allows a traced process to have a selection of events created for it. Traces consist of streams of trace event types.

A trace event type is identified on the one hand by a trace event type name, also referenced as a trace event name, and on the other hand by a trace event type identifier. A trace event name is a human-readable string. A trace event type identifier is an opaque identifier used by the trace system. There shall be a one-to-one relationship between trace event type identifiers and trace event names for a given trace stream and also for a given traced process. The trace event type identifier shall be generated automatically from a trace event name by the trace system either when a trace controller process invokes *posix_trace_trid_eventid_open*( ) or when an instrumented application process invokes *posix_trace_eventid_open*( ). Trace event type identifiers are used to filter trace event types, to allow interpretation of user data, and to identify the kind of trace point that generated a trace event.

Each trace event shall be of a particular trace event type, and associated with a trace event type identifier. The execution of a trace point shall generate a trace event if a trace stream has been created and started for the process that executed the trace point and if the corresponding trace event type identifier is not ignored by filtering.

A generated trace event shall be recorded in a trace stream, and optionally also in a trace log if a trace log is associated with the trace stream, except that:

- For a trace stream, if no resources are available for the event, the event is lost.
- For a trace log, if no resources are available for the event, or a flush operation does not succeed, the event is lost.

A trace event recorded in an active trace stream may be retrieved by an application having the appropriate privileges.

A trace event recorded in a trace log may be retrieved by an application having the appropriate privileges after opening the trace log as a pre-recorded trace stream, with the function *posix_trace_open*( ).

When a trace event is reported it is possible to retrieve the following:

- A trace event type identifier
- A timestamp
- The process ID of the traced process, if the trace event is process-dependent
- Any optional trace event data including its length

- If the Threads option is supported, the thread ID, if the trace event is process-dependent
- The program address at which the trace point was invoked

Trace events may be mapped from trace event types to trace event names. One such mapping shall be associated with each trace stream. An active trace stream is associated with a traced process, and also with its children if the Trace Inherit option is supported and also the inheritance policy is set to _POSIX_TRACE_INHERIT. Therefore each traced process has a mapping of the trace event names to trace event type identifiers that have been defined for that process.

Traces can be recorded into either trace streams or trace logs.

The implementation and format of a trace stream are unspecified. A trace stream need not be and generally is not persistent. A trace stream may be either active or pre-recorded:

- An active trace stream is a trace stream that has been created and has not yet been shut down. It can be of one of the two following classes:
  1. An active trace stream without a trace log that was created with the *posix_trace_create*( ) function
  2. If the Trace Log option is supported, an active trace stream with a trace log that was created with the *posix_trace_create_withlog*( ) function
- A pre-recorded trace stream is a trace stream that was opened from a trace log object using the *posix_trace_open*( ) function.

An active trace stream can loop. This behavior means that when the resources allocated by the trace system for the trace stream are exhausted, the trace system reuses the resources associated with the oldest recorded trace events to record new trace events.

If the Trace Log option is supported, an active trace stream with a trace log can be flushed. This operation causes the trace system to write trace events from the trace stream to the associated trace log, following the defined policies or using an explicit function call. After this operation, the trace system may reuse the resources associated with the flushed trace events.

An active trace stream with or without a trace log can be cleared. This operation shall cause all the resources associated with this trace stream to be reinitialized. The trace stream shall behave as if it was returning from its creation, except that the mapping of trace event type identifiers to trace event names shall not be cleared. If a trace log was associated with this trace stream, the trace log shall also be reinitialized.

A trace log shall be recorded when the *posix_trace_shutdown*( ) operation is invoked or during tracing, depending on the tracing strategy which is defined by a log policy. After the trace stream has been shut down, the trace information can be retrieved from the associated trace log using the same interface used to retrieve information from an active trace stream.

For a traced process, if the Trace Inherit option is supported and the trace stream's inheritance attribute is _POSIX_TRACE_INHERIT, the initial targeted traced process shall be traced together with all of its future children. The *posix_pid* member of each trace event in a trace stream shall be the process ID of the traced process.

Each trace point may be an implementation-defined action such as a context switch, or an application-programmed action such as a call to a specific operating system service (for example, *fork*( )) or a call to *posix_trace_event*( ).

Trace points may be filtered. The operation of the filter is to filter out (ignore) selected trace events. By default, no trace events are filtered.

The results of the tracing operations can be analyzed and monitored by a trace controller process or a trace analyzer process.

Only the trace controller process has control of the trace stream it has created. The control of the operation of a trace stream is done using its corresponding trace stream identifier. The trace controller process is able to:

- Initialize the attributes of a trace stream
- Create the trace stream
- Start and stop tracing
- Know the mapping of the traced process
- If the Trace Event Filter option is supported, filter the type of trace events to be recorded
- Shut the trace stream down

A traced process may also be a trace controller process. Only the trace controller process can control its trace stream(s). A trace stream created by a trace controller process shall be shut down if its controller process terminates or executes another file.

A trace controller process may also be a trace analyzer process. Trace analysis can be done concurrently with the traced process or can be done off-line, in the same or in a different platform.

4.18 Treatment of Error Conditions for Mathematical Functions

For all the functions in the **<math.h>** header, an application wishing to check for error situations should set *errno* to 0 and call *feclearexcept*(FE_ALL_EXCEPT) before calling the function. On return, if *errno* is non-zero or *fetestexcept*(FE_INVALID | FE_DIVBYZERO | FE_OVERFLOW | FE_UNDERFLOW) is non-zero, an error has occurred.

The following error conditions are defined for all functions in the **<math.h>** header.

4.18.1 Domain Error

A ''domain error'' shall occur if an input argument is outside the domain over which the mathematical function is defined. The description of each function lists any required domain errors; an implementation may define additional domain errors, provided that such errors are consistent with the mathematical definition of the function.

On a domain error, the function shall return an implementation-defined value; if the integer expression (math_errhandling & MATH_ERRNO) is non-zero, *errno* shall be set to [EDOM]; if the integer expression (math_errhandling & MATH_ERREXCEPT) is non-zero, the ''invalid'' floating-point exception shall be raised.

4.18.2 Pole Error

A ‘‘pole error’’ occurs if the mathematical result of the function is an exact infinity (for example, log(0.0)).

On a pole error, the function shall return the value of the macro HUGE_VAL, HUGE_VALF, or HUGE_VALL according to the return type, with the same sign as the correct value of the function; if the integer expression (math_errhandling & MATH_ERRNO) is non-zero, *errno* shall be set to [ERANGE]; if the integer expression (math_errhandling & MATH_ERREXCEPT) is non-zero, the ‘‘divide-by-zero’’ floating-point exception shall be raised.

4.18.3 Range Error

A ‘‘range error’’ shall occur if the finite mathematical result of the function cannot be represented in an object of the specified type, due to extreme magnitude.

4.18.3.1 Result Overflows

A floating result overflows if the magnitude of the mathematical result is finite but so large that the mathematical result cannot be represented without extraordinary roundoff error in an object of the specified type. If a floating result overflows and default rounding is in effect, then the function shall return the value of the macro HUGE_VAL, HUGE_VALF, or HUGE_VALL according to the return type, with the same sign as the correct value of the function; if the integer expression (math_errhandling & MATH_ERRNO) is non-zero, *errno* shall be set to [ERANGE]; if the integer expression (math_errhandling & MATH_ERREXCEPT) is non-zero, the ‘‘overflow’’ floating-point exception shall be raised.

4.18.3.2 Result Underflows

The result underflows if the magnitude of the mathematical result is so small that the mathematical result cannot be represented, without extraordinary roundoff error, in an object of the specified type. If the result underflows, the function shall return an implementation-defined value whose magnitude is no greater than the smallest normalized positive number in the specified type; if the integer expression (math_errhandling & MATH_ERRNO) is non-zero, whether *errno* is set to [ERANGE] is implementation-defined; if the integer expression (math_errhandling & MATH_ERREXCEPT) is non-zero, whether the ‘‘underflow’’ floating-point exception is raised is implementation-defined.

4.19 Treatment of NaN Arguments for the Mathematical Functions

For functions called with a NaN argument, no errors shall occur and a NaN shall be returned, except where stated otherwise.

If a function with one or more NaN arguments returns a NaN result, the result should be the same as one of the NaN arguments (after possible type conversion), except perhaps for the sign.

On implementations that support the IEC 60559:1989 standard floating point, functions with signaling NaN argument(s) shall be treated as if the function were called with an argument that is a required domain error and shall return a quiet NaN result, except where stated otherwise.

Note: The function might never see the signaling NaN, since it might trigger when the arguments are evaluated during the function call.

On implementations that support the IEC 60559:1989 standard floating point, for those functions that do not have a documented domain error, the following shall apply:

These functions shall fail if:

Domain Error Any argument is a signaling NaN.

Either, the integer expression (math_errhandling & MATH_ERRNO) is non-zero and *errno* shall be set to [EDOM], or the integer expression (math_errhandling & MATH_ERREXCEPT) is non-zero and the invalid floating-point exception shall be raised.

4.20 Utility

A utility program shall be either an executable file, such as might be produced by a compiler or linker system from computer source code, or a file of shell source code, directly interpreted by the shell. The program may have been produced by the user, provided by the system implementor, or acquired from an independent distributor.

The system may implement certain utilities as shell functions (see the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.9.5, Function Definition Command) or built-in utilities, but only an application that is aware of the command search order described in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.9.1.1, Command Search and Execution or of performance characteristics can discern differences between the behavior of such a function or built-in utility and that of an executable file.

4.21 Variable Assignment

In the shell command language, a word consisting of the following parts:

varname=*value*

When used in a context where assignment is defined to occur and at no other time, the *value* (representing a word or field) shall be assigned as the value of the variable denoted by *varname*.

Note: For further information, see the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.9.1, Simple Commands.

The *varname* and *value* parts shall meet the requirements for a name and a word, respectively, except that they are delimited by the embedded unquoted equals-sign, in addition to other delimiters.

Note: Additional delimiters are described in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.3, Token Recognition.

When a variable assignment is done, the variable shall be created if it did not already exist. If *value* is not specified, the variable shall be given a null value.

Note: An alternative form of variable assignment:

symbol=*value*

(where *symbol* is a valid word delimited by an equals-sign, but not a valid name) produces unspecified results. The form *symbol*=*value* is used by the KornShell *name*[*expression*]=*value* syntax.

3423

Chapter 5

File Format Notation

The STDIN, STDOUT, STDERR, INPUT FILES, and OUTPUT FILES sections of the utility descriptions use a syntax to describe the data organization within the files, when that organization is not otherwise obvious. The syntax is similar to that used by the System Interfaces volume of IEEE Std 1003.1-2001 *printf*( ) function, as described in this chapter. When used in STDIN or INPUT FILES sections of the utility descriptions, this syntax describes the format that could have been used to write the text to be read, not a format that could be used by the System Interfaces volume of IEEE Std 1003.1-2001 *scanf*( ) function to read the input file.

The description of an individual record is as follows:

"*<format>*", **[***<arg1>*, *<arg2>*,..., *<argn>***]**

The *format* is a character string that contains three types of objects defined below:

1. *Characters* that are not ‘‘escape sequences’’ or ‘‘conversion specifications’’, as described below, shall be copied to the output.
2. *Escape Sequences* represent non-graphic characters.
3. *Conversion Specifications* specify the output format of each argument; see below.

The following characters have the following special meaning in the format string:

’’ (An empty character position.) Represents one or more <blank>s.

Δ Represents exactly one <space>.

Table 5-1 lists escape sequences and associated actions on display devices capable of the action.

Table 5-1 Escape Sequences and Associated Actions

Escape Sequence	Represents Character	Terminal Action
'\\'	backslash	Print the character '\'.
'\a'	alert	Attempt to alert the user through audible or visible notification.
'\b'	backspace	Move the printing position to one column before the current position, unless the current position is the start of a line.
'\f'	form-feed	Move the printing position to the initial printing position of the next logical page.
'\n'	newline	Move the printing position to the start of the next line.
'\r'	carriage-return	Move the printing position to the start of the current line.
'\t'	tab	Move the printing position to the next tab position on the current line. If there are no more tab positions remaining on the line, the behavior is undefined.
'\v'	vertical-tab	Move the printing position to the start of the next vertical tab position. If there are no more vertical tab positions left on the page, the behavior is undefined.

Each conversion specification is introduced by the percent-sign character ('%'). After the character '%', the following shall appear in sequence:

flags Zero or more *flags*, in any order, that modify the meaning of the conversion specification.

field width An optional string of decimal digits to specify a minimum field width. For an output field, if the converted value has fewer bytes than the field width, it shall be padded on the left (or right, if the left-adjustment flag ('–'), described below, has been given) to the field width.

precision Gives the minimum number of digits to appear for the d, o, i, u, x, or X conversion specifiers (the field is padded with leading zeros), the number of digits to appear after the radix character for the e and f conversion specifiers, the maximum number of significant digits for the g conversion specifier; or the maximum number of bytes to be written from a string in the s conversion specifier. The precision shall take the form of a period ('.') followed by a decimal digit string; a null digit string is treated as zero.

conversion specifier characters
A conversion specifier character (see below) that indicates the type of conversion to be applied.

The *flag* characters and their meanings are:

– The result of the conversion shall be left-justified within the field.

+ The result of a signed conversion shall always begin with a sign ('+' or '–').

<space> If the first character of a signed conversion is not a sign, a <space> shall be prefixed to the result. This means that if the <space> and '+' flags both appear, the <space> flag shall be ignored.

The value shall be converted to an alternative form. For c, d, i, u, and s conversion specifiers, the behavior is undefined. For the o conversion specifier, it shall increase the precision to force the first digit of the result to be a zero. For x or X conversion specifiers, a non-zero result has 0x or 0X prefixed to it, respectively. For

3488 3489 3490 `e`, `E`, `f`, `g`, and `G` conversion specifiers, the result shall always contain a radix character, even if no digits follow the radix character. For `g` and `G` conversion specifiers, trailing zeros shall not be removed from the result as they usually are.

3491 3492 3493 3494 3495 3496 `0` For `d`, `i`, `o`, `u`, `x`, `X`, `e`, `E`, `f`, `g`, and `G` conversion specifiers, leading zeros (following any indication of sign or base) shall be used to pad to the field width; no space padding is performed. If the `'0'` and `'−'` flags both appear, the `'0'` flag shall be ignored. For `d`, `i`, `o`, `u`, `x`, and `X` conversion specifiers, if a precision is specified, the `'0'` flag shall be ignored. For other conversion specifiers, the behavior is undefined.

3497 3498 3499 Each conversion specifier character shall result in fetching zero or more arguments. The results are undefined if there are insufficient arguments for the format. If the format is exhausted while arguments remain, the excess arguments shall be ignored.

3500 The conversion specifiers and their meanings are:

3501 3502 3503 3504 3505 3506 3507 3508 3509 3510 3511 3512 3513 `d,i,o,u,x,X` The integer argument shall be written as signed decimal (`d` or `i`), unsigned octal (`o`), unsigned decimal (`u`), or unsigned hexadecimal notation (`x` and `X`). The `d` and `i` specifiers shall convert to signed decimal in the style "[−]*dddd*". The `x` conversion specifier shall use the numbers and letters "0123456789abcdef" and the `X` conversion specifier shall use the numbers and letters "0123456789ABCDEF". The *precision* component of the argument shall specify the minimum number of digits to appear. If the value being converted can be represented in fewer digits than the specified minimum, it shall be expanded with leading zeros. The default precision shall be 1. The result of converting a zero value with a precision of 0 shall be no characters. If both the field width and precision are omitted, the implementation may precede, follow, or precede and follow numeric arguments of types `d`, `i`, and `u` with <blank>s; arguments of type `o` (octal) may be preceded with leading zeros.

3514 3515 3516 3517 3518 3519 `f` The floating-point number argument shall be written in decimal notation in the style **[**−**]***ddd.ddd*, where the number of digits after the radix character (shown here as a decimal point) shall be equal to the *precision* specification. The *LC_NUMERIC* locale category shall determine the radix character to use in this format. If the *precision* is omitted from the argument, six digits shall be written after the radix character; if the *precision* is explicitly 0, no radix character shall appear.

3520 3521 3522 3523 3524 3525 3526 3527 3528 3529 `e,E` The floating-point number argument shall be written in the style **[**−**]***d.ddd*e±*dd* (the symbol `'±'` indicates either a plus or minus sign), where there is one digit before the radix character (shown here as a decimal point) and the number of digits after it is equal to the precision. The *LC_NUMERIC* locale category shall determine the radix character to use in this format. When the precision is missing, six digits shall be written after the radix character; if the precision is 0, no radix character shall appear. The `E` conversion specifier shall produce a number with `E` instead of `e` introducing the exponent. The exponent shall always contain at least two digits. However, if the value to be written requires an exponent greater than two digits, additional exponent digits shall be written as necessary.

3530 3531 3532 3533 3534 3535 `g,G` The floating-point number argument shall be written in style `f` or `e` (or in style `F` or `E` in the case of a `G` conversion specifier), with the precision specifying the number of significant digits. The style used depends on the value converted: style `e` (or `E`) shall be used only if the exponent resulting from the conversion is less than −4 or greater than or equal to the precision. Trailing zeros are removed from the result. A radix character shall appear only if it is followed by a digit.

3536 c The integer argument shall be converted to an **unsigned char** and the resulting
3537 byte shall be written.

3538 s The argument shall be taken to be a string and bytes from the string shall be
3539 written until the end of the string or the number of bytes indicated by the *precision*
3540 specification of the argument is reached. If the precision is omitted from the
3541 argument, it shall be taken to be infinite, so all bytes up to the end of the string
3542 shall be written.

3543 % Write a '%' character; no argument is converted.

3544 In no case does a nonexistent or insufficient field width cause truncation of a field; if the result of
3545 a conversion is wider than the field width, the field is simply expanded to contain the conversion
3546 result. The term ‘‘field width’’ should not be confused with the term ‘‘precision’’ used in the
3547 description of %s.

3548 **Examples**

3549 To represent the output of a program that prints a date and time in the form Sunday, July 3,
3550 10:02, where *weekday* and *month* are strings:

3551 `"%s,Δ%sΔ%d,Δ%d:%.2d\n" <weekday>, <month>, <day>, <hour>, <min>`

3552 To show 'π' written to 5 decimal places:

3553 `"piΔ=Δ%.5f\n",<value of π>`

3554 To show an input file format consisting of five colon-separated fields:

3555 `"%s:%s:%s:%s:%s\n", <arg1>, <arg2>, <arg3>, <arg4>, <arg5>`

Chapter 6

Character Set

6.1 Portable Character Set

Conforming implementations shall support one or more coded character sets. Each supported locale shall include the *portable character set*, which is the set of symbolic names for characters in Table 6-1. This is used to describe characters within the text of IEEE Std 1003.1-2001. The first eight entries in Table 6-1 are defined in the ISO/IEC 6429:1992 standard and the rest of the characters are defined in the ISO/IEC 10646-1:2000 standard.

Table 6-1 Portable Character Set

Symbolic Name	Glyph	UCS	Description
<NUL>		<U0000>	NULL (NUL)
<alert>		<U0007>	BELL (BEL)
<backspace>		<U0008>	BACKSPACE (BS)
<tab>		<U0009>	CHARACTER TABULATION (HT)
<carriage-return>		<U000D>	CARRIAGE RETURN (CR)
<newline>		<U000A>	LINE FEED (LF)
<vertical-tab>		<U000B>	LINE TABULATION (VT)
<form-feed>		<U000C>	FORM FEED (FF)
<space>		<U0020>	SPACE
<exclamation-mark>	!	<U0021>	EXCLAMATION MARK
<quotation-mark>	"	<U0022>	QUOTATION MARK
<number-sign>	#	<U0023>	NUMBER SIGN
<dollar-sign>	$	<U0024>	DOLLAR SIGN
<percent-sign>	%	<U0025>	PERCENT SIGN
<ampersand>	&	<U0026>	AMPERSAND
<apostrophe>	'	<U0027>	APOSTROPHE
<left-parenthesis>	(	<U0028>	LEFT PARENTHESIS
<right-parenthesis>	)	<U0029>	RIGHT PARENTHESIS
<asterisk>	*	<U002A>	ASTERISK
<plus-sign>	+	<U002B>	PLUS SIGN
<comma>	,	<U002C>	COMMA
<hyphen-minus>	–	<U002D>	HYPHEN-MINUS
<hyphen>	-	<U002D>	HYPHEN-MINUS
<full-stop>	.	<U002E>	FULL STOP
<period>	.	<U002E>	FULL STOP
<slash>	/	<U002F>	SOLIDUS
<solidus>	/	<U002F>	SOLIDUS
<zero>	0	<U0030>	DIGIT ZERO
<one>	1	<U0031>	DIGIT ONE
<two>	2	<U0032>	DIGIT TWO
<three>	3	<U0033>	DIGIT THREE

Symbolic Name	Glyph	UCS	Description
<four>	4	<U0034>	DIGIT FOUR
<five>	5	<U0035>	DIGIT FIVE
<six>	6	<U0036>	DIGIT SIX
<seven>	7	<U0037>	DIGIT SEVEN
<eight>	8	<U0038>	DIGIT EIGHT
<nine>	9	<U0039>	DIGIT NINE
<colon>	:	<U003A>	COLON
<semicolon>	;	<U003B>	SEMICOLON
<less-than-sign>	<	<U003C>	LESS-THAN SIGN
<equals-sign>	=	<U003D>	EQUALS SIGN
<greater-than-sign>	>	<U003E>	GREATER-THAN SIGN
<question-mark>	?	<U003F>	QUESTION MARK
<commercial-at>	@	<U0040>	COMMERCIAL AT
<A>	A	<U0041>	LATIN CAPITAL LETTER A
<B>	B	<U0042>	LATIN CAPITAL LETTER B
<C>	C	<U0043>	LATIN CAPITAL LETTER C
<D>	D	<U0044>	LATIN CAPITAL LETTER D
<E>	E	<U0045>	LATIN CAPITAL LETTER E
<F>	F	<U0046>	LATIN CAPITAL LETTER F
<G>	G	<U0047>	LATIN CAPITAL LETTER G
<H>	H	<U0048>	LATIN CAPITAL LETTER H
<I>	I	<U0049>	LATIN CAPITAL LETTER I
<J>	J	<U004A>	LATIN CAPITAL LETTER J
<K>	K	<U004B>	LATIN CAPITAL LETTER K
<L>	L	<U004C>	LATIN CAPITAL LETTER L
<M>	M	<U004D>	LATIN CAPITAL LETTER M
<N>	N	<U004E>	LATIN CAPITAL LETTER N
<O>	O	<U004F>	LATIN CAPITAL LETTER O
<P>	P	<U0050>	LATIN CAPITAL LETTER P
<Q>	Q	<U0051>	LATIN CAPITAL LETTER Q
<R>	R	<U0052>	LATIN CAPITAL LETTER R
<S>	S	<U0053>	LATIN CAPITAL LETTER S
<T>	T	<U0054>	LATIN CAPITAL LETTER T
<U>	U	<U0055>	LATIN CAPITAL LETTER U
<V>	V	<U0056>	LATIN CAPITAL LETTER V
<W>	W	<U0057>	LATIN CAPITAL LETTER W
<X>	X	<U0058>	LATIN CAPITAL LETTER X
<Y>	Y	<U0059>	LATIN CAPITAL LETTER Y
<Z>	Z	<U005A>	LATIN CAPITAL LETTER Z
<left-square-bracket>	[	<U005B>	LEFT SQUARE BRACKET
<backslash>	\	<U005C>	REVERSE SOLIDUS
<reverse-solidus>	\	<U005C>	REVERSE SOLIDUS
<right-square-bracket>	]	<U005D>	RIGHT SQUARE BRACKET
<circumflex-accent>	^	<U005E>	CIRCUMFLEX ACCENT
<circumflex>	^	<U005E>	CIRCUMFLEX ACCENT
<low-line>	_	<U005F>	LOW LINE
<underscore>	_	<U005F>	LOW LINE

Symbolic Name	Glyph	UCS	Description
<grave-accent>	‘	<U0060>	GRAVE ACCENT
<a>	a	<U0061>	LATIN SMALL LETTER A
<b>	b	<U0062>	LATIN SMALL LETTER B
<c>	c	<U0063>	LATIN SMALL LETTER C
<d>	d	<U0064>	LATIN SMALL LETTER D
<e>	e	<U0065>	LATIN SMALL LETTER E
<f>	f	<U0066>	LATIN SMALL LETTER F
<g>	g	<U0067>	LATIN SMALL LETTER G
<h>	h	<U0068>	LATIN SMALL LETTER H
<i>	i	<U0069>	LATIN SMALL LETTER I
<j>	j	<U006A>	LATIN SMALL LETTER J
<k>	k	<U006B>	LATIN SMALL LETTER K
<l>	l	<U006C>	LATIN SMALL LETTER L
<m>	m	<U006D>	LATIN SMALL LETTER M
<n>	n	<U006E>	LATIN SMALL LETTER N
<o>	o	<U006F>	LATIN SMALL LETTER O
<p>	p	<U0070>	LATIN SMALL LETTER P
<q>	q	<U0071>	LATIN SMALL LETTER Q
<r>	r	<U0072>	LATIN SMALL LETTER R
<s>	s	<U0073>	LATIN SMALL LETTER S
<t>	t	<U0074>	LATIN SMALL LETTER T
<u>	u	<U0075>	LATIN SMALL LETTER U
<v>	v	<U0076>	LATIN SMALL LETTER V
<w>	w	<U0077>	LATIN SMALL LETTER W
<x>	x	<U0078>	LATIN SMALL LETTER X
<y>	y	<U0079>	LATIN SMALL LETTER Y
<z>	z	<U007A>	LATIN SMALL LETTER Z
<left-brace>	{	<U007B>	LEFT CURLY BRACKET
<left-curly-bracket>	{	<U007B>	LEFT CURLY BRACKET
<vertical-line>	|	<U007C>	VERTICAL LINE
<right-brace>	}	<U007D>	RIGHT CURLY BRACKET
<right-curly-bracket>	}	<U007D>	RIGHT CURLY BRACKET
<tilde>	~	<U007E>	TILDE

IEEE Std 1003.1-2001 uses character names other than the above, but only in an informative way; for example, in examples to illustrate the use of characters beyond the portable character set with the facilities of IEEE Std 1003.1-2001.

Table 6-1 (on page 113) defines the characters in the portable character set and the corresponding symbolic character names used to identify each character in a character set description file. The table contains more than one symbolic character name for characters whose traditional name differs from the chosen name. Characters defined in Table 6-2 (on page 118) may also be used in character set description files.

IEEE Std 1003.1-2001 places only the following requirements on the encoded values of the characters in the portable character set:

- If the encoded values associated with each member of the portable character set are not invariant across all locales supported by the implementation, if an application accesses any pair of locales where the character encodings differ, or accesses data from an application running in a locale which has different encodings from the application’s current locale, the results are unspecified.

- The encoded values associated with the digits 0 to 9 shall be such that the value of each character after 0 shall be one greater than the value of the previous character.
- A null character, NUL, which has all bits set to zero, shall be in the set of characters.
- The encoded values associated with the members of the portable character set are each represented in a single byte. Moreover, if the value is stored in an object of C-language type **char**, it is guaranteed to be positive (except the NUL, which is always zero).

Conforming implementations shall support certain character and character set attributes, as defined in Section 7.2 (on page 124).

6.2 Character Encoding

The POSIX locale contains the characters in Table 6-1 (on page 113), which have the properties listed in Section 7.3.1 (on page 126). In other locales, the presence, meaning, and representation of any additional characters are locale-specific.

In locales other than the POSIX locale, a character may have a state-dependent encoding. There are two types of these encodings:

- A single-shift encoding (where each character not in the initial shift state is preceded by a shift code) can be defined if each shift-code and character sequence is considered a multi-byte character. This is done using the concatenated-constant format in a character set description file, as described in Section 6.4 (on page 117). If the implementation supports a character encoding of this type, all of the standard utilities in the Shell and Utilities volume of IEEE Std 1003.1-2001 shall support it. Use of a single-shift encoding with any of the functions in the System Interfaces volume of IEEE Std 1003.1-2001 that do not specifically mention the effects of state-dependent encoding is implementation-defined.
- A locking-shift encoding (where the state of the character is determined by a shift code that may affect more than the single character following it) cannot be defined with the current character set description file format. Use of a locking-shift encoding with any of the standard utilities in the Shell and Utilities volume of IEEE Std 1003.1-2001 or with any of the functions in the System Interfaces volume of IEEE Std 1003.1-2001 that do not specifically mention the effects of state-dependent encoding is implementation-defined.

While in the initial shift state, all characters in the portable character set shall retain their usual interpretation and shall not alter the shift state. The interpretation for subsequent bytes in the sequence shall be a function of the current shift state. A byte with all bits zero shall be interpreted as the null character independent of shift state. Thus a byte with all bits zero shall never occur in the second or subsequent bytes of a character.

The maximum allowable number of bytes in a character in the current locale shall be indicated by {MB_CUR_MAX}, defined in the **<stdlib.h>** header and by the **<mb_cur_max>** value in a character set description file; see Section 6.4 (on page 117). The implementation's maximum number of bytes in a character shall be defined by the C-language macro {MB_LEN_MAX}.

6.3 C Language Wide-Character Codes

In the shell, the standard utilities are written so that the encodings of characters are described by the locale's *LC_CTYPE* definition (see Section 7.3.1 (on page 126)) and there is no differentiation between characters consisting of single octets (8-bit bytes) or multiple bytes. However, in the C language, a differentiation is made. To ease the handling of variable length characters, the C language has introduced the concept of wide-character codes.

All wide-character codes in a given process consist of an equal number of bits. This is in contrast to characters, which can consist of a variable number of bytes. The byte or byte sequence that represents a character can also be represented as a wide-character code. Wide-character codes thus provide a uniform size for manipulating text data. A wide-character code having all bits zero is the null wide-character code (see Section 3.246 (on page 69)), and terminates wide-character strings (see Section 3.432 (on page 94)). The wide-character value for each member of the portable character set shall equal its value when used as the lone character in an integer character constant. Wide-character codes for other characters are locale and implementation-defined. State shift bytes shall not have a wide-character code representation. This standard provides no means of defining a wide-character codeset.

6.4 Character Set Description File

Implementations shall provide a character set description file for at least one coded character set supported by the implementation. These files are referred to elsewhere in IEEE Std 1003.1-2001 as *charmap* files. It is implementation-defined whether or not users or applications can provide additional character set description files.

IEEE Std 1003.1-2001 does not require that multiple character sets or codesets be supported. Although multiple charmap files are supported, it is the responsibility of the implementation to provide the file or files; if only one is provided, only that one is accessible using the *localedef* utility's **–f** option.

Each character set description file, except those that use the ISO/IEC 10646-1:2000 standard position values as the encoding values, shall define characteristics for the coded character set and the encoding for the characters specified in Table 6-1 (on page 113), and may define encoding for additional characters supported by the implementation. Other information about the coded character set may also be in the file. Coded character set character values shall be defined using symbolic character names followed by character encoding values.

Each symbolic name specified in Table 6-1 (on page 113) shall be included in the file and shall be mapped to a unique coding value, except as noted below. The glyphs '{', '}', '_', '-', '/', '\', '.', and '^' have more than one symbolic name; all symbolic names for each such glyph shall be included, each with identical encoding. If some or all of the control characters identified in Table 6-2 (on page 118) are supported by the implementation, the symbolic names and their corresponding encoding values shall be included in the file. Some of the encodings associated with the symbolic names in Table 6-2 (on page 118) may be the same as characters found in Table 6-1 (on page 113); both names shall be provided for each encoding.

Table 6-2 Control Character Set

<ACK>	<DC2>	<ENQ>	<FS>	<IS4>	<SOH>
<BEL>	<DC3>	<EOT>	<GS>	<LF>	<STX>
<BS>	<DC4>	<ESC>	<HT>	<NAK>	<SUB>
<CAN>	<DEL>	<ETB>	<IS1>	<RS>	<SYN>
<CR>	<DLE>	<ETX>	<IS2>	<SI>	<US>
<DC1>	<EM>	<FF>	<IS3>	<SO>	<VT>

The following declarations can precede the character definitions. Each shall consist of the symbol shown in the following list, starting in column 1, including the surrounding brackets, followed by one or more <blank>s, followed by the value to be assigned to the symbol.

<code_set_name> The name of the coded character set for which the character set description file is defined. The characters of the name shall be taken from the set of characters with visible glyphs defined in Table 6-1 (on page 113).

<mb_cur_max> The maximum number of bytes in a multi-byte character. This shall default to 1.

<mb_cur_min> XSI An unsigned positive integer value that defines the minimum number of bytes in a character for the encoded character set. On XSI-conformant systems, **<mb_cur_min>** shall always be 1.

<escape_char> The character used to indicate that the characters following shall be interpreted in a special way, as defined later in this section. This shall default to backslash (`'\'`), which is the character used in all the following text and examples, unless otherwise noted.

<comment_char> The character that, when placed in column 1 of a charmap line, is used to indicate that the line shall be ignored. The default character shall be the number sign (`'#'`).

The character set mapping definitions shall be all the lines immediately following an identifier line containing the string `"CHARMAP"` starting in column 1, and preceding a trailer line containing the string `"END CHARMAP"` starting in column 1. Empty lines and lines containing a **<comment_char>** in the first column shall be ignored. Each non-comment line of the character set mapping definition (that is, between the `"CHARMAP"` and `"END CHARMAP"` lines of the file) shall be in either of two forms:

```
"%s %s %s\n", <symbolic-name>, <encoding>, <comments>
```

or:

```
"%s...%s %s %s\n", <symbolic-name>, <symbolic-name>,
    <encoding>, <comments>
```

In the first format, the line in the character set mapping definition shall define a single symbolic name and a corresponding encoding. A symbolic name is one or more characters from the set shown with visible glyphs in Table 6-1 (on page 113), enclosed between angle brackets. A character following an escape character is interpreted as itself; for example, the sequence `"<\\\>>"` represents the symbolic name `"\>"` enclosed between angle brackets.

In the second format, the line in the character set mapping definition shall define a range of one or more symbolic names. In this form, the symbolic names shall consist of zero or more non-numeric characters from the set shown with visible glyphs in Table 6-1 (on page 113), followed by an integer formed by one or more decimal digits. Both integers shall contain the same number of digits. The characters preceding the integer shall be identical in the two symbolic names, and

the integer formed by the digits in the second symbolic name shall be equal to or greater than the integer formed by the digits in the first name. This shall be interpreted as a series of symbolic names formed from the common part and each of the integers between the first and the second integer, inclusive. As an example, <j0101>...<j0104> is interpreted as the symbolic names <j0101>, <j0102>, <j0103>, and <j0104>, in that order.

A character set mapping definition line shall exist for all symbolic names specified in Table 6-1 (on page 113), and shall define the coded character value that corresponds to the character indicated in the table, or the coded character value that corresponds to the control character symbolic name. If the control characters commonly associated with the symbolic names in Table 6-2 (on page 118) are supported by the implementation, the symbolic name and the corresponding encoding value shall be included in the file. Additional unique symbolic names may be included. A coded character value can be represented by more than one symbolic name.

The encoding part is expressed as one (for single-byte character values) or more concatenated decimal, octal, or hexadecimal constants in the following formats:

```
"%cd%u", <escape_char>, <decimal byte value>
"%cx%x", <escape_char>, <hexadecimal byte value>
"%c%o", <escape_char>, <octal byte value>
```

Decimal constants shall be represented by two or three decimal digits, preceded by the escape character and the lowercase letter *'d'*; for example, "\d05", "\d97", or "\d143". Hexadecimal constants shall be represented by two hexadecimal digits, preceded by the escape character and the lowercase letter *'x'*; for example, "\x05", "\x61", or "\x8f". Octal constants shall be represented by two or three octal digits, preceded by the escape character; for example, "\05", "\141", or "\217". In a portable charmap file, each constant represents an 8-bit byte. When constants are concatenated for multi-byte character values, they shall be of the same type, and interpreted in byte order from first to last with the least significant byte of the multi-byte character specified by the last constant. The manner in which these constants are represented in the character stored in the system is implementation-defined. (This notation was chosen for reasons of portability. There is no requirement that the internal representation in the computer memory be in this same order.) Omitting bytes from a multi-byte character definition produces undefined results.

In lines defining ranges of symbolic names, the encoded value shall be the value for the first symbolic name in the range (the symbolic name preceding the ellipsis). Subsequent symbolic names defined by the range shall have encoding values in increasing order. Bytes shall be treated as unsigned octets, and carry shall be propagated between the bytes as necessary to represent the range. However, because this causes a null byte in the second or subsequent bytes of a character, such a declaration should not be specified. For example, the line: 2 2

```
<j0101>...<j0104>  \d129\d254
```

is interpreted as:

```
<j0101>            \d129\d254
<j0102>            \d129\d255
<j0103>            \d130\d00                    2
<j0104>            \d130\d01                    2
```

The expanded declaration of the symbol <j0103> in the above example is an invalid specification, because it contains a null byte in the second byte of a character. 2 2

The comment is optional. 2

This standard provides no means of defining a wide-character codeset. 2

The following declarations can follow the character set mapping definitions (after the "END CHARMAP" statement). Each shall consist of the keyword shown in the following list, starting in column 1, followed by the value(s) to be associated to the keyword, as defined below.

WIDTH A non-negative integer value defining the column width (see Section 3.103 (on page 49)) for the printable characters in the coded character set specified in Table 6-1 (on page 113) and Table 6-2 (on page 118). Coded character set character values shall be defined using symbolic character names followed by column width values. Defining a character with more than one **WIDTH** produces undefined results. The **END WIDTH** keyword shall be used to terminate the **WIDTH** definitions. Specifying the width of a non-printable character in a **WIDTH** declaration produces undefined results. 2

WIDTH_DEFAULT
A non-negative integer value defining the default column width for any printable character not listed by one of the **WIDTH** keywords. If no **WIDTH_DEFAULT** keyword is included in the charmap, the default character width shall be 1. 2

Example

After the "END CHARMAP" statement, a syntax for a width definition would be:

```
WIDTH
<A> 1
<B> 1
<C>...<Z> 1
...
<foo1>...<foon> 2
...
END WIDTH
```

In this example, the numerical code point values represented by the symbols **<A>** and **<B>** are assigned a width of 1. The code point values **<C>** to **<Z>** inclusive (**<C>**, **<D>**, **<E>**, and so on) are also assigned a width of 1. Using **<A>**...**<Z>** would have required fewer lines, but the alternative was shown to demonstrate flexibility. The keyword **WIDTH_DEFAULT** could have been added as appropriate.

6.4.1 State-Dependent Character Encodings

This section addresses the use of state-dependent character encodings (that is, those in which the encoding of a character is dependent on one or more shift codes that may precede it).

A single-shift encoding (where each character not in the initial shift state is preceded by a shift code) can be defined in the charmap format if each shift-code/character sequence is considered a multi-byte character, defined using the concatenated-constant format described in Section 6.4 (on page 117). If the implementation supports a character encoding of this type, all of the standard utilities shall support it. A locking-shift encoding (where the state of the character is determined by a shift code that may affect more than the single character following it) could be defined with an extension to the charmap format described in Section 6.4 (on page 117). If the implementation supports a character encoding of this type, any of the standard utilities that describe character (*versus* byte) or text-file manipulation shall have the following characteristics:

1. The utility shall process the statefully encoded data as a concatenation of state-independent characters. The presence of redundant locking shifts shall not affect the comparison of two statefully encoded strings.

2. A utility that divides, truncates, or extracts substrings from statefully encoded data shall produce output that contains locking shifts at the beginning or end of the resulting data, if appropriate, to retain correct state information.

3912

Chapter 7

Locale

7.1 General

A locale is the definition of the subset of a user's environment that depends on language and cultural conventions. It is made up from one or more categories. Each category is identified by its name and controls specific aspects of the behavior of components of the system. Category names correspond to the following environment variable names:

LC_CTYPE Character classification and case conversion.

LC_COLLATE Collation order.

LC_MONETARY Monetary formatting.

LC_NUMERIC Numeric, non-monetary formatting.

LC_TIME Date and time formats.

LC_MESSAGES Formats of informative and diagnostic messages and interactive responses.

The standard utilities in the Shell and Utilities volume of IEEE Std 1003.1-2001 shall base their behavior on the current locale, as defined in the ENVIRONMENT VARIABLES section for each utility. The behavior of some of the C-language functions defined in the System Interfaces volume of IEEE Std 1003.1-2001 shall also be modified based on the current locale, as defined by the last call to *setlocale*( ).

Locales other than those supplied by the implementation can be created via the *localedef* utility, provided that the _POSIX2_LOCALEDEF symbol is defined on the system. Even if *localedef* is not provided, all implementations conforming to the System Interfaces volume of IEEE Std 1003.1-2001 shall provide one or more locales that behave as described in this chapter. The input to the utility is described in Section 7.3 (on page 124). The value that is used to specify a locale when using environment variables shall be the string specified as the *name* operand to the *localedef* utility when the locale was created. The strings `"C"` and `"POSIX"` are reserved as identifiers for the POSIX locale (see Section 7.2 (on page 124)). When the value of a locale environment variable begins with a slash (`'/'`), it shall be interpreted as the pathname of the locale definition; the type of file (regular, directory, and so on) used to store the locale definition is implementation-defined. If the value does not begin with a slash, the mechanism used to locate the locale is implementation-defined.

If different character sets are used by the locale categories, the results achieved by an application utilizing these categories are undefined. Likewise, if different codesets are used for the data being processed by interfaces whose behavior is dependent on the current locale, or the codeset is different from the codeset assumed when the locale was created, the result is also undefined.

Applications can select the desired locale by invoking the *setlocale*( ) function (or equivalent) with the appropriate value. If the function is invoked with an empty string, such as:

```
setlocale(LC_ALL, "");
```

the value of the corresponding environment variable is used. If the environment variable is unset or is set to the empty string, the implementation shall set the appropriate environment as defined in Chapter 8 (on page 161).

7.2 POSIX Locale

Conforming systems shall provide a POSIX locale, also known as the C locale. The behavior of standard utilities and functions in the POSIX locale shall be as if the locale was defined via the *localedef* utility with input data from the POSIX locale tables in Section 7.3.

The tables in Section 7.3 describe the characteristics and behavior of the POSIX locale for data consisting entirely of characters from the portable character set and the control character set. For other characters, the behavior is unspecified. For C-language programs, the POSIX locale shall be the default locale when the *setlocale*( ) function is not called.

The POSIX locale can be specified by assigning to the appropriate environment variables the values `"C"` or `"POSIX"`.

All implementations shall define a locale as the default locale, to be invoked when no environment variables are set, or set to the empty string. This default locale can be the POSIX locale or any other implementation-defined locale. Some implementations may provide facilities for local installation administrators to set the default locale, customizing it for each location. IEEE Std 1003.1-2001 does not require such a facility.

7.3 Locale Definition

The capability to specify additional locales to those provided by an implementation is optional, denoted by the _POSIX2_LOCALEDEF symbol. If the option is not supported, only implementation-supplied locales are available. Such locales shall be documented using the format specified in this section.

Locales can be described with the file format presented in this section. The file format is that accepted by the *localedef* utility. For the purposes of this section, the file is referred to as the ‘‘locale definition file’’, but no locales shall be affected by this file unless it is processed by *localedef* or some similar mechanism. Any requirements in this section imposed upon the utility shall apply to *localedef* or to any other similar utility used to install locale information using the locale definition file format described here.

The locale definition file shall contain one or more locale category source definitions, and shall not contain more than one definition for the same locale category. If the file contains source definitions for more than one category, implementation-defined categories, if present, shall appear after the categories defined by Section 7.1 (on page 123). A category source definition contains either the definition of a category or a **copy** directive. For a description of the **copy** directive, see *localedef*. In the event that some of the information for a locale category, as specified in this volume of IEEE Std 1003.1-2001, is missing from the locale source definition, the behavior of that category, if it is referenced, is unspecified.

A category source definition shall consist of a category header, a category body, and a category trailer. A category header shall consist of the character string naming of the category, beginning with the characters *LC_*. The category trailer shall consist of the string `"END"`, followed by one or more <blank>s and the string used in the corresponding category header.

The category body shall consist of one or more lines of text. Each line shall contain an identifier, optionally followed by one or more operands. Identifiers shall be either keywords, identifying a particular locale element, or collating elements. In addition to the keywords defined in this volume of IEEE Std 1003.1-2001, the source can contain implementation-defined keywords. Each keyword within a locale shall have a unique name (that is, two categories cannot have a commonly-named keyword); no keyword shall start with the characters *LC_*. Identifiers shall be separated from the operands by one or more <blank>s.

Operands shall be characters, collating elements, or strings of characters. Strings shall be enclosed in double-quotes. Literal double-quotes within strings shall be preceded by the <*escape character*>, described below. When a keyword is followed by more than one operand, the operands shall be separated by semicolons; <blank>s shall be allowed both before and after a semicolon.

The first category header in the file can be preceded by a line modifying the comment character. It shall have the following format, starting in column 1:

```
"comment_char %c\n", <comment character>
```

The comment character shall default to the number sign (`'#'`). Blank lines and lines containing the <*comment character*> in the first position shall be ignored.

The first category header in the file can be preceded by a line modifying the escape character to be used in the file. It shall have the following format, starting in column 1:

```
"escape_char %c\n", <escape character>
```

The escape character shall default to backslash, which is the character used in all examples shown in this volume of IEEE Std 1003.1-2001.

A line can be continued by placing an escape character as the last character on the line; this continuation character shall be discarded from the input. Although the implementation need not accept any one portion of a continued line with a length exceeding {LINE_MAX} bytes, it shall place no limits on the accumulated length of the continued line. Comment lines shall not be continued on a subsequent line using an escaped <newline>.

Individual characters, characters in strings, and collating elements shall be represented using symbolic names, as defined below. In addition, characters can be represented using the characters themselves or as octal, hexadecimal, or decimal constants. When non-symbolic notation is used, the resultant locale definitions are in many cases not portable between systems. The left angle bracket (`'<'`) is a reserved symbol, denoting the start of a symbolic name; when used to represent itself it shall be preceded by the escape character. The following rules apply to character representation:

1. A character can be represented via a symbolic name, enclosed within angle brackets `'<'` and `'>'`. The symbolic name, including the angle brackets, shall exactly match a symbolic name defined in the charmap file specified via the *localedef* **–f** option, and it shall be replaced by a character value determined from the value associated with the symbolic name in the charmap file. The use of a symbolic name not found in the charmap file shall constitute an error, unless the category is *LC_CTYPE* or *LC_COLLATE*, in which case it shall constitute a warning condition (see *localedef* for a description of actions resulting from errors and warnings). The specification of a symbolic name in a **collating-element** or **collating-symbol** section that duplicates a symbolic name in the charmap file (if present) shall be an error. Use of the escape character or a right angle bracket within a symbolic name is invalid unless the character is preceded by the escape character.

   For example:

   ```
   <c>;<c–cedilla>  "<M><a><y>"
   ```

2. A character in the portable character set can be represented by the character itself, in which case the value of the character is implementation-defined. (Implementations may allow other characters to be represented as themselves, but such locale definitions are not portable.) Within a string, the double-quote character, the escape character, and the right angle bracket character shall be escaped (preceded by the escape character) to be interpreted as the character itself. Outside strings, the characters:

4043 `,` `;` `<` `>` *`escape_char`*

4044 shall be escaped to be interpreted as the character itself.

4045 For example:

4046 `c "May"`

4047 3. A character can be represented as an octal constant. An octal constant shall be specified as
4048 the escape character followed by two or three octal digits. Each constant shall represent a
4049 byte value. Multi-byte values can be represented by concatenated constants specified in
4050 byte order with the last constant specifying the least significant byte of the character.

4051 For example:

4052 `\143;\347;\143\150 "\115\141\171"`

4053 4. A character can be represented as a hexadecimal constant. A hexadecimal constant shall be
4054 specified as the escape character followed by an `'x'` followed by two hexadecimal digits.
4055 Each constant shall represent a byte value. Multi-byte values can be represented by
4056 concatenated constants specified in byte order with the last constant specifying the least
4057 significant byte of the character.

4058 For example:

4059 `\x63;\xe7;\x63\x68 "\x4d\x61\x79"`

4060 5. A character can be represented as a decimal constant. A decimal constant shall be specified
4061 as the escape character followed by a `'d'` followed by two or three decimal digits. Each
4062 constant represents a byte value. Multi-byte values can be represented by concatenated
4063 constants specified in byte order with the last constant specifying the least significant byte
4064 of the character.

4065 For example:

4066 `\d99;\d231;\d99\d104 "\d77\d97\d121"`

4067 Implementations may accept single-digit octal, decimal, or hexadecimal constants following the
4068 escape character. Only characters existing in the character set for which the locale definition is
4069 created shall be specified, whether using symbolic names, the characters themselves, or octal,
4070 decimal, or hexadecimal constants. If a charmap file is present, only characters defined in the
4071 charmap can be specified using octal, decimal, or hexadecimal constants. Symbolic names not
4072 present in the charmap file can be specified and shall be ignored, as specified under item 1
4073 above.

4074 ### 7.3.1 LC_CTYPE

4075 The *LC_CTYPE* category shall define character classification, case conversion, and other
4076 character attributes. In addition, a series of characters can be represented by three adjacent
4077 periods representing an ellipsis symbol (`"..."`). The ellipsis specification shall be interpreted as
4078 meaning that all values between the values preceding and following it represent valid
4079 characters. The ellipsis specification shall be valid only within a single encoded character set;
4080 that is, within a group of characters of the same size. An ellipsis shall be interpreted as including
4081 in the list all characters with an encoded value higher than the encoded value of the character
4082 preceding the ellipsis and lower than the encoded value of the character following the ellipsis.

4083 For example:

4084 `\x30;...;\x39;`

includes in the character class all characters with encoded values between the endpoints.

The following keywords shall be recognized. In the descriptions, the term ‘‘automatically included’’ means that it shall not be an error either to include or omit any of the referenced characters; the implementation provides them if missing (even if the entire keyword is missing) and accepts them silently if present. When the implementation automatically includes a missing character, it shall have an encoded value dependent on the charmap file in effect (see the description of the *localedef* **–f** option); otherwise, it shall have a value derived from an implementation-defined character mapping.

The character classes **digit**, **xdigit**, **lower**, **upper**, and **space** have a set of automatically included characters. These only need to be specified if the character values (that is, encoding) differ from the implementation default values. It is not possible to define a locale without these automatically included characters unless some implementation extension is used to prevent their inclusion. Such a definition would not be a proper superset of the C or POSIX locale and, thus, it might not be possible for conforming applications to work properly.

copy Specify the name of an existing locale which shall be used as the definition of this category. If this keyword is specified, no other keyword shall be specified.

upper Define characters to be classified as uppercase letters.

In the POSIX locale, the 26 uppercase letters shall be included:

```
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
```

In a locale definition file, no character specified for the keywords **cntrl**, **digit**, **punct**, or **space** shall be specified. The uppercase letters <A> to <Z>, as defined in Section 6.4 (on page 117) (the portable character set), are automatically included in this class.

lower Define characters to be classified as lowercase letters.

In the POSIX locale, the 26 lowercase letters shall be included:

```
a b c d e f g h i j k l m n o p q r s t u v w x y z
```

In a locale definition file, no character specified for the keywords **cntrl**, **digit**, **punct**, or **space** shall be specified. The lowercase letters <a> to <z> of the portable character set are automatically included in this class.

alpha Define characters to be classified as letters.

In the POSIX locale, all characters in the classes **upper** and **lower** shall be included.

In a locale definition file, no character specified for the keywords **cntrl**, **digit**, **punct**, or **space** shall be specified. Characters classified as either **upper** or **lower** are automatically included in this class.

digit Define the characters to be classified as numeric digits.

In the POSIX locale, only:

```
0 1 2 3 4 5 6 7 8 9
```

shall be included.

In a locale definition file, only the digits <zero>, <one>, <two>, <three>, <four>, <five>, <six>, <seven>, <eight>, and <nine> shall be specified, and in contiguous ascending sequence by numerical value. The digits <zero> to <nine> of the portable character set are automatically included in this class.

alnum Define characters to be classified as letters and numeric digits. Only the characters specified for the **alpha** and **digit** keywords shall be specified. Characters specified for the keywords **alpha** and **digit** are automatically included in this class.

space Define characters to be classified as white-space characters.

In the POSIX locale, at a minimum, the <space>, <form-feed>, <newline>, <carriage-return>, <tab>, and <vertical-tab> shall be included.

In a locale definition file, no character specified for the keywords **upper**, **lower**, **alpha**, **digit**, **graph**, or **xdigit** shall be specified. The <space>, <form-feed>, <newline>, <carriage-return>, <tab>, and <vertical-tab> of the portable character set, and any characters included in the class **blank** are automatically included in this class.

cntrl Define characters to be classified as control characters.

In the POSIX locale, no characters in classes **alpha** or **print** shall be included.

In a locale definition file, no character specified for the keywords **upper**, **lower**, **alpha**, **digit**, **punct**, **graph**, **print**, or **xdigit** shall be specified.

punct Define characters to be classified as punctuation characters.

In the POSIX locale, neither the <space> nor any characters in classes **alpha**, **digit**, or **cntrl** shall be included.

In a locale definition file, no character specified for the keywords **upper**, **lower**, **alpha**, **digit**, **cntrl**, **xdigit**, or as the <space> shall be specified.

graph Define characters to be classified as printable characters, not including the <space>.

In the POSIX locale, all characters in classes **alpha**, **digit**, and **punct** shall be included; no characters in class **cntrl** shall be included.

In a locale definition file, characters specified for the keywords **upper**, **lower**, **alpha**, **digit**, **xdigit**, and **punct** are automatically included in this class. No character specified for the keyword **cntrl** shall be specified.

print Define characters to be classified as printable characters, including the <space>.

In the POSIX locale, all characters in class **graph** shall be included; no characters in class **cntrl** shall be included.

In a locale definition file, characters specified for the keywords **upper**, **lower**, **alpha**, **digit**, **xdigit**, **punct, graph**, and the <space> are automatically included in this class. No character specified for the keyword **cntrl** shall be specified.

xdigit Define the characters to be classified as hexadecimal digits.

In the POSIX locale, only:

```
0 1 2 3 4 5 6 7 8 9 A B C D E F a b c d e f
```

shall be included.

In a locale definition file, only the characters defined for the class **digit** shall be specified, in contiguous ascending sequence by numerical value, followed by one or more sets of six characters representing the hexadecimal digits 10 to 15

inclusive, with each set in ascending order (for example, <A>, <B>, <C>, <D>, <E>, <F>, <a>, <b>, <c>, <d>, <e>, <f>). The digits <zero> to <nine>, the uppercase letters <A> to <F>, and the lowercase letters <a> to <f> of the portable character set are automatically included in this class.

blank Define characters to be classified as <blank>s.

In the POSIX locale, only the <space> and <tab> shall be included.

In a locale definition file, the <space> and <tab> are automatically included in this class.

charclass Define one or more locale-specific character class names as strings separated by semicolons. Each named character class can then be defined subsequently in the *LC_CTYPE* definition. A character class name shall consist of at least one and at most {CHARCLASS_NAME_MAX} bytes of alphanumeric characters from the portable filename character set. The first character of a character class name shall not be a digit. The name shall not match any of the *LC_CTYPE* keywords defined in this volume of IEEE Std 1003.1-2001. Future revisions of IEEE Std 1003.1-2001 will not specify any *LC_CTYPE* keywords containing uppercase letters.

charclass-name Define characters to be classified as belonging to the named locale-specific character class. In the POSIX locale, locale-specific named character classes need not exist.

If a class name is defined by a **charclass** keyword, but no characters are subsequently assigned to it, this is not an error; it represents a class without any characters belonging to it.

The *charclass-name* can be used as the *property* argument to the *wctype*( ) function, in regular expression and shell pattern-matching bracket expressions, and by the *tr* command.

toupper Define the mapping of lowercase letters to uppercase letters.

In the POSIX locale, at a minimum, the 26 lowercase characters:

```
a b c d e f g h i j k l m n o p q r s t u v w x y z
```

shall be mapped to the corresponding 26 uppercase characters:

```
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
```

In a locale definition file, the operand shall consist of character pairs, separated by semicolons. The characters in each character pair shall be separated by a comma and the pair enclosed by parentheses. The first character in each pair is the lowercase letter, the second the corresponding uppercase letter. Only characters specified for the keywords **lower** and **upper** shall be specified. The lowercase letters <a> to <z>, and their corresponding uppercase letters <A> to <Z>, of the portable character set are automatically included in this mapping, but only when the **toupper** keyword is omitted from the locale definition.

tolower Define the mapping of uppercase letters to lowercase letters.

In the POSIX locale, at a minimum, the 26 uppercase characters:

```
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
```

4213 shall be mapped to the corresponding 26 lowercase characters:

4214 `a b c d e f g h i j k l m n o p q r s t u v w x y z`

4215 In a locale definition file, the operand shall consist of character pairs,
4216 separated by semicolons. The characters in each character pair shall be
4217 separated by a comma and the pair enclosed by parentheses. The first
4218 character in each pair is the uppercase letter, the second the corresponding
4219 lowercase letter. Only characters specified for the keywords **lower** and **upper**
4220 shall be specified. If the **tolower** keyword is omitted from the locale definition,
4221 the mapping is the reverse mapping of the one specified for **toupper**.

4222 The following table shows the character class combinations allowed:

4223 **Table 7-1** Valid Character Class Combinations

	Can Also Belong To										
In Class	**upper**	**lower**	**alpha**	**digit**	**space**	**cntrl**	**punct**	**graph**	**print**	**xdigit**	**blank**
upper		—	A	x	x	x	x	A	A	—	x
lower	—		A	x	x	x	x	A	A	—	x
alpha	—	—		x	x	x	x	A	A	—	x
digit	x	x	x		x	x	x	A	A	A	x
space	x	x	x	x		—	*	*	*	x	—
cntrl	x	x	x	x	—		x	x	x	x	—
punct	x	x	x	x	—	x		A	A	x	—
graph	—	—	—	—	—	x	—		A	—	—
print	—	—	—	—	—	x	—	—		—	—
xdigit	—	—	—	—	x	x	x	A	A		x
blank	x	x	x	x	A	—	*	*	*	x	

4237 **Notes:**

4238 1. Explanation of codes:

4239 A Automatically included; see text.

4240 — Permitted.

4241 x Mutually-exclusive.

4242 * See note 2.

4243 2. The <space>, which is part of the **space** and **blank** classes, cannot belong to **punct** or
4244 **graph**, but shall automatically belong to the **print** class. Other **space** or **blank** characters
4245 can be classified as any of **punct**, **graph**, or **print**.

4246 *7.3.1.1 LC_CTYPE Category in the POSIX Locale*

4247 The character classifications for the POSIX locale follow; the code listing depicts the *localedef*
4248 input, and the table represents the same information, sorted by character.

```
4249 LC_CTYPE
4250 # The following is the POSIX locale LC_CTYPE.
4251 # "alpha" is by default "upper" and "lower"
4252 # "alnum" is by definition "alpha" and "digit"
4253 # "print" is by default "alnum", "punct", and the <space>
4254 # "graph" is by default "alnum" and "punct"
4255 #
4256 upper    <A>;<B>;<C>;<D>;<E>;<F>;<G>;<H>;<I>;<J>;<K>;<L>;<M>;\
```

```
4257                <N>;<O>;<P>;<Q>;<R>;<S>;<T>;<U>;<V>;<W>;<X>;<Y>;<Z>
4258        #
4259        lower   <a>;<b>;<c>;<d>;<e>;<f>;<g>;<h>;<i>;<j>;<k>;<l>;<m>;\
4260                <n>;<o>;<p>;<q>;<r>;<s>;<t>;<u>;<v>;<w>;<x>;<y>;<z>
4261        #
4262        digit   <zero>;<one>;<two>;<three>;<four>;<five>;<six>;\
4263                <seven>;<eight>;<nine>
4264        #
4265        space   <tab>;<newline>;<vertical-tab>;<form-feed>;\
4266                <carriage-return>;<space>
4267        #
4268        cntrl   <alert>;<backspace>;<tab>;<newline>;<vertical-tab>;\
4269                <form-feed>;<carriage-return>;\
4270                <NUL>;<SOH>;<STX>;<ETX>;<EOT>;<ENQ>;<ACK>;<SO>;\
4271                <SI>;<DLE>;<DC1>;<DC2>;<DC3>;<DC4>;<NAK>;<SYN>;\
4272                <ETB>;<CAN>;<EM>;<SUB>;<ESC>;<IS4>;<IS3>;<IS2>;\
4273                <IS1>;<DEL>
4274        #
4275        punct   <exclamation-mark>;<quotation-mark>;<number-sign>;\
4276                <dollar-sign>;<percent-sign>;<ampersand>;<apostrophe>;\
4277                <left-parenthesis>;<right-parenthesis>;<asterisk>;\
4278                <plus-sign>;<comma>;<hyphen>;<period>;<slash>;\
4279                <colon>;<semicolon>;<less-than-sign>;<equals-sign>;\
4280                <greater-than-sign>;<question-mark>;<commercial-at>;\
4281                <left-square-bracket>;<backslash>;<right-square-bracket>;\
4282                <circumflex>;<underscore>;<grave-accent>;<left-curly-bracket>;\
4283                <vertical-line>;<right-curly-bracket>;<tilde>
4284        #
4285        xdigit  <zero>;<one>;<two>;<three>;<four>;<five>;<six>;<seven>;\
4286                <eight>;<nine>;<A>;<B>;<C>;<D>;<E>;<F>;<a>;<b>;<c>;<d>;<e>;<f>
4287        #
4288        blank   <space>;<tab>
4289        #
4290        toupper (<a>,<A>);(<b>,<B>);(<c>,<C>);(<d>,<D>);(<e>,<E>);\
4291                (<f>,<F>);(<g>,<G>);(<h>,<H>);(<i>,<I>);(<j>,<J>);\
4292                (<k>,<K>);(<l>,<L>);(<m>,<M>);(<n>,<N>);(<o>,<O>);\
4293                (<p>,<P>);(<q>,<Q>);(<r>,<R>);(<s>,<S>);(<t>,<T>);\
4294                (<u>,<U>);(<v>,<V>);(<w>,<W>);(<x>,<X>);(<y>,<Y>);(<z>,<Z>)
4295        #
4296        tolower (<A>,<a>);(<B>,<b>);(<C>,<c>);(<D>,<d>);(<E>,<e>);\
4297                (<F>,<f>);(<G>,<g>);(<H>,<h>);(<I>,<i>);(<J>,<j>);\
4298                (<K>,<k>);(<L>,<l>);(<M>,<m>);(<N>,<n>);(<O>,<o>);\
4299                (<P>,<p>);(<Q>,<q>);(<R>,<r>);(<S>,<s>);(<T>,<t>);\
4300                (<U>,<u>);(<V>,<v>);(<W>,<w>);(<X>,<x>);(<Y>,<y>);(<Z>,<z>)
4301        END LC_CTYPE
```


Symbolic Name	Other Case	Character Classes
<NUL>		**cntrl**
<SOH>		**cntrl**
<STX>		**cntrl**
<ETX>		**cntrl**
<EOT>		**cntrl**
<ENQ>		**cntrl**
<ACK>		**cntrl**
<alert>		**cntrl**
<backspace>		**cntrl**
<tab>		**cntrl, space, blank**
<newline>		**cntrl, space**
<vertical-tab>		**cntrl, space**
<form-feed>		**cntrl, space**
<carriage-return>		**cntrl, space**
<SO>		**cntrl**
<SI>		**cntrl**
<DLE>		**cntrl**
<DC1>		**cntrl**
<DC2>		**cntrl**
<DC3>		**cntrl**
<DC4>		**cntrl**
<NAK>		**cntrl**
<SYN>		**cntrl**
<ETB>		**cntrl**
<CAN>		**cntrl**
<EM>		**cntrl**
<SUB>		**cntrl**
<ESC>		**cntrl**
<IS4>		**cntrl**
<IS3>		**cntrl**
<IS2>		**cntrl**
<IS1>		**cntrl**
<space>		**space, print, blank**
<exclamation-mark>		**punct, print, graph**
<quotation-mark>		**punct, print, graph**
<number-sign>		**punct, print, graph**
<dollar-sign>		**punct, print, graph**
<percent-sign>		**punct, print, graph**
<ampersand>		**punct, print, graph**
<apostrophe>		**punct, print, graph**
<left-parenthesis>		**punct, print, graph**
<right-parenthesis>		**punct, print, graph**
<asterisk>		**punct, print, graph**
<plus-sign>		**punct, print, graph**
<comma>		**punct, print, graph**
<hyphen>		**punct, print, graph**
<period>		**punct, print, graph**

Symbolic Name	Other Case	Character Classes
<slash>		**punct, print, graph**
<zero>		**digit, xdigit, print, graph**
<one>		**digit, xdigit, print, graph**
<two>		**digit, xdigit, print, graph**
<three>		**digit, xdigit, print, graph**
<four>		**digit, xdigit, print, graph**
<five>		**digit, xdigit, print, graph**
<six>		**digit, xdigit, print, graph**
<seven>		**digit, xdigit, print, graph**
<eight>		**digit, xdigit, print, graph**
<nine>		**digit, xdigit, print, graph**
<colon>		**punct, print, graph**
<semicolon>		**punct, print, graph**
<less-than-sign>		**punct, print, graph**
<equals-sign>		**punct, print, graph**
<greater-than-sign>		**punct, print, graph**
<question-mark>		**punct, print, graph**
<commercial-at>		**punct, print, graph**
<A>	<a>	**upper, xdigit, alpha, print, graph**
<B>	<b>	**upper, xdigit, alpha, print, graph**
<C>	<c>	**upper, xdigit, alpha, print, graph**
<D>	<d>	**upper, xdigit, alpha, print, graph**
<E>	<e>	**upper, xdigit, alpha, print, graph**
<F>	<f>	**upper, xdigit, alpha, print, graph**
<G>	<g>	**upper, alpha, print, graph**
<H>	<h>	**upper, alpha, print, graph**
<I>	<i>	**upper, alpha, print, graph**
<J>	<j>	**upper, alpha, print, graph**
<K>	<k>	**upper, alpha, print, graph**
<L>	<l>	**upper, alpha, print, graph**
<M>	<m>	**upper, alpha, print, graph**
<N>	<n>	**upper, alpha, print, graph**
<O>	<o>	**upper, alpha, print, graph**
<P>	<p>	**upper, alpha, print, graph**
<Q>	<q>	**upper, alpha, print, graph**
<R>	<r>	**upper, alpha, print, graph**
<S>	<s>	**upper, alpha, print, graph**
<T>	<t>	**upper, alpha, print, graph**
<U>	<u>	**upper, alpha, print, graph**
<V>	<v>	**upper, alpha, print, graph**
<W>	<w>	**upper, alpha, print, graph**
<X>	<x>	**upper, alpha, print, graph**
<Y>	<y>	**upper, alpha, print, graph**
<Z>	<z>	**upper, alpha, print, graph**
<left-square-bracket>		**punct, print, graph**
<backslash>		**punct, print, graph**
<right-square-bracket>		**punct, print, graph**

Symbolic Name	Other Case	Character Classes
<circumflex>		**punct, print, graph**
<underscore>		**punct, print, graph**
<grave-accent>		**punct, print, graph**
<a>	<A>	**lower, xdigit, alpha, print, graph**
<b>	<B>	**lower, xdigit, alpha, print, graph**
<c>	<C>	**lower, xdigit, alpha, print, graph**
<d>	<D>	**lower, xdigit, alpha, print, graph**
<e>	<E>	**lower, xdigit, alpha, print, graph**
<f>	<F>	**lower, xdigit, alpha, print, graph**
<g>	<G>	**lower, alpha, print, graph**
<h>	<H>	**lower, alpha, print, graph**
<i>	<I>	**lower, alpha, print, graph**
<j>	<J>	**lower, alpha, print, graph**
<k>	<K>	**lower, alpha, print, graph**
<l>	<L>	**lower, alpha, print, graph**
<m>	<M>	**lower, alpha, print, graph**
<n>	<N>	**lower, alpha, print, graph**
<o>	<O>	**lower, alpha, print, graph**
<p>	<P>	**lower, alpha, print, graph**
<q>	<Q>	**lower, alpha, print, graph**
<r>	<R>	**lower, alpha, print, graph**
<s>	<S>	**lower, alpha, print, graph**
<t>	<T>	**lower, alpha, print, graph**
<u>	<U>	**lower, alpha, print, graph**
<v>	<V>	**lower, alpha, print, graph**
<w>	<W>	**lower, alpha, print, graph**
<x>	<X>	**lower, alpha, print, graph**
<y>	<Y>	**lower, alpha, print, graph**
<z>	<Z>	**lower, alpha, print, graph**
<left-curly-bracket>		**punct, print, graph**
<vertical-line>		**punct, print, graph**
<right-curly-bracket>		**punct, print, graph**
<tilde>		**punct, print, graph**
<DEL>		**cntrl**

7.3.2 LC_COLLATE

The *LC_COLLATE* category provides a collation sequence definition for numerous utilities in the Shell and Utilities volume of IEEE Std 1003.1-2001 (*sort*, *uniq*, and so on), regular expression matching (see Chapter 9 (on page 169)), and the *strcoll*( ), *strxfrm*( ), *wcscoll*( ), and *wcsxfrm*( ) functions in the System Interfaces volume of IEEE Std 1003.1-2001.

A collation sequence definition shall define the relative order between collating elements (characters and multi-character collating elements) in the locale. This order is expressed in terms of collation values; that is, by assigning each element one or more collation values (also known as collation weights). This does not imply that implementations shall assign such values, but that ordering of strings using the resultant collation definition in the locale behaves as if such assignment is done and used in the collation process. At least the following capabilities are provided:

1. **Multi-character collating elements**. Specification of multi-character collating elements (that is, sequences of two or more characters to be collated as an entity).

2. **User-defined ordering of collating elements**. Each collating element shall be assigned a collation value defining its order in the character (or basic) collation sequence. This ordering is used by regular expressions and pattern matching and, unless collation weights are explicitly specified, also as the collation weight to be used in sorting.
3. **Multiple weights and equivalence classes**. Collating elements can be assigned one or more (up to the limit {COLL_WEIGHTS_MAX}, as defined in **<limits.h>**) collating weights for use in sorting. The first weight is hereafter referred to as the primary weight.
4. **One-to-many mapping**. A single character is mapped into a string of collating elements.
5. **Equivalence class definition**. Two or more collating elements have the same collation value (primary weight).
6. **Ordering by weights**. When two strings are compared to determine their relative order, the two strings are first broken up into a series of collating elements; the elements in each successive pair of elements are then compared according to the relative primary weights for the elements. If equal, and more than one weight has been assigned, then the pairs of collating elements are re-compared according to the relative subsequent weights, until either a pair of collating elements compare unequal or the weights are exhausted.

The following keywords shall be recognized in a collation sequence definition. They are described in detail in the following sections.

copy	Specify the name of an existing locale which shall be used as the definition of this category. If this keyword is specified, no other keyword shall be specified.
collating-element	Define a collating-element symbol representing a multi-character collating element. This keyword is optional.
collating-symbol	Define a collating symbol for use in collation order statements. This keyword is optional.
order_start	Define collation rules. This statement shall be followed by one or more collation order statements, assigning character collation values and collation weights to collating elements.
order_end	Specify the end of the collation-order statements.

7.3.2.1 The collating-element Keyword

In addition to the collating elements in the character set, the **collating-element** keyword can be used to define multi-character collating elements. The syntax is as follows:

```
"collating-element %s from \"%s\"\n", <collating-symbol>, <string>
```

The <*collating-symbol*> operand shall be a symbolic name, enclosed between angle brackets (`'<'` and `'>'`), and shall not duplicate any symbolic name in the current charmap file (if any), or any other symbolic name defined in this collation definition. The string operand is a string of two or more characters that collates as an entity. A <*collating-element*> defined via this keyword is only recognized with the *LC_COLLATE* category.

For example:

```
collating-element <ch> from "<c><h>"
collating-element <e-acute> from "<acute><e>"
collating-element <ll> from "ll"
```


4492 *7.3.2.2 The collating-symbol Keyword*

4493 This keyword shall be used to define symbols for use in collation sequence statements; that is,
4494 between the **order_start** and the **order_end** keywords. The syntax is as follows:

4495 `"collating-symbol %s\n", <collating-symbol>`

4496 The <*collating-symbol*> shall be a symbolic name, enclosed between angle brackets (`'<'` and
4497 `'>'`), and shall not duplicate any symbolic name in the current charmap file (if any), or any
4498 other symbolic name defined in this collation definition. A <*collating-symbol*> defined via this
4499 keyword is only recognized within the *LC_COLLATE* category.

4500 For example:

4501 `collating-symbol <UPPER_CASE>`
4502 `collating-symbol <HIGH>`

4503 The **collating-symbol** keyword defines a symbolic name that can be associated with a relative
4504 position in the character order sequence. While such a symbolic name does not represent any
4505 collating element, it can be used as a weight.

4506 *7.3.2.3 The order_start Keyword*

4507 The **order_start** keyword shall precede collation order entries and also define the number of
4508 weights for this collation sequence definition and other collation rules. The syntax is as follows:

4509 `"order_start %s;%s;...;%s\n", <sort-rules>, <sort-rules> ...`

4510 The operands to the **order_start** keyword are optional. If present, the operands define rules to be
4511 applied when strings are compared. The number of operands define how many weights each
4512 element is assigned; if no operands are present, one **forward** operand is assumed. If present, the
4513 first operand defines rules to be applied when comparing strings using the first (primary)
4514 weight; the second when comparing strings using the second weight, and so on. Operands shall
4515 be separated by semicolons (`';'`). Each operand shall consist of one or more collation
4516 directives, separated by commas (`','`). If the number of operands exceeds the
4517 {COLL_WEIGHTS_MAX} limit, the utility shall issue a warning message. The following
4518 directives shall be supported:

4519 **forward** Specifies that comparison operations for the weight level shall proceed from start
4520 of string towards the end of string.

4521 **backward** Specifies that comparison operations for the weight level shall proceed from end of
4522 string towards the beginning of string.

4523 **position** Specifies that comparison operations for the weight level shall consider the relative
4524 position of elements in the strings not subject to **IGNORE**. The string containing
4525 an element not subject to **IGNORE** after the fewest collating elements subject to
4526 **IGNORE** from the start of the compare shall collate first. If both strings contain a
4527 character not subject to **IGNORE** in the same relative position, the collating values
4528 assigned to the elements shall determine the ordering. In case of equality,
4529 subsequent characters not subject to **IGNORE** shall be considered in the same
4530 manner.

4531 The directives **forward** and **backward** are mutually-exclusive.

4532 If no operands are specified, a single **forward** operand shall be assumed.

For example:

```
order_start    forward;backward
```

7.3.2.4 Collation Order

The **order_start** keyword shall be followed by collating identifier entries. The syntax for the collating element entries is as follows:

```
"%s %s;%s;...;%s\n", <collating-identifier>, <weight>, <weight>, ...
```

Each *collating-identifier* shall consist of either a character (in any of the forms defined in Section 7.3 (on page 124)), a <*collating-element*>, a <*collating-symbol*>, an ellipsis, or the special symbol **UNDEFINED**. The order in which collating elements are specified determines the character order sequence, such that each collating element shall compare less than the elements following it.

A <*collating-element*> shall be used to specify multi-character collating elements, and indicates that the character sequence specified via the <*collating-element*> is to be collated as a unit and in the relative order specified by its place.

A <*collating-symbol*> can be used to define a position in the relative order for use in weights. No weights shall be specified with a <*collating-symbol*>.

The ellipsis symbol specifies that a sequence of characters shall collate according to their encoded character values. It shall be interpreted as indicating that all characters with a coded character set value higher than the value of the character in the preceding line, and lower than the coded character set value for the character in the following line, in the current coded character set, shall be placed in the character collation order between the previous and the following character in ascending order according to their coded character set values. An initial ellipsis shall be interpreted as if the preceding line specified the NUL character, and a trailing ellipsis as if the following line specified the highest coded character set value in the current coded character set. An ellipsis shall be treated as invalid if the preceding or following lines do not specify characters in the current coded character set. The use of the ellipsis symbol ties the definition to a specific coded character set and may preclude the definition from being portable between implementations.

The symbol **UNDEFINED** shall be interpreted as including all coded character set values not specified explicitly or via the ellipsis symbol. Such characters shall be inserted in the character collation order at the point indicated by the symbol, and in ascending order according to their coded character set values. If no **UNDEFINED** symbol is specified, and the current coded character set contains characters not specified in this section, the utility shall issue a warning message and place such characters at the end of the character collation order.

The optional operands for each collation-element shall be used to define the primary, secondary, or subsequent weights for the collating element. The first operand specifies the relative primary weight, the second the relative secondary weight, and so on. Two or more collation-elements can be assigned the same weight; they belong to the same ‘‘equivalence class’’ if they have the same primary weight. Collation shall behave as if, for each weight level, elements subject to **IGNORE** are removed, unless the **position** collation directive is specified for the corresponding level with the **order_start** keyword. Then each successive pair of elements shall be compared according to the relative weights for the elements. If the two strings compare equal, the process shall be repeated for the next weight level, up to the limit {COLL_WEIGHTS_MAX}.

Weights shall be expressed as characters (in any of the forms specified in Section 7.3 (on page 124)), <*collating-symbol*>s, <*collating-element*>s, an ellipsis, or the special symbol **IGNORE**. A single character, a <*collating-symbol*>, or a <*collating-element*> shall represent the relative position

in the character collating sequence of the character or symbol, rather than the character or characters themselves. Thus, rather than assigning absolute values to weights, a particular weight is expressed using the relative order value assigned to a collating element based on its order in the character collation sequence.

One-to-many mapping is indicated by specifying two or more concatenated characters or symbolic names. For example, if the <eszet> is given the string `"<s><s>"` as a weight, comparisons are performed as if all occurrences of the <eszet> are replaced by `"<s><s>"` (assuming that `"<s>"` has the collating weight `"<s>"`). If it is necessary to define <eszet> and `"<s><s>"` as an equivalence class, then a collating element must be defined for the string `"ss"`.

All characters specified via an ellipsis shall by default be assigned unique weights, equal to the relative order of characters. Characters specified via an explicit or implicit **UNDEFINED** special symbol shall by default be assigned the same primary weight (that is, they belong to the same equivalence class). An ellipsis symbol as a weight shall be interpreted to mean that each character in the sequence shall have unique weights, equal to the relative order of their character in the character collation sequence. The use of the ellipsis as a weight shall be treated as an error if the collating element is neither an ellipsis nor the special symbol **UNDEFINED**.

The special keyword **IGNORE** as a weight shall indicate that when strings are compared using the weights at the level where **IGNORE** is specified, the collating element shall be ignored; that is, as if the string did not contain the collating element. In regular expressions and pattern matching, all characters that are subject to **IGNORE** in their primary weight form an equivalence class.

An empty operand shall be interpreted as the collating element itself.

For example, the order statement:

```
<a>     <a>;<a>
```

is equal to:

```
<a>
```

An ellipsis can be used as an operand if the collating element was an ellipsis, and shall be interpreted as the value of each character defined by the ellipsis.

The collation order as defined in this section affects the interpretation of bracket expressions in regular expressions (see Section 9.3.5 (on page 172)).

For example:


```
order_start  forward;backward
UNDEFINED    IGNORE;IGNORE
<LOW>
<space>      <LOW>;<space>
...          <LOW>;...
<a>          <a>;<a>
<a-acute>    <a>;<a-acute>
<a-grave>    <a>;<a-grave>
<A>          <a>;<A>
<A-acute>    <a>;<A-acute>
<A-grave>    <a>;<A-grave>
<ch>         <ch>;<ch>
<Ch>         <ch>;<Ch>
<s>          <s>;<s>
<eszet>      "<s><s>";"<eszet><eszet>"
order_end
```

This example is interpreted as follows:

1. The **UNDEFINED** means that all characters not specified in this definition (explicitly or via the ellipsis) shall be ignored for collation purposes.
2. All characters between <space> and `'a'` shall have the same primary equivalence class and individual secondary weights based on their ordinal encoded values.
3. All characters based on the uppercase or lowercase character `'a'` belong to the same primary equivalence class.
4. The multi-character collating element <ch> is represented by the collating symbol <ch> and belongs to the same primary equivalence class as the multi-character collating element <Ch>.

7.3.2.5 The order_end Keyword

The collating order entries shall be terminated with an **order_end** keyword.

7.3.2.6 LC_COLLATE Category in the POSIX Locale

The collation sequence definition of the POSIX locale follows; the code listing depicts the *localedef* input.

```
LC_COLLATE
# This is the POSIX locale definition for the LC_COLLATE category.
# The order is the same as in the ASCII codeset.
order_start forward
<NUL>
<SOH>
<STX>
<ETX>
<EOT>
<ENQ>
<ACK>
<alert>
<backspace>
<tab>
<newline>
```



```
        <vertical-tab>
        <form-feed>
        <carriage-return>
        <SO>
        <SI>
        <DLE>
        <DC1>
        <DC2>
        <DC3>
        <DC4>
        <NAK>
        <SYN>
        <ETB>
        <CAN>
        <EM>
        <SUB>
        <ESC>
        <IS4>
        <IS3>
        <IS2>
        <IS1>
        <space>
        <exclamation-mark>
        <quotation-mark>
        <number-sign>
        <dollar-sign>
        <percent-sign>
        <ampersand>
        <apostrophe>
        <left-parenthesis>
        <right-parenthesis>
        <asterisk>
        <plus-sign>
        <comma>
        <hyphen>
        <period>
        <slash>
        <zero>
        <one>
        <two>
        <three>
        <four>
        <five>
        <six>
        <seven>
        <eight>
        <nine>
        <colon>
        <semicolon>
        <less-than-sign>
        <equals-sign>
        <greater-than-sign>
```



```
        <question-mark>
        <commercial-at>
        <A>
        <B>
        <C>
        <D>
        <E>
        <F>
        <G>
        <H>
        <I>
        <J>
        <K>
        <L>
        <M>
        <N>
        <O>
        <P>
        <Q>
        <R>
        <S>
        <T>
        <U>
        <V>
        <W>
        <X>
        <Y>
        <Z>
        <left-square-bracket>
        <backslash>
        <right-square-bracket>
        <circumflex>
        <underscore>
        <grave-accent>
        <a>
        <b>
        <c>
        <d>
        <e>
        <f>
        <g>
        <h>
        <i>
        <j>
        <k>
        <l>
        <m>
        <n>
        <o>
        <p>
        <q>
        <r>
```



```
<s>
<t>
<u>
<v>
<w>
<x>
<y>
<z>
<left-curly-bracket>
<vertical-line>
<right-curly-bracket>
<tilde>
<DEL>
order_end
#
END LC_COLLATE
```

7.3.3 LC_MONETARY

The *LC_MONETARY* category shall define the rules and symbols that are used to format monetary numeric information.

XSI This information is available through the *localeconv*( ) function and is used by the *strfmon*( ) function.

XSI Some of the information is also available in an alternative form via the *nl_langinfo*( ) function (see CRNCYSTR in **<langinfo.h>**).

The following items are defined in this category of the locale. The item names are the keywords recognized by the *localedef* utility when defining a locale. They are also similar to the member names of the **lconv** structure defined in **<locale.h>**; see **<locale.h>** for the exact symbols in the header. The *localeconv*( ) function returns {CHAR_MAX} for unspecified integer items and the empty string ("") for unspecified or size zero string items.

In a locale definition file, the operands are strings, formatted as indicated by the grammar in Section 7.4 (on page 153). For some keywords, the strings can contain only integers. Keywords that are not provided, string values set to the empty string (""), or integer keywords set to –1, are used to indicate that the value is not available in the locale. The following keywords shall be recognized:

copy Specify the name of an existing locale which shall be used as the definition of this category. If this keyword is specified, no other keyword shall be specified.

Note: This is a *localedef* utility keyword, unavailable through *localeconv*( ).

int_curr_symbol The international currency symbol. The operand shall be a four-character string, with the first three characters containing the alphabetic international currency symbol. The international currency symbol should be chosen in accordance with those specified in the ISO 4217 standard. The fourth character shall be the character used to separate the international currency symbol from the monetary quantity.

currency_symbol The string that shall be used as the local currency symbol.

mon_decimal_point The operand is a string containing the symbol that shall be used as the decimal delimiter (radix character) in monetary formatted quantities.

mon_thousands_sep The operand is a string containing the symbol that shall be used as a separator for groups of digits to the left of the decimal delimiter in formatted monetary quantities.

mon_grouping Define the size of each group of digits in formatted monetary quantities. The operand is a sequence of integers separated by semicolons. Each integer specifies the number of digits in each group, with the initial integer defining the size of the group immediately preceding the decimal delimiter, and the following integers defining the preceding groups. If the last integer is not –1, then the size of the previous group (if any) shall be repeatedly used for the remainder of the digits. If the last integer is –1, then no further grouping shall be performed.

positive_sign A string that shall be used to indicate a non-negative-valued formatted monetary quantity.

negative_sign A string that shall be used to indicate a negative-valued formatted monetary quantity.

int_frac_digits An integer representing the number of fractional digits (those to the right of the decimal delimiter) to be written in a formatted monetary quantity using **int_curr_symbol**.

frac_digits An integer representing the number of fractional digits (those to the right of the decimal delimiter) to be written in a formatted monetary quantity using **currency_symbol**.

p_cs_precedes An integer set to 1 if the **currency_symbol** precedes the value for a monetary quantity with a non-negative value, and set to 0 if the symbol succeeds the value.

p_sep_by_space Set to a value indicating the separation of the **currency_symbol**, the sign string, and the value for a non-negative formatted monetary quantity. 2 2

The values of **p_sep_by_space**, **n_sep_by_space**, **int_p_sep_by_space**, and **int_n_sep_by_space** are interpreted according to the following: 2 2

0 No space separates the currency symbol and value. 2

1 If the currency symbol and sign string are adjacent, a space separates them from the value; otherwise, a space separates the currency symbol from the value. 2 2 2

2 If the currency symbol and sign string are adjacent, a space separates them; otherwise, a space separates the sign string from the value. 2 2

n_cs_precedes An integer set to 1 if the **currency_symbol** precedes the value for a monetary quantity with a negative value, and set to 0 if the symbol succeeds the value.

n_sep_by_space Set to a value indicating the separation of the **currency_symbol**, the sign string, and the value for a negative formatted monetary quantity. 2 2

p_sign_posn An integer set to a value indicating the positioning of the **positive_sign** for a monetary quantity with a non-negative value. The following integer values shall be recognized for **int_n_sign_posn**, **int_p_sign_posn**, **n_sign_posn**, and **p_sign_posn**:

0 Parentheses enclose the quantity and the **currency_symbol**.

1 The sign string precedes the quantity and the **currency_symbol**.

2 The sign string succeeds the quantity and the **currency_symbol**.

3 The sign string precedes the **currency_symbol**.

4 The sign string succeeds the **currency_symbol**.

n_sign_posn An integer set to a value indicating the positioning of the **negative_sign** for a negative formatted monetary quantity.

int_p_cs_precedes An integer set to 1 if the **int_curr_symbol** precedes the value for a monetary quantity with a non-negative value, and set to 0 if the symbol succeeds the value.

int_n_cs_precedes An integer set to 1 if the **int_curr_symbol** precedes the value for a monetary quantity with a negative value, and set to 0 if the symbol succeeds the value.

int_p_sep_by_space Set to a value indicating the separation of the **int_curr_symbol**, the sign string, and the value for a non-negative internationally formatted monetary quantity. 2

int_n_sep_by_space Set to a value indicating the separation of the **int_curr_symbol**, the sign string, and the value for a negative internationally formatted monetary quantity. 2

int_p_sign_posn An integer set to a value indicating the positioning of the **positive_sign** for a positive monetary quantity formatted with the international format.

int_n_sign_posn An integer set to a value indicating the positioning of the **negative_sign** for a negative monetary quantity formatted with the international format.

7.3.3.1 LC_MONETARY Category in the POSIX Locale

The monetary formatting definitions for the POSIX locale follow; the code listing depicting the XSI *localedef* input, the table representing the same information with the addition of *localeconv*() and *nl_langinfo*() formats. All values are unspecified in the POSIX locale.

```
LC_MONETARY
# This is the POSIX locale definition for
# the LC_MONETARY category.
#
int_curr_symbol      ""
currency_symbol      ""
mon_decimal_point    ""
mon_thousands_sep    ""
mon_grouping         -1
positive_sign        ""
negative_sign        ""
int_frac_digits      -1
frac_digits          -1
p_cs_precedes        -1
p_sep_by_space       -1
n_cs_precedes        -1
n_sep_by_space       -1
p_sign_posn          -1
n_sign_posn          -1
```



```
int_p_cs_precedes    -1                                          1
int_p_sep_by_space   -1                                          1
int_n_cs_precedes    -1                                          1
int_n_sep_by_space   -1                                          1
int_p_sign_posn      -1                                          1
int_n_sign_posn      -1                                          1
#
END LC_MONETARY
```

Item	langinfo Constant	POSIX Locale Value	localeconv() Value	localedef Value	
int_curr_symbol	—	N/A	""	""	
currency_symbol	CRNCYSTR	N/A	""	""	
mon_decimal_point	—	N/A	""	""	
mon_thousands_sep	—	N/A	""	""	
mon_grouping	—	N/A	""	–1	
positive_sign	—	N/A	""	""	
negative_sign	—	N/A	""	""	
int_frac_digits	—	N/A	{CHAR_MAX}	–1	
frac_digits	—	N/A	{CHAR_MAX}	–1	
p_cs_precedes	CRNCYSTR	N/A	{CHAR_MAX}	–1	
p_sep_by_space	—	N/A	{CHAR_MAX}	–1	
n_cs_precedes	CRNCYSTR	N/A	{CHAR_MAX}	–1	
n_sep_by_space	—	N/A	{CHAR_MAX}	–1	
p_sign_posn	—	N/A	{CHAR_MAX}	–1	
n_sign_posn	—	N/A	{CHAR_MAX}	–1	
int_p_cs_precedes	—	N/A	{CHAR_MAX}	–1	1
int_p_sep_by_space	—	N/A	{CHAR_MAX}	–1	1
int_n_cs_precedes	—	N/A	{CHAR_MAX}	–1	1
int_n_sep_by_space	—	N/A	{CHAR_MAX}	–1	1
int_p_sign_posn	—	N/A	{CHAR_MAX}	–1	1
int_n_sign_posn	—	N/A	{CHAR_MAX}	–1	1

XSI In the preceding table, the **langinfo Constant** column represents an XSI-conformant extension. The entry N/A indicates that the value is not available in the POSIX locale.

7.3.4 LC_NUMERIC

The *LC_NUMERIC* category shall define the rules and symbols that are used to format non-monetary numeric information. This information is available through the *localeconv*( ) function.

XSI Some of the information is also available in an alternative form via the *nl_langinfo*( ) function.

The following items are defined in this category of the locale. The item names are the keywords recognized by the *localedef* utility when defining a locale. They are also similar to the member names of the **lconv** structure defined in **<locale.h>**; see **<locale.h>** for the exact symbols in the header. The *localeconv*( ) function returns {CHAR_MAX} for unspecified integer items and the empty string ("") for unspecified or size zero string items.

In a locale definition file, the operands are strings, formatted as indicated by the grammar in Section 7.4 (on page 153). For some keywords, the strings can only contain integers. Keywords that are not provided, string values set to the empty string (""), or integer keywords set to –1, shall be used to indicate that the value is not available in the locale. The following keywords shall be recognized:

copy Specify the name of an existing locale which shall be used as the definition of this category. If this keyword is specified, no other keyword shall be specified.

Note: This is a *localedef* utility keyword, unavailable through *localeconv*( ).

decimal_point The operand is a string containing the symbol that shall be used as the decimal delimiter (radix character) in numeric, non-monetary formatted quantities. This keyword cannot be omitted and cannot be set to the empty string. In contexts where standards limit the **decimal_point** to a single byte, the result of specifying a multi-byte operand shall be unspecified.

thousands_sep The operand is a string containing the symbol that shall be used as a separator for groups of digits to the left of the decimal delimiter in numeric, non-monetary formatted monetary quantities. In contexts where standards limit the **thousands_sep** to a single byte, the result of specifying a multi-byte operand shall be unspecified.

grouping Define the size of each group of digits in formatted non-monetary quantities. The operand is a sequence of integers separated by semicolons. Each integer specifies the number of digits in each group, with the initial integer defining the size of the group immediately preceding the decimal delimiter, and the following integers defining the preceding groups. If the last integer is not –1, then the size of the previous group (if any) shall be repeatedly used for the remainder of the digits. If the last integer is –1, then no further grouping shall be performed.

7.3.4.1 LC_NUMERIC Category in the POSIX Locale

The non-monetary numeric formatting definitions for the POSIX locale follow; the code listing depicting the *localedef* input, the table representing the same information with the addition of XSI *localeconv*( ) values, and *nl_langinfo*( ) constants.

```
LC_NUMERIC
# This is the POSIX locale definition for
# the LC_NUMERIC category.
#
decimal_point    "<period>"
thousands_sep    ""
grouping         -1
#
END LC_NUMERIC
```

Item	langinfo Constant	POSIX Locale Value	localeconv() Value	localedef Value
decimal_point	RADIXCHAR	"."	"."	.
thousands_sep	THOUSEP	N/A	""	""
grouping	—	N/A	""	–1

XSI In the preceding table, the **langinfo Constant** column represents an XSI-conforming extension. The entry N/A indicates that the value is not available in the POSIX locale.

7.3.5 LC_TIME

The *LC_TIME* category shall define the interpretation of the conversion specifications supported by the *date* utility and shall affect the behavior of the *strftime*( ), *wcsftime*( ), *strptime*( ), and *nl_langinfo*( ) functions. Since the interfaces for C-language access and locale definition differ significantly, they are described separately.

XSI

7.3.5.1 LC_TIME Locale Definition

In a locale definition, the following mandatory keywords shall be recognized:

copy Specify the name of an existing locale which shall be used as the definition of this category. If this keyword is specified, no other keyword shall be specified.

abday Define the abbreviated weekday names, corresponding to the %a conversion specification (conversion specification in the *strftime*( ), *wcsftime*( ), and *strptime*( ) functions). The operand shall consist of seven semicolon-separated strings, each surrounded by double-quotes. The first string shall be the abbreviated name of the day corresponding to Sunday, the second the abbreviated name of the day corresponding to Monday, and so on.

day Define the full weekday names, corresponding to the %A conversion specification. The operand shall consist of seven semicolon-separated strings, each surrounded by double-quotes. The first string is the full name of the day corresponding to Sunday, the second the full name of the day corresponding to Monday, and so on.

abmon Define the abbreviated month names, corresponding to the %b conversion specification. The operand shall consist of twelve semicolon-separated strings, each surrounded by double-quotes. The first string shall be the abbreviated name of the first month of the year (January), the second the abbreviated name of the second month, and so on.

mon Define the full month names, corresponding to the %B conversion specification. The operand shall consist of twelve semicolon-separated strings, each surrounded by double-quotes. The first string shall be the full name of the first month of the year (January), the second the full name of the second month, and so on.

d_t_fmt Define the appropriate date and time representation, corresponding to the %c conversion specification. The operand shall consist of a string containing any combination of characters and conversion specifications. In addition, the string can contain escape sequences defined in the table in Table 5-1 (on page 110) (’\\’, ’\a’, ’\b’, ’\f’, ’\n’, ’\r’, ’\t’, ’\v’).

d_fmt Define the appropriate date representation, corresponding to the %x conversion specification. The operand shall consist of a string containing any combination of characters and conversion specifications. In addition, the string can contain escape sequences defined in Table 5-1 (on page 110).

t_fmt Define the appropriate time representation, corresponding to the %X conversion specification. The operand shall consist of a string containing any combination of characters and conversion specifications. In addition, the string can contain escape sequences defined in Table 5-1 (on page 110).

am_pm Define the appropriate representation of the *ante-meridiem* and *post-meridiem* strings, corresponding to the %p conversion specification. The operand shall consist of two strings, separated by a semicolon, each surrounded by double-

quotes. The first string shall represent the *ante-meridiem* designation, the last string the *post-meridiem* designation.

t_fmt_ampm Define the appropriate time representation in the 12-hour clock format with **am_pm**, corresponding to the %r conversion specification. The operand shall consist of a string and can contain any combination of characters and conversion specifications. If the string is empty, the 12-hour format is not supported in the locale.

era Define how years are counted and displayed for each era in a locale. The operand shall consist of semicolon-separated strings. Each string shall be an era description segment with the format:

direction:*offset*:*start_date*:*end_date*:*era_name*:*era_format*

according to the definitions below. There can be as many era description segments as are necessary to describe the different eras.

Note: The start of an era might not be the earliest point in the era—it may be the latest. For example, the Christian era BC starts on the day before January 1, AD 1, and increases with earlier time.

direction Either a '+' or a '−' character. The '+' character shall indicate that years closer to the *start_date* have lower numbers than those closer to the *end_date*. The '−' character shall indicate that years closer to the *start_date* have higher numbers than those closer to the *end_date*.

offset The number of the year closest to the *start_date* in the era, corresponding to the %Ey conversion specification.

start_date A date in the form *yyyy*/*mm*/*dd*, where *yyyy*, *mm*, and *dd* are the year, month, and day numbers respectively of the start of the era. Years prior to AD 1 shall be represented as negative numbers.

end_date The ending date of the era, in the same format as the *start_date*, or one of the two special values "−*" or "+*". The value "−*" shall indicate that the ending date is the beginning of time. The value "+*" shall indicate that the ending date is the end of time.

era_name A string representing the name of the era, corresponding to the %EC conversion specification.

era_format A string for formatting the year in the era, corresponding to the %EY conversion specification.

era_d_fmt Define the format of the date in alternative era notation, corresponding to the %Ex conversion specification.

era_t_fmt Define the locale's appropriate alternative time format, corresponding to the %EX conversion specification.

era_d_t_fmt Define the locale's appropriate alternative date and time format, corresponding to the %Ec conversion specification.

alt_digits Define alternative symbols for digits, corresponding to the %O modified conversion specification. The operand shall consist of semicolon-separated strings, each surrounded by double-quotes. The first string shall be the alternative symbol corresponding with zero, the second string the symbol

corresponding with one, and so on. Up to 100 alternative symbol strings can be specified. The %O modifier shall indicate that the string corresponding to the value specified via the conversion specification shall be used instead of the value.

7.3.5.2 LC_TIME C-Language Access

XSI This section describes extensions to access information in the *LC_TIME* category using the *nl_langinfo*( ) function. This functionality is dependent on support of the XSI extension (and the rest of this section is not further shaded for this option).

The following constants used to identify items of *langinfo* data can be used as arguments to the *nl_langinfo*( ) function to access information in the *LC_TIME* category. These constants are defined in the **<langinfo.h>** header.

ABDAY_*x* The abbreviated weekday names (for example, Sun), where *x* is a number from 1 to 7.

DAY_*x* The full weekday names (for example, Sunday), where *x* is a number from 1 to 7.

ABMON_*x* The abbreviated month names (for example, Jan), where *x* is a number from 1 to 12.

MON_*x* The full month names (for example, January), where *x* is a number from 1 to 12.

D_T_FMT The appropriate date and time representation.

D_FMT The appropriate date representation.

T_FMT The appropriate time representation.

AM_STR The appropriate ante-meridiem affix.

PM_STR The appropriate post-meridiem affix.

T_FMT_AMPM The appropriate time representation in the 12-hour clock format with AM_STR and PM_STR.

ERA The era description segments, which describe how years are counted and displayed for each era in a locale. Each era description segment shall have the format:

direction:*offset*:*start_date*:*end_date*:*era_name*:*era_format*

according to the definitions below. There can be as many era description segments as are necessary to describe the different eras. Era description segments are separated by semicolons.

direction Either a '+' or a '−' character. The '+' character shall indicate that years closer to the *start_date* have lower numbers than those closer to the *end_date*. The '−' character shall indicate that years closer to the *start_date* have higher numbers than those closer to the *end_date*.

offset The number of the year closest to the *start_date* in the era.

start_date A date in the form *yyyy*/*mm*/*dd*, where *yyyy*, *mm*, and *dd* are the year, month, and day numbers respectively of the start of the era. Years prior to AD 1 shall be represented as negative

numbers.

end_date The ending date of the era, in the same format as the *start_date*, or one of the two special values "−*" or "+*". The value "−*" shall indicate that the ending date is the beginning of time. The value "+*" shall indicate that the ending date is the end of time.

era_name The era, corresponding to the %EC conversion specification.

era_format The format of the year in the era, corresponding to the %EY conversion specification.

ERA_D_FMT The era date format.

ERA_T_FMT The locale's appropriate alternative time format, corresponding to the %EX conversion specification.

ERA_D_T_FMT The locale's appropriate alternative date and time format, corresponding to the %Ec conversion specification.

ALT_DIGITS The alternative symbols for digits, corresponding to the %O conversion specification modifier. The value consists of semicolon-separated symbols. The first is the alternative symbol corresponding to zero, the second is the symbol corresponding to one, and so on. Up to 100 alternative symbols may be specified.

7.3.5.3 LC_TIME Category in the POSIX Locale

The *LC_TIME* category definition of the POSIX locale follows; the code listing depicts the *localedef* input; the table represents the same information with the addition of *localedef* keywords, conversion specifiers used by the *date* utility and the *strftime*( ), *wcsftime*( ), and *strptime*( ) functions, XSI and *nl_langinfo*( ) constants.

```
LC_TIME
# This is the POSIX locale definition for
# the LC_TIME category.
#
# Abbreviated weekday names (%a)
abday      "<S><u><n>";"<M><o><n>";"<T><u><e>";"<W><e><d>";\
           "<T><h><u>";"<F><r><i>";"<S><a><t>"
#
# Full weekday names (%A)
day        "<S><u><n><d><a><y>";"<M><o><n><d><a><y>";\
           "<T><u><e><s><d><a><y>";"<W><e><d><n><e><s><d><a><y>";\
           "<T><h><u><r><s><d><a><y>";"<F><r><i><d><a><y>";\
           "<S><a><t><u><r><d><a><y>"
#
# Abbreviated month names (%b)
abmon      "<J><a><n>";"<F><e><b>";"<M><a><r>";\
           "<A><p><r>";"<M><a><y>";"<J><u><n>";\
           "<J><u><l>";"<A><u><g>";"<S><e><p>";\
           "<O><c><t>";"<N><o><v>";"<D><e><c>"
#
# Full month names (%B)
mon        "<J><a><n><u><a><r><y>";"<F><e><b><r><u><a><r><y>";\
           "<M><a><r><c><h>";"<A><p><r><i><l>";\
           "<M><a><y>";"<J><u><n><e>";\
```



```
                "<J><u><l><y>";"<A><u><g><u><s><t>";\
                "<S><e><p><t><e><m><b><e><r>";"<O><c><t><o><b><e><r>";\
                "<N><o><v><e><m><b><e><r>";"<D><e><c><e><m><b><e><r>"
        #
        # Equivalent of AM/PM (%p)      "AM";"PM"
        am_pm       "<A><M>";"<P><M>"
        #
        # Appropriate date and time representation (%c)
        #    "%a %b %e %H:%M:%S %Y"
        d_t_fmt     "<percent-sign><a><space><percent-sign><b>\
        <space><percent-sign><e><space><percent-sign><H>\
        <colon><percent-sign><M><colon><percent-sign><S>\
        <space><percent-sign><Y>"
        #
        # Appropriate date representation (%x)   "%m/%d/%y"
        d_fmt       "<percent-sign><m><slash><percent-sign><d>\
        <slash><percent-sign><y>"
        #
        # Appropriate time representation (%X)   "%H:%M:%S"
        t_fmt       "<percent-sign><H><colon><percent-sign><M>\
        <colon><percent-sign><S>"
        #
        # Appropriate 12-hour time representation (%r) "%I:%M:%S %p"
        t_fmt_ampm "<percent-sign><I><colon><percent-sign><M><colon>\
        <percent-sign><S><space><percent_sign><p>"
        #
        END LC_TIME
```

localedef Keyword	**langinfo Constant**	**Conversion Specification**	**POSIX Locale Value**
d_t_fmt	D_T_FMT	%c	"%a %b %e %H:%M:%S %Y"
d_fmt	D_FMT	%x	"%m/%d/%y"
t_fmt	T_FMT	%X	"%H:%M:%S"
am_pm	AM_STR	%p	"AM"
am_pm	PM_STR	%p	"PM"
t_fmt_ampm	T_FMT_AMPM	%r	"%I:%M:%S %p"
day	DAY_1	%A	"Sunday"
day	DAY_2	%A	"Monday"
day	DAY_3	%A	"Tuesday"
day	DAY_4	%A	"Wednesday"
day	DAY_5	%A	"Thursday"
day	DAY_6	%A	"Friday"
day	DAY_7	%A	"Saturday"
abday	ABDAY_1	%a	"Sun"
abday	ABDAY_2	%a	"Mon"
abday	ABDAY_3	%a	"Tue"
abday	ABDAY_4	%a	"Wed"
abday	ABDAY_5	%a	"Thu"

localedef Keyword	langinfo Constant	Conversion Specification	POSIX Locale Value
abday	ABDAY_6	%a	"Fri"
abday	ABDAY_7	%a	"Sat"
mon	MON_1	%B	"January"
mon	MON_2	%B	"February"
mon	MON_3	%B	"March"
mon	MON_4	%B	"April"
mon	MON_5	%B	"May"
mon	MON_6	%B	"June"
mon	MON_7	%B	"July"
mon	MON_8	%B	"August"
mon	MON_9	%B	"September"
mon	MON_10	%B	"October"
mon	MON_11	%B	"November"
mon	MON_12	%B	"December"
abmon	ABMON_1	%b	"Jan"
abmon	ABMON_2	%b	"Feb"
abmon	ABMON_3	%b	"Mar"
abmon	ABMON_4	%b	"Apr"
abmon	ABMON_5	%b	"May"
abmon	ABMON_6	%b	"Jun"
abmon	ABMON_7	%b	"Jul"
abmon	ABMON_8	%b	"Aug"
abmon	ABMON_9	%b	"Sep"
abmon	ABMON_10	%b	"Oct"
abmon	ABMON_11	%b	"Nov"
abmon	ABMON_12	%b	"Dec"
era	ERA	%EC, %Ey, %EY	N/A
era_d_fmt	ERA_D_FMT	%Ex	N/A
era_t_fmt	ERA_T_FMT	%EX	N/A
era_d_t_fmt	ERA_D_T_FMT	%Ec	N/A
alt_digits	ALT_DIGITS	%O	N/A

XSI In the preceding table, the **langinfo Constant** column represents an XSI-conformant extension.

The entry N/A indicates the value is not available in the POSIX locale.

7.3.6 LC_MESSAGES

The *LC_MESSAGES* category shall define the format and values used by various utilities for XSI affirmative and negative responses. This information is available through the *nl_langinfo*() function.

XSI The message catalog used by the standard utilities and selected by the *catopen*() function shall be determined by the setting of *NLSPATH*; see Chapter 8 (on page 161). The *LC_MESSAGES* category can be specified as part of an *NLSPATH* substitution field.

The following keywords shall be recognized as part of the locale definition file.

copy Specify the name of an existing locale which shall be used as the definition of this category. If this keyword is specified, no other keyword shall be specified.

Note: This is a *localedef* keyword, unavailable through *nl_langinfo*().

yesexpr The operand consists of an extended regular expression (see Section 9.4 (on page 175)) that describes the acceptable affirmative response to a question expecting an affirmative or negative response.

noexpr The operand consists of an extended regular expression that describes the acceptable negative response to a question expecting an affirmative or negative response.

7.3.6.1 *LC_MESSAGES Category in the POSIX Locale*

The format and values for affirmative and negative responses of the POSIX locale follow; the code listing depicting the *localedef* input, the table representing the same information with the addition of *nl_langinfo*( ) constants.

XSI

```
LC_MESSAGES
# This is the POSIX locale definition for
# the LC_MESSAGES category.
#
yesexpr "<circumflex><left-square-bracket><y><Y><right-square-bracket>"
#
noexpr  "<circumflex><left-square-bracket><n><N><right-square-bracket>"
#
END LC_MESSAGES
```

localedef Keyword	langinfo Constant	POSIX Locale Value
yesexpr	YESEXPR	"^[yY]"
noexpr	NOEXPR	"^[nN]"

In the preceding table, the **langinfo Constant** column represents an XSI-conformant extension.

XSI

7.4 Locale Definition Grammar

The grammar and lexical conventions in this section shall together describe the syntax for the locale definition source. The general conventions for this style of grammar are described in the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 1.10, Grammar Conventions. The grammar shall take precedence over the text in this chapter.

7.4.1 Locale Lexical Conventions

The lexical conventions for the locale definition grammar are described in this section.

The following tokens shall be processed (in addition to those string constants shown in the grammar):

LOC_NAME A string of characters representing the name of a locale.

CHAR Any single character.

NUMBER A decimal number, represented by one or more decimal digits.

COLLSYMBOL A symbolic name, enclosed between angle brackets. The string cannot duplicate any charmap symbol defined in the current charmap (if any), or a **COLLELEMENT** symbol.

COLLELEMENT A symbolic name, enclosed between angle brackets, which cannot duplicate either any charmap symbol or a **COLLSYMBOL** symbol.

CHARCLASS A string of alphanumeric characters from the portable character set, the first of which is not a digit, consisting of at least one and at most {CHARCLASS_NAME_MAX} bytes, and optionally surrounded by double-quotes.

CHARSYMBOL A symbolic name, enclosed between angle brackets, from the current charmap (if any).

OCTAL_CHAR One or more octal representations of the encoding of each byte in a single character. The octal representation consists of an escape character (normally a backslash) followed by two or more octal digits.

HEX_CHAR One or more hexadecimal representations of the encoding of each byte in a single character. The hexadecimal representation consists of an escape character followed by the constant *x* and two or more hexadecimal digits.

DECIMAL_CHAR One or more decimal representations of the encoding of each byte in a single character. The decimal representation consists of an escape character followed by a character `'d'` and two or more decimal digits.

ELLIPSIS The string `"..."`.

EXTENDED_REG_EXP An extended regular expression as defined in the grammar in Section 9.5 (on page 179).

EOL The line termination character <newline>.

7.4.2 Locale Grammar

This section presents the grammar for the locale definition.

```
%token              LOC_NAME
%token              CHAR
%token              NUMBER
%token              COLLSYMBOL COLLELEMENT
%token              CHARSYMBOL OCTAL_CHAR HEX_CHAR DECIMAL_CHAR
%token              ELLIPSIS
%token              EXTENDED_REG_EXP
%token              EOL

%start              locale_definition

%%

locale_definition   : global_statements locale_categories
                    |                   locale_categories
                    ;

global_statements   : global_statements symbol_redefine
                    | symbol_redefine
                    ;

symbol_redefine     : 'escape_char'  CHAR EOL
                    | 'comment_char' CHAR EOL
                    ;
```



```
5341        locale_categories   : locale_categories locale_category
5342                            | locale_category
5343                            ;
5344        locale_category     : lc_ctype | lc_collate | lc_messages
5345                            | lc_monetary | lc_numeric | lc_time
5346                            ;
5347        /* The following grammar rules are common to all categories */
5348        char_list           : char_list char_symbol
5349                            | char_symbol
5350                            ;
5351        char_symbol         : CHAR | CHARSYMBOL
5352                            | OCTAL_CHAR | HEX_CHAR | DECIMAL_CHAR
5353                            ;
5354        elem_list           : elem_list char_symbol
5355                            | elem_list COLLSYMBOL
5356                            | elem_list COLLELEMENT
5357                            | char_symbol
5358                            | COLLSYMBOL
5359                            | COLLELEMENT
5360                            ;
5361        symb_list           : symb_list COLLSYMBOL
5362                            | COLLSYMBOL
5363                            ;
5364        locale_name         : LOC_NAME
5365                            | '"' LOC_NAME '"'
5366                            ;
5367        /* The following is the LC_CTYPE category grammar */
5368        lc_ctype            : ctype_hdr ctype_keywords         ctype_tlr
5369                            | ctype_hdr 'copy' locale_name EOL ctype_tlr
5370                            ;
5371        ctype_hdr           : 'LC_CTYPE' EOL
5372                            ;
5373        ctype_keywords      : ctype_keywords ctype_keyword
5374                            | ctype_keyword
5375                            ;
5376        ctype_keyword       : charclass_keyword charclass_list EOL
5377                            | charconv_keyword charconv_list EOL
5378                            | 'charclass' charclass_namelist EOL
5379                            ;
5380        charclass_namelist  : charclass_namelist ';' CHARCLASS
5381                            | CHARCLASS
5382                            ;
5383        charclass_keyword   : 'upper' | 'lower' | 'alpha' | 'digit'
5384                            | 'punct' | 'xdigit' | 'space' | 'print'
5385                            | 'graph' | 'blank' | 'cntrl' | 'alnum'
```



```
                        | CHARCLASS
                        ;

charclass_list          : charclass_list ';' char_symbol
                        | charclass_list ';' ELLIPSIS ';' char_symbol
                        | char_symbol
                        ;

charconv_keyword        : 'toupper'
                        | 'tolower'
                        ;

charconv_list           : charconv_list ';' charconv_entry
                        | charconv_entry
                        ;

charconv_entry          : '(' char_symbol ',' char_symbol ')'
                        ;

ctype_tlr               : 'END' 'LC_CTYPE' EOL
                        ;

/* The following is the LC_COLLATE category grammar */

lc_collate              : collate_hdr collate_keywords       collate_tlr
                        | collate_hdr 'copy' locale_name EOL collate_tlr
                        ;

collate_hdr             : 'LC_COLLATE' EOL
                        ;

collate_keywords        :                order_statements
                        | opt_statements order_statements
                        ;

opt_statements          : opt_statements collating_symbols
                        | opt_statements collating_elements
                        | collating_symbols
                        | collating_elements
                        ;

collating_symbols       : 'collating-symbol' COLLSYMBOL EOL
                        ;

collating_elements      : 'collating-element' COLLELEMENT
                        | 'from' '"' elem_list '"' EOL
                        ;

order_statements        : order_start collation_order order_end
                        ;

order_start             : 'order_start' EOL
                        | 'order_start' order_opts EOL
                        ;

order_opts              : order_opts ';' order_opt
                        | order_opt
                        ;
```

```
order_opt           : order_opt ',' opt_word
                    | opt_word
                    ;

opt_word            : 'forward' | 'backward' | 'position'
                    ;

collation_order     : collation_order collation_entry
                    | collation_entry
                    ;

collation_entry     : COLLSYMBOL EOL
                    | collation_element weight_list EOL
                    | collation_element             EOL
                    ;

collation_element   : char_symbol
                    | COLLELEMENT
                    | ELLIPSIS
                    | 'UNDEFINED'
                    ;

weight_list         : weight_list ';' weight_symbol
                    | weight_list ';'
                    | weight_symbol
                    ;

weight_symbol       : /* empty */
                    | char_symbol
                    | COLLSYMBOL
                    | '"' elem_list '"'
                    | '"' symb_list '"'
                    | ELLIPSIS
                    | 'IGNORE'
                    ;

order_end           : 'order_end' EOL
                    ;

collate_tlr         : 'END' 'LC_COLLATE' EOL
                    ;

/* The following is the LC_MESSAGES category grammar */

lc_messages         : messages_hdr messages_keywords      messages_tlr
                    | messages_hdr 'copy' locale_name EOL messages_tlr
                    ;

messages_hdr        : 'LC_MESSAGES' EOL
                    ;

messages_keywords   : messages_keywords messages_keyword
                    | messages_keyword
                    ;

messages_keyword    : 'yesexpr' '"' EXTENDED_REG_EXP '"' EOL
                    | 'noexpr'  '"' EXTENDED_REG_EXP '"' EOL
                    ;
```



```
messages_tlr        : 'END' 'LC_MESSAGES' EOL
                    ;
/* The following is the LC_MONETARY category grammar */
lc_monetary         : monetary_hdr monetary_keywords       monetary_tlr
                    | monetary_hdr 'copy' locale_name EOL  monetary_tlr
                    ;
monetary_hdr        : 'LC_MONETARY' EOL
                    ;
monetary_keywords   : monetary_keywords monetary_keyword
                    | monetary_keyword
                    ;
monetary_keyword    : mon_keyword_string mon_string EOL
                    | mon_keyword_char NUMBER EOL
                    | mon_keyword_char '-1'   EOL
                    | mon_keyword_grouping mon_group_list EOL
                    ;
mon_keyword_string  : 'int_curr_symbol' | 'currency_symbol'
                    | 'mon_decimal_point' | 'mon_thousands_sep'
                    | 'positive_sign' | 'negative_sign'
                    ;
mon_string          : '"' char_list '"'
                    | '""'
                    ;
mon_keyword_char    : 'int_frac_digits' | 'frac_digits'
                    | 'p_cs_precedes' | 'p_sep_by_space'
                    | 'n_cs_precedes' | 'n_sep_by_space'
                    | 'p_sign_posn' | 'n_sign_posn'
                    | 'int_p_cs_precedes' | 'int_p_sep_by_space'         1
                    | 'int_n_cs_precedes' | 'int_n_sep_by_space'         1
                    | 'int_p_sign_posn' | 'int_n_sign_posn'              1
                    ;                                                    1
mon_keyword_grouping : 'mon_grouping'
                    ;
mon_group_list      : NUMBER
                    | mon_group_list ';' NUMBER
                    ;
monetary_tlr        : 'END' 'LC_MONETARY' EOL
                    ;
/* The following is the LC_NUMERIC category grammar */
lc_numeric          : numeric_hdr numeric_keywords       numeric_tlr
                    | numeric_hdr 'copy' locale_name EOL numeric_tlr
                    ;
numeric_hdr         : 'LC_NUMERIC' EOL
                    ;
```

```
numeric_keywords    : numeric_keywords numeric_keyword
                    | numeric_keyword
                    ;

numeric_keyword     : num_keyword_string num_string EOL
                    | num_keyword_grouping num_group_list EOL
                    ;

num_keyword_string  : 'decimal_point'
                    | 'thousands_sep'
                    ;

num_string          : '"' char_list '"'
                    | '""'
                    ;

num_keyword_grouping: 'grouping'
                    ;

num_group_list      : NUMBER
                    | num_group_list ';' NUMBER
                    ;

numeric_tlr         : 'END' 'LC_NUMERIC' EOL
                    ;

/* The following is the LC_TIME category grammar */

lc_time             : time_hdr time_keywords          time_tlr
                    | time_hdr 'copy' locale_name EOL time_tlr
                    ;

time_hdr            : 'LC_TIME' EOL
                    ;

time_keywords       : time_keywords time_keyword
                    | time_keyword
                    ;

time_keyword        : time_keyword_name time_list EOL
                    | time_keyword_fmt time_string EOL
                    | time_keyword_opt time_list EOL
                    ;

time_keyword_name   : 'abday' | 'day' | 'abmon' | 'mon'
                    ;

time_keyword_fmt    : 'd_t_fmt' | 'd_fmt' | 't_fmt'
                    | 'am_pm' | 't_fmt_ampm'
                    ;

time_keyword_opt    : 'era' | 'era_d_fmt' | 'era_t_fmt'
                    | 'era_d_t_fmt' | 'alt_digits'
                    ;

time_list           : time_list ';' time_string
                    | time_string
                    ;
```



```
5561        time_string         : '"' char_list '"'
5562                            ;
5563        time_tlr            : 'END' 'LC_TIME' EOL
5564                            ;
```

Chapter 8

Environment Variables

8.1 Environment Variable Definition

Environment variables defined in this chapter affect the operation of multiple utilities, functions, and applications. There are other environment variables that are of interest only to specific utilities. Environment variables that apply to a single utility only are defined as part of the utility description. See the ENVIRONMENT VARIABLES section of the utility descriptions in the Shell and Utilities volume of IEEE Std 1003.1-2001 for information on environment variable usage.

The value of an environment variable is a string of characters. For a C-language program, an array of strings called the environment shall be made available when a process begins. The array is pointed to by the external variable *environ*, which is defined as:

```
extern char **environ;
```

These strings have the form *name*=*value*; *name*s shall not contain the character '='. For values to be portable across systems conforming to IEEE Std 1003.1-2001, the value shall be composed of characters from the portable character set (except NUL and as indicated below). There is no meaning associated with the order of strings in the environment. If more than one string in a process' environment has the same *name*, the consequences are undefined.

Environment variable names used by the utilities in the Shell and Utilities volume of IEEE Std 1003.1-2001 consist solely of uppercase letters, digits, and the '_' (underscore) from the characters defined in Table 6-1 (on page 113) and do not begin with a digit. Other characters may be permitted by an implementation; applications shall tolerate the presence of such names. Uppercase and lowercase letters shall retain their unique identities and shall not be folded together. The name space of environment variable names containing lowercase letters is reserved for applications. Applications can define any environment variables with names from this name space without modifying the behavior of the standard utilities.

Note: Other applications may have difficulty dealing with environment variable names that start with a digit. For this reason, use of such names is not recommended anywhere.

The *values* that the environment variables may be assigned are not restricted except that they are considered to end with a null byte and the total space used to store the environment and the arguments to the process is limited to {ARG_MAX} bytes.

Other *name*=*value* pairs may be placed in the environment by, for example, calling any of the XSI *setenv*(), *unsetenv*(), or *putenv*() functions, manipulating the *environ* variable, or by using *envp* arguments when creating a process; see *exec* in the System Interfaces volume of IEEE Std 1003.1-2001.

It is unwise to conflict with certain variables that are frequently exported by widely used command interpreters and applications:

ARFLAGS	*IFS*	*MAILPATH*	*PS1*
CC	*LANG*	*MAILRC*	*PS2*
CDPATH	*LC_ALL*	*MAKEFLAGS*	*PS3*
CFLAGS	*LC_COLLATE*	*MAKESHELL*	*PS4*
CHARSET	*LC_CTYPE*	*MANPATH*	*PWD*
COLUMNS	*LC_MESSAGES*	*MBOX*	*RANDOM*
DATEMSK	*LC_MONETARY*	*MORE*	*SECONDS*
DEAD	*LC_NUMERIC*	*MSGVERB*	*SHELL*
EDITOR	*LC_TIME*	*NLSPATH*	*TERM*
ENV	*LDFLAGS*	*NPROC*	*TERMCAP*
EXINIT	*LEX*	*OLDPWD*	*TERMINFO*
FC	*LFLAGS*	*OPTARG*	*TMPDIR*
FCEDIT	*LINENO*	*OPTERR*	*TZ*
FFLAGS	*LINES*	*OPTIND*	*USER*
GET	*LISTER*	*PAGER*	*VISUAL*
GFLAGS	*LOGNAME*	*PATH*	*YACC*
HISTFILE	*LPDEST*	*PPID*	*YFLAGS*
HISTORY	*MAIL*	*PRINTER*	
HISTSIZE	*MAILCHECK*	*PROCLANG*	
HOME	*MAILER*	*PROJECTDIR*	

If the variables in the following two sections are present in the environment during the execution of an application or utility, they shall be given the meaning described below. Some are placed into the environment by the implementation at the time the user logs in; all can be added or changed by the user or any ancestor of the current process. The implementation adds or changes environment variables named in IEEE Std 1003.1-2001 only as specified in IEEE Std 1003.1-2001. If they are defined in the application's environment, the utilities in the Shell and Utilities volume of IEEE Std 1003.1-2001 and the functions in the System Interfaces volume of IEEE Std 1003.1-2001 assume they have the specified meaning. Conforming applications shall not set these environment variables to have meanings other than as described. See *getenv*( ) and the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.12, Shell Execution Environment for methods of accessing these variables.

8.2 Internationalization Variables

This section describes environment variables that are relevant to the operation of internationalized interfaces described in IEEE Std 1003.1-2001.

Users may use the following environment variables to announce specific localization requirements to applications. Applications can retrieve this information using the *setlocale*( ) function to initialize the correct behavior of the internationalized interfaces. The descriptions of the internationalization environment variables describe the resulting behavior only when the application locale is initialized in this way. The use of the internationalization variables by utilities described in the Shell and Utilities volume of IEEE Std 1003.1-2001 is described in the ENVIRONMENT VARIABLES section for those utilities in addition to the global effects described in this section.

LANG This variable shall determine the locale category for native language, local customs, and coded character set in the absence of the *LC_ALL* and other *LC_** (*LC_COLLATE*, *LC_CTYPE*, *LC_MESSAGES*, *LC_MONETARY*, *LC_NUMERIC*, *LC_TIME*) environment variables. This can be used by applications to determine the language to use for error messages and instructions, collating sequences, date formats, and so on.

LC_ALL This variable shall determine the values for all locale categories. The value of the *LC_ALL* environment variable has precedence over any of the other environment variables starting with *LC_* (*LC_COLLATE*, *LC_CTYPE*, *LC_MESSAGES*, *LC_MONETARY*, *LC_NUMERIC*, *LC_TIME*) and the *LANG* environment variable.

LC_COLLATE This variable shall determine the locale category for character collation. It determines collation information for regular expressions and sorting, including equivalence classes and multi-character collating elements, in various utilities and the *strcoll*( ) and *strxfrm*( ) functions. Additional semantics of this variable, if any, are implementation-defined.

LC_CTYPE This variable shall determine the locale category for character handling functions, such as *tolower*( ), *toupper*( ), and *isalpha*( ). This environment variable determines the interpretation of sequences of bytes of text data as characters (for example, single as opposed to multi-byte characters), the classification of characters (for example, alpha, digit, graph), and the behavior of character classes. Additional semantics of this variable, if any, are implementation-defined.

LC_MESSAGES This variable shall determine the locale category for processing affirmative and negative responses and the language and cultural conventions in which XSI messages should be written. It also affects the behavior of the *catopen*( ) function in determining the message catalog. Additional semantics of this variable, if any, are implementation-defined. The language and cultural conventions of diagnostic and informative messages whose format is unspecified by IEEE Std 1003.1-2001 should be affected by the setting of *LC_MESSAGES*.

LC_MONETARY This variable shall determine the locale category for monetary-related numeric formatting information. Additional semantics of this variable, if any, are implementation-defined.

LC_NUMERIC This variable shall determine the locale category for numeric formatting (for example, thousands separator and radix character) information in various utilities as well as the formatted I/O operations in *printf*( ) and *scanf*( ) and the string conversion functions in *strtod*( ). Additional semantics of this variable, if any, are implementation-defined.

LC_TIME This variable shall determine the locale category for date and time formatting information. It affects the behavior of the time functions in *strftime*( ). Additional semantics of this variable, if any, are implementation-defined.

XSI *NLSPATH* This variable shall contain a sequence of templates that the *catopen*( ) function uses when attempting to locate message catalogs. Each template consists of an optional prefix, one or more conversion specifications, a filename, and an optional suffix.

For example:

```
NLSPATH="/system/nlslib/%N.cat"
```

defines that *catopen*( ) should look for all message catalogs in the directory **/system/nlslib**, where the catalog name should be constructed from the *name* parameter passed to *catopen*( ) (%N), with the suffix **.cat**.

Conversion specifications consist of a '%' symbol, followed by a single-letter keyword. The following keywords are currently defined:

5696 `%N` The value of the *name* parameter passed to *catopen*( ).

5697 `%L` The value of the *LC_MESSAGES* category.

5698 `%l` The *language* element from the *LC_MESSAGES* category.

5699 `%t` The *territory* element from the *LC_MESSAGES* category.

5700 `%c` The *codeset* element from the *LC_MESSAGES* category.

5701 `%%` A single `'%'` character.

5702 An empty string is substituted if the specified value is not currently defined.
5703 The separators underscore (`'_'`) and period (`'.'`) are not included in the `%t`
5704 and `%c` conversion specifications.

5705 Templates defined in *NLSPATH* are separated by colons (`':'`). A leading or
5706 two adjacent colons `"::"` is equivalent to specifying `%N`. For example:

5707 ```
NLSPATH=":%N.cat:/nlslib/%L/%N.cat"
```

5708 indicates to *catopen*( ) that it should look for the requested message catalog in
5709 *name*, *name***.cat**, and **/nlslib/***category*/*name***.cat**, where *category* is the value of the
5710 *LC_MESSAGES* category of the current locale.

5711 Users should not set the *NLSPATH* variable unless they have a specific reason
5712 to override the default system path. Setting *NLSPATH* to override the default
5713 system path produces undefined results in the standard utilities and in
5714 applications with appropriate privileges.

5715 The environment variables *LANG*, *LC_ALL*, *LC_COLLATE*, *LC_CTYPE*, *LC_MESSAGES*,
5716 XSI *LC_MONETARY*, *LC_NUMERIC*, *LC_TIME*, and *NLSPATH* provide for the support of
5717 internationalized applications. The standard utilities shall make use of these environment
5718 variables as described in this section and the individual ENVIRONMENT VARIABLES sections
5719 for the utilities. If these variables specify locale categories that are not based upon the same
5720 underlying codeset, the results are unspecified.

5721 The values of locale categories shall be determined by a precedence order; the first condition met
5722 below determines the value:

5723 1. If the *LC_ALL* environment variable is defined and is not null, the value of *LC_ALL* shall be
5724 used.

5725 2. If the *LC_** environment variable (*LC_COLLATE*, *LC_CTYPE*, *LC_MESSAGES*,
5726 *LC_MONETARY*, *LC_NUMERIC*, *LC_TIME*) is defined and is not null, the value of the
5727 environment variable shall be used to initialize the category that corresponds to the
5728 environment variable.

5729 3. If the *LANG* environment variable is defined and is not null, the value of the *LANG*
5730 environment variable shall be used.

5731 4. If the *LANG* environment variable is not set or is set to the empty string, the
5732 implementation-defined default locale shall be used.

5733 If the locale value is `"C"` or `"POSIX"`, the POSIX locale shall be used and the standard utilities
5734 behave in accordance with the rules in Section 7.2 (on page 124) for the associated category.

5735 If the locale value begins with a slash, it shall be interpreted as the pathname of a file that was
5736 created in the output format used by the *localedef* utility; see OUTPUT FILES under *localedef*.
5737 Referencing such a pathname shall result in that locale being used for the indicated category.
```

5738 XSI If the locale value has the form:

5739 ***language*[_*territory*][.*codeset*]**

5740 it refers to an implementation-provided locale, where settings of language, territory, and codeset
5741 are implementation-defined.

5742 *LC_COLLATE*, *LC_CTYPE*, *LC_MESSAGES*, *LC_MONETARY*, *LC_NUMERIC*, and *LC_TIME* are
5743 defined to accept an additional field *@modifier*, which allows the user to select a specific instance
5744 of localization data within a single category (for example, for selecting the dictionary as opposed
5745 to the character ordering of data). The syntax for these environment variables is thus defined as:

5746 **[*language*[_*territory*][.*codeset*][@*modifier*]]**

5747 For example, if a user wanted to interact with the system in French, but required to sort German
5748 text files, *LANG* and *LC_COLLATE* could be defined as:

```
5749    LANG=Fr_FR
5750    LC_COLLATE=De_DE
```

5751 This could be extended to select dictionary collation (say) by use of the *@modifier* field; for
5752 example:

```
5753    LC_COLLATE=De_DE@dict
```

5754

5755 An implementation may support other formats.

5756 If the locale value is not recognized by the implementation, the behavior is unspecified.

5757 At runtime, these values are bound to a program's locale by calling the *setlocale*( ) function.

5758 Additional criteria for determining a valid locale name are implementation-defined.

5759 8.3 Other Environment Variables

5760 *COLUMNS* This variable shall represent a decimal integer >0 used to indicate the user's
5761 preferred width in column positions for the terminal screen or window; see
5762 Section 3.103 (on page 49). If this variable is unset or null, the implementation
5763 determines the number of columns, appropriate for the terminal or window,
5764 in an unspecified manner. When *COLUMNS* is set, any terminal-width
5765 information implied by *TERM* is overridden. Users and conforming
5766 applications should not set *COLUMNS* unless they wish to override the
5767 system selection and produce output unrelated to the terminal characteristics.

5768 Users should not need to set this variable in the environment unless there is a
5769 specific reason to override the implementation's default behavior, such as to
5770 display data in an area arbitrarily smaller than the terminal or window.

5771 XSI *DATEMSK* Indicates the pathname of the template file used by *getdate*( ).

5772 *HOME* The system shall initialize this variable at the time of login to be a pathname of
5773 the user's home directory. See **<pwd.h>**.

5774 *LINES* This variable shall represent a decimal integer >0 used to indicate the user's
5775 preferred number of lines on a page or the vertical screen or window size in
5776 lines. A line in this case is a vertical measure large enough to hold the tallest
5777 character in the character set being displayed. If this variable is unset or null,
5778 the implementation determines the number of lines, appropriate for the

terminal or window (size, terminal baud rate, and so on), in an unspecified manner. When *LINES* is set, any terminal-height information implied by *TERM* is overridden. Users and conforming applications should not set *LINES* unless they wish to override the system selection and produce output unrelated to the terminal characteristics.

Users should not need to set this variable in the environment unless there is a specific reason to override the implementation's default behavior, such as to display data in an area arbitrarily smaller than the terminal or window.

LOGNAME The system shall initialize this variable at the time of login to be the user's login name. See **<pwd.h>**. For a value of *LOGNAME* to be portable across implementations of IEEE Std 1003.1-2001, the value should be composed of characters from the portable filename character set.

XSI *MSGVERB* Describes which message components shall be used in writing messages by *fmtmsg*( ).

PATH This variable shall represent the sequence of path prefixes that certain functions and utilities apply in searching for an executable file known only by a filename. The prefixes shall be separated by a colon (':'). When a non-zero-length prefix is applied to this filename, a slash shall be inserted between the prefix and the filename. A zero-length prefix is a legacy feature that indicates the current working directory. It appears as two adjacent colons ("::"), as an initial colon preceding the rest of the list, or as a trailing colon following the rest of the list. A strictly conforming application shall use an actual pathname (such as **.**) to represent the current working directory in *PATH*. The list shall be searched from beginning to end, applying the filename to each prefix, until an executable file with the specified name and appropriate execution permissions is found. If the pathname being sought contains a slash, the search through the path prefixes shall not be performed. If the pathname begins with a slash, the specified path is resolved (see Section 4.11 (on page 100)). If *PATH* is unset or is set to null, the path search is implementation-defined.

PWD This variable shall represent an absolute pathname of the current working directory. It shall not contain any filename components of dot or dot-dot. The value is set by the *cd* utility.

SHELL This variable shall represent a pathname of the user's preferred command language interpreter. If this interpreter does not conform to the Shell Command Language in the Shell and Utilities volume of IEEE Std 1003.1-2001, Chapter 2, Shell Command Language, utilities may behave differently from those described in IEEE Std 1003.1-2001.

TMPDIR This variable shall represent a pathname of a directory made available for programs that need a place to create temporary files.

TERM This variable shall represent the terminal type for which output is to be prepared. This information is used by utilities and application programs wishing to exploit special capabilities specific to a terminal. The format and allowable values of this environment variable are unspecified.

TZ This variable shall represent timezone information. The contents of the environment variable named *TZ* shall be used by the *ctime*( ), *localtime*( ), TSF *strftime*( ), *mktime*( ), *ctime_r*( ), and *localtime_r*( ) functions, and by various utilities, to override the default timezone. The value of *TZ* has one of the two 1

forms (spaces inserted for clarity):

```
:characters
```

or:

```
std offset dst offset, rule
```

If *TZ* is of the first format (that is, if the first character is a colon), the characters following the colon are handled in an implementation-defined manner.

The expanded format (for all *TZ*s whose value does not have a colon as the first character) is as follows:

```
stdoffset[dst[offset][,start[/time],end[/time]]]
```

Where:

std and *dst* Indicate no less than three, nor more than {TZNAME_MAX}, bytes that are the designation for the standard (*std*) or the alternative (*dst*—such as Daylight Savings Time) timezone. Only *std* is required; if *dst* is missing, then the alternative time does not apply in this locale.

Each of these fields may occur in either of two formats quoted or unquoted:

— In the quoted form, the first character shall be the less-than (`'<'`) character and the last character shall be the greater-than (`'>'`) character. All characters between these quoting characters shall be alphanumeric characters from the portable character set in the current locale, the plus-sign (`'+'`) character, or the minus-sign (`'−'`) character. The *std* and *dst* fields in this case shall not include the quoting characters.

— In the unquoted form, all characters in these fields shall be alphabetic characters from the portable character set in the current locale.

The interpretation of these fields is unspecified if either field is less than three bytes (except for the case when *dst* is missing), more than {TZNAME_MAX} bytes, or if they contain characters other than those specified.

offset Indicates the value added to the local time to arrive at Coordinated Universal Time. The *offset* has the form:

```
hh[:mm[:ss]]
```

The minutes (*mm*) and seconds (*ss*) are optional. The hour (*hh*) shall be required and may be a single digit. The *offset* following *std* shall be required. If no *offset* follows *dst*, the alternative time is assumed to be one hour ahead of standard time. One or more digits may be used; the value is always interpreted as a decimal number. The hour shall be between zero and 24, and the minutes (and seconds)—if present—between zero and 59. The result of using values outside of this range is unspecified. If preceded by a `'−'`, the timezone shall be east of the Prime Meridian;

otherwise, it shall be west (which may be indicated by an optional preceding '+').

rule Indicates when to change to and back from the alternative time. The *rule* has the form:

date[/*time*],*date*[/*time*]

where the first *date* describes when the change from standard to alternative time occurs and the second *date* describes when the change back happens. Each *time* field describes when, in current local time, the change to the other time is made.

The format of *date* is one of the following:

J*n* The Julian day *n* ($1 \le n \le 365$). Leap days shall not be counted. That is, in all years—including leap years—February 28 is day 59 and March 1 is day 60. It is impossible to refer explicitly to the occasional February 29.

n The zero-based Julian day ($0 \le n \le 365$). Leap days shall be counted, and it is possible to refer to February 29.

M*m.n.d* The *d*'th day ($0 \le d \le 6$) of week *n* of month *m* of the year ($1 \le n \le 5$, $1 \le m \le 12$, where week 5 means ''the last *d* day in month *m*'' which may occur in either the fourth or the fifth week). Week 1 is the first week in which the *d*'th day occurs. Day zero is Sunday.

The *time* has the same format as *offset* except that no leading sign ('−' or '+') is allowed. The default, if *time* is not given, shall be 02:00:00.

Chapter 9

Regular Expressions

Regular Expressions (REs) provide a mechanism to select specific strings from a set of character strings.

Regular expressions are a context-independent syntax that can represent a wide variety of character sets and character set orderings, where these character sets are interpreted according to the current locale. While many regular expressions can be interpreted differently depending on the current locale, many features, such as character class expressions, provide for contextual invariance across locales.

The Basic Regular Expression (BRE) notation and construction rules in Section 9.3 (on page 171) shall apply to most utilities supporting regular expressions. Some utilities, instead, support the Extended Regular Expressions (ERE) described in Section 9.4 (on page 175); any exceptions for both cases are noted in the descriptions of the specific utilities using regular expressions. Both BREs and EREs are supported by the Regular Expression Matching interface in the System Interfaces volume of IEEE Std 1003.1-2001 under *regcomp*( ), *regexec*( ), and related functions.

9.1 Regular Expression Definitions

For the purposes of this section, the following definitions shall apply:

entire regular expression
The concatenated set of one or more BREs or EREs that make up the pattern specified for string selection.

matched
A sequence of zero or more characters shall be said to be matched by a BRE or ERE when the characters in the sequence correspond to a sequence of characters defined by the pattern.

Matching shall be based on the bit pattern used for encoding the character, not on the graphic representation of the character. This means that if a character set contains two or more encodings for a graphic symbol, or if the strings searched contain text encoded in more than one codeset, no attempt is made to search for any other representation of the encoded symbol. If that is required, the user can specify equivalence classes containing all variations of the desired graphic symbol.

The search for a matching sequence starts at the beginning of a string and stops when the first sequence matching the expression is found, where ‘‘first’’ is defined to mean ‘‘begins earliest in the string’’. If the pattern permits a variable number of matching characters and thus there is more than one such sequence starting at that point, the longest such sequence is matched. For example, the BRE `"bb*"` matches the second to fourth characters of the string `"abbbc"`, and the ERE `"(wee|week)(knights|night)"` matches all ten characters of the string `"weeknights"`.

Consistent with the whole match being the longest of the leftmost matches, each subpattern, from left to right, shall match the longest possible string. For this purpose, a null string shall be considered to be longer than no match at all. For example, matching the BRE `"\(.*\).*"` against `"abcdef"`, the subexpression `"(\1)"` is `"abcdef"`, and matching the BRE `"\(a*\)*"` against `"bc"`, the subexpression `"(\1)"` is the null string.

When a multi-character collating element in a bracket expression (see Section 9.3.5 (on page 172)) is involved, the longest sequence shall be measured in characters consumed from the string to be matched; that is, the collating element counts not as one element, but as the number of characters it matches.

BRE (ERE) matching a single character
A BRE or ERE that shall match either a single character or a single collating element.

Only a BRE or ERE of this type that includes a bracket expression (see Section 9.3.5 (on page 172)) can match a collating element.

BRE (ERE) matching multiple characters
A BRE or ERE that shall match a concatenation of single characters or collating elements.

Such a BRE or ERE is made up from a BRE (ERE) matching a single character and BRE (ERE) special characters.

invalid
This section uses the term ‘‘invalid’’ for certain constructs or conditions. Invalid REs shall cause the utility or function using the RE to generate an error condition. When invalid is not used, violations of the specified syntax or semantics for REs produce undefined results: this may entail an error, enabling an extended syntax for that RE, or using the construct in error as literal characters to be matched. For example, the BRE construct `"\{1,2,3\}"` does not comply with the grammar. A conforming application cannot rely on it producing an error nor matching the literal characters `"\{1,2,3\}"`.

9.2 Regular Expression General Requirements

The requirements in this section shall apply to both basic and extended regular expressions.

The use of regular expressions is generally associated with text processing. REs (BREs and EREs) operate on text strings; that is, zero or more characters followed by an end-of-string delimiter (typically NUL). Some utilities employing regular expressions limit the processing to lines; that is, zero or more characters followed by a <newline>. In the regular expression processing described in IEEE Std 1003.1-2001, the <newline> is regarded as an ordinary character and both a period and a non-matching list can match one. The Shell and Utilities volume of IEEE Std 1003.1-2001 specifies within the individual descriptions of those standard utilities employing regular expressions whether they permit matching of <newline>s; if not stated otherwise, the use of literal <newline>s or any escape sequence equivalent produces undefined results. Those utilities (like *grep*) that do not allow <newline>s to match are responsible for eliminating any <newline> from strings before matching against the RE. The *regcomp*( ) function in the System Interfaces volume of IEEE Std 1003.1-2001, however, can provide support for such processing without violating the rules of this section.

The interfaces specified in IEEE Std 1003.1-2001 do not permit the inclusion of a NUL character in an RE or in the string to be matched. If during the operation of a standard utility a NUL is included in the text designated to be matched, that NUL may designate the end of the text string for the purposes of matching.

When a standard utility or function that uses regular expressions specifies that pattern matching shall be performed without regard to the case (uppercase or lowercase) of either data or patterns, then when each character in the string is matched against the pattern, not only the character, but also its case counterpart (if any), shall be matched. This definition of case-insensitive processing is intended to allow matching of multi-character collating elements as well as characters, as each character in the string is matched using both its cases. For example, in

a locale where "Ch" is a multi-character collating element and where a matching list expression matches such elements, the RE "[[.Ch.]]" when matched against the string "char" is in reality matched against "ch", "Ch", "cH", and "CH".

The implementation shall support any regular expression that does not exceed 256 bytes in length.

9.3 Basic Regular Expressions

9.3.1 BREs Matching a Single Character or Collating Element

A BRE ordinary character, a special character preceded by a backslash, or a period shall match a single character. A bracket expression shall match a single character or a single collating element.

9.3.2 BRE Ordinary Characters

An ordinary character is a BRE that matches itself: any character in the supported character set, except for the BRE special characters listed in Section 9.3.3.

The interpretation of an ordinary character preceded by a backslash ('\') is undefined, except for:

- The characters ')', '(', '{', and '}'
- The digits 1 to 9 inclusive (see Section 9.3.6 (on page 174))
- A character inside a bracket expression

9.3.3 BRE Special Characters

A BRE special character has special properties in certain contexts. Outside those contexts, or when preceded by a backslash, such a character is a BRE that matches the special character itself. The BRE special characters and the contexts in which they have their special meaning are as follows:

. [\ The period, left-bracket, and backslash shall be special except when used in a bracket expression (see Section 9.3.5 (on page 172)). An expression containing a '[' that is not preceded by a backslash and is not part of a bracket expression produces undefined results.

* The asterisk shall be special except when used:

- In a bracket expression
- As the first character of an entire BRE (after an initial '^', if any)
- As the first character of a subexpression (after an initial '^', if any); see Section 9.3.6 (on page 174)

^ The circumflex shall be special when used as:

- An anchor (see Section 9.3.8 (on page 175))
- The first character of a bracket expression (see Section 9.3.5 (on page 172))

$ The dollar sign shall be special when used as an anchor.

9.3.4 Periods in BREs

A period (`'.'`), when used outside a bracket expression, is a BRE that shall match any character in the supported character set except NUL.

9.3.5 RE Bracket Expression

A bracket expression (an expression enclosed in square brackets, `"[ ]"`) is an RE that shall match a single collating element contained in the non-empty set of collating elements represented by the bracket expression.

The following rules and definitions apply to bracket expressions:

1. A bracket expression is either a matching list expression or a non-matching list expression. It consists of one or more expressions: collating elements, collating symbols, equivalence classes, character classes, or range expressions. The right-bracket (`']'`) shall lose its special meaning and represent itself in a bracket expression if it occurs first in the list (after an initial circumflex (`'^'`), if any). Otherwise, it shall terminate the bracket expression, unless it appears in a collating symbol (such as `"[.].]"`) or is the ending right-bracket for a collating symbol, equivalence class, or character class. The special characters `'.'`, `'*'`, `'['`, and `'\'` (period, asterisk, left-bracket, and backslash, respectively) shall lose their special meaning within a bracket expression.

   The character sequences `"[."`, `"[="`, and `"[:"` (left-bracket followed by a period, equals-sign, or colon) shall be special inside a bracket expression and are used to delimit collating symbols, equivalence class expressions, and character class expressions. These symbols shall be followed by a valid expression and the matching terminating sequence `".]"`, `"=]"`, or `":]"`, as described in the following items.

2. A matching list expression specifies a list that shall match any single-character collating element in any of the expressions represented in the list. The first character in the list shall not be the circumflex; for example, `"[abc]"` is an RE that matches any of the characters `'a'`, `'b'`, or `'c'`. It is unspecified whether a matching list expression matches a multi-character collating element that is matched by one of the expressions.

3. A non-matching list expression begins with a circumflex (`'^'`), and specifies a list that shall match any single-character collating element except for the expressions represented in the list after the leading circumflex. For example, `"[^abc]"` is an RE that matches any character except the characters `'a'`, `'b'`, or `'c'`. It is unspecified whether a non-matching list expression matches a multi-character collating element that is not matched by any of the expressions. The circumflex shall have this special meaning only when it occurs first in the list, immediately following the left-bracket.

4. A collating symbol is a collating element enclosed within bracket-period (`"[."` and `".]"`) delimiters. Collating elements are defined as described in Section 7.3.2.4 (on page 137). Conforming applications shall represent multi-character collating elements as collating symbols when it is necessary to distinguish them from a list of the individual characters that make up the multi-character collating element. For example, if the string `"ch"` is a collating element defined using the line:

   ```
   collating-element <ch-digraph> from "<c><h>"
   ```

   in the locale definition, the expression `"[[.ch.]]"` shall be treated as an RE containing the collating symbol `'ch'`, while `"[ch]"` shall be treated as an RE matching `'c'` or `'h'`. Collating symbols are recognized only inside bracket expressions. If the string is not a collating element in the current locale, the expression is invalid.

5. An equivalence class expression shall represent the set of collating elements belonging to an equivalence class, as described in Section 7.3.2.4 (on page 137). Only primary equivalence classes shall be recognized. The class shall be expressed by enclosing any one of the collating elements in the equivalence class within bracket-equal ("[=" and "=]") delimiters. For example, if 'a', 'à', and 'â' belong to the same equivalence class, then "[[=a=]b]", "[[=à=]b]", and "[[=â=]b]" are each equivalent to "[aàâb]". If the collating element does not belong to an equivalence class, the equivalence class expression shall be treated as a collating symbol.

6. A character class expression shall represent the union of two sets:

   a. The set of single-character collating elements whose characters belong to the character class, as defined in the *LC_CTYPE* category in the current locale.

   b. An unspecified set of multi-character collating elements.

   All character classes specified in the current locale shall be recognized. A character class expression is expressed as a character class name enclosed within bracket-colon ("[:" and ":]") delimiters.

   The following character class expressions shall be supported in all locales:

   ```
   [:alnum:]   [:cntrl:]   [:lower:]   [:space:]
   [:alpha:]   [:digit:]   [:print:]   [:upper:]
   [:blank:]   [:graph:]   [:punct:]   [:xdigit:]
   ```

   In addition, character class expressions of the form:

   [:*name*:]

   are recognized in those locales where the *name* keyword has been given a **charclass** definition in the *LC_CTYPE* category.

7. In the POSIX locale, a range expression represents the set of collating elements that fall between two elements in the collation sequence, inclusive. In other locales, a range expression has unspecified behavior: strictly conforming applications shall not rely on whether the range expression is valid, or on the set of collating elements matched. A range expression shall be expressed as the starting point and the ending point separated by a hyphen ('-').

   In the following, all examples assume the POSIX locale.

   The starting range point and the ending range point shall be a collating element or collating symbol. An equivalence class expression used as a starting or ending point of a range expression produces unspecified results. An equivalence class can be used portably within a bracket expression, but only outside the range. If the represented set of collating elements is empty, it is unspecified whether the expression matches nothing, or is treated as invalid.

   The interpretation of range expressions where the ending range point is also the starting range point of a subsequent range expression (for example, "[a-m-o]") is undefined.

   The hyphen character shall be treated as itself if it occurs first (after an initial '^', if any) or last in the list, or as an ending range point in a range expression. As examples, the expressions "[-ac]" and "[ac-]" are equivalent and match any of the characters 'a', 'c', or '-'; "[^-ac]" and "[^ac-]" are equivalent and match any characters except 'a', 'c', or '-'; the expression "[%--]" matches any of the characters between '%' and '-' inclusive; the expression "[--@]" matches any of the characters between '-' and '@' inclusive; and the expression "[a--@]" is either invalid or equivalent to '@',

because the letter 'a' follows the symbol '–' in the POSIX locale. To use a hyphen as the starting range point, it shall either come first in the bracket expression or be specified as a collating symbol; for example, "[][.-.]-0]", which matches either a right bracket or any character or collating element that collates between hyphen and 0, inclusive.

If a bracket expression specifies both '–' and ']', the ']' shall be placed first (after the '^', if any) and the '–' last within the bracket expression.

9.3.6 BREs Matching Multiple Characters

The following rules can be used to construct BREs matching multiple characters from BREs matching a single character:

1. The concatenation of BREs shall match the concatenation of the strings matched by each component of the BRE.

2. A subexpression can be defined within a BRE by enclosing it between the character pairs "\(" and "\)". Such a subexpression shall match whatever it would have matched without the "\(" and "\)", except that anchoring within subexpressions is optional behavior; see Section 9.3.8 (on page 175). Subexpressions can be arbitrarily nested.

3. The back-reference expression '\n' shall match the same (possibly empty) string of characters as was matched by a subexpression enclosed between "\(" and "\)" preceding the '\n'. The character 'n' shall be a digit from 1 through 9, specifying the *n*th subexpression (the one that begins with the *n*th "\(" from the beginning of the pattern and ends with the corresponding paired "\)"). The expression is invalid if less than *n* subexpressions precede the '\n'. For example, the expression "\(.*\)\1$" matches a line consisting of two adjacent appearances of the same string, and the expression "\(a\)*\1" fails to match 'a'. When the referenced subexpression matched more than one string, the back-referenced expression shall refer to the last matched string. If the subexpression referenced by the back-reference matches more than one string because of an asterisk ('*') or an interval expression (see item (5)), the back-reference shall match the last (rightmost) of these strings.

4. When a BRE matching a single character, a subexpression, or a back-reference is followed by the special character asterisk ('*'), together with that asterisk it shall match what zero or more consecutive occurrences of the BRE would match. For example, "[ab]*" and "[ab][ab]" are equivalent when matching the string "ab".

5. When a BRE matching a single character, a subexpression, or a back-reference is followed by an interval expression of the format "\{m\}", "\{m,\}", or "\{m,n\}", together with that interval expression it shall match what repeated consecutive occurrences of the BRE would match. The values of *m* and *n* are decimal integers in the range $0 \le m \le n \le \{RE\_DUP\_MAX\}$, where *m* specifies the exact or minimum number of occurrences and *n* specifies the maximum number of occurrences. The expression "\{m\}" shall match exactly *m* occurrences of the preceding BRE, "\{m,\}" shall match at least *m* occurrences, and "\{m,n\}" shall match any number of occurrences between *m* and *n*, inclusive.

   For example, in the string "abababccccccd" the BRE "c\{3\}" is matched by characters seven to nine, the BRE "\(ab\)\{4,\}" is not matched at all, and the BRE "c\{1,3\}d" is matched by characters ten to thirteen.

The behavior of multiple adjacent duplication symbols ('*' and intervals) produces undefined results.

A subexpression repeated by an asterisk ('*') or an interval expression shall not match a null expression unless this is the only match for the repetition or it is necessary to satisfy the exact or

minimum number of occurrences for the interval expression.

9.3.7 BRE Precedence

The order of precedence shall be as shown in the following table:

BRE Precedence (from high to low)	
Collation-related bracket symbols	`[==] [::] [..]`
Escaped characters	`\<special character>`
Bracket expression	`[]`
Subexpressions / back-references	`\(\) \n`
Single-character-BRE duplication	`* \{m,n\}`
Concatenation	
Anchoring	`^ $`

9.3.8 BRE Expression Anchoring

A BRE can be limited to matching strings that begin or end a line; this is called ‘‘anchoring’’. The circumflex and dollar sign special characters shall be considered BRE anchors in the following contexts:

1. A circumflex (`'^'`) shall be an anchor when used as the first character of an entire BRE. The implementation may treat the circumflex as an anchor when used as the first character of a subexpression. The circumflex shall anchor the expression (or optionally subexpression) to the beginning of a string; only sequences starting at the first character of a string shall be matched by the BRE. For example, the BRE `"^ab"` matches `"ab"` in the string `"abcdef"`, but fails to match in the string `"cdefab"`. The BRE `"\(^ab\)"` may match the former string. A portable BRE shall escape a leading circumflex in a subexpression to match a literal circumflex.

2. A dollar sign (`'$'`) shall be an anchor when used as the last character of an entire BRE. The implementation may treat a dollar sign as an anchor when used as the last character of a subexpression. The dollar sign shall anchor the expression (or optionally subexpression) to the end of the string being matched; the dollar sign can be said to match the end-of-string following the last character.

3. A BRE anchored by both `'^'` and `'$'` shall match only an entire string. For example, the BRE `"^abcdef$"` matches strings consisting only of `"abcdef"`.

9.4 Extended Regular Expressions

The extended regular expression (ERE) notation and construction rules shall apply to utilities defined as using extended regular expressions; any exceptions to the following rules are noted in the descriptions of the specific utilities using EREs.

9.4.1 EREs Matching a Single Character or Collating Element

An ERE ordinary character, a special character preceded by a backslash, or a period shall match a single character. A bracket expression shall match a single character or a single collating element. An ERE matching a single character enclosed in parentheses shall match the same as the ERE without parentheses would have matched.

9.4.2 ERE Ordinary Characters

An ordinary character is an ERE that matches itself. An ordinary character is any character in the supported character set, except for the ERE special characters listed in Section 9.4.3. The interpretation of an ordinary character preceded by a backslash (`'\'`) is undefined.

9.4.3 ERE Special Characters

An ERE special character has special properties in certain contexts. Outside those contexts, or when preceded by a backslash, such a character shall be an ERE that matches the special character itself. The extended regular expression special characters and the contexts in which they shall have their special meaning are as follows:

`. [ \ (` The period, left-bracket, backslash, and left-parenthesis shall be special except when used in a bracket expression (see Section 9.3.5 (on page 172)). Outside a bracket expression, a left-parenthesis immediately followed by a right-parenthesis produces undefined results.

`)` The right-parenthesis shall be special when matched with a preceding left-parenthesis, both outside a bracket expression.

`* + ? {` The asterisk, plus-sign, question-mark, and left-brace shall be special except when used in a bracket expression (see Section 9.3.5 (on page 172)). Any of the following uses produce undefined results:

- If these characters appear first in an ERE, or immediately following a vertical-line, circumflex, or left-parenthesis
- If a left-brace is not part of a valid interval expression (see Section 9.4.6 (on page 177))

`|` The vertical-line is special except when used in a bracket expression (see Section 9.3.5 (on page 172)). A vertical-line appearing first or last in an ERE, or immediately following a vertical-line or a left-parenthesis, or immediately preceding a right-parenthesis, produces undefined results.

`^` The circumflex shall be special when used as:

- An anchor (see Section 9.4.9 (on page 178))
- The first character of a bracket expression (see Section 9.3.5 (on page 172))

`$` The dollar sign shall be special when used as an anchor.

9.4.4 Periods in EREs

A period (`'.'`), when used outside a bracket expression, is an ERE that shall match any character in the supported character set except NUL.

9.4.5 ERE Bracket Expression

The rules for ERE Bracket Expressions are the same as for Basic Regular Expressions; see Section 9.3.5 (on page 172).

9.4.6 EREs Matching Multiple Characters

The following rules shall be used to construct EREs matching multiple characters from EREs matching a single character:

1. A concatenation of EREs shall match the concatenation of the character sequences matched by each component of the ERE. A concatenation of EREs enclosed in parentheses shall match whatever the concatenation without the parentheses matches. For example, both the ERE `"cd"` and the ERE `"(cd)"` are matched by the third and fourth character of the string `"abcdefabcdef"`.

2. When an ERE matching a single character or an ERE enclosed in parentheses is followed by the special character plus-sign (`'+'`), together with that plus-sign it shall match what one or more consecutive occurrences of the ERE would match. For example, the ERE `"b+(bc)"` matches the fourth to seventh characters in the string `"acabbbcde"`. And, `"[ab]+"` and `"[ab][ab]*"` are equivalent.

3. When an ERE matching a single character or an ERE enclosed in parentheses is followed by the special character asterisk (`'*'`), together with that asterisk it shall match what zero or more consecutive occurrences of the ERE would match. For example, the ERE `"b*c"` matches the first character in the string `"cabbbcde"`, and the ERE `"b*cd"` matches the third to seventh characters in the string `"cabbbcdebbbbbbcdbc"`. And, `"[ab]*"` and `"[ab][ab]"` are equivalent when matching the string `"ab"`.

4. When an ERE matching a single character or an ERE enclosed in parentheses is followed by the special character question-mark (`'?'`), together with that question-mark it shall match what zero or one consecutive occurrences of the ERE would match. For example, the ERE `"b?c"` matches the second character in the string `"acabbbcde"`.

5. When an ERE matching a single character or an ERE enclosed in parentheses is followed by an interval expression of the format `"{m}"`, `"{m,}"`, or `"{m,n}"`, together with that interval expression it shall match what repeated consecutive occurrences of the ERE would match. The values of *m* and *n* are decimal integers in the range $0 \le m \le n \le \{RE\_DUP\_MAX\}$, where *m* specifies the exact or minimum number of occurrences and *n* specifies the maximum number of occurrences. The expression `"{m}"` matches exactly *m* occurrences of the preceding ERE, `"{m,}"` matches at least *m* occurrences, and `"{m,n}"` matches any number of occurrences between *m* and *n*, inclusive.

   For example, in the string `"abababccccccd"` the ERE `"c{3}"` is matched by characters seven to nine and the ERE `"(ab){2,}"` is matched by characters one to six.

The behavior of multiple adjacent duplication symbols (`'+'`, `'*'`, `'?'`, and intervals) produces undefined results.

An ERE matching a single character repeated by an `'*'`, `'?'`, or an interval expression shall not match a null expression unless this is the only match for the repetition or it is necessary to satisfy the exact or minimum number of occurrences for the interval expression.

9.4.7 ERE Alternation

Two EREs separated by the special character vertical-line (`'|'`) shall match a string that is matched by either. For example, the ERE `"a((bc)|d)"` matches the string `"abc"` and the string `"ad"`. Single characters, or expressions matching single characters, separated by the vertical bar and enclosed in parentheses, shall be treated as an ERE matching a single character.

9.4.8 ERE Precedence

The order of precedence shall be as shown in the following table:

ERE Precedence (from high to low)	
Collation-related bracket symbols	`[==] [::] [..]`
Escaped characters	`\<special character>`
Bracket expression	`[]`
Grouping	`()`
Single-character-ERE duplication	`* + ? {m,n}`
Concatenation	
Anchoring	`^ $`
Alternation	`|`

For example, the ERE `"abba|cde"` matches either the string `"abba"` or the string `"cde"` (rather than the string `"abbade"` or `"abbcde"`, because concatenation has a higher order of precedence than alternation).

9.4.9 ERE Expression Anchoring

An ERE can be limited to matching strings that begin or end a line; this is called ‘‘anchoring’’. The circumflex and dollar sign special characters shall be considered ERE anchors when used anywhere outside a bracket expression. This shall have the following effects:

1. A circumflex (`'^'`) outside a bracket expression shall anchor the expression or subexpression it begins to the beginning of a string; such an expression or subexpression can match only a sequence starting at the first character of a string. For example, the EREs `"^ab"` and `"(^ab)"` match `"ab"` in the string `"abcdef"`, but fail to match in the string `"cdefab"`, and the ERE `"a^b"` is valid, but can never match because the `'a'` prevents the expression `"^b"` from matching starting at the first character.

2. A dollar sign (`'$'`) outside a bracket expression shall anchor the expression or subexpression it ends to the end of a string; such an expression or subexpression can match only a sequence ending at the last character of a string. For example, the EREs `"ef$"` and `"(ef$)"` match `"ef"` in the string `"abcdef"`, but fail to match in the string `"cdefab"`, and the ERE `"e$f"` is valid, but can never match because the `'f'` prevents the expression `"e$"` from matching ending at the last character.

9.5 Regular Expression Grammar

Grammars describing the syntax of both basic and extended regular expressions are presented in this section. The grammar takes precedence over the text. See the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 1.10, Grammar Conventions.

9.5.1 BRE/ERE Grammar Lexical Conventions

The lexical conventions for regular expressions are as described in this section.

Except as noted, the longest possible token or delimiter beginning at a given point is recognized.

The following tokens are processed (in addition to those string constants shown in the grammar):

COLL_ELEM_SINGLE
Any single-character collating element, unless it is a **META_CHAR**.

COLL_ELEM_MULTI
Any multi-character collating element.

BACKREF Applicable only to basic regular expressions. The character string consisting of '\' followed by a single-digit numeral, '1' to '9'.

DUP_COUNT Represents a numeric constant. It shall be an integer in the range 0 ≤**DUP_COUNT** ≤{RE_DUP_MAX}. This token is only recognized when the context of the grammar requires it. At all other times, digits not preceded by '\' are treated as **ORD_CHAR**.

META_CHAR One of the characters:

^ When found first in a bracket expression

– When found anywhere but first (after an initial '^', if any) or last in a bracket expression, or as the ending range point in a range expression

] When found anywhere but first (after an initial '^', if any) in a bracket expression

L_ANCHOR Applicable only to basic regular expressions. The character '^' when it appears as the first character of a basic regular expression and when not **QUOTED_CHAR**. The '^' may be recognized as an anchor elsewhere; see Section 9.3.8 (on page 175).

ORD_CHAR A character, other than one of the special characters in **SPEC_CHAR**.

QUOTED_CHAR In a BRE, one of the character sequences:

```
\^    \.    \*    \[    \$    \\
```

In an ERE, one of the character sequences:

```
\^    \.    \[    \$    \(    \)    \|
\*    \+    \?    \{    \\
```

R_ANCHOR (Applicable only to basic regular expressions.) The character '$' when it appears as the last character of a basic regular expression and when not **QUOTED_CHAR**. The '$' may be recognized as an anchor elsewhere; see Section 9.3.8 (on page 175).

SPEC_CHAR For basic regular expressions, one of the following special characters:

`.` Anywhere outside bracket expressions

`\` Anywhere outside bracket expressions

`[` Anywhere outside bracket expressions

`^` When used as an anchor (see Section 9.3.8 (on page 175)) or when first in a bracket expression

`$` When used as an anchor

`*` Anywhere except first in an entire RE, anywhere in a bracket expression, directly following "`\(`", directly following an anchoring '`^`'

For extended regular expressions, shall be one of the following special characters found anywhere outside bracket expressions:

```
^    .    [    $    (    )    |
*    +    ?    {    \
```

(The close-parenthesis shall be considered special in this context only if matched with a preceding open-parenthesis.)

9.5.2 RE and Bracket Expression Grammar

This section presents the grammar for basic regular expressions, including the bracket expression grammar that is common to both BREs and EREs.

```
%token    ORD_CHAR QUOTED_CHAR DUP_COUNT

%token    BACKREF L_ANCHOR R_ANCHOR

%token    Back_open_paren  Back_close_paren
/*          '\('             '\)'        */

%token    Back_open_brace  Back_close_brace
/*          '\{'             '\}'         */

/* The following tokens are for the Bracket Expression
   grammar common to both REs and EREs. */

%token    COLL_ELEM_SINGLE COLL_ELEM_MULTI META_CHAR

%token    Open_equal Equal_close Open_dot Dot_close Open_colon Colon_close
/*          '[='       '=]'        '[.'     '.]'      '[:'       ':]'  */

%token    class_name
/* class_name is a keyword to the LC_CTYPE locale category */
/* (representing a character class) in the current locale */
/* and is only recognized between [: and :] */

%start    basic_reg_exp
%%

/* -------------------------------------------
   Basic Regular Expression
   -------------------------------------------
*/
basic_reg_exp  :          RE_expression
```



```
                    | L_ANCHOR
                    |                       R_ANCHOR
                    | L_ANCHOR              R_ANCHOR
                    | L_ANCHOR RE_expression
                    |          RE_expression R_ANCHOR
                    | L_ANCHOR RE_expression R_ANCHOR
                    ;
RE_expression  :              simple_RE
                    | RE_expression simple_RE
                    ;
simple_RE      : nondupl_RE
                    | nondupl_RE RE_dupl_symbol
                    ;
nondupl_RE     : one_char_or_coll_elem_RE
                    | Back_open_paren RE_expression Back_close_paren
                    | BACKREF
                    ;
one_char_or_coll_elem_RE : ORD_CHAR
                    | QUOTED_CHAR
                    | '.'
                    | bracket_expression
                    ;
RE_dupl_symbol : '*'
                    | Back_open_brace DUP_COUNT              Back_close_brace
                    | Back_open_brace DUP_COUNT ','          Back_close_brace
                    | Back_open_brace DUP_COUNT ',' DUP_COUNT Back_close_brace
                    ;
/* ------------------------------------------
   Bracket Expression
   ------------------------------------------
*/
bracket_expression : '[' matching_list ']'
                    | '[' nonmatching_list ']'
                    ;
matching_list  : bracket_list
                    ;
nonmatching_list : '^' bracket_list
                    ;
bracket_list   : follow_list
                    | follow_list '-'
                    ;
follow_list    :             expression_term
                    | follow_list expression_term
                    ;
expression_term : single_expression
                    | range_expression
                    ;
single_expression : end_range
                    | character_class
                    | equivalence_class
                    ;
range_expression : start_range end_range
```



```
                    | start_range '-'
                    ;
start_range         : end_range '-'
                    ;
end_range           : COLL_ELEM_SINGLE
                    | collating_symbol
                    ;
collating_symbol : Open_dot COLL_ELEM_SINGLE Dot_close
                    | Open_dot COLL_ELEM_MULTI Dot_close
                    | Open_dot META_CHAR Dot_close
                    ;
equivalence_class : Open_equal COLL_ELEM_SINGLE Equal_close
                    | Open_equal COLL_ELEM_MULTI Equal_close
                    ;
character_class : Open_colon class_name Colon_close
                    ;
```

The BRE grammar does not permit **L_ANCHOR** or **R_ANCHOR** inside "\(" and "\)" (which implies that '^' and '$' are ordinary characters). This reflects the semantic limits on the application, as noted in Section 9.3.8 (on page 175). Implementations are permitted to extend the language to interpret '^' and '$' as anchors in these locations, and as such, conforming applications cannot use unescaped '^' and '$' in positions inside "\(" and "\)" that might be interpreted as anchors.

9.5.3 ERE Grammar

This section presents the grammar for extended regular expressions, excluding the bracket expression grammar.

Note: The bracket expression grammar and the associated **%token** lines are identical between BREs and EREs. It has been omitted from the ERE section to avoid unnecessary editorial duplication.

```
%token  ORD_CHAR QUOTED_CHAR DUP_COUNT
%start  extended_reg_exp
%%

/* -------------------------------------------
   Extended Regular Expression
   -------------------------------------------
*/
extended_reg_exp   :                       ERE_branch
                   | extended_reg_exp '|' ERE_branch
                   ;
ERE_branch         :            ERE_expression
                   | ERE_branch ERE_expression
                   ;
ERE_expression     : one_char_or_coll_elem_ERE
                   | '^'
                   | '$'
                   | '(' extended_reg_exp ')'
                   | ERE_expression ERE_dupl_symbol
                   ;
one_char_or_coll_elem_ERE  : ORD_CHAR
                   | QUOTED_CHAR
                   | '.'
```



```
                    | bracket_expression
                    ;
ERE_dupl_symbol     : '*'
                    | '+'
                    | '?'
                    | '{' DUP_COUNT               '}'
                    | '{' DUP_COUNT ','           '}'
                    | '{' DUP_COUNT ',' DUP_COUNT '}'
                    ;
```

The ERE grammar does not permit several constructs that previous sections specify as having undefined results:

- **ORD_CHAR** preceded by '\'
- One or more *ERE_dupl_symbol*s appearing first in an ERE, or immediately following '|', '^', or '('
- '{' not part of a valid *ERE_dupl_symbol*
- '|' appearing first or last in an ERE, or immediately following '|' or '(', or immediately preceding ')'

Implementations are permitted to extend the language to allow these. Conforming applications cannot use such constructs.

6504

Chapter 10

Directory Structure and Devices

10.1 Directory Structure and Files

The following directories shall exist on conforming systems and conforming applications shall make use of them only as described. Strictly conforming applications shall not assume the ability to create files in any of these directories, unless specified below.

/ The root directory.

/dev Contains **/dev/console**, **/dev/null**, and **/dev/tty**, described below.

The following directory shall exist on conforming systems and shall be used as described:

/tmp A directory made available for applications that need a place to create temporary files. Applications shall be allowed to create files in this directory, but shall not assume that such files are preserved between invocations of the application.

The following files shall exist on conforming systems and shall be both readable and writable:

/dev/null An infinite data source and data sink. Data written to **/dev/null** shall be discarded. Reads from **/dev/null** shall always return end-of-file (EOF).

/dev/tty In each process, a synonym for the controlling terminal associated with the process group of that process, if any. It is useful for programs or shell procedures that wish to be sure of writing messages to or reading data from the terminal no matter how output has been redirected. It can also be used for applications that demand the name of a file for output, when typed output is desired and it is tiresome to find out what terminal is currently in use.

The following file shall exist on conforming systems and need not be readable or writable:

/dev/console The **/dev/console** file is a generic name given to the system console (see Section 3.382 (on page 88)). It is usually linked to an implementation-defined special file. It shall provide an interface to the system console conforming to the requirements of the Base Definitions volume of IEEE Std 1003.1-2001, Chapter 11, General Terminal Interface.

10.2 Output Devices and Terminal Types

The utilities in the Shell and Utilities volume of IEEE Std 1003.1-2001 historically have been implemented on a wide range of terminal types, but a conforming implementation need not support all features of all utilities on every conceivable terminal. IEEE Std 1003.1-2001 states which features are optional for certain classes of terminals in the individual utility description sections. The implementation shall document in the system documentation which terminal types it supports and which of these features and utilities are not supported by each terminal. 2 2

When a feature or utility is not supported on a specific terminal type, as allowed by IEEE Std 1003.1-2001, and the implementation considers such a condition to be an error preventing use of the feature or utility, the implementation shall indicate such conditions through diagnostic messages or exit status values or both (as appropriate to the specific utility description) that inform the user that the terminal type lacks the appropriate capability.

IEEE Std 1003.1-2001 uses a notational convention based on historical practice that identifies some of the control characters defined in Section 7.3.1 (on page 126) in a manner easily remembered by users on many terminals. The correspondence between this ''<control>-*char*'' notation and the actual control characters is shown in the following table. When IEEE Std 1003.1-2001 refers to a character by its <control>-*name*, it is referring to the actual control character shown in the Value column of the table, which is not necessarily the exact control key sequence on all terminals. Some terminals have keyboards that do not allow the direct transmission of all the non-alphanumeric characters shown. In such cases, the system documentation shall describe which data sequences transmitted by the terminal are interpreted by the system as representing the special characters.

Table 10-1 Control Character Names

Name	Value	Symbolic Name	Name	Value	Symbolic Name
<control>-A	<SOH>	<SOH>	<control>-Q	<DC1>	<DC1>
<control>-B	<STX>	<STX>	<control>-R	<DC2>	<DC2>
<control>-C	<ETX>	<ETX>	<control>-S	<DC3>	<DC3>
<control>-D	<EOT>	<EOT>	<control>-T	<DC4>	<DC4>
<control>-E	<ENQ>	<ENQ>	<control>-U	<NAK>	<NAK>
<control>-F	<ACK>	<ACK>	<control>-V	<SYN>	<SYN>
<control>-G	<BEL>	<alert>	<control>-W	<ETB>	<ETB>
<control>-H	<BS>	<backspace>	<control>-X	<CAN>	<CAN>
<control>-I	<HT>	<tab>	<control>-Y	<EM>	<EM>
<control>-J	<LF>	<linefeed>	<control>-Z	<SUB>	<SUB>
<control>-K	<VT>	<vertical-tab>	<control>-[	<ESC>	<ESC>
<control>-L	<FF>	<form-feed>	<control>-\	<FS>	<FS>
<control>-M	<CR>	<carriage-return>	<control>-]	<GS>	<GS>
<control>-N	<SO>	<SO>	<control>-^	<RS>	<RS>
<control>-O	<SI>	<SI>	<control>-_	<US>	<US>
<control>-P	<DLE>	<DLE>	<control>-?	<DEL>	<DEL>

Note: The notation uses uppercase letters for arbitrary editorial reasons. There is no implication that the keystrokes represent control-shift-letter sequences.

Chapter 11

General Terminal Interface

This chapter describes a general terminal interface that shall be provided. It shall be supported on any asynchronous communications ports if the implementation provides them. It is implementation-defined whether it supports network connections or synchronous ports, or both.

11.1 Interface Characteristics

11.1.1 Opening a Terminal Device File

When a terminal device file is opened, it normally causes the thread to wait until a connection is established. In practice, application programs seldom open these files; they are opened by special programs and become an application's standard input, output, and error files.

As described in *open*( ), opening a terminal device file with the O_NONBLOCK flag clear shall cause the thread to block until the terminal device is ready and available. If CLOCAL mode is not set, this means blocking until a connection is established. If CLOCAL mode is set in the terminal, or the O_NONBLOCK flag is specified in the *open*( ), the *open*( ) function shall return a file descriptor without waiting for a connection to be established.

11.1.2 Process Groups

A terminal may have a foreground process group associated with it. This foreground process group plays a special role in handling signal-generating input characters, as discussed in Section 11.1.9 (on page 191).

A command interpreter process supporting job control can allocate the terminal to different jobs, or process groups, by placing related processes in a single process group and associating this process group with the terminal. A terminal's foreground process group may be set or examined by a process, assuming the permission requirements are met; see *tcgetpgrp*( ) and *tcsetpgrp*( ). The terminal interface aids in this allocation by restricting access to the terminal by processes that are not in the current process group; see Section 11.1.4 (on page 188).

When there is no longer any process whose process ID or process group ID matches the foreground process group ID, the terminal shall have no foreground process group. It is unspecified whether the terminal has a foreground process group when there is a process whose process ID matches the foreground process group ID, but whose process group ID does not. No actions defined in IEEE Std 1003.1-2001, other than allocation of a controlling terminal or a successful call to *tcsetpgrp*( ), shall cause a process group to become the foreground process group of the terminal.

11.1.3 The Controlling Terminal

A terminal may belong to a process as its controlling terminal. Each process of a session that has a controlling terminal has the same controlling terminal. A terminal may be the controlling terminal for at most one session. The controlling terminal for a session is allocated by the session leader in an implementation-defined manner. If a session leader has no controlling terminal, and opens a terminal device file that is not already associated with a session without using the O_NOCTTY option (see *open*( )), it is implementation-defined whether the terminal becomes the controlling terminal of the session leader. If a process which is not a session leader opens a terminal file, or the O_NOCTTY option is used on *open*( ), then that terminal shall not become the controlling terminal of the calling process. When a controlling terminal becomes associated with a session, its foreground process group shall be set to the process group of the session leader.

The controlling terminal is inherited by a child process during a *fork*( ) function call. A process relinquishes its controlling terminal when it creates a new session with the *setsid*( ) function; other processes remaining in the old session that had this terminal as their controlling terminal continue to have it. Upon the close of the last file descriptor in the system (whether or not it is in the current session) associated with the controlling terminal, it is unspecified whether all processes that had that terminal as their controlling terminal cease to have any controlling terminal. Whether and how a session leader can reacquire a controlling terminal after the controlling terminal has been relinquished in this fashion is unspecified. A process does not relinquish its controlling terminal simply by closing all of its file descriptors associated with the controlling terminal if other processes continue to have it open.

When a controlling process terminates, the controlling terminal is dissociated from the current session, allowing it to be acquired by a new session leader. Subsequent access to the terminal by other processes in the earlier session may be denied, with attempts to access the terminal treated as if a modem disconnect had been sensed.

11.1.4 Terminal Access Control

If a process is in the foreground process group of its controlling terminal, read operations shall be allowed, as described in Section 11.1.5 (on page 189). Any attempts by a process in a background process group to read from its controlling terminal cause its process group to be sent a SIGTTIN signal unless one of the following special cases applies: if the reading process is ignoring or blocking the SIGTTIN signal, or if the process group of the reading process is orphaned, the *read*( ) shall return –1, with *errno* set to [EIO] and no signal shall be sent. The default action of the SIGTTIN signal shall be to stop the process to which it is sent. See **<signal.h>**.

If a process is in the foreground process group of its controlling terminal, write operations shall be allowed as described in Section 11.1.8 (on page 191). Attempts by a process in a background process group to write to its controlling terminal shall cause the process group to be sent a SIGTTOU signal unless one of the following special cases applies: if TOSTOP is not set, or if TOSTOP is set and the process is ignoring or blocking the SIGTTOU signal, the process is allowed to write to the terminal and the SIGTTOU signal is not sent. If TOSTOP is set, and the process group of the writing process is orphaned, and the writing process is not ignoring or blocking the SIGTTOU signal, the *write*( ) shall return –1, with *errno* set to [EIO] and no signal shall be sent.

Certain calls that set terminal parameters are treated in the same fashion as *write*( ), except that TOSTOP is ignored; that is, the effect is identical to that of terminal writes when TOSTOP is set (see Section 11.2.5 (on page 197), *tcdrain*( ), *tcflow*( ), *tcflush*( ), *tcsendbreak*( ), *tcsetattr*( ), and *tcsetpgrp*( )).

11.1.5 Input Processing and Reading Data

A terminal device associated with a terminal device file may operate in full-duplex mode, so that data may arrive even while output is occurring. Each terminal device file has an input queue associated with it, into which incoming data is stored by the system before being read by a process. The system may impose a limit, {MAX_INPUT}, on the number of bytes that may be stored in the input queue. The behavior of the system when this limit is exceeded is implementation-defined.

Two general kinds of input processing are available, determined by whether the terminal device file is in canonical mode or non-canonical mode. These modes are described in Section 11.1.6 and Section 11.1.7 (on page 190). Additionally, input characters are processed according to the *c_iflag* (see Section 11.2.2 (on page 193)) and *c_lflag* (see Section 11.2.5 (on page 197)) fields. Such processing can include ''echoing'', which in general means transmitting input characters immediately back to the terminal when they are received from the terminal. This is useful for terminals that can operate in full-duplex mode.

The manner in which data is provided to a process reading from a terminal device file is dependent on whether the terminal file is in canonical or non-canonical mode, and on whether or not the O_NONBLOCK flag is set by *open*( ) or *fcntl*( ).

If the O_NONBLOCK flag is clear, then the read request shall be blocked until data is available or a signal has been received. If the O_NONBLOCK flag is set, then the read request shall be completed, without blocking, in one of three ways:

1. If there is enough data available to satisfy the entire request, the *read*( ) shall complete successfully and shall return the number of bytes read.
2. If there is not enough data available to satisfy the entire request, the *read*( ) shall complete successfully, having read as much data as possible, and shall return the number of bytes it was able to read.
3. If there is no data available, the *read*( ) shall return −1, with *errno* set to [EAGAIN].

When data is available depends on whether the input processing mode is canonical or non-canonical. Section 11.1.6 and Section 11.1.7 (on page 190) describe each of these input processing modes.

11.1.6 Canonical Mode Input Processing

In canonical mode input processing, terminal input is processed in units of lines. A line is delimited by a newline character (NL), an end-of-file character (EOF), or an end-of-line (EOL) character. See Section 11.1.9 (on page 191) for more information on EOF and EOL. This means that a read request shall not return until an entire line has been typed or a signal has been received. Also, no matter how many bytes are requested in the *read*( ) call, at most one line shall be returned. It is not, however, necessary to read a whole line at once; any number of bytes, even one, may be requested in a *read*( ) without losing information.

If {MAX_CANON} is defined for this terminal device, it shall be a limit on the number of bytes in a line. The behavior of the system when this limit is exceeded is implementation-defined. If {MAX_CANON} is not defined, there shall be no such limit; see *pathconf*( ).

Erase and kill processing occur when either of two special characters, the ERASE and KILL characters (see Section 11.1.9 (on page 191)), is received. This processing shall affect data in the input queue that has not yet been delimited by an NL, EOF, or EOL character. This un-delimited data makes up the current line. The ERASE character shall delete the last character in the current line, if there is one. The KILL character shall delete all data in the current line, if there is any. The ERASE and KILL characters shall have no effect if there is no data in the current line. The ERASE

6699 and KILL characters themselves shall not be placed in the input queue.

6700 11.1.7 Non-Canonical Mode Input Processing

6701 In non-canonical mode input processing, input bytes are not assembled into lines, and erase and
6702 kill processing shall not occur. The values of the MIN and TIME members of the *c_cc* array are
6703 used to determine how to process the bytes received. IEEE Std 1003.1-2001 does not specify
6704 whether the setting of O_NONBLOCK takes precedence over MIN or TIME settings. Therefore,
6705 if O_NONBLOCK is set, *read*( ) may return immediately, regardless of the setting of MIN or
6706 TIME. Also, if no data is available, *read*( ) may either return 0, or return –1 with *errno* set to
6707 [EAGAIN].

6708 MIN represents the minimum number of bytes that should be received when the *read*( ) function
6709 returns successfully. TIME is a timer of 0.1 second granularity that is used to time out bursty and
6710 short-term data transmissions. If MIN is greater than {MAX_INPUT}, the response to the request
6711 is undefined. The four possible values for MIN and TIME and their interactions are described
6712 below.

6713 **Case A: MIN>0, TIME>0**

6714 In case A, TIME serves as an inter-byte timer which shall be activated after the first byte is
6715 received. Since it is an inter-byte timer, it shall be reset after a byte is received. The interaction
6716 between MIN and TIME is as follows. As soon as one byte is received, the inter-byte timer shall
6717 be started. If MIN bytes are received before the inter-byte timer expires (remember that the timer
6718 is reset upon receipt of each byte), the read shall be satisfied. If the timer expires before MIN
6719 bytes are received, the characters received to that point shall be returned to the user. Note that if
6720 TIME expires at least one byte shall be returned because the timer would not have been enabled
6721 unless a byte was received. In this case (MIN>0, TIME>0) the read shall block until the MIN and
6722 TIME mechanisms are activated by the receipt of the first byte, or a signal is received. If data is in
6723 the buffer at the time of the *read*( ), the result shall be as if data has been received immediately
6724 after the *read*( ).

6725 **Case B: MIN>0, TIME=0**

6726 In case B, since the value of TIME is zero, the timer plays no role and only MIN is significant. A
6727 pending read shall not be satisfied until MIN bytes are received (that is, the pending read shall
6728 block until MIN bytes are received), or a signal is received. A program that uses case B to read
6729 record-based terminal I/O may block indefinitely in the read operation.

6730 **Case C: MIN=0, TIME>0**

6731 In case C, since MIN=0, TIME no longer represents an inter-byte timer. It now serves as a read
6732 timer that shall be activated as soon as the *read*( ) function is processed. A read shall be satisfied
6733 as soon as a single byte is received or the read timer expires. Note that in case C if the timer
6734 expires, no bytes shall be returned. If the timer does not expire, the only way the read can be
6735 satisfied is if a byte is received. If bytes are not received, the read shall not block indefinitely
6736 waiting for a byte; if no byte is received within TIME*0.1 seconds after the read is initiated, the
6737 *read*( ) shall return a value of zero, having read no data. If data is in the buffer at the time of the
6738 *read*( ), the timer shall be started as if data has been received immediately after the *read*( ).

Case D: MIN=0, TIME=0

The minimum of either the number of bytes requested or the number of bytes currently available shall be returned without waiting for more bytes to be input. If no characters are available, *read*( ) shall return a value of zero, having read no data.

11.1.8 Writing Data and Output Processing

When a process writes one or more bytes to a terminal device file, they are processed according to the *c_oflag* field (see Section 11.2.3 (on page 194)). The implementation may provide a buffering mechanism; as such, when a call to *write*( ) completes, all of the bytes written have been scheduled for transmission to the device, but the transmission has not necessarily completed. See *write*( ) for the effects of O_NONBLOCK on *write*( ).

11.1.9 Special Characters

Certain characters have special functions on input or output or both. These functions are summarized as follows:

INTR Special character on input, which is recognized if the ISIG flag is set. Generates a SIGINT signal which is sent to all processes in the foreground process group for which the terminal is the controlling terminal. If ISIG is set, the INTR character shall be discarded when processed.

QUIT Special character on input, which is recognized if the ISIG flag is set. Generates a SIGQUIT signal which is sent to all processes in the foreground process group for which the terminal is the controlling terminal. If ISIG is set, the QUIT character shall be discarded when processed.

ERASE Special character on input, which is recognized if the ICANON flag is set. Erases the last character in the current line; see Section 11.1.6 (on page 189). It shall not erase beyond the start of a line, as delimited by an NL, EOF, or EOL character. If ICANON is set, the ERASE character shall be discarded when processed.

KILL Special character on input, which is recognized if the ICANON flag is set. Deletes the entire line, as delimited by an NL, EOF, or EOL character. If ICANON is set, the KILL character shall be discarded when processed.

EOF Special character on input, which is recognized if the ICANON flag is set. When received, all the bytes waiting to be read are immediately passed to the process without waiting for a newline, and the EOF is discarded. Thus, if there are no bytes waiting (that is, the EOF occurred at the beginning of a line), a byte count of zero shall be returned from the *read*( ), representing an end-of-file indication. If ICANON is set, the EOF character shall be discarded when processed.

NL Special character on input, which is recognized if the ICANON flag is set. It is the line delimiter newline. It cannot be changed.

EOL Special character on input, which is recognized if the ICANON flag is set. It is an additional line delimiter, like NL.

SUSP If the ISIG flag is set, receipt of the SUSP character shall cause a SIGTSTP signal to be sent to all processes in the foreground process group for which the terminal is the controlling terminal, and the SUSP character shall be discarded when processed.

STOP Special character on both input and output, which is recognized if the IXON (output control) or IXOFF (input control) flag is set. Can be used to suspend output temporarily. It is useful with CRT terminals to prevent output from disappearing

before it can be read. If IXON is set, the STOP character shall be discarded when processed.

START Special character on both input and output, which is recognized if the IXON (output control) or IXOFF (input control) flag is set. Can be used to resume output that has been suspended by a STOP character. If IXON is set, the START character shall be discarded when processed.

CR Special character on input, which is recognized if the ICANON flag is set; it is the carriage-return character. When ICANON and ICRNL are set and IGNCR is not set, this character shall be translated into an NL, and shall have the same effect as an NL character.

The NL and CR characters cannot be changed. It is implementation-defined whether the START and STOP characters can be changed. The values for INTR, QUIT, ERASE, KILL, EOF, EOL, and SUSP shall be changeable to suit individual tastes. Special character functions associated with changeable special control characters can be disabled individually.

If two or more special characters have the same value, the function performed when that character is received is undefined.

A special character is recognized not only by its value, but also by its context; for example, an implementation may support multi-byte sequences that have a meaning different from the meaning of the bytes when considered individually. Implementations may also support additional single-byte functions. These implementation-defined multi-byte or single-byte functions shall be recognized only if the IEXTEN flag is set; otherwise, data is received without interpretation, except as required to recognize the special characters defined in this section.

XSI If IEXTEN is set, the ERASE, KILL, and EOF characters can be escaped by a preceding '\' character, in which case no special function shall occur.

11.1.10 Modem Disconnect

If a modem disconnect is detected by the terminal interface for a controlling terminal, and if CLOCAL is not set in the *c_cflag* field for the terminal (see Section 11.2.4 (on page 196)), the SIGHUP signal shall be sent to the controlling process for which the terminal is the controlling terminal. Unless other arrangements have been made, this shall cause the controlling process to terminate (see *exit*( )). Any subsequent read from the terminal device shall return the value of zero, indicating end-of-file; see *read*( ). Thus, processes that read a terminal file and test for end-of-file can terminate appropriately after a disconnect. If the EIO condition as specified in *read*( ) also exists, it is unspecified whether on EOF condition or [EIO] is returned. Any subsequent *write*( ) to the terminal device shall return −1, with *errno* set to [EIO], until the device is closed.

11.1.11 Closing a Terminal Device File

The last process to close a terminal device file shall cause any output to be sent to the device and any input to be discarded. If HUPCL is set in the control modes and the communications port supports a disconnect function, the terminal device shall perform a disconnect.

11.2 Parameters that Can be Set

11.2.1 The termios Structure

Routines that need to control certain terminal I/O characteristics shall do so by using the **termios** structure as defined in the **<termios.h>** header. The members of this structure include (but are not limited to):

Member Type	Array Size	Member Name	Description
tcflag_t		*c_iflag*	Input modes.
tcflag_t		*c_oflag*	Output modes.
tcflag_t		*c_cflag*	Control modes.
tcflag_t		*c_lflag*	Local modes.
cc_t	NCCS	*c_cc*[ ]	Control characters.

The types **tcflag_t** and **cc_t** are defined in the **<termios.h>** header. They shall be unsigned integer types.

11.2.2 Input Modes

Values of the *c_iflag* field describe the basic terminal input control, and are composed of the bitwise-inclusive OR of the masks shown, which shall be bitwise-distinct. The mask name symbols in this table are defined in **<termios.h>**:

Mask Name	Description
BRKINT	Signal interrupt on break.
ICRNL	Map CR to NL on input.
IGNBRK	Ignore break condition.
IGNCR	Ignore CR.
IGNPAR	Ignore characters with parity errors.
INLCR	Map NL to CR on input.
INPCK	Enable input parity check.
ISTRIP	Strip character.
XSI IXANY	Enable any character to restart output.
IXOFF	Enable start/stop input control.
IXON	Enable start/stop output control.
PARMRK	Mark parity errors.

In the context of asynchronous serial data transmission, a break condition shall be defined as a sequence of zero-valued bits that continues for more than the time to send one byte. The entire sequence of zero-valued bits is interpreted as a single break condition, even if it continues for a time equivalent to more than one byte. In contexts other than asynchronous serial data transmission, the definition of a break condition is implementation-defined.

If IGNBRK is set, a break condition detected on input shall be ignored; that is, not put on the input queue and therefore not read by any process. If IGNBRK is not set and BRKINT is set, the break condition shall flush the input and output queues, and if the terminal is the controlling terminal of a foreground process group, the break condition shall generate a single SIGINT signal to that foreground process group. If neither IGNBRK nor BRKINT is set, a break condition shall be read as a single 0x00, or if PARMRK is set, as 0xff 0x00 0x00.

If IGNPAR is set, a byte with a framing or parity error (other than break) shall be ignored.

6865 If PARMRK is set, and IGNPAR is not set, a byte with a framing or parity error (other than
6866 break) shall be given to the application as the three-byte sequence 0xff 0x00 X, where 0xff 0x00 is
6867 a two-byte flag preceding each sequence and X is the data of the byte received in error. To avoid
6868 ambiguity in this case, if ISTRIP is not set, a valid byte of 0xff is given to the application as 0xff
6869 0xff. If neither PARMRK nor IGNPAR is set, a framing or parity error (other than break) shall be
6870 given to the application as a single byte 0x00.

6871 If INPCK is set, input parity checking shall be enabled. If INPCK is not set, input parity checking
6872 shall be disabled, allowing output parity generation without input parity errors. Note that
6873 whether input parity checking is enabled or disabled is independent of whether parity detection
6874 is enabled or disabled (see Section 11.2.4 (on page 196)). If parity detection is enabled but input
6875 parity checking is disabled, the hardware to which the terminal is connected shall recognize the
6876 parity bit, but the terminal special file shall not check whether or not this bit is correctly set.

6877 If ISTRIP is set, valid input bytes shall first be stripped to seven bits; otherwise, all eight bits
6878 shall be processed.

6879 If INLCR is set, a received NL character shall be translated into a CR character. If IGNCR is set, a
6880 received CR character shall be ignored (not read). If IGNCR is not set and ICRNL is set, a
6881 received CR character shall be translated into an NL character.

6882 XSI If IXANY is set, any input character shall restart output that has been suspended.

6883 If IXON is set, start/stop output control shall be enabled. A received STOP character shall
6884 suspend output and a received START character shall restart output. When IXON is set, START
6885 and STOP characters are not read, but merely perform flow control functions. When IXON is not
6886 set, the START and STOP characters shall be read.

6887 If IXOFF is set, start/stop input control shall be enabled. The system shall transmit STOP
6888 characters, which are intended to cause the terminal device to stop transmitting data, as needed
6889 to prevent the input queue from overflowing and causing implementation-defined behavior, and
6890 shall transmit START characters, which are intended to cause the terminal device to resume
6891 transmitting data, as soon as the device can continue transmitting data without risk of
6892 overflowing the input queue. The precise conditions under which STOP and START characters
6893 are transmitted are implementation-defined.

6894 The initial input control value after *open*( ) is implementation-defined.

6895 11.2.3 Output Modes

6896 The *c_oflag* field specifies the terminal interface's treatment of output, and is composed of the
6897 bitwise-inclusive OR of the masks shown, which shall be bitwise-distinct. The mask name
6898 symbols in the following table are defined in **<termios.h>**:

Mask Name	Description
OPOST	Perform output processing.
XSI ONLCR	Map NL to CR-NL on output.
OCRNL	Map CR to NL on output.
ONOCR	No CR output at column 0.
ONLRET	NL performs CR function.
OFILL	Use fill characters for delay.
OFDEL	Fill is DEL, else NUL.
NLDLY	Select newline delays:
NL0	Newline character type 0.
NL1	Newline character type 1.
CRDLY	Select carriage-return delays:
CR0	Carriage-return delay type 0.
CR1	Carriage-return delay type 1.
CR2	Carriage-return delay type 2.
CR3	Carriage-return delay type 3.
TABDLY	Select horizontal-tab delays:
TAB0	Horizontal-tab delay type 0.
TAB1	Horizontal-tab delay type 1.
TAB2	Horizontal-tab delay type 2.
TAB3	Expand tabs to spaces.
BSDLY	Select backspace delays:
BS0	Backspace-delay type 0.
BS1	Backspace-delay type 1.
VTDLY	Select vertical-tab delays:
VT0	Vertical-tab delay type 0.
VT1	Vertical-tab delay type 1.
FFDLY	Select form-feed delays:
FF0	Form-feed delay type 0.
FF1	Form-feed delay type 1.

If OPOST is set, output data shall be post-processed as described below, so that lines of text are modified to appear appropriately on the terminal device; otherwise, characters shall be transmitted without change.

XSI If ONLCR is set, the NL character shall be transmitted as the CR-NL character pair. If OCRNL is set, the CR character shall be transmitted as the NL character. If ONOCR is set, no CR character shall be transmitted when at column 0 (first position). If ONLRET is set, the NL character is assumed to do the carriage-return function; the column pointer shall be set to 0 and the delays specified for CR shall be used. Otherwise, the NL character is assumed to do just the line-feed function; the column pointer remains unchanged. The column pointer shall also be set to 0 if the CR character is actually transmitted.

The delay bits specify how long transmission stops to allow for mechanical or other movement when certain characters are sent to the terminal. In all cases a value of 0 shall indicate no delay. If OFILL is set, fill characters shall be transmitted for delay instead of a timed delay. This is useful for high baud rate terminals which need only a minimal delay. If OFDEL is set, the fill character shall be DEL; otherwise, NUL.

If a form-feed or vertical-tab delay is specified, it shall last for about 2 seconds.

Newline delay shall last about 0.10 seconds. If ONLRET is set, the carriage-return delays shall be used instead of the newline delays. If OFILL is set, two fill characters shall be transmitted.

Carriage-return delay type 1 shall be dependent on the current column position, type 2 shall be about 0.10 seconds, and type 3 shall be about 0.15 seconds. If OFILL is set, delay type 1 shall transmit two fill characters, and type 2 four fill characters.

Horizontal-tab delay type 1 shall be dependent on the current column position. Type 2 shall be about 0.10 seconds. Type 3 specifies that tabs shall be expanded into spaces. If OFILL is set, two fill characters shall be transmitted for any delay.

Backspace delay shall last about 0.05 seconds. If OFILL is set, one fill character shall be transmitted.

The actual delays depend on line speed and system load.

The initial output control value after *open*( ) is implementation-defined.

11.2.4 Control Modes

The *c_cflag* field describes the hardware control of the terminal, and is composed of the bitwise-inclusive OR of the masks shown, which shall be bitwise-distinct. The mask name symbols in this table are defined in **<termios.h>**; not all values specified are required to be supported by the underlying hardware:

Mask Name	Description
CLOCAL	Ignore modem status lines.
CREAD	Enable receiver.
CSIZE	Number of bits transmitted or received per byte:
CS5	5 bits
CS6	6 bits
CS7	7 bits
CS8	8 bits.
CSTOPB	Send two stop bits, else one.
HUPCL	Hang up on last close.
PARENB	Parity enable.
PARODD	Odd parity, else even.

In addition, the input and output baud rates are stored in the **termios** structure. The symbols in the following table are defined in **<termios.h>**. Not all values specified are required to be supported by the underlying hardware.

Name	Description	Name	Description
B0	Hang up	B600	600 baud
B50	50 baud	B1200	1200 baud
B75	75 baud	B1800	1800 baud
B110	110 baud	B2400	2400 baud
B134	134.5 baud	B4800	4800 baud
B150	150 baud	B9600	9600 baud
B200	200 baud	B19200	19200 baud
B300	300 baud	B38400	38400 baud

The following functions are provided for getting and setting the values of the input and output baud rates in the **termios** structure: *cfgetispeed*( ), *cfgetospeed*( ), *cfsetispeed*( ), and *cfsetospeed*( ). The effects on the terminal device shall not become effective and not all errors need be detected until the *tcsetattr*( ) function is successfully called.

The CSIZE bits shall specify the number of transmitted or received bits per byte. If ISTRIP is not set, the value of all the other bits is unspecified. If ISTRIP is set, the value of all but the 7 low-

order bits shall be zero, but the value of any other bits beyond CSIZE is unspecified when read. CSIZE shall not include the parity bit, if any. If CSTOPB is set, two stop bits shall be used; otherwise, one stop bit. For example, at 110 baud, two stop bits are normally used.

If CREAD is set, the receiver shall be enabled; otherwise, no characters shall be received.

If PARENB is set, parity generation and detection shall be enabled and a parity bit is added to each byte. If parity is enabled, PARODD shall specify odd parity if set; otherwise, even parity shall be used.

If HUPCL is set, the modem control lines for the port shall be lowered when the last process with the port open closes the port or the process terminates. The modem connection shall be broken.

If CLOCAL is set, a connection shall not depend on the state of the modem status lines. If CLOCAL is clear, the modem status lines shall be monitored.

Under normal circumstances, a call to the *open*( ) function shall wait for the modem connection to complete. However, if the O_NONBLOCK flag is set (see *open*( )) or if CLOCAL has been set, the *open*( ) function shall return immediately without waiting for the connection.

If the object for which the control modes are set is not an asynchronous serial connection, some of the modes may be ignored; for example, if an attempt is made to set the baud rate on a network connection to a terminal on another host, the baud rate need not be set on the connection between that terminal and the machine to which it is directly connected.

The initial hardware control value after *open*( ) is implementation-defined.

11.2.5 Local Modes

The *c_lflag* field of the argument structure is used to control various functions. It is composed of the bitwise-inclusive OR of the masks shown, which shall be bitwise-distinct. The mask name symbols in this table are defined in **<termios.h>**; not all values specified are required to be supported by the underlying hardware:

Mask Name	Description
ECHO	Enable echo.
ECHOE	Echo ERASE as an error correcting backspace.
ECHOK	Echo KILL.
ECHONL	Echo <newline>.
ICANON	Canonical input (erase and kill processing).
IEXTEN	Enable extended (implementation-defined) functions.
ISIG	Enable signals.
NOFLSH	Disable flush after interrupt, quit, or suspend.
TOSTOP	Send SIGTTOU for background output.

If ECHO is set, input characters shall be echoed back to the terminal. If ECHO is clear, input characters shall not be echoed.

If ECHOE and ICANON are set, the ERASE character shall cause the terminal to erase, if possible, the last character in the current line from the display. If there is no character to erase, an implementation may echo an indication that this was the case, or do nothing.

If ECHOK and ICANON are set, the KILL character shall either cause the terminal to erase the line from the display or shall echo the newline character after the KILL character.

If ECHONL and ICANON are set, the newline character shall be echoed even if ECHO is not set.

If ICANON is set, canonical processing shall be enabled. This enables the erase and kill edit functions, and the assembly of input characters into lines delimited by NL, EOF, and EOL, as described in Section 11.1.6 (on page 189).

If ICANON is not set, read requests shall be satisfied directly from the input queue. A read shall not be satisfied until at least MIN bytes have been received or the timeout value TIME expired between bytes. The time value represents tenths of a second. See Section 11.1.7 (on page 190) for more details.

If IEXTEN is set, implementation-defined functions shall be recognized from the input data. It is implementation-defined how IEXTEN being set interacts with ICANON, ISIG, IXON, or IXOFF. If IEXTEN is not set, implementation-defined functions shall not be recognized and the corresponding input characters are processed as described for ICANON, ISIG, IXON, and IXOFF.

If ISIG is set, each input character shall be checked against the special control characters INTR, QUIT, and SUSP. If an input character matches one of these control characters, the function associated with that character shall be performed. If ISIG is not set, no checking shall be done. Thus these special input functions are possible only if ISIG is set.

If NOFLSH is set, the normal flush of the input and output queues associated with the INTR, QUIT, and SUSP characters shall not be done.

If TOSTOP is set, the signal SIGTTOU shall be sent to the process group of a process that tries to write to its controlling terminal if it is not in the foreground process group for that terminal. This signal, by default, stops the members of the process group. Otherwise, the output generated by that process shall be output to the current output stream. Processes that are blocking or ignoring SIGTTOU signals are excepted and allowed to produce output, and the SIGTTOU signal shall not be sent.

The initial local control value after *open*( ) is implementation-defined.

11.2.6 Special Control Characters

The special control character values shall be defined by the array *c_cc*. The subscript name and description for each element in both canonical and non-canonical modes are as follows:

Subscript Usage		
Canonical Mode	**Non-Canonical Mode**	**Description**
VEOF		EOF character
VEOL		EOL character
VERASE		ERASE character
VINTR	VINTR	INTR character
VKILL		KILL character
	VMIN	MIN value
VQUIT	VQUIT	QUIT character
VSUSP	VSUSP	SUSP character
	VTIME	TIME value
VSTART	VSTART	START character
VSTOP	VSTOP	STOP character

The subscript values are unique, except that the VMIN and VTIME subscripts may have the same values as the VEOF and VEOL subscripts, respectively.

Implementations that do not support changing the START and STOP characters may ignore the character values in the *c_cc* array indexed by the VSTART and VSTOP subscripts when *tcsetattr*( ) is called, but shall return the value in use when *tcgetattr*( ) is called.

The initial values of all control characters are implementation-defined.

If the value of one of the changeable special control characters (see Section 11.1.9 (on page 191)) is _POSIX_VDISABLE, that function shall be disabled; that is, no input data is recognized as the disabled special character. If ICANON is not set, the value of _POSIX_VDISABLE has no special meaning for the VMIN and VTIME entries of the *c_cc* array.

7090

Chapter 12

Utility Conventions

12.1 Utility Argument Syntax

This section describes the argument syntax of the standard utilities and introduces terminology used throughout IEEE Std 1003.1-2001 for describing the arguments processed by the utilities.

Within IEEE Std 1003.1-2001, a special notation is used for describing the syntax of a utility's arguments. Unless otherwise noted, all utility descriptions use this notation, which is illustrated by this example (see the Shell and Utilities volume of IEEE Std 1003.1-2001, Section 2.9.1, Simple Commands):

```
utility_name[–a][–b][–c option_argument]
    [–d|–e][–foption_argument][operand...]
```

The notation used for the SYNOPSIS sections imposes requirements on the implementors of the standard utilities and provides a simple reference for the application developer or system user.

1. The utility in the example is named *utility_name*. It is followed by options, option-arguments, and operands. The arguments that consist of hyphens and single letters or digits, such as `'a'`, are known as ''options'' (or, historically, ''flags''). Certain options are followed by an ''option-argument'', as shown with [**–c** *option_argument*]. The arguments following the last options and option-arguments are named ''operands''.

2. Option-arguments are sometimes shown separated from their options by <blank>s, sometimes directly adjacent. This reflects the situation that in some cases an option-argument is included within the same argument string as the option; in most cases it is the next argument. The Utility Syntax Guidelines in Section 12.2 (on page 203) require that the option be a separate argument from its option-argument, but there are some exceptions in IEEE Std 1003.1-2001 to ensure continued operation of historical applications:

   a. If the SYNOPSIS of a standard utility shows a <space> between an option and option-argument (as with [**–c** *option_argument*] in the example), a conforming application shall use separate arguments for that option and its option-argument.

   b. If a <space> is not shown (as with [**–f***option_argument*] in the example), a conforming application shall place an option and its option-argument directly adjacent in the same argument string, without intervening <blank>s.

   c. Notwithstanding the preceding requirements on conforming applications, a conforming implementation shall permit an application to specify options and option-arguments as a single argument or as separate arguments whether or not a <space> is shown on the synopsis line, except in those cases (marked with the XSI portability warning) where an option-argument is optional and no separation can be used.

   XSI

   d. A standard utility may also be implemented to operate correctly when the required separation into multiple arguments is violated by a non-conforming application.

3. Options are usually listed in alphabetical order unless this would make the utility description more confusing. There are no implied relationships between the options based upon the order in which they appear, unless otherwise stated in the OPTIONS section, or unless the exception in Guideline 11 of Section 12.2 (on page 203) applies. If an option that

does not have option-arguments is repeated, the results are undefined, unless otherwise stated.

4. Frequently, names of parameters that require substitution by actual values are shown with embedded underscores. Alternatively, parameters are shown as follows:

   ```
   <parameter name>
   ```

   The angle brackets are used for the symbolic grouping of a phrase representing a single parameter and conforming applications shall not include them in data submitted to the utility.

5. When a utility has only a few permissible options, they are sometimes shown individually, as in the example. Utilities with many flags generally show all of the individual flags (that do not take option-arguments) grouped, as in:

   ```
   utility_name [–abcDxyz][–p arg][operand]
   ```

   Utilities with very complex arguments may be shown as follows:

   ```
   utility_name [options][operands]
   ```

6. Unless otherwise specified, whenever an operand or option-argument is, or contains, a numeric value:

   - The number is interpreted as a decimal integer.
   - Numerals in the range 0 to 2 147 483 647 are syntactically recognized as numeric values.
   - When the utility description states that it accepts negative numbers as operands or option-arguments, numerals in the range –2 147 483 647 to 2 147 483 647 are syntactically recognized as numeric values.
   - Ranges greater than those listed here are allowed.

   This does not mean that all numbers within the allowable range are necessarily semantically correct. A standard utility that accepts an option-argument or operand that is to be interpreted as a number, and for which a range of values smaller than that shown above is permitted by the IEEE Std 1003.1-2001, describes that smaller range along with the description of the option-argument or operand. If an error is generated, the utility's diagnostic message shall indicate that the value is out of the supported range, not that it is syntactically incorrect.

7. Arguments or option-arguments enclosed in the '[' and ']' notation are optional and can be omitted. Conforming applications shall not include the '[' and ']' symbols in data submitted to the utility.

8. Arguments separated by the '|' vertical bar notation are mutually-exclusive. Conforming applications shall not include the '|' symbol in data submitted to the utility. Alternatively, mutually-exclusive options and operands may be listed with multiple synopsis lines. For example:

   ```
   utility_name –d[–a][–c option_argument][operand...]
   utility_name[–a][–b][operand...]
   ```

   When multiple synopsis lines are given for a utility, it is an indication that the utility has mutually-exclusive arguments. These mutually-exclusive arguments alter the functionality of the utility so that only certain other arguments are valid in combination with one of the mutually-exclusive arguments. Only one of the mutually-exclusive arguments is allowed for invocation of the utility. Unless otherwise stated in an accompanying OPTIONS section, the relationships between arguments depicted in the SYNOPSIS sections are

mandatory requirements placed on conforming applications. The use of conflicting mutually-exclusive arguments produces undefined results, unless a utility description specifies otherwise. When an option is shown without the '[' and ']' brackets, it means that option is required for that version of the SYNOPSIS. However, it is not required to be the first argument, as shown in the example above, unless otherwise stated.

9. Ellipses ("...") are used to denote that one or more occurrences of an option or operand are allowed. When an option or an operand followed by ellipses is enclosed in brackets, zero or more options or operands can be specified. The forms:

   ```
   utility_name –f option_argument...[operand...]
   utility_name [–g option_argument]...[operand...]
   ```

   indicate that multiple occurrences of the option and its option-argument preceding the ellipses are valid, with semantics as indicated in the OPTIONS section of the utility. (See also Guideline 11 in Section 12.2.) In the first example, each option-argument requires a preceding **–f** and at least one **–f** *option_argument* must be given.

10. When the synopsis line is too long to be printed on a single line in the Shell and Utilities volume of IEEE Std 1003.1-2001, the indented lines following the initial line are continuation lines. An actual use of the command would appear on a single logical line.

12.2 Utility Syntax Guidelines

The following guidelines are established for the naming of utilities and for the specification of options, option-arguments, and operands. The *getopt*( ) function in the System Interfaces volume of IEEE Std 1003.1-2001 assists utilities in handling options and operands that conform to these guidelines.

Operands and option-arguments can contain characters not specified in the portable character set.

The guidelines are intended to provide guidance to the authors of future utilities, such as those written specific to a local system or that are components of a larger application. Some of the standard utilities do not conform to all of these guidelines; in those cases, the OPTIONS sections describe the deviations.

Guideline 1: Utility names should be between two and nine characters, inclusive.

Guideline 2: Utility names should include lowercase letters (the **lower** character classification) and digits only from the portable character set.

Guideline 3: Each option name should be a single alphanumeric character (the **alnum** character classification) from the portable character set. The **–W** (capital-W) option shall be reserved for vendor options.

Multi-digit options should not be allowed.

Guideline 4: All options should be preceded by the '–' delimiter character.

Guideline 5: Options without option-arguments should be accepted when grouped behind one '–' delimiter.

Guideline 6: Each option and option-argument should be a separate argument, except as noted in Section 12.1 (on page 201), item (2).

Guideline 7: Option-arguments should not be optional.

Guideline 8: When multiple option-arguments are specified to follow a single option, they should be presented as a single argument, using commas within that argument or <blank>s within that argument to separate them.

Guideline 9: All options should precede operands on the command line.

Guideline 10: The argument `--` should be accepted as a delimiter indicating the end of options. Any following arguments should be treated as operands, even if they begin with the `'-'` character. The `--` argument should not be used as an option or as an operand.

Guideline 11: The order of different options relative to one another should not matter, unless the options are documented as mutually-exclusive and such an option is documented to override any incompatible options preceding it. If an option that has option-arguments is repeated, the option and option-argument combinations should be interpreted in the order specified on the command line.

Guideline 12: The order of operands may matter and position-related interpretations should be determined on a utility-specific basis.

Guideline 13: For utilities that use operands to represent files to be opened for either reading or writing, the `'-'` operand should be used only to mean standard input (or standard output when it is clear from context that an output file is being specified).

The utilities in the Shell and Utilities volume of IEEE Std 1003.1-2001 that claim conformance to these guidelines shall conform completely to these guidelines as if these guidelines contained the term ''shall'' instead of ''should''. On some implementations, the utilities accept usage in violation of these guidelines for backwards-compatibility as well as accepting the required form.

It is recommended that all future utilities and applications use these guidelines to enhance user portability. The fact that some historical utilities could not be changed (to avoid breaking existing applications) should not deter this future goal.

Chapter 13

Headers

This chapter describes the contents of headers.

Headers contain function prototypes, the definition of symbolic constants, common structures, preprocessor macros, and defined types. Each function in the System Interfaces volume of IEEE Std 1003.1-2001 specifies the headers that an application shall include in order to use that function. In most cases, only one header is required. These headers are present on an application development system; they need not be present on the target execution system.

13.1 Format of Entries

The entries in this chapter are based on a common format as follows. The only sections relating to conformance are the SYNOPSIS and DESCRIPTION.

NAME

This section gives the name or names of the entry and briefly states its purpose.

SYNOPSIS

This section summarizes the use of the entry being described.

DESCRIPTION

This section describes the functionality of the header.

APPLICATION USAGE

This section is informative.

This section gives warnings and advice to application writers about the entry. In the event of conflict between warnings and advice and a normative part of this volume of IEEE Std 1003.1-2001, the normative material is to be taken as correct.

RATIONALE

This section is informative.

This section contains historical information concerning the contents of this volume of IEEE Std 1003.1-2001 and why features were included or discarded by the standard developers.

FUTURE DIRECTIONS

This section is informative.

This section provides comments which should be used as a guide to current thinking; there is not necessarily a commitment to adopt these future directions.

SEE ALSO

This section is informative.

This section gives references to related information.

CHANGE HISTORY

This section is informative.

This section shows the derivation of the entry and any significant changes that have been made to it.

NAME

aio.h — asynchronous input and output (**REALTIME**)

SYNOPSIS

AIO

```
#include <aio.h>
```

DESCRIPTION

The **<aio.h>** header shall define the **aiocb** structure which shall include at least the following members:

`int`	`aio_fildes`	File descriptor.
`off_t`	`aio_offset`	File offset.
`volatile void *`	`aio_buf`	Location of buffer.
`size_t`	`aio_nbytes`	Length of transfer.
`int`	`aio_reqprio`	Request priority offset.
`struct sigevent`	`aio_sigevent`	Signal number and value.
`int`	`aio_lio_opcode`	Operation to be performed.

This header shall also include the following constants:

AIO_ALLDONE
: A return value indicating that none of the requested operations could be canceled since they are already complete.

AIO_CANCELED
: A return value indicating that all requested operations have been canceled.

AIO_NOTCANCELED
: A return value indicating that some of the requested operations could not be canceled since they are in progress.

LIO_NOP
: A *lio_listio*( ) element operation option indicating that no transfer is requested.

LIO_NOWAIT
: A *lio_listio*( ) synchronization operation indicating that the calling thread is to continue execution while the *lio_listio*( ) operation is being performed, and no notification is given when the operation is complete.

LIO_READ
: A *lio_listio*( ) element operation option requesting a read.

LIO_WAIT
: A *lio_listio*( ) synchronization operation indicating that the calling thread is to suspend until the *lio_listio*( ) operation is complete.

LIO_WRITE
: A *lio_listio*( ) element operation option requesting a write.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int      aio_cancel(int, struct aiocb *);
int      aio_error(const struct aiocb *);
int      aio_fsync(int, struct aiocb *);
int      aio_read(struct aiocb *);
ssize_t  aio_return(struct aiocb *);
int      aio_suspend(const struct aiocb *const[], int,
             const struct timespec *);
int      aio_write(struct aiocb *);
int      lio_listio(int, struct aiocb *restrict const[restrict], int,
             struct sigevent *restrict);
```

Inclusion of the **<aio.h>** header may make visible symbols defined in the headers **<fcntl.h>**, **<signal.h>**, **<sys/types.h>**, and **<time.h>**.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<fcntl.h>, **<signal.h>**, **<sys/types.h>**, **<time.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *fsync*( ), *lseek*( ), *read*( ), *write*( )

CHANGE HISTORY

First released in Issue 5. Included for alignment with the POSIX Realtime Extension.

Issue 6

The **<aio.h>** header is marked as part of the Asynchronous Input and Output option.

The description of the constants is expanded.

The **restrict** keyword is added to the prototype for *lio_listio*( ).

NAME

arpa/inet.h — definitions for internet operations

SYNOPSIS

```
#include <arpa/inet.h>
```

DESCRIPTION

The **in_port_t** and **in_addr_t** types shall be defined as described in **<netinet/in.h>**.

The **in_addr** structure shall be defined as described in **<netinet/in.h>**.

IP6 The INET_ADDRSTRLEN and INET6_ADDRSTRLEN macros shall be defined as described in **<netinet/in.h>**.

The following shall either be declared as functions, defined as macros, or both. If functions are declared, function prototypes shall be provided.

```
uint32_t htonl(uint32_t);
uint16_t htons(uint16_t);
uint32_t ntohl(uint32_t);
uint16_t ntohs(uint16_t);
```

The **uint32_t** and **uint16_t** types shall be defined as described in **<inttypes.h>**.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
in_addr_t    inet_addr(const char *);
char        *inet_ntoa(struct in_addr);
const char  *inet_ntop(int, const void *restrict, char *restrict,
                    socklen_t);
int          inet_pton(int, const char *restrict, void *restrict);
```

Inclusion of the **<arpa/inet.h>** header may also make visible all symbols from **<netinet/in.h>** and **<inttypes.h>**.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<netinet/in.h>, **<inttypes.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *htonl*( ), *inet_addr*( )

CHANGE HISTORY

First released in Issue 6. Derived from the XNS, Issue 5.2 specification.

The **restrict** keyword is added to the prototypes for *inet_ntop*( ) and *inet_pton*( ).

NAME

assert.h — verify program assertion

SYNOPSIS

```
#include <assert.h>
```

DESCRIPTION

CX The functionality described on this reference page is aligned with the ISO C standard. Any conflict between the requirements described here and the ISO C standard is unintentional. This volume of IEEE Std 1003.1-2001 defers to the ISO C standard.

The **<assert.h>** header shall define the *assert*( ) macro. It refers to the macro NDEBUG which is not defined in the header. If NDEBUG is defined as a macro name before the inclusion of this header, the *assert*( ) macro shall be defined simply as:

```
#define assert(ignore)((void) 0)
```

Otherwise, the macro behaves as described in *assert*( ).

The *assert*( ) macro shall be redefined according to the current state of NDEBUG each time **<assert.h>** is included.

The *assert*( ) macro shall be implemented as a macro, not as a function. If the macro definition is suppressed in order to access an actual function, the behavior is undefined.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *assert*( )

CHANGE HISTORY

First released in Issue 1. Derived from Issue 1 of the SVID.

Issue 6

The definition of the *assert*( ) macro is changed for alignment with the ISO/IEC 9899:1999 standard.

NAME

complex.h — complex arithmetic

SYNOPSIS

```
#include <complex.h>
```

DESCRIPTION

CX The functionality described on this reference page is aligned with the ISO C standard. Any conflict between the requirements described here and the ISO C standard is unintentional. This volume of IEEE Std 1003.1-2001 defers to the ISO C standard.

The **<complex.h>** header shall define the following macros:

complex	Expands to **_Complex**.
_Complex_I	Expands to a constant expression of type **const float _Complex**, with the value of the imaginary unit (that is, a number i such that $i^2=-1$).
imaginary	Expands to **_Imaginary**.
_Imaginary_I	Expands to a constant expression of type **const float _Imaginary** with the value of the imaginary unit.
I	Expands to either _Imaginary_I or _Complex_I. If _Imaginary_I is not defined, I expands to _Complex_I.

The macros imaginary and _Imaginary_I shall be defined if and only if the implementation supports imaginary types.

An application may undefine and then, perhaps, redefine the complex, imaginary, and I macros.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
double               cabs(double complex);
float                cabsf(float complex);
long double          cabsl(long double complex);
double complex       cacos(double complex);
float complex        cacosf(float complex);
double complex       cacosh(double complex);
float complex        cacoshf(float complex);
long double complex  cacoshl(long double complex);
long double complex  cacosl(long double complex);
double               carg(double complex);
float                cargf(float complex);
long double          cargl(long double complex);
double complex       casin(double complex);
float complex        casinf(float complex);
double complex       casinh(double complex);
float complex        casinhf(float complex);
long double complex  casinhl(long double complex);
long double complex  casinl(long double complex);
double complex       catan(double complex);
float complex        catanf(float complex);
double complex       catanh(double complex);
float complex        catanhf(float complex);
long double complex  catanhl(long double complex);
long double complex  catanl(long double complex);
```



```
7455        double complex       ccos(double complex);
7456        float complex        ccosf(float complex);
7457        double complex       ccosh(double complex);
7458        float complex        ccoshf(float complex);
7459        long double complex  ccoshl(long double complex);
7460        long double complex  ccosl(long double complex);
7461        double complex       cexp(double complex);
7462        float complex        cexpf(float complex);
7463        long double complex  cexpl(long double complex);
7464        double               cimag(double complex);
7465        float                cimagf(float complex);
7466        long double          cimagl(long double complex);
7467        double complex       clog(double complex);
7468        float complex        clogf(float complex);
7469        long double complex  clogl(long double complex);
7470        double complex       conj(double complex);
7471        float complex        conjf(float complex);
7472        long double complex  conjl(long double complex);
7473        double complex       cpow(double complex, double complex);
7474        float complex        cpowf(float complex, float complex);
7475        long double complex  cpowl(long double complex, long double complex);
7476        double complex       cproj(double complex);
7477        float complex        cprojf(float complex);
7478        long double complex  cprojl(long double complex);
7479        double               creal(double complex);
7480        float                crealf(float complex);
7481        long double          creall(long double complex);
7482        double complex       csin(double complex);
7483        float complex        csinf(float complex);
7484        double complex       csinh(double complex);
7485        float complex        csinhf(float complex);
7486        long double complex  csinhl(long double complex);
7487        long double complex  csinl(long double complex);
7488        double complex       csqrt(double complex);
7489        float complex        csqrtf(float complex);
7490        long double complex  csqrtl(long double complex);
7491        double complex       ctan(double complex);
7492        float complex        ctanf(float complex);
7493        double complex       ctanh(double complex);
7494        float complex        ctanhf(float complex);
7495        long double complex  ctanhl(long double complex);
7496        long double complex  ctanl(long double complex);
```

7497 **APPLICATION USAGE**

7498 Values are interpreted as radians, not degrees.

7499 **RATIONALE**

7500 The choice of *I* instead of *i* for the imaginary unit concedes to the widespread use of the
7501 identifier *i* for other purposes. The application can use a different identifier, say *j*, for the
7502 imaginary unit by following the inclusion of the **<complex.h>** header with:

```
7503        #undef I
7504        #define j _Imaginary_I
```

An *I* suffix to designate imaginary constants is not required, as multiplication by *I* provides a sufficiently convenient and more generally useful notation for imaginary terms. The corresponding real type for the imaginary unit is **float**, so that use of *I* for algorithmic or notational convenience will not result in widening types.

On systems with imaginary types, the application has the ability to control whether use of the macro I introduces an imaginary type, by explicitly defining I to be _Imaginary_I or _Complex_I. Disallowing imaginary types is useful for some applications intended to run on implementations without support for such types.

The macro _Imaginary_I provides a test for whether imaginary types are supported.

The *cis*( ) function (*cos*(*x*) + *I***sin*(*x*)) was considered but rejected because its implementation is easy and straightforward, even though some implementations could compute sine and cosine more efficiently in tandem.

FUTURE DIRECTIONS

The following function names and the same names suffixed with *f* or *l* are reserved for future use, and may be added to the declarations in the **<complex.h>** header.

cerf( )	*cexpm1*( )	*clog2*( )
cerfc( )	*clog10*( )	*clgamma*( )
cexp2( )	*clog1p*( )	*ctgamma*( )

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *cabs*( ), *cacos*( ), *cacosh*( ), *carg*( ), *casin*( ), *casinh*( ), *catan*( ), *catanh*( ), *ccos*( ), *ccosh*( ), *cexp*( ), *cimag*( ), *clog*( ), *conj*( ), *cpow*( ), *cproj*( ), *creal*( ), *csin*( ), *csinh*( ), *csqrt*( ), *ctan*( ), *ctanh*( )

CHANGE HISTORY

First released in Issue 6. Included for alignment with the ISO / IEC 9899: 1999 standard.

NAME

cpio.h — cpio archive values

SYNOPSIS

XSI
```
#include <cpio.h>
```

DESCRIPTION

Values needed by the *c_mode* field of the *cpio* archive format are described as follows:

Name	Description	Value (Octal)
C_IRUSR	Read by owner.	0000400
C_IWUSR	Write by owner.	0000200
C_IXUSR	Execute by owner.	0000100
C_IRGRP	Read by group.	0000040
C_IWGRP	Write by group.	0000020
C_IXGRP	Execute by group.	0000010
C_IROTH	Read by others.	0000004
C_IWOTH	Write by others.	0000002
C_IXOTH	Execute by others.	0000001
C_ISUID	Set user ID.	0004000
C_ISGID	Set group ID.	0002000
C_ISVTX	On directories, restricted deletion flag.	0001000
C_ISDIR	Directory.	0040000
C_ISFIFO	FIFO.	0010000
C_ISREG	Regular file.	0100000
C_ISBLK	Block special.	0060000
C_ISCHR	Character special.	0020000
C_ISCTG	Reserved.	0110000
C_ISLNK	Symbolic link.	0120000
C_ISSOCK	Socket.	0140000

The header shall define the symbolic constant:

```
MAGIC    "070707"
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The Shell and Utilities volume of IEEE Std 1003.1-2001, *pax*

CHANGE HISTORY

First released in the Headers Interface, Issue 3 specification. Derived from the POSIX.1-1988 standard.

Issue 6

The SEE ALSO is updated to refer to *pax*, since the *cpio* utility is not included in the Shell and Utilities volume of IEEE Std 1003.1-2001.

NAME

ctype.h — character types

SYNOPSIS

```
#include <ctype.h>
```

DESCRIPTION

CX Some of the functionality described on this reference page extends the ISO C standard. Applications shall define the appropriate feature test macro (see the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.2, The Compilation Environment) to enable the visibility of these symbols in this header.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int   isalnum(int);
int   isalpha(int);
XSI int   isascii(int);
int   isblank(int);
int   iscntrl(int);
int   isdigit(int);
int   isgraph(int);
int   islower(int);
int   isprint(int);
int   ispunct(int);
int   isspace(int);
int   isupper(int);
int   isxdigit(int);
XSI int   toascii(int);
int   tolower(int);
int   toupper(int);
```

The following are defined as macros:

```
XSI int   _toupper(int);
int   _tolower(int);
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<locale.h>, the System Interfaces volume of IEEE Std 1003.1-2001, *isalnum*( ), *isalpha*( ), *isascii*( ), *iscntrl*( ), *isdigit*( ), *isgraph*( ), *islower*( ), *isprint*( ), *ispunct*( ), *isspace*( ), *isupper*( ), *isxdigit*( ), *mblen*( ), *mbstowcs*( ), *mbtowc*( ), *setlocale*( ), *toascii*( ), *tolower*( ), *_tolower*( ), *toupper*( ), *_toupper*( ), *wcstombs*( ), *wctomb*( )

CHANGE HISTORY

First released in Issue 1. Derived from Issue 1 of the SVID.

Issue 6

Extensions beyond the ISO C standard are marked.

NAME

dirent.h — format of directory entries

SYNOPSIS

```
#include <dirent.h>
```

DESCRIPTION

The internal format of directories is unspecified.

The **<dirent.h>** header shall define the following type:

DIR A type representing a directory stream.

It shall also define the structure **dirent** which shall include the following members:

XSI
```
ino_t  d_ino      File serial number.
char   d_name[]   Name of entry.
```

XSI The type **ino_t** shall be defined as described in **<sys/types.h>**.

The character array *d_name* is of unspecified size, but the number of bytes preceding the terminating null byte shall not exceed {NAME_MAX}.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int            closedir(DIR *);
DIR           *opendir(const char *);
struct dirent *readdir(DIR *);
```
TSF
```
int            readdir_r(DIR *restrict, struct dirent *restrict,
                   struct dirent **restrict);
```
```
void           rewinddir(DIR *);
```
XSI
```
void           seekdir(DIR *, long);
long           telldir(DIR *);
```

APPLICATION USAGE

None.

RATIONALE

Information similar to that in the **<dirent.h>** header is contained in a file **<sys/dir.h>** in 4.2 BSD and 4.3 BSD. The equivalent in these implementations of **struct dirent** from this volume of IEEE Std 1003.1-2001 is **struct direct**. The filename was changed because the name **<sys/dir.h>** was also used in earlier implementations to refer to definitions related to the older access method; this produced name conflicts. The name of the structure was changed because this volume of IEEE Std 1003.1-2001 does not completely define what is in the structure, so it could be different on some implementations from **struct direct**.

The name of an array of **char** of an unspecified size should not be used as an lvalue. Use of:

```
sizeof(d_name)
```

is incorrect; use:

```
strlen(d_name)
```

instead.

The array of **char** *d_name* is not a fixed size. Implementations may need to declare **struct dirent** with an array size for *d_name* of 1, but the actual number of characters provided matches (or only slightly exceeds) the length of the filename.

FUTURE DIRECTIONS

None.

SEE ALSO

<sys/types.h>, the System Interfaces volume of IEEE Std 1003.1-2001, *closedir*( ), *opendir*( ), *readdir*( ), *readdir_r*( ), *rewinddir*( ), *seekdir*( ), *telldir*( )

CHANGE HISTORY

First released in Issue 2.

Issue 5

The DESCRIPTION is updated for alignment with the POSIX Threads Extension.

Issue 6

The Open Group Corrigendum U026/7 is applied, correcting the prototype for *readdir_r*( ).

The **restrict** keyword is added to the prototype for *readdir_r*( ).

NAME

dlfcn.h — dynamic linking

SYNOPSIS

XSI

```
#include <dlfcn.h>
```

DESCRIPTION

The **<dlfcn.h>** header shall define at least the following macros for use in the construction of a *dlopen*( ) *mode* argument:

RTLD_LAZY	Relocations are performed at an implementation-defined time.
RTLD_NOW	Relocations are performed when the object is loaded.
RTLD_GLOBAL	All symbols are available for relocation processing of other modules.
RTLD_LOCAL	All symbols are not made available for relocation processing by other modules.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int    dlclose(void *);
char  *dlerror(void);
void  *dlopen(const char *, int);
void  *dlsym(void *restrict, const char *restrict);
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *dlopen*( ), *dlclose*( ), *dlsym*( ), *dlerror*( )

CHANGE HISTORY

First released in Issue 5.

Issue 6

The **restrict** keyword is added to the prototype for *dlsym*( ).

NAME

errno.h — system error numbers

SYNOPSIS

```
#include <errno.h>
```

DESCRIPTION

CX Some of the functionality described on this reference page extends the ISO C standard. Any conflict between the requirements described here and the ISO C standard is unintentional. This volume of IEEE Std 1003.1-2001 defers to the ISO C standard.

CX The ISO C standard only requires the symbols [EDOM], [EILSEQ], and [ERANGE] to be defined.

The **<errno.h>** header shall provide a declaration for *errno* and give positive values for the following symbolic constants. Their values shall be unique except as noted below.

[E2BIG]	Argument list too long.
[EACCES]	Permission denied.
[EADDRINUSE]	Address in use.
[EADDRNOTAVAIL]	Address not available.
[EAFNOSUPPORT]	Address family not supported.
[EAGAIN]	Resource unavailable, try again (may be the same value as [EWOULDBLOCK]).
[EALREADY]	Connection already in progress.
[EBADF]	Bad file descriptor.
[EBADMSG]	Bad message.
[EBUSY]	Device or resource busy.
[ECANCELED]	Operation canceled.
[ECHILD]	No child processes.
[ECONNABORTED]	Connection aborted.
[ECONNREFUSED]	Connection refused.
[ECONNRESET]	Connection reset.
[EDEADLK]	Resource deadlock would occur.
[EDESTADDRREQ]	Destination address required.
[EDOM]	Mathematics argument out of domain of function.
[EDQUOT]	Reserved.
[EEXIST]	File exists.
[EFAULT]	Bad address.
[EFBIG]	File too large.
[EHOSTUNREACH]	Host is unreachable.
[EIDRM]	Identifier removed.
[EILSEQ]	Illegal byte sequence.

7743		[EINPROGRESS]	Operation in progress.
7744		[EINTR]	Interrupted function.
7745		[EINVAL]	Invalid argument.
7746		[EIO]	I/O error.
7747		[EISCONN]	Socket is connected.
7748		[EISDIR]	Is a directory.
7749		[ELOOP]	Too many levels of symbolic links.
7750		[EMFILE]	Too many open files.
7751		[EMLINK]	Too many links.
7752		[EMSGSIZE]	Message too large.
7753		[EMULTIHOP]	Reserved.
7754		[ENAMETOOLONG]	Filename too long.
7755		[ENETDOWN]	Network is down.
7756		[ENETRESET]	Connection aborted by network.
7757		[ENETUNREACH]	Network unreachable.
7758		[ENFILE]	Too many files open in system.
7759		[ENOBUFS]	No buffer space available.
7760	XSR	[ENODATA]	No message is available on the STREAM head read queue.
7761		[ENODEV]	No such device.
7762		[ENOENT]	No such file or directory.
7763		[ENOEXEC]	Executable file format error.
7764		[ENOLCK]	No locks available.
7765		[ENOLINK]	Reserved.
7766		[ENOMEM]	Not enough space.
7767		[ENOMSG]	No message of the desired type.
7768		[ENOPROTOOPT]	Protocol not available.
7769		[ENOSPC]	No space left on device.
7770	XSR	[ENOSR]	No STREAM resources.
7771	XSR	[ENOSTR]	Not a STREAM.
7772		[ENOSYS]	Function not supported.
7773		[ENOTCONN]	The socket is not connected.
7774		[ENOTDIR]	Not a directory.
7775		[ENOTEMPTY]	Directory not empty.
7776		[ENOTSOCK]	Not a socket.

[ENOTSUP]	Not supported.
[ENOTTY]	Inappropriate I/O control operation.
[ENXIO]	No such device or address.
[EOPNOTSUPP]	Operation not supported on socket.
[EOVERFLOW]	Value too large to be stored in data type.
[EPERM]	Operation not permitted.
[EPIPE]	Broken pipe.
[EPROTO]	Protocol error.
[EPROTONOSUPPORT]	Protocol not supported.
[EPROTOTYPE]	Protocol wrong type for socket.
[ERANGE]	Result too large.
[EROFS]	Read-only file system.
[ESPIPE]	Invalid seek.
[ESRCH]	No such process.
[ESTALE]	Reserved.
XSR [ETIME]	Stream *ioctl*( ) timeout.
[ETIMEDOUT]	Connection timed out.
[ETXTBSY]	Text file busy.
[EWOULDBLOCK]	Operation would block (may be the same value as [EAGAIN]).
[EXDEV]	Cross-device link.

APPLICATION USAGE

Additional error numbers may be defined on conforming systems; see the System Interfaces volume of IEEE Std 1003.1-2001.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, Section 2.3, Error Numbers

CHANGE HISTORY

First released in Issue 1. Derived from Issue 1 of the SVID.

Issue 5

Updated for alignment with the POSIX Realtime Extension.

Issue 6

The following new requirements on POSIX implementations derive from alignment with the Single UNIX Specification:

- The majority of the error conditions previously marked as extensions are now mandatory, except for the STREAMS-related error conditions.

Values for *errno* are now required to be distinct positive values rather than non-zero values. This change is for alignment with the ISO / IEC 9899: 1999 standard.

7818 **NAME**

7819 fcntl.h — file control options

7820 **SYNOPSIS**

7821 `#include <fcntl.h>`

7822 **DESCRIPTION**

7823 The **<fcntl.h>** header shall define the following requests and arguments for use by the functions
7824 *fcntl*( ) and *open*( ).

7825 Values for *cmd* used by *fcntl*( ) (the following values are unique) are as follows:

7826 F_DUPFD Duplicate file descriptor.

7827 F_GETFD Get file descriptor flags.

7828 F_SETFD Set file descriptor flags.

7829 F_GETFL Get file status flags and file access modes.

7830 F_SETFL Set file status flags.

7831 F_GETLK Get record locking information.

7832 F_SETLK Set record locking information.

7833 F_SETLKW Set record locking information; wait if blocked.

7834 F_GETOWN Get process or process group ID to receive SIGURG signals.

7835 F_SETOWN Set process or process group ID to receive SIGURG signals.

7836 File descriptor flags used for *fcntl*( ) are as follows:

7837 FD_CLOEXEC Close the file descriptor upon execution of an *exec* family function.

7838 Values for *l_type* used for record locking with *fcntl*( ) (the following values are unique) are as
7839 follows:

7840 F_RDLCK Shared or read lock.

7841 F_UNLCK Unlock.

7842 F_WRLCK Exclusive or write lock.

7843 XSI The values used for *l_whence*, SEEK_SET, SEEK_CUR, and SEEK_END shall be defined as
7844 described in **<unistd.h>**.

7845 The following values are file creation flags and are used in the *oflag* value to *open*( ). They shall
7846 be bitwise-distinct.

7847 O_CREAT Create file if it does not exist.

7848 O_EXCL Exclusive use flag.

7849 O_NOCTTY Do not assign controlling terminal.

7850 O_TRUNC Truncate flag.

7851 File status flags used for *open*( ) and *fcntl*( ) are as follows:

7852 O_APPEND Set append mode.

7853 SIO O_DSYNC Write according to synchronized I/O data integrity completion.

7854 O_NONBLOCK Non-blocking mode.

SIO O_RSYNC Synchronized read I/O operations.

O_SYNC Write according to synchronized I/O file integrity completion.

Mask for use with file access modes is as follows:

O_ACCMODE Mask for file access modes.

File access modes used for *open*( ) and *fcntl*( ) are as follows:

O_RDONLY Open for reading only.

O_RDWR Open for reading and writing.

O_WRONLY Open for writing only.

XSI The symbolic names for file modes for use as values of **mode_t** shall be defined as described in **<sys/stat.h>**.

ADV Values for *advice* used by *posix_fadvise*( ) are as follows:

POSIX_FADV_NORMAL
The application has no advice to give on its behavior with respect to the specified data. It is the default characteristic if no advice is given for an open file.

POSIX_FADV_SEQUENTIAL
The application expects to access the specified data sequentially from lower offsets to higher offsets.

POSIX_FADV_RANDOM
The application expects to access the specified data in a random order.

POSIX_FADV_WILLNEED
The application expects to access the specified data in the near future.

POSIX_FADV_DONTNEED
The application expects that it will not access the specified data in the near future.

POSIX_FADV_NOREUSE
The application expects to access the specified data once and then not reuse it thereafter.

The structure **flock** describes a file lock. It shall include the following members:

```
short  l_type    Type of lock; F_RDLCK, F_WRLCK, F_UNLCK.
short  l_whence  Flag for starting offset.
off_t  l_start   Relative offset in bytes.
off_t  l_len     Size; if 0 then until EOF.
pid_t  l_pid     Process ID of the process holding the lock; returned with F_GETLK.
```

The **mode_t**, **off_t**, and **pid_t** types shall be defined as described in **<sys/types.h>**.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int  creat(const char *, mode_t);
int  fcntl(int, int, ...);
int  open(const char *, int, ...);
ADV int  posix_fadvise(int, off_t, off_t, int);                    2
int  posix_fallocate(int, off_t, off_t);                           2
```


7896 XSI Inclusion of the **<fcntl.h>** header may also make visible all symbols from **<sys/stat.h>** and
7897 **<unistd.h>**.

7898 **APPLICATION USAGE**

7899 None.

7900 **RATIONALE**

7901 None.

7902 **FUTURE DIRECTIONS**

7903 None.

7904 **SEE ALSO**

7905 **<sys/stat.h>**, **<sys/types.h>**, **<unistd.h>**, the System Interfaces volume of IEEE Std 1003.1-2001,
7906 *creat*( ), *exec*, *fcntl*( ), *open*( ), *posix_fadvise*( ), *posix_fallocate*( ), *posix_madvise*( )

7907 **CHANGE HISTORY**

7908 First released in Issue 1. Derived from Issue 1 of the SVID.

7909 **Issue 5**

7910 The DESCRIPTION is updated for alignment with the POSIX Realtime Extension.

7911 **Issue 6**

7912 The following changes are made for alignment with the ISO POSIX-1: 1996 standard:

7913 • O_DSYNC and O_RSYNC are marked as part of the Synchronized Input and Output option.

7914 The following new requirements on POSIX implementations derive from alignment with the
7915 Single UNIX Specification:

7916 • The definition of the **mode_t**, **off_t**, and **pid_t** types is mandated.

7917 The F_GETOWN and F_SETOWN values are added for sockets.

7918 The *posix_fadvise*( ), *posix_fallocate*( ), and *posix_madvise*( ) functions are added for alignment with
7919 IEEE Std 1003.1d-1999.

7920 IEEE PASC Interpretation 1003.1 #102 is applied, moving the prototype for *posix_madvise*( ) to
7921 **<sys/mman.h>**.

7922 IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/18 is applied, updating the protoypes for 2
7923 *posix_fadvise*( ) and *posix_fallocate*( ) to be large file-aware, using **off_t** instead of **size_t**. 2

7924 **NAME**

7925 fenv.h — floating-point environment

7926 **SYNOPSIS**

7927 `#include <fenv.h>`

7928 **DESCRIPTION**

7929 CX The functionality described on this reference page is aligned with the ISO C standard. Any
7930 conflict between the requirements described here and the ISO C standard is unintentional. This
7931 volume of IEEE Std 1003.1-2001 defers to the ISO C standard.

7932 The **<fenv.h>** header shall define the following data types through **typedef**:

7933 **fenv_t** Represents the entire floating-point environment. The floating-point environment
7934 refers collectively to any floating-point status flags and control modes supported
7935 by the implementation.

7936 **fexcept_t** Represents the floating-point status flags collectively, including any status the
7937 implementation associates with the flags. A floating-point status flag is a system
7938 variable whose value is set (but never cleared) when a floating-point exception is
7939 raised, which occurs as a side effect of exceptional floating-point arithmetic to
7940 provide auxiliary information. A floating-point control mode is a system variable
7941 whose value may be set by the user to affect the subsequent behavior of floating-
7942 point arithmetic.

7943 The **<fenv.h>** header shall define the following constants if and only if the implementation
7944 supports the floating-point exception by means of the floating-point functions *feclearexcept*( ),
7945 *fegetexceptflag*( ), *feraiseexcept*( ), *fesetexceptflag*( ), and *fetestexcept*( ). Each expands to an integer
7946 constant expression with values such that bitwise-inclusive ORs of all combinations of the
7947 constants result in distinct values.

7948 FE_DIVBYZERO
7949 FE_INEXACT
7950 FE_INVALID
7951 FE_OVERFLOW
7952 FE_UNDERFLOW

7953 The **<fenv.h>** header shall define the following constant, which is simply the bitwise-inclusive
7954 OR of all floating-point exception constants defined above:

7955 FE_ALL_EXCEPT

7956 The **<fenv.h>** header shall define the following constants if and only if the implementation
7957 supports getting and setting the represented rounding direction by means of the *fegetround*( )
7958 and *fesetround*( ) functions. Each expands to an integer constant expression whose values are
7959 distinct non-negative vales.

7960 FE_DOWNWARD
7961 FE_TONEAREST
7962 FE_TOWARDZERO
7963 FE_UPWARD

7964 The **<fenv.h>** header shall define the following constant, which represents the default floating-
7965 point environment (that is, the one installed at program startup) and has type pointer to const-
7966 qualified **fenv_t**. It can be used as an argument to the functions within the **<fenv.h>** header that
7967 manage the floating-point environment.

7968 FE_DFL_ENV

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int  feclearexcept(int);
int  fegetexceptflag(fexcept_t *, int);
int  feraiseexcept(int);
int  fesetexceptflag(const fexcept_t *, int);
int  fetestexcept(int);
int  fegetround(void);
int  fesetround(int);
int  fegetenv(fenv_t *);
int  feholdexcept(fenv_t *);
int  fesetenv(const fenv_t *);
int  feupdateenv(const fenv_t *);
```

The FENV_ACCESS pragma provides a means to inform the implementation when an application might access the floating-point environment to test floating-point status flags or run under non-default floating-point control modes. The pragma shall occur either outside external declarations or preceding all explicit declarations and statements inside a compound statement. When outside external declarations, the pragma takes effect from its occurrence until another FENV_ACCESS pragma is encountered, or until the end of the translation unit. When inside a compound statement, the pragma takes effect from its occurrence until another FENV_ACCESS pragma is encountered (including within a nested compound statement), or until the end of the compound statement; at the end of a compound statement the state for the pragma is restored to its condition just before the compound statement. If this pragma is used in any other context, the behavior is undefined. If part of an application tests floating-point status flags, sets floating-point control modes, or runs under non-default mode settings, but was translated with the state for the FENV_ACCESS pragma off, the behavior is undefined. The default state (on or off) for the pragma is implementation-defined. (When execution passes from a part of the application translated with FENV_ACCESS off to a part translated with FENV_ACCESS on, the state of the floating-point status flags is unspecified and the floating-point control modes have their default settings.)

APPLICATION USAGE

This header is designed to support the floating-point exception status flags and directed-rounding control modes required by the IEC 60559:1989 standard, and other similar floating-point state information. Also it is designed to facilitate code portability among all systems.

Certain application programming conventions support the intended model of use for the floating-point environment:

- A function call does not alter its caller's floating-point control modes, clear its caller's floating-point status flags, nor depend on the state of its caller's floating-point status flags unless the function is so documented.
- A function call is assumed to require default floating-point control modes, unless its documentation promises otherwise.
- A function call is assumed to have the potential for raising floating-point exceptions, unless its documentation promises otherwise.

With these conventions, an application can safely assume default floating-point control modes (or be unaware of them). The responsibilities associated with accessing the floating-point environment fall on the application that does so explicitly.

Even though the rounding direction macros may expand to constants corresponding to the values of FLT_ROUNDS, they are not required to do so.

For example:

```
#include <fenv.h>
void f(double x)
{
    #pragma STDC FENV_ACCESS ON
    void g(double);
    void h(double);
    /* ... */
    g(x + 1);
    h(x + 1);
    /* ... */
}
```

If the function *g*() might depend on status flags set as a side effect of the first *x*+1, or if the second *x*+1 might depend on control modes set as a side effect of the call to function *g*(), then the application shall contain an appropriately placed invocation as follows:

```
#pragma STDC FENV_ACCESS ON
```

RATIONALE

The fexcept_t Type

fexcept_t does not have to be an integer type. Its values must be obtained by a call to *fegetexceptflag*(), and cannot be created by logical operations from the exception macros. An implementation might simply implement **fexcept_t** as an **int** and use the representations reflected by the exception macros, but is not required to; other representations might contain extra information about the exceptions. **fexcept_t** might be a **struct** with a member for each exception (that might hold the address of the first or last floating-point instruction that caused that exception). The ISO/IEC 9899:1999 standard makes no claims about the internals of an **fexcept_t**, and so the user cannot inspect it.

Exception and Rounding Macros

Macros corresponding to unsupported modes and rounding directions are not defined by the implementation and must not be defined by the application. An application might use **#ifdef** to test for this.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *feclearexcept*(), *fegetenv*(), *fegetexceptflag*(), *fegetround*(), *feholdexcept*(), *feraiseexcept*(), *fesetenv*(), *fesetexceptflag*(), *fesetround*(), *fetestexcept*(), *feupdateenv*()

CHANGE HISTORY

First released in Issue 6. Included for alignment with the ISO/IEC 9899:1999 standard.

The return types for *feclearexcept*(), *fegetexceptflag*(), *feraiseexcept*(), *fesetexceptflag*(), *fegetenv*(), *fesetenv*(), and *feupdateenv*() are changed from **void** to **int** for alignment with the ISO/IEC 9899:1999 standard, Defect Report 202.

NAME

float.h — floating types

SYNOPSIS

```
#include <float.h>
```

DESCRIPTION

CX The functionality described on this reference page is aligned with the ISO C standard. Any conflict between the requirements described here and the ISO C standard is unintentional. This volume of IEEE Std 1003.1-2001 defers to the ISO C standard.

The characteristics of floating types are defined in terms of a model that describes a representation of floating-point numbers and values that provide information about an implementation's floating-point arithmetic.

The following parameters are used to define the model for each floating-point type:

s Sign (±1).

b Base or radix of exponent representation (an integer >1).

e Exponent (an integer between a minimum $e_{\min}$ and a maximum $e_{\max}$).

p Precision (the number of base–*b* digits in the significand).

f_k Non-negative integers less than *b* (the significand digits).

A floating-point number *x* is defined by the following model:

$$x = sb^e \sum_{k=1}^{p} f_k\, b^{-k},\ e_{\min} \le e \le e_{\max}$$

In addition to normalized floating-point numbers ($f_1>0$ if $x\neq0$), floating types may be able to contain other kinds of floating-point numbers, such as subnormal floating-point numbers ($x\neq0$, $e=e_{\min}$, $f_1=0$) and unnormalized floating-point numbers ($x\neq0$, $e>e_{\min}$, $f_1=0$), and values that are not floating-point numbers, such as infinities and NaNs. A *NaN* is an encoding signifying Not-a-Number. A *quiet NaN* propagates through almost every arithmetic operation without raising a floating-point exception; a *signaling NaN* generally raises a floating-point exception when occurring as an arithmetic operand.

The accuracy of the floating-point operations (`'+'`, `'–'`, `'*'`, `'/'`) and of the library functions in **<math.h>** and **<complex.h>** that return floating-point results is implementation-defined. The implementation may state that the accuracy is unknown.

All integer values in the **<float.h>** header, except FLT_ROUNDS, shall be constant expressions suitable for use in **#if** preprocessing directives; all floating values shall be constant expressions. All except DECIMAL_DIG, FLT_EVAL_METHOD, FLT_RADIX, and FLT_ROUNDS have separate names for all three floating-point types. The floating-point model representation is provided for all values except FLT_EVAL_METHOD and FLT_ROUNDS.

The rounding mode for floating-point addition is characterized by the implementation-defined value of FLT_ROUNDS:

–1 Indeterminable.

0 Toward zero.

1 To nearest.

2 Toward positive infinity.

3 Toward negative infinity.

All other values for FLT_ROUNDS characterize implementation-defined rounding behavior.

The values of operations with floating operands and values subject to the usual arithmetic conversions and of floating constants are evaluated to a format whose range and precision may be greater than required by the type. The use of evaluation formats is characterized by the implementation-defined value of FLT_EVAL_METHOD:

−1 Indeterminable.

0 Evaluate all operations and constants just to the range and precision of the type.

1 Evaluate operations and constants of type **float** and **double** to the range and precision of the **double** type; evaluate **long double** operations and constants to the range and precision of the **long double** type.

2 Evaluate all operations and constants to the range and precision of the **long double** type.

All other negative values for FLT_EVAL_METHOD characterize implementation-defined behavior.

The values given in the following list shall be defined as constant expressions with implementation-defined values that are greater or equal in magnitude (absolute value) to those shown, with the same sign.

- Radix of exponent representation, *b*.

  FLT_RADIX 2

- Number of base-FLT_RADIX digits in the floating-point significand, *p*.

  FLT_MANT_DIG

  DBL_MANT_DIG

  LDBL_MANT_DIG

- Number of decimal digits, *n*, such that any floating-point number in the widest supported floating type with $p_{\max}$ radix *b* digits can be rounded to a floating-point number with *n* decimal digits and back again without change to the value.

$$\begin{cases} p_{\max} \log_{10} b & \text{if } b \text{ is a power of } 10 \\ \left\lceil 1 + p_{\max} \log_{10} b \right\rceil & \text{otherwise} \end{cases}$$

  DECIMAL_DIG 10

- Number of decimal digits, *q*, such that any floating-point number with *q* decimal digits can be rounded into a floating-point number with *p* radix *b* digits and back again without change to the *q* decimal digits.

$$\begin{cases} p \log_{10} b & \text{if } b \text{ is a power of } 10 \\ \left\lfloor (p-1) \log_{10} b \right\rfloor & \text{otherwise} \end{cases}$$

  FLT_DIG 6

  DBL_DIG 10

8132 LDBL_DIG 10

8133 • Minimum negative integer such that FLT_RADIX raised to that power minus 1 is a
8134 normalized floating-point number, $e_{\min}$.

8135 FLT_MIN_EXP

8136 DBL_MIN_EXP

8137 LDBL_MIN_EXP

8138 • Minimum negative integer such that 10 raised to that power is in the range of normalized
8139 floating-point numbers.

8140 $$\left\lceil \log_{10} b^{e_{\min}-1} \right\rceil$$

8141 FLT_MIN_10_EXP –37

8142 DBL_MIN_10_EXP –37

8143 LDBL_MIN_10_EXP –37

8144 • Maximum integer such that FLT_RADIX raised to that power minus 1 is a representable
8145 finite floating-point number, $e_{\max}$.

8146 FLT_MAX_EXP

8147 DBL_MAX_EXP

8148 LDBL_MAX_EXP

8149 • Maximum integer such that 10 raised to that power is in the range of representable finite
8150 floating-point numbers.

8151 $$\left\lfloor \log_{10}((1 - b^{-p})\, b^{e_{\max}}) \right\rfloor$$

8152 FLT_MAX_10_EXP +37

8153 DBL_MAX_10_EXP +37

8154 LDBL_MAX_10_EXP +37

8155 The values given in the following list shall be defined as constant expressions with
8156 implementation-defined values that are greater than or equal to those shown:

8157 • Maximum representable finite floating-point number.

8158 $$(1 - b^{-p})\, b^{e_{\max}}$$

8159 FLT_MAX 1E+37

8160 DBL_MAX 1E+37

8161 LDBL_MAX 1E+37

8162 The values given in the following list shall be defined as constant expressions with
8163 implementation-defined (positive) values that are less than or equal to those shown:

8164 • The difference between 1 and the least value greater than 1 that is representable in the given
8165 floating-point type, b^{1-p}.

8166 FLT_EPSILON 1E–5

8167 DBL_EPSILON 1E–9

8168 LDBL_EPSILON 1E–9

8169 • Minimum normalized positive floating-point number, $b^{e_{min}-1}$.

8170 FLT_MIN 1E–37

8171 DBL_MIN 1E–37

8172 LDBL_MIN 1E–37

8173 **APPLICATION USAGE**

8174 None.

8175 **RATIONALE**

8176 None.

8177 **FUTURE DIRECTIONS**

8178 None.

8179 **SEE ALSO**

8180 **<complex.h>**, **<math.h>**

8181 **CHANGE HISTORY**

8182 First released in Issue 4. Derived from the ISO C standard.

8183 **Issue 6**

8184 The description of the operations with floating-point values is updated for alignment with the
8185 ISO / IEC 9899: 1999 standard.

NAME

fmtmsg.h — message display structures

SYNOPSIS

XSI
```
#include <fmtmsg.h>
```

DESCRIPTION

The **<fmtmsg.h>** header shall define the following macros, which expand to constant integer expressions:

MM_HARD	Source of the condition is hardware.
MM_SOFT	Source of the condition is software.
MM_FIRM	Source of the condition is firmware.
MM_APPL	Condition detected by application.
MM_UTIL	Condition detected by utility.
MM_OPSYS	Condition detected by operating system.
MM_RECOVER	Recoverable error.
MM_NRECOV	Non-recoverable error.
MM_HALT	Error causing application to halt.
MM_ERROR	Application has encountered a non-fatal fault.
MM_WARNING	Application has detected unusual non-error condition.
MM_INFO	Informative message.
MM_NOSEV	No severity level provided for the message.
MM_PRINT	Display message on standard error.
MM_CONSOLE	Display message on system console.

The table below indicates the null values and identifiers for *fmtmsg*( ) arguments. The **<fmtmsg.h>** header shall define the macros in the **Identifier** column, which expand to constant expressions that expand to expressions of the type indicated in the **Type** column:

Argument	Type	Null-Value	Identifier
label	**char ***	(**char***)0	MM_NULLLBL
severity	**int**	0	MM_NULLSEV
class	**long**	**0L**	MM_NULLMC
text	**char ***	(**char***)0	MM_NULLTXT
action	**char ***	(**char***)0	MM_NULLACT
tag	**char ***	(**char***)0	MM_NULLTAG

The **<fmtmsg.h>** header shall also define the following macros for use as return values for *fmtmsg*( ):

MM_OK	The function succeeded.
MM_NOTOK	The function failed completely.
MM_NOMSG	The function was unable to generate a message on standard error, but otherwise succeeded.

8226 MM_NOCON The function was unable to generate a console message, but otherwise
8227 succeeded.

8228 The following shall be declared as a function and may also be defined as a macro. A function
8229 prototype shall be provided.

```
8230 int fmtmsg(long, const char *, int,
8231     const char *, const char *, const char *);
```

8232 **APPLICATION USAGE**

8233 None.

8234 **RATIONALE**

8235 None.

8236 **FUTURE DIRECTIONS**

8237 None.

8238 **SEE ALSO**

8239 The System Interfaces volume of IEEE Std 1003.1-2001, *fmtmsg*( )

8240 **CHANGE HISTORY**

8241 First released in Issue 4, Version 2.

NAME

fnmatch.h — filename-matching types

SYNOPSIS

```
#include <fnmatch.h>
```

DESCRIPTION

The **<fnmatch.h>** header shall define the following constants:

FNM_NOMATCH	The string does not match the specified pattern.
FNM_PATHNAME	Slash in *string* only matches slash in *pattern*.
FNM_PERIOD	Leading period in *string* must be exactly matched by period in *pattern*.
FNM_NOESCAPE	Disable backslash escaping.
OB XSI FNM_NOSYS	Reserved.

The following shall be declared as a function and may also be defined as a macro. A function prototype shall be provided.

```
int fnmatch(const char *, const char *, int);
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *fnmatch*( ), the Shell and Utilities volume of IEEE Std 1003.1-2001

CHANGE HISTORY

First released in Issue 4. Derived from the ISO POSIX-2 standard.

Issue 6

The constant FNM_NOSYS is marked obsolescent.

8269 **NAME**

8270 ftw.h — file tree traversal

8271 **SYNOPSIS**

8272 XSI
```
#include <ftw.h>
```
8273

8274 **DESCRIPTION**

8275 The **<ftw.h>** header shall define the **FTW** structure that includes at least the following members:

8276
```
int  base
```
8277
```
int  level
```

8278 The **<ftw.h>** header shall define macros for use as values of the third argument to the
8279 application-supplied function that is passed as the second argument to *ftw*( ) and *nftw*( ):

8280 FTW_F File.

8281 FTW_D Directory.

8282 FTW_DNR Directory without read permission.

8283 FTW_DP Directory with subdirectories visited.

8284 FTW_NS Unknown type; *stat*( ) failed.

8285 FTW_SL Symbolic link.

8286 FTW_SLN Symbolic link that names a nonexistent file.

8287 The **<ftw.h>** header shall define macros for use as values of the fourth argument to *nftw*( ):

8288 FTW_PHYS Physical walk, does not follow symbolic links. Otherwise, *nftw*( ) follows
8289 links but does not walk down any path that crosses itself.

8290 FTW_MOUNT The walk does not cross a mount point.

8291 FTW_DEPTH All subdirectories are visited before the directory itself.

8292 FTW_CHDIR The walk changes to each directory before reading it.

8293 The following shall be declared as functions and may also be defined as macros. Function
8294 prototypes shall be provided.

8295
```
int ftw(const char *, int (*)(const char *, const struct stat *,
8296     int), int);
8297 int nftw(const char *, int (*)(const char *, const struct stat *,
8298     int, struct FTW*), int, int);
```

8299 The **<ftw.h>** header shall define the **stat** structure and the symbolic names for *st_mode* and the
8300 file type test macros as described in **<sys/stat.h>**.

8301 Inclusion of the **<ftw.h>** header may also make visible all symbols from **<sys/stat.h>**.

8302 **APPLICATION USAGE**

8303 None.

8304 **RATIONALE**

8305 None.

8306 **FUTURE DIRECTIONS**

8307 None.

8308 **SEE ALSO**

8309 **<sys/stat.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *ftw*( ), *nftw*( )

8310 **CHANGE HISTORY**

8311 First released in Issue 1. Derived from Issue 1 of the SVID.

8312 **Issue 5**

8313 A description of FTW_DP is added.

NAME

glob.h — pathname pattern-matching types

SYNOPSIS

```
#include <glob.h>
```

DESCRIPTION

The **<glob.h>** header shall define the structures and symbolic constants used by the *glob*( ) function.

The structure type **glob_t** shall contain at least the following members:

```
size_t   gl_pathc  Count of paths matched by pattern.
char   **gl_pathv  Pointer to a list of matched pathnames.
size_t   gl_offs   Slots to reserve at the beginning of gl_pathv.
```

The following constants shall be provided as values for the *flags* argument:

GLOB_APPEND	Append generated pathnames to those previously obtained.
GLOB_DOOFFS	Specify how many null pointers to add to the beginning of *gl_pathv*.
GLOB_ERR	Cause *glob*( ) to return on error.
GLOB_MARK	Each pathname that is a directory that matches *pattern* has a slash appended.
GLOB_NOCHECK	If *pattern* does not match any pathname, then return a list consisting of only *pattern*.
GLOB_NOESCAPE	Disable backslash escaping.
GLOB_NOSORT	Do not sort the pathnames returned.

The following constants shall be defined as error return values:

GLOB_ABORTED	The scan was stopped because GLOB_ERR was set or (**errfunc*)( ) returned non-zero.
GLOB_NOMATCH	The pattern does not match any existing pathname, and GLOB_NOCHECK was not set in *flags*.
GLOB_NOSPACE	An attempt to allocate memory failed.
OB XSI GLOB_NOSYS	Reserved.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int  glob(const char *restrict, int, int (*)(const char *, int),
         glob_t *restrict);
void globfree(glob_t *);
```

The implementation may define additional macros or constants using names beginning with GLOB_.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *glob*( ), the Shell and Utilities volume of IEEE Std 1003.1-2001

CHANGE HISTORY

First released in Issue 4. Derived from the ISO POSIX-2 standard.

Issue 6

The **restrict** keyword is added to the prototype for *glob*( ).

The constant GLOB_NOSYS is marked obsolescent.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/8 is applied, correcting the *glob*( ) prototype definition by removing the **restrict** qualifier from the function pointer argument.

NAME

grp.h — group structure

SYNOPSIS

```
#include <grp.h>
```

DESCRIPTION

The **<grp.h>** header shall declare the structure **group** which shall include the following members:

`char *gr_name`	The name of the group.
`gid_t gr_gid`	Numerical group ID.
`char **gr_mem`	Pointer to a null-terminated array of character pointers to member names.

The **gid_t** type shall be defined as described in **<sys/types.h>**.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
struct group  *getgrgid(gid_t);
struct group  *getgrnam(const char *);
TSF int            getgrgid_r(gid_t, struct group *, char *,
                       size_t, struct group **);
int            getgrnam_r(const char *, struct group *, char *,
                       size_t , struct group **);
XSI struct group  *getgrent(void);
void           endgrent(void);
void           setgrent(void);
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<sys/types.h>, the System Interfaces volume of IEEE Std 1003.1-2001, *endgrent*( ), *getgrgid*( ), *getgrnam*( )

CHANGE HISTORY

First released in Issue 1.

Issue 5

The DESCRIPTION is updated for alignment with the POSIX Threads Extension.

Issue 6

The following new requirements on POSIX implementations derive from alignment with the Single UNIX Specification:

- The definition of **gid_t** is mandated.
- The *getgrgid_r*( ) and *getgrnam_r*( ) functions are marked as part of the Thread-Safe Functions option.

NAME

iconv.h — codeset conversion facility

SYNOPSIS

XSI
```
#include <iconv.h>
```

DESCRIPTION

The **<iconv.h>** header shall define the following type:

iconv_t Identifies the conversion from one codeset to another.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
iconv_t iconv_open(const char *, const char *);
size_t  iconv(iconv_t, char **restrict, size_t *restrict,
            char **restrict, size_t *restrict);
int     iconv_close(iconv_t);
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *iconv*( ), *iconv_close*( ), *iconv_open*( )

CHANGE HISTORY

First released in Issue 4.

Issue 6

The **restrict** keyword is added to the prototype for *iconv*( ).

NAME

inttypes.h — fixed size integer types

SYNOPSIS

```
#include <inttypes.h>
```

DESCRIPTION

CX Some of the functionality described on this reference page extends the ISO C standard. Applications shall define the appropriate feature test macro (see the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.2, The Compilation Environment) to enable the visibility of these symbols in this header.

The **<inttypes.h>** header shall include the **<stdint.h>** header.

The **<inttypes.h>** header shall include a definition of at least the following type:

imaxdiv_t Structure type that is the type of the value returned by the *imaxdiv*( ) function.

The following macros shall be defined. Each expands to a character string literal containing a conversion specifier, possibly modified by a length modifier, suitable for use within the *format* argument of a formatted input/output function when converting the corresponding integer type. These macros have the general form of PRI (character string literals for the *fprintf*( ) and *fwprintf*( ) family of functions) or SCN (character string literals for the *fscanf*( ) and *fwscanf*( ) family of functions), followed by the conversion specifier, followed by a name corresponding to a similar type name in **<stdint.h>**. In these names, *N* represents the width of the type as described in **<stdint.h>**. For example, *PRIdFAST32* can be used in a format string to print the value of an integer of type **int_fast32_t**.

The *fprintf*( ) macros for signed integers are:

PRId*N*	PRIdLEAST*N*	PRIdFAST*N*	PRIdMAX	PRIdPTR
PRIi*N*	PRIiLEAST*N*	PRIiFAST*N*	PRIiMAX	PRIiPTR

The *fprintf*( ) macros for unsigned integers are:

PRIo*N*	PRIoLEAST*N*	PRIoFAST*N*	PRIoMAX	PRIoPTR
PRIu*N*	PRIuLEAST*N*	PRIuFAST*N*	PRIuMAX	PRIuPTR
PRIx*N*	PRIxLEAST*N*	PRIxFAST*N*	PRIxMAX	PRIxPTR
PRIX*N*	PRIXLEAST*N*	PRIXFAST*N*	PRIXMAX	PRIXPTR

The *fscanf*( ) macros for signed integers are:

SCNd*N*	SCNdLEAST*N*	SCNdFAST*N*	SCNdMAX	SCNdPTR
SCNi*N*	SCNiLEAST*N*	SCNiFAST*N*	SCNiMAX	SCNiPTR

The *fscanf*( ) macros for unsigned integers are:

SCNo*N*	SCNoLEAST*N*	SCNoFAST*N*	SCNoMAX	SCNoPTR
SCNu*N*	SCNuLEAST*N*	SCNuFAST*N*	SCNuMAX	SCNuPTR
SCNx*N*	SCNxLEAST*N*	SCNxFAST*N*	SCNxMAX	SCNxPTR

For each type that the implementation provides in **<stdint.h>**, the corresponding *fprintf*( ) and *fwprintf*( ) macros shall be defined and the corresponding *fscanf*( ) and *fwscanf*( ) macros shall be defined unless the implementation does not have a suitable modifier for the type.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
intmax_t  imaxabs(intmax_t);
imaxdiv_t imaxdiv(intmax_t, intmax_t);
intmax_t  strtoimax(const char *restrict, char **restrict, int);
```



```
8478        uintmax_t strtoumax(const char *restrict, char **restrict, int);
8479        intmax_t  wcstoimax(const wchar_t *restrict, wchar_t **restrict, int);
8480        uintmax_t wcstoumax(const wchar_t *restrict, wchar_t **restrict, int);
```

EXAMPLES

```
8482        #include <inttypes.h>
8483        #include <wchar.h>
8484        int main(void)
8485        {
8486            uintmax_t i = UINTMAX_MAX; // This type always exists.
8487            wprintf(L"The largest integer value is %020"
8488                PRIxMAX "\n", i);
8489            return 0;
8490        }
```

APPLICATION USAGE

The purpose of **<inttypes.h>** is to provide a set of integer types whose definitions are consistent across machines and independent of operating systems and other implementation idiosyncrasies. It defines, via **typedef**, integer types of various sizes. Implementations are free to **typedef** them as ISO C standard integer types or extensions that they support. Consistent use of this header will greatly increase the portability of applications across platforms.

RATIONALE

The ISO/IEC 9899:1990 standard specified that the language should support four signed and unsigned integer data types—**char**, **short**, **int**, and **long**—but placed very little requirement on their size other than that **int** and **short** be at least 16 bits and **long** be at least as long as **int** and not smaller than 32 bits. For 16-bit systems, most implementations assigned 8, 16, 16, and 32 bits to **char**, **short**, **int**, and **long**, respectively. For 32-bit systems, the common practice has been to assign 8, 16, 32, and 32 bits to these types. This difference in **int** size can create some problems for users who migrate from one system to another which assigns different sizes to integer types, because the ISO C standard integer promotion rule can produce silent changes unexpectedly. The need for defining an extended integer type increased with the introduction of 64-bit systems.

FUTURE DIRECTIONS

Macro names beginning with PRI or SCN followed by any lowercase letter or `'X'` may be added to the macros defined in the **<inttypes.h>** header.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *imaxdiv*( )

CHANGE HISTORY

First released in Issue 5.

Issue 6

The Open Group Base Resolution bwg97-006 is applied.

This reference page is updated to align with the ISO/IEC 9899:1999 standard.

NAME

iso646.h — alternative spellings

SYNOPSIS

```
#include <iso646.h>
```

DESCRIPTION

CX The functionality described on this reference page is aligned with the ISO C standard. Any conflict between the requirements described here and the ISO C standard is unintentional. This volume of IEEE Std 1003.1-2001 defers to the ISO C standard.

The **<iso646.h>** header shall define the following eleven macros (on the left) that expand to the corresponding tokens (on the right):

and	&&
and_eq	&=
bitand	&
bitor	|
compl	~
not	!
not_eq	!=
or	||
or_eq	|=
xor	^
xor_eq	^=

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

None.

CHANGE HISTORY

First released in Issue 5. Derived from ISO/IEC 9899:1990/Amendment 1:1995 (E).

NAME

langinfo.h — language information constants

SYNOPSIS

XSI
```
#include <langinfo.h>
```

DESCRIPTION

The **<langinfo.h>** header contains the constants used to identify items of *langinfo* data (see *nl_langinfo*( )). The type of the constant, **nl_item**, shall be defined as described in **<nl_types.h>**.

The following constants shall be defined. The entries under **Category** indicate in which *setlocale*( ) category each item is defined.

Constant	Category	Meaning
CODESET	*LC_CTYPE*	Codeset name.
D_T_FMT	*LC_TIME*	String for formatting date and time.
D_FMT	*LC_TIME*	Date format string.
T_FMT	*LC_TIME*	Time format string.
T_FMT_AMPM	*LC_TIME*	a.m. or p.m. time format string.
AM_STR	*LC_TIME*	Ante-meridiem affix.
PM_STR	*LC_TIME*	Post-meridiem affix.
DAY_1	*LC_TIME*	Name of the first day of the week (for example, Sunday).
DAY_2	*LC_TIME*	Name of the second day of the week (for example, Monday).
DAY_3	*LC_TIME*	Name of the third day of the week (for example, Tuesday).
DAY_4	*LC_TIME*	Name of the fourth day of the week (for example, Wednesday).
DAY_5	*LC_TIME*	Name of the fifth day of the week (for example, Thursday).
DAY_6	*LC_TIME*	Name of the sixth day of the week (for example, Friday).
DAY_7	*LC_TIME*	Name of the seventh day of the week (for example, Saturday).
ABDAY_1	*LC_TIME*	Abbreviated name of the first day of the week.
ABDAY_2	*LC_TIME*	Abbreviated name of the second day of the week.
ABDAY_3	*LC_TIME*	Abbreviated name of the third day of the week.
ABDAY_4	*LC_TIME*	Abbreviated name of the fourth day of the week.
ABDAY_5	*LC_TIME*	Abbreviated name of the fifth day of the week.
ABDAY_6	*LC_TIME*	Abbreviated name of the sixth day of the week.
ABDAY_7	*LC_TIME*	Abbreviated name of the seventh day of the week.
MON_1	*LC_TIME*	Name of the first month of the year.
MON_2	*LC_TIME*	Name of the second month.
MON_3	*LC_TIME*	Name of the third month.
MON_4	*LC_TIME*	Name of the fourth month.
MON_5	*LC_TIME*	Name of the fifth month.
MON_6	*LC_TIME*	Name of the sixth month.
MON_7	*LC_TIME*	Name of the seventh month.
MON_8	*LC_TIME*	Name of the eighth month.
MON_9	*LC_TIME*	Name of the ninth month.
MON_10	*LC_TIME*	Name of the tenth month.
MON_11	*LC_TIME*	Name of the eleventh month.
MON_12	*LC_TIME*	Name of the twelfth month.

Constant	Category	Meaning
ABMON_1	*LC_TIME*	Abbreviated name of the first month.
ABMON_2	*LC_TIME*	Abbreviated name of the second month.
ABMON_3	*LC_TIME*	Abbreviated name of the third month.
ABMON_4	*LC_TIME*	Abbreviated name of the fourth month.
ABMON_5	*LC_TIME*	Abbreviated name of the fifth month.
ABMON_6	*LC_TIME*	Abbreviated name of the sixth month.
ABMON_7	*LC_TIME*	Abbreviated name of the seventh month.
ABMON_8	*LC_TIME*	Abbreviated name of the eighth month.
ABMON_9	*LC_TIME*	Abbreviated name of the ninth month.
ABMON_10	*LC_TIME*	Abbreviated name of the tenth month.
ABMON_11	*LC_TIME*	Abbreviated name of the eleventh month.
ABMON_12	*LC_TIME*	Abbreviated name of the twelfth month.
ERA	*LC_TIME*	Era description segments.
ERA_D_FMT	*LC_TIME*	Era date format string.
ERA_D_T_FMT	*LC_TIME*	Era date and time format string.
ERA_T_FMT	*LC_TIME*	Era time format string.
ALT_DIGITS	*LC_TIME*	Alternative symbols for digits.
RADIXCHAR	*LC_NUMERIC*	Radix character.
THOUSEP	*LC_NUMERIC*	Separator for thousands.
YESEXPR	*LC_MESSAGES*	Affirmative response expression.
NOEXPR	*LC_MESSAGES*	Negative response expression.
CRNCYSTR	*LC_MONETARY*	Local currency symbol, preceded by '–' if the symbol should appear before the value, '+' if the symbol should appear after the value, or '.' if the symbol should replace the radix character. If the local currency symbol is the empty string, implementations may return the empty string ("").

If the locale's values for **p_cs_precedes** and **n_cs_precedes** do not match, the value of *nl_langinfo*(CRNCYSTR) is unspecified.

The following shall be declared as a function and may also be defined as a macro. A function prototype shall be provided.

```
char *nl_langinfo(nl_item);
```

Inclusion of the **<langinfo.h>** header may also make visible all symbols from **<nl_types.h>**.

APPLICATION USAGE

Wherever possible, users are advised to use functions compatible with those in the ISO C standard to access items of *langinfo* data. In particular, the *strftime*( ) function should be used to access date and time information defined in category *LC_TIME*. The *localeconv*( ) function should be used to access information corresponding to RADIXCHAR, THOUSEP, and CRNCYSTR.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *nl_langinfo*( ), *localeconv*( ), *strfmon*( ), *strftime*( ), Chapter 7 (on page 123)

CHANGE HISTORY

First released in Issue 2.

Issue 5

The constants YESSTR and NOSTR are marked LEGACY.

Issue 6

The constants YESSTR and NOSTR are removed.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/9 is applied, adding a sentence to the ''Meaning'' column entry for the CRNCYSTR constant. This change is to accommodate historic practice.

NAME

libgen.h — definitions for pattern matching functions

SYNOPSIS

XSI
```
#include <libgen.h>
```

DESCRIPTION

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
char  *basename(char *);
char  *dirname(char *);
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *basename*( ), *dirname*( )

CHANGE HISTORY

First released in Issue 4, Version 2.

Issue 5

The function prototypes for *basename*( ) and *dirname*( ) are changed to indicate that the first argument is of type **char *** rather than **const char ***.

Issue 6

The **__loc1** symbol and the *regcmp*( ) and *regex*( ) functions are removed.

NAME

limits.h — implementation-defined constants

SYNOPSIS

```
#include <limits.h>
```

DESCRIPTION

CX Some of the functionality described on this reference page extends the ISO C standard. Applications shall define the appropriate feature test macro (see the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.2, The Compilation Environment) to enable the visibility of these symbols in this header.

CX Many of the symbols listed here are not defined by the ISO/IEC 9899:1999 standard. Such symbols are not shown as CX shaded.

The **<limits.h>** header shall define various symbolic names. Different categories of names are described below.

The names represent various limits on resources that the implementation imposes on applications.

Implementations may choose any appropriate value for each limit, provided it is not more restrictive than the Minimum Acceptable Values listed below. Symbolic constant names beginning with _POSIX may be found in **<unistd.h>**.

Applications should not assume any particular value for a limit. To achieve maximum portability, an application should not require more resource than the Minimum Acceptable Value quantity. However, an application wishing to avail itself of the full amount of a resource available on an implementation may make use of the value given in **<limits.h>** on that particular implementation, by using the symbolic names listed below. It should be noted, however, that many of the listed limits are not invariant, and at runtime, the value of the limit may differ from those given in this header, for the following reasons:

- The limit is pathname-dependent.
- The limit differs between the compile and runtime machines.

For these reasons, an application may use the *fpathconf*( ), *pathconf*( ), and *sysconf*( ) functions to determine the actual value of a limit at runtime.

The items in the list ending in _MIN give the most negative values that the mathematical types are guaranteed to be capable of representing. Numbers of a more negative value may be supported on some implementations, as indicated by the **<limits.h>** header on the implementation, but applications requiring such numbers are not guaranteed to be portable to all implementations. For positive constants ending in _MIN, this indicates the minimum acceptable value.

Runtime Invariant Values (Possibly Indeterminate)

A definition of one of the symbolic names in the following list shall be omitted from **<limits.h>** on specific implementations where the corresponding value is equal to or greater than the stated minimum, but is unspecified.

This indetermination might depend on the amount of available memory space on a specific instance of a specific implementation. The actual value supported by a specific instance shall be provided by the *sysconf*( ) function.

AIO {AIO_LISTIO_MAX}
Maximum number of I/O operations in a single list I/O call supported by the

implementation.
Minimum Acceptable Value: {_POSIX_AIO_LISTIO_MAX}

AIO {AIO_MAX}
Maximum number of outstanding asynchronous I/O operations supported by the implementation.
Minimum Acceptable Value: {_POSIX_AIO_MAX}

AIO {AIO_PRIO_DELTA_MAX}
The maximum amount by which a process can decrease its asynchronous I/O priority level from its own scheduling priority.
Minimum Acceptable Value: 0

{ARG_MAX}
Maximum length of argument to the *exec* functions including environment data.
Minimum Acceptable Value: {_POSIX_ARG_MAX}

XSI {ATEXIT_MAX}
Maximum number of functions that may be registered with *atexit*( ).
Minimum Acceptable Value: 32

{CHILD_MAX}
Maximum number of simultaneous processes per real user ID.
Minimum Acceptable Value: {_POSIX_CHILD_MAX}

TMR {DELAYTIMER_MAX}
Maximum number of timer expiration overruns.
Minimum Acceptable Value: {_POSIX_DELAYTIMER_MAX}

{HOST_NAME_MAX}
Maximum length of a host name (not including the terminating null) as returned from the *gethostname*( ) function.
Minimum Acceptable Value: {_POSIX_HOST_NAME_MAX}

XSI {IOV_MAX}
Maximum number of **iovec** structures that one process has available for use with *readv*( ) or *writev*( ).
Minimum Acceptable Value: {_XOPEN_IOV_MAX}

{LOGIN_NAME_MAX}
Maximum length of a login name.
Minimum Acceptable Value: {_POSIX_LOGIN_NAME_MAX}

MSG {MQ_OPEN_MAX}
The maximum number of open message queue descriptors a process may hold.
Minimum Acceptable Value: {_POSIX_MQ_OPEN_MAX}

MSG {MQ_PRIO_MAX}
The maximum number of message priorities supported by the implementation.
Minimum Acceptable Value: {_POSIX_MQ_PRIO_MAX}

{OPEN_MAX}
Maximum number of files that one process can have open at any one time.
Minimum Acceptable Value: {_POSIX_OPEN_MAX}

{PAGESIZE}
Size in bytes of a page.
Minimum Acceptable Value: 1

8766 XSI {PAGE_SIZE}
8767 Equivalent to {PAGESIZE}. If either {PAGESIZE} or {PAGE_SIZE} is defined, the other is
8768 defined with the same value.

8769 THR {PTHREAD_DESTRUCTOR_ITERATIONS}
8770 Maximum number of attempts made to destroy a thread's thread-specific data values on
8771 thread exit.
8772 Minimum Acceptable Value: {_POSIX_THREAD_DESTRUCTOR_ITERATIONS}

8773 THR {PTHREAD_KEYS_MAX}
8774 Maximum number of data keys that can be created by a process.
8775 Minimum Acceptable Value: {_POSIX_THREAD_KEYS_MAX}

8776 THR {PTHREAD_STACK_MIN}
8777 Minimum size in bytes of thread stack storage.
8778 Minimum Acceptable Value: 0

8779 THR {PTHREAD_THREADS_MAX}
8780 Maximum number of threads that can be created per process.
8781 Minimum Acceptable Value: {_POSIX_THREAD_THREADS_MAX}

8782 {RE_DUP_MAX}
8783 The number of repeated occurrences of a BRE permitted by the *regexec*( ) and *regcomp*( )
8784 functions when using the interval notation {\(*m*,*n*\}; see Section 9.3.6 (on page 174).
8785 Minimum Acceptable Value: {_POSIX2_RE_DUP_MAX}

8786 RTS {RTSIG_MAX}
8787 Maximum number of realtime signals reserved for application use in this implementation.
8788 Minimum Acceptable Value: {_POSIX_RTSIG_MAX}

8789 SEM {SEM_NSEMS_MAX}
8790 Maximum number of semaphores that a process may have.
8791 Minimum Acceptable Value: {_POSIX_SEM_NSEMS_MAX}

8792 SEM {SEM_VALUE_MAX}
8793 The maximum value a semaphore may have.
8794 Minimum Acceptable Value: {_POSIX_SEM_VALUE_MAX}

8795 RTS {SIGQUEUE_MAX}
8796 Maximum number of queued signals that a process may send and have pending at the
8797 receiver(s) at any time.
8798 Minimum Acceptable Value: {_POSIX_SIGQUEUE_MAX}

8799 SS|TSP {SS_REPL_MAX}
8800 The maximum number of replenishment operations that may be simultaneously pending
8801 for a particular sporadic server scheduler.
8802 Minimum Acceptable Value: {_POSIX_SS_REPL_MAX}

8803 {STREAM_MAX}
8804 The number of streams that one process can have open at one time. If defined, it has the
8805 same value as {FOPEN_MAX} (see **<stdio.h>**).
8806 Minimum Acceptable Value: {_POSIX_STREAM_MAX}

8807 {SYMLOOP_MAX}
8808 Maximum number of symbolic links that can be reliably traversed in the resolution of a
8809 pathname in the absence of a loop.
8810 Minimum Acceptable Value: {_POSIX_SYMLOOP_MAX}

TMR {TIMER_MAX}
Maximum number of timers per process supported by the implementation.
Minimum Acceptable Value: {_POSIX_TIMER_MAX}

TRC {TRACE_EVENT_NAME_MAX}
Maximum length of the trace event name.
Minimum Acceptable Value: {_POSIX_TRACE_EVENT_NAME_MAX}

TRC {TRACE_NAME_MAX}
Maximum length of the trace generation version string or of the trace stream name.
Minimum Acceptable Value: {_POSIX_TRACE_NAME_MAX}

TRC {TRACE_SYS_MAX}
Maximum number of trace streams that may simultaneously exist in the system.
Minimum Acceptable Value: {_POSIX_TRACE_SYS_MAX}

TRC {TRACE_USER_EVENT_MAX}
Maximum number of user trace event type identifiers that may simultaneously exist in a traced process, including the predefined user trace event POSIX_TRACE_UNNAMED_USER_EVENT.
Minimum Acceptable Value: {_POSIX_TRACE_USER_EVENT_MAX}

{TTY_NAME_MAX}
Maximum length of terminal device name.
Minimum Acceptable Value: {_POSIX_TTY_NAME_MAX}

{TZNAME_MAX}
Maximum number of bytes supported for the name of a timezone (not of the *TZ* variable).
Minimum Acceptable Value: {_POSIX_TZNAME_MAX}

Note: The length given by {TZNAME_MAX} does not include the quoting characters mentioned in Section 8.3 (on page 165).

Pathname Variable Values

The values in the following list may be constants within an implementation or may vary from one pathname to another. For example, file systems or directories may have different characteristics.

A definition of one of the values shall be omitted from the **<limits.h>** header on specific implementations where the corresponding value is equal to or greater than the stated minimum, but where the value can vary depending on the file to which it is applied. The actual value supported for a specific pathname shall be provided by the *pathconf*( ) function.

{FILESIZEBITS}
Minimum number of bits needed to represent, as a signed integer value, the maximum size of a regular file allowed in the specified directory.
Minimum Acceptable Value: 32

{LINK_MAX}
Maximum number of links to a single file.
Minimum Acceptable Value: {_POSIX_LINK_MAX}

{MAX_CANON}
Maximum number of bytes in a terminal canonical input line.
Minimum Acceptable Value: {_POSIX_MAX_CANON}

{MAX_INPUT}
Minimum number of bytes for which space is available in a terminal input queue; therefore,

the maximum number of bytes a conforming application may require to be typed as input before reading them.
Minimum Acceptable Value: {_POSIX_MAX_INPUT}

{NAME_MAX}
Maximum number of bytes in a filename (not including terminating null).
Minimum Acceptable Value: {_POSIX_NAME_MAX}
XSI Minimum Acceptable Value: {_XOPEN_NAME_MAX}

{PATH_MAX}
Maximum number of bytes in a pathname, including the terminating null character.
Minimum Acceptable Value: {_POSIX_PATH_MAX}
XSI Minimum Acceptable Value: {_XOPEN_PATH_MAX}

{PIPE_BUF}
Maximum number of bytes that is guaranteed to be atomic when writing to a pipe.
Minimum Acceptable Value: {_POSIX_PIPE_BUF}

ADV {POSIX_ALLOC_SIZE_MIN}
Minimum number of bytes of storage actually allocated for any portion of a file.
Minimum Acceptable Value: Not specified.

ADV {POSIX_REC_INCR_XFER_SIZE}
Recommended increment for file transfer sizes between the {POSIX_REC_MIN_XFER_SIZE} and {POSIX_REC_MAX_XFER_SIZE} values.
Minimum Acceptable Value: Not specified.

ADV {POSIX_REC_MAX_XFER_SIZE}
Maximum recommended file transfer size.
Minimum Acceptable Value: Not specified.

ADV {POSIX_REC_MIN_XFER_SIZE}
Minimum recommended file transfer size.
Minimum Acceptable Value: Not specified.

ADV {POSIX_REC_XFER_ALIGN}
Recommended file transfer buffer alignment.
Minimum Acceptable Value: Not specified.

{SYMLINK_MAX}
Maximum number of bytes in a symbolic link.
Minimum Acceptable Value: {_POSIX_SYMLINK_MAX}

Runtime Increasable Values

The magnitude limitations in the following list shall be fixed by specific implementations. An application should assume that the value supplied by **<limits.h>** in a specific implementation is the minimum that pertains whenever the application is run under that implementation. A specific instance of a specific implementation may increase the value relative to that supplied by **<limits.h>** for that implementation. The actual value supported by a specific instance shall be provided by the *sysconf*( ) function.

{BC_BASE_MAX}
Maximum *obase* values allowed by the *bc* utility.
Minimum Acceptable Value: {_POSIX2_BC_BASE_MAX}

{BC_DIM_MAX}
Maximum number of elements permitted in an array by the *bc* utility.

Minimum Acceptable Value: {_POSIX2_BC_DIM_MAX}

{BC_SCALE_MAX}
Maximum *scale* value allowed by the *bc* utility.
Minimum Acceptable Value: {_POSIX2_BC_SCALE_MAX}

{BC_STRING_MAX}
Maximum length of a string constant accepted by the *bc* utility.
Minimum Acceptable Value: {_POSIX2_BC_STRING_MAX}

{CHARCLASS_NAME_MAX}
Maximum number of bytes in a character class name.
Minimum Acceptable Value: {_POSIX2_CHARCLASS_NAME_MAX}

{COLL_WEIGHTS_MAX}
Maximum number of weights that can be assigned to an entry of the *LC_COLLATE* **order** keyword in the locale definition file; see Chapter 7 (on page 123).
Minimum Acceptable Value: {_POSIX2_COLL_WEIGHTS_MAX}

{EXPR_NEST_MAX}
Maximum number of expressions that can be nested within parentheses by the *expr* utility.
Minimum Acceptable Value: {_POSIX2_EXPR_NEST_MAX}

{LINE_MAX}
Unless otherwise noted, the maximum length, in bytes, of a utility's input line (either standard input or another file), when the utility is described as processing text files. The length includes room for the trailing <newline>.
Minimum Acceptable Value: {_POSIX2_LINE_MAX}

{NGROUPS_MAX}
Maximum number of simultaneous supplementary group IDs per process.
Minimum Acceptable Value: {_POSIX_NGROUPS_MAX}

{RE_DUP_MAX}
Maximum number of repeated occurrences of a regular expression permitted when using the interval notation \{*m*,*n*\}; see Chapter 9 (on page 169).
Minimum Acceptable Value: {_POSIX2_RE_DUP_MAX}

Maximum Values

TMR The symbolic constants in the following list shall be defined in **<limits.h>** with the values shown. These are symbolic names for the most restrictive value for certain features on an implementation supporting the Timers option. A conforming implementation shall provide values no larger than these values. A conforming application must not require a smaller value for correct operation.

TMR {_POSIX_CLOCKRES_MIN}
The resolution of the CLOCK_REALTIME clock, in nanoseconds.
Value: 20 000 000

MON If the Monotonic Clock option is supported, the resolution of the CLOCK_MONOTONIC clock, in nanoseconds, is represented by {_POSIX_CLOCKRES_MIN}.

Minimum Values

The symbolic constants in the following list shall be defined in **<limits.h>** with the values shown. These are symbolic names for the most restrictive value for certain features on an implementation conforming to this volume of IEEE Std 1003.1-2001. Related symbolic constants are defined elsewhere in this volume of IEEE Std 1003.1-2001 which reflect the actual implementation and which need not be as restrictive. A conforming implementation shall provide values at least this large. A strictly conforming application must not require a larger value for correct operation.

AIO {_POSIX_AIO_LISTIO_MAX}
The number of I/O operations that can be specified in a list I/O call.
Value: 2

AIO {_POSIX_AIO_MAX}
The number of outstanding asynchronous I/O operations.
Value: 1

{_POSIX_ARG_MAX}
Maximum length of argument to the *exec* functions including environment data.
Value: 4 096

{_POSIX_CHILD_MAX}
Maximum number of simultaneous processes per real user ID.
Value: 25

TMR {_POSIX_DELAYTIMER_MAX}
The number of timer expiration overruns.
Value: 32

{_POSIX_HOST_NAME_MAX}
Maximum length of a host name (not including the terminating null) as returned from the *gethostname*( ) function.
Value: 255

{_POSIX_LINK_MAX}
Maximum number of links to a single file.
Value: 8

{_POSIX_LOGIN_NAME_MAX}
The size of the storage required for a login name, in bytes, including the terminating null.
Value: 9

{_POSIX_MAX_CANON}
Maximum number of bytes in a terminal canonical input queue.
Value: 255

{_POSIX_MAX_INPUT}
Maximum number of bytes allowed in a terminal input queue.
Value: 255

MSG {_POSIX_MQ_OPEN_MAX}
The number of message queues that can be open for a single process.
Value: 8

MSG {_POSIX_MQ_PRIO_MAX}
The maximum number of message priorities supported by the implementation.
Value: 32

{_POSIX_NAME_MAX}
Maximum number of bytes in a filename (not including terminating null).
Value: 14

{_POSIX_NGROUPS_MAX}
Maximum number of simultaneous supplementary group IDs per process.
Value: 8

{_POSIX_OPEN_MAX}
Maximum number of files that one process can have open at any one time.
Value: 20

{_POSIX_PATH_MAX}
Maximum number of bytes in a pathname.
Value: 256

{_POSIX_PIPE_BUF}
Maximum number of bytes that is guaranteed to be atomic when writing to a pipe.
Value: 512

{_POSIX_RE_DUP_MAX}
The number of repeated occurrences of a BRE permitted by the *regexec*( ) and *regcomp*( ) functions when using the interval notation {\(*m*,*n*\}; see Section 9.3.6 (on page 174).
Value: 255

RTS {_POSIX_RTSIG_MAX}
The number of realtime signal numbers reserved for application use.
Value: 8

SEM {_POSIX_SEM_NSEMS_MAX}
The number of semaphores that a process may have.
Value: 256

SEM {_POSIX_SEM_VALUE_MAX}
The maximum value a semaphore may have.
Value: 32 767

RTS {_POSIX_SIGQUEUE_MAX}
The number of queued signals that a process may send and have pending at the receiver(s) at any time.
Value: 32

{_POSIX_SSIZE_MAX}
The value that can be stored in an object of type **ssize_t**.
Value: 32 767

{_POSIX_STREAM_MAX}
The number of streams that one process can have open at one time.
Value: 8

SS|TSP {_POSIX_SS_REPL_MAX}
The number of replenishment operations that may be simultaneously pending for a particular sporadic server scheduler.
Value: 4

{_POSIX_SYMLINK_MAX}
The number of bytes in a symbolic link.
Value: 255

{_POSIX_SYMLOOP_MAX}
The number of symbolic links that can be traversed in the resolution of a pathname in the absence of a loop.
Value: 8

THR {_POSIX_THREAD_DESTRUCTOR_ITERATIONS}
The number of attempts made to destroy a thread's thread-specific data values on thread exit.
Value: 4

THR {_POSIX_THREAD_KEYS_MAX}
The number of data keys per process.
Value: 128

THR {_POSIX_THREAD_THREADS_MAX}
The number of threads per process.
Value: 64

TMR {_POSIX_TIMER_MAX}
The per-process number of timers.
Value: 32

TRC {_POSIX_TRACE_EVENT_NAME_MAX}
The length in bytes of a trace event name.
Value: 30

TRC {_POSIX_TRACE_NAME_MAX}
The length in bytes of a trace generation version string or a trace stream name.
Value: 8

TRC {_POSIX_TRACE_SYS_MAX}
The number of trace streams that may simultaneously exist in the system.
Value: 8

TRC {_POSIX_TRACE_USER_EVENT_MAX}
The number of user trace event type identifiers that may simultaneously exist in a traced process, including the predefined user trace event POSIX_TRACE_UNNAMED_USER_EVENT.
Value: 32

{_POSIX_TTY_NAME_MAX}
The size of the storage required for a terminal device name, in bytes, including the terminating null.
Value: 9

{_POSIX_TZNAME_MAX}
Maximum number of bytes supported for the name of a timezone (not of the *TZ* variable).
Value: 6

Note: The length given by {_POSIX_TZNAME_MAX} does not include the quoting characters mentioned in Section 8.3 (on page 165).

{_POSIX2_BC_BASE_MAX}
Maximum *obase* values allowed by the *bc* utility.
Value: 99

{_POSIX2_BC_DIM_MAX}
Maximum number of elements permitted in an array by the *bc* utility.
Value: 2 048

{_POSIX2_BC_SCALE_MAX}
Maximum *scale* value allowed by the *bc* utility.
Value: 99

{_POSIX2_BC_STRING_MAX}
Maximum length of a string constant accepted by the *bc* utility.
Value: 1 000

{_POSIX2_CHARCLASS_NAME_MAX}
Maximum number of bytes in a character class name.
Value: 14

{_POSIX2_COLL_WEIGHTS_MAX}
Maximum number of weights that can be assigned to an entry of the *LC_COLLATE* **order** keyword in the locale definition file; see Chapter 7 (on page 123).
Value: 2

{_POSIX2_EXPR_NEST_MAX}
Maximum number of expressions that can be nested within parentheses by the *expr* utility.
Value: 32

{_POSIX2_LINE_MAX}
Unless otherwise noted, the maximum length, in bytes, of a utility's input line (either standard input or another file), when the utility is described as processing text files. The length includes room for the trailing <newline>.
Value: 2 048

{_POSIX2_RE_DUP_MAX]
Maximum number of repeated occurrences of a regular expression permitted when using the interval notation \{*m*,*n*\}; see Chapter 9 (on page 169).
Value: 255

XSI {_XOPEN_IOV_MAX}
Maximum number of **iovec** structures that one process has available for use with *readv*( ) or *writev*( ).
Value: 16

XSI {_XOPEN_NAME_MAX}
Maximum number of bytes in a filename (not including the terminating null).
Value: 255

XSI {_XOPEN_PATH_MAX}
Maximum number of bytes in a pathname.
Value: 1 024

Numerical Limits

The values in the following lists shall be defined in **<limits.h>** and are constant expressions XSI suitable for use in **#if** preprocessing directives. Moreover, except for {CHAR_BIT}, {DBL_DIG}, {DBL_MAX}, {FLT_DIG}, {FLT_MAX}, {LONG_BIT}, {WORD_BIT}, and {MB_LEN_MAX}, the symbolic names are defined as expressions of the correct type.

If the value of an object of type **char** is treated as a signed integer when used in an expression, the value of {CHAR_MIN} is the same as that of {SCHAR_MIN} and the value of {CHAR_MAX} is the same as that of {SCHAR_MAX}. Otherwise, the value of {CHAR_MIN} is 0 and the value of {CHAR_MAX} is the same as that of {UCHAR_MAX}.

{CHAR_BIT}
Number of bits in a type **char**.
CX Value: 8

{CHAR_MAX}
Maximum value of type **char**.
Value: {UCHAR_MAX} or {SCHAR_MAX}

{CHAR_MIN}
Minimum value of type **char**.
Value: {SCHAR_MIN} or 0

{INT_MAX}
Maximum value of an **int**.
CX Minimum Acceptable Value: 2 147 483 647 2

XSI {LONG_BIT}
Number of bits in a **long**.
Minimum Acceptable Value: 32

{LONG_MAX}
Maximum value of a **long**.
Minimum Acceptable Value: +2 147 483 647

{MB_LEN_MAX}
Maximum number of bytes in a character, for any supported locale.
Minimum Acceptable Value: 1

{SCHAR_MAX}
Maximum value of type **signed char**.
CX Value: +127

{SHRT_MAX}
Maximum value of type **short**.
Minimum Acceptable Value: +32 767

{SSIZE_MAX}
Maximum value of an object of type **ssize_t**.
Minimum Acceptable Value: {_POSIX_SSIZE_MAX}

{UCHAR_MAX}
Maximum value of type **unsigned char**.
CX Value: 255

{UINT_MAX}
Maximum value of type **unsigned**.
CX Minimum Acceptable Value: 4 294 967 295 2

{ULONG_MAX}
Maximum value of type **unsigned long**.
Minimum Acceptable Value: 4 294 967 295

{USHRT_MAX}
Maximum value for a type **unsigned short**.
Minimum Acceptable Value: 65 535

XSI {WORD_BIT}
Number of bits in a type **int**.
Minimum Acceptable Value: 32 2

{INT_MIN}
Minimum value of type **int**.
CX Maximum Acceptable Value: –2 147 483 647

{LONG_MIN}
Minimum value of type **long**.
Maximum Acceptable Value: –2 147 483 647

{SCHAR_MIN}
Minimum value of type **signed char**.
CX Value: –128

{SHRT_MIN}
Minimum value of type **short**.
Maximum Acceptable Value: –32 767

{LLONG_MIN}
Minimum value of type **long long**.
Maximum Acceptable Value: –9 223 372 036 854 775 807

{LLONG_MAX}
Maximum value of type **long long**.
Minimum Acceptable Value: +9 223 372 036 854 775 807

{ULLONG_MAX}
Maximum value of type **unsigned long long**.
Minimum Acceptable Value: 18 446 744 073 709 551 615

Other Invariant Values

XSI The following constants shall be defined on all implementations in **<limits.h>**:

XSI {NL_ARGMAX}
Maximum value of *digit* in calls to the *printf*( ) and *scanf*( ) functions.
Minimum Acceptable Value: 9

XSI {NL_LANGMAX}
Maximum number of bytes in a *LANG* name.
Minimum Acceptable Value: 14

XSI {NL_MSGMAX}
Maximum message number.
Minimum Acceptable Value: 32 767

XSI {NL_NMAX}
Maximum number of bytes in an N-to-1 collation mapping.
Minimum Acceptable Value: No guaranteed value across all conforming implementations.

XSI {NL_SETMAX}
Maximum set number.
Minimum Acceptable Value: 255

XSI {NL_TEXTMAX}
Maximum number of bytes in a message string.
Minimum Acceptable Value: {_POSIX2_LINE_MAX}

XSI {NZERO}
Default process priority.
Minimum Acceptable Value: 20

APPLICATION USAGE

None.

RATIONALE

A request was made to reduce the value of {_POSIX_LINK_MAX} from the value of 8 specified for it in the POSIX.1-1990 standard to 2. The standard developers decided to deny this request for several reasons:

- They wanted to avoid making any changes to the standard that could break conforming applications, and the requested change could have that effect.
- The use of multiple hard links to a file cannot always be replaced with use of symbolic links. Symbolic links are semantically different from hard links in that they associate a pathname with another pathname rather than a pathname with a file. This has implications for access control, file permanence, and transparency.
- The original standard developers had considered the issue of allowing for implementations that did not in general support hard links, and decided that this would reduce consensus on the standard.

Systems that support historical versions of the development option of the ISO POSIX-2 standard retain the name {_POSIX2_RE_DUP_MAX} as an alias for {_POSIX_RE_DUP_MAX}.

{PATH_MAX}

IEEE PASC Interpretation 1003.1 #15 addressed the inconsistency in the standard with the definition of pathname and the description of {PATH_MAX}, allowing application writers to allocate either {PATH_MAX} or {PATH_MAX}+1 bytes. The inconsistency has been removed by correction to the {PATH_MAX} definition to include the null character. With this change, applications that previously allocated {PATH_MAX} bytes will continue to succeed.

{SYMLINK_MAX}

This symbol refers to space for data that is stored in the file system, as opposed to {PATH_MAX} which is the length of a name that can be passed to a function. In some existing implementations, the filenames pointed to by symbolic links are stored in the inodes of the links, so it is important that {SYMLINK_MAX} not be constrained to be as large as {PATH_MAX}.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *fpathconf*( ), *pathconf*( ), *sysconf*( )

CHANGE HISTORY

First released in Issue 1.

Issue 5

The DESCRIPTION is updated for alignment with the POSIX Realtime Extension and the POSIX Threads Extension.

{FILESIZEBITS} is added for the Large File Summit extensions.

The minimum acceptable values for {INT_MAX}, {INT_MIN}, and {UINT_MAX} are changed to make 32-bit values the minimum requirement.

The entry is restructured to improve readability.

Issue 6

The Open Group Corrigendum U033/4 is applied. The wording is made clear for {CHAR_MIN}, {INT_MIN}, {LONG_MIN}, {SCHAR_MIN}, and {SHRT_MIN} that these are maximum acceptable values.

The following new requirements on POSIX implementations derive from alignment with the Single UNIX Specification:

- The minimum value for {CHILD_MAX} is 25. This is a FIPS requirement.
- The minimum value for {OPEN_MAX} is 20. This is a FIPS requirement.
- The minimum value for {NGROUPS_MAX} is 8. This is also a FIPS requirement.

Symbolic constants are added for {_POSIX_SYMLINK_MAX}, {_POSIX_SYMLOOP_MAX}, {_POSIX_RE_DUP_MAX}, {RE_DUP_MAX}, {SYMLOOP_MAX}, and {SYMLINK_MAX}.

The following values are added for alignment with IEEE Std 1003.1d-1999:

{_POSIX_SS_REPL_MAX}
{SS_REPL_MAX}
{POSIX_ALLOC_SIZE_MIN}
{POSIX_REC_INCR_XFER_SIZE}
{POSIX_REC_MAX_XFER_SIZE}
{POSIX_REC_MIN_XFER_SIZE}
{POSIX_REC_XFER_ALIGN}

Reference to CLOCK_MONOTONIC is added in the description of {_POSIX_CLOCKRES_MIN} for alignment with IEEE Std 1003.1j-2000.

The constants {LLONG_MIN}, {LLONG_MAX}, and {ULLONG_MAX} are added for alignment with the ISO/IEC 9899:1999 standard.

The following values are added for alignment with IEEE Std 1003.1q-2000:

{_POSIX_TRACE_EVENT_NAME_MAX}
{_POSIX_TRACE_NAME_MAX}
{_POSIX_TRACE_SYS_MAX}
{_POSIX_TRACE_USER_EVENT_MAX}
{TRACE_EVENT_NAME_MAX}
{TRACE_NAME_MAX}
{TRACE_SYS_MAX}
{TRACE_USER_EVENT_MAX}

The new limits {_XOPEN_NAME_MAX} and {_XOPEN_PATH_MAX} are added as minimum values for {PATH_MAX} and {NAME_MAX} limits on XSI-conformant systems.

The legacy symbols {PASS_MAX} and {TMP_MAX} are removed.

The values for the limits {CHAR_BIT}, {SCHAR_MAX}, and {UCHAR_MAX} are now required to be 8, +127, and 255, respectively.

The value for the limit {CHAR_MAX} is now {UCHAR_MAX} or {SCHAR_MAX}.

The value for the limit {CHAR_MIN} is now {SCHAR_MIN} or zero.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/10 is applied, correcting the value of {_POSIX_CHILD_MAX} from 6 to 25. This is for FIPS 151-2 alignment. 1 1

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/19 is applied, updating the values for {INT_MAX}, {UINT_MAX}, and {INT_MIN} to be CX extensions over the ISO C standard, and 2 2

correcting {WORD_BIT} from 16 to 32.

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/20 is applied, removing {CHARCLASS_NAME_MAX} from the ''Other Invariant Values'' section (it also occurs under ''Runtime Increasable Values'').

NAME

locale.h — category macros

SYNOPSIS

```
#include <locale.h>
```

DESCRIPTION

CX Some of the functionality described on this reference page extends the ISO C standard. Any conflict between the requirements described here and the ISO C standard is unintentional. This volume of IEEE Std 1003.1-2001 defers to the ISO C standard.

The **<locale.h>** header shall provide a definition for **lconv** structure, which shall include at least the following members. (See the definitions of *LC_MONETARY* in Section 7.3.3 (on page 142) and Section 7.3.4 (on page 145).)

```
char    *currency_symbol
char    *decimal_point
char     frac_digits
char    *grouping
char    *int_curr_symbol
char     int_frac_digits
char     int_n_cs_precedes
char     int_n_sep_by_space
char     int_n_sign_posn
char     int_p_cs_precedes
char     int_p_sep_by_space
char     int_p_sign_posn
char    *mon_decimal_point
char    *mon_grouping
char    *mon_thousands_sep
char    *negative_sign
char     n_cs_precedes
char     n_sep_by_space
char     n_sign_posn
char    *positive_sign
char     p_cs_precedes
char     p_sep_by_space
char     p_sign_posn
char    *thousands_sep
```

The **<locale.h>** header shall define NULL (as defined in **<stddef.h>**) and at least the following as macros:

LC_ALL
LC_COLLATE
LC_CTYPE
CX *LC_MESSAGES*
LC_MONETARY
LC_NUMERIC
LC_TIME

which shall expand to distinct integer constant expressions, for use as the first argument to the *setlocale*( ) function.

Additional macro definitions, beginning with the characters *LC_* and an uppercase letter, may also be given here.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
struct  lconv *localeconv(void);
char   *setlocale(int, const char *);
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *localeconv*( ), *setlocale*( ), Chapter 8 (on page 161)

CHANGE HISTORY

First released in Issue 3.

Included for alignment with the ISO C standard.

Issue 6

The **lconv** structure is expanded with new members (**int_n_cs_precedes**, **int_n_sep_by_space**, **int_n_sign_posn**, **int_p_cs_precedes**, **int_p_sep_by_space**, and **int_p_sign_posn**) for alignment with the ISO/IEC 9899:1999 standard.

Extensions beyond the ISO C standard are marked.

NAME

math.h — mathematical declarations

SYNOPSIS

```
#include <math.h>
```

DESCRIPTION

CX Some of the functionality described on this reference page extends the ISO C standard. Applications shall define the appropriate feature test macro (see the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.2, The Compilation Environment) to enable the visibility of these symbols in this header.

The **<math.h>** header shall include definitions for at least the following types:

float_t A real-floating type at least as wide as **float**.

double_t A real-floating type at least as wide as **double**, and at least as wide as **float_t**.

If FLT_EVAL_METHOD equals 0, **float_t** and **double_t** shall be **float** and **double**, respectively; if FLT_EVAL_METHOD equals 1, they shall both be **double**; if FLT_EVAL_METHOD equals 2, they shall both be **long double**; for other values of FLT_EVAL_METHOD, they are otherwise implementation-defined.

The **<math.h>** header shall define the following macros, where real-floating indicates that the argument shall be an expression of real-floating type:

```
int fpclassify(real-floating x);
int isfinite(real-floating x);
int isinf(real-floating x);
int isnan(real-floating x);
int isnormal(real-floating x);
int signbit(real-floating x);
int isgreater(real-floating x, real-floating y);
int isgreaterequal(real-floating x, real-floating y);
int isless(real-floating x, real-floating y);
int islessequal(real-floating x, real-floating y);
int islessgreater(real-floating x, real-floating y);
int isunordered(real-floating x, real-floating y);
```

The **<math.h>** header shall provide for the following constants. The values are of type **double** and are accurate within the precision of the **double** type.

XSI

M_E	Value of e
M_LOG2E	Value of $\log_2 e$
M_LOG10E	Value of $\log_{10} e$
M_LN2	Value of $\log_e 2$
M_LN10	Value of $\log_e 10$
M_PI	Value of π
M_PI_2	Value of $\pi/2$
M_PI_4	Value of $\pi/4$
M_1_PI	Value of $1/\pi$
M_2_PI	Value of $2/\pi$

	M_2_SQRTPI	Value of $2/\sqrt{\pi}$
	M_SQRT2	Value of $\sqrt{2}$
	M_SQRT1_2	Value of $1/\sqrt{2}$

The header shall define the following symbolic constants:

XSI	MAXFLOAT	Value of maximum non-infinite single-precision floating-point number.
	HUGE_VAL	A positive **double** expression, not necessarily representable as a **float**. Used as an error value returned by the mathematics library. HUGE_VAL evaluates to +infinity on systems supporting IEEE Std 754-1985.
	HUGE_VALF	A positive **float** constant expression. Used as an error value returned by the mathematics library. HUGE_VALF evaluates to +infinity on systems supporting IEEE Std 754-1985.
	HUGE_VALL	A positive **long double** constant expression. Used as an error value returned by the mathematics library. HUGE_VALL evaluates to +infinity on systems supporting IEEE Std 754-1985.
	INFINITY	A constant expression of type **float** representing positive or unsigned infinity, if available; else a positive constant of type **float** that overflows at translation time.
	NAN	A constant expression of type **float** representing a quiet NaN. This symbolic constant is only defined if the implementation supports quiet NaNs for the **float** type.

The following macros shall be defined for number classification. They represent the mutually-exclusive kinds of floating-point values. They expand to integer constant expressions with distinct values. Additional implementation-defined floating-point classifications, with macro definitions beginning with FP_ and an uppercase letter, may also be specified by the implementation.

FP_INFINITE
FP_NAN
FP_NORMAL
FP_SUBNORMAL
FP_ZERO

The following optional macros indicate whether the *fma*( ) family of functions are fast compared with direct code:

FP_FAST_FMA
FP_FAST_FMAF
FP_FAST_FMAL

If defined, the FP_FAST_FMA macro shall indicate that the *fma*( ) function generally executes about as fast as, or faster than, a multiply and an add of **double** operands. If undefined, the speed of execution is unspecified. The other macros have the equivalent meaning for the **float** and **long double** versions.

The following macros shall expand to integer constant expressions whose values are returned by *ilogb*(*x*) if *x* is zero or NaN, respectively. The value of FP_ILOGB0 shall be either {INT_MIN} or –{INT_MAX}. The value of FP_ILOGBNAN shall be either {INT_MAX} or {INT_MIN}.

FP_ILOGB0
FP_ILOGBNAN

The following macros shall expand to the integer constants 1 and 2, respectively;

MATH_ERRNO
MATH_ERREXCEPT

The following macro shall expand to an expression that has type **int** and the value MATH_ERRNO, MATH_ERREXCEPT, or the bitwise-inclusive OR of both:

math_errhandling

The value of math_errhandling is constant for the duration of the program. It is unspecified whether math_errhandling is a macro or an identifier with external linkage. If a macro definition is suppressed or a program defines an identifier with the name math_errhandling , the behavior is undefined. If the expression (math_errhandling & MATH_ERREXCEPT) can be non-zero, the implementation shall define the macros FE_DIVBYZERO, FE_INVALID, and FE_OVERFLOW in **<fenv.h>**.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
double      acos(double);
float       acosf(float);
double      acosh(double);
float       acoshf(float);
long double acoshl(long double);
long double acosl(long double);
double      asin(double);
float       asinf(float);
double      asinh(double);
float       asinhf(float);
long double asinhl(long double);
long double asinl(long double);
double      atan(double);
double      atan2(double, double);
float       atan2f(float, float);
long double atan2l(long double, long double);
float       atanf(float);
double      atanh(double);
float       atanhf(float);
long double atanhl(long double);
long double atanl(long double);
double      cbrt(double);
float       cbrtf(float);
long double cbrtl(long double);
double      ceil(double);
float       ceilf(float);
long double ceill(long double);
double      copysign(double, double);
float       copysignf(float, float);
long double copysignl(long double, long double);
double      cos(double);
float       cosf(float);
double      cosh(double);
```



```
9502        float       coshf(float);
9503        long double coshl(long double);
9504        long double cosl(long double);
9505        double      erf(double);
9506        double      erfc(double);
9507        float       erfcf(float);
9508        long double erfcl(long double);
9509        float       erff(float);
9510        long double erfl(long double);
9511        double      exp(double);
9512        double      exp2(double);
9513        float       exp2f(float);
9514        long double exp2l(long double);
9515        float       expf(float);
9516        long double expl(long double);
9517        double      expm1(double);
9518        float       expm1f(float);
9519        long double expm1l(long double);
9520        double      fabs(double);
9521        float       fabsf(float);
9522        long double fabsl(long double);
9523        double      fdim(double, double);
9524        float       fdimf(float, float);
9525        long double fdiml(long double, long double);
9526        double      floor(double);
9527        float       floorf(float);
9528        long double floorl(long double);
9529        double      fma(double, double, double);
9530        float       fmaf(float, float, float);
9531        long double fmal(long double, long double, long double);
9532        double      fmax(double, double);
9533        float       fmaxf(float, float);
9534        long double fmaxl(long double, long double);
9535        double      fmin(double, double);
9536        float       fminf(float, float);
9537        long double fminl(long double, long double);
9538        double      fmod(double, double);
9539        float       fmodf(float, float);
9540        long double fmodl(long double, long double);
9541        double      frexp(double, int *);
9542        float       frexpf(float value, int *);
9543        long double frexpl(long double value, int *);
9544        double      hypot(double, double);
9545        float       hypotf(float, float);
9546        long double hypotl(long double, long double);
9547        int         ilogb(double);
9548        int         ilogbf(float);
9549        int         ilogbl(long double);
9550 XSI    double      j0(double);
9551        double      j1(double);
9552        double      jn(int, double);
9553        double      ldexp(double, int);
```



```
9554        float       ldexpf(float, int);
9555        long double ldexpl(long double, int);
9556        double      lgamma(double);
9557        float       lgammaf(float);
9558        long double lgammal(long double);
9559        long long   llrint(double);
9560        long long   llrintf(float);
9561        long long   llrintl(long double);
9562        long long   llround(double);
9563        long long   llroundf(float);
9564        long long   llroundl(long double);
9565        double      log(double);
9566        double      log10(double);
9567        float       log10f(float);
9568        long double log10l(long double);
9569        double      log1p(double);
9570        float       log1pf(float);
9571        long double log1pl(long double);
9572        double      log2(double);
9573        float       log2f(float);
9574        long double log2l(long double);
9575        double      logb(double);
9576        float       logbf(float);
9577        long double logbl(long double);
9578        float       logf(float);
9579        long double logl(long double);
9580        long        lrint(double);
9581        long        lrintf(float);
9582        long        lrintl(long double);
9583        long        lround(double);
9584        long        lroundf(float);
9585        long        lroundl(long double);
9586        double      modf(double, double *);
9587        float       modff(float, float *);
9588        long double modfl(long double, long double *);
9589        double      nan(const char *);
9590        float       nanf(const char *);
9591        long double nanl(const char *);
9592        double      nearbyint(double);
9593        float       nearbyintf(float);
9594        long double nearbyintl(long double);
9595        double      nextafter(double, double);
9596        float       nextafterf(float, float);
9597        long double nextafterl(long double, long double);
9598        double      nexttoward(double, long double);
9599        float       nexttowardf(float, long double);
9600        long double nexttowardl(long double, long double);
9601        double      pow(double, double);
9602        float       powf(float, float);
9603        long double powl(long double, long double);
9604        double      remainder(double, double);
9605        float       remainderf(float, float);
```

```
        long double remainderl(long double, long double);
        double      remquo(double, double, int *);
        float       remquof(float, float, int *);
        long double remquol(long double, long double, int *);
        double      rint(double);
        float       rintf(float);
        long double rintl(long double);
        double      round(double);
        float       roundf(float);
        long double roundl(long double);
XSI     double      scalb(double, double);
        double      scalbln(double, long);
        float       scalblnf(float, long);
        long double scalblnl(long double, long);
        double      scalbn(double, int);
        float       scalbnf(float, int);
        long double scalbnl(long double, int);
        double      sin(double);
        float       sinf(float);
        double      sinh(double);
        float       sinhf(float);
        long double sinhl(long double);
        long double sinl(long double);
        double      sqrt(double);
        float       sqrtf(float);
        long double sqrtl(long double);
        double      tan(double);
        float       tanf(float);
        double      tanh(double);
        float       tanhf(float);
        long double tanhl(long double);
        long double tanl(long double);
        double      tgamma(double);
        float       tgammaf(float);
        long double tgammal(long double);
        double      trunc(double);
        float       truncf(float);
        long double truncl(long double);
XSI     double      y0(double);
        double      y1(double);
        double      yn(int, double);
```

The following external variable shall be defined:

```
XSI     extern int signgam;
```

The behavior of each of the functions defined in **<math.h>** is specified in the System Interfaces volume of IEEE Std 1003.1-2001 for all representable values of its input arguments, except where stated otherwise. Each function shall execute as if it were a single operation without generating any externally visible exceptional conditions.

APPLICATION USAGE

The FP_CONTRACT pragma can be used to allow (if the state is on) or disallow (if the state is off) the implementation to contract expressions. Each pragma can occur either outside external declarations or preceding all explicit declarations and statements inside a compound statement. When outside external declarations, the pragma takes effect from its occurrence until another FP_CONTRACT pragma is encountered, or until the end of the translation unit. When inside a compound statement, the pragma takes effect from its occurrence until another FP_CONTRACT pragma is encountered (including within a nested compound statement), or until the end of the compound statement; at the end of a compound statement the state for the pragma is restored to its condition just before the compound statement. If this pragma is used in any other context, the behavior is undefined. The default state (on or off) for the pragma is implementation-defined.

RATIONALE

Before the ISO/IEC 9899:1999 standard, the math library was defined only for the floating type **double**. All the names formed by appending `'f'` or `'l'` to a name in **<math.h>** were reserved to allow for the definition of **float** and **long double** libraries; and the ISO/IEC 9899:1999 standard provides for all three versions of math functions.

The functions *ecvt*(), *fcvt*(), and *gcvt*() have been dropped from the ISO C standard since their capability is available through *sprintf*(). These are provided on XSI-conformant systems supporting the Legacy Option Group.

FUTURE DIRECTIONS

None.

SEE ALSO

<stddef.h>, **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *acos*(), *acosh*(), *asin*(), *atan*(), *atan2*(), *cbrt*(), *ceil*(), *cos*(), *cosh*(), *erf*(), *exp*(), *expm1*(), *fabs*(), *floor*(), *fmod*(), *frexp*(), *hypot*(), *ilogb*(), *isnan*(), *j0*(), *ldexp*(), *lgamma*(), *log*(), *log10*(), *log1p*(), *logb*(), *modf*(), *nextafter*(), *pow*(), *remainder*(), *rint*(), *scalb*(), *sin*(), *sinh*(), *sqrt*(), *tan*(), *tanh*(), *y0*()

CHANGE HISTORY

First released in Issue 1.

Issue 6

This reference page is updated to align with the ISO/IEC 9899:1999 standard.

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/21 is applied, making it clear that the meaning of the FP_FAST_FMA macro is unspecified if the macro is undefined. 2 2

9687 **NAME**

9688 monetary.h — monetary types

9689 **SYNOPSIS**

9690 XSI
```
#include <monetary.h>
```
9691

9692 **DESCRIPTION**

9693 The **<monetary.h>** header shall define the following types:

9694 **size_t** As described in **<stddef.h>**.

9695 **ssize_t** As described in **<sys/types.h>**.

9696 The following shall be declared as a function and may also be defined as a macro. A function
9697 prototype shall be provided.

9698
```
ssize_t  strfmon(char *restrict, size_t, const char *restrict, ...);
```

9699 **APPLICATION USAGE**

9700 None.

9701 **RATIONALE**

9702 None.

9703 **FUTURE DIRECTIONS**

9704 None.

9705 **SEE ALSO**

9706 The System Interfaces volume of IEEE Std 1003.1-2001, *strfmon*( )

9707 **CHANGE HISTORY**

9708 First released in Issue 4.

9709 **Issue 6**

9710 The **restrict** keyword is added to the prototype for *strfmon*( ).

NAME

mqueue.h — message queues (**REALTIME**)

SYNOPSIS

MSG
```
#include <mqueue.h>
```

DESCRIPTION

The **<mqueue.h>** header shall define the **mqd_t** type, which is used for message queue descriptors. This is not an array type.

The **<mqueue.h>** header shall define the **sigevent** structure (as described in **<signal.h>**) and the **mq_attr** structure, which is used in getting and setting the attributes of a message queue. Attributes are initially set when the message queue is created. An **mq_attr** structure shall have at least the following fields:

`long`	`mq_flags`	Message queue flags.
`long`	`mq_maxmsg`	Maximum number of messages.
`long`	`mq_msgsize`	Maximum message size.
`long`	`mq_curmsgs`	Number of messages currently queued.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int      mq_close(mqd_t);
int      mq_getattr(mqd_t, struct mq_attr *);
int      mq_notify(mqd_t, const struct sigevent *);
mqd_t    mq_open(const char *, int, ...);
ssize_t  mq_receive(mqd_t, char *, size_t, unsigned *);
int      mq_send(mqd_t, const char *, size_t, unsigned );
int      mq_setattr(mqd_t, const struct mq_attr *restrict,
             struct mq_attr *restrict);
```
TMO
```
ssize_t  mq_timedreceive(mqd_t, char *restrict, size_t,
             unsigned *restrict, const struct timespec *restrict);
int      mq_timedsend(mqd_t, const char *, size_t, unsigned ,
             const struct timespec *);
```
```
int      mq_unlink(const char *);
```

Inclusion of the **<mqueue.h>** header may make visible symbols defined in the headers **<fcntl.h>**, **<signal.h>**, **<sys/types.h>**, and **<time.h>**.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<fcntl.h>, **<signal.h>**, **<sys/types.h>**, **<time.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *mq_close*( ), *mq_getattr*( ), *mq_notify*( ), *mq_open*( ), *mq_receive*( ), *mq_send*( ), *mq_setattr*( ), *mq_timedreceive*( ), *mq_timedsend*( ), *mq_unlink*( )

CHANGE HISTORY

First released in Issue 5. Included for alignment with the POSIX Realtime Extension.

Issue 6

The **<mqueue.h>** header is marked as part of the Message Passing option.

The *mq_timedreceive*( ) and *mq_timedsend*( ) functions are added for alignment with IEEE Std 1003.1d-1999.

The **restrict** keyword is added to the prototypes for *mq_setattr*( ) and *mq_timedreceive*( ).

NAME

ndbm.h — definitions for ndbm database operations

SYNOPSIS

XSI
```
#include <ndbm.h>
```

DESCRIPTION

The **<ndbm.h>** header shall define the **datum** type as a structure that includes at least the following members:

`void`	`*dptr`	A pointer to the application's data.
`size_t`	`dsize`	The size of the object pointed to by *dptr*.

The **size_t** type shall be defined as described in **<stddef.h>**.

The **<ndbm.h>** header shall define the **DBM** type.

The following constants shall be defined as possible values for the *store_mode* argument to *dbm_store*( ):

DBM_INSERT	Insertion of new entries only.
DBM_REPLACE	Allow replacing existing entries.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int     dbm_clearerr(DBM *);
void    dbm_close(DBM *);
int     dbm_delete(DBM *, datum);
int     dbm_error(DBM *);
datum   dbm_fetch(DBM *, datum);
datum   dbm_firstkey(DBM *);
datum   dbm_nextkey(DBM *);
DBM    *dbm_open(const char *, int, mode_t);
int     dbm_store(DBM *, datum, datum, int);
```

The **mode_t** type shall be defined through **typedef** as described in **<sys/types.h>**.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<stddef.h>, **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *dbm_clearerr*( )

CHANGE HISTORY

First released in Issue 4, Version 2.

Issue 5

References to the definitions of **size_t** and **mode_t** are added to the DESCRIPTION.

NAME

net/if.h — sockets local interfaces

SYNOPSIS

```
#include <net/if.h>
```

DESCRIPTION

The **<net/if.h>** header shall define the **if_nameindex** structure that includes at least the following members:

```
unsigned  if_index   Numeric index of the interface.
char      *if_name   Null-terminated name of the interface.
```

The **<net/if.h>** header shall define the following macro for the length of a buffer containing an interface name (including the terminating NULL character):

IF_NAMESIZE Interface name length.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
unsigned              if_nametoindex(const char *);
char                 *if_indextoname(unsigned, char *);
struct if_nameindex  *if_nameindex(void);
void                  if_freenameindex(struct if_nameindex *);
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *if_freenameindex*( ), *if_indextoname*( ), *if_nameindex*( ), *if_nametoindex*( )

CHANGE HISTORY

First released in Issue 6. Derived from the XNS, Issue 5.2 specification.

NAME

netdb.h — definitions for network database operations

SYNOPSIS

```
#include <netdb.h>
```

DESCRIPTION

The **<netdb.h>** header may define the **in_port_t** type and the **in_addr_t** type as described in **<netinet/in.h>**.

The **<netdb.h>** header shall define the **hostent** structure that includes at least the following members:

`char *h_name`	Official name of the host.
`char **h_aliases`	A pointer to an array of pointers to alternative host names, terminated by a null pointer.
`int h_addrtype`	Address type.
`int h_length`	The length, in bytes, of the address.
`char **h_addr_list`	A pointer to an array of pointers to network addresses (in network byte order) for the host, terminated by a null pointer.

The **<netdb.h>** header shall define the **netent** structure that includes at least the following members:

`char *n_name`	Official, fully-qualified (including the domain) name of the host.
`char **n_aliases`	A pointer to an array of pointers to alternative network names, terminated by a null pointer.
`int n_addrtype`	The address type of the network.
`uint32_t n_net`	The network number, in host byte order.

The **uint32_t** type shall be defined as described in **<inttypes.h>**.

The **<netdb.h>** header shall define the **protoent** structure that includes at least the following members:

`char *p_name`	Official name of the protocol.
`char **p_aliases`	A pointer to an array of pointers to alternative protocol names, terminated by a null pointer.
`int p_proto`	The protocol number.

The **<netdb.h>** header shall define the **servent** structure that includes at least the following members:

`char *s_name`	Official name of the service.
`char **s_aliases`	A pointer to an array of pointers to alternative service names, terminated by a null pointer.
`int s_port`	The port number at which the service resides, in network byte order.
`char *s_proto`	The name of the protocol to use when contacting the service.

The **<netdb.h>** header shall define the IPPORT_RESERVED macro with the value of the highest reserved Internet port number.

OB When the **<netdb.h>** header is included, *h_errno* shall be available as a modifiable lvalue of type **int**. It is unspecified whether *h_errno* is a macro or an identifier declared with external linkage.

The **<netdb.h>** header shall define the following macros for use as error values for *gethostbyaddr*( ) and *gethostbyname*( ):

HOST_NOT_FOUND
NO_DATA
NO_RECOVERY
TRY_AGAIN

Address Information Structure

The **<netdb.h>** header shall define the **addrinfo** structure that includes at least the following members:

`int`	`ai_flags`	Input flags.
`int`	`ai_family`	Address family of socket.
`int`	`ai_socktype`	Socket type.
`int`	`ai_protocol`	Protocol of socket.
`socklen_t`	`ai_addrlen`	Length of socket address.
`struct sockaddr`	`*ai_addr`	Socket address of socket.
`char`	`*ai_canonname`	Canonical name of service location.
`struct addrinfo`	`*ai_next`	Pointer to next in list.

The **<netdb.h>** header shall define the following macros that evaluate to bitwise-distinct integer constants for use in the *flags* field of the **addrinfo** structure:

AI_PASSIVE Socket address is intended for *bind*( ).

AI_CANONNAME
Request for canonical name.

AI_NUMERICHOST
Return numeric host address as name.

AI_NUMERICSERV
Inhibit service name resolution.

AI_V4MAPPED If no IPv6 addresses are found, query for IPv4 addresses and return them to the caller as IPv4-mapped IPv6 addresses.

AI_ALL Query for both IPv4 and IPv6 addresses.

AI_ADDRCONFIG
Query for IPv4 addresses only when an IPv4 address is configured; query for IPv6 addresses only when an IPv6 address is configured.

The **<netdb.h>** header shall define the following macros that evaluate to bitwise-distinct integer constants for use in the *flags* argument to *getnameinfo*( ):

NI_NOFQDN Only the nodename portion of the FQDN is returned for local hosts.

NI_NUMERICHOST
The numeric form of the node's address is returned instead of its name.

NI_NAMEREQD Return an error if the node's name cannot be located in the database.

NI_NUMERICSERV
The numeric form of the service address is returned instead of its name.

NI_NUMERICSCOPE 1
For IPv6 addresses, the numeric form of the scope identifier is returned 1
instead of its name. 1

NI_DGRAM Indicates that the service is a datagram service (SOCK_DGRAM).

Address Information Errors

The **<netdb.h>** header shall define the following macros for use as error values for *getaddrinfo*( ) and *getnameinfo*( ):

EAI_AGAIN The name could not be resolved at this time. Future attempts may succeed.

EAI_BADFLAGS The flags had an invalid value.

EAI_FAIL A non-recoverable error occurred.

EAI_FAMILY The address family was not recognized or the address length was invalid for the specified family.

EAI_MEMORY There was a memory allocation failure.

EAI_NONAME The name does not resolve for the supplied parameters.

NI_NAMEREQD is set and the host's name cannot be located, or both *nodename* and *servname* were null.

EAI_SERVICE The service passed was not recognized for the specified socket type.

EAI_SOCKTYPE The intended socket type was not recognized.

EAI_SYSTEM A system error occurred. The error code can be found in *errno*.

EAI_OVERFLOW
An argument buffer overflowed.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
void              endhostent(void);
void              endnetent(void);
void              endprotoent(void);
void              endservent(void);
void              freeaddrinfo(struct addrinfo *);
const char       *gai_strerror(int);
int               getaddrinfo(const char *restrict, const char *restrict,
                      const struct addrinfo *restrict,
                      struct addrinfo **restrict);
struct hostent   *gethostbyaddr(const void *, socklen_t, int);
struct hostent   *gethostbyname(const char *);
struct hostent   *gethostent(void);
int               getnameinfo(const struct sockaddr *restrict, socklen_t,
                      char *restrict, socklen_t, char *restrict,
                      socklen_t, int);                                    1
struct netent    *getnetbyaddr(uint32_t, int);
struct netent    *getnetbyname(const char *);
```



```
struct netent    *getnetent(void);
struct protoent  *getprotobyname(const char *);
struct protoent  *getprotobynumber(int);
struct protoent  *getprotoent(void);
struct servent   *getservbyname(const char *, const char *);
struct servent   *getservbyport(int, const char *);
struct servent   *getservent(void);
void              sethostent(int);
void              setnetent(int);
void              setprotoent(int);
void              setservent(int);
```

The type **socklen_t** shall be defined through **typedef** as described in **<sys/socket.h>**.

Inclusion of the **<netdb.h>** header may also make visible all symbols from **<netinet/in.h>**, **<sys/socket.h>**, and **<inttypes.h>**.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<netinet/in.h>, **<inttypes.h>**, **<sys/socket.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *bind*( ), *endhostent*( ), *endnetent*( ), *endprotoent*( ), *endservent*( ), *getaddrinfo*( ), *getnameinfo*( )

CHANGE HISTORY

First released in Issue 6. Derived from the XNS, Issue 5.2 specification.

The Open Group Base Resolution bwg2001-009 is applied, which changes the return type for *gai_strerror*( ) from **char *** to **const char ***. This is for coordination with the IPnG Working Group.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/11 is applied, adding a description of the NI_NUMERICSCOPE macro and correcting the *getnameinfo*( ) function prototype. These changes are for alignment with IPv6.

NAME

netinet/in.h — Internet address family

SYNOPSIS

```
#include <netinet/in.h>
```

DESCRIPTION

The **<netinet/in.h>** header shall define the following types:

in_port_t Equivalent to the type **uint16_t** as defined in **<inttypes.h>**.

in_addr_t Equivalent to the type **uint32_t** as defined in **<inttypes.h>**.

The **sa_family_t** type shall be defined as described in **<sys/socket.h>**.

The **uint8_t** and **uint32_t** type shall be defined as described in **<inttypes.h>**. Inclusion of the **<netinet/in.h>** header may also make visible all symbols from **<inttypes.h>** and **<sys/socket.h>**.

The **<netinet/in.h>** header shall define the **in_addr** structure that includes at least the following member:

```
in_addr_t  s_addr
```

The **<netinet/in.h>** header shall define the **sockaddr_in** structure that includes at least the following members: 2 2

`sa_family_t`	`sin_family`	AF_INET.
`in_port_t`	`sin_port`	Port number.
`struct in_addr`	`sin_addr`	IP address.

The *sin_port* and *sin_addr* members shall be in network byte order. 2

The **sockaddr_in** structure is used to store addresses for the Internet address family. Values of this type shall be cast by applications to **struct sockaddr** for use with socket functions.

IP6 The **<netinet/in.h>** header shall define the **in6_addr** structure that contains at least the following member:

```
uint8_t s6_addr[16]
```

This array is used to contain a 128-bit IPv6 address, stored in network byte order.

The **<netinet/in.h>** header shall define the **sockaddr_in6** structure that includes at least the following members: 2 2

`sa_family_t`	`sin6_family`	AF_INET6.
`in_port_t`	`sin6_port`	Port number.
`uint32_t`	`sin6_flowinfo`	IPv6 traffic class and flow information.
`struct in6_addr`	`sin6_addr`	IPv6 address.
`uint32_t`	`sin6_scope_id`	Set of interfaces for a scope.

The *sin6_port* and *sin6_addr* members shall be in network byte order. 2

The **sockaddr_in6** structure shall be set to zero by an application prior to using it, since implementations are free to have additional, implementation-defined fields in **sockaddr_in6**.

The *sin6_scope_id* field is a 32-bit integer that identifies a set of interfaces as appropriate for the scope of the address carried in the *sin6_addr* field. For a link scope *sin6_addr*, the application shall ensure that *sin6_scope_id* is a link index. For a site scope *sin6_addr*, the application shall ensure that *sin6_scope_id* is a site index. The mapping of *sin6_scope_id* to an interface or set of interfaces is implementation-defined.

The **<netinet/in.h>** header shall declare the following external variable:

```
const struct in6_addr in6addr_any
```

This variable is initialized by the system to contain the wildcard IPv6 address. The **<netinet/in.h>** header also defines the IN6ADDR_ANY_INIT macro. This macro must be constant at compile time and can be used to initialize a variable of type **struct in6_addr** to the IPv6 wildcard address.

The **<netinet/in.h>** header shall declare the following external variable:

```
const struct in6_addr in6addr_loopback
```

This variable is initialized by the system to contain the loopback IPv6 address. The **<netinet/in.h>** header also defines the IN6ADDR_LOOPBACK_INIT macro. This macro must be constant at compile time and can be used to initialize a variable of type **struct in6_addr** to the IPv6 loopback address.

The **<netinet/in.h>** header shall define the **ipv6_mreq** structure that includes at least the following members:

```
struct in6_addr  ipv6mr_multiaddr   IPv6 multicast address.
unsigned         ipv6mr_interface   Interface index.
```

The **<netinet/in.h>** header shall define the following macros for use as values of the *level* argument of *getsockopt*( ) and *setsockopt*( ):

IPPROTO_IP	Internet protocol.
IP6 IPPROTO_IPV6	Internet Protocol Version 6.
IPPROTO_ICMP	Control message protocol.
RS IPPROTO_RAW	Raw IP Packets Protocol.
IPPROTO_TCP	Transmission control protocol.
IPPROTO_UDP	User datagram protocol.

The **<netinet/in.h>** header shall define the following macros for use as destination addresses for *connect*( ), *sendmsg*( ), and *sendto*( ):

INADDR_ANY	IPv4 local host address.
INADDR_BROADCAST	IPv4 broadcast address.

The **<netinet/in.h>** header shall define the following macro to help applications declare buffers of the proper size to store IPv4 addresses in string form:

INET_ADDRSTRLEN	16. Length of the string form for IP.

The *htonl*( ), *htons*( ), *ntohl*( ), and *ntohs*( ) functions shall be available as defined in **<arpa/inet.h>**. Inclusion of the **<netinet/in.h>** header may also make visible all symbols from **<arpa/inet.h>**.

IP6 The **<netinet/in.h>** header shall define the following macro to help applications declare buffers of the proper size to store IPv6 addresses in string form:

INET6_ADDRSTRLEN	46. Length of the string form for IPv6.

The **<netinet/in.h>** header shall define the following macros, with distinct integer values, for use in the *option_name* argument in the *getsockopt*( ) or *setsockopt*( ) functions at protocol level IPPROTO_IPV6:

IPV6_JOIN_GROUP	Join a multicast group.
IPV6_LEAVE_GROUP	Quit a multicast group.
IPV6_MULTICAST_HOPS	Multicast hop limit.
IPV6_MULTICAST_IF	Interface to use for outgoing multicast packets.
IPV6_MULTICAST_LOOP	Multicast packets are delivered back to the local application.
IPV6_UNICAST_HOPS	Unicast hop limit.
IPV6_V6ONLY	Restrict AF_INET6 socket to IPv6 communications only.

The **<netinet/in.h>** header shall define the following macros that test for special IPv6 addresses. Each macro is of type **int** and takes a single argument of type **const struct in6_addr ***:

IN6_IS_ADDR_UNSPECIFIED
: Unspecified address.

IN6_IS_ADDR_LOOPBACK
: Loopback address.

IN6_IS_ADDR_MULTICAST
: Multicast address.

IN6_IS_ADDR_LINKLOCAL
: Unicast link-local address.

IN6_IS_ADDR_SITELOCAL
: Unicast site-local address.

IN6_IS_ADDR_V4MAPPED
: IPv4 mapped address.

IN6_IS_ADDR_V4COMPAT
: IPv4-compatible address.

IN6_IS_ADDR_MC_NODELOCAL
: Multicast node-local address.

IN6_IS_ADDR_MC_LINKLOCAL
: Multicast link-local address.

IN6_IS_ADDR_MC_SITELOCAL
: Multicast site-local address.

IN6_IS_ADDR_MC_ORGLOCAL
: Multicast organization-local address.

IN6_IS_ADDR_MC_GLOBAL
: Multicast global address.

10106 **APPLICATION USAGE**

10107 None.

10108 **RATIONALE**

10109 None.

10110 **FUTURE DIRECTIONS**

10111 None.

10112 **SEE ALSO**

10113 Section 4.8 (on page 99), **<arpa/inet.h>**, **<inttypes.h>**, **<sys/socket.h>**, the System Interfaces
10114 volume of IEEE Std 1003.1-2001, *connect*( ), *getsockopt*( ), *htonl*( ), *htons*( ), *ntohl*( ), *ntohs*( ),
10115 *sendmsg*( ), *sendto*( ), *setsockopt*( )

10116 **CHANGE HISTORY**

10117 First released in Issue 6. Derived from the XNS, Issue 5.2 specification.

10118 The *sin_zero* member was removed from the **sockaddr_in** structure as per The Open Group Base
10119 Resolution bwg2001-004.

10120 IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/12 is applied, adding **const** qualifiers to 1
10121 the *in6addr_any* and *in6addr_loopback* external variables. 1

10122 IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/22 is applied, making it clear which 2
10123 structure members are in network byte order. 2

NAME

netinet/tcp.h — definitions for the Internet Transmission Control Protocol (TCP)

SYNOPSIS

```
#include <netinet/tcp.h>
```

DESCRIPTION

The **<netinet/tcp.h>** header shall define the following macro for use as a socket option at the IPPROTO_TCP level:

TCP_NODELAY Avoid coalescing of small segments.

The macro shall be defined in the header. The implementation need not allow the value of the option to be set via *setsockopt*( ) or retrieved via *getsockopt*( ).

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<sys/socket.h>, the System Interfaces volume of IEEE Std 1003.1-2001, *getsockopt*( ), *setsockopt*( )

CHANGE HISTORY

First released in Issue 6. Derived from the XNS, Issue 5.2 specification.

NAME

nl_types.h — data types

SYNOPSIS

XSI
```
#include <nl_types.h>
```

DESCRIPTION

The **<nl_types.h>** header shall contain definitions of at least the following types:

nl_catd Used by the message catalog functions *catopen*( ), *catgets*( ), and *catclose*( ) to identify a catalog descriptor.

nl_item Used by *nl_langinfo*( ) to identify items of *langinfo* data. Values of objects of type **nl_item** are defined in **<langinfo.h>**.

The **<nl_types.h>** header shall contain definitions of at least the following constants:

NL_SETD Used by *gencat* when no $*set* directive is specified in a message text source file; see the Internationalization Guide. This constant can be passed as the value of *set_id* on subsequent calls to *catgets*( ) (that is, to retrieve messages from the default message set). The value of NL_SETD is implementation-defined.

NL_CAT_LOCALE Value that must be passed as the *oflag* argument to *catopen*( ) to ensure that message catalog selection depends on the *LC_MESSAGES* locale category, rather than directly on the *LANG* environment variable.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int       catclose(nl_catd);
char     *catgets(nl_catd, int, int, const char *);
nl_catd   catopen(const char *, int);
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<langinfo.h>, the System Interfaces volume of IEEE Std 1003.1-2001, *catclose*( ), *catgets*( ), *catopen*( ), *nl_langinfo*( ), the Shell and Utilities volume of IEEE Std 1003.1-2001, *gencat*

CHANGE HISTORY

First released in Issue 2.

10180 **NAME**

10181 poll.h — definitions for the poll( ) function

10182 **SYNOPSIS**

10183 XSI
```
#include <poll.h>
```
10184

10185 **DESCRIPTION**

10186 The **<poll.h>** header shall define the **pollfd** structure that includes at least the following
10187 members:

10188 `int fd` The following descriptor being polled.
10189 `short events` The input event flags (see below).
10190 `short revents` The output event flags (see below).

10191 The **<poll.h>** header shall define the following type through **typedef**:

10192 **nfds_t** An unsigned integer type used for the number of file descriptors.

10193 The implementation shall support one or more programming environments in which the width
10194 of **nfds_t** is no greater than the width of type **long**. The names of these programming
10195 environments can be obtained using the *confstr*( ) function or the *getconf* utility.

10196 The following symbolic constants shall be defined, zero or more of which may be OR'ed together
10197 to form the *events* or *revents* members in the **pollfd** structure:

10198 POLLIN Data other than high-priority data may be read without blocking.

10199 POLLRDNORM Normal data may be read without blocking.

10200 POLLRDBAND Priority data may be read without blocking.

10201 POLLPRI High priority data may be read without blocking.

10202 POLLOUT Normal data may be written without blocking.

10203 POLLWRNORM Equivalent to POLLOUT.

10204 POLLWRBAND Priority data may be written.

10205 POLLERR An error has occurred (*revents* only).

10206 POLLHUP Device has been disconnected (*revents* only).

10207 POLLNVAL Invalid *fd* member (*revents* only).

10208 The significance and semantics of normal, priority, and high-priority data are file and device-
10209 specific.

10210 The following shall be declared as a function and may also be defined as a macro. A function
10211 prototype shall be provided.

10212
```
int   poll(struct pollfd[], nfds_t, int);
```


APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *confstr*( ), *poll*( ), the Shell and Utilities volume of IEEE Std 1003.1-2001, *getconf*

CHANGE HISTORY

First released in Issue 4, Version 2.

Issue 6

The description of the symbolic constants is updated to match the *poll*( ) function.

Text related to STREAMS has been moved to the *poll*( ) reference page.

A note is added to the DESCRIPTION regarding the significance and semantics of normal, priority, and high-priority data.

NAME

pthread.h — threads

SYNOPSIS

THR
```
#include <pthread.h>
```

DESCRIPTION

The **<pthread.h>** header shall define the following symbols:

BAR PTHREAD_BARRIER_SERIAL_THREAD
PTHREAD_CANCEL_ASYNCHRONOUS
PTHREAD_CANCEL_ENABLE
PTHREAD_CANCEL_DEFERRED
PTHREAD_CANCEL_DISABLE
PTHREAD_CANCELED
PTHREAD_COND_INITIALIZER
PTHREAD_CREATE_DETACHED
PTHREAD_CREATE_JOINABLE
PTHREAD_EXPLICIT_SCHED
PTHREAD_INHERIT_SCHED
XSI PTHREAD_MUTEX_DEFAULT
PTHREAD_MUTEX_ERRORCHECK
PTHREAD_MUTEX_INITIALIZER
XSI PTHREAD_MUTEX_NORMAL
PTHREAD_MUTEX_RECURSIVE
PTHREAD_ONCE_INIT
TPI PTHREAD_PRIO_INHERIT 1
TPP|TPI PTHREAD_PRIO_NONE 1
TPP PTHREAD_PRIO_PROTECT 1
PTHREAD_PROCESS_SHARED
PTHREAD_PROCESS_PRIVATE
TPS PTHREAD_SCOPE_PROCESS
PTHREAD_SCOPE_SYSTEM

The following types shall be defined as described in **<sys/types.h>**:

pthread_attr_t
BAR **pthread_barrier_t**
pthread_barrierattr_t
pthread_cond_t
pthread_condattr_t
pthread_key_t
pthread_mutex_t
pthread_mutexattr_t
pthread_once_t
pthread_rwlock_t
pthread_rwlockattr_t
SPI **pthread_spinlock_t**
pthread_t

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.


```
10277          int   pthread_atfork(void (*)(void), void (*)(void),
10278                    void(*)(void));
10279          int   pthread_attr_destroy(pthread_attr_t *);
10280          int   pthread_attr_getdetachstate(const pthread_attr_t *, int *);
10281 XSI      int   pthread_attr_getguardsize(const pthread_attr_t *restrict,
10282                    size_t *restrict);
10283 TPS      int   pthread_attr_getinheritsched(const pthread_attr_t *restrict,
10284                    int *restrict);
10285          int   pthread_attr_getschedparam(const pthread_attr_t *restrict,
10286                    struct sched_param *restrict);
10287 TPS      int   pthread_attr_getschedpolicy(const pthread_attr_t *restrict,
10288                    int *restrict);
10289 TPS      int   pthread_attr_getscope(const pthread_attr_t *restrict,
10290                    int *restrict);
10291 TSA TSS  int   pthread_attr_getstack(const pthread_attr_t *restrict,
10292                    void **restrict, size_t *restrict);
10293 TSA      int   pthread_attr_getstackaddr(const pthread_attr_t *restrict,
10294                    void **restrict);
10295 TSS      int   pthread_attr_getstacksize(const pthread_attr_t *restrict,          1
10296                    size_t *restrict);
10297          int   pthread_attr_init(pthread_attr_t *);
10298          int   pthread_attr_setdetachstate(pthread_attr_t *, int);
10299 XSI      int   pthread_attr_setguardsize(pthread_attr_t *, size_t);
10300 TPS      int   pthread_attr_setinheritsched(pthread_attr_t *, int);
10301          int   pthread_attr_setschedparam(pthread_attr_t *restrict,
10302                    const struct sched_param *restrict);
10303 TPS      int   pthread_attr_setschedpolicy(pthread_attr_t *, int);
10304          int   pthread_attr_setscope(pthread_attr_t *, int);
10305 TSA TSS  int   pthread_attr_setstack(pthread_attr_t *, void *, size_t);
10306 TSA      int   pthread_attr_setstackaddr(pthread_attr_t *, void *);
10307 TSS      int   pthread_attr_setstacksize(pthread_attr_t *, size_t);               1
10308 BAR      int   pthread_barrier_destroy(pthread_barrier_t *);
10309          int   pthread_barrier_init(pthread_barrier_t *restrict,
10310                    const pthread_barrierattr_t *restrict, unsigned);
10311          int   pthread_barrier_wait(pthread_barrier_t *);
10312          int   pthread_barrierattr_destroy(pthread_barrierattr_t *);
10313 BAR TSH  int   pthread_barrierattr_getpshared(
10314                    const pthread_barrierattr_t *restrict, int *restrict);
10315 BAR      int   pthread_barrierattr_init(pthread_barrierattr_t *);
10316 BAR TSH  int   pthread_barrierattr_setpshared(pthread_barrierattr_t *, int);
10317          int   pthread_cancel(pthread_t);
10318          void  pthread_cleanup_push(void (*)(void *), void *);
10319          void  pthread_cleanup_pop(int);
10320          int   pthread_cond_broadcast(pthread_cond_t *);
10321          int   pthread_cond_destroy(pthread_cond_t *);
10322          int   pthread_cond_init(pthread_cond_t *restrict,
10323                    const pthread_condattr_t *restrict);
10324          int   pthread_cond_signal(pthread_cond_t *);
10325          int   pthread_cond_timedwait(pthread_cond_t *restrict,
10326                    pthread_mutex_t *restrict, const struct timespec *restrict);
10327          int   pthread_cond_wait(pthread_cond_t *restrict,
10328                    pthread_mutex_t *restrict);
```



```
10329          int   pthread_condattr_destroy(pthread_condattr_t *);
10330 CS       int   pthread_condattr_getclock(const pthread_condattr_t *restrict,
10331                    clockid_t *restrict);
10332 TSH      int   pthread_condattr_getpshared(const pthread_condattr_t *restrict,
10333                    int *restrict);
10334          int   pthread_condattr_init(pthread_condattr_t *);
10335 CS       int   pthread_condattr_setclock(pthread_condattr_t *, clockid_t);
10336 TSH      int   pthread_condattr_setpshared(pthread_condattr_t *, int);
10337          int   pthread_create(pthread_t *restrict, const pthread_attr_t *restrict,
10338                    void *(*)(void *), void *restrict);
10339          int   pthread_detach(pthread_t);
10340          int   pthread_equal(pthread_t, pthread_t);
10341          void  pthread_exit(void *);
10342 XSI      int   pthread_getconcurrency(void);
10343 TCT      int   pthread_getcpuclockid(pthread_t, clockid_t *);
10344 TPS      int   pthread_getschedparam(pthread_t, int *restrict,
10345                    struct sched_param *restrict);
10346          void *pthread_getspecific(pthread_key_t);
10347          int   pthread_join(pthread_t, void **);
10348          int   pthread_key_create(pthread_key_t *, void (*)(void *));
10349          int   pthread_key_delete(pthread_key_t);
10350          int   pthread_mutex_destroy(pthread_mutex_t *);
10351 TPP      int   pthread_mutex_getprioceiling(const pthread_mutex_t *restrict,
10352                    int *restrict);
10353          int   pthread_mutex_init(pthread_mutex_t *restrict,
10354                    const pthread_mutexattr_t *restrict);
10355          int   pthread_mutex_lock(pthread_mutex_t *);
10356 TPP      int   pthread_mutex_setprioceiling(pthread_mutex_t *restrict, int,
10357                    int *restrict);
10358 TMO      int   pthread_mutex_timedlock(pthread_mutex_t *,
10359                    const struct timespec *);
10360          int   pthread_mutex_trylock(pthread_mutex_t *);
10361          int   pthread_mutex_unlock(pthread_mutex_t *);
10362          int   pthread_mutexattr_destroy(pthread_mutexattr_t *);
10363 TPP      int   pthread_mutexattr_getprioceiling(
10364                    const pthread_mutexattr_t *restrict, int *restrict);
10365 TPP|TPI  int   pthread_mutexattr_getprotocol(const pthread_mutexattr_t *restrict,
10366                    int *restrict);
10367 TSH      int   pthread_mutexattr_getpshared(const pthread_mutexattr_t *restrict,  1
10368                    int *restrict);
10369 XSI      int   pthread_mutexattr_gettype(const pthread_mutexattr_t *restrict,
10370                    int *restrict);
10371          int   pthread_mutexattr_init(pthread_mutexattr_t *);
10372 TPP      int   pthread_mutexattr_setprioceiling(pthread_mutexattr_t *, int);
10373 TPP|TPI  int   pthread_mutexattr_setprotocol(pthread_mutexattr_t *, int);
10374 TSH      int   pthread_mutexattr_setpshared(pthread_mutexattr_t *, int);          1
10375 XSI      int   pthread_mutexattr_settype(pthread_mutexattr_t *, int);
10376          int   pthread_once(pthread_once_t *, void (*)(void));
10377          int   pthread_rwlock_destroy(pthread_rwlock_t *);
10378          int   pthread_rwlock_init(pthread_rwlock_t *restrict,
10379                    const pthread_rwlockattr_t *restrict);
10380          int   pthread_rwlock_rdlock(pthread_rwlock_t *);
```

```
TMO  int   pthread_rwlock_timedrdlock(pthread_rwlock_t *restrict,
                const struct timespec *restrict);
     int   pthread_rwlock_timedwrlock(pthread_rwlock_t *restrict,
                const struct timespec *restrict);
     int   pthread_rwlock_tryrdlock(pthread_rwlock_t *);
     int   pthread_rwlock_trywrlock(pthread_rwlock_t *);
     int   pthread_rwlock_unlock(pthread_rwlock_t *);
     int   pthread_rwlock_wrlock(pthread_rwlock_t *);
     int   pthread_rwlockattr_destroy(pthread_rwlockattr_t *);
TSH  int   pthread_rwlockattr_getpshared(
                const pthread_rwlockattr_t *restrict, int *restrict);
     int   pthread_rwlockattr_init(pthread_rwlockattr_t *);
TSH  int   pthread_rwlockattr_setpshared(pthread_rwlockattr_t *, int);
     pthread_t
           pthread_self(void);
     int   pthread_setcancelstate(int, int *);
     int   pthread_setcanceltype(int, int *);
XSI  int   pthread_setconcurrency(int);
TPS  int   pthread_setschedparam(pthread_t, int,
                const struct sched_param *);
TPS  int   pthread_setschedprio(pthread_t, int);
     int   pthread_setspecific(pthread_key_t, const void *);
SPI  int   pthread_spin_destroy(pthread_spinlock_t *);
     int   pthread_spin_init(pthread_spinlock_t *, int);
     int   pthread_spin_lock(pthread_spinlock_t *);
     int   pthread_spin_trylock(pthread_spinlock_t *);
     int   pthread_spin_unlock(pthread_spinlock_t *);
     void  pthread_testcancel(void);
```

Inclusion of the **<pthread.h>** header shall make symbols defined in the headers **<sched.h>** and **<time.h>** visible.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<sched.h>, **<sys/types.h>**, **<time.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *pthread_attr_getguardsize*( ), *pthread_attr_init*( ), *pthread_attr_setscope*( ), *pthread_barrier_destroy*( ), *pthread_barrier_init*( ), *pthread_barrier_wait*( ), *pthread_barrierattr_destroy*( ), *pthread_barrierattr_getpshared*( ), *pthread_barrierattr_init*( ), *pthread_barrierattr_setpshared*( ), *pthread_cancel*( ), *pthread_cleanup_pop*( ), *pthread_cond_init*( ), *pthread_cond_signal*( ), *pthread_cond_wait*( ), *pthread_condattr_getclock*( ), *pthread_condattr_init*( ), *pthread_condattr_setclock*( ), *pthread_create*( ), *pthread_detach*( ), *pthread_equal*( ), *pthread_exit*( ), *pthread_getconcurrency*( ), *pthread_getcpuclockid*( ), *pthread_getschedparam*( ), *pthread_join*( ), *pthread_key_create*( ), *pthread_key_delete*( ), *pthread_mutex_init*( ), *pthread_mutex_lock*( ), *pthread_mutex_setprioceiling*( ), *pthread_mutex_timedlock*( ), *pthread_mutexattr_init*( ), *pthread_mutexattr_gettype*( ), *pthread_mutexattr_setprotocol*( ), *pthread_once*( ), *pthread_rwlock_destroy*( ), *pthread_rwlock_init*( ), *pthread_rwlock_rdlock*( ), *pthread_rwlock_timedrdlock*( ), *pthread_rwlock_timedwrlock*( ), *pthread_rwlock_tryrdlock*( ),

pthread_rwlock_trywrlock( ), *pthread_rwlock_unlock*( ), *pthread_rwlock_wrlock*( ), *pthread_rwlockattr_destroy*( ), *pthread_rwlockattr_getpshared*( ), *pthread_rwlockattr_init*( ), *pthread_rwlockattr_setpshared*( ), *pthread_self*( ), *pthread_setcancelstate*( ), *pthread_setspecific*( ), *pthread_spin_destroy*( ), *pthread_spin_init*( ), *pthread_spin_lock*( ), *pthread_spin_trylock*( ), *pthread_spin_unlock*( )

CHANGE HISTORY

First released in Issue 5. Included for alignment with the POSIX Threads Extension.

Issue 6

The RTT margin markers are broken out into their POSIX options.

The Open Group Corrigendum U021/9 is applied, correcting the prototype for the *pthread_cond_wait*( ) function.

The Open Group Corrigendum U026/2 is applied, correcting the prototype for the *pthread_setschedparam*( ) function so that its second argument is of type **int**.

The *pthread_getcpuclockid*( ) and *pthread_mutex_timedlock*( ) functions are added for alignment with IEEE Std 1003.1d-1999.

The following functions are added for alignment with IEEE Std 1003.1j-2000:
pthread_barrier_destroy( ), *pthread_barrier_init*( ), *pthread_barrier_wait*( ), *pthread_barrierattr_destroy*( ), *pthread_barrierattr_getpshared*( ), *pthread_barrierattr_init*( ), *pthread_barrierattr_setpshared*( ), *pthread_condattr_getclock*( ), *pthread_condattr_setclock*( ), *pthread_rwlock_timedrdlock*( ), *pthread_rwlock_timedwrlock*( ), *pthread_spin_destroy*( ), *pthread_spin_init*( ), *pthread_spin_lock*( ), *pthread_spin_trylock*( ), and *pthread_spin_unlock*( ).

PTHREAD_RWLOCK_INITIALIZER is deleted for alignment with IEEE Std 1003.1j-2000.

Functions previously marked as part of the Read-Write Locks option are now moved to the Threads option.

The **restrict** keyword is added to the prototypes for *pthread_attr_getguardsize*( ), *pthread_attr_getinheritsched*( ), *pthread_attr_getschedparam*( ), *pthread_attr_getschedpolicy*( ), *pthread_attr_getscope*( ), *pthread_attr_getstackaddr*( ), *pthread_attr_getstacksize*( ), *pthread_attr_setschedparam*( ), *pthread_barrier_init*( ), *pthread_barrierattr_getpshared*( ), *pthread_cond_init*( ), *pthread_cond_signal*( ), *pthread_cond_timedwait*( ), *pthread_cond_wait*( ), *pthread_condattr_getclock*( ), *pthread_condattr_getpshared*( ), *pthread_create*( ), *pthread_getschedparam*( ), *pthread_mutex_getprioceiling*( ), *pthread_mutex_init*( ), *pthread_mutex_setprioceiling*( ), *pthread_mutexattr_getprioceiling*( ), *pthread_mutexattr_getprotocol*( ), *pthread_mutexattr_getpshared*( ), *pthread_mutexattr_gettype*( ), *pthread_rwlock_init*( ), *pthread_rwlock_timedrdlock*( ), *pthread_rwlock_timedwrlock*( ), *pthread_rwlockattr_getpshared*( ), and *pthread_sigmask*( ).

IEEE PASC Interpretation 1003.1 #86 is applied, allowing the symbols from **<sched.h>** and **<time.h>** to be made visible when **<pthread.h>** is included. Previously this was an XSI extension.

IEEE PASC Interpretation 1003.1c #42 is applied, removing the requirement for prototypes for the *pthread_kill*( ) and *pthread_sigmask*( ) functions. These are required to be in the **<signal.h>** header. They are allowed here through the name space rules.

IEEE PASC Interpretation 1003.1 #96 is applied, adding the *pthread_setschedprio*( ) function.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/13 is applied, correcting shading errors that were in contradiction with the System Interfaces volume of IEEE Std 1003.1-2001.

10475 **NAME**

10476 pwd.h — password structure

10477 **SYNOPSIS**

10478 `#include <pwd.h>`

10479 **DESCRIPTION**

10480 The **<pwd.h>** header shall provide a definition for **struct passwd**, which shall include at least the
10481 following members:

10482 `char *pw_name` User's login name.
10483 `uid_t pw_uid` Numerical user ID.
10484 `gid_t pw_gid` Numerical group ID.
10485 `char *pw_dir` Initial working directory.
10486 `char *pw_shell` Program to use as shell.

10487 The **gid_t** and **uid_t** types shall be defined as described in **<sys/types.h>**.

10488 The following shall be declared as functions and may also be defined as macros. Function
10489 prototypes shall be provided.

```
10490      struct passwd *getpwnam(const char *);
10491      struct passwd *getpwuid(uid_t);
10492 TSF  int           getpwnam_r(const char *, struct passwd *, char *,
10493                        size_t, struct passwd **);
10494      int           getpwuid_r(uid_t, struct passwd *, char *,
10495                        size_t, struct passwd **);
10496 XSI  void          endpwent(void);
10497      struct passwd *getpwent(void);
10498      void          setpwent(void);
```

10499

10500 **APPLICATION USAGE**

10501 None.

10502 **RATIONALE**

10503 None.

10504 **FUTURE DIRECTIONS**

10505 None.

10506 **SEE ALSO**

10507 **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *endpwent*( ), *getpwnam*( ),
10508 *getpwuid*( )

10509 **CHANGE HISTORY**

10510 First released in Issue 1.

10511 **Issue 5**

10512 The DESCRIPTION is updated for alignment with the POSIX Threads Extension.

10513 **Issue 6**

10514 The following new requirements on POSIX implementations derive from alignment with the
10515 Single UNIX Specification:

10516 - The **gid_t** and **uid_t** types are mandated.

10517 - The *getpwnam_r*( ) and *getpwuid_r*( ) functions are marked as part of the Thread-Safe
10518 Functions option.

10519 **NAME**

10520 regex.h — regular expression matching types

10521 **SYNOPSIS**

10522 `#include <regex.h>`

10523 **DESCRIPTION**

10524 The **<regex.h>** header shall define the structures and symbolic constants used by the *regcomp*( ),
10525 *regexec*( ), *regerror*( ), and *regfree*( ) functions.

10526 The structure type **regex_t** shall contain at least the following member:

10527 `size_t re_nsub` Number of parenthesized subexpressions.

10528 The type **size_t** shall be defined as described in **<sys/types.h>**.

10529 The type **regoff_t** shall be defined as a signed integer type that can hold the largest value that
10530 can be stored in either a type **off_t** or type **ssize_t**. The structure type **regmatch_t** shall contain
10531 at least the following members:

10532 `regoff_t rm_so` Byte offset from start of string
10533 to start of substring.
10534 `regoff_t rm_eo` Byte offset from start of string of the
10535 first character after the end of substring.

10536 Values for the *cflags* parameter to the *regcomp*( ) function are as follows:

10537 REG_EXTENDED Use Extended Regular Expressions.

10538 REG_ICASE Ignore case in match.

10539 REG_NOSUB Report only success or fail in *regexec*( ).

10540 REG_NEWLINE Change the handling of <newline>.

10541 Values for the *eflags* parameter to the *regexec*( ) function are as follows:

10542 REG_NOTBOL The circumflex character (`'^'`), when taken as a special character, does
10543 not match the beginning of *string*.

10544 REG_NOTEOL The dollar sign (`'$'`), when taken as a special character, does not match
10545 the end of *string*.

10546 The following constants shall be defined as error return values:

10547 REG_NOMATCH *regexec*( ) failed to match.

10548 REG_BADPAT Invalid regular expression.

10549 REG_ECOLLATE Invalid collating element referenced.

10550 REG_ECTYPE Invalid character class type referenced.

10551 REG_EESCAPE Trailing `'\'` in pattern.

10552 REG_ESUBREG Number in *digit* invalid or in error.

10553 REG_EBRACK `"[]"` imbalance.

10554 REG_EPAREN `"\(\)"` or `"()"` imbalance.

10555 REG_EBRACE `"\{\}"` imbalance.

10556 REG_BADBR Content of `"\{\}"` invalid: not a number, number too large, more than
10557 two numbers, first larger than second.

REG_ERANGE	Invalid endpoint in range expression.
REG_ESPACE	Out of memory.
REG_BADRPT	`'?'`, `'*'`, or `'+'` not preceded by valid regular expression.
OB REG_ENOSYS	Reserved.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int    regcomp(regex_t *restrict, const char *restrict, int);
size_t regerror(int, const regex_t *restrict, char *restrict, size_t);
int    regexec(const regex_t *restrict, const char *restrict, size_t,
           regmatch_t[restrict], int);
void   regfree(regex_t *);
```

The implementation may define additional macros or constants using names beginning with REG_.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<sys/types.h>, the System Interfaces volume of IEEE Std 1003.1-2001, *regcomp*( ), the Shell and Utilities volume of IEEE Std 1003.1-2001

CHANGE HISTORY

First released in Issue 4.

Originally derived from the ISO POSIX-2 standard.

Issue 6

The REG_ENOSYS constant is marked obsolescent.

The **restrict** keyword is added to the prototypes for *regcomp*( ), *regerror*( ), and *regexec*( ).

A statement is added that the **size_t** type is defined as described in **<sys/types.h>**.

NAME

sched.h — execution scheduling (**REALTIME**)

SYNOPSIS

PS
```
#include <sched.h>
```

DESCRIPTION

The **<sched.h>** header shall define the **sched_param** structure, which contains the scheduling parameters required for implementation of each supported scheduling policy. This structure shall contain at least the following member:

THR	`int`	`sched_priority`	Process or thread execution scheduling priority. 2

SS|TSP In addition, if _POSIX_SPORADIC_SERVER or _POSIX_THREAD_SPORADIC_SERVER is defined, the **sched_param** structure defined in **<sched.h>** shall contain the following members in addition to those specified above:

`int`	`sched_ss_low_priority`	Low scheduling priority for sporadic server.
`struct timespec`	`sched_ss_repl_period`	Replenishment period for sporadic server.
`struct timespec`	`sched_ss_init_budget`	Initial budget for sporadic server.
`int`	`sched_ss_max_repl`	Maximum pending replenishments for sporadic server.

THR Each process or thread is controlled by an associated scheduling policy and priority. Associated with each policy is a priority range. Each policy definition specifies the minimum priority range for that policy. The priority ranges for each policy may overlap the priority ranges of other policies. 2

Four scheduling policies are defined; others may be defined by the implementation. The four standard policies are indicated by the values of the following symbolic constants:

SCHED_FIFO	First in-first out (FIFO) scheduling policy.
SCHED_RR	Round robin scheduling policy.
SS|TSP SCHED_SPORADIC	Sporadic server scheduling policy.
SCHED_OTHER	Another scheduling policy.

The values of these constants are distinct.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
TPS int    sched_get_priority_max(int);                                    1
    int    sched_get_priority_min(int);
    int    sched_getparam(pid_t, struct sched_param *);                    1
    int    sched_getscheduler(pid_t);
TPS int    sched_rr_get_interval(pid_t, struct timespec *);                1
    int    sched_setparam(pid_t, const struct sched_param *);              1
    int    sched_setscheduler(pid_t, int, const struct sched_param *);
THR int    sched_yield(void);                                              1
```

Inclusion of the **<sched.h>** header may make visible all symbols from the **<time.h>** header.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<time.h>

CHANGE HISTORY

First released in Issue 5. Included for alignment with the POSIX Realtime Extension.

Issue 6

The **<sched.h>** header is marked as part of the Process Scheduling option.

Sporadic server members are added to the **sched_param** structure, and the SCHED_SPORADIC scheduling policy is added for alignment with IEEE Std 1003.1d-1999.

IEEE PASC Interpretation 1003.1 #108 is applied, correcting the **sched_param** structure whose members *sched_ss_repl_period* and *sched_ss_init_budget* should be type **struct timespec** and not **timespec**.

Symbols from **<time.h>** may be made visible when **<sched.h>** is included.

IEEE Std 1003.1-2001/Cor 1-2002, items XSH/TC1/D6/52 and XSH/TC1/D6/53 are applied, aligning the function prototype shading and margin codes with the System Interfaces volume of IEEE Std 1003.1-2001. 1

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/23 is applied, updating the DESCRIPTION to differentiate between thread and process execution. 2

10654 **NAME**

10655 search.h — search tables

10656 **SYNOPSIS**

10657 XSI
```
#include <search.h>
```
10658

10659 **DESCRIPTION**

10660 The **<search.h>** header shall define the **ENTRY** type for structure **entry** which shall include the
10661 following members:

```
10662 char    *key
10663 void    *data
```

10664 and shall define **ACTION** and **VISIT** as enumeration data types through type definitions as
10665 follows:

```
10666 enum { FIND, ENTER } ACTION;
10667 enum { preorder, postorder, endorder, leaf } VISIT;
```

10668 The **size_t** type shall be defined as described in **<sys/types.h>**.

10669 The following shall be declared as functions and may also be defined as macros. Function
10670 prototypes shall be provided.

```
10671 int    hcreate(size_t);
10672 void   hdestroy(void);
10673 ENTRY *hsearch(ENTRY, ACTION);
10674 void   insque(void *, void *);
10675 void  *lfind(const void *, const void *, size_t *,
10676             size_t, int (*)(const void *, const void *));
10677 void  *lsearch(const void *, void *, size_t *,
10678             size_t, int (*)(const void *, const void *));
10679 void   remque(void *);
10680 void  *tdelete(const void *restrict, void **restrict,
10681             int(*)(const void *, const void *));
10682 void  *tfind(const void *, void *const *,
10683             int(*)(const void *, const void *));
10684 void  *tsearch(const void *, void **,
10685             int(*)(const void *, const void *));
10686 void   twalk(const void *,
10687             void (*)(const void *, VISIT, int ));
```

10688 **APPLICATION USAGE**

10689 None.

10690 **RATIONALE**

10691 None.

10692 **FUTURE DIRECTIONS**

10693 None.

10694 **SEE ALSO**

10695 **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *hcreate*( ), *insque*( ),
10696 *lsearch*( ), *remque*( ), *tsearch*( )

10697 **CHANGE HISTORY**

10698 First released in Issue 1. Derived from Issue 1 of the SVID.

10699 **Issue 6**

10700 The Open Group Corrigendum U021/6 is applied, updating the prototypes for *tdelete*() and
10701 *tsearch*().

10702 The **restrict** keyword is added to the prototype for *tdelete*().

NAME

semaphore.h — semaphores (**REALTIME**)

SYNOPSIS

SEM
```
#include <semaphore.h>
```

DESCRIPTION

The **<semaphore.h>** header shall define the **sem_t** type, used in performing semaphore operations. The semaphore may be implemented using a file descriptor, in which case applications are able to open up at least a total of {OPEN_MAX} files and semaphores. The symbol SEM_FAILED shall be defined (see *sem_open*( )).

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int    sem_close(sem_t *);
int    sem_destroy(sem_t *);
int    sem_getvalue(sem_t *restrict, int *restrict);
int    sem_init(sem_t *, int, unsigned);
sem_t *sem_open(const char *, int, ...);
int    sem_post(sem_t *);
```
TMO
```
int    sem_timedwait(sem_t *restrict, const struct timespec *restrict);
```
```
int    sem_trywait(sem_t *);
int    sem_unlink(const char *);
int    sem_wait(sem_t *);
```

Inclusion of the **<semaphore.h>** header may make visible symbols defined in the headers **<fcntl.h>** and **<sys/types.h>**.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<fcntl.h>, **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *sem_destroy*( ), *sem_getvalue*( ), *sem_init*( ), *sem_open*( ), *sem_post*( ), *sem_timedwait*( ), *sem_trywait*( ), *sem_unlink*( ), *sem_wait*( )

CHANGE HISTORY

First released in Issue 5. Included for alignment with the POSIX Realtime Extension.

Issue 6

The **<semaphore.h>** header is marked as part of the Semaphores option.

The Open Group Corrigendum U021/3 is applied, adding a description of SEM_FAILED.

The *sem_timedwait*( ) function is added for alignment with IEEE Std 1003.1d-1999.

The **restrict** keyword is added to the prototypes for *sem_getvalue*( ) and *sem_timedwait*( ).

NAME

setjmp.h — stack environment declarations

SYNOPSIS

```
#include <setjmp.h>
```

DESCRIPTION

CX Some of the functionality described on this reference page extends the ISO C standard. Applications shall define the appropriate feature test macro (see the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.2, The Compilation Environment) to enable the visibility of these symbols in this header.

CX The **<setjmp.h>** header shall define the array types **jmp_buf** and **sigjmp_buf**.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
void   longjmp(jmp_buf, int);
CX void   siglongjmp(sigjmp_buf, int);
XSI void  _longjmp(jmp_buf, int);
```

The following may be declared as a function, or defined as a macro, or both. Function prototypes shall be provided.

```
int    setjmp(jmp_buf);
CX int    sigsetjmp(sigjmp_buf, int);
XSI int   _setjmp(jmp_buf);
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *longjmp*( ), *_longjmp*( ), *setjmp*( ), *siglongjmp*( ), *sigsetjmp*( )

CHANGE HISTORY

First released in Issue 1.

Issue 6

Extensions beyond the ISO C standard are marked.

NAME

signal.h — signals

SYNOPSIS

```
#include <signal.h>
```

DESCRIPTION

CX Some of the functionality described on this reference page extends the ISO C standard. Applications shall define the appropriate feature test macro (see the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.2, The Compilation Environment) to enable the visibility of these symbols in this header.

The **<signal.h>** header shall define the following symbolic constants, each of which expands to a distinct constant expression of the type:

```
void (*)(int)
```

whose value matches no declarable function.

SIG_DFL	Request for default signal handling.
SIG_ERR	Return value from *signal*( ) in case of error.
CX SIG_HOLD	Request that signal be held.
SIG_IGN	Request that signal be ignored.

The following data types shall be defined through **typedef**:

sig_atomic_t	Possibly volatile-qualified integer type of an object that can be accessed as an atomic entity, even in the presence of asynchronous interrupts.
CX **sigset_t**	Integer or structure type of an object used to represent sets of signals.
CX **pid_t**	As described in **<sys/types.h>**.

RTS The **<signal.h>** header shall define the **sigevent** structure, which has at least the following members:

`int`	`sigev_notify`	Notification type.
`int`	`sigev_signo`	Signal number.
`union sigval`	`sigev_value`	Signal value.
`void(*)(union sigval)`	`sigev_notify_function`	Notification function.
`(pthread_attr_t *)`	`sigev_notify_attributes`	Notification attributes.

The following values of *sigev_notify* shall be defined:

SIGEV_NONE	No asynchronous notification is delivered when the event of interest occurs.
SIGEV_SIGNAL	A queued signal, with an application-defined value, is generated when the event of interest occurs.
SIGEV_THREAD	A notification function is called to perform notification.

The **sigval** union shall be defined as:

`int`	`sival_int`	Integer signal value.
`void *`	`sival_ptr`	Pointer signal value.

This header shall also declare the macros SIGRTMIN and SIGRTMAX, which evaluate to integer expressions, and specify a range of signal numbers that are reserved for application use and for which the realtime signal behavior specified in this volume of IEEE Std 1003.1-2001 is supported.

The signal numbers in this range do not overlap any of the signals specified in the following table.

The range SIGRTMIN through SIGRTMAX inclusive shall include at least {RTSIG_MAX} signal numbers.

It is implementation-defined whether realtime signal behavior is supported for other signals.

This header also declares the constants that are used to refer to the signals that occur in the system. Signals defined here begin with the letters SIG. Each of the signals have distinct positive integer values. The value 0 is reserved for use as the null signal (see *kill*()). Additional implementation-defined signals may occur in the system.

CX The ISO C standard only requires the signal names SIGABRT, SIGFPE, SIGILL, SIGINT, SIGSEGV, and SIGTERM to be defined.

The following signals shall be supported on all implementations (default actions are explained below the table):

Signal	Default Action	Description
SIGABRT	A	Process abort signal.
SIGALRM	T	Alarm clock.
SIGBUS	A	Access to an undefined portion of a memory object.
SIGCHLD	I	Child process terminated, stopped,
XSI		or continued.
SIGCONT	C	Continue executing, if stopped.
SIGFPE	A	Erroneous arithmetic operation.
SIGHUP	T	Hangup.
SIGILL	A	Illegal instruction.
SIGINT	T	Terminal interrupt signal.
SIGKILL	T	Kill (cannot be caught or ignored).
SIGPIPE	T	Write on a pipe with no one to read it.
SIGQUIT	A	Terminal quit signal.
SIGSEGV	A	Invalid memory reference.
SIGSTOP	S	Stop executing (cannot be caught or ignored).
SIGTERM	T	Termination signal.
SIGTSTP	S	Terminal stop signal.
SIGTTIN	S	Background process attempting read.
SIGTTOU	S	Background process attempting write.
SIGUSR1	T	User-defined signal 1.
SIGUSR2	T	User-defined signal 2.
XSI SIGPOLL	T	Pollable event.
SIGPROF	T	Profiling timer expired.
SIGSYS	A	Bad system call.
SIGTRAP	A	Trace/breakpoint trap.
SIGURG	I	High bandwidth data is available at a socket.
XSI SIGVTALRM	T	Virtual timer expired.
SIGXCPU	A	CPU time limit exceeded.
SIGXFSZ	A	File size limit exceeded.

The default actions are as follows:

T Abnormal termination of the process. The process is terminated with all the consequences of *_exit*() except that the status made available to *wait*() and *waitpid*() indicates abnormal termination by the specified signal.

A Abnormal termination of the process.

XSI Additionally, implementation-defined abnormal termination actions, such as creation of a **core** file, may occur.

I Ignore the signal.

S Stop the process.

C Continue the process, if it is stopped; otherwise, ignore the signal.

CX The header shall provide a declaration of **struct sigaction**, including at least the following members:

`void (*sa_handler)(int)`	Pointer to a signal-catching function or one of the macros SIG_IGN or SIG_DFL.
`sigset_t sa_mask`	Set of signals to be blocked during execution of the signal handling function.
`int sa_flags`	Special flags.
`void (*sa_sigaction)(int, siginfo_t *, void *)`	Pointer to a signal-catching function.

XSI The storage occupied by *sa_handler* and *sa_sigaction* may overlap, and a conforming application shall not use both simultaneously.

The following shall be declared as constants:

CX XSI SA_NOCLDSTOP	Do not generate SIGCHLD when children stop or stopped children continue.
CX SIG_BLOCK	The resulting set is the union of the current set and the signal set pointed to by the argument *set*.
CX SIG_UNBLOCK	The resulting set is the intersection of the current set and the complement of the signal set pointed to by the argument *set*.
CX SIG_SETMASK	The resulting set is the signal set pointed to by the argument *set*.
XSI SA_ONSTACK	Causes signal delivery to occur on an alternate stack.
XSI SA_RESETHAND	Causes signal dispositions to be set to SIG_DFL on entry to signal handlers.
XSI SA_RESTART	Causes certain functions to become restartable.
XSI SA_SIGINFO	Causes extra information to be passed to signal handlers at the time of receipt of a signal.
XSI SA_NOCLDWAIT	Causes implementations not to create zombie processes on child death.
XSI SA_NODEFER	Causes signal not to be automatically blocked on entry to signal handler.
XSI SS_ONSTACK	Process is executing on an alternate signal stack.
XSI SS_DISABLE	Alternate signal stack is disabled.
XSI MINSIGSTKSZ	Minimum stack size for a signal handler.
XSI SIGSTKSZ	Default size in bytes for the alternate signal stack.

XSI The **ucontext_t** structure shall be defined through **typedef** as described in **<ucontext.h>**.

The **mcontext_t** type shall be defined through **typedef** as described in **<ucontext.h>**.

The **<signal.h>** header shall define the **stack_t** type as a structure that includes at least the following members:

`void`	`*ss_sp`	Stack base or pointer.
`size_t`	`ss_size`	Stack size.
`int`	`ss_flags`	Flags.

The **<signal.h>** header shall define the **sigstack** structure that includes at least the following members:

`int`	`ss_onstack`	Non-zero when signal stack is in use.
`void`	`*ss_sp`	Signal stack pointer.

CX The **<signal.h>** header shall define the **siginfo_t** type as a structure that includes at least the following members:

CX	`int`	`si_signo`	Signal number.
	`int`	`si_code`	Signal code. 2
XSI	`int`	`si_errno`	If non-zero, an *errno* value associated with this signal, as defined in **<errno.h>.** 2
	`pid_t`	`si_pid`	Sending process ID. 2
	`uid_t`	`si_uid`	Real user ID of sending process.
	`void`	`*si_addr`	Address of faulting instruction.
	`int`	`si_status`	Exit value or signal.
	`long`	`si_band`	Band event for SIGPOLL.
RTS	`union sigval`	`si_value`	Signal value.

The macros specified in the **Code** column of the following table are defined for use as values of *si_code* that are signal-specific or non-signal-specific reasons why the signal was generated.

Signal	Code	Reason
SIGILL	ILL_ILLOPC	Illegal opcode.
	ILL_ILLOPN	Illegal operand.
	ILL_ILLADR	Illegal addressing mode.
	ILL_ILLTRP	Illegal trap.
	ILL_PRVOPC	Privileged opcode.
	ILL_PRVREG	Privileged register.
	ILL_COPROC	Coprocessor error.
	ILL_BADSTK	Internal stack error.
SIGFPE	FPE_INTDIV	Integer divide by zero.
	FPE_INTOVF	Integer overflow.
	FPE_FLTDIV	Floating-point divide by zero.
	FPE_FLTOVF	Floating-point overflow.
	FPE_FLTUND	Floating-point underflow.
	FPE_FLTRES	Floating-point inexact result.
	FPE_FLTINV	Invalid floating-point operation.
	FPE_FLTSUB	Subscript out of range.
SIGSEGV	SEGV_MAPERR	Address not mapped to object.
	SEGV_ACCERR	Invalid permissions for mapped object.
SIGBUS	BUS_ADRALN	Invalid address alignment.
	BUS_ADRERR	Nonexistent physical address.
	BUS_OBJERR	Object-specific hardware error.
SIGTRAP	TRAP_BRKPT	Process breakpoint.
	TRAP_TRACE	Process trace trap.
SIGCHLD	CLD_EXITED	Child has exited.
	CLD_KILLED	Child has terminated abnormally and did not create a **core** file.
	CLD_DUMPED	Child has terminated abnormally and created a **core** file.
	CLD_TRAPPED	Traced child has trapped.
	CLD_STOPPED	Child has stopped.
	CLD_CONTINUED	Stopped child has continued.
SIGPOLL	POLL_IN	Data input available.
	POLL_OUT	Output buffers available.
	POLL_MSG	Input message available.
	POLL_ERR	I/O error.
	POLL_PRI	High priority input available.
	POLL_HUP	Device disconnected.
Any	SI_USER	Signal sent by *kill*().
	SI_QUEUE	Signal sent by the *sigqueue*().
	SI_TIMER	Signal generated by expiration of a timer set by *timer_settime*().
	SI_ASYNCIO	Signal generated by completion of an asynchronous I/O request.
	SI_MESGQ	Signal generated by arrival of a message on an empty message queue.

Implementations may support additional *si_code* values not included in this list, may generate values included in this list under circumstances other than those described in this list, and may contain extensions or limitations that prevent some values from being generated. Implementations do not generate a different value from the ones described in this list for circumstances described in this list.

In addition, the following signal-specific information shall be available:

Signal	Member	Value
SIGILL SIGFPE	**void *** *si_addr*	Address of faulting instruction.
SIGSEGV SIGBUS	**void *** *si_addr*	Address of faulting memory reference.
SIGCHLD	**pid_t** *si_pid* **int** *si_status* **uid_t** *si_uid*	Child process ID. Exit value or signal. Real user ID of the process that sent the signal.
SIGPOLL	**long** *si_band*	Band event for POLL_IN, POLL_OUT, or POLL_MSG.

For some implementations, the value of *si_addr* may be inaccurate.

The following shall be declared as functions and may also be defined as macros:

```
XSI  void (*bsd_signal(int, void (*)(int)))(int);
CX   int    kill(pid_t, int);
XSI  int    killpg(pid_t, int);
THR  int    pthread_kill(pthread_t, int);
     int    pthread_sigmask(int, const sigset_t *, sigset_t *);
     int    raise(int);
CX   int    sigaction(int, const struct sigaction *restrict,
                struct sigaction *restrict);
     int    sigaddset(sigset_t *, int);
XSI  int    sigaltstack(const stack_t *restrict, stack_t *restrict);
CX   int    sigdelset(sigset_t *, int);
     int    sigemptyset(sigset_t *);
     int    sigfillset(sigset_t *);
XSI  int    sighold(int);
     int    sigignore(int);
     int    siginterrupt(int, int);
CX   int    sigismember(const sigset_t *, int);
     void (*signal(int, void (*)(int)))(int);
XSI  int    sigpause(int);
CX   int    sigpending(sigset_t *);
     int    sigprocmask(int, const sigset_t *restrict, sigset_t *restrict);
RTS  int    sigqueue(pid_t, int, const union sigval);
XSI  int    sigrelse(int);
     void (*sigset(int, void (*)(int)))(int);
CX   int    sigsuspend(const sigset_t *);
RTS  int    sigtimedwait(const sigset_t *restrict, siginfo_t *restrict,
                const struct timespec *restrict);
CX   int    sigwait(const sigset_t *restrict, int *restrict);
RTS  int    sigwaitinfo(const sigset_t *restrict, siginfo_t *restrict);
```

CX Inclusion of the **<signal.h>** header may make visible all symbols from the **<time.h>** header.

11026 **APPLICATION USAGE**

11027 None.

11028 **RATIONALE**

11029 None.

11030 **FUTURE DIRECTIONS**

11031 None.

11032 **SEE ALSO**

11033 **<errno.h>**, **<stropts.h>**, **<sys/types.h>**, **<time.h>**, **<ucontext.h>**, the System Interfaces volume of
11034 IEEE Std 1003.1-2001, *alarm*( ), *bsd_signal*( ), *ioctl*( ), *kill*( ), *killpg*( ), *raise*( ), *sigaction*( ), *sigaddset*( ),
11035 *sigaltstack*( ), *sigdelset*( ), *sigemptyset*( ), *sigfillset*( ), *siginterrupt*( ), *sigismember*( ), *signal*( ),
11036 *sigpending*( ), *sigprocmask*( ), *sigqueue*( ), *sigsuspend*( ), *sigwaitinfo*( ), *wait*( ), *waitid*( )

11037 **CHANGE HISTORY**

11038 First released in Issue 1.

11039 **Issue 5**

11040 The DESCRIPTION is updated for alignment with the POSIX Realtime Extension and the POSIX
11041 Threads Extension.

11042 The default action for SIGURG is changed from i to iii. The function prototype for *sigmask*( ) is
11043 removed.

11044 **Issue 6**

11045 The Open Group Corrigendum U035/2 is applied. In the DESCRIPTION, the wording for
11046 abnormal termination is clarified.

11047 The Open Group Corrigendum U028/8 is applied, correcting the prototype for the *sigset*( )
11048 function.

11049 The Open Group Corrigendum U026/3 is applied, correcting the type of the *sigev_notify_function*
11050 function member of the **sigevent** structure.

11051 The following new requirements on POSIX implementations derive from alignment with the
11052 Single UNIX Specification:

11053 • The SIGCHLD, SIGCONT, SIGSTOP, SIGTSTP, SIGTTIN, and SIGTTOU signals are now
11054 mandated. This is also a FIPS requirement.

11055 • The **pid_t** definition is mandated.

11056 The RT markings are changed to RTS to denote that the semantics are part of the Realtime 1
11057 Signals Extension option.

11058 The **restrict** keyword is added to the prototypes for *sigaction*( ), *sigaltstack*( ), *sigprocmask*( ),
11059 *sigtimedwait*( ), *sigwait*( ), and *sigwaitinfo*( ).

11060 IEEE PASC Interpretation 1003.1 #85 is applied, adding the statement that symbols from
11061 **<time.h>** may be made visible when **<signal.h>** is included.

11062 Extensions beyond the ISO C standard are marked.

11063 IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/14 is applied, changing the descriptive 1
11064 text for members of **struct sigaction**. 1

11065 IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/15 is applied, correcting the definition of 1
11066 the *sa_sigaction* member of **struct sigaction**. 1

11067 IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/24 is applied, reworking the ordering of 2
11068 the **siginfo_t** type structure in the DESCRIPTION. This is an editorial change and no normative 2

11069 change is intended. 2

11070 **NAME**

11071 spawn.h — spawn (**ADVANCED REALTIME**)

11072 **SYNOPSIS**

11073 SPN
```
#include <spawn.h>
```

11074

11075 **DESCRIPTION**

11076 The **<spawn.h>** header shall define the **posix_spawnattr_t** and **posix_spawn_file_actions_t**
11077 types used in performing spawn operations.

11078 The **<spawn.h>** header shall define the flags that may be set in a **posix_spawnattr_t** object using
11079 the *posix_spawnattr_setflags*( ) function:

11080 POSIX_SPAWN_RESETIDS
11081 POSIX_SPAWN_SETPGROUP
11082 PS POSIX_SPAWN_SETSCHEDPARAM
11083 POSIX_SPAWN_SETSCHEDULER
11084 POSIX_SPAWN_SETSIGDEF
11085 POSIX_SPAWN_SETSIGMASK

11086 The following shall be declared as functions and may also be defined as macros. Function
11087 prototypes shall be provided.

```
11088       int   posix_spawn(pid_t *restrict, const char *restrict,
11089                 const posix_spawn_file_actions_t *,
11090                 const posix_spawnattr_t *restrict, char *const [restrict],
11091                 char *const [restrict]);
11092       int   posix_spawn_file_actions_addclose(posix_spawn_file_actions_t *,
11093                 int);
11094       int   posix_spawn_file_actions_adddup2(posix_spawn_file_actions_t *,
11095                 int, int);
11096       int   posix_spawn_file_actions_addopen(posix_spawn_file_actions_t *restrict,
11097                 int, const char *restrict, int, mode_t);
11098       int   posix_spawn_file_actions_destroy(posix_spawn_file_actions_t *);
11099       int   posix_spawn_file_actions_init(posix_spawn_file_actions_t *);
11100       int   posix_spawnattr_destroy(posix_spawnattr_t *);
11101       int   posix_spawnattr_getsigdefault(const posix_spawnattr_t *restrict,
11102                 sigset_t *restrict);
11103       int   posix_spawnattr_getflags(const posix_spawnattr_t *restrict,
11104                 short *restrict);
11105       int   posix_spawnattr_getpgroup(const posix_spawnattr_t *restrict,
11106                 pid_t *restrict);
11107 PS    int   posix_spawnattr_getschedparam(const posix_spawnattr_t *restrict,
11108                 struct sched_param *restrict);
11109       int   posix_spawnattr_getschedpolicy(const posix_spawnattr_t *restrict,
11110                 int *restrict);
11111       int   posix_spawnattr_getsigmask(const posix_spawnattr_t *restrict,
11112                 sigset_t *restrict);
11113       int   posix_spawnattr_init(posix_spawnattr_t *);
11114       int   posix_spawnattr_setsigdefault(posix_spawnattr_t *restrict,
11115                 const sigset_t *restrict);
11116       int   posix_spawnattr_setflags(posix_spawnattr_t *, short);
11117       int   posix_spawnattr_setpgroup(posix_spawnattr_t *, pid_t);
```

```
PS      int   posix_spawnattr_setschedparam(posix_spawnattr_t *restrict,
                  const struct sched_param *restrict);
        int   posix_spawnattr_setschedpolicy(posix_spawnattr_t *, int);
        int   posix_spawnattr_setsigmask(posix_spawnattr_t *restrict,
                  const sigset_t *restrict);
        int   posix_spawnp(pid_t *restrict, const char *restrict,
                  const posix_spawn_file_actions_t *,
                  const posix_spawnattr_t *restrict,
                  char *const [restrict], char *const [restrict]);
```

Inclusion of the **<spawn.h>** header may make visible symbols defined in the **<sched.h>**, **<signal.h>**, and **<sys/types.h>** headers.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<sched.h>, **<semaphore.h>**, **<signal.h>**, **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *posix_spawnattr_destroy*( ), *posix_spawnattr_getsigdefault*( ), *posix_spawnattr_getflags*( ), *posix_spawnattr_getpgroup*( ), *posix_spawnattr_getschedparam*( ), *posix_spawnattr_getschedpolicy*( ), *posix_spawnattr_getsigmask*( ), *posix_spawnattr_init*( ), *posix_spawnattr_setsigdefault*( ), *posix_spawnattr_setflags*( ), *posix_spawnattr_setpgroup*( ), *posix_spawnattr_setschedparam*( ), *posix_spawnattr_setschedpolicy*( ), *posix_spawnattr_setsigmask*( ), *posix_spawn*( ), *posix_spawn_file_actions_addclose*( ), *posix_spawn_file_actions_adddup2*( ), *posix_spawn_file_actions_addopen*( ), *posix_spawn_file_actions_destroy*( ), *posix_spawn_file_actions_init*( ), *posix_spawnp*( )

CHANGE HISTORY

First released in Issue 6. Included for alignment with IEEE Std 1003.1d-1999.

The **restrict** keyword is added to the prototypes for *posix_spawn*( ), *posix_spawn_file_actions_addopen*( ), *posix_spawnattr_getsigdefault*( ), *posix_spawnattr_getflags*( ), *posix_spawnattr_getpgroup*( ), *posix_spawnattr_getschedparam*( ), *posix_spawnattr_getschedpolicy*( ), *posix_spawnattr_getsigmask*( ), *posix_spawnattr_setsigdefault*( ), *posix_spawnattr_setschedparam*( ), *posix_spawnattr_setsigmask*( ), and *posix_spawnp*( ).

NAME

stdarg.h — handle variable argument list

SYNOPSIS

```
#include <stdarg.h>

void va_start(va_list ap, argN);
void va_copy(va_list dest, va_list src);
type va_arg(va_list ap, type);
void va_end(va_list ap);
```

DESCRIPTION

CX The functionality described on this reference page is aligned with the ISO C standard. Any conflict between the requirements described here and the ISO C standard is unintentional. This volume of IEEE Std 1003.1-2001 defers to the ISO C standard.

The **<stdarg.h>** header shall contain a set of macros which allows portable functions that accept variable argument lists to be written. Functions that have variable argument lists (such as *printf*()) but do not use these macros are inherently non-portable, as different systems use different argument-passing conventions.

The type **va_list** shall be defined for variables used to traverse the list.

The *va_start*() macro is invoked to initialize *ap* to the beginning of the list before any calls to *va_arg*().

The *va_copy*() macro initializes *dest* as a copy of *src*, as if the *va_start*() macro had been applied to *dest* followed by the same sequence of uses of the *va_arg*() macro as had previously been used to reach the present state of *src*. Neither the *va_copy*() nor *va_start*() macro shall be invoked to reinitialize *dest* without an intervening invocation of the *va_end*() macro for the same *dest*.

The object *ap* may be passed as an argument to another function; if that function invokes the *va_arg*() macro with parameter *ap*, the value of *ap* in the calling function is unspecified and shall be passed to the *va_end*() macro prior to any further reference to *ap*. The parameter *argN* is the identifier of the rightmost parameter in the variable parameter list in the function definition (the one just before the ...). If the parameter *argN* is declared with the **register** storage class, with a function type or array type, or with a type that is not compatible with the type that results after application of the default argument promotions, the behavior is undefined.

The *va_arg*() macro shall return the next argument in the list pointed to by *ap*. Each invocation of *va_arg*() modifies *ap* so that the values of successive arguments are returned in turn. The *type* parameter shall be a type name specified such that the type of a pointer to an object that has the specified type can be obtained simply by postfixing a '*' to type. If there is no actual next argument, or if *type* is not compatible with the type of the actual next argument (as promoted according to the default argument promotions), the behavior is undefined, except for the following cases:

- One type is a signed integer type, the other type is the corresponding unsigned integer type, and the value is representable in both types.
- One type is a pointer to **void** and the other is a pointer to a character type.
- XSI Both types are pointers.

Different types can be mixed, but it is up to the routine to know what type of argument is expected.

The *va_end*() macro is used to clean up; it invalidates *ap* for use (unless *va_start*() or *va_copy*() is invoked again).

Each invocation of the *va_start*( ) and *va_copy*( ) macros shall be matched by a corresponding invocation of the *va_end*( ) macro in the same function.

Multiple traversals, each bracketed by *va_start*( ) ... *va_end*( ), are possible.

EXAMPLES

This example is a possible implementation of *execl*( ):

```
#include <stdarg.h>

#define  MAXARGS     31

/*
 * execl is called by
 * execl(file, arg1, arg2, ..., (char *)(0));
 */
int execl(const char *file, const char *args, ...)
{
    va_list ap;
    char *array[MAXARGS +1];
    int argno = 0;

    va_start(ap, args);
    while (args != 0 && argno < MAXARGS)
    {
        array[argno++] = args;
        args = va_arg(ap, const char *);
    }
    array[argno] = (char *) 0;
    va_end(ap);
    return execv(file, array);
}
```

APPLICATION USAGE

It is up to the calling routine to communicate to the called routine how many arguments there are, since it is not always possible for the called routine to determine this in any other way. For example, *execl*( ) is passed a null pointer to signal the end of the list. The *printf*( ) function can tell how many arguments are there by the *format* argument.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *exec*, *printf*( )

CHANGE HISTORY

First released in Issue 4. Derived from the ANSI C standard.

Issue 6

This reference page is updated to align with the ISO / IEC 9899: 1999 standard.

NAME

stdbool.h — boolean type and values

SYNOPSIS

```
#include <stdbool.h>
```

DESCRIPTION

CX The functionality described on this reference page is aligned with the ISO C standard. Any conflict between the requirements described here and the ISO C standard is unintentional. This volume of IEEE Std 1003.1-2001 defers to the ISO C standard.

The **<stdbool.h>** header shall define the following macros:

bool Expands to **_Bool**.

true Expands to the integer constant 1.

false Expands to the integer constant 0.

__bool_true_false_are_defined
Expands to the integer constant 1.

An application may undefine and then possibly redefine the macros bool, true, and false.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

The ability to undefine and redefine the macros bool, true, and false is an obsolescent feature and may be withdrawn in a future version.

SEE ALSO

None.

CHANGE HISTORY

First released in Issue 6. Included for alignment with the ISO/IEC 9899: 1999 standard.

NAME

stddef.h — standard type definitions

SYNOPSIS

```
#include <stddef.h>
```

DESCRIPTION

CX The functionality described on this reference page is aligned with the ISO C standard. Any conflict between the requirements described here and the ISO C standard is unintentional. This volume of IEEE Std 1003.1-2001 defers to the ISO C standard.

The **<stddef.h>** header shall define the following macros:

NULL Null pointer constant.

offsetof(*type*, *member-designator*)
Integer constant expression of type **size_t**, the value of which is the offset in bytes to the structure member (*member-designator*), from the beginning of its structure (*type*).

The **<stddef.h>** header shall define the following types:

ptrdiff_t Signed integer type of the result of subtracting two pointers.

wchar_t Integer type whose range of values can represent distinct wide-character codes for all members of the largest character set specified among the locales supported by the compilation environment: the null character has the code value 0 and each member of the portable character set has a code value equal to its value when used as the lone character in an integer character constant.

size_t Unsigned integer type of the result of the *sizeof* operator.

The implementation shall support one or more programming environments in which the widths of **ptrdiff_t**, **size_t**, and **wchar_t** are no greater than the width of type **long**. The names of these programming environments can be obtained using the *confstr*( ) function or the *getconf* utility.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<wchar.h>, **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *confstr*( ), the Shell and Utilities volume of IEEE Std 1003.1-2001, *getconf*

CHANGE HISTORY

First released in Issue 4. Derived from the ANSI C standard.

NAME

stdint.h — integer types

SYNOPSIS

```
#include <stdint.h>
```

DESCRIPTION

CX Some of the functionality described on this reference page extends the ISO C standard. Applications shall define the appropriate feature test macro (see the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.2, The Compilation Environment) to enable the visibility of these symbols in this header.

The **<stdint.h>** header shall declare sets of integer types having specified widths, and shall define corresponding sets of macros. It shall also define macros that specify limits of integer types corresponding to types defined in other standard headers.

Note: The ''width'' of an integer type is the number of bits used to store its value in a pure binary system; the actual type may use more bits than that (for example, a 28-bit type could be stored in 32 bits of actual storage). An N-bit signed type has values in the range -2^{N-1} or $1-2^{N-1}$ to $2^{N-1}-1$, while an N-bit unsigned type has values in the range 0 to $2^{N}-1$.

Types are defined in the following categories:

- Integer types having certain exact widths
- Integer types having at least certain specified widths
- Fastest integer types having at least certain specified widths
- Integer types wide enough to hold pointers to objects
- Integer types having greatest width

(Some of these types may denote the same type.)

Corresponding macros specify limits of the declared types and construct suitable constants.

For each type described herein that the implementation provides, the **<stdint.h>** header shall declare that **typedef** name and define the associated macros. Conversely, for each type described herein that the implementation does not provide, the **<stdint.h>** header shall not declare that **typedef** name, nor shall it define the associated macros. An implementation shall provide those types described as required, but need not provide any of the others (described as optional).

Integer Types

When **typedef** names differing only in the absence or presence of the initial *u* are defined, they shall denote corresponding signed and unsigned types as described in the ISO/IEC 9899:1999 standard, Section 6.2.5; an implementation providing one of these corresponding types shall also provide the other.

In the following descriptions, the symbol *N* represents an unsigned decimal integer with no leading zeros (for example, 8 or 24, but not 04 or 048).

- Exact-width integer types

  The **typedef** name **int***N***_t** designates a signed integer type with width *N*, no padding bits, and a two's-complement representation. Thus, **int8_t** denotes a signed integer type with a width of exactly 8 bits.

  The **typedef** name **uint***N***_t** designates an unsigned integer type with width *N*. Thus, **uint24_t** denotes an unsigned integer type with a width of exactly 24 bits.

11342 CX The following types are required:

11343 **int8_t**
11344 **int16_t**
11345 **int32_t**
11346 **uint8_t**
11347 **uint16_t**
11348 **uint32_t**

11349 If an implementation provides integer types with width 64 that meet these requirements,
11350 then the following types are required:

11351 **int64_t**
11352 **uint64_t**

11353 CX In particular, this will be the case if any of the following are true:

11354 — The implementation supports the _POSIX_V6_ILP32_OFFBIG programming
11355 environment and the application is being built in the _POSIX_V6_ILP32_OFFBIG
11356 programming environment (see the Shell and Utilities volume of IEEE Std 1003.1-2001,
11357 *c99*, Programming Environments).

11358 — The implementation supports the _POSIX_V6_LP64_OFF64 programming environment
11359 and the application is being built in the _POSIX_V6_LP64_OFF64 programming
11360 environment.

11361 — The implementation supports the _POSIX_V6_LPBIG_OFFBIG programming
11362 environment and the application is being built in the _POSIX_V6_LPBIG_OFFBIG
11363 programming environment.

11364 All other types of this form are optional.

11365 • Minimum-width integer types

11366 The **typedef** name **int_least***N***_t** designates a signed integer type with a width of at least *N*,
11367 such that no signed integer type with lesser size has at least the specified width. Thus,
11368 **int_least32_t** denotes a signed integer type with a width of at least 32 bits.

11369 The **typedef** name **uint_least***N***_t** designates an unsigned integer type with a width of at least
11370 *N*, such that no unsigned integer type with lesser size has at least the specified width. Thus,
11371 **uint_least16_t** denotes an unsigned integer type with a width of at least 16 bits.

11372 The following types are required:

11373 **int_least8_t**
11374 **int_least16_t**
11375 **int_least32_t**
11376 **int_least64_t**
11377 **uint_least8_t**
11378 **uint_least16_t**
11379 **uint_least32_t**
11380 **uint_least64_t**

11381 All other types of this form are optional.

11382 • Fastest minimum-width integer types

11383 Each of the following types designates an integer type that is usually fastest to operate with
11384 among all integer types that have at least the specified width.

The designated type is not guaranteed to be fastest for all purposes; if the implementation has no clear grounds for choosing one type over another, it will simply pick some integer type satisfying the signedness and width requirements.

The **typedef** name **int_fast***N***_t** designates the fastest signed integer type with a width of at least *N*. The **typedef** name **uint_fast***N***_t** designates the fastest unsigned integer type with a width of at least *N*.

The following types are required:

int_fast8_t
int_fast16_t
int_fast32_t
int_fast64_t
uint_fast8_t
uint_fast16_t
uint_fast32_t
uint_fast64_t

All other types of this form are optional.

- Integer types capable of holding object pointers

The following type designates a signed integer type with the property that any valid pointer to **void** can be converted to this type, then converted back to a pointer to **void**, and the result will compare equal to the original pointer:

intptr_t

The following type designates an unsigned integer type with the property that any valid pointer to **void** can be converted to this type, then converted back to a pointer to **void**, and the result will compare equal to the original pointer:

uintptr_t

XSI On XSI-conformant systems, the **intptr_t** and **uintptr_t** types are required; otherwise, they are optional.

- Greatest-width integer types

The following type designates a signed integer type capable of representing any value of any signed integer type:

intmax_t

The following type designates an unsigned integer type capable of representing any value of any unsigned integer type:

uintmax_t

These types are required.

Note: Applications can test for optional types by using the corresponding limit macro from **Limits of Specified-Width Integer Types** (on page 321).

11422 **Limits of Specified-Width Integer Types**

11423 The following macros specify the minimum and maximum limits of the types declared in the
11424 **<stdint.h>** header. Each macro name corresponds to a similar type name in **Integer Types** (on
11425 page 318).

11426 Each instance of any defined macro shall be replaced by a constant expression suitable for use in
11427 **#if** preprocessing directives, and this expression shall have the same type as would an
11428 expression that is an object of the corresponding type converted according to the integer
11429 promotions. Its implementation-defined value shall be equal to or greater in magnitude
11430 (absolute value) than the corresponding value given below, with the same sign, except where
11431 stated to be exactly the given value.

11432 • Limits of exact-width integer types

11433 — Minimum values of exact-width signed integer types:

11434 {INT*N*_MIN} Exactly $-(2^{N-1})$

11435 — Maximum values of exact-width signed integer types:

11436 {INT*N*_MAX} Exactly $2^{N-1}-1$

11437 — Maximum values of exact-width unsigned integer types:

11438 {UINT*N*_MAX} Exactly $2^{N}-1$

11439 • Limits of minimum-width integer types

11440 — Minimum values of minimum-width signed integer types:

11441 {INT_LEAST*N*_MIN} $-(2^{N-1}-1)$

11442 — Maximum values of minimum-width signed integer types:

11443 {INT_LEAST*N*_MAX} $2^{N-1}-1$

11444 — Maximum values of minimum-width unsigned integer types:

11445 {UINT_LEAST*N*_MAX} $2^{N}-1$

11446 • Limits of fastest minimum-width integer types

11447 — Minimum values of fastest minimum-width signed integer types:

11448 {INT_FAST*N*_MIN} $-(2^{N-1}-1)$

11449 — Maximum values of fastest minimum-width signed integer types:

11450 {INT_FAST*N*_MAX} $2^{N-1}-1$

11451 — Maximum values of fastest minimum-width unsigned integer types:

11452 {UINT_FAST*N*_MAX} $2^{N}-1$

11453 • Limits of integer types capable of holding object pointers

11454 — Minimum value of pointer-holding signed integer type:

11455 {INTPTR_MIN} $-(2^{15}-1)$

11456 — Maximum value of pointer-holding signed integer type:

11457 {INTPTR_MAX} $2^{15}-1$

11458 — Maximum value of pointer-holding unsigned integer type:

11459 {UINTPTR_MAX} $2^{16} - 1$

11460 • Limits of greatest-width integer types

11461 — Minimum value of greatest-width signed integer type:

11462 {INTMAX_MIN} $-(2^{63} - 1)$

11463 — Maximum value of greatest-width signed integer type:

11464 {INTMAX_MAX} $2^{63} - 1$

11465 — Maximum value of greatest-width unsigned integer type:

11466 {UINTMAX_MAX} $2^{64} - 1$

11467 **Limits of Other Integer Types**

11468 The following macros specify the minimum and maximum limits of integer types corresponding
11469 to types defined in other standard headers.

11470 Each instance of these macros shall be replaced by a constant expression suitable for use in **#if**
11471 preprocessing directives, and this expression shall have the same type as would an expression
11472 that is an object of the corresponding type converted according to the integer promotions. Its
11473 implementation-defined value shall be equal to or greater in magnitude (absolute value) than
11474 the corresponding value given below, with the same sign.

11475 • Limits of **ptrdiff_t**:

11476 {PTRDIFF_MIN} –65 535

11477 {PTRDIFF_MAX} +65 535

11478 • Limits of **sig_atomic_t**:

11479 {SIG_ATOMIC_MIN} See below.

11480 {SIG_ATOMIC_MAX} See below.

11481 • Limit of **size_t**:

11482 {SIZE_MAX} 65 535

11483 • Limits of **wchar_t**:

11484 {WCHAR_MIN} See below.

11485 {WCHAR_MAX} See below.

11486 • Limits of **wint_t**:

11487 {WINT_MIN} See below.

11488 {WINT_MAX} See below.

11489 If **sig_atomic_t** (see the **<signal.h>** header) is defined as a signed integer type, the value of
11490 {SIG_ATOMIC_MIN} shall be no greater than –127 and the value of {SIG_ATOMIC_MAX} shall
11491 be no less than 127; otherwise, **sig_atomic_t** shall be defined as an unsigned integer type, and the
11492 value of {SIG_ATOMIC_MIN} shall be 0 and the value of {SIG_ATOMIC_MAX} shall be no less
11493 than 255.

11494 If **wchar_t** (see the **<stddef.h>** header) is defined as a signed integer type, the value of
11495 {WCHAR_MIN} shall be no greater than –127 and the value of {WCHAR_MAX} shall be no less
11496 than 127; otherwise, **wchar_t** shall be defined as an unsigned integer type, and the value of
11497 {WCHAR_MIN} shall be 0 and the value of {WCHAR_MAX} shall be no less than 255.

If **wint_t** (see the **<wchar.h>** header) is defined as a signed integer type, the value of {WINT_MIN} shall be no greater than –32 767 and the value of {WINT_MAX} shall be no less than 32 767; otherwise, **wint_t** shall be defined as an unsigned integer type, and the value of {WINT_MIN} shall be 0 and the value of {WINT_MAX} shall be no less than 65 535.

Macros for Integer Constant Expressions

The following macros expand to integer constant expressions suitable for initializing objects that have integer types corresponding to types defined in the **<stdint.h>** header. Each macro name corresponds to a similar type name listed under *Minimum-width integer types* and *Greatest-width integer types*.

Each invocation of one of these macros shall expand to an integer constant expression suitable for use in **#if** preprocessing directives. The type of the expression shall have the same type as would an expression that is an object of the corresponding type converted according to the integer promotions. The value of the expression shall be that of the argument.

The argument in any instance of these macros shall be a decimal, octal, or hexadecimal constant with a value that does not exceed the limits for the corresponding type.

- Macros for minimum-width integer constant expressions

  The macro *INTN_C*(*value*) shall expand to an integer constant expression corresponding to the type **int_least***N***_t**. The macro *UINTN_C*(*value*) shall expand to an integer constant expression corresponding to the type **uint_least***N***_t**. For example, if **uint_least64_t** is a name for the type **unsigned long long**, then *UINT64_C*(0x123) might expand to the integer constant 0x123ULL.

- Macros for greatest-width integer constant expressions

  The following macro expands to an integer constant expression having the value specified by its argument and the type **intmax_t**:

  INTMAX_C(*value*)

  The following macro expands to an integer constant expression having the value specified by its argument and the type **uintmax_t**:

  UINTMAX_C(*value*)

APPLICATION USAGE

None.

RATIONALE

The **<stdint.h>** header is a subset of the **<inttypes.h>** header more suitable for use in freestanding environments, which might not support the formatted I/O functions. In some environments, if the formatted conversion support is not wanted, using this header instead of the **<inttypes.h>** header avoids defining such a large number of macros.

As a consequence of adding **int8_t**, the following are true:

- A byte is exactly 8 bits.
- {CHAR_BIT} has the value 8, {SCHAR_MAX} has the value 127, {SCHAR_MIN} has the value –127 or –128, and {UCHAR_MAX} has the value 255.

FUTURE DIRECTIONS

typedef names beginning with **int** or **uint** and ending with _t may be added to the types defined in the **<stdint.h>** header. Macro names beginning with INT or UINT and ending with _MAX, _MIN, or _C may be added to the macros defined in the **<stdint.h>** header.

SEE ALSO

<inttypes.h>, **<signal.h>**, **<stddef.h>**, **<wchar.h>**

CHANGE HISTORY

First released in Issue 6. Included for alignment with the ISO / IEC 9899: 1999 standard.

ISO / IEC 9899: 1999 standard, Technical Corrigendum 1 is incorporated.

11546 **NAME**

11547 stdio.h — standard buffered input/output

11548 **SYNOPSIS**

11549 `#include <stdio.h>`

11550 **DESCRIPTION**

11551 CX Some of the functionality described on this reference page extends the ISO C standard.
11552 Applications shall define the appropriate feature test macro (see the System Interfaces volume of
11553 IEEE Std 1003.1-2001, Section 2.2, The Compilation Environment) to enable the visibility of these
11554 symbols in this header.

11555 The **<stdio.h>** header shall define the following macros as positive integer constant expressions:

11556	BUFSIZ	Size of **<stdio.h>** buffers.
11557	_IOFBF	Input/output fully buffered.
11558	_IOLBF	Input/output line buffered.
11559	_IONBF	Input/output unbuffered.
11560 CX	L_ctermid	Maximum size of character array to hold *ctermid*( ) output.
11561	L_tmpnam	Maximum size of character array to hold *tmpnam*( ) output.
11562	SEEK_CUR	Seek relative to current position.
11563	SEEK_END	Seek relative to end-of-file.
11564	SEEK_SET	Seek relative to start-of-file.

11565 The following macros shall be defined as positive integer constant expressions which denote
11566 implementation limits:

11567	{FILENAME_MAX}	Maximum size in bytes of the longest filename string that the implementation guarantees can be opened.
11569	{FOPEN_MAX}	Number of streams which the implementation guarantees can be open simultaneously. The value is at least eight.
11571	{TMP_MAX}	Minimum number of unique filenames generated by *tmpnam*( ). Maximum number of times an application can call *tmpnam*( ) reliably. The
11573 XSI		value of {TMP_MAX} is at least 25. On XSI-conformant systems, the
11574		value of {TMP_MAX} is at least 10 000.

11575 The following macro name shall be defined as a negative integer constant expression:

11576	EOF	End-of-file return value.

11577 The following macro name shall be defined as a null pointer constant:

11578	NULL	Null pointer.

11579 The following macro name shall be defined as a string constant:

11580 XSI	P_tmpdir	Default directory prefix for *tempnam*( ).

11581 The following shall be defined as expressions of type ''pointer to **FILE**'' that point to the **FILE**
11582 objects associated, respectively, with the standard error, input, and output streams:

11583	*stderr*	Standard error output stream.
11584	*stdin*	Standard input stream.

stdout Standard output stream.

The following data types shall be defined through **typedef**:

FILE A structure containing information about a file.

fpos_t A non-array type containing all information needed to specify uniquely every position within a file.

XSI **va_list** As described in **<stdarg.h>**.

size_t As described in **<stddef.h>**.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
void     clearerr(FILE *);
CX
char    *ctermid(char *);
int      fclose(FILE *);
CX
FILE    *fdopen(int, const char *);
int      feof(FILE *);
int      ferror(FILE *);
int      fflush(FILE *);
int      fgetc(FILE *);
int      fgetpos(FILE *restrict, fpos_t *restrict);
char    *fgets(char *restrict, int, FILE *restrict);
CX
int      fileno(FILE *);
TSF
void     flockfile(FILE *);
FILE    *fopen(const char *restrict, const char *restrict);
int      fprintf(FILE *restrict, const char *restrict, ...);
int      fputc(int, FILE *);
int      fputs(const char *restrict, FILE *restrict);
size_t   fread(void *restrict, size_t, size_t, FILE *restrict);
FILE    *freopen(const char *restrict, const char *restrict,
                     FILE *restrict);
int      fscanf(FILE *restrict, const char *restrict, ...);
int      fseek(FILE *, long, int);
CX
int      fseeko(FILE *, off_t, int);
int      fsetpos(FILE *, const fpos_t *);
long     ftell(FILE *);
CX
off_t    ftello(FILE *);
TSF
int      ftrylockfile(FILE *);
void     funlockfile(FILE *);
size_t   fwrite(const void *restrict, size_t, size_t, FILE *restrict);
int      getc(FILE *);
int      getchar(void);
TSF
int      getc_unlocked(FILE *);
int      getchar_unlocked(void);
char    *gets(char *);
CX
int      pclose(FILE *);
void     perror(const char *);
CX
FILE    *popen(const char *, const char *);
int      printf(const char *restrict, ...);
int      putc(int, FILE *);
int      putchar(int);
TSF
```



```
11634       int      putc_unlocked(int, FILE *);
11635       int      putchar_unlocked(int);
11636       int      puts(const char *);
11637       int      remove(const char *);
11638       int      rename(const char *, const char *);
11639       void     rewind(FILE *);
11640       int      scanf(const char *restrict, ...);
11641       void     setbuf(FILE *restrict, char *restrict);
11642       int      setvbuf(FILE *restrict, char *restrict, int, size_t);
11643       int      snprintf(char *restrict, size_t, const char *restrict, ...);
11644       int      sprintf(char *restrict, const char *restrict, ...);
11645       int      sscanf(const char *restrict, const char *restrict, int ...);
11646 XSI   char    *tempnam(const char *, const char *);
11647       FILE    *tmpfile(void);
11648       char    *tmpnam(char *);
11649       int      ungetc(int, FILE *);
11650       int      vfprintf(FILE *restrict, const char *restrict, va_list);
11651       int      vfscanf(FILE *restrict, const char *restrict, va_list);
11652       int      vprintf(const char *restrict, va_list);
11653       int      vscanf(const char *restrict, va_list);
11654       int      vsnprintf(char *restrict, size_t, const char *restrict,
11655                    va_list);
11656       int      vsprintf(char *restrict, const char *restrict, va_list);
11657       int      vsscanf(const char *restrict, const char *restrict,
11658                    va_list arg);
```

11659 XSI Inclusion of the **<stdio.h>** header may also make visible all symbols from **<stddef.h>**.

11660 **APPLICATION USAGE**

11661 None.

11662 **RATIONALE**

11663 None.

11664 **FUTURE DIRECTIONS**

11665 None.

11666 **SEE ALSO**

11667 **<stdarg.h>**, **<stddef.h>**, **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001,
11668 *clearerr*( ), *ctermid*( ), *fclose*( ), *fdopen*( ), *fgetc*( ), *fgetpos*( ), *ferror*( ), *feof*( ), *fflush*( ), *fgets*( ), *fileno*( ),
11669 *flockfile*( ), *fopen*( ), *fputc*( ), *fputs*( ), *fread*( ), *freopen*( ), *fseek*( ), *fsetpos*( ), *ftell*( ), *fwrite*( ), *getc*( ),
11670 *getc_unlocked*( ), *getwchar*( ), *getchar*( ), *getopt*( ), *gets*( ), *pclose*( ), *perror*( ), *popen*( ), *printf*( ), *putc*( ),
11671 *putchar*( ), *puts*( ), *putwchar*( ), *remove*( ), *rename*( ), *rewind*( ), *scanf*( ), *setbuf*( ), *setvbuf*( ), *sscanf*( ),
11672 *stdin*, *system*( ), *tempnam*( ), *tmpfile*( ), *tmpnam*( ), *ungetc*( ), *vfscanf*( ), *vscanf*( ), *vprintf*( ), *vsscanf*( )

11673 **CHANGE HISTORY**

11674 First released in Issue 1. Derived from Issue 1 of the SVID.

11675 **Issue 5**

11676 The DESCRIPTION is updated for alignment with the POSIX Threads Extension.

11677 Large File System extensions are added.

11678 The constant L_cuserid and the external variables *optarg*, *opterr*, *optind*, and *optopt* are marked as
11679 extensions and LEGACY.

The *cuserid*( ) and *getopt*( ) functions are marked LEGACY.

Issue 6

The constant L_cuserid and the external variables *optarg*, *opterr*, *optind*, and *optopt* are removed as they were previously marked LEGACY.

The *cuserid*( ), *getopt*( ), and *getw*( ) functions are removed as they were previously marked LEGACY.

Several functions are marked as part of the Thread-Safe Functions option.

This reference page is updated to align with the ISO/IEC 9899:1999 standard. Note that the description of the **fpos_t** type is now explicitly updated to exclude array types.

Extensions beyond the ISO C standard are marked.

11690 **NAME**

11691 stdlib.h — standard library definitions

11692 **SYNOPSIS**

11693 `#include <stdlib.h>`

11694 **DESCRIPTION**

11695 CX Some of the functionality described on this reference page extends the ISO C standard.
11696 Applications shall define the appropriate feature test macro (see the System Interfaces volume of
11697 IEEE Std 1003.1-2001, Section 2.2, The Compilation Environment) to enable the visibility of these
11698 symbols in this header.

11699 The **<stdlib.h>** header shall define the following macros:

11700 EXIT_FAILURE Unsuccessful termination for *exit*( ); evaluates to a non-zero value.

11701 EXIT_SUCCESS Successful termination for *exit*( ); evaluates to 0.

11702 NULL Null pointer.

11703 {RAND_MAX} Maximum value returned by *rand*( ); at least 32 767.

11704 {MB_CUR_MAX} Integer expression whose value is the maximum number of bytes in a
11705 character specified by the current locale.

11706 The following data types shall be defined through **typedef**:

11707 **div_t** Structure type returned by the *div*( ) function.

11708 **ldiv_t** Structure type returned by the *ldiv*( ) function.

11709 **lldiv_t** Structure type returned by the *lldiv*( ) function.

11710 **size_t** As described in **<stddef.h>**.

11711 **wchar_t** As described in **<stddef.h>**.

11712 In addition, the following symbolic names and macros shall be defined as in **<sys/wait.h>**, for
11713 use in decoding the return value from *system*( ):

11714 XSI WNOHANG
11715 WUNTRACED
11716 WEXITSTATUS
11717 WIFEXITED
11718 WIFSIGNALED
11719 WIFSTOPPED
11720 WSTOPSIG
11721 WTERMSIG
11722

11723 The following shall be declared as functions and may also be defined as macros. Function
11724 prototypes shall be provided.

```
11725 void        _Exit(int);
11726 XSI long    a64l(const char *);
11727 void        abort(void);
11728 int         abs(int);
11729 int         atexit(void (*)(void));
11730 double      atof(const char *);
11731 int         atoi(const char *);
11732 long        atol(const char *);
```



```
11733          long long     atoll(const char *);
11734          void         *bsearch(const void *, const void *, size_t, size_t,
11735                            int (*)(const void *, const void *));
11736          void         *calloc(size_t, size_t);
11737          div_t         div(int, int);
11738 XSI      double        drand48(void);
11739          char         *ecvt(double, int, int *restrict, int *restrict); (LEGACY)
11740          double        erand48(unsigned short[3]);
11741          void          exit(int);
11742 XSI      char         *fcvt(double, int, int *restrict, int *restrict); (LEGACY)
11743          void          free(void *);
11744 XSI      char         *gcvt(double, int, char *); (LEGACY)
11745          char         *getenv(const char *);
11746 XSI      int           getsubopt(char **, char *const *, char **);
11747          int           grantpt(int);
11748          char         *initstate(unsigned, char *, size_t);
11749          long          jrand48(unsigned short[3]);
11750          char         *l64a(long);
11751          long          labs(long);
11752 XSI      void          lcong48(unsigned short[7]);
11753          ldiv_t        ldiv(long, long);
11754          long long     llabs(long long);
11755          lldiv_t       lldiv(long long, long long);
11756 XSI      long          lrand48(void);
11757          void         *malloc(size_t);
11758          int           mblen(const char *, size_t);
11759          size_t        mbstowcs(wchar_t *restrict, const char *restrict, size_t);
11760          int           mbtowc(wchar_t *restrict, const char *restrict, size_t);
11761 XSI      char         *mktemp(char *); (LEGACY)
11762          int           mkstemp(char *);
11763          long          mrand48(void);
11764          long          nrand48(unsigned short[3]);
11765 ADV      int           posix_memalign(void **, size_t, size_t);
11766 XSI      int           posix_openpt(int);
11767          char         *ptsname(int);
11768          int           putenv(char *);
11769          void          qsort(void *, size_t, size_t, int (*)(const void *,
11770                            const void *));
11771          int           rand(void);
11772 TSF      int           rand_r(unsigned *);
11773 XSI      long          random(void);
11774          void         *realloc(void *, size_t);
11775 XSI      char         *realpath(const char *restrict, char *restrict);
11776          unsigned short seed48(unsigned short[3]);
11777 CX       int           setenv(const char *, const char *, int);
11778 XSI      void          setkey(const char *);
11779          char         *setstate(const char *);
11780          void          srand(unsigned);
11781 XSI      void          srand48(long);
11782          void          srandom(unsigned);
11783          double        strtod(const char *restrict, char **restrict);
11784          float         strtof(const char *restrict, char **restrict);
```

```
11785       long          strtol(const char *restrict, char **restrict, int);
11786       long double   strtold(const char *restrict, char **restrict);
11787       long long     strtoll(const char *restrict, char **restrict, int);
11788       unsigned long strtoul(const char *restrict, char **restrict, int);
11789       unsigned long long
11790                     strtoull(const char *restrict, char **restrict, int);
11791       int           system(const char *);
11792 XSI   int           unlockpt(int);
11793 CX    int           unsetenv(const char *);
11794       size_t        wcstombs(char *restrict, const wchar_t *restrict, size_t);
11795       int           wctomb(char *, wchar_t);
```

11796 XSI Inclusion of the **<stdlib.h>** header may also make visible all symbols from **<stddef.h>**,
11797 **<limits.h>**, **<math.h>**, and **<sys/wait.h>**.

11798 **APPLICATION USAGE**

11799 None.

11800 **RATIONALE**

11801 None.

11802 **FUTURE DIRECTIONS**

11803 None.

11804 **SEE ALSO**

11805 **<limits.h>**, **<math.h>**, **<stddef.h>**, **<sys/types.h>**, **<sys/wait.h>**, the System Interfaces volume of
11806 IEEE Std 1003.1-2001, *_Exit*( ), *a64l*( ), *abort*( ), *abs*( ), *atexit*( ), *atof*( ), *atoi*( ), *atol*( ), *atoll*( ), *bsearch*( ),
11807 *calloc*( ), *div*( ), *drand48*( ), *erand48*( ), *exit*( ), *free*( ), *getenv*( ), *getsubopt*( ), *grantpt*( ), *initstate*( ),
11808 *jrand48*( ), *l64a*( ), *labs*( ), *lcong48*( ), *ldiv*( ), *llabs*( ), *lldiv*( ), *lrand48*( ), *malloc*( ), *mblen*( ), *mbstowcs*( ),
11809 *mbtowc*( ), *mkstemp*( ), *mrand48*( ), *nrand48*( ), *posix_memalign*( ), *ptsname*( ), *putenv*( ), *qsort*( ),
11810 *rand*( ), *realloc*( ), *realpath*( ), *setstate*( ), *srand*( ), *srand48*( ), *srandom*( ), *strtod*( ), *strtof*( ), *strtol*( ),
11811 *strtold*( ), *strtoll*( ), *strtoul*( ), *strtoull*( ), *unlockpt*( ), *wcstombs*( ), *wctomb*( )

11812 **CHANGE HISTORY**

11813 First released in Issue 3.

11814 **Issue 5**

11815 The DESCRIPTION is updated for alignment with the POSIX Threads Extension.

11816 The *ttyslot*( ) and *valloc*( ) functions are marked LEGACY.

11817 The type of the third argument to *initstate*( ) is changed from **int** to **size_t**. The type of the return
11818 value from *setstate*( ) is changed from **char** to **char ***, and the type of the first argument is
11819 changed from **char *** to **const char ***.

11820 **Issue 6**

11821 The Open Group Corrigendum U021/1 is applied, correcting the prototype for *realpath*( ) to be
11822 consistent with the reference page.

11823 The Open Group Corrigendum U028/13 is applied, correcting the prototype for *putenv*( ) to be
11824 consistent with the reference page.

11825 The *rand_r*( ) function is marked as part of the Thread-Safe Functions option.

11826 Function prototypes for *setenv*( ) and *unsetenv*( ) are added.

11827 The *posix_memalign*( ) function is added for alignment with IEEE Std 1003.1d-1999.

11828 This reference page is updated to align with the ISO/IEC 9899:1999 standard.

The *ecvt*( ), *fcvt*( ), *gcvt*( ), and *mktemp*( ) functions are marked LEGACY.

The *ttyslot*( ) and *valloc*( ) functions are removed as they were previously marked LEGACY.

Extensions beyond the ISO C standard are marked.

NAME

string.h — string operations

SYNOPSIS

```
#include <string.h>
```

DESCRIPTION

CX Some of the functionality described on this reference page extends the ISO C standard. Applications shall define the appropriate feature test macro (see the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.2, The Compilation Environment) to enable the visibility of these symbols in this header.

The **<string.h>** header shall define the following:

NULL	Null pointer constant.
size_t	As described in **<stddef.h>**.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
XSI void    *memccpy(void *restrict, const void *restrict, int, size_t);
    void    *memchr(const void *, int, size_t);
    int      memcmp(const void *, const void *, size_t);
    void    *memcpy(void *restrict, const void *restrict, size_t);
    void    *memmove(void *, const void *, size_t);
    void    *memset(void *, int, size_t);
    char    *strcat(char *restrict, const char *restrict);
    char    *strchr(const char *, int);
    int      strcmp(const char *, const char *);
    int      strcoll(const char *, const char *);
    char    *strcpy(char *restrict, const char *restrict);
    size_t   strcspn(const char *, const char *);
XSI char    *strdup(const char *);
    char    *strerror(int);
TSF int     *strerror_r(int, char *, size_t);
    size_t   strlen(const char *);
    char    *strncat(char *restrict, const char *restrict, size_t);
    int      strncmp(const char *, const char *, size_t);
    char    *strncpy(char *restrict, const char *restrict, size_t);
    char    *strpbrk(const char *, const char *);
    char    *strrchr(const char *, int);
    size_t   strspn(const char *, const char *);
    char    *strstr(const char *, const char *);
    char    *strtok(char *restrict, const char *restrict);
TSF char    *strtok_r(char *, const char *, char **);
    size_t   strxfrm(char *restrict, const char *restrict, size_t);
```

XSI Inclusion of the **<string.h>** header may also make visible all symbols from **<stddef.h>**.

11873 **APPLICATION USAGE**

11874 None.

11875 **RATIONALE**

11876 None.

11877 **FUTURE DIRECTIONS**

11878 None.

11879 **SEE ALSO**

11880 **<stddef.h>**, **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *memccpy*( ),
11881 *memchr*( ), *memcmp*( ), *memcpy*( ), *memmove*( ), *memset*( ), *strcat*( ), *strchr*( ), *strcmp*( ), *strcoll*( ),
11882 *strcpy*( ), *strcspn*( ), *strdup*( ), *strerror*( ), *strlen*( ), *strncat*( ), *strncmp*( ), *strncpy*( ), *strpbrk*( ), *strrchr*( ),
11883 *strspn*( ), *strstr*( ), *strtok*( ), *strxfrm*( )

11884 **CHANGE HISTORY**

11885 First released in Issue 1. Derived from Issue 1 of the SVID.

11886 **Issue 5**

11887 The DESCRIPTION is updated for alignment with the POSIX Threads Extension.

11888 **Issue 6**

11889 The *strtok_r*( ) function is marked as part of the Thread-Safe Functions option.

11890 This reference page is updated to align with the ISO / IEC 9899: 1999 standard.

11891 The *strerror_r*( ) function is added in response to IEEE PASC Interpretation 1003.1c #39.

NAME

strings.h — string operations

SYNOPSIS

XSI
```
#include <strings.h>
```

DESCRIPTION

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int    bcmp(const void *, const void *, size_t); (LEGACY)
void   bcopy(const void *, void *, size_t); (LEGACY)
void   bzero(void *, size_t); (LEGACY)
int    ffs(int);
char  *index(const char *, int); (LEGACY)
char  *rindex(const char *, int); (LEGACY)
int    strcasecmp(const char *, const char *);
int    strncasecmp(const char *, const char *, size_t);
```

The **size_t** type shall be defined through **typedef** as described in **<stddef.h>**.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<stddef.h>, the System Interfaces volume of IEEE Std 1003.1-2001, *ffs*( ), *strcasecmp*( ), *strncasecmp*( )

CHANGE HISTORY

First released in Issue 4, Version 2.

Issue 6

The Open Group Corrigendum U021/2 is applied, correcting the prototype for *index*( ) to be consistent with the reference page.

The *bcmp*( ), *bcopy*( ), *bzero*( ), *index*( ), and *rindex*( ) functions are marked LEGACY.

11924 **NAME**

11925 stropts.h — STREAMS interface (**STREAMS**)

11926 **SYNOPSIS**

11927 XSR
```
#include <stropts.h>
```
11928

11929 **DESCRIPTION**

11930 The **<stropts.h>** header shall define the **bandinfo** structure that includes at least the following
11931 members:

11932 `unsigned char`	`bi_pri`	Priority band.
11933 `int`	`bi_flag`	Flushing type.

11934 The **<stropts.h>** header shall define the **strpeek** structure that includes at least the following
11935 members:

11936 `struct strbuf`	`ctlbuf`	The control portion of the message.
11937 `struct strbuf`	`databuf`	The data portion of the message.
11938 `t_uscalar_t`	`flags`	RS_HIPRI or 0.

11939 The **<stropts.h>** header shall define the **strbuf** structure that includes at least the following
11940 members:

11941 `int`	`maxlen`	Maximum buffer length.
11942 `int`	`len`	Length of data.
11943 `char`	`*buf`	Pointer to buffer.

11944 The **<stropts.h>** header shall define the **strfdinsert** structure that includes at least the following
11945 members:

11946 `struct strbuf`	`ctlbuf`	The control portion of the message.
11947 `struct strbuf`	`databuf`	The data portion of the message.
11948 `t_uscalar_t`	`flags`	RS_HIPRI or 0.
11949 `int`	`fildes`	File descriptor of the other STREAM.
11950 `int`	`offset`	Relative location of the stored value.

11951 The **<stropts.h>** header shall define the **strioctl** structure that includes at least the following
11952 members:

11953 `int`	`ic_cmd`	*ioctl*( ) command.
11954 `int`	`ic_timout`	Timeout for response.
11955 `int`	`ic_len`	Length of data.
11956 `char`	`*ic_dp`	Pointer to buffer.

11957 The **<stropts.h>** header shall define the **strrecvfd** structure that includes at least the following
11958 members:

11959 `int`	`fda`	Received file descriptor.
11960 `uid_t`	`uid`	UID of sender.
11961 `gid_t`	`gid`	GID of sender.

11962 The **uid_t** and **gid_t** types shall be defined through **typedef** as described in **<sys/types.h>**.

11963 The **<stropts.h>** header shall define the **t_scalar_t** and **t_uscalar_t** types, respectively, as signed
11964 and unsigned opaque types of equal length of at least 32 bits.

11965 The **<stropts.h>** header shall define the **str_list** structure that includes at least the following
11966 members:

11967 `int sl_nmods` Number of STREAMS module names.
11968 `struct str_mlist *sl_modlist` STREAMS module names.

11969 The **<stropts.h>** header shall define the **str_mlist** structure that includes at least the following
11970 member:

11971 `char l_name[FMNAMESZ+1]` A STREAMS module name.

11972 At least the following macros shall be defined for use as the *request* argument to *ioctl*( ):

11973 I_PUSH Push a STREAMS module.
11974 I_POP Pop a STREAMS module.
11975 I_LOOK Get the top module name.
11976 I_FLUSH Flush a STREAM.
11977 I_FLUSHBAND Flush one band of a STREAM.
11978 I_SETSIG Ask for notification signals.
11979 I_GETSIG Retrieve current notification signals.
11980 I_FIND Look for a STREAMS module.
11981 I_PEEK Peek at the top message on a STREAM.
11982 I_SRDOPT Set the read mode.
11983 I_GRDOPT Get the read mode.
11984 I_NREAD Size the top message.
11985 I_FDINSERT Send implementation-defined information about another STREAM.
11986 I_STR Send a STREAMS *ioctl*( ).
11987 I_SWROPT Set the write mode.
11988 I_GWROPT Get the write mode.
11989 I_SENDFD Pass a file descriptor through a STREAMS pipe.
11990 I_RECVFD Get a file descriptor sent via I_SENDFD.
11991 I_LIST Get all the module names on a STREAM.
11992 I_ATMARK Is the top message ‘‘marked’’?
11993 I_CKBAND See if any messages exist in a band.
11994 I_GETBAND Get the band of the top message on a STREAM.
11995 I_CANPUT Is a band writable?
11996 I_SETCLTIME Set close time delay.
11997 I_GETCLTIME Get close time delay.
11998 I_LINK Connect two STREAMs.
11999 I_UNLINK Disconnect two STREAMs.
12000 I_PLINK Persistently connect two STREAMs.
12001 I_PUNLINK Dismantle a persistent STREAMS link.

12002 At least the following macros shall be defined for use with I_LOOK:

12003 FMNAMESZ The minimum size in bytes of the buffer referred to by the *arg* argument.

12004 At least the following macros shall be defined for use with I_FLUSH:

12005 FLUSHR Flush read queues.

12006 FLUSHW Flush write queues.

12007 FLUSHRW Flush read and write queues.

12008 At least the following macros shall be defined for use with I_SETSIG:

12009 S_RDNORM A normal (priority band set to 0) message has arrived at the head of a
12010 STREAM head read queue.

12011 S_RDBAND A message with a non-zero priority band has arrived at the head of a STREAM
12012 head read queue.

12013 S_INPUT A message, other than a high-priority message, has arrived at the head of a
12014 STREAM head read queue.

12015 S_HIPRI A high-priority message is present on a STREAM head read queue.

12016 S_OUTPUT The write queue for normal data (priority band 0) just below the STREAM
12017 head is no longer full. This notifies the process that there is room on the queue
12018 for sending (or writing) normal data downstream.

12019 S_WRNORM Equivalent to S_OUTPUT.

12020 S_WRBAND The write queue for a non-zero priority band just below the STREAM head is
12021 no longer full.

12022 S_MSG A STREAMS signal message that contains the SIGPOLL signal reaches the
12023 front of the STREAM head read queue.

12024 S_ERROR Notification of an error condition reaches the STREAM head.

12025 S_HANGUP Notification of a hangup reaches the STREAM head.

12026 S_BANDURG When used in conjunction with S_RDBAND, SIGURG is generated instead of
12027 SIGPOLL when a priority message reaches the front of the STREAM head read
12028 queue.

12029 At least the following macros shall be defined for use with I_PEEK:

12030 RS_HIPRI Only look for high-priority messages.

12031 At least the following macros shall be defined for use with I_SRDOPT:

12032 RNORM Byte-STREAM mode, the default.

12033 RMSGD Message-discard mode.

12034 RMSGN Message-non-discard mode.

12035 RPROTNORM Fail *read*( ) with [EBADMSG] if a message containing a control part is at the
12036 front of the STREAM head read queue.

12037 RPROTDAT Deliver the control part of a message as data when a process issues a *read*( ).

12038 RPROTDIS Discard the control part of a message, delivering any data part, when a
12039 process issues a *read*( ).

At least the following macros shall be defined for use with I_SWOPT:

SNDZERO	Send a zero-length message downstream when a *write*( ) of 0 bytes occurs.

At least the following macros shall be defined for use with I_ATMARK:

ANYMARK	Check if the message is marked.
LASTMARK	Check if the message is the last one marked on the queue.

At least the following macros shall be defined for use with I_UNLINK:

MUXID_ALL	Unlink all STREAMs linked to the STREAM associated with *fildes*.

The following macros shall be defined for *getmsg*( ), *getpmsg*( ), *putmsg*( ), and *putpmsg*( ):

MSG_ANY	Receive any message.
MSG_BAND	Receive message from specified band.
MSG_HIPRI	Send/receive high-priority message.
MORECTL	More control information is left in message.
MOREDATA	More data is left in message.

The **<stropts.h>** header may make visible all of the symbols from **<unistd.h>**.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int    isastream(int);
int    getmsg(int, struct strbuf *restrict, struct strbuf *restrict,
           int *restrict);
int    getpmsg(int, struct strbuf *restrict, struct strbuf *restrict,
           int *restrict, int *restrict);
int    ioctl(int, int, ... );
int    putmsg(int, const struct strbuf *, const struct strbuf *, int);
int    putpmsg(int, const struct strbuf *, const struct strbuf *, int,
           int);
int    fattach(int, const char *);
int    fdetach(const char *);
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<sys/types.h>, **<unistd.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *close*( ), *fcntl*( ), *getmsg*( ), *ioctl*( ), *open*( ), *pipe*( ), *read*( ), *poll*( ), *putmsg*( ), *signal*( ), *write*( )

CHANGE HISTORY

First released in Issue 4, Version 2.

Issue 5

The *flags* members of the **strpeek** and **strfdinsert** structures are changed from **type long** to **t_uscalar_t**.

Issue 6

This header is marked as part of the XSI STREAMS Option Group.

The **restrict** keyword is added to the prototypes for *getmsg*( ) and *getpmsg*( ).

12084 **NAME**

12085 sys/ipc.h — XSI interprocess communication access structure

12086 **SYNOPSIS**

12087 XSI
```
#include <sys/ipc.h>
```
12088

12089 **DESCRIPTION**

12090 The **<sys/ipc.h>** header is used by three mechanisms for XSI interprocess communication (IPC):
12091 messages, semaphores, and shared memory. All use a common structure type, **ipc_perm**, to pass
12092 information used in determining permission to perform an IPC operation.

12093 The **ipc_perm** structure shall contain the following members:

12094 `uid_t` `uid` Owner's user ID.
12095 `gid_t` `gid` Owner's group ID.
12096 `uid_t` `cuid` Creator's user ID.
12097 `gid_t` `cgid` Creator's group ID.
12098 `mode_t` `mode` Read/write permission.

12099 The **uid_t**, **gid_t**, **mode_t**, and **key_t** types shall be defined as described in **<sys/types.h>**.

12100 Definitions shall be provided for the following constants:

12101 Mode bits:

12102 IPC_CREAT Create entry if key does not exist.

12103 IPC_EXCL Fail if key exists.

12104 IPC_NOWAIT Error if request must wait.

12105 Keys:

12106 IPC_PRIVATE Private key.

12107 Control commands:

12108 IPC_RMID Remove identifier.

12109 IPC_SET Set options.

12110 IPC_STAT Get options.

12111 The following shall be declared as a function and may also be defined as a macro. A function
12112 prototype shall be provided.

12113
```
key_t  ftok(const char *, int);
```

12114 **APPLICATION USAGE**

12115 None.

12116 **RATIONALE**

12117 None.

12118 **FUTURE DIRECTIONS**

12119 None.

12120 **SEE ALSO**

12121 **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *ftok*( )

12122 **CHANGE HISTORY**

12123 First released in Issue 2. Derived from System V Release 2.0.

12124 **NAME**

12125 sys/mman.h — memory management declarations

12126 **SYNOPSIS**

12127 `#include <sys/mman.h>`

12128 **DESCRIPTION**

12129 The **<sys/mman.h>** header shall be supported if the implementation supports at least one of the
12130 following options:

12131 MF • The Memory Mapped Files option

12132 SHM • The Shared Memory Objects option

12133 ML • The Process Memory Locking option

12134 MPR • The Memory Protection option

12135 TYM • The Typed Memory Objects option

12136 SIO • The Synchronized Input and Output option

12137 ADV • The Advisory Information option

12138 MC2 If one or more of the Advisory Information, Memory Mapped Files, or Shared Memory Objects
12139 options are supported, the following protection options shall be defined:

12140 MC2	PROT_READ	Page can be read.
12141 MC2	PROT_WRITE	Page can be written.
12142 MC2	PROT_EXEC	Page can be executed.
12143 MC2	PROT_NONE	Page cannot be accessed.

12144 The following *flag* options shall be defined:

12145 MF|SHM	MAP_SHARED	Share changes.
12146 MF|SHM	MAP_PRIVATE	Changes are private.
12147 MF|SHM	MAP_FIXED	Interpret *addr* exactly.

12148 The following flags shall be defined for *msync*( ):

12149 MF|SIO	MS_ASYNC	Perform asynchronous writes.
12150 MF|SIO	MS_SYNC	Perform synchronous writes.
12151 MF|SIO	MS_INVALIDATE	Invalidate mappings.

12152 ML The following symbolic constants shall be defined for the *mlockall*( ) function:

12153 ML	MCL_CURRENT	Lock currently mapped pages.
12154 ML	MCL_FUTURE	Lock pages that become mapped.

12155 MF|SHM The symbolic constant MAP_FAILED shall be defined to indicate a failure from the *mmap*( )
12156 function.

12157 MC1 If the Advisory Information and either the Memory Mapped Files or Shared Memory Objects
12158 options are supported, values for *advice* used by *posix_madvise*( ) shall be defined as follows:

12159 POSIX_MADV_NORMAL
12160 The application has no advice to give on its behavior with respect to the specified range. It
12161 is the default characteristic if no advice is given for a range of memory.

POSIX_MADV_SEQUENTIAL
The application expects to access the specified range sequentially from lower addresses to higher addresses.

POSIX_MADV_RANDOM
The application expects to access the specified range in a random order.

POSIX_MADV_WILLNEED
The application expects to access the specified range in the near future.

POSIX_MADV_DONTNEED
The application expects that it will not access the specified range in the near future.

TYM The following flags shall be defined for *posix_typed_mem_open*( ):

POSIX_TYPED_MEM_ALLOCATE
Allocate on *mmap*( ).

POSIX_TYPED_MEM_ALLOCATE_CONTIG
Allocate contiguously on *mmap*( ).

POSIX_TYPED_MEM_MAP_ALLOCATABLE
Map on *mmap*( ), without affecting allocatability.

The **mode_t**, **off_t**, and **size_t** types shall be defined as described in **<sys/types.h>**.

TYM The **<sys/mman.h>** header shall define the structure **posix_typed_mem_info**, which includes at least the following member:

`size_t`	`posix_tmi_length`	Maximum length which may be allocated from a typed memory object.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
MLR  int    mlock(const void *, size_t);                                          1
ML   int    mlockall(int);                                                        1
MC3  void  *mmap(void *, size_t, int, int, int, off_t);                           1
MPR  int    mprotect(void *, size_t, int);
MF|SIO int  msync(void *, size_t, int);
MLR  int    munlock(const void *, size_t);                                        1
ML   int    munlockall(void);                                                     1
MC3  int    munmap(void *, size_t);                                               1
ADV  int    posix_madvise(void *, size_t, int);
TYM  int    posix_mem_offset(const void *restrict, size_t, off_t *restrict,
                size_t *restrict, int *restrict);
     int    posix_typed_mem_get_info(int, struct posix_typed_mem_info *);
     int    posix_typed_mem_open(const char *, int, int);
SHM  int    shm_open(const char *, int, mode_t);
     int    shm_unlink(const char *);
```

12204 **APPLICATION USAGE**

12205 None.

12206 **RATIONALE**

12207 None.

12208 **FUTURE DIRECTIONS**

12209 None.

12210 **SEE ALSO**

12211 **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *mlock*( ), *mlockall*( ),
12212 *mmap*( ), *mprotect*( ), *msync*( ), *munlock*( ), *munlockall*( ), *munmap*( ), *posix_mem_offset*( ),
12213 *posix_typed_mem_get_info*( ), *posix_typed_mem_open*( ), *shm_open*( ), *shm_unlink*( )

12214 **CHANGE HISTORY**

12215 First released in Issue 4, Version 2.

12216 **Issue 5**

12217 Updated for alignment with the POSIX Realtime Extension.

12218 **Issue 6**

12219 The **<sys/mman.h>** header is marked as dependent on support for either the Memory Mapped
12220 Files, Process Memory Locking, or Shared Memory Objects options.

12221 The following changes are made for alignment with IEEE Std 1003.1j-2000:

12222 • The TYM margin code is added to the list of margin codes for the **<sys/mman.h>** header line,
12223 as well as for other lines.

12224 • The POSIX_TYPED_MEM_ALLOCATE, POSIX_TYPED_MEM_ALLOCATE_CONTIG, and
12225 POSIX_TYPED_MEM_MAP_ALLOCATABLE flags are added.

12226 • The **posix_tmi_length** structure is added.

12227 • The *posix_mem_offset*( ), *posix_typed_mem_get_info*( ), and *posix_typed_mem_open*( ) functions
12228 are added.

12229 The **restrict** keyword is added to the prototype for *posix_mem_offset*( ).

12230 IEEE PASC Interpretation 1003.1 #102 is applied, adding the prototype for *posix_madvise*( ).

12231 IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/16 is applied, correcting margin code and 1
12232 shading errors for the *mlock*( ) and *munlock*( ) functions. 1

12233 IEEE Std 1003.1-2001/Cor 1-2002, item XSH/TC1/D6/34 is applied, changing the margin code 1
12234 for the *mmap*( ) function from MF|SHM to MC3 (notation for MF|SHM|TYM). 1

12235 IEEE Std 1003.1-2001/Cor 1-2002, item XSH/TC1/D6/36 is applied, changing the margin code 1
12236 for the *munmap*( ) function from MF|SHM to MC3 (notation for MF|SHM|TYM). 1

12237 **NAME**

12238 sys/msg.h — XSI message queue structures

12239 **SYNOPSIS**

12240 XSI
```
#include <sys/msg.h>
```
12241

12242 **DESCRIPTION**

12243 The **<sys/msg.h>** header shall define the following data types through **typedef**:

12244 **msgqnum_t** Used for the number of messages in the message queue.

12245 **msglen_t** Used for the number of bytes allowed in a message queue.

12246 These types shall be unsigned integer types that are able to store values at least as large as a type
12247 **unsigned short**.

12248 The **<sys/msg.h>** header shall define the following constant as a message operation flag:

12249 MSG_NOERROR No error if big message.

12250 The **msqid_ds** structure shall contain the following members:

12251	`struct ipc_perm msg_perm`	Operation permission structure.
12252	`msgqnum_t msg_qnum`	Number of messages currently on queue.
12253	`msglen_t msg_qbytes`	Maximum number of bytes allowed on queue.
12254	`pid_t msg_lspid`	Process ID of last *msgsnd*( ).
12255	`pid_t msg_lrpid`	Process ID of last *msgrcv*( ).
12256	`time_t msg_stime`	Time of last *msgsnd*( ).
12257	`time_t msg_rtime`	Time of last *msgrcv*( ).
12258	`time_t msg_ctime`	Time of last change.

12259 The **pid_t**, **time_t**, **key_t**, **size_t**, and **ssize_t** types shall be defined as described in **<sys/types.h>**.

12260 The following shall be declared as functions and may also be defined as macros. Function
12261 prototypes shall be provided.

```
12262 int       msgctl(int, int, struct msqid_ds *);
12263 int       msgget(key_t, int);
12264 ssize_t   msgrcv(int, void *, size_t, long, int);
12265 int       msgsnd(int, const void *, size_t, int);
```

12266 In addition, all of the symbols from **<sys/ipc.h>** shall be defined when this header is included.

12267 **APPLICATION USAGE**

12268 None.

12269 **RATIONALE**

12270 None.

12271 **FUTURE DIRECTIONS**

12272 None.

12273 **SEE ALSO**

12274 **<sys/ipc.h>**, **<sys/types.h>**, *msgctl*( ), *msgget*( ), *msgrcv*( ), *msgsnd*( )

12275 **CHANGE HISTORY**

12276 First released in Issue 2. Derived from System V Release 2.0.

12277 **NAME**

12278 sys/resource.h — definitions for XSI resource operations

12279 **SYNOPSIS**

12280 XSI
```
#include <sys/resource.h>
```
12281

12282 **DESCRIPTION**

12283 The **<sys/resource.h>** header shall define the following symbolic constants as possible values of
12284 the *which* argument of *getpriority*( ) and *setpriority*( ):

12285 PRIO_PROCESS Identifies the *who* argument as a process ID.

12286 PRIO_PGRP Identifies the *who* argument as a process group ID.

12287 PRIO_USER Identifies the *who* argument as a user ID.

12288 The following type shall be defined through **typedef**:

12289 **rlim_t** Unsigned integer type used for limit values.

12290 The following symbolic constants shall be defined:

12291 RLIM_INFINITY A value of **rlim_t** indicating no limit.

12292 RLIM_SAVED_MAX A value of type **rlim_t** indicating an unrepresentable saved hard
12293 limit.

12294 RLIM_SAVED_CUR A value of type **rlim_t** indicating an unrepresentable saved soft limit.

12295 On implementations where all resource limits are representable in an object of type **rlim_t**,
12296 RLIM_SAVED_MAX and RLIM_SAVED_CUR need not be distinct from RLIM_INFINITY.

12297 The following symbolic constants shall be defined as possible values of the *who* parameter of
12298 *getrusage*( ):

12299 RUSAGE_SELF Returns information about the current process.

12300 RUSAGE_CHILDREN Returns information about children of the current process.

12301 The **<sys/resource.h>** header shall define the **rlimit** structure that includes at least the following
12302 members:

12303 `rlim_t rlim_cur` The current (soft) limit.
12304 `rlim_t rlim_max` The hard limit.

12305 The **<sys/resource.h>** header shall define the **rusage** structure that includes at least the following
12306 members:

12307 `struct timeval ru_utime` User time used.
12308 `struct timeval ru_stime` System time used.

12309 The **timeval** structure shall be defined as described in **<sys/time.h>**.

12310 The following symbolic constants shall be defined as possible values for the *resource* argument of
12311 *getrlimit*( ) and *setrlimit*( ):

12312 RLIMIT_CORE Limit on size of **core** file.

12313 RLIMIT_CPU Limit on CPU time per process.

12314 RLIMIT_DATA Limit on data segment size.

12315 RLIMIT_FSIZE Limit on file size.

12316	RLIMIT_NOFILE	Limit on number of open files.
12317	RLIMIT_STACK	Limit on stack size.
12318	RLIMIT_AS	Limit on address space size.

12319 The following shall be declared as functions and may also be defined as macros. Function
12320 prototypes shall be provided.

```
12321 int  getpriority(int, id_t);
12322 int  getrlimit(int, struct rlimit *);
12323 int  getrusage(int, struct rusage *);
12324 int  setpriority(int, id_t, int);
12325 int  setrlimit(int, const struct rlimit *);
```

12326 The **id_t** type shall be defined through **typedef** as described in **<sys/types.h>**.

12327 Inclusion of the **<sys/resource.h>** header may also make visible all symbols from **<sys/time.h>**.

12328 **APPLICATION USAGE**

12329 None.

12330 **RATIONALE**

12331 None.

12332 **FUTURE DIRECTIONS**

12333 None.

12334 **SEE ALSO**

12335 **<sys/time.h>**, **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *getpriority*( ),
12336 *getrusage*( ), *getrlimit*( )

12337 **CHANGE HISTORY**

12338 First released in Issue 4, Version 2.

12339 **Issue 5**

12340 Large File System extensions are added.

12341 **NAME**

12342 sys/select.h — select types

12343 **SYNOPSIS**

12344 `#include <sys/select.h>`

12345 **DESCRIPTION**

12346 The **<sys/select.h>** header shall define the **timeval** structure that includes at least the following
12347 members:

12348 `time_t`	`tv_sec`	Seconds.
12349 `suseconds_t`	`tv_usec`	Microseconds.

12350 The **time_t** and **suseconds_t** types shall be defined as described in **<sys/types.h>**.

12351 The **sigset_t** type shall be defined as described in **<signal.h>**.

12352 The **timespec** structure shall be defined as described in **<time.h>**.

12353 The **<sys/select.h>** header shall define the **fd_set** type as a structure.

12354 Each of the following may be declared as a function, or defined as a macro, or both:

12355 **void** *FD_CLR*(**int** *fd*, **fd_set ***fdset*)
12356 Clears the bit for the file descriptor *fd* in the file descriptor set *fdset*.

12357 **int** *FD_ISSET*(**int** *fd*, **fd_set ***fdset*)
12358 Returns a non-zero value if the bit for the file descriptor *fd* is set in the file descriptor set by
12359 *fdset*, and 0 otherwise.

12360 **void** *FD_SET*(**int** *fd*, **fd_set ***fdset*)
12361 Sets the bit for the file descriptor *fd* in the file descriptor set *fdset*.

12362 **void** *FD_ZERO*(**fd_set ***fdset*)
12363 Initializes the file descriptor set *fdset* to have zero bits for all file descriptors.

12364 If implemented as macros, these may evaluate their arguments more than once, so applications
12365 should ensure that the arguments they supply are never expressions with side effects.

12366 The following shall be defined as a macro:

12367 FD_SETSIZE
12368 Maximum number of file descriptors in an **fd_set** structure.

12369 The following shall be declared as functions and may also be defined as macros. Function
12370 prototypes shall be provided.

```
12371 int  pselect(int, fd_set *restrict, fd_set *restrict, fd_set *restrict,
12372          const struct timespec *restrict, const sigset_t *restrict);
12373 int  select(int, fd_set *restrict, fd_set *restrict, fd_set *restrict,
12374          struct timeval *restrict);
```

12375 Inclusion of the **<sys/select.h>** header may make visible all symbols from the headers
12376 **<signal.h>**, **<sys/time.h>**, and **<time.h>**.

12377 **APPLICATION USAGE**

12378 None.

12379 **RATIONALE**

12380 None.

12381 **FUTURE DIRECTIONS**

12382 None.

12383 **SEE ALSO**

12384 **<signal.h>**, **<sys/time.h>**, **<sys/types.h>**, **<time.h>**, the System Interfaces volume of
12385 IEEE Std 1003.1-2001, *pselect*( ), *select*( )

12386 **CHANGE HISTORY**

12387 First released in Issue 6. Derived from IEEE Std 1003.1g-2000.

12388 The requirement for the **fd_set** structure to have a member *fds_bits* has been removed as per The
12389 Open Group Base Resolution bwg2001-005.

12390 **NAME**

12391 sys/sem.h — XSI semaphore facility

12392 **SYNOPSIS**

12393 XSI
```
#include <sys/sem.h>
```
12394

12395 **DESCRIPTION**

12396 The **<sys/sem.h>** header shall define the following constants and structures.

12397 Semaphore operation flags:

12398 SEM_UNDO Set up adjust on exit entry.

12399 Command definitions for the *semctl*( ) function shall be provided as follows:

12400 GETNCNT Get *semncnt*.

12401 GETPID Get *sempid*.

12402 GETVAL Get *semval*.

12403 GETALL Get all cases of *semval*.

12404 GETZCNT Get *semzcnt*.

12405 SETVAL Set *semval*.

12406 SETALL Set all cases of *semval*.

12407 The **semid_ds** structure shall contain the following members:

12408 `struct ipc_perm` `sem_perm` Operation permission structure.
12409 `unsigned short` `sem_nsems` Number of semaphores in set.
12410 `time_t` `sem_otime` Last *semop*( ) time.
12411 `time_t` `sem_ctime` Last time changed by *semctl*( ).

12412 The **pid_t**, **time_t**, **key_t**, and **size_t** types shall be defined as described in **<sys/types.h>**.

12413 A semaphore shall be represented by an anonymous structure containing the following
12414 members:

12415 `unsigned short` `semval` Semaphore value.
12416 `pid_t` `sempid` Process ID of last operation.
12417 `unsigned short` `semncnt` Number of processes waiting for *semval*
12418 to become greater than current value.
12419 `unsigned short` `semzcnt` Number of processes waiting for *semval*
12420 to become 0.

12421 The **sembuf** structure shall contain the following members:

12422 `unsigned short` `sem_num` Semaphore number.
12423 `short` `sem_op` Semaphore operation.
12424 `short` `sem_flg` Operation flags.

12425 The following shall be declared as functions and may also be defined as macros. Function
12426 prototypes shall be provided.

```
12427 int   semctl(int, int, int, ...);
12428 int   semget(key_t, int, int);
12429 int   semop(int, struct sembuf *, size_t);
```


12430 In addition, all of the symbols from **<sys/ipc.h>** shall be defined when this header is included.

12431 **APPLICATION USAGE**

12432 None.

12433 **RATIONALE**

12434 None.

12435 **FUTURE DIRECTIONS**

12436 None.

12437 **SEE ALSO**

12438 **<sys/ipc.h>**, **<sys/types.h>**, *semctl*( ), *semget*( ), *semop*( )

12439 **CHANGE HISTORY**

12440 First released in Issue 2. Derived from System V Release 2.0.

12441 **NAME**

12442 sys/shm.h — XSI shared memory facility

12443 **SYNOPSIS**

12444 XSI
```
#include <sys/shm.h>
```
12445

12446 **DESCRIPTION**

12447 The **<sys/shm.h>** header shall define the following symbolic constants:

12448 SHM_RDONLY Attach read-only (else read-write).

12449 SHM_RND Round attach address to SHMLBA.

12450 The **<sys/shm.h>** header shall define the following symbolic value:

12451 SHMLBA Segment low boundary address multiple.

12452 The following data types shall be defined through **typedef**:

12453 **shmatt_t** Unsigned integer used for the number of current attaches that must be able to
12454 store values at least as large as a type **unsigned short**.

12455 The **shmid_ds** structure shall contain the following members:

12456	`struct ipc_perm shm_perm`	Operation permission structure.
12457	`size_t shm_segsz`	Size of segment in bytes.
12458	`pid_t shm_lpid`	Process ID of last shared memory operation.
12459	`pid_t shm_cpid`	Process ID of creator.
12460	`shmatt_t shm_nattch`	Number of current attaches.
12461	`time_t shm_atime`	Time of last *shmat*( ).
12462	`time_t shm_dtime`	Time of last *shmdt*( ).
12463	`time_t shm_ctime`	Time of last change by *shmctl*( ).

12464 The **pid_t**, **time_t**, **key_t**, and **size_t** types shall be defined as described in **<sys/types.h>**.

12465 The following shall be declared as functions and may also be defined as macros. Function
12466 prototypes shall be provided.

```
12467 void *shmat(int, const void *, int);
12468 int   shmctl(int, int, struct shmid_ds *);
12469 int   shmdt(const void *);
12470 int   shmget(key_t, size_t, int);
```

12471 In addition, all of the symbols from **<sys/ipc.h>** shall be defined when this header is included.

12472 **APPLICATION USAGE**

12473 None.

12474 **RATIONALE**

12475 None.

12476 **FUTURE DIRECTIONS**

12477 None.

12478 **SEE ALSO**

12479 **<sys/ipc.h>**, **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *shmat*( ),
12480 *shmctl*( ), *shmdt*( ), *shmget*( )

12481 **CHANGE HISTORY**

12482 First released in Issue 2. Derived from System V Release 2.0.

12483 **Issue 5**

12484 The type of *shm_segsz* is changed from **int** to **size_t**.

12485 **NAME**

12486 sys/socket.h — main sockets header

12487 **SYNOPSIS**

12488 `#include <sys/socket.h>`

12489 **DESCRIPTION**

12490 The **<sys/socket.h>** header shall define the type **socklen_t**, which is an integer type of width of
12491 at least 32 bits; see APPLICATION USAGE.

12492 The **<sys/socket.h>** header shall define the unsigned integer type **sa_family_t**.

12493 The **<sys/socket.h>** header shall define the **sockaddr** structure that includes at least the
12494 following members:

12495 `sa_family_t  sa_family` Address family.
12496 `char  sa_data[]` Socket address (variable-length data).

12497 The **sockaddr** structure is used to define a socket address which is used in the *bind*( ), *connect*( ),
12498 *getpeername*( ), *getsockname*( ), *recvfrom*( ), and *sendto*( ) functions.

12499 The **<sys/socket.h>** header shall define the **sockaddr_storage** structure. This structure shall be:

12500 - Large enough to accommodate all supported protocol-specific address structures

12501 - Aligned at an appropriate boundary so that pointers to it can be cast as pointers to protocol-
12502 specific address structures and used to access the fields of those structures without
12503 alignment problems

12504 The **sockaddr_storage** structure shall contain at least the following members:

12505 `sa_family_t  ss_family`

12506 When a **sockaddr_storage** structure is cast as a **sockaddr** structure, the *ss_family* field of the
12507 **sockaddr_storage** structure shall map onto the *sa_family* field of the **sockaddr** structure. When a
12508 **sockaddr_storage** structure is cast as a protocol-specific address structure, the *ss_family* field
12509 shall map onto a field of that structure that is of type **sa_family_t** and that identifies the
12510 protocol's address family.

12511 The **<sys/socket.h>** header shall define the **msghdr** structure that includes at least the following
12512 members:

12513 `void  *msg_name` Optional address.
12514 `socklen_t  msg_namelen` Size of address.
12515 `struct iovec  *msg_iov` Scatter/gather array.
12516 `int  msg_iovlen` Members in *msg_iov*.
12517 `void  *msg_control` Ancillary data; see below.
12518 `socklen_t  msg_controllen` Ancillary data buffer *len*.
12519 `int  msg_flags` Flags on received message.

12520 The **msghdr** structure is used to minimize the number of directly supplied parameters to the
12521 *recvmsg*( ) and *sendmsg*( ) functions. This structure is used as a *value-result* parameter in the
12522 *recvmsg*( ) function and *value* only for the *sendmsg*( ) function.

12523 The **iovec** structure shall be defined as described in **<sys/uio.h>**.

12524 The **<sys/socket.h>** header shall define the **cmsghdr** structure that includes at least the following
12525 members:

12526 `socklen_t  cmsg_len` Data byte count, including the **cmsghdr**.
12527 `int  cmsg_level` Originating protocol.

12528 `int cmsg_type` Protocol-specific type.

12529 The **cmsghdr** structure is used for storage of ancillary data object information.

12530 Ancillary data consists of a sequence of pairs, each consisting of a **cmsghdr** structure followed
12531 by a data array. The data array contains the ancillary data message, and the **cmsghdr** structure
12532 contains descriptive information that allows an application to correctly parse the data.

12533 The values for *cmsg_level* shall be legal values for the *level* argument to the *getsockopt*( ) and
12534 *setsockopt*( ) functions. The system documentation shall specify the *cmsg_type* definitions for the
12535 supported protocols.

12536 Ancillary data is also possible at the socket level. The **<sys/socket.h>** header defines the
12537 following macro for use as the *cmsg_type* value when *cmsg_level* is SOL_SOCKET:

12538 SCM_RIGHTS Indicates that the data array contains the access rights to be sent or
12539 received.

12540 The **<sys/socket.h>** header defines the following macros to gain access to the data arrays in the
12541 ancillary data associated with a message header:

12542 CMSG_DATA(*cmsg*)
12543 If the argument is a pointer to a **cmsghdr** structure, this macro shall return an unsigned
12544 character pointer to the data array associated with the **cmsghdr** structure.

12545 CMSG_NXTHDR(*mhdr*,*cmsg*)
12546 If the first argument is a pointer to a **msghdr** structure and the second argument is a pointer
12547 to a **cmsghdr** structure in the ancillary data pointed to by the *msg_control* field of that
12548 **msghdr** structure, this macro shall return a pointer to the next **cmsghdr** structure, or a null
12549 pointer if this structure is the last **cmsghdr** in the ancillary data.

12550 CMSG_FIRSTHDR(*mhdr*)
12551 If the argument is a pointer to a **msghdr** structure, this macro shall return a pointer to the
12552 first **cmsghdr** structure in the ancillary data associated with this **msghdr** structure, or a null
12553 pointer if there is no ancillary data associated with the **msghdr** structure.

12554 The **<sys/socket.h>** header shall define the **linger** structure that includes at least the following
12555 members:

12556 `int l_onoff` Indicates whether linger option is enabled.
12557 `int l_linger` Linger time, in seconds.

12558 The **<sys/socket.h>** header shall define the following macros, with distinct integer values:

12559 SOCK_DGRAM Datagram socket.

12560 RS SOCK_RAW Raw Protocol Interface.

12561 SOCK_SEQPACKET Sequenced-packet socket.

12562 SOCK_STREAM Byte-stream socket.

12563 The **<sys/socket.h>** header shall define the following macro for use as the *level* argument of
12564 *setsockopt*( ) and *getsockopt*( ).

12565 SOL_SOCKET Options to be accessed at socket level, not protocol level.

12566 The **<sys/socket.h>** header shall define the following macros, with distinct integer values, for
12567 use as the *option_name* argument in *getsockopt*( ) or *setsockopt*( ) calls:

12568 SO_ACCEPTCONN Socket is accepting connections.

12569	SO_BROADCAST	Transmission of broadcast messages is supported.
12570	SO_DEBUG	Debugging information is being recorded.
12571	SO_DONTROUTE	Bypass normal routing.
12572	SO_ERROR	Socket error status.
12573	SO_KEEPALIVE	Connections are kept alive with periodic messages.
12574	SO_LINGER	Socket lingers on close.
12575	SO_OOBINLINE	Out-of-band data is transmitted in line.
12576	SO_RCVBUF	Receive buffer size.
12577	SO_RCVLOWAT	Receive ‘‘low water mark’’.
12578	SO_RCVTIMEO	Receive timeout.
12579	SO_REUSEADDR	Reuse of local addresses is supported.
12580	SO_SNDBUF	Send buffer size.
12581	SO_SNDLOWAT	Send ‘‘low water mark’’.
12582	SO_SNDTIMEO	Send timeout.
12583	SO_TYPE	Socket type.

12584 The **<sys/socket.h>** header shall define the following macro as the maximum *backlog* queue
12585 length which may be specified by the *backlog* field of the *listen*( ) function:

12586	SOMAXCONN	The maximum *backlog* queue length.

12587 The **<sys/socket.h>** header shall define the following macros, with distinct integer values, for
12588 use as the valid values for the *msg_flags* field in the **msghdr** structure, or the *flags* parameter in
12589 *recvfrom*( ), *recvmsg*( ), *sendmsg*( ), or *sendto*( ) calls:

12590	MSG_CTRUNC	Control data truncated.
12591	MSG_DONTROUTE	Send without using routing tables.
12592	MSG_EOR	Terminates a record (if supported by the protocol).
12593	MSG_OOB	Out-of-band data.
12594	MSG_PEEK	Leave received data in queue.
12595	MSG_TRUNC	Normal data truncated.
12596	MSG_WAITALL	Attempt to fill the read buffer.

12597 The **<sys/socket.h>** header shall define the following macros, with distinct integer values:

12598		AF_INET	Internet domain sockets for use with IPv4 addresses.
12599	IP6	AF_INET6	Internet domain sockets for use with IPv6 addresses.
12600		AF_UNIX	UNIX domain sockets.
12601		AF_UNSPEC	Unspecified.

12602 The **<sys/socket.h>** header shall define the following macros, with distinct integer values:

12603	SHUT_RD	Disables further receive operations.

12604 SHUT_RDWR Disables further send and receive operations.

12605 SHUT_WR Disables further send operations.

12606 The following shall be declared as functions and may also be defined as macros. Function
12607 prototypes shall be provided.

```
12608 int     accept(int, struct sockaddr *restrict, socklen_t *restrict);
12609 int     bind(int, const struct sockaddr *, socklen_t);
12610 int     connect(int, const struct sockaddr *, socklen_t);
12611 int     getpeername(int, struct sockaddr *restrict, socklen_t *restrict);
12612 int     getsockname(int, struct sockaddr *restrict, socklen_t *restrict);
12613 int     getsockopt(int, int, int, void *restrict, socklen_t *restrict);
12614 int     listen(int, int);
12615 ssize_t recv(int, void *, size_t, int);
12616 ssize_t recvfrom(int, void *restrict, size_t, int,
12617         struct sockaddr *restrict, socklen_t *restrict);
12618 ssize_t recvmsg(int, struct msghdr *, int);
12619 ssize_t send(int, const void *, size_t, int);
12620 ssize_t sendmsg(int, const struct msghdr *, int);
12621 ssize_t sendto(int, const void *, size_t, int, const struct sockaddr *,
12622         socklen_t);
12623 int     setsockopt(int, int, int, const void *, socklen_t);
12624 int     shutdown(int, int);
12625 int     socket(int, int, int);
12626 int     sockatmark(int);
12627 int     socketpair(int, int, int, int[2]);
```

12628 Inclusion of **<sys/socket.h>** may also make visible all symbols from **<sys/uio.h>**.

12629 **APPLICATION USAGE**

12630 To forestall portability problems, it is recommended that applications not use values larger than
12631 $2^{31}-1$ for the **socklen_t** type.

12632 The **sockaddr_storage** structure solves the problem of declaring storage for automatic variables
12633 which is both large enough and aligned enough for storing the socket address data structure of
12634 any family. For example, code with a file descriptor and without the context of the address
12635 family can pass a pointer to a variable of this type, where a pointer to a socket address structure
12636 is expected in calls such as *getpeername*( ), and determine the address family by accessing the
12637 received content after the call.

12638 The example below illustrates a data structure which aligns on a 64-bit boundary. An
12639 implementation-defined field *_ss_align* following *_ss_pad1* is used to force a 64-bit alignment
12640 which covers proper alignment good enough for needs of at least **sockaddr_in6** (IPv6) and
12641 **sockaddr_in** (IPv4) address data structures. The size of padding field *_ss_pad1* depends on the
12642 chosen alignment boundary. The size of padding field *_ss_pad2* depends on the value of overall
12643 size chosen for the total size of the structure. This size and alignment are represented in the
12644 above example by implementation-defined (not required) constants _SS_MAXSIZE (chosen
12645 value 128) and _SS_ALIGNMENT (with chosen value 8). Constants _SS_PAD1SIZE (derived
12646 value 6) and _SS_PAD2SIZE (derived value 112) are also for illustration and not required. The
12647 implementation-defined definitions and structure field names above start with an underscore to
12648 denote implementation private name space. Portable code is not expected to access or reference
12649 those fields or constants.

```
12650 /*
12651  *  Desired design of maximum size and alignment.
```



```
12652          */
12653         #define _SS_MAXSIZE 128
12654             /* Implementation-defined maximum size. */
12655         #define _SS_ALIGNSIZE (sizeof(int64_t))
12656             /* Implementation-defined desired alignment. */
12657         /*
12658          *  Definitions used for sockaddr_storage structure paddings design.
12659          */
12660         #define _SS_PAD1SIZE (_SS_ALIGNSIZE – sizeof(sa_family_t))
12661         #define _SS_PAD2SIZE (_SS_MAXSIZE – (sizeof(sa_family_t)+ \
12662                               _SS_PAD1SIZE + _SS_ALIGNSIZE))
12663         struct sockaddr_storage {
12664             sa_family_t  ss_family;  /* Address family. */
12665         /*
12666          *  Following fields are implementation-defined.
12667          */
12668             char _ss_pad1[_SS_PAD1SIZE];
12669                 /* 6-byte pad; this is to make implementation-defined
12670                    pad up to alignment field that follows explicit in
12671                    the data structure. */
12672             int64_t _ss_align;  /* Field to force desired structure
12673                                    storage alignment. */
12674             char _ss_pad2[_SS_PAD2SIZE];
12675                 /* 112-byte pad to achieve desired size,
12676                    _SS_MAXSIZE value minus size of ss_family
12677                    __ss_pad1, __ss_align fields is 112. */
12678         };
```

12679 **RATIONALE**

12680 None.

12681 **FUTURE DIRECTIONS**

12682 None.

12683 **SEE ALSO**

12684 **<sys/uio.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *accept*( ), *bind*( ), *connect*( ),
12685 *getpeername*( ), *getsockname*( ), *getsockopt*( ), *listen*( ), *recv*( ), *recvfrom*( ), *recvmsg*( ), *send*( ),
12686 *sendmsg*( ), *sendto*( ), *setsockopt*( ), *shutdown*( ), *socket*( ), *socketpair*( )

12687 **CHANGE HISTORY**

12688 First released in Issue 6. Derived from the XNS, Issue 5.2 specification.

12689 The **restrict** keyword is added to the prototypes for *accept*( ), *getpeername*( ), *getsockname*( ),
12690 *getsockopt*( ), and *recvfrom*( ).

12691 **NAME**

12692 sys/stat.h — data returned by the stat( ) function

12693 **SYNOPSIS**

12694 `#include <sys/stat.h>`

12695 **DESCRIPTION**

12696 The **<sys/stat.h>** header shall define the structure of the data returned by the functions *fstat*( ),
12697 *lstat*( ), and *stat*( ).

12698 The **stat** structure shall contain at least the following members:

12699	`dev_t`	`st_dev`	Device ID of device containing file.
12700	`ino_t`	`st_ino`	File serial number.
12701	`mode_t`	`st_mode`	Mode of file (see below).
12702	`nlink_t`	`st_nlink`	Number of hard links to the file.
12703	`uid_t`	`st_uid`	User ID of file.
12704	`gid_t`	`st_gid`	Group ID of file.
12705 XSI	`dev_t`	`st_rdev`	Device ID (if file is character or block special).
12706	`off_t`	`st_size`	For regular files, the file size in bytes.
12707			For symbolic links, the length in bytes of the
12708			pathname contained in the symbolic link.
12709 SHM			For a shared memory object, the length in bytes.
12710 TYM			For a typed memory object, the length in bytes.
12711			For other file types, the use of this field is
12712			unspecified.
12713	`time_t`	`st_atime`	Time of last access.
12714	`time_t`	`st_mtime`	Time of last data modification.
12715	`time_t`	`st_ctime`	Time of last status change.
12716 XSI	`blksize_t`	`st_blksize`	A file system-specific preferred I/O block size for
12717			this object. In some file system types, this may
12718			vary from file to file.
12719	`blkcnt_t`	`st_blocks`	Number of blocks allocated for this object.

12720

12721 The *st_ino* and *st_dev* fields taken together uniquely identify the file within the system. The
12722 **blkcnt_t**, **blksize_t**, **dev_t**, **ino_t**, **mode_t**, **nlink_t**, **uid_t**, **gid_t**, **off_t**, and **time_t** types shall be
12723 defined as described in **<sys/types.h>**. The **timespec** structure may be defined as described in 2
12724 **<time.h>**. Times shall be given in seconds since the Epoch. 2

12725 Unless otherwise specified, the structure members *st_mode*, *st_ino*, *st_dev*, *st_uid*, *st_gid*, *st_atime*,
12726 *st_ctime*, and *st_mtime* shall have meaningful values for all file types defined in
12727 IEEE Std 1003.1-2001.

12728 For symbolic links, the *st_mode* member shall contain meaningful information, which can be
12729 used with the file type macros described below, that take a *mode* argument. The *st_size* member
12730 shall contain the length, in bytes, of the pathname contained in the symbolic link. File mode bits
12731 and the contents of the remaining members of the **stat** structure are unspecified. The value
12732 returned in the *st_size* field shall be the length of the contents of the symbolic link, and shall not
12733 count a trailing null if one is present.

12734 The following symbolic names for the values of type **mode_t** shall also be defined.

12735 File type:

12736 XSI	S_IFMT	Type of file.

		S_IFBLK	Block special.
		S_IFCHR	Character special.
		S_IFIFO	FIFO special.
		S_IFREG	Regular.
		S_IFDIR	Directory.
		S_IFLNK	Symbolic link.
		S_IFSOCK	Socket.

File mode bits:

	S_IRWXU	Read, write, execute/search by owner.	
		S_IRUSR	Read permission, owner.
		S_IWUSR	Write permission, owner.
		S_IXUSR	Execute/search permission, owner.
	S_IRWXG	Read, write, execute/search by group.	
		S_IRGRP	Read permission, group.
		S_IWGRP	Write permission, group.
		S_IXGRP	Execute/search permission, group.
	S_IRWXO	Read, write, execute/search by others.	
		S_IROTH	Read permission, others.
		S_IWOTH	Write permission, others.
		S_IXOTH	Execute/search permission, others.
	S_ISUID	Set-user-ID on execution.	
	S_ISGID	Set-group-ID on execution.	
XSI	S_ISVTX	On directories, restricted deletion flag.	

The bits defined by S_IRUSR, S_IWUSR, S_IXUSR, S_IRGRP, S_IWGRP, S_IXGRP, S_IROTH, S_IWOTH, S_IXOTH, S_ISUID, S_ISGID, and S_ISVTX shall be unique. XSI

S_IRWXU is the bitwise-inclusive OR of S_IRUSR, S_IWUSR, and S_IXUSR.

S_IRWXG is the bitwise-inclusive OR of S_IRGRP, S_IWGRP, and S_IXGRP.

S_IRWXO is the bitwise-inclusive OR of S_IROTH, S_IWOTH, and S_IXOTH.

Implementations may OR other implementation-defined bits into S_IRWXU, S_IRWXG, and S_IRWXO, but they shall not overlap any of the other bits defined in this volume of IEEE Std 1003.1-2001. The *file permission bits* are defined to be those corresponding to the bitwise-inclusive OR of S_IRWXU, S_IRWXG, and S_IRWXO.

The following macros shall be provided to test whether a file is of the specified type. The value *m* supplied to the macros is the value of *st_mode* from a **stat** structure. The macro shall evaluate to a non-zero value if the test is true; 0 if the test is false.

S_ISBLK(*m*)	Test for a block special file.	

S_ISCHR(*m*) Test for a character special file.

S_ISDIR(*m*) Test for a directory.

S_ISFIFO(*m*) Test for a pipe or FIFO special file.

S_ISREG(*m*) Test for a regular file.

S_ISLNK(*m*) Test for a symbolic link.

S_ISSOCK(*m*) Test for a socket.

The implementation may implement message queues, semaphores, or shared memory objects as distinct file types. The following macros shall be provided to test whether a file is of the specified type. The value of the *buf* argument supplied to the macros is a pointer to a **stat** structure. The macro shall evaluate to a non-zero value if the specified object is implemented as a distinct file type and the specified file type is contained in the **stat** structure referenced by *buf*. Otherwise, the macro shall evaluate to zero.

S_TYPEISMQ(*buf*) Test for a message queue.

S_TYPEISSEM(*buf*) Test for a semaphore.

S_TYPEISSHM(*buf*) Test for a shared memory object.

TYM The implementation may implement typed memory objects as distinct file types, and the following macro shall test whether a file is of the specified type. The value of the *buf* argument supplied to the macros is a pointer to a **stat** structure. The macro shall evaluate to a non-zero value if the specified object is implemented as a distinct file type and the specified file type is contained in the **stat** structure referenced by *buf*. Otherwise, the macro shall evaluate to zero.

S_TYPEISTMO(*buf*) Test macro for a typed memory object.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int    chmod(const char *, mode_t);
int    fchmod(int, mode_t);
int    fstat(int, struct stat *);
int    lstat(const char *restrict, struct stat *restrict);
int    mkdir(const char *, mode_t);
int    mkfifo(const char *, mode_t);
XSI int    mknod(const char *, mode_t, dev_t);
int    stat(const char *restrict, struct stat *restrict);
mode_t umask(mode_t);
```

APPLICATION USAGE

Use of the macros is recommended for determining the type of a file.

RATIONALE

A conforming C-language application must include **<sys/stat.h>** for functions that have arguments or return values of type **mode_t**, so that symbolic values for that type can be used. An alternative would be to require that these constants are also defined by including **<sys/types.h>**.

The S_ISUID and S_ISGID bits may be cleared on any write, not just on *open*( ), as some historical implementations do.

System calls that update the time entry fields in the **stat** structure must be documented by the implementors. POSIX-conforming systems should not update the time entry fields for functions

listed in the System Interfaces volume of IEEE Std 1003.1-2001 unless the standard requires that they do, except in the case of documented extensions to the standard.

Note that *st_dev* must be unique within a Local Area Network (LAN) in a ''system'' made up of multiple computers' file systems connected by a LAN.

Networked implementations of a POSIX-conforming system must guarantee that all files visible within the file tree (including parts of the tree that may be remotely mounted from other machines on the network) on each individual processor are uniquely identified by the combination of the *st_ino* and *st_dev* fields.

The unit for the *st_blocks* member of the **stat** structure is not defined within IEEE Std 1003.1-2001. In some implementations it is 512 bytes. It may differ on a file system basis. There is no correlation between values of the *st_blocks* and *st_blksize*, and the *f_bsize* (from **<sys/statvfs.h>**) structure members.

Traditionally, some implementations defined the multiplier for *st_blocks* in **<sys/param.h>** as the symbol DEV_BSIZE.

FUTURE DIRECTIONS

No new S_IFMT symbolic names for the file type values of **mode_t** will be defined by IEEE Std 1003.1-2001; if new file types are required, they will only be testable through *S_ISxx*( ) or *S_TYPEISxxx*( ) macros instead.

SEE ALSO

<sys/statvfs.h>, **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *chmod*( ), *fchmod*( ), *fstat*( ), *lstat*( ), *mkdir*( ), *mkfifo*( ), *mknod*( ), *stat*( ), *umask*( )

CHANGE HISTORY

First released in Issue 1. Derived from Issue 1 of the SVID.

Issue 5

The DESCRIPTION is updated for alignment with the POSIX Realtime Extension.

The type of *st_blksize* is changed from **long** to **blksize_t**; the type of *st_blocks* is changed from **long** to **blkcnt_t**.

Issue 6

The S_TYPEISMQ( ), S_TYPEISSEM( ), and S_TYPEISSHM( ) macros are unconditionally mandated.

The Open Group Corrigendum U035/4 is applied. In the DESCRIPTION, the types **blksize_t** and **blkcnt_t** have been described.

The following new requirements on POSIX implementations derive from alignment with the Single UNIX Specification:

- The **dev_t**, **ino_t**, **mode_t**, **nlink_t**, **uid_t**, **gid_t**, **off_t**, and **time_t** types are mandated.

S_IFSOCK and S_ISSOCK are added for sockets.

The description of **stat** structure members is changed to reflect contents when file type is a symbolic link.

The test macro S_TYPEISTMO is added for alignment with IEEE Std 1003.1j-2000.

The **restrict** keyword is added to the prototypes for *lstat*( ) and *stat*( ).

The *lstat*( ) function is made mandatory.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/17 is applied, adding text regarding the *st_blocks* member of the **stat** structure to the RATIONALE.

12860 IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/25 is applied, adding to the 2
12861 DESCRIPTION that the **timespec** structure may be defined as described in the **<time.h>** header. 2

12862 **NAME**

12863 sys/statvfs.h — VFS File System information structure

12864 **SYNOPSIS**

12865 XSI
```
#include <sys/statvfs.h>
```
12866

12867 **DESCRIPTION**

12868 The **<sys/statvfs.h>** header shall define the **statvfs** structure that includes at least the following
12869 members:

12870	`unsigned long f_bsize`	File system block size.
12871	`unsigned long f_frsize`	Fundamental file system block size.
12872	`fsblkcnt_t f_blocks`	Total number of blocks on file system in units of *f_frsize*.
12873	`fsblkcnt_t f_bfree`	Total number of free blocks.
12874	`fsblkcnt_t f_bavail`	Number of free blocks available to
12875		non-privileged process.
12876	`fsfilcnt_t f_files`	Total number of file serial numbers.
12877	`fsfilcnt_t f_ffree`	Total number of free file serial numbers.
12878	`fsfilcnt_t f_favail`	Number of file serial numbers available to
12879		non-privileged process.
12880	`unsigned long f_fsid`	File system ID.
12881	`unsigned long f_flag`	Bit mask of *f_flag* values.
12882	`unsigned long f_namemax`	Maximum filename length.

12883 The **fsblkcnt_t** and **fsfilcnt_t** types shall be defined as described in **<sys/types.h>**.

12884 The following flags for the *f_flag* member shall be defined:

12885 ST_RDONLY Read-only file system.

12886 ST_NOSUID Does not support the semantics of the ST_ISUID and ST_ISGID file mode bits. 1

12887 The following shall be declared as functions and may also be defined as macros. Function
12888 prototypes shall be provided.

```
12889 int statvfs(const char *restrict, struct statvfs *restrict);
12890 int fstatvfs(int, struct statvfs *);
```

12891 **APPLICATION USAGE**

12892 None.

12893 **RATIONALE**

12894 None.

12895 **FUTURE DIRECTIONS**

12896 None.

12897 **SEE ALSO**

12898 **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *fstatvfs*( ), *statvfs*( )

12899 **CHANGE HISTORY**

12900 First released in Issue 4, Version 2.

12901 **Issue 5**

12902 The type of *f_blocks*, *f_bfree*, and *f_bavail* is changed from **unsigned long** to **fsblkcnt_t**; the type
12903 of *f_files*, *f_ffree*, and *f_favail* is changed from **unsigned long** to **fsfilcnt_t**.

Issue 6

The Open Group Corrigendum U035/5 is applied. In the DESCRIPTION, the types **fsblkcnt_t** and **fsfilcnt_t** have been described.

The **restrict** keyword is added to the prototype for *statvfs*().

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/18 is applied, changing the description of ST_NOSUID from ''Does not support *setuid*()/*setgid*() semantics'' to ''Does not support the semantics of the ST_ISUID and ST_ISGID file mode bits''.

12911 **NAME**

12912 sys/time.h — time types

12913 **SYNOPSIS**

12914 XSI
```
#include <sys/time.h>
```
12915

12916 **DESCRIPTION**

12917 The **<sys/time.h>** header shall define the **timeval** structure that includes at least the following
12918 members:

12919 `time_t`	`tv_sec`	Seconds.
12920 `suseconds_t`	`tv_usec`	Microseconds.

12921 The **<sys/time.h>** header shall define the **itimerval** structure that includes at least the following
12922 members:

12923 `struct timeval it_interval`	Timer interval.
12924 `struct timeval it_value`	Current value.

12925 The **time_t** and **suseconds_t** types shall be defined as described in **<sys/types.h>**.

12926 The **fd_set** type shall be defined as described in **<sys/select.h>**.

12927 The **<sys/time.h>** header shall define the following values for the *which* argument of *getitimer*( )
12928 and *setitimer*( ):

12929 ITIMER_REAL	Decrements in real time.
12930 ITIMER_VIRTUAL	Decrements in process virtual time.
12931 ITIMER_PROF	Decrements both in process virtual time and when the system is running 12932 on behalf of the process.

12933 The following shall be defined as described in **<sys/select.h>**:

12934 *FD_CLR*( )
12935 *FD_ISSET*( )
12936 *FD_SET*( )
12937 *FD_ZERO*( )
12938 FD_SETSIZE

12939 The following shall be declared as functions and may also be defined as macros. Function
12940 prototypes shall be provided.

```
12941 int   getitimer(int, struct itimerval *);
12942 int   gettimeofday(struct timeval *restrict, void *restrict);
12943 int   select(int, fd_set *restrict, fd_set *restrict, fd_set *restrict,
12944           struct timeval *restrict);
12945 int   setitimer(int, const struct itimerval *restrict,
12946           struct itimerval *restrict);
12947 int   utimes(const char *, const struct timeval [2]); (LEGACY)
```

12948 Inclusion of the **<sys/time.h>** header may make visible all symbols from the **<sys/select.h>**
12949 header.

12950 **APPLICATION USAGE**

12951 None.

12952 **RATIONALE**

12953 None.

12954 **FUTURE DIRECTIONS**

12955 None.

12956 **SEE ALSO**

12957 **<sys/select.h>**, **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *getitimer*( ),
12958 *gettimeofday*( ), *select*( ), *setitimer*( )

12959 **CHANGE HISTORY**

12960 First released in Issue 4, Version 2.

12961 **Issue 5**

12962 The type of *tv_usec* is changed from **long** to **suseconds_t**.

12963 **Issue 6**

12964 The **restrict** keyword is added to the prototypes for *gettimeofday*( ), *select*( ), and *setitimer*( ).

12965 The note is added that inclusion of this header may also make symbols visible from
12966 **<sys/select.h>**.

12967 The *utimes*( ) function is marked LEGACY.

12968 **NAME**

12969 sys/timeb.h — additional definitions for date and time

12970 **SYNOPSIS**

12971 XSI
```
#include <sys/timeb.h>
```
12972

12973 **DESCRIPTION**

12974 The **<sys/timeb.h>** header shall define the **timeb** structure that includes at least the following
12975 members:

12976 `time_t`	`time`	The seconds portion of the current time.
12977 `unsigned short`	`millitm`	The milliseconds portion of the current time.
12978 `short`	`timezone`	The local timezone in minutes west of Greenwich.
12979 `short`	`dstflag`	TRUE if Daylight Savings Time is in effect.

12980 The **time_t** type shall be defined as described in **<sys/types.h>**.

12981 The following shall be declared as a function and may also be defined as a macro. A function
12982 prototype shall be provided.

12983
```
int   ftime(struct timeb *); (LEGACY)
```

12984 **APPLICATION USAGE**

12985 None.

12986 **RATIONALE**

12987 None.

12988 **FUTURE DIRECTIONS**

12989 None.

12990 **SEE ALSO**

12991 **<sys/types.h>**, **<time.h>**

12992 **CHANGE HISTORY**

12993 First released in Issue 4, Version 2.

12994 **Issue 6**

12995 The *ftime*( ) function is marked LEGACY.

12996 **NAME**

12997 sys/times.h — file access and modification times structure

12998 **SYNOPSIS**

12999 `#include <sys/times.h>`

13000 **DESCRIPTION**

13001 The **<sys/times.h>** header shall define the structure **tms**, which is returned by *times*() and
13002 includes at least the following members:

13003 `clock_t tms_utime` User CPU time.
13004 `clock_t tms_stime` System CPU time.
13005 `clock_t tms_cutime` User CPU time of terminated child processes.
13006 `clock_t tms_cstime` System CPU time of terminated child processes.

13007 The **clock_t** type shall be defined as described in **<sys/types.h>**.

13008 The following shall be declared as a function and may also be defined as a macro. A function
13009 prototype shall be provided.

13010 `clock_t times(struct tms *);`

13011 **APPLICATION USAGE**

13012 None.

13013 **RATIONALE**

13014 None.

13015 **FUTURE DIRECTIONS**

13016 None.

13017 **SEE ALSO**

13018 **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *times*()

13019 **CHANGE HISTORY**

13020 First released in Issue 1. Derived from Issue 1 of the SVID.

13021 **NAME**

13022 sys/types.h — data types

13023 **SYNOPSIS**

13024 `#include <sys/types.h>`

13025 **DESCRIPTION**

13026 The **<sys/types.h>** header shall include definitions for at least the following types:

13027		**blkcnt_t**	Used for file block counts.
13028		**blksize_t**	Used for block sizes.
13029	XSI	**clock_t**	Used for system times in clock ticks or CLOCKS_PER_SEC; see **<time.h>**.
13031	TMR	**clockid_t**	Used for clock ID type in the clock and timer functions.
13032		**dev_t**	Used for device IDs.
13033	XSI	**fsblkcnt_t**	Used for file system block counts.
13034	XSI	**fsfilcnt_t**	Used for file system file counts.
13035		**gid_t**	Used for group IDs.
13036	XSI	**id_t**	Used as a general identifier; can be used to contain at least a **pid_t**, **uid_t**, or **gid_t**.
13038		**ino_t**	Used for file serial numbers.
13039	XSI	**key_t**	Used for XSI interprocess communication.
13040		**mode_t**	Used for some file attributes.
13041		**nlink_t**	Used for link counts.
13042		**off_t**	Used for file sizes.
13043		**pid_t**	Used for process IDs and process group IDs.
13044	THR	**pthread_attr_t**	Used to identify a thread attribute object.
13045	BAR	**pthread_barrier_t**	Used to identify a barrier.
13046	BAR	**pthread_barrierattr_t**	Used to define a barrier attributes object.
13047	THR	**pthread_cond_t**	Used for condition variables.
13048	THR	**pthread_condattr_t**	Used to identify a condition attribute object.
13049	THR	**pthread_key_t**	Used for thread-specific data keys.
13050	THR	**pthread_mutex_t**	Used for mutexes.
13051	THR	**pthread_mutexattr_t**	Used to identify a mutex attribute object.
13052	THR	**pthread_once_t**	Used for dynamic package initialization.
13053	THR	**pthread_rwlock_t**	Used for read-write locks.
13054	THR	**pthread_rwlockattr_t**	Used for read-write lock attributes.
13055	SPI	**pthread_spinlock_t**	Used to identify a spin lock.
13056	THR	**pthread_t**	Used to identify a thread.

13057		**size_t**	Used for sizes of objects.
13058		**ssize_t**	Used for a count of bytes or an error indication.
13059	XSI	**suseconds_t**	Used for time in microseconds.
13060		**time_t**	Used for time in seconds.
13061	TMR	**timer_t**	Used for timer ID returned by *timer_create*( ).
13062	TRC	**trace_attr_t**	Used to identify a trace stream attributes object.
13063	TRC	**trace_event_id_t**	Used to identify a trace event type.
13064	TRC TEF	**trace_event_set_t**	Used to identify a trace event type set.
13065	TRC	**trace_id_t**	Used to identify a trace stream.
13066		**uid_t**	Used for user IDs.
13067	XSI	**useconds_t**	Used for time in microseconds.

13068 All of the types shall be defined as arithmetic types of an appropriate length, with the following
13069 exceptions:

13070 XSI **key_t**
13071 THR **pthread_attr_t**
13072 BAR **pthread_barrier_t**
13073 **pthread_barrierattr_t**
13074 THR **pthread_cond_t**
13075 **pthread_condattr_t**
13076 **pthread_key_t**
13077 **pthread_mutex_t**
13078 **pthread_mutexattr_t**
13079 **pthread_once_t**
13080 **pthread_rwlock_t**
13081 **pthread_rwlockattr_t**
13082 SPI **pthread_spinlock_t**
13083 THR **pthread_t**
13084 TRC **trace_attr_t**
13085 **trace_event_id_t**
13086 TRC TEF **trace_event_set_t**
13087 TRC **trace_id_t**
13088

13089 Additionally:

13090 - **mode_t** shall be an integer type.
13091 - **nlink_t**, **uid_t**, **gid_t**, and **id_t** shall be integer types.
13092 - **blkcnt_t** and **off_t** shall be signed integer types.
13093 XSI - **fsblkcnt_t**, **fsfilcnt_t**, and **ino_t** shall be defined as unsigned integer types.
13094 - **size_t** shall be an unsigned integer type.
13095 - **blksize_t**, **pid_t**, and **ssize_t** shall be signed integer types.
13096 - **time_t** and **clock_t** shall be integer or real-floating types.

13097 XSI The type **ssize_t** shall be capable of storing values at least in the range [–1, {SSIZE_MAX}]. The
13098 type **useconds_t** shall be an unsigned integer type capable of storing values at least in the range

[0, 1 000 000]. The type **suseconds_t** shall be a signed integer type capable of storing values at least in the range [–1, 1 000 000].

The implementation shall support one or more programming environments in which the widths of **blksize_t**, **pid_t**, **size_t**, **ssize_t**, **suseconds_t**, and **useconds_t** are no greater than the width of type **long**. The names of these programming environments can be obtained using the *confstr*( ) function or the *getconf* utility.

There are no defined comparison or assignment operators for the following types:

THR **pthread_attr_t**
BAR **pthread_barrier_t**
pthread_barrierattr_t
THR **pthread_cond_t**
pthread_condattr_t
pthread_mutex_t
pthread_mutexattr_t
pthread_rwlock_t
pthread_rwlockattr_t
SPI **pthread_spinlock_t**
TRC **trace_attr_t**

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<time.h>, the System Interfaces volume of IEEE Std 1003.1-2001, *confstr*( ), the Shell and Utilities volume of IEEE Std 1003.1-2001, *getconf*

CHANGE HISTORY

First released in Issue 1. Derived from Issue 1 of the SVID.

Issue 5

The **clockid_t** and **timer_t** types are defined for alignment with the POSIX Realtime Extension.

The types **blkcnt_t**, **blksize_t**, **fsblkcnt_t**, **fsfilcnt_t**, and **suseconds_t** are added.

Large File System extensions are added.

Updated for alignment with the POSIX Threads Extension.

Issue 6

The **pthread_barrier_t**, **pthread_barrierattr_t**, and **pthread_spinlock_t** types are added for alignment with IEEE Std 1003.1j-2000.

The margin code is changed from XSI to THR for the **pthread_rwlock_t** and **pthread_rwlockattr_t** types as Read-Write Locks have been absorbed into the POSIX Threads option. The threads types are marked THR.

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/26 is applied, adding **pthread_t** to the list of types that are not required to be arithmetic types, thus allowing **pthread_t** to be defined as a structure. 2

NAME

sys/uio.h — definitions for vector I/O operations

SYNOPSIS

XSI
```
#include <sys/uio.h>
```

DESCRIPTION

The **<sys/uio.h>** header shall define the **iovec** structure that includes at least the following members:

`void *iov_base`	Base address of a memory region for input or output.
`size_t iov_len`	The size of the memory pointed to by *iov_base*.

The **<sys/uio.h>** header uses the **iovec** structure for scatter/gather I/O.

The **ssize_t** and **size_t** types shall be defined as described in **<sys/types.h>**.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
ssize_t readv(int, const struct iovec *, int);
ssize_t writev(int, const struct iovec *, int);
```

APPLICATION USAGE

The implementation can put a limit on the number of scatter/gather elements which can be processed in one call. The symbol {IOV_MAX} defined in **<limits.h>** should always be used to learn about the limits instead of assuming a fixed value.

RATIONALE

Traditionally, the maximum number of scatter/gather elements the system can process in one call were described by the symbolic value {UIO_MAXIOV}. In IEEE Std 1003.1-2001 this value is replaced by the constant {IOV_MAX} which can be found in **<limits.h>**.

FUTURE DIRECTIONS

None.

SEE ALSO

<limits.h>, **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *read*( ), *write*( )

CHANGE HISTORY

First released in Issue 4, Version 2.

Issue 6

Text referring to scatter/gather I/O is added to the DESCRIPTION.

13175 **NAME**

13176 sys/un.h — definitions for UNIX domain sockets

13177 **SYNOPSIS**

13178 `#include <sys/un.h>`

13179 **DESCRIPTION**

13180 The **<sys/un.h>** header shall define the **sockaddr_un** structure that includes at least the
13181 following members:

13182 `sa_family_t sun_family` Address family.
13183 `char sun_path[]` Socket pathname.

13184 The **sockaddr_un** structure is used to store addresses for UNIX domain sockets. Values of this
13185 type shall be cast by applications to **struct sockaddr** for use with socket functions.

13186 The **sa_family_t** type shall be defined as described in **<sys/socket.h>**.

13187 **APPLICATION USAGE**

13188 The size of *sun_path* has intentionally been left undefined. This is because different
13189 implementations use different sizes. For example, 4.3 BSD uses a size of 108, and 4.4 BSD uses a
13190 size of 104. Since most implementations originate from BSD versions, the size is typically in the
13191 range 92 to 108.

13192 Applications should not assume a particular length for *sun_path* or assume that it can hold
13193 {_POSIX_PATH_MAX} characters (255).

13194 **RATIONALE**

13195 None.

13196 **FUTURE DIRECTIONS**

13197 None.

13198 **SEE ALSO**

13199 **<sys/socket.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *bind*( ), *socket*( ),
13200 *socketpair*( )

13201 **CHANGE HISTORY**

13202 First released in Issue 6. Derived from the XNS, Issue 5.2 specification.

NAME

sys/utsname.h — system name structure

SYNOPSIS

```
#include <sys/utsname.h>
```

DESCRIPTION

The **<sys/utsname.h>** header shall define the structure **utsname** which shall include at least the following members:

`char`	`sysname[]`	Name of this implementation of the operating system.
`char`	`nodename[]`	Name of this node within the communications network to which this node is attached, if any. 2 2
`char`	`release[]`	Current release level of this implementation.
`char`	`version[]`	Current version level of this release.
`char`	`machine[]`	Name of the hardware type on which the system is running.

The character arrays are of unspecified size, but the data stored in them shall be terminated by a null byte.

The following shall be declared as a function and may also be defined as a macro:

```
int uname(struct utsname *);
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *uname*( )

CHANGE HISTORY

First released in Issue 1. Derived from Issue 1 of the SVID.

Issue 6 2

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/27 is applied, changing the description of *nodename* within the **utsname** structure from ‘‘an implementation-defined communications network’’ to ‘‘the communications network to which this node is attached, if any’’. 2 2 2 2

13234 **NAME**

13235 sys/wait.h — declarations for waiting

13236 **SYNOPSIS**

13237 `#include <sys/wait.h>`

13238 **DESCRIPTION**

13239 The **<sys/wait.h>** header shall define the following symbolic constants for use with *waitpid*( ):

13240 WNOHANG Do not hang if no status is available; return immediately.

13241 WUNTRACED Report status of stopped child process.

13242 The **<sys/wait.h>** header shall define the following macros for analysis of process status values:

13243 WEXITSTATUS Return exit status.

13244 XSI WIFCONTINUED True if child has been continued.

13245 WIFEXITED True if child exited normally.

13246 WIFSIGNALED True if child exited due to uncaught signal.

13247 WIFSTOPPED True if child is currently stopped.

13248 WSTOPSIG Return signal number that caused process to stop.

13249 WTERMSIG Return signal number that caused process to terminate.

13250 XSI The following symbolic constants shall be defined as possible values for the *options* argument to
13251 *waitid*( ):

13252 WEXITED Wait for processes that have exited.

13253 WSTOPPED Status is returned for any child that has stopped upon receipt of a signal.

13254 WCONTINUED Status is returned for any child that was stopped and has been continued.

13255 WNOHANG Return immediately if there are no children to wait for.

13256 WNOWAIT Keep the process whose status is returned in *infop* in a waitable state.

13257 The type **idtype_t** shall be defined as an enumeration type whose possible values shall include
13258 at least the following:

13259 P_ALL
13260 P_PID
13261 P_PGID

13262

13263 The **id_t** and **pid_t** types shall be defined as described in **<sys/types.h>**.

13264 XSI The **siginfo_t** type shall be defined as described in **<signal.h>**.

13265 The **rusage** structure shall be defined as described in **<sys/resource.h>**.

13266 Inclusion of the **<sys/wait.h>** header may also make visible all symbols from **<signal.h>** and
13267 **<sys/resource.h>**.

13268 The following shall be declared as functions and may also be defined as macros. Function
13269 prototypes shall be provided.

13270 `pid_t  wait(int *);`
13271 XSI `int    waitid(idtype_t, id_t, siginfo_t *, int);`
13272 `pid_t  waitpid(pid_t, int *, int);`

13273 **APPLICATION USAGE**

13274 None.

13275 **RATIONALE**

13276 None.

13277 **FUTURE DIRECTIONS**

13278 None.

13279 **SEE ALSO**

13280 **<signal.h>**, **<sys/resource.h>**, **<sys/types.h>**, the System Interfaces volume of
13281 IEEE Std 1003.1-2001, *wait*( ), *waitid*( )

13282 **CHANGE HISTORY**

13283 First released in Issue 3.

13284 Included for alignment with the POSIX.1-1988 standard.

13285 **Issue 6**

13286 The *wait3*( ) function is removed.

13287 **NAME**

13288 syslog.h — definitions for system error logging

13289 **SYNOPSIS**

13290 XSI
```
#include <syslog.h>
```
13291

13292 **DESCRIPTION**

13293 The **<syslog.h>** header shall define the following symbolic constants, zero or more of which may
13294 be OR'ed together to form the *logopt* option of *openlog*( ):

13295 LOG_PID Log the process ID with each message.

13296 LOG_CONS Log to the system console on error.

13297 LOG_NDELAY Connect to syslog daemon immediately.

13298 LOG_ODELAY Delay open until *syslog*( ) is called.

13299 LOG_NOWAIT Do not wait for child processes.

13300 The following symbolic constants shall be defined as possible values of the *facility* argument to
13301 *openlog*( ):

13302 LOG_KERN Reserved for message generated by the system.

13303 LOG_USER Message generated by a process.

13304 LOG_MAIL Reserved for message generated by mail system.

13305 LOG_NEWS Reserved for message generated by news system.

13306 LOG_UUCP Reserved for message generated by UUCP system.

13307 LOG_DAEMON Reserved for message generated by system daemon.

13308 LOG_AUTH Reserved for message generated by authorization daemon.

13309 LOG_CRON Reserved for message generated by clock daemon.

13310 LOG_LPR Reserved for message generated by printer system.

13311 LOG_LOCAL0 Reserved for local use.

13312 LOG_LOCAL1 Reserved for local use.

13313 LOG_LOCAL2 Reserved for local use.

13314 LOG_LOCAL3 Reserved for local use.

13315 LOG_LOCAL4 Reserved for local use.

13316 LOG_LOCAL5 Reserved for local use.

13317 LOG_LOCAL6 Reserved for local use.

13318 LOG_LOCAL7 Reserved for local use.

13319 The following shall be declared as macros for constructing the *maskpri* argument to *setlogmask*( ).
13320 The following macros expand to an expression of type **int** when the argument *pri* is an
13321 expression of type **int**:

13322 LOG_MASK(*pri*) A mask for priority *pri*.

13323 The following constants shall be defined as possible values for the *priority* argument of *syslog*( ):

LOG_EMERG	A panic condition was reported to all processes.
LOG_ALERT	A condition that should be corrected immediately.
LOG_CRIT	A critical condition.
LOG_ERR	An error message.
LOG_WARNING	A warning message.
LOG_NOTICE	A condition requiring special handling.
LOG_INFO	A general information message.
LOG_DEBUG	A message useful for debugging programs.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
void  closelog(void);
void  openlog(const char *, int, int);
int   setlogmask(int);
void  syslog(int, const char *, ...);
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *closelog*( )

CHANGE HISTORY

First released in Issue 4, Version 2.

Issue 5

Moved from X/Open UNIX to BASE.

NAME

tar.h — extended tar definitions

SYNOPSIS

```
#include <tar.h>
```

DESCRIPTION

The **<tar.h>** header shall define header block definitions as follows.

General definitions:

Name	Description	Value
TMAGIC	"ustar"	ustar plus null byte.
TMAGLEN	6	Length of the above.
TVERSION	"00"	00 without a null byte.
TVERSLEN	2	Length of the above.

Typeflag field definitions:

Name	Description	Value
REGTYPE	'0'	Regular file.
AREGTYPE	'\0'	Regular file.
LNKTYPE	'1'	Link.
SYMTYPE	'2'	Symbolic link.
CHRTYPE	'3'	Character special.
BLKTYPE	'4'	Block special.
DIRTYPE	'5'	Directory.
FIFOTYPE	'6'	FIFO special.
CONTTYPE	'7'	Reserved.

Mode field bit definitions (octal):

Name	Description	Value
TSUID	04000	Set UID on execution.
TSGID	02000	Set GID on execution.
XSI TSVTX	01000	On directories, restricted deletion flag.
TUREAD	00400	Read by owner.
TUWRITE	00200	Write by owner special.
TUEXEC	00100	Execute/search by owner.
TGREAD	00040	Read by group.
TGWRITE	00020	Write by group.
TGEXEC	00010	Execute/search by group.
TOREAD	00004	Read by other.
TOWRITE	00002	Write by other.
TOEXEC	00001	Execute/search by other.

13390 **APPLICATION USAGE**

13391 None.

13392 **RATIONALE**

13393 None.

13394 **FUTURE DIRECTIONS**

13395 None.

13396 **SEE ALSO**

13397 The Shell and Utilities volume of IEEE Std 1003.1-2001, *pax*

13398 **CHANGE HISTORY**

13399 First released in Issue 3. Derived from the POSIX.1-1988 standard.

13400 **Issue 6**

13401 The SEE ALSO section now refers to *pax* since the Shell and Utilities volume of
13402 IEEE Std 1003.1-2001 no longer contains the *tar* utility.

13403 **NAME**

13404 termios.h — define values for termios

13405 **SYNOPSIS**

13406 `#include <termios.h>`

13407 **DESCRIPTION**

13408 The **<termios.h>** header contains the definitions used by the terminal I/O interfaces (see
13409 Chapter 11 (on page 187) for the structures and names defined).

13410 **The termios Structure**

13411 The following data types shall be defined through **typedef**:

13412 **cc_t** Used for terminal special characters.

13413 **speed_t** Used for terminal baud rates.

13414 **tcflag_t** Used for terminal modes.

13415 The above types shall be all unsigned integer types.

13416 The implementation shall support one or more programming environments in which the widths
13417 of **cc_t**, **speed_t**, and **tcflag_t** are no greater than the width of type **long**. The names of these
13418 programming environments can be obtained using the *confstr*( ) function or the *getconf* utility.

13419 The **termios** structure shall be defined, and shall include at least the following members:

13420 `tcflag_t c_iflag` Input modes.
13421 `tcflag_t c_oflag` Output modes.
13422 `tcflag_t c_cflag` Control modes.
13423 `tcflag_t c_lflag` Local modes.
13424 `cc_t c_cc[NCCS]` Control characters.

13425 A definition shall be provided for:

13426 NCCS Size of the array *c_cc* for control characters.

13427 The following subscript names for the array *c_cc* shall be defined:

13428
13429
13430

Subscript Usage		
Canonical Mode	**Non-Canonical Mode**	**Description**
13431 VEOF		EOF character.
13432 VEOL		EOL character.
13433 VERASE		ERASE character.
13434 VINTR	VINTR	INTR character.
13435 VKILL		KILL character.
13436	VMIN	MIN value.
13437 VQUIT	VQUIT	QUIT character.
13438 VSTART	VSTART	START character.
13439 VSTOP	VSTOP	STOP character.
13440 VSUSP	VSUSP	SUSP character.
13441	VTIME	TIME value.

13442 The subscript values shall be unique, except that the VMIN and VTIME subscripts may have the
13443 same values as the VEOF and VEOL subscripts, respectively.

13444 The following flags shall be provided.

13445 **Input Modes**

13446 The *c_iflag* field describes the basic terminal input control:

13447	BRKINT	Signal interrupt on break.
13448	ICRNL	Map CR to NL on input.
13449	IGNBRK	Ignore break condition.
13450	IGNCR	Ignore CR.
13451	IGNPAR	Ignore characters with parity errors.
13452	INLCR	Map NL to CR on input.
13453	INPCK	Enable input parity check.
13454	ISTRIP	Strip character.
13455 XSI	IXANY	Enable any character to restart output.
13456	IXOFF	Enable start/stop input control.
13457	IXON	Enable start/stop output control.
13458	PARMRK	Mark parity errors.

13459 **Output Modes**

13460 The *c_oflag* field specifies the system treatment of output:

13461	OPOST	Post-process output.	
13462 XSI	ONLCR	Map NL to CR-NL on output.	
13463	OCRNL	Map CR to NL on output.	
13464	ONOCR	No CR output at column 0.	
13465	ONLRET	NL performs CR function.	
13466	OFILL	Use fill characters for delay.	
13467	NLDLY	Select newline delays:	
13468		NL0	Newline type 0.
13469		NL1	Newline type 1.
13470	CRDLY	Select carriage-return delays:	
13471		CR0	Carriage-return delay type 0.
13472		CR1	Carriage-return delay type 1.
13473		CR2	Carriage-return delay type 2.
13474		CR3	Carriage-return delay type 3.
13475	TABDLY	Select horizontal-tab delays:	
13476		TAB0	Horizontal-tab delay type 0.
13477		TAB1	Horizontal-tab delay type 1.
13478		TAB2	Horizontal-tab delay type 2.

	TAB3	Expand tabs to spaces.
BSDLY	Select backspace delays:	
	BS0	Backspace-delay type 0.
	BS1	Backspace-delay type 1.
VTDLY	Select vertical-tab delays:	
	VT0	Vertical-tab delay type 0.
	VT1	Vertical-tab delay type 1.
FFDLY	Select form-feed delays:	
	FF0	Form-feed delay type 0.
	FF1	Form-feed delay type 1.

Baud Rate Selection

The input and output baud rates are stored in the **termios** structure. These are the valid values for objects of type **speed_t**. The following values shall be defined, but not all baud rates need be supported by the underlying hardware.

B0	Hang up
B50	50 baud
B75	75 baud
B110	110 baud
B134	134.5 baud
B150	150 baud
B200	200 baud
B300	300 baud
B600	600 baud
B1200	1 200 baud
B1800	1 800 baud
B2400	2 400 baud
B4800	4 800 baud
B9600	9 600 baud
B19200	19 200 baud
B38400	38 400 baud

13509 **Control Modes**

13510 The *c_cflag* field describes the hardware control of the terminal; not all values specified are
13511 required to be supported by the underlying hardware:

13512 CSIZE Character size:

13513 CS5 5 bits

13514 CS6 6 bits

13515 CS7 7 bits

13516 CS8 8 bits

13517 CSTOPB Send two stop bits, else one.

13518 CREAD Enable receiver.

13519 PARENB Parity enable.

13520 PARODD Odd parity, else even.

13521 HUPCL Hang up on last close.

13522 CLOCAL Ignore modem status lines.

13523 The implementation shall support the functionality associated with the symbols CS7, CS8,
13524 CSTOPB, PARODD, and PARENB.

13525 **Local Modes**

13526 The *c_lflag* field of the argument structure is used to control various terminal functions:

13527 ECHO Enable echo.

13528 ECHOE Echo erase character as error-correcting backspace.

13529 ECHOK Echo KILL.

13530 ECHONL Echo NL.

13531 ICANON Canonical input (erase and kill processing).

13532 IEXTEN Enable extended input character processing.

13533 ISIG Enable signals.

13534 NOFLSH Disable flush after interrupt or quit.

13535 TOSTOP Send SIGTTOU for background output.

13536 **Attribute Selection**

13537 The following symbolic constants for use with *tcsetattr*( ) are defined:

13538 TCSANOW Change attributes immediately.

13539 TCSADRAIN Change attributes when output has drained.

13540 TCSAFLUSH Change attributes when output has drained; also flush pending input.

Line Control

The following symbolic constants for use with *tcflush*( ) shall be defined:

TCIFLUSH	Flush pending input.
TCIOFLUSH	Flush both pending input and untransmitted output.
TCOFLUSH	Flush untransmitted output.

The following symbolic constants for use with *tcflow*( ) shall be defined:

TCIOFF	Transmit a STOP character, intended to suspend input data.
TCION	Transmit a START character, intended to restart input data.
TCOOFF	Suspend output.
TCOON	Restart output.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
speed_t cfgetispeed(const struct termios *);
speed_t cfgetospeed(const struct termios *);
int     cfsetispeed(struct termios *, speed_t);
int     cfsetospeed(struct termios *, speed_t);
int     tcdrain(int);
int     tcflow(int, int);
int     tcflush(int, int);
int     tcgetattr(int, struct termios *);
pid_t   tcgetsid(int);
int     tcsendbreak(int, int);
int     tcsetattr(int, int, const struct termios *);
```

XSI

APPLICATION USAGE

The following names are reserved for XSI-conformant systems to use as an extension to the above; therefore strictly conforming applications shall not use them:

CBAUD	EXTB	VDSUSP
DEFECHO	FLUSHO	VLNEXT
ECHOCTL	LOBLK	VREPRINT
ECHOKE	PENDIN	VSTATUS
ECHOPRT	SWTCH	VWERASE
EXTA	VDISCARD	

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *cfgetispeed*( ), *cfgetospeed*( ), *cfsetispeed*( ), *cfsetospeed*( ), *confstr*( ), *tcdrain*( ), *tcflow*( ), *tcflush*( ), *tcgetattr*( ), *tcgetsid*( ), *tcsendbreak*( ), *tcsetattr*( ), the Shell and Utilities volume of IEEE Std 1003.1-2001, *getconf*, Chapter 11 (on page 187)

13581 **CHANGE HISTORY**

13582 First released in Issue 3.

13583 Included for alignment with the ISO POSIX-1 standard.

13584 **Issue 6**

13585 The LEGACY symbols IUCLC, OLCUC, and XCASE are removed.

13586 FIPS 151-2 requirements for the symbols CS7, CS8, CSTOPB, PARODD, and PARENB are
13587 reaffirmed.

13588 IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/19 is applied, changing ECHOK to 1
13589 ECHOKE in the APPLICATION USAGE section. 1

13590 **NAME**

13591 tgmath.h — type-generic macros

13592 **SYNOPSIS**

13593 `#include <tgmath.h>`

13594 **DESCRIPTION**

13595 CX The functionality described on this reference page is aligned with the ISO C standard. Any
13596 conflict between the requirements described here and the ISO C standard is unintentional. This
13597 volume of IEEE Std 1003.1-2001 defers to the ISO C standard.

13598 The **<tgmath.h>** header shall include the headers **<math.h>** and **<complex.h>** and shall define
13599 several type-generic macros.

13600 Of the functions contained within the **<math.h>** and **<complex.h>** headers without an *f* (**float**) or
13601 *l* (**long double**) suffix, several have one or more parameters whose corresponding real type is
13602 **double**. For each such function, except *modf*( ), there shall be a corresponding type-generic
13603 macro. The parameters whose corresponding real type is **double** in the function synopsis are
13604 generic parameters. Use of the macro invokes a function whose corresponding real type and
13605 type domain are determined by the arguments for the generic parameters.

13606 Use of the macro invokes a function whose generic parameters have the corresponding real type
13607 determined as follows:

13608 • First, if any argument for generic parameters has type **long double**, the type determined is
13609 **long double**.

13610 • Otherwise, if any argument for generic parameters has type **double** or is of integer type, the
13611 type determined is **double**.

13612 • Otherwise, the type determined is **float**.

13613 For each unsuffixed function in the **<math.h>** header for which there is a function in the
13614 **<complex.h>** header with the same name except for a *c* prefix, the corresponding type-generic
13615 macro (for both functions) has the same name as the function in the **<math.h>** header. The
13616 corresponding type-generic macro for *fabs*( ) and *cabs*( ) is *fabs*( ).

13617 13618

<math.h> Function	**<complex.h> Function**	**Type-Generic Macro**
13619 *acos*( )	*cacos*( )	*acos*( )
13620 *asin*( )	*casin*( )	*asin*( )
13621 *atan*( )	*catan*( )	*atan*( )
13622 *acosh*( )	*cacosh*( )	*acosh*( )
13623 *asinh*( )	*casinh*( )	*asinh*( )
13624 *atanh*( )	*catanh*( )	*atanh*( )
13625 *cos*( )	*ccos*( )	*cos*( )
13626 *sin*( )	*csin*( )	*sin*( )
13627 *tan*( )	*ctan*( )	*tan*( )
13628 *cosh*( )	*ccosh*( )	*cosh*( )
13629 *sinh*( )	*csinh*( )	*sinh*( )
13630 *tanh*( )	*ctanh*( )	*tanh*( )
13631 *exp*( )	*cexp*( )	*exp*( )
13632 *log*( )	*clog*( )	*log*( )
13633 *pow*( )	*cpow*( )	*pow*( )
13634 *sqrt*( )	*csqrt*( )	*sqrt*( )
13635 *fabs*( )	*cabs*( )	*fabs*( )

If at least one argument for a generic parameter is complex, then use of the macro invokes a complex function; otherwise, use of the macro invokes a real function.

For each unsuffixed function in the **<math.h>** header without a *c*-prefixed counterpart in the **<complex.h>** header, the corresponding type-generic macro has the same name as the function. These type-generic macros are:

atan2( )	*fma*( )	*llround*( )	*remainder*( )
cbrt( )	*fmax*( )	*log10*( )	*remquo*( )
ceil( )	*fmin*( )	*log1p*( )	*rint*( )
copysign( )	*fmod*( )	*log2*( )	*round*( )
erf( )	*frexp*( )	*logb*( )	*scalbn*( )
erfc( )	*hypot*( )	*lrint*( )	*scalbln*( )
exp2( )	*ilogb*( )	*lround*( )	*tgamma*( )
expm1( )	*ldexp*( )	*nearbyint*( )	*trunc*( )
fdim( )	*lgamma*( )	*nextafter*( )	
floor( )	*llrint*( )	*nexttoward*( )	

If all arguments for generic parameters are real, then use of the macro invokes a real function; otherwise, use of the macro results in undefined behavior.

For each unsuffixed function in the **<complex.h>** header that is not a *c*-prefixed counterpart to a function in the **<math.h>** header, the corresponding type-generic macro has the same name as the function. These type-generic macros are:

carg( )
cimag( )
conj( )
cproj( )
creal( )

Use of the macro with any real or complex argument invokes a complex function.

APPLICATION USAGE

With the declarations:

```
#include <tgmath.h>
int n;
float f;
double d;
long double ld;
float complex fc;
double complex dc;
long double complex ldc;
```

functions invoked by use of type-generic macros are shown in the following table:

Macro	Use Invokes
exp(*n*)	*exp*(*n*), the function
acosh(*f*)	*acoshf*(*f*)
sin(*d*)	*sin*(*d*), the function
atan(*ld*)	*atanl*(*ld*)

Macro	Use Invokes
log(*fc*)	*clogf*(*fc*)
sqrt(*dc*)	*csqrt*(*dc*)
pow(*ldc*,*f*)	*cpowl*(*ldc*, *f*)
remainder(*n*,*n*)	*remainder*(*n*, *n*), the function
nextafter(*d*,*f*)	*nextafter*(*d*, *f*), the function
nexttoward(*f*,*ld*)	*nexttowardf*(*f*, *ld*)
copysign(*n*,*ld*)	*copysignl*(*n*, *ld*)
ceil(*fc*)	Undefined behavior
rint(*dc*)	Undefined behavior
fmax(*ldc*,*ld*)	Undefined behavior
carg(*n*)	*carg*(*n*), the function
cproj(*f*)	*cprojf*(*f*)
creal(*d*)	*creal*(*d*), the function
cimag(*ld*)	*cimagl*(*ld*)
cabs(*fc*)	*cabsf*(*fc*)
carg(*dc*)	*carg*(*dc*), the function
cproj(*ldc*)	*cprojl*(*ldc*)

RATIONALE

Type-generic macros allow calling a function whose type is determined by the argument type, as is the case for C operators such as `'+'` and `'*'`. For example, with a type-generic *cos*( ) macro, the expression *cos*((**float**)*x*) will have type **float**. This feature enables writing more portably efficient code and alleviates need for awkward casting and suffixing in the process of porting or adjusting precision. Generic math functions are a widely appreciated feature of Fortran.

The only arguments that affect the type resolution are the arguments corresponding to the parameters that have type **double** in the synopsis. Hence the type of a type-generic call to *nexttoward*( ), whose second parameter is **long double** in the synopsis, is determined solely by the type of the first argument.

The term ‘‘type-generic’’ was chosen over the proposed alternatives of intrinsic and overloading. The term is more specific than intrinsic, which already is widely used with a more general meaning, and reflects a closer match to Fortran’s generic functions than to C++ overloading.

The macros are placed in their own header in order not to silently break old programs that include the **<math.h>** header; for example, with:

```
printf ("%e", sin(x))
```

modf(**double**, **double ***) is excluded because no way was seen to make it safe without complicating the type resolution.

The implementation might, as an extension, endow appropriate ones of the macros that IEEE Std 1003.1-2001 specifies only for real arguments with the ability to invoke the complex functions.

IEEE Std 1003.1-2001 does not prescribe any particular implementation mechanism for generic macros. It could be implemented simply with built-in macros. The generic macro for *sqrt*( ), for example, could be implemented with:

```
#undef sqrt
#define sqrt(x) __BUILTIN_GENERIC_sqrt(x)
```

Generic macros are designed for a useful level of consistency with C++ overloaded math functions.

The great majority of existing C programs are expected to be unaffected when the **<tgmath.h>** header is included instead of the **<math.h>** or **<complex.h>** headers. Generic macros are similar to the ISO / IEC 9899: 1999 standard library masking macros, though the semantic types of return values differ.

The ability to overload on integer as well as floating types would have been useful for some functions; for example, *copysign*( ). Overloading with different numbers of arguments would have allowed reusing names; for example, *remainder*( ) for *remquo*( ). However, these facilities would have complicated the specification; and their natural consistent use, such as for a floating *abs*( ) or a two-argument *atan*( ), would have introduced further inconsistencies with the ISO / IEC 9899: 1999 standard for insufficient benefit.

The ISO C standard in no way limits the implementation's options for efficiency, including inlining library functions.

FUTURE DIRECTIONS

None.

SEE ALSO

<math.h>, **<complex.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *cabs*( ), *fabs*( ), *modf*( )

CHANGE HISTORY

First released in Issue 6. Included for alignment with the ISO / IEC 9899: 1999 standard.

NAME

time.h — time types

SYNOPSIS

```
#include <time.h>
```

DESCRIPTION

CX Some of the functionality described on this reference page extends the ISO C standard. Applications shall define the appropriate feature test macro (see the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.2, The Compilation Environment) to enable the visibility of these symbols in this header.

The **<time.h>** header shall declare the structure **tm**, which shall include at least the following members:

`int`	`tm_sec`	Seconds [0,60].
`int`	`tm_min`	Minutes [0,59].
`int`	`tm_hour`	Hour [0,23].
`int`	`tm_mday`	Day of month [1,31].
`int`	`tm_mon`	Month of year [0,11].
`int`	`tm_year`	Years since 1900.
`int`	`tm_wday`	Day of week [0,6] (Sunday =0).
`int`	`tm_yday`	Day of year [0,365].
`int`	`tm_isdst`	Daylight Savings flag.

The value of *tm_isdst* shall be positive if Daylight Savings Time is in effect, 0 if Daylight Savings Time is not in effect, and negative if the information is not available.

The **<time.h>** header shall define the following symbolic names:

NULL Null pointer constant.

CLOCKS_PER_SEC A number used to convert the value returned by the *clock*( ) function into seconds.

TMR|CPT CLOCK_PROCESS_CPUTIME_ID
The identifier of the CPU-time clock associated with the process making a *clock*( ) or *timer**( ) function call.

TMR|TCT CLOCK_THREAD_CPUTIME_ID
The identifier of the CPU-time clock associated with the thread making a *clock*( ) or *timer**( ) function call.

TMR The **<time.h>** header shall declare the structure **timespec**, which has at least the following members:

`time_t`	`tv_sec`	Seconds.
`long`	`tv_nsec`	Nanoseconds.

The **<time.h>** header shall also declare the **itimerspec** structure, which has at least the following members:

`struct timespec`	`it_interval`	Timer period.
`struct timespec`	`it_value`	Timer expiration.

The following manifest constants shall be defined:

CLOCK_REALTIME The identifier of the system-wide realtime clock.

TIMER_ABSTIME Flag indicating time is absolute. For functions taking timer objects, this refers to the clock associated with the timer.

13789 MON CLOCK_MONOTONIC
13790 The identifier for the system-wide monotonic clock, which is defined as a
13791 clock whose value cannot be set via *clock_settime*() and which cannot
13792 have backward clock jumps. The maximum possible clock jump shall be
13793 implementation-defined.

13794 TMR The **clock_t**, **size_t**, **time_t**, **clockid_t**, and **timer_t** types shall be defined as described in
13795 **<sys/types.h>**.

13796 XSI Although the value of CLOCKS_PER_SEC is required to be 1 million on all XSI-conformant
13797 systems, it may be variable on other systems, and it should not be assumed that
13798 CLOCKS_PER_SEC is a compile-time constant.

13799 XSI The **<time.h>** header shall provide a declaration for *getdate_err*.

13800 The following shall be declared as functions and may also be defined as macros. Function
13801 prototypes shall be provided.

```
13802       char      *asctime(const struct tm *);
13803 TSF   char      *asctime_r(const struct tm *restrict, char *restrict);
13804       clock_t    clock(void);
13805 CPT   int        clock_getcpuclockid(pid_t, clockid_t *);
13806 TMR   int        clock_getres(clockid_t, struct timespec *);
13807       int        clock_gettime(clockid_t, struct timespec *);
13808 CS    int        clock_nanosleep(clockid_t, int, const struct timespec *,
13809                      struct timespec *);
13810 TMR   int        clock_settime(clockid_t, const struct timespec *);
13811       char      *ctime(const time_t *);
13812 TSF   char      *ctime_r(const time_t *, char *);
13813       double     difftime(time_t, time_t);
13814 XSI   struct tm *getdate(const char *);
13815       struct tm *gmtime(const time_t *);
13816 TSF   struct tm *gmtime_r(const time_t *restrict, struct tm *restrict);
13817       struct tm *localtime(const time_t *);
13818 TSF   struct tm *localtime_r(const time_t *restrict, struct tm *restrict);
13819       time_t     mktime(struct tm *);
13820 TMR   int        nanosleep(const struct timespec *, struct timespec *);
13821       size_t     strftime(char *restrict, size_t, const char *restrict,
13822                  const struct tm *restrict);
13823 XSI   char      *strptime(const char *restrict, const char *restrict,
13824                      struct tm *restrict);
13825       time_t     time(time_t *);
13826 TMR   int        timer_create(clockid_t, struct sigevent *restrict,
13827                      timer_t *restrict);
13828       int        timer_delete(timer_t);
13829       int        timer_gettime(timer_t, struct itimerspec *);
13830       int        timer_getoverrun(timer_t);
13831       int        timer_settime(timer_t, int, const struct itimerspec *restrict,
13832                      struct itimerspec *restrict);
13833 CX    void       tzset(void);
13834
```

The following shall be declared as variables:

XSI
```
extern int    daylight;
extern long   timezone;
```
CX
```
extern char  *tzname[];
```

CX Inclusion of the **<time.h>** header may make visible all symbols from the **<signal.h>** header.

APPLICATION USAGE

The range [0,60] for *tm_sec* allows for the occasional leap second.

tm_year is a signed value; therefore, years before 1900 may be represented.

To obtain the number of clock ticks per second returned by the *times*( ) function, applications should call *sysconf*(_SC_CLK_TCK).

RATIONALE

The range [0,60] seconds allows for positive or negative leap seconds. The formal definition of UTC does not permit double leap seconds, so all mention of double leap seconds has been removed, and the range shortened from the former [0,61] seconds seen in previous versions of POSIX.

FUTURE DIRECTIONS

None.

SEE ALSO

<signal.h>, **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *asctime*( ), *clock*( ), *clock_getcpuclockid*( ), *clock_getres*( ), *clock_nanosleep*( ), *ctime*( ), *difftime*( ), *getdate*( ), *gmtime*( ), *localtime*( ), *mktime*( ), *nanosleep*( ), *strftime*( ), *strptime*( ), *sysconf*( ), *time*( ), *timer_create*( ), *timer_delete*( ), *timer_getoverrun*( ), *tzname*, *tzset*( ), *utime*( )

CHANGE HISTORY

First released in Issue 1. Derived from Issue 1 of the SVID.

Issue 5

The DESCRIPTION is updated for alignment with the POSIX Realtime Extension and the POSIX Threads Extension.

Issue 6

The Open Group Corrigendum U035/6 is applied. In the DESCRIPTION, the types **clockid_t** and **timer_t** have been described.

The following changes are made for alignment with the ISO POSIX-1: 1996 standard:

- The POSIX timer-related functions are marked as part of the Timers option.

The symbolic name CLK_TCK is removed. Application usage is added describing how its equivalent functionality can be obtained using *sysconf*( ).

The *clock_getcpuclockid*( ) function and manifest constants CLOCK_PROCESS_CPUTIME_ID and CLOCK_THREAD_CPUTIME_ID are added for alignment with IEEE Std 1003.1d-1999.

The manifest constant CLOCK_MONOTONIC and the *clock_nanosleep*( ) function are added for alignment with IEEE Std 1003.1j-2000.

The following changes are made for alignment with the ISO/IEC 9899: 1999 standard:

- The range for seconds is changed from [0,61] to [0,60].
- The **restrict** keyword is added to the prototypes for *asctime_r*( ), *gmtime_r*( ), *localtime_r*( ), *strftime*( ), *strptime*( ), *timer_create*( ), and *timer_settime*( ).

IEEE PASC Interpretation 1003.1 #84 is applied adding the statement that symbols from the **<signal.h>** header may be made visible when the **<time.h>** header is included.

Extensions beyond the ISO C standard are marked.

NAME

trace.h — tracing

SYNOPSIS

TRC
```
#include <trace.h>
```

DESCRIPTION

The **<trace.h>** header shall define the **posix_trace_event_info** structure that includes at least the following members:

```
trace_event_id_t  posix_event_id
pid_t             posix_pid
void             *posix_prog_address
int               posix_truncation_status
struct timespec   posix_timestamp
```
THR
```
pthread_t         posix_thread_id
```

The **<trace.h>** header shall define the **posix_trace_status_info** structure that includes at least the following members:

```
int     posix_stream_status
int     posix_stream_full_status
int     posix_stream_overrun_status
```
TRL
```
int     posix_stream_flush_status
int     posix_stream_flush_error
int     posix_log_overrun_status
int     posix_log_full_status
```

The **<trace.h>** header shall define the following symbols:

POSIX_TRACE_ALL_EVENTS
TRL POSIX_TRACE_APPEND
TRI POSIX_TRACE_CLOSE_FOR_CHILD
TEF POSIX_TRACE_FILTER
TRL POSIX_TRACE_FLUSH
POSIX_TRACE_FLUSH_START
POSIX_TRACE_FLUSH_STOP
POSIX_TRACE_FLUSHING
POSIX_TRACE_FULL
POSIX_TRACE_LOOP
POSIX_TRACE_NO_OVERRUN
TRL POSIX_TRACE_NOT_FLUSHING
POSIX_TRACE_NOT_FULL
TRI POSIX_TRACE_INHERITED
POSIX_TRACE_NOT_TRUNCATED
POSIX_TRACE_OVERFLOW
POSIX_TRACE_OVERRUN
POSIX_TRACE_RESUME
POSIX_TRACE_RUNNING
POSIX_TRACE_START
POSIX_TRACE_STOP
POSIX_TRACE_SUSPENDED
POSIX_TRACE_SYSTEM_EVENTS

POSIX_TRACE_TRUNCATED_READ
POSIX_TRACE_TRUNCATED_RECORD
POSIX_TRACE_UNNAMED_USER_EVENT
POSIX_TRACE_UNTIL_FULL
POSIX_TRACE_WOPID_EVENTS

The following types shall be defined as described in **<sys/types.h>**:

trace_attr_t
trace_id_t
trace_event_id_t
TEF **trace_event_set_t**

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int  posix_trace_attr_destroy(trace_attr_t *);
int  posix_trace_attr_getclockres(const trace_attr_t *,
         struct timespec *);
int  posix_trace_attr_getcreatetime(const trace_attr_t *,
         struct timespec *);
int  posix_trace_attr_getgenversion(const trace_attr_t *, char *);
TRI int  posix_trace_attr_getinherited(const trace_attr_t *restrict,
         int *restrict);
TRL int  posix_trace_attr_getlogfullpolicy(const trace_attr_t *restrict,
         int *restrict);
int  posix_trace_attr_getlogsize(const trace_attr_t *restrict,
         size_t *restrict);
int  posix_trace_attr_getmaxdatasize(const trace_attr_t *restrict,
         size_t *restrict);
int  posix_trace_attr_getmaxsystemeventsize(const trace_attr_t *restrict,
         size_t *restrict);
int  posix_trace_attr_getmaxusereventsize(const trace_attr_t *restrict,
         size_t, size_t *restrict);
int  posix_trace_attr_getname(const trace_attr_t *, char *);
int  posix_trace_attr_getstreamfullpolicy(const trace_attr_t *restrict,
         int *restrict);
int  posix_trace_attr_getstreamsize(const trace_attr_t *restrict,
         size_t *restrict);
int  posix_trace_attr_init(trace_attr_t *);
TRI int  posix_trace_attr_setinherited(trace_attr_t *, int);
TRL int  posix_trace_attr_setlogfullpolicy(trace_attr_t *, int);
int  posix_trace_attr_setlogsize(trace_attr_t *, size_t);
int  posix_trace_attr_setmaxdatasize(trace_attr_t *, size_t);
int  posix_trace_attr_setname(trace_attr_t *, const char *);
int  posix_trace_attr_setstreamsize(trace_attr_t *, size_t);
int  posix_trace_attr_setstreamfullpolicy(trace_attr_t *, int);
int  posix_trace_clear(trace_id_t);
TRL int  posix_trace_close(trace_id_t);
int  posix_trace_create(pid_t, const trace_attr_t *restrict,
         trace_id_t *restrict);
TRL int  posix_trace_create_withlog(pid_t, const trace_attr_t *restrict,
         int, trace_id_t *restrict);
```

```
13980         void posix_trace_event(trace_event_id_t, const void *restrict, size_t);
13981         int  posix_trace_eventid_equal(trace_id_t, trace_event_id_t,
13982                   trace_event_id_t);
13983         int  posix_trace_eventid_get_name(trace_id_t, trace_event_id_t, char *);
13984         int  posix_trace_eventid_open(const char *restrict,
13985                   trace_event_id_t *restrict);
13986 TEF     int  posix_trace_eventset_add(trace_event_id_t, trace_event_set_t *);
13987         int  posix_trace_eventset_del(trace_event_id_t, trace_event_set_t *);
13988         int  posix_trace_eventset_empty(trace_event_set_t *);
13989         int  posix_trace_eventset_fill(trace_event_set_t *, int);
13990         int  posix_trace_eventset_ismember(trace_event_id_t,
13991                   const trace_event_set_t *restrict, int *restrict);
13992         int  posix_trace_eventtypelist_getnext_id(trace_id_t,
13993                   trace_event_id_t *restrict, int *restrict);
13994         int  posix_trace_eventtypelist_rewind(trace_id_t);
13995 TRL     int  posix_trace_flush(trace_id_t);                                  1
13996         int  posix_trace_get_attr(trace_id_t, trace_attr_t *);
13997 TEF     int  posix_trace_get_filter(trace_id_t, trace_event_set_t *);
13998         int  posix_trace_get_status(trace_id_t,
13999                   struct posix_trace_status_info *);
14000         int  posix_trace_getnext_event(trace_id_t,
14001                   struct posix_trace_event_info *restrict , void *restrict,
14002                   size_t, size_t *restrict, int *restrict);
14003 TRL     int  posix_trace_open(int, trace_id_t *);
14004         int  posix_trace_rewind(trace_id_t);
14005 TEF     int  posix_trace_set_filter(trace_id_t, const trace_event_set_t *, int);
14006         int  posix_trace_shutdown(trace_id_t);
14007         int  posix_trace_start(trace_id_t);
14008         int  posix_trace_stop(trace_id_t);
14009 TMO     int  posix_trace_timedgetnext_event(trace_id_t,
14010                   struct posix_trace_event_info *restrict, void *restrict,
14011                   size_t, size_t *restrict, int *restrict,
14012                   const struct timespec *restrict);
14013 TEF     int  posix_trace_trid_eventid_open(trace_id_t, const char *restrict,
14014                   trace_event_id_t *restrict);
14015         int  posix_trace_trygetnext_event(trace_id_t,
14016                   struct posix_trace_event_info *restrict, void *restrict, size_t,
14017                   size_t *restrict, int *restrict);
```

14018 **APPLICATION USAGE**

14019 None.

14020 **RATIONALE**

14021 None.

14022 **FUTURE DIRECTIONS**

14023 None.

14024 **SEE ALSO**

14025 **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.11, Tracing,
14026 *posix_trace_attr_destroy*( ), *posix_trace_attr_getclockres*( ), *posix_trace_attr_getcreatetime*( ),
14027 *posix_trace_attr_getgenversion*( ), *posix_trace_attr_getinherited*( ), *posix_trace_attr_getlogfullpolicy*( ),
14028 *posix_trace_attr_getlogsize*( ), *posix_trace_attr_getmaxdatasize*( ),
14029 *posix_trace_attr_getmaxsystemeventsize*( ), *posix_trace_attr_getmaxusereventsize*( ),

14030 *posix_trace_attr_getname*( ), *posix_trace_attr_getstreamfullpolicy*( ), *posix_trace_attr_getstreamsize*( ),
14031 *posix_trace_attr_init*( ), *posix_trace_attr_setinherited*( ), *posix_trace_attr_setlogfullpolicy*( ),
14032 *posix_trace_attr_setlogsize*( ), *posix_trace_attr_setmaxdatasize*( ), *posix_trace_attr_setname*( ),
14033 *posix_trace_attr_setstreamsize*( ), *posix_trace_attr_setstreamfullpolicy*( ), *posix_trace_clear*( ),
14034 *posix_trace_close*( ), *posix_trace_create*( ), *posix_trace_create_withlog*( ), *posix_trace_event*( ),
14035 *posix_trace_eventid_equal*( ), *posix_trace_eventid_get_name*( ), *posix_trace_eventid_open*( ),
14036 *posix_trace_eventtypelist_getnext_id*( ), *posix_trace_eventtypelist_rewind*( ),
14037 *posix_trace_eventset_add*( ), *posix_trace_eventset_del*( ), *posix_trace_eventset_empty*( ),
14038 *posix_trace_eventset_fill*( ), *posix_trace_eventset_ismember*( ), *posix_trace_flush*( ),
14039 *posix_trace_get_attr*( ), *posix_trace_get_filter*( ), *posix_trace_get_status*( ), *posix_trace_getnext_event*( ),
14040 *posix_trace_open*( ), *posix_trace_rewind*( ), *posix_trace_set_filter*( ), *posix_trace_shutdown*( ),
14041 *posix_trace_start*( ), *posix_trace_stop*( ), *posix_trace_timedgetnext_event*( ),
14042 *posix_trace_trid_eventid_open*( ), *posix_trace_trygetnext_event*( )

14043 **CHANGE HISTORY**

14044 First released in Issue 6. Derived from IEEE Std 1003.1q-2000.

14045 IEEE Std 1003.1-2001/Cor 1-2002, item XSH/TC1/D6/40 is applied, adding the TRL margin 1
14046 code to the *posix_trace_flush*( ) function, for alignment with the System Interfaces volume of 1
14047 IEEE Std 1003.1-2001. 1

NAME

ucontext.h — user context

SYNOPSIS

XSI
```
#include <ucontext.h>
```

DESCRIPTION

The **<ucontext.h>** header shall define the **mcontext_t** type through **typedef**.

The **<ucontext.h>** header shall define the **ucontext_t** type as a structure that shall include at least the following members:

`ucontext_t *uc_link`		Pointer to the context that is resumed when this context returns.
`sigset_t`	`uc_sigmask`	The set of signals that are blocked when this context is active.
`stack_t`	`uc_stack`	The stack used by this context.
`mcontext_t`	`uc_mcontext`	A machine-specific representation of the saved context.

The types **sigset_t** and **stack_t** shall be defined as in **<signal.h>**.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

OB
```
int  getcontext(ucontext_t *);                                          2
void makecontext(ucontext_t *, void (*)(void), int, ...);               2
int  setcontext(const ucontext_t *);                                    2
int  swapcontext(ucontext_t *restrict, const ucontext_t *restrict);     2
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<signal.h>, the System Interfaces volume of IEEE Std 1003.1-2001, *getcontext*( ), *makecontext*( ), *sigaction*( ), *sigprocmask*( ), *sigaltstack*( )

CHANGE HISTORY

First released in Issue 4, Version 2.

Issue 6 2

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/28 is applied, updating the *getcontext*( ), *makecontext*( ), *setcontext*( ), and *swapcontext*( ) functions to be obsolescent. 2

NAME

ulimit.h — ulimit commands

SYNOPSIS

XSI
```
#include <ulimit.h>
```

DESCRIPTION

The **<ulimit.h>** header shall define the symbolic constants used by the *ulimit*( ) function.

Symbolic constants:

UL_GETFSIZE Get maximum file size.

UL_SETFSIZE Set maximum file size.

The following shall be declared as a function and may also be defined as a macro. A function prototype shall be provided.

```
long ulimit(int, ...);
```

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

The System Interfaces volume of IEEE Std 1003.1-2001, *ulimit*( )

CHANGE HISTORY

First released in Issue 3.

14109 **NAME**

14110 unistd.h — standard symbolic constants and types

14111 **SYNOPSIS**

14112 `#include <unistd.h>`

14113 **DESCRIPTION**

14114 The **<unistd.h>** header defines miscellaneous symbolic constants and types, and declares
14115 miscellaneous functions. The actual values of the constants are unspecified except as shown. The
14116 contents of this header are shown below.

14117 **Version Test Macros**

14118 The following symbolic constants shall be defined:

14119 _POSIX_VERSION
14120 Integer value indicating version of IEEE Std 1003.1 (C-language binding) to which the
14121 implementation conforms. For implementations conforming to IEEE Std 1003.1-2001, the
14122 value shall be 200112L.

14123 _POSIX2_VERSION
14124 Integer value indicating version of the Shell and Utilities volume of IEEE Std 1003.1 to
14125 which the implementation conforms. For implementations conforming to
14126 IEEE Std 1003.1-2001, the value shall be 200112L.

14127 The following symbolic constant shall be defined only if the implementation supports the XSI
14128 option; see Section 2.1.4 (on page 21).

14129 XSI _XOPEN_VERSION
14130 Integer value indicating version of the X/Open Portability Guide to which the
14131 implementation conforms. The value shall be 600.

14132 **Constants for Options and Option Groups**

14133 The following symbolic constants, if defined in **<unistd.h>**, shall have a value of –1, 0, or greater,
14134 unless otherwise specified below. If these are undefined, the *fpathconf*( ), *pathconf*( ), or *sysconf*( )
14135 functions can be used to determine whether the option is provided for a particular invocation of
14136 the application.

14137 If a symbolic constant is defined with the value –1, the option is not supported. Headers, data
14138 types, and function interfaces required only for the option need not be supplied. An application
14139 that attempts to use anything associated only with the option is considered to be requiring an
14140 extension.

14141 If a symbolic constant is defined with a value greater than zero, the option shall always be
14142 supported when the application is executed. All headers, data types, and functions shall be
14143 present and shall operate as specified.

14144 If a symbolic constant is defined with the value zero, all headers, data types, and functions shall
14145 be present. The application can check at runtime to see whether the option is supported by
14146 calling *fpathconf*( ), *pathconf*( ), or *sysconf*( ) with the indicated *name* parameter.

14147 Unless explicitly specified otherwise, the behavior of functions associated with an unsupported
14148 option is unspecified, and an application that uses such functions without first checking
14149 *fpathconf*( ), *pathconf*( ), or *sysconf*( ) is considered to be requiring an extension.

14150 For conformance requirements, refer to Chapter 2 (on page 17).

ADV _POSIX_ADVISORY_INFO
The implementation supports the Advisory Information option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

AIO _POSIX_ASYNCHRONOUS_IO
The implementation supports the Asynchronous Input and Output option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

BAR _POSIX_BARRIERS
The implementation supports the Barriers option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

_POSIX_CHOWN_RESTRICTED
The use of *chown*( ) and *fchown*( ) is restricted to a process with appropriate privileges, and to changing the group ID of a file only to the effective group ID of the process or to one of its supplementary group IDs. This symbol shall either be undefined or defined with a value other than –1.

CS _POSIX_CLOCK_SELECTION
The implementation supports the Clock Selection option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

CPT _POSIX_CPUTIME
The implementation supports the Process CPU-Time Clocks option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

FSC _POSIX_FSYNC
The implementation supports the File Synchronization option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

_POSIX_IPV6 1
The implementation supports the IPv6 option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

_POSIX_JOB_CONTROL
The implementation supports job control. This symbol shall always be set to a value greater than zero.

MF _POSIX_MAPPED_FILES
The implementation supports the Memory Mapped Files option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

ML _POSIX_MEMLOCK
The implementation supports the Process Memory Locking option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

MLR _POSIX_MEMLOCK_RANGE
The implementation supports the Range Memory Locking option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported

by *sysconf*( ) shall either be –1 or 200112L.

MPR _POSIX_MEMORY_PROTECTION
The implementation supports the Memory Protection option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

MSG _POSIX_MESSAGE_PASSING
The implementation supports the Message Passing option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

MON _POSIX_MONOTONIC_CLOCK
The implementation supports the Monotonic Clock option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

_POSIX_NO_TRUNC
Pathname components longer than {NAME_MAX} generate an error. This symbol shall either be undefined or defined with a value other than –1.

PIO _POSIX_PRIORITIZED_IO
The implementation supports the Prioritized Input and Output option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

PS _POSIX_PRIORITY_SCHEDULING
The implementation supports the Process Scheduling option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

RS _POSIX_RAW_SOCKETS
The implementation supports the Raw Sockets option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

THR _POSIX_READER_WRITER_LOCKS
The implementation supports the Read-Write Locks option. This is always set to a value greater than zero if the Threads option is supported. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

RTS _POSIX_REALTIME_SIGNALS
The implementation supports the Realtime Signals Extension option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L.

_POSIX_REGEXP
The implementation supports the Regular Expression Handling option. This symbol shall always be set to a value greater than zero.

_POSIX_SAVED_IDS
Each process has a saved set-user-ID and a saved set-group-ID. This symbol shall always be set to a value greater than zero.

SEM _POSIX_SEMAPHORES
The implementation supports the Semaphores option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by

14244 *sysconf*( ) shall either be –1 or 200112L.

14245 SHM _POSIX_SHARED_MEMORY_OBJECTS
14246 The implementation supports the Shared Memory Objects option. If this symbol is defined
14247 in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported
14248 by *sysconf*( ) shall either be –1 or 200112L.

14249 _POSIX_SHELL
14250 The implementation supports the POSIX shell. This symbol shall always be set to a value
14251 greater than zero.

14252 SPN _POSIX_SPAWN
14253 The implementation supports the Spawn option. If this symbol is defined in **<unistd.h>**, it
14254 shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall
14255 either be –1 or 200112L.

14256 SPI _POSIX_SPIN_LOCKS
14257 The implementation supports the Spin Locks option. If this symbol is defined in
14258 **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by
14259 *sysconf*( ) shall either be –1 or 200112L.

14260 SS _POSIX_SPORADIC_SERVER
14261 The implementation supports the Process Sporadic Server option. If this symbol is defined
14262 in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported
14263 by *sysconf*( ) shall either be –1 or 200112L.

14264 SIO _POSIX_SYNCHRONIZED_IO
14265 The implementation supports the Synchronized Input and Output option. If this symbol is
14266 defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol
14267 reported by *sysconf*( ) shall either be –1 or 200112L.

14268 TSA _POSIX_THREAD_ATTR_STACKADDR
14269 The implementation supports the Thread Stack Address Attribute option. If this symbol is
14270 defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol
14271 reported by *sysconf*( ) shall either be –1 or 200112L.

14272 TSS _POSIX_THREAD_ATTR_STACKSIZE
14273 The implementation supports the Thread Stack Size Attribute option. If this symbol is
14274 defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol
14275 reported by *sysconf*( ) shall either be –1 or 200112L.

14276 TCT _POSIX_THREAD_CPUTIME
14277 The implementation supports the Thread CPU-Time Clocks option. If this symbol is
14278 defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol
14279 reported by *sysconf*( ) shall either be –1 or 200112L.

14280 TPI _POSIX_THREAD_PRIO_INHERIT
14281 The implementation supports the Thread Priority Inheritance option. If this symbol is
14282 defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol
14283 reported by *sysconf*( ) shall either be –1 or 200112L.

14284 TPP _POSIX_THREAD_PRIO_PROTECT
14285 The implementation supports the Thread Priority Protection option. If this symbol is
14286 defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol
14287 reported by *sysconf*( ) shall either be –1 or 200112L.

14288 TPS _POSIX_THREAD_PRIORITY_SCHEDULING
14289 The implementation supports the Thread Execution Scheduling option. If this symbol is

14290 defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol
14291 reported by *sysconf*( ) shall either be –1 or 200112L.

14292 TSH _POSIX_THREAD_PROCESS_SHARED
14293 The implementation supports the Thread Process-Shared Synchronization option. If this
14294 symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this
14295 symbol reported by *sysconf*( ) shall either be –1 or 200112L.

14296 TSF _POSIX_THREAD_SAFE_FUNCTIONS
14297 The implementation supports the Thread-Safe Functions option. If this symbol is defined in
14298 **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by
14299 *sysconf*( ) shall either be –1 or 200112L.

14300 TSP _POSIX_THREAD_SPORADIC_SERVER
14301 The implementation supports the Thread Sporadic Server option. If this symbol is defined
14302 in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported
14303 by *sysconf*( ) shall either be –1 or 200112L.

14304 THR _POSIX_THREADS
14305 The implementation supports the Threads option. If this symbol is defined in **<unistd.h>**, it
14306 shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall
14307 either be –1 or 200112L.

14308 TMO _POSIX_TIMEOUTS
14309 The implementation supports the Timeouts option. If this symbol is defined in **<unistd.h>**,
14310 it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( )
14311 shall either be –1 or 200112L.

14312 TMR _POSIX_TIMERS
14313 The implementation supports the Timers option. If this symbol is defined in **<unistd.h>**, it
14314 shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall
14315 either be –1 or 200112L.

14316 TRC _POSIX_TRACE
14317 The implementation supports the Trace option. If this symbol is defined in **<unistd.h>**, it
14318 shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall
14319 either be –1 or 200112L.

14320 TEF _POSIX_TRACE_EVENT_FILTER
14321 The implementation supports the Trace Event Filter option. If this symbol is defined in
14322 **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by
14323 *sysconf*( ) shall either be –1 or 200112L.

14324 TRI _POSIX_TRACE_INHERIT
14325 The implementation supports the Trace Inherit option. If this symbol is defined in
14326 **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by
14327 *sysconf*( ) shall either be –1 or 200112L.

14328 TRL _POSIX_TRACE_LOG
14329 The implementation supports the Trace Log option. If this symbol is defined in **<unistd.h>**,
14330 it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( )
14331 shall either be –1 or 200112L.

14332 TYM _POSIX_TYPED_MEMORY_OBJECTS
14333 The implementation supports the Typed Memory Objects option. If this symbol is defined
14334 in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported
14335 by *sysconf*( ) shall either be –1 or 200112L.

14336 _POSIX_VDISABLE
14337 This symbol shall be defined to be the value of a character that shall disable terminal special
14338 character handling as described in **<termios.h>**. This symbol shall always be set to a value
14339 other than –1.

14340 _POSIX2_C_BIND
14341 The implementation supports the C-Language Binding option. This symbol shall always
14342 have the value 200112L.

14343 CD _POSIX2_C_DEV
14344 The implementation supports the C-Language Development Utilities option. If this symbol 2
14345 is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol 2
14346 reported by *sysconf*( ) shall either be –1 or 200112L. 2

14347 _POSIX2_CHAR_TERM
14348 The implementation supports at least one terminal type.

14349 FD _POSIX2_FORT_DEV
14350 The implementation supports the FORTRAN Development Utilities option. If this symbol 2
14351 is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol 2
14352 reported by *sysconf*( ) shall either be –1 or 200112L. 2

14353 FR _POSIX2_FORT_RUN
14354 The implementation supports the FORTRAN Runtime Utilities option. If this symbol is 2
14355 defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol 2
14356 reported by *sysconf*( ) shall either be –1 or 200112L. 2

14357 _POSIX2_LOCALEDEF
14358 The implementation supports the creation of locales by the *localedef* utility. If this symbol is 2
14359 defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol 2
14360 reported by *sysconf*( ) shall either be –1 or 200112L. 2

14361 BE _POSIX2_PBS
14362 The implementation supports the Batch Environment Services and Utilities option. If this 2
14363 symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this 2
14364 symbol reported by *sysconf*( ) shall either be –1 or 200112L. 2

14365 BE _POSIX2_PBS_ACCOUNTING
14366 The implementation supports the Batch Accounting option. If this symbol is defined in 2
14367 **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by 2
14368 *sysconf*( ) shall either be –1 or 200112L. 2

14369 BE _POSIX2_PBS_CHECKPOINT
14370 The implementation supports the Batch Checkpoint/Restart option. If this symbol is 2
14371 defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol 2
14372 reported by *sysconf*( ) shall either be –1 or 200112L. 2

14373 BE _POSIX2_PBS_LOCATE
14374 The implementation supports the Locate Batch Job Request option. If this symbol is defined 2
14375 in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported 2
14376 by *sysconf*( ) shall either be –1 or 200112L. 2

14377 BE _POSIX2_PBS_MESSAGE
14378 The implementation supports the Batch Job Message Request option. If this symbol is 2
14379 defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol 2
14380 reported by *sysconf*( ) shall either be –1 or 200112L. 2

BE _POSIX2_PBS_TRACK
The implementation supports the Track Batch Job Request option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L. 2

SD _POSIX2_SW_DEV
The implementation supports the Software Development Utilities option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L. 2

UP _POSIX2_UPE
The implementation supports the User Portability Utilities option. If this symbol is defined in **<unistd.h>**, it shall be defined to be –1, 0, or 200112L. The value of this symbol reported by *sysconf*( ) shall either be –1 or 200112L. 2

_POSIX_V6_ILP32_OFF32 2
The implementation provides a C-language compilation environment with 32-bit **int**, **long**, **pointer**, and **off_t** types.

_POSIX_V6_ILP32_OFFBIG 2
The implementation provides a C-language compilation environment with 32-bit **int**, **long**, and **pointer** types and an **off_t** type using at least 64 bits.

_POSIX_V6_LP64_OFF64 2
The implementation provides a C-language compilation environment with 32-bit **int** and 64-bit **long**, **pointer**, and **off_t** types.

_POSIX_V6_LPBIG_OFFBIG 2
The implementation provides a C-language compilation environment with an **int** type using at least 32 bits and **long**, **pointer**, and **off_t** types using at least 64 bits.

XSI _XBS5_ILP32_OFF32 (**LEGACY**)
The implementation provides a C-language compilation environment with 32-bit **int**, **long**, **pointer**, and **off_t** types.

XSI _XBS5_ILP32_OFFBIG (**LEGACY**)
The implementation provides a C-language compilation environment with 32-bit **int**, **long**, and **pointer** types and an **off_t** type using at least 64 bits.

XSI _XBS5_LP64_OFF64 (**LEGACY**)
The implementation provides a C-language compilation environment with 32-bit **int** and 64-bit **long**, **pointer**, and **off_t** types.

XSI _XBS5_LPBIG_OFFBIG (**LEGACY**)
The implementation provides a C-language compilation environment with an **int** type using at least 32 bits and **long**, **pointer**, and **off_t** types using at least 64 bits.

XSI _XOPEN_CRYPT
The implementation supports the X/Open Encryption Option Group.

_XOPEN_ENH_I18N
The implementation supports the Issue 4, Version 2 Enhanced Internationalization Option Group. This symbol shall always be set to a value other than –1.

_XOPEN_LEGACY
The implementation supports the Legacy Option Group.

_XOPEN_REALTIME
The implementation supports the X/Open Realtime Option Group.

14426 _XOPEN_REALTIME_THREADS
14427 The implementation supports the X/Open Realtime Threads Option Group.

14428 _XOPEN_SHM
14429 The implementation supports the Issue 4, Version 2 Shared Memory Option Group. This
14430 symbol shall always be set to a value other than –1.

14431 _XOPEN_STREAMS
14432 The implementation supports the XSI STREAMS Option Group.

14433 XSI _XOPEN_UNIX
14434 The implementation supports the XSI extension.

14435 **Execution-Time Symbolic Constants**

14436 If any of the following constants are not defined in the **<unistd.h>** header, the value shall vary
14437 depending on the file to which it is applied.

14438 If any of the following constants are defined to have value –1 in the **<unistd.h>** header, the
14439 implementation shall not provide the option on any file; if any are defined to have a value other
14440 than –1 in the **<unistd.h>** header, the implementation shall provide the option on all applicable
14441 files.

14442 All of the following constants, whether defined in **<unistd.h>** or not, may be queried with
14443 respect to a specific file using the *pathconf*( ) or *fpathconf*( ) functions:

14444 _POSIX_ASYNC_IO
14445 Asynchronous input or output operations may be performed for the associated file.

14446 _POSIX_PRIO_IO
14447 Prioritized input or output operations may be performed for the associated file.

14448 _POSIX_SYNC_IO
14449 Synchronized input or output operations may be performed for the associated file.

14450 **Constants for Functions**

14451 The following symbolic constant shall be defined:

14452 NULL Null pointer

14453 The following symbolic constants shall be defined for the *access*( ) function:

14454 F_OK Test for existence of file.

14455 R_OK Test for read permission.

14456 W_OK Test for write permission.

14457 X_OK Test for execute (search) permission.

14458 The constants F_OK, R_OK, W_OK, and X_OK and the expressions *R_OK*|*W_OK*, *R_OK*|*X_OK*,
14459 and *R_OK*|*W_OK*|*X_OK* shall all have distinct values.

14460 The following symbolic constants shall be defined for the *confstr*( ) function:

14461 _CS_PATH
14462 This is the value for the *PATH* environment variable that finds all standard utilities.

14463 _CS_POSIX_V6_ILP32_OFF32_CFLAGS
14464 If *sysconf*(_SC_V6_ILP32_OFF32) returns –1, the meaning of this value is unspecified.
14465 Otherwise, this value is the set of initial options to be given to the *c99* utility to build an

14466 application using a programming model with 32-bit **int**, **long**, **pointer**, and **off_t** types.

14467 _CS_POSIX_V6_ILP32_OFF32_LDFLAGS
14468 If *sysconf*(_SC_V6_ILP32_OFF32) returns −1, the meaning of this value is unspecified.
14469 Otherwise, this value is the set of final options to be given to the *c99* utility to build an
14470 application using a programming model with 32-bit **int**, **long**, **pointer**, and **off_t** types.

14471 _CS_POSIX_V6_ILP32_OFF32_LIBS
14472 If *sysconf*(_SC_V6_ILP32_OFF32) returns −1, the meaning of this value is unspecified.
14473 Otherwise, this value is the set of libraries to be given to the *c99* utility to build an
14474 application using a programming model with 32-bit **int**, **long**, **pointer**, and **off_t** types.

14475 _CS_POSIX_V6_ILP32_OFFBIG_CFLAGS
14476 If *sysconf*(_SC_V6_ILP32_OFFBIG) returns −1, the meaning of this value is unspecified.
14477 Otherwise, this value is the set of initial options to be given to the *c99* utility to build an
14478 application using a programming model with 32-bit **int**, **long**, and **pointer** types, and an
14479 **off_t** type using at least 64 bits.

14480 _CS_POSIX_V6_ILP32_OFFBIG_LDFLAGS
14481 If *sysconf*(_SC_V6_ILP32_OFFBIG) returns −1, the meaning of this value is unspecified.
14482 Otherwise, this value is the set of final options to be given to the *c99* utility to build an
14483 application using a programming model with 32-bit **int**, **long**, and **pointer** types, and an
14484 **off_t** type using at least 64 bits.

14485 _CS_POSIX_V6_ILP32_OFFBIG_LIBS
14486 If *sysconf*(_SC_V6_ILP32_OFFBIG) returns −1, the meaning of this value is unspecified.
14487 Otherwise, this value is the set of libraries to be given to the *c99* utility to build an
14488 application using a programming model with 32-bit **int**, **long**, and **pointer** types, and an
14489 **off_t** type using at least 64 bits.

14490 _CS_POSIX_V6_LP64_OFF64_CFLAGS
14491 If *sysconf*(_SC_V6_LP64_OFF64) returns −1, the meaning of this value is unspecified.
14492 Otherwise, this value is the set of initial options to be given to the *c99* utility to build an 1
14493 application using a programming model with 32-bit **int** and 64-bit **long**, **pointer**, and **off_t** 1
14494 types.

14495 _CS_POSIX_V6_LP64_OFF64_LDFLAGS
14496 If *sysconf*(_SC_V6_LP64_OFF64) returns −1, the meaning of this value is unspecified.
14497 Otherwise, this value is the set of final options to be given to the *c99* utility to build an 1
14498 application using a programming model with 32-bit **int** and 64-bit **long**, **pointer**, and **off_t** 1
14499 types.

14500 _CS_POSIX_V6_LP64_OFF64_LIBS
14501 If *sysconf*(_SC_V6_LP64_OFF64) returns −1, the meaning of this value is unspecified.
14502 Otherwise, this value is the set of libraries to be given to the *c99* utility to build an 1
14503 application using a programming model with 32-bit **int** and 64-bit **long**, **pointer**, and **off_t** 1
14504 types.

14505 _CS_POSIX_V6_LPBIG_OFFBIG_CFLAGS
14506 If *sysconf*(_SC_V6_LPBIG_OFFBIG) returns −1, the meaning of this value is unspecified.
14507 Otherwise, this value is the set of initial options to be given to the *c99* utility to build an
14508 application using a programming model with an **int** type using at least 32 bits and **long**,
14509 **pointer**, and **off_t** types using at least 64 bits.

14510 _CS_POSIX_V6_LPBIG_OFFBIG_LDFLAGS
14511 If *sysconf*(_SC_V6_LPBIG_OFFBIG) returns −1, the meaning of this value is unspecified.
14512 Otherwise, this value is the set of final options to be given to the *c99* utility to build an

14513 application using a programming model with an **int** type using at least 32 bits and **long**,
14514 **pointer**, and **off_t** types using at least 64 bits.

14515 _CS_POSIX_V6_LPBIG_OFFBIG_LIBS
14516 If *sysconf*(_SC_V6_LPBIG_OFFBIG) returns –1, the meaning of this value is unspecified.
14517 Otherwise, this value is the set of libraries to be given to the *c99* utility to build an
14518 application using a programming model with an **int** type using at least 32 bits and **long**,
14519 **pointer**, and **off_t** types using at least 64 bits.

14520 _CS_POSIX_V6_WIDTH_RESTRICTED_ENVS
14521 This value is a <newline>-separated list of names of programming environments supported
14522 by the implementation in which the widths of the **blksize_t**, **cc_t**, **mode_t**, **nfds_t**, **pid_t**,
14523 **ptrdiff_t**, **size_t**, **speed_t**, **ssize_t**, **suseconds_t**, **tcflag_t**, **useconds_t**, **wchar_t**, and **wint_t**
14524 types are no greater than the width of type **long**. The format of each name shall be suitable 2
14525 for use with the *getconf* –**v** option. 2

14526 XSI The following symbolic constants are reserved for compatibility with Issue 5:

14527 _CS_XBS5_ILP32_OFF32_CFLAGS (**LEGACY**)
14528 _CS_XBS5_ILP32_OFF32_LDFLAGS (**LEGACY**)
14529 _CS_XBS5_ILP32_OFF32_LIBS (**LEGACY**)
14530 _CS_XBS5_ILP32_OFF32_LINTFLAGS (**LEGACY**)
14531 _CS_XBS5_ILP32_OFFBIG_CFLAGS (**LEGACY**)
14532 _CS_XBS5_ILP32_OFFBIG_LDFLAGS (**LEGACY**)
14533 _CS_XBS5_ILP32_OFFBIG_LIBS (**LEGACY**)
14534 _CS_XBS5_ILP32_OFFBIG_LINTFLAGS (**LEGACY**)
14535 _CS_XBS5_LP64_OFF64_CFLAGS (**LEGACY**)
14536 _CS_XBS5_LP64_OFF64_LDFLAGS (**LEGACY**)
14537 _CS_XBS5_LP64_OFF64_LIBS (**LEGACY**)
14538 _CS_XBS5_LP64_OFF64_LINTFLAGS (**LEGACY**)
14539 _CS_XBS5_LPBIG_OFFBIG_CFLAGS (**LEGACY**)
14540 _CS_XBS5_LPBIG_OFFBIG_LDFLAGS (**LEGACY**)
14541 _CS_XBS5_LPBIG_OFFBIG_LIBS (**LEGACY**)
14542 _CS_XBS5_LPBIG_OFFBIG_LINTFLAGS (**LEGACY**)
14543

14544 The following symbolic constants shall be defined for the *lseek*( ) and *fcntl*( ) functions and shall
14545 have distinct values:

14546 SEEK_CUR Set file offset to current plus *offset*.

14547 SEEK_END Set file offset to EOF plus *offset*.

14548 SEEK_SET Set file offset to *offset*.

14549 The following symbolic constants shall be defined as possible values for the *function* argument
14550 to the *lockf*( ) function:

14551 F_LOCK Lock a section for exclusive use.

14552 F_TEST Test section for locks by other processes.

14553 F_TLOCK Test and lock a section for exclusive use.

14554 F_ULOCK Unlock locked sections.

The following symbolic constants shall be defined for *pathconf*( ):

_PC_2_SYMLINKS	2
_PC_ALLOC_SIZE_MIN	1
_PC_ASYNC_IO	1
_PC_CHOWN_RESTRICTED	1
_PC_FILESIZEBITS	
_PC_LINK_MAX	
_PC_MAX_CANON	
_PC_MAX_INPUT	
_PC_NAME_MAX	
_PC_NO_TRUNC	
_PC_PATH_MAX	
_PC_PIPE_BUF	
_PC_PRIO_IO	
_PC_REC_INCR_XFER_SIZE	1
_PC_REC_MIN_XFER_SIZE	1
_PC_REC_XFER_ALIGN	
_PC_SYMLINK_MAX	1
_PC_SYNC_IO	1
_PC_VDISABLE	

The following symbolic constants shall be defined for *sysconf*( ):

_SC_2_C_BIND	
_SC_2_C_DEV	
_SC_2_CHAR_TERM	2
_SC_2_FORT_DEV	
_SC_2_FORT_RUN	
_SC_2_LOCALEDEF	
_SC_2_PBS	
_SC_2_PBS_ACCOUNTING	
_SC_2_PBS_CHECKPOINT	
_SC_2_PBS_LOCATE	
_SC_2_PBS_MESSAGE	
_SC_2_PBS_TRACK	
_SC_2_SW_DEV	
_SC_2_UPE	
_SC_2_VERSION	
_SC_ADVISORY_INFO	
_SC_AIO_LISTIO_MAX	
_SC_AIO_MAX	
_SC_AIO_PRIO_DELTA_MAX	
_SC_ARG_MAX	
_SC_ASYNCHRONOUS_IO	
_SC_ATEXIT_MAX	1
_SC_BARRIERS	1
_SC_BC_BASE_MAX	1
_SC_BC_DIM_MAX	
_SC_BC_SCALE_MAX	
_SC_BC_STRING_MAX	
_SC_CHILD_MAX	
_SC_CLK_TCK	
_SC_CLOCK_SELECTION	1

14606	_SC_COLL_WEIGHTS_MAX	1
14607	_SC_CPUTIME	
14608	_SC_DELAYTIMER_MAX	
14609	_SC_EXPR_NEST_MAX	
14610	_SC_FSYNC	2
14611	_SC_GETGR_R_SIZE_MAX	
14612	_SC_GETPW_R_SIZE_MAX	
14613	_SC_HOST_NAME_MAX	
14614	_SC_IOV_MAX	1
14615	_SC_IPV6	1
14616	_SC_JOB_CONTROL	1
14617	_SC_LINE_MAX	
14618	_SC_LOGIN_NAME_MAX	
14619	_SC_MAPPED_FILES	
14620	_SC_MEMLOCK	
14621	_SC_MEMLOCK_RANGE	
14622	_SC_MEMORY_PROTECTION	
14623	_SC_MESSAGE_PASSING	
14624	_SC_MONOTONIC_CLOCK	1
14625	_SC_MQ_OPEN_MAX	1
14626	_SC_MQ_PRIO_MAX	
14627	_SC_NGROUPS_MAX	
14628	_SC_OPEN_MAX	
14629	_SC_PAGE_SIZE	1
14630	_SC_PAGESIZE	
14631	_SC_PRIORITIZED_IO	1
14632	_SC_PRIORITY_SCHEDULING	
14633	_SC_RAW_SOCKETS	1
14634	_SC_RE_DUP_MAX	1
14635	_SC_READER_WRITER_LOCKS	1
14636	_SC_REALTIME_SIGNALS	1
14637	_SC_REGEXP	
14638	_SC_RTSIG_MAX	
14639	_SC_SAVED_IDS	
14640	_SC_SEM_NSEMS_MAX	1
14641	_SC_SEM_VALUE_MAX	
14642	_SC_SEMAPHORES	1
14643	_SC_SHARED_MEMORY_OBJECTS	1
14644	_SC_SHELL	
14645	_SC_SIGQUEUE_MAX	
14646	_SC_SPAWN	
14647	_SC_SPIN_LOCKS	1
14648	_SC_SPORADIC_SERVER	1
14649	_SC_SS_REPL_MAX	2
14650	_SC_STREAM_MAX	
14651	_SC_SYMLOOP_MAX	1
14652	_SC_SYNCHRONIZED_IO	1
14653	_SC_THREAD_ATTR_STACKADDR	
14654	_SC_THREAD_ATTR_STACKSIZE	
14655	_SC_THREAD_CPUTIME	
14656	_SC_THREAD_DESTRUCTOR_ITERATIONS	
14657	_SC_THREAD_KEYS_MAX	

14658 _SC_THREAD_PRIO_INHERIT
14659 _SC_THREAD_PRIO_PROTECT
14660 _SC_THREAD_PRIORITY_SCHEDULING
14661 _SC_THREAD_PROCESS_SHARED
14662 _SC_THREAD_SAFE_FUNCTIONS
14663 _SC_THREAD_SPORADIC_SERVER
14664 _SC_THREAD_STACK_MIN
14665 _SC_THREAD_THREADS_MAX
14666 _SC_THREADS 1
14667 _SC_TIMEOUTS 1
14668 _SC_TIMER_MAX 1
14669 _SC_TIMERS 1
14670 _SC_TRACE 1
14671 _SC_TRACE_EVENT_FILTER 1
14672 _SC_TRACE_EVENT_NAME_MAX 2
14673 _SC_TRACE_INHERIT 1
14674 _SC_TRACE_LOG 1
14675 _SC_TRACE_NAME_MAX 2
14676 _SC_TRACE_SYS_MAX 2
14677 _SC_TRACE_USER_EVENT_MAX 2
14678 _SC_TTY_NAME_MAX 1
14679 _SC_TYPED_MEMORY_OBJECTS 1
14680 _SC_TZNAME_MAX 1
14681 _SC_V6_ILP32_OFF32
14682 _SC_V6_ILP32_OFFBIG
14683 _SC_V6_LP64_OFF64
14684 _SC_V6_LPBIG_OFFBIG
14685 _SC_VERSION
14686 _SC_XBS5_ILP32_OFF32 (**LEGACY**) 1
14687 _SC_XBS5_ILP32_OFFBIG (**LEGACY**)
14688 _SC_XBS5_LP64_OFF64 (**LEGACY**)
14689 _SC_XBS5_LPBIG_OFFBIG (**LEGACY**)
14690 _SC_XOPEN_CRYPT
14691 _SC_XOPEN_ENH_I18N
14692 _SC_XOPEN_LEGACY
14693 _SC_XOPEN_REALTIME
14694 _SC_XOPEN_REALTIME_THREADS
14695 _SC_XOPEN_SHM
14696 _SC_XOPEN_STREAMS
14697 _SC_XOPEN_UNIX
14698 _SC_XOPEN_VERSION

14699 The two constants _SC_PAGESIZE and _SC_PAGE_SIZE may be defined to have the same 1
14700 value.

14701 The following symbolic constants shall be defined for file streams:

14702 STDERR_FILENO File number of *stderr*; 2.

14703 STDIN_FILENO File number of *stdin*; 0.

14704 STDOUT_FILENO File number of *stdout*; 1.

Type Definitions

The **size_t**, **ssize_t**, **uid_t**, **gid_t**, **off_t**, **pid_t**, and **useconds_t** types shall be defined as described in **<sys/types.h>**.

The **intptr_t** type shall be defined as described in **<inttypes.h>**.

Declarations

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
int          access(const char *, int);
unsigned     alarm(unsigned);
int          chdir(const char *);
int          chown(const char *, uid_t, gid_t);
int          close(int);
size_t       confstr(int, char *, size_t);
char        *crypt(const char *, const char *);
char        *ctermid(char *);
int          dup(int);
int          dup2(int, int);
void         encrypt(char[64], int);
int          execl(const char *, const char *, ...);
int          execle(const char *, const char *, ...);
int          execlp(const char *, const char *, ...);
int          execv(const char *, char *const []);
int          execve(const char *, char *const [], char *const []);
int          execvp(const char *, char *const []);
void        _exit(int);
int          fchown(int, uid_t, gid_t);
int          fchdir(int);
int          fdatasync(int);
pid_t        fork(void);
long         fpathconf(int, int);
int          fsync(int);                                              1
int          ftruncate(int, off_t);
char        *getcwd(char *, size_t);
gid_t        getegid(void);
uid_t        geteuid(void);
gid_t        getgid(void);
int          getgroups(int, gid_t []);
long         gethostid(void);
int          gethostname(char *, size_t);
char        *getlogin(void);
int          getlogin_r(char *, size_t);
int          getopt(int, char * const [], const char *);
pid_t        getpgid(pid_t);
pid_t        getpgrp(void);
pid_t        getpid(void);
pid_t        getppid(void);
pid_t        getsid(pid_t);
uid_t        getuid(void);
```

```
14754          char        *getwd(char *); (LEGACY)
14755          int          isatty(int);
14756 XSI      int          lchown(const char *, uid_t, gid_t);
14757          int          link(const char *, const char *);
14758 XSI      int          lockf(int, int, off_t);
14759          off_t        lseek(int, off_t, int);
14760 XSI      int          nice(int);
14761          long         pathconf(const char *, int);
14762          int          pause(void);
14763          int          pipe(int [2]);
14764 XSI      ssize_t      pread(int, void *, size_t, off_t);
14765          ssize_t      pwrite(int, const void *, size_t, off_t);
14766          ssize_t      read(int, void *, size_t);
14767          ssize_t      readlink(const char *restrict, char *restrict, size_t);
14768          int          rmdir(const char *);
14769          int          setegid(gid_t);
14770          int          seteuid(uid_t);
14771          int          setgid(gid_t);
14772          int          setpgid(pid_t, pid_t);
14773 XSI      pid_t        setpgrp(void);
14774          int          setregid(gid_t, gid_t);
14775          int          setreuid(uid_t, uid_t);
14776          pid_t        setsid(void);
14777          int          setuid(uid_t);
14778          unsigned     sleep(unsigned);
14779 XSI      void         swab(const void *restrict, void *restrict, ssize_t);
14780          int          symlink(const char *, const char *);                    2
14781 XSI      void         sync(void);                                             2
14782          long         sysconf(int);
14783          pid_t        tcgetpgrp(int);
14784          int          tcsetpgrp(int, pid_t);
14785 XSI      int          truncate(const char *, off_t);
14786          char        *ttyname(int);
14787          int          ttyname_r(int, char *, size_t);
14788 XSI      useconds_t   ualarm(useconds_t, useconds_t);
14789          int          unlink(const char *);
14790 XSI      int          usleep(useconds_t);
14791          pid_t        vfork(void);
14792          ssize_t      write(int, const void *, size_t);
```

14793 Implementations may also include the *pthread_atfork*( ) prototype as defined in **<pthread.h>** (on
14794 page 290).

14795 The following external variables shall be declared:

```
14796          extern char  *optarg;
14797          extern int    optind, opterr, optopt;
```


APPLICATION USAGE

IEEE Std 1003.1-2001 only describes the behavior of systems that claim conformance to it. However, application developers who want to write applications that adapt to other versions of IEEE Std 1003.1 (or to systems that do not conform to any POSIX standard) may find it useful to code them so as to conditionally compile different code depending on the value of _POSIX_VERSION, for example:

```
#if _POSIX_VERSION >= 200112L
/* Use the newer function that copes with large files. */
off_t pos=ftello(fp);
#else
/* Either this is an old version of POSIX, or _POSIX_VERSION is
   not even defined, so use the traditional function. */
long pos=ftell(fp);
#endif
```

Earlier versions of IEEE Std 1003.1 and of the Single UNIX Specification can be identified by the following macros:

POSIX.1-1988 standard
_POSIX_VERSION= =198808L

POSIX.1-1990 standard
_POSIX_VERSION= =199009L

ISO POSIX-1: 1996 standard
_POSIX_VERSION= =199506L

Single UNIX Specification, Version 1
_XOPEN_UNIX and _XOPEN_VERSION= =4

Single UNIX Specification, Version 2
_XOPEN_UNIX and _XOPEN_VERSION= =500

IEEE Std 1003.1-2001 does not make any attempt to define application binary interaction with the underlying operating system. However, application developers may find it useful to query _SC_VERSION at runtime via *sysconf*() to determine whether the current version of the operating system supports the necessary functionality as in the following program fragment:

```
if (sysconf(_SC_VERSION) < 200112L) {
    fprintf(stderr, "POSIX.1-2001 system required, terminating \n");
    exit(1);
}
```

New applications should not use _XOPEN_SHM or _XOPEN_ENH_I18N. 1

RATIONALE

As IEEE Std 1003.1-2001 evolved, certain options became sufficiently standardized that it was concluded that simply requiring one of the option choices was simpler than retaining the option. However, for backwards-compatibility, the option flags (with required constant values) are retained.

Version Test Macros

The standard developers considered altering the definition of _POSIX_VERSION and removing _SC_VERSION from the specification of *sysconf*( ) since the utility to an application was deemed by some to be minimal, and since the implementation of the functionality is potentially problematic. However, they recognized that support for existing application binaries is a concern to manufacturers, application developers, and the users of implementations conforming to IEEE Std 1003.1-2001.

While the example using _SC_VERSION in the APPLICATION USAGE section does not provide the greatest degree of imaginable utility to the application developer or user, it is arguably better than a **core** file or some other equally obscure result. (It is also possible for implementations to encode and recognize application binaries compiled in various POSIX.1-conforming environments, and modify the semantics of the underlying system to conform to the expectations of the application.) For the reasons outlined in the preceding paragraphs and in the APPLICATION USAGE section, the standard developers elected to retain the _POSIX_VERSION and _SC_VERSION functionality.

Compile-Time Symbolic Constants for System-Wide Options

IEEE Std 1003.1-2001 now includes support in certain areas for the newly adopted policy governing options and stubs.

This policy provides flexibility for implementations in how they support options. It also specifies how conforming applications can adapt to different implementations that support different sets of options. It allows the following:

1. If an implementation has no interest in supporting an option, it does not have to provide anything associated with that option beyond the announcement that it does not support it.
2. An implementation can support a partial or incompatible version of an option (as a non-standard extension) as long as it does not claim to support the option.
3. An application can determine whether the option is supported. A strictly conforming application must check this announcement mechanism before first using anything associated with the option.

There is an important implication of this policy. IEEE Std 1003.1-2001 cannot dictate the behavior of interfaces associated with an option when the implementation does not claim to support the option. In particular, it cannot require that a function associated with an unsupported option will fail if it does not perform as specified. However, this policy does not prevent a standard from requiring certain functions to always be present, but that they shall always fail on some implementations. The *setpgid*( ) function in the POSIX.1-1990 standard, for example, is considered appropriate.

The POSIX standards include various options, and the C-language binding support for an option implies that the implementation must supply data types and function interfaces. An application must be able to discover whether the implementation supports each option.

Any application must consider the following three cases for each option:

1. Option never supported.

   The implementation advertises at compile time that the option will never be supported. In this case, it is not necessary for the implementation to supply any of the data types or function interfaces that are provided only as part of the option. The implementation might provide data types and functions that are similar to those defined by IEEE Std 1003.1-2001, but there is no guarantee for any particular behavior.

2. Option always supported.

   The implementation advertises at compile time that the option will always be supported. In this case, all data types and function interfaces shall be available and shall operate as specified.

3. Option might or might not be supported.

   Some implementations might not provide a mechanism to specify support of options at compile time. In addition, the implementation might be unable or unwilling to specify support or non-support at compile time. In either case, any application that might use the option at runtime must be able to compile and execute. The implementation must provide, at compile time, all data types and function interfaces that are necessary to allow this. In this situation, there must be a mechanism that allows the application to query, at runtime, whether the option is supported. If the application attempts to use the option when it is not supported, the result is unspecified unless explicitly specified otherwise in IEEE Std 1003.1-2001.

FUTURE DIRECTIONS

None.

SEE ALSO

<inttypes.h>, **<limits.h>**, **<sys/socket.h>**, **<sys/types.h>**, **<termios.h>**, **<wctype.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *access*( ), *alarm*( ), *chdir*( ), *chown*( ), *close*( ), *crypt*( ), *ctermid*( ), *dup*( ), *encrypt*( ), *environ*, *exec*, *exit*( ), *fchdir*( ), *fchown*( ), *fcntl*( ), *fork*( ), *fpathconf*( ), *fsync*( ), *ftruncate*( ), *getcwd*( ), *getegid*( ), *geteuid*( ), *getgid*( ), *getgroups*( ), *gethostid*( ), *gethostname*( ), *getlogin*( ), *getpgid*( ), *getpgrp*( ), *getpid*( ), *getppid*( ), *getsid*( ), *getuid*( ), *isatty*( ), *lchown*( ), *link*( ), *lockf*( ), *lseek*( ), *nice*( ), *pathconf*( ), *pause*( ), *pipe*( ), *read*( ), *readlink*( ), *rmdir*( ), *setgid*( ), *setpgid*( ), *setpgrp*( ), *setregid*( ), *setreuid*( ), *setsid*( ), *setuid*( ), *sleep*( ), *swab*( ), *symlink*( ), *sync*( ), *sysconf*( ), *tcgetpgrp*( ), *tcsetpgrp*( ), *truncate*( ), *ttyname*( ), *ualarm*( ), *unlink*( ), *usleep*( ), *vfork*( ), *write*( )

CHANGE HISTORY

First released in Issue 1. Derived from Issue 1 of the SVID.

Issue 5

The DESCRIPTION is updated for alignment with the POSIX Realtime Extension and the POSIX Threads Extension.

The symbolic constants _XOPEN_REALTIME and _XOPEN_REALTIME_THREADS are added. _POSIX2_C_BIND, _XOPEN_ENH_I18N, and _XOPEN_SHM must now be set to a value other than −1 by a conforming implementation.

Large File System extensions are added.

The type of the argument to *sbrk*( ) is changed from **int** to **intptr_t**.

XBS constants are added to the list of constants for Options and Option Groups, to the list of constants for the *confstr*( ) function, and to the list of constants to the *sysconf*( ) function. These are all marked EX.

Issue 6

_POSIX2_C_VERSION is removed.

The Open Group Corrigendum U026/4 is applied, adding the prototype for *fdatasync*( ).

The Open Group Corrigendum U026/1 is applied, adding the symbols _SC_XOPEN_LEGACY, _SC_XOPEN_REALTIME, and _SC_XOPEN_REALTIME_THREADS.

The symbols _XOPEN_STREAMS and _SC_XOPEN_STREAMS are added to support the XSI STREAMS Option Group.

Text in the DESCRIPTION relating to conformance requirements is moved elsewhere in IEEE Std 1003.1-2001.

The legacy symbol _SC_PASS_MAX is removed.

The following new requirements on POSIX implementations derive from alignment with the Single UNIX Specification:

- The _CS_POSIX_* and _CS_XBS5_* constants are added for the *confstr*( ) function.
- The _SC_XBS5_* constants are added for the *sysconf*( ) function.
- The symbolic constants F_ULOCK, F_LOCK, F_TLOCK, and F_TEST are added.
- The **uid_t**, **gid_t**, **off_t**, **pid_t**, and **useconds_t** types are mandated.

The *gethostname*( ) prototype is added for sockets.

A new section is added for System-Wide Options.

Function prototypes for *setegid*( ) and *seteuid*( ) are added.

Option symbolic constants are added for _POSIX_ADVISORY_INFO, _POSIX_CPUTIME, _POSIX_SPAWN, _POSIX_SPORADIC_SERVER, _POSIX_THREAD_CPUTIME, _POSIX_THREAD_SPORADIC_SERVER, and _POSIX_TIMEOUTS, and *pathconf*( ) variables are added for _PC_ALLOC_SIZE_MIN, _PC_REC_INCR_XFER_SIZE, _PC_REC_MAX_XFER_SIZE, _PC_REC_MIN_XFER_SIZE, and _PC_REC_XFER_ALIGN for alignment with IEEE Std 1003.1d-1999.

The following are added for alignment with IEEE Std 1003.1j-2000:

- Option symbolic constants _POSIX_BARRIERS, _POSIX_CLOCK_SELECTION, _POSIX_MONOTONIC_CLOCK, _POSIX_READER_WRITER_LOCKS, _POSIX_SPIN_LOCKS, and _POSIX_TYPED_MEMORY_OBJECTS
- *sysconf*( ) variables _SC_BARRIERS, _SC_CLOCK_SELECTION, _SC_MONOTONIC_CLOCK, _SC_READER_WRITER_LOCKS, _SC_SPIN_LOCKS, and _SC_TYPED_MEMORY_OBJECTS

The _SC_XBS5 macros associated with the ISO/IEC 9899:1990 standard are marked LEGACY, and new equivalent _SC_V6 macros associated with the ISO/IEC 9899:1999 standard are introduced.

The *getwd*( ) function is marked LEGACY.

The **restrict** keyword is added to the prototypes for *readlink*( ) and *swab*( ).

Constants for options are now harmonized, so when supported they take the year of approval of IEEE Std 1003.1-2001 as the value.

The following are added for alignment with IEEE Std 1003.1q-2000:

- Optional symbolic constants _POSIX_TRACE, _POSIX_TRACE_EVENT_FILTER, _POSIX_TRACE_LOG, and _POSIX_TRACE_INHERIT
- The *sysconf*( ) symbolic constants _SC_TRACE, _SC_TRACE_EVENT_FILTER, _SC_TRACE_LOG, and _SC_TRACE_INHERIT

The *brk*( ) and *sbrk*( ) legacy functions are removed.

The Open Group Base Resolution bwg2001-006 is applied, which reworks the XSI versioning information.

The Open Group Base Resolution bwg2001-008 is applied, changing the *namelen* parameter for *gethostname*( ) from **socklen_t** to **size_t**.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/2 is applied, changing ''Thread Stack Address Size'' to ''Thread Stack Size Attribute''.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/20 is applied, adding the _POSIX_IPV6, _SC_V6, and _SC_RAW_SOCKETS symbols.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/21 is applied, correcting the description in ''Constants for Functions'' for the _CS_POSIX_V6_LP64_OFF64_CFLAGS, _CS_POSIX_V6_LP64_OFF64_LDFLAGS, and _CS_POSIX_V6_LP64_OFF64_LIBS symbols.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/22 is applied, removing the shading for the _PC* and _SC* constants, since these are mandatory on all implementations.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/23 is applied, adding the _PC_SYMLINK_MAX and _SC_SYMLOOP_MAX constants.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/24 is applied, correcting the shading and margin code for the *fsync*( ) function.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/25 is applied, adding the following text to the APPLICATION USAGE section: ''New applications should not use _XOPEN_SHM or _XOPEN_ENH_I18N.''.

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/29 is applied, clarifying the requirements for when constants for Options and Option Groups can be defined or undefined.

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/30 is applied, changing the _V6_ILP32_OFF32, _V6_ILP32_OFFBIG, _V6_LP64_OFF64, and _V6_LPBIG_OFFBIG symbols to _POSIX_V6_ILP32_OFF32, _POSIX_V6_ILP32_OFFBIG, _POSIX_V6_LP64_OFF64, and _POSIX_V6_LPBIG_OFFBIG, respectively. This is for consistency with the *sysconf*( ) and *c99* reference pages.

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/31 is applied, adding that the format of names of programming environments can be obtained using the *getconf* **−v** option.

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/32 is applied, deleting the _SC_FILE_LOCKING, _SC_2_C_VERSION, and _SC_XOPEN_XCU_VERSION constants.

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/33 is applied, adding _SC_SS_REPL_MAX, _SC_TRACE_EVENT_NAME_MAX, _SC_TRACE_NAME_MAX, _SC_TRACE_SYS_MAX, and _SC_TRACE_USER_EVENT_MAX to the list of symbolic constants for *sysconf*( ).

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/34 is applied, updating the prototype for the *symlink*( ) function to match that in the System Interfaces volume of IEEE Std 1003.1-2001.

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/35 is applied, adding _PC_2_SYMLINKS to the symbolic constants list for *pathconf*( ). This corresponds to the definition of POSIX2_SYMLINKS in the Shell and Utilities volume of IEEE Std 1003.1-2001.

15006 **NAME**

15007 utime.h — access and modification times structure

15008 **SYNOPSIS**

15009 `#include <utime.h>`

15010 **DESCRIPTION**

15011 The **<utime.h>** header shall declare the structure **utimbuf**, which shall include the following
15012 members:

15013 `time_t` `actime` Access time.
15014 `time_t` `modtime` Modification time.

15015 The times shall be measured in seconds since the Epoch.

15016 The type **time_t** shall be defined as described in **<sys/types.h>**.

15017 The following shall be declared as a function and may also be defined as a macro. A function
15018 prototype shall be provided.

15019 `int utime(const char *, const struct utimbuf *);`

15020 **APPLICATION USAGE**

15021 None.

15022 **RATIONALE**

15023 None.

15024 **FUTURE DIRECTIONS**

15025 None.

15026 **SEE ALSO**

15027 **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *utime*( )

15028 **CHANGE HISTORY**

15029 First released in Issue 3.

15030 **Issue 6**

15031 The following new requirements on POSIX implementations derive from alignment with the
15032 Single UNIX Specification:

15033 - The **time_t** type is defined.

15034 **NAME**

15035 utmpx.h — user accounting database definitions

15036 **SYNOPSIS**

15037 XSI
```
#include <utmpx.h>
```
15038

15039 **DESCRIPTION**

15040 The **<utmpx.h>** header shall define the **utmpx** structure that shall include at least the following
15041 members:

15042 `char`	`ut_user[]`	User login name.
15043 `char`	`ut_id[]`	Unspecified initialization process identifier.
15044 `char`	`ut_line[]`	Device name.
15045 `pid_t`	`ut_pid`	Process ID.
15046 `short`	`ut_type`	Type of entry.
15047 `struct timeval`	`ut_tv`	Time entry was made.

15048 The **pid_t** type shall be defined through **typedef** as described in **<sys/types.h>**.

15049 The **timeval** structure shall be defined as described in **<sys/time.h>**.

15050 Inclusion of the **<utmpx.h>** header may also make visible all symbols from **<sys/time.h>**.

15051 The following symbolic constants shall be defined as possible values for the *ut_type* member of
15052 the **utmpx** structure:

15053 EMPTY	No valid user accounting information.
15054 BOOT_TIME	Identifies time of system boot.
15055 OLD_TIME	Identifies time when system clock changed.
15056 NEW_TIME	Identifies time after system clock changed.
15057 USER_PROCESS	Identifies a process.
15058 INIT_PROCESS	Identifies a process spawned by the init process.
15059 LOGIN_PROCESS	Identifies the session leader of a logged-in user.
15060 DEAD_PROCESS	Identifies a session leader who has exited.

15061 The following shall be declared as functions and may also be defined as macros. Function
15062 prototypes shall be provided.

```
15063 void          endutxent(void);
15064 struct utmpx *getutxent(void);
15065 struct utmpx *getutxid(const struct utmpx *);
15066 struct utmpx *getutxline(const struct utmpx *);
15067 struct utmpx *pututxline(const struct utmpx *);
15068 void          setutxent(void);
```

15069 **APPLICATION USAGE**

15070 None.

15071 **RATIONALE**

15072 None.

15073 **FUTURE DIRECTIONS**

15074 None.

15075 **SEE ALSO**

15076 **<sys/time.h>**, **<sys/types.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *endutxent*( )

15077 **CHANGE HISTORY**

15078 First released in Issue 4, Version 2.

NAME

wchar.h — wide-character handling

SYNOPSIS

```
#include <wchar.h>
```

DESCRIPTION

CX Some of the functionality described on this reference page extends the ISO C standard. Applications shall define the appropriate feature test macro (see the System Interfaces volume of IEEE Std 1003.1-2001, Section 2.2, The Compilation Environment) to enable the visibility of these symbols in this header.

The **<wchar.h>** header shall define the following types:

wchar_t As described in **<stddef.h>**.

wint_t An integer type capable of storing any valid value of **wchar_t** or WEOF.

XSI **wctype_t** A scalar type of a data object that can hold values which represent locale-specific character classification.

mbstate_t An object type other than an array type that can hold the conversion state information necessary to convert between sequences of (possibly multi-byte) characters and wide characters. If a codeset is being used such that an **mbstate_t** needs to preserve more than 2 levels of reserved state, the results are unspecified.

XSI **FILE** As described in **<stdio.h>**.

size_t As described in **<stddef.h>**.

XSI **va_list** As described in **<stdarg.h>**.

The implementation shall support one or more programming environments in which the width of **wint_t** is no greater than the width of type **long**. The names of these programming environments can be obtained using the *confstr*( ) function or the *getconf* utility.

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```
wint_t        btowc(int);
wint_t        fgetwc(FILE *);
wchar_t      *fgetws(wchar_t *restrict, int, FILE *restrict);
wint_t        fputwc(wchar_t, FILE *);
int           fputws(const wchar_t *restrict, FILE *restrict);
int           fwide(FILE *, int);
int           fwprintf(FILE *restrict, const wchar_t *restrict, ...);
int           fwscanf(FILE *restrict, const wchar_t *restrict, ...);
wint_t        getwc(FILE *);
wint_t        getwchar(void);
int           iswalnum(wint_t);
int           iswalpha(wint_t);
int           iswcntrl(wint_t);
int           iswctype(wint_t, wctype_t);
int           iswdigit(wint_t);
int           iswgraph(wint_t);
int           iswlower(wint_t);
int           iswprint(wint_t);
int           iswpunct(wint_t);
```



```
15125          int             iswspace(wint_t);
15126          int             iswupper(wint_t);
15127          int             iswxdigit(wint_t);
15128          size_t          mbrlen(const char *restrict, size_t, mbstate_t *restrict);
15129          size_t          mbrtowc(wchar_t *restrict, const char *restrict, size_t,
15130                              mbstate_t *restrict);
15131          int             mbsinit(const mbstate_t *);
15132          size_t          mbsrtowcs(wchar_t *restrict, const char **restrict, size_t,
15133                              mbstate_t *restrict);
15134          wint_t          putwc(wchar_t, FILE *);
15135          wint_t          putwchar(wchar_t);
15136          int             swprintf(wchar_t *restrict, size_t,
15137                              const wchar_t *restrict, ...);
15138          int             swscanf(const wchar_t *restrict,
15139                              const wchar_t *restrict, ...);
15140 XSI      wint_t          towlower(wint_t);
15141          wint_t          towupper(wint_t);
15142          wint_t          ungetwc(wint_t, FILE *);
15143          int             vfwprintf(FILE *restrict, const wchar_t *restrict, va_list);
15144          int             vfwscanf(FILE *restrict, const wchar_t *restrict, va_list);
15145          int             vwprintf(const wchar_t *restrict, va_list);
15146          int             vswprintf(wchar_t *restrict, size_t,
15147                              const wchar_t *restrict, va_list);
15148          int             vswscanf(const wchar_t *restrict, const wchar_t *restrict,
15149                              va_list);
15150          int             vwscanf(const wchar_t *restrict, va_list);
15151          size_t          wcrtomb(char *restrict, wchar_t, mbstate_t *restrict);
15152          wchar_t        *wcscat(wchar_t *restrict, const wchar_t *restrict);
15153          wchar_t        *wcschr(const wchar_t *, wchar_t);
15154          int             wcscmp(const wchar_t *, const wchar_t *);
15155          int             wcscoll(const wchar_t *, const wchar_t *);
15156          wchar_t        *wcscpy(wchar_t *restrict, const wchar_t *restrict);
15157          size_t          wcscspn(const wchar_t *, const wchar_t *);
15158          size_t          wcsftime(wchar_t *restrict, size_t,
15159                              const wchar_t *restrict, const struct tm *restrict);
15160          size_t          wcslen(const wchar_t *);
15161          wchar_t        *wcsncat(wchar_t *restrict, const wchar_t *restrict, size_t);
15162          int             wcsncmp(const wchar_t *, const wchar_t *, size_t);
15163          wchar_t        *wcsncpy(wchar_t *restrict, const wchar_t *restrict, size_t);
15164          wchar_t        *wcspbrk(const wchar_t *, const wchar_t *);
15165          wchar_t        *wcsrchr(const wchar_t *, wchar_t);
15166          size_t          wcsrtombs(char *restrict, const wchar_t **restrict,
15167                              size_t, mbstate_t *restrict);
15168          size_t          wcsspn(const wchar_t *, const wchar_t *);
15169          wchar_t        *wcsstr(const wchar_t *restrict, const wchar_t *restrict);
15170          double          wcstod(const wchar_t *restrict, wchar_t **restrict);
15171          float           wcstof(const wchar_t *restrict, wchar_t **restrict);
15172          wchar_t        *wcstok(wchar_t *restrict, const wchar_t *restrict,
15173                              wchar_t **restrict);
15174          long            wcstol(const wchar_t *restrict, wchar_t **restrict, int);
15175          long double     wcstold(const wchar_t *restrict, wchar_t **restrict);
15176          long long       wcstoll(const wchar_t *restrict, wchar_t **restrict, int);
```



```
15177       unsigned long wcstoul(const wchar_t *restrict, wchar_t **restrict, int);
15178       unsigned long long
15179                     wcstoull(const wchar_t *restrict, wchar_t **restrict, int);
15180 XSI   wchar_t      *wcswcs(const wchar_t *, const wchar_t *);
15181       int           wcswidth(const wchar_t *, size_t);
15182       size_t        wcsxfrm(wchar_t *restrict, const wchar_t *restrict, size_t);
15183       int           wctob(wint_t);
15184 XSI   wctype_t      wctype(const char *);
15185       int           wcwidth(wchar_t);
15186       wchar_t      *wmemchr(const wchar_t *, wchar_t, size_t);
15187       int           wmemcmp(const wchar_t *, const wchar_t *, size_t);
15188       wchar_t      *wmemcpy(wchar_t *restrict, const wchar_t *restrict, size_t);
15189       wchar_t      *wmemmove(wchar_t *, const wchar_t *, size_t);
15190       wchar_t      *wmemset(wchar_t *, wchar_t, size_t);
15191       int           wprintf(const wchar_t *restrict, ...);
15192       int           wscanf(const wchar_t *restrict, ...);
```

15193 The **<wchar.h>** header shall define the following macros:

15194 WCHAR_MAX The maximum value representable by an object of type **wchar_t**.

15195 WCHAR_MIN The minimum value representable by an object of type **wchar_t**.

15196 WEOF Constant expression of type **wint_t** that is returned by several WP functions
15197 to indicate end-of-file.

15198 NULL As described in **<stddef.h>**.

15199 The tag **tm** shall be declared as naming an incomplete structure type, the contents of which are
15200 described in the header **<time.h>**.

15201 CX Inclusion of the **<wchar.h>** header may make visible all symbols from the headers **<ctype.h>**,
15202 **<string.h>**, **<stdarg.h>**, **<stddef.h>**, **<stdio.h>**, **<stdlib.h>**, and **<time.h>**.

15203 **APPLICATION USAGE**

15204 The *iswblank*( ) function was a late addition to the ISO C standard and was introduced at the 1
15205 same time as the ISO C standard introduced **<wctype.h>**, which contains all of the *isw**( ) 1
15206 functions. The Open Group Base Specifications had previously aligned with the MSE working 1
15207 draft and had introduced the rest of the *isw**( ) functions into **<wchar.h>**. For backwards- 1
15208 compatibility, the original set of *isw**( ) functions, without *iswblank*( ), are permitted (as an XSI 1
15209 extension) in **<wchar.h>**. For maximum portability, applications should include **<wctype.h>** in 1
15210 order to obtain declarations for the *isw**( ) functions. 1

15211 **RATIONALE**

15212 In the ISO C standard, the symbols referenced as XSI extensions are in **<wctype.h>**. Their
15213 presence here is thus an extension.

15214 **FUTURE DIRECTIONS**

15215 None.

15216 **SEE ALSO**

15217 **<ctype.h>**, **<stdarg.h>**, **<stddef.h>**, **<stdio.h>**, **<stdlib.h>**, **<string.h>**, **<time.h>**, **<wctype.h>**, the
15218 System Interfaces volume of IEEE Std 1003.1-2001, *btowc*( ), *confstr*( ), *fgetwc*( ), *fgetws*( ), *fputwc*( ),
15219 *fputws*( ), *fwide*( ), *fwprintf*( ), *fwscanf*( ), *getwc*( ), *getwchar*( ), *iswalnum*( ), *iswalpha*( ), *iswcntrl*( ),
15220 *iswctype*( ), *iswdigit*( ), *iswgraph*( ), *iswlower*( ), *iswprint*( ), *iswpunct*( ), *iswspace*( ), *iswupper*( ),
15221 *iswxdigit*( ), *iswctype*( ), *mbsinit*( ), *mbrlen*( ), *mbrtowc*( ), *mbsrtowcs*( ), *putwc*( ), *putwchar*( ),
15222 *swprintf*( ), *swscanf*( ), *towlower*( ), *towupper*( ), *ungetwc*( ), *vfwprintf*( ), *vfwscanf*( ), *vswprintf*( ),
15223 *vswscanf*( ), *vwscanf*( ), *wcrtomb*( ), *wcsrtombs*( ), *wcscat*( ), *wcschr*( ), *wcscmp*( ), *wcscoll*( ), *wcscpy*( ),

15224 *wcscspn*( ), *wcsftime*( ), *wcslen*( ), *wcsncat*( ), *wcsncmp*( ), *wcsncpy*( ), *wcspbrk*( ), *wcsrchr*( ), *wcsspn*( ),
15225 *wcsstr*( ), *wcstod*( ), *wcstof*( ), *wcstok*( ), *wcstol*( ), *wcstold*( ), *wcstoll*( ), *wcstoul*( ), *wcstoull*( ), *wcswcs*( ),
15226 *wcswidth*( ), *wcsxfrm*( ), *wctob*( ), *wctype*( ), *wcwidth*( ), *wmemchr*( ), *wmemcmp*( ), *wmemcpy*( ),
15227 *wmemmove*( ), *wmemset*( ), *wprintf*( ), *wscanf*( ), the Shell and Utilities volume of
15228 IEEE Std 1003.1-2001, *getconf*

15229 **CHANGE HISTORY**

15230 First released in Issue 4.

15231 **Issue 5**

15232 Aligned with the ISO / IEC 9899: 1990 / Amendment 1: 1995 (E).

15233 **Issue 6**

15234 The Open Group Corrigendum U021 / 10 is applied. The prototypes for *wcswidth*( ) and
15235 *wcwidth*( ) are marked as extensions.

15236 The Open Group Corrigendum U028 / 5 is applied, correcting the prototype for the *mbsinit*( )
15237 function.

15238 The following changes are made for alignment with the ISO / IEC 9899: 1999 standard:

15239 • Various function prototypes are updated to add the **restrict** keyword.

15240 • The functions *vfwscanf*( ), *vswscanf*( ), *wcstof*( ), *wcstold*( ), *wcstoll*( ), and *wcstoull*( ) are added.

15241 The type **wctype_t**, the *isw**( ), *to**( ), and *wctype*( ) functions are marked as XSI extensions.

15242 IEEE Std 1003.1-2001 / Cor 1-2002, item XBD / TC1 / D6 / 26 is applied, adding the APPLICATION 1
15243 USAGE section. 1

15244 **NAME**

15245 wctype.h — wide-character classification and mapping utilities

15246 **SYNOPSIS**

15247 `#include <wctype.h>`

15248 **DESCRIPTION**

15249 CX Some of the functionality described on this reference page extends the ISO C standard.
15250 Applications shall define the appropriate feature test macro (see the System Interfaces volume of
15251 IEEE Std 1003.1-2001, Section 2.2, The Compilation Environment) to enable the visibility of these
15252 symbols in this header.

15253 The **<wctype.h>** header shall define the following types:

15254 **wint_t** As described in **<wchar.h>**.

15255 **wctrans_t** A scalar type that can hold values which represent locale-specific character
15256 mappings.

15257 **wctype_t** As described in **<wchar.h>**.

15258 The following shall be declared as functions and may also be defined as macros. Function
15259 prototypes shall be provided.

```
15260 int       iswalnum(wint_t);
15261 int       iswalpha(wint_t);
15262 int       iswblank(wint_t);
15263 int       iswcntrl(wint_t);
15264 int       iswdigit(wint_t);
15265 int       iswgraph(wint_t);
15266 int       iswlower(wint_t);
15267 int       iswprint(wint_t);
15268 int       iswpunct(wint_t);
15269 int       iswspace(wint_t);
15270 int       iswupper(wint_t);
15271 int       iswxdigit(wint_t);
15272 int       iswctype(wint_t, wctype_t);
15273 wint_t    towctrans(wint_t, wctrans_t);
15274 wint_t    towlower(wint_t);
15275 wint_t    towupper(wint_t);
15276 wctrans_t wctrans(const char *);
15277 wctype_t  wctype(const char *);
```

15278 The **<wctype.h>** header shall define the following macro name:

15279 WEOF Constant expression of type **wint_t** that is returned by several MSE functions
15280 to indicate end-of-file.

15281 For all functions described in this header that accept an argument of type **wint_t**, the value is
15282 representable as a **wchar_t** or equals the value of WEOF. If this argument has any other value,
15283 the behavior is undefined.

15284 The behavior of these functions shall be affected by the *LC_CTYPE* category of the current locale.

15285 CX Inclusion of the **<wctype.h>** header may make visible all symbols from the headers **<ctype.h>**,
15286 **<stdarg.h>**, **<stddef.h>**, **<stdio.h>**, **<stdlib.h>**, **<string.h>**, **<time.h>**, and **<wchar.h>**.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<ctype.h>, **<locale.h>**, **<stdarg.h>**, **<stddef.h>**, **<stdio.h>**, **<stdlib.h>**, **<string.h>**, **<time.h>**, **<wchar.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *iswalnum*( ), *iswalpha*( ), *iswblank*( ), *iswcntrl*( ), *iswctype*( ), *iswdigit*( ), *iswgraph*( ), *iswlower*( ), *iswprint*( ), *iswpunct*( ), *iswspace*( ), *iswupper*( ), *iswxdigit*( ), *setlocale*( ), *towctrans*( ), *towlower*( ), *towupper*( ), *wctrans*( ), *wctype*( )

CHANGE HISTORY

First released in Issue 5. Derived from the ISO / IEC 9899: 1990 / Amendment 1: 1995 (E).

Issue 6

The *iswblank*( ) function is added for alignment with the ISO / IEC 9899: 1999 standard.

15303 **NAME**

15304 wordexp.h — word-expansion types

15305 **SYNOPSIS**

15306 `#include <wordexp.h>`

15307 **DESCRIPTION**

15308 The **<wordexp.h>** header shall define the structures and symbolic constants used by the
15309 *wordexp*( ) and *wordfree*( ) functions.

15310 The structure type **wordexp_t** shall contain at least the following members:

15311 `size_t  we_wordc` Count of words matched by *words*.
15312 `char  **we_wordv` Pointer to list of expanded words.
15313 `size_t  we_offs` Slots to reserve at the beginning of *we_wordv*.

15314 The *flags* argument to the *wordexp*( ) function shall be the bitwise-inclusive OR of the following
15315 flags:

15316 WRDE_APPEND Append words to those previously generated.

15317 WRDE_DOOFFS Number of null pointers to prepend to *we_wordv*.

15318 WRDE_NOCMD Fail if command substitution is requested.

15319 WRDE_REUSE The *pwordexp* argument was passed to a previous successful call to
15320 *wordexp*( ), and has not been passed to *wordfree*( ). The result is the same
15321 as if the application had called *wordfree*( ) and then called *wordexp*( )
15322 without WRDE_REUSE.

15323 WRDE_SHOWERR Do not redirect *stderr* to **/dev/null**.

15324 WRDE_UNDEF Report error on an attempt to expand an undefined shell variable.

15325 The following constants shall be defined as error return values:

15326 WRDE_BADCHAR One of the unquoted characters—<newline>, `'|'`, `'&'`, `';'`, `'<'`, `'>'`,
15327 `'('`, `')'`, `'{'`, `'}'`—appears in *words* in an inappropriate context.

15328 WRDE_BADVAL Reference to undefined shell variable when WRDE_UNDEF is set in *flags*.

15329 WRDE_CMDSUB Command substitution requested when WRDE_NOCMD was set in *flags*.

15330 WRDE_NOSPACE Attempt to allocate memory failed.

15331 OB XSI WRDE_NOSYS Reserved.

15332 WRDE_SYNTAX Shell syntax error, such as unbalanced parentheses or unterminated
15333 string.

15334 The **<wordexp.h>** header shall define the following type:

15335 XSI **size_t** As described in **<stddef.h>**.

15336 The following shall be declared as functions and may also be defined as macros. Function
15337 prototypes shall be provided.

15338 `int  wordexp(const char *restrict, wordexp_t *restrict, int);`
15339 `void wordfree(wordexp_t *);`

15340 The implementation may define additional macros or constants using names beginning with
15341 WRDE_.

15342 **APPLICATION USAGE**

15343 None.

15344 **RATIONALE**

15345 None.

15346 **FUTURE DIRECTIONS**

15347 None.

15348 **SEE ALSO**

15349 **<stddef.h>**, the System Interfaces volume of IEEE Std 1003.1-2001, *wordexp*( ), the Shell and
15350 Utilities volume of IEEE Std 1003.1-2001

15351 **CHANGE HISTORY**

15352 First released in Issue 4. Derived from the ISO POSIX-2 standard.

15353 **Issue 6**

15354 The **restrict** keyword is added to the prototype for *wordexp*( ).

15355 The WRDE_NOSYS constant is marked obsolescent.

Index

