

PROCORE SOLO

Single Phase Battery Charger



Available in 120V AND 240V

KEY FEATURES

- 1 and 2 module cabinets
- Small, convenient and lightweight
- No configuration required, plug in and go
- No battery monitor required
- Wide range input over voltage, over current, over temperature, reverse polarity, short circuit, and shock/vibration protections
- Charger provides a float charge to keep the battery at 100%
- Built-in handle for portability

TECHNICAL SPECIFICATIONS

ProCore Solo Single Phase

	Voltage	Number of Modules	Nominal Volt	Output Current	Input Current
PCS-24-120 PCS-24-240	120 VAC	1	24V	40A	13.5A
240 PCS-48-120	240 VAC	2	24V	90A	8A
PCS-48-240 Input	120VAC	1	36V/48V	26A	13.5A
Voltage Power	240VAC	2	36V/48V	52A	8A
Rating	120 or 240 VAC 50/60Hz Single Phase				
Efficiency User	1.2kW @120VAC, 2.7kW @ 240VAC				
Interface	Maximum Power Factor > 90% to 99%				
Cooling	Efficiency up to 95%				
Dimensions (WxDxH)	LED				
Weight	Forced Air (fans)				
Certifications	11.9" W x 11.9" D x 5.2" H (with feet)				
	1X: ≤ 25 lbs 2X: ≤30 lbs				
	UL and cUL listed; CEC Compliant				



Have questions or need more info?

Send us a message!

Orders@PosiCharge.com

PosiCharge is a product line of Ampure

1960 Walker Ave

Monrovia, CA 91016 USA

Hotline: +1 888-833-2148 (UNITED STATES)

Download this Spec Sheet

