

DVS 300 / 400

Flexible Dual-Vehicle Fast Charger



Technical Specifications

	DVS 300: Powerserver	DVS 400: Powerserver
Power Rating	30kW	40kW
Utility Requirements	480 / 600 VAC, 3-phase	480 / 600 VAC, 3-phase
Full Load Amp Draw	40A / 32A	40A / 32A
Max Circuit Breaker Rating	50A / 40A	70A / 60A
Power Factor	0.96	0.96
Efficiency	90%	90%
Battery Voltage Range	24V - 96V	24V - 96V
Max Output Current (Dual Mode)	250A	250A
Max Output Current (Single Mode)	500A	500A
Weight	905 LBS	915 LBS
Dimensions	60"H X 32.4"W X 21.9"D	60"H X 32.4"W X 21.9"D
Communication Port	RS232	RS232
Operating Temperature	-40°C -50°C	-40°C -50°C



The PosiCharge DVS 300 / 400 are stand-alone industrial chargers designed to power one vehicle up to 500 A or two vehicles simultaneously at 250 A each. Built with ultra-efficient IGBT power electronics and an integrated AC-to-DC power server, it delivers high performance with significantly lower installation and utility costs than other fast chargers.

When paired with a PosiCharge BMID, the DVS intelligently manages battery temperatures using communicated temperature data and configurable foldback settings—enhancing charging safety and speed. Like all PosiCharge systems, it supports a wide range of battery voltages and offers comprehensive data management and onboard intelligence.

KEY FEATURES:

- Charge one vehicle up to 500 A or two vehicles simultaneously at 250 A
- Communicates via CAN protocol for lithium battery compatibility
- Works with all PosiCharge BMIDs for adaptive charging and data capture
- Supports multiple vehicles and battery types on one charger
- Delivers up to 3× the equipment throughput of conventional chargers using the same power
- High-efficiency IGBT technology
- Automatic start/stop, anti-arcing disconnect, and auto-thermal shutdown
- Rugged NEMA 3R outdoor-rated enclosure for all-weather operation
- Euro and Burton connector options

DVS 330

Flexible Dual-Vehicle Fast Charger



Technical Specifications

Power Rating	33kW
Utility Requirements	380 / 400 / 415 VAC, 3-phase
Full Load Amp Draw	56A / 53A / 51A
Max Circuit Breaker Rating	64A
Power Factor	0.96
Efficiency	90%
Battery Voltage Range	24V - 96V
Max Output Current (Dual Mode)	250A
Max Output Current (Single Mode)	500A
Weight	905 LBS
Dimensions	60"H X 32.4"W X 21.9"D
Communication Port	RS232
Operating Temperature	-40°C -50°C



The PosiCharge DVS330 is a stand-alone industrial charger designed to power one vehicle up to 500 A or two vehicles simultaneously at 250 A each. Built with high-efficiency IGBT power electronics and an integrated AC-to-DC power server, it delivers high performance with lower installation and utility costs compared to other fast chargers.

When paired with a PosiCharge BMID, the DVS intelligently manages battery temperatures using communicated temperature data and configurable foldback settings—enhancing charging safety and speed. Like all PosiCharge systems, it supports a wide range of battery voltages and offers comprehensive data management and onboard intelligence.

KEY FEATURES:

- Charges one vehicle up to 500 A or two simultaneously at 250 A
- Ultra-efficient IGBT technology with integrated AC-to-DC power server
- GBT CAN protocol compatibility available via add-on kit
- CAN communication for lithium battery integration
- Works with all PosiCharge BMIDs for adaptive charging and data capture
- Supports multiple vehicles and battery types on one charger
- Up to 3× the equipment throughput of conventional chargers
- Automatic start/stop, anti-arcing disconnect, auto-thermal shutdown
- Euro or Burton connector options

DVS 330 IP55

Flexible Dual-Vehicle Fast Charger



CE Compliant

Technical Specifications

Power Rating	33kW
Utility Requirements	380 / 400 / 415 VAC, 3-phase
Full Load Amp Draw	56A / 53A / 51A
Max Circuit Breaker Rating	64A
Power Factor	0.96
Efficiency	90%
Battery Voltage Range	24V - 96V
Max Output Current (Dual Mode)	250A
Max Output Current (Single Mode)	500A
Weight	905 LBS
Dimensions	60"H X 32.4"W X 21.9"D
Communication Port	RS232
Operating Temperature	-40°C -50°C



The PosiCharge DVS330 is a stand-alone industrial charger designed to power one vehicle up to 500 A or two vehicles simultaneously at 250 A each. Built with high-efficiency IGBT power electronics and an integrated AC-to-DC power server, it delivers high performance with lower installation and utility costs compared to other fast chargers.

When paired with a PosiCharge BMID, the DVS intelligently manages battery temperatures using communicated temperature data and configurable foldback settings—enhancing charging safety and speed. Like all PosiCharge systems, it supports a wide range of battery voltages and offers comprehensive data management and onboard intelligence.

KEY FEATURES:

- Charges one vehicle up to 500 A or two simultaneously at 250 A
- Ultra-efficient IGBT technology with integrated AC-to-DC power server
- GBT CAN protocol compatibility available via add-on kit
- CAN communication for lithium battery integration
- Works with all PosiCharge BMIDs for adaptive charging and data capture
- Supports multiple vehicles and battery types on one charger
- Up to 3× the equipment throughput of conventional chargers
- Automatic start/stop, anti-arcing disconnect, auto-thermal shutdown
- Euro or Burton connector options