

HIGH VOLTAGE POWER STATION

20kW DC Fast Charger
for eGSE + EVs



30kW quick charge via CCS1 + NACS

Flexible install: Runs on
PosiCharge DC bus or stand-alone

KEY FEATURES

- **High-Voltage Power Delivery** – Supports today's higher-voltage, higher-capacity assets, including compatible eGSE and EVs.
- **Backwards Compatible** – Designed to operate with DVS and MVS systems (with a required software update).
- **Scalable Power Infrastructure** – Expands fleet charging without new utility drops by replacing a standard power station with a high-voltage unit.
- **CCS1 or NACS Single-Port Output** – Standard 5 m CCS1 or NACS connector options, supporting compatible industrial eGSE as well as road EVs.
- **Industrial Durability** – NEMA 3S enclosure, designed for industrial environments.
- **Proven Reliability** – Built on proven modular power conversion technology

Specifications

Input Voltage	PosiCharge DC Bus 240 Vac Single Phase 208 or 240 Vac 3-Phase (3P + PE) Delta 480/277 Vac 3-Phase (3P + N + PE) Wye
Input Operating Range and Current	240 Vac Single Phase: 216 to 252 V, 150 A max, 60 Hz 208/240 Vac 3-Phase Delta: 190 to 252 V, 100 A max, 60 Hz 480 Vac 3-Phase Wye: 432 to 504 V, 45 A max, 60 Hz
Output Power	20 kW maximum via PosiCharge DC Bus 30 kW maximum via AC input
Output Voltage	250 to 920 Vdc
Efficiency	95%
Charging Connector	CCS1 and NACS
Charging Cable Length	5 m standard
Charging/Data Protocols	DIN 70121 and OCPP 1.6J compliant
Network Interface	Cellular 4G LTE, Wi-Fi
Display	7" color LCD
Operational Temperature	-30 °C to +50 °C
Storage Temperature	-40 °C to +80 °C
Relative Humidity	Up to 95% non-condensing
Altitude	2000 m (6560 ft)
Enclosure Rating	NEMA 3S; IP54
Impact Resistance	IK10
Weight	140 kg (Charger only)
Mounting	Wall-mounted or pedestal (both sold separately)
Certifications	AC configuration: cETLus listed to UL 2202, UL2231-1 & -2, and CSA C22.2 No. 281.1, 281.2 and 346 DC configuration: cETLus listing pending



PosiCharge is a product line of Ampure

1333 S. Mayflower Ave Suite 100
Monrovia, CA 91016 USA

Hotline: +1 888-833-2148 (UNITED STATES)

