

MVS 400

Multi-Port, Multi-Vehicle Fast Charge System



Technical Specifications

	MVS 400: Powerserver
Power Rating	40kW
Utility Requirements	480 / 600 VAC, 3-phase
Full Load Amp Draw	56A / 45A
Max Circuit Breaker Rating	70A / 60A
Power Factor	0.96
Efficiency	90%
Weight	915 LBS
Dimensions	60"H X 32.4"W X 21.9"D

	Powerstation
Power Rating	60kW
Battery Voltage Range	24V - 96V
Max Output Current (Dual Mode)	250A
Max Output Current (Single Mode)	500A
Weight	304 LBS
Dimensions	30"H X 30"W X 19"D
Communication Port	RS232



The PosiCharge MVS400 is a multi-port, multi-vehicle fast charge system designed to lower utility costs and maximize available infrastructure. Built on the DVS400 platform, it supports up to three additional power stations, enabling as many as eight industrial vehicles—such as tow tugs, baggage tractors, and belt loaders—to charge simultaneously.

Featuring intelligent power-sharing technology, the MVS400 automatically prioritizes vehicles with the lowest state of charge while distributing power efficiently across all connected units, providing faster charging and greater cost savings as fleet size increases. Like all PosiCharge systems, it supports a broad range of battery voltages and offers comprehensive data management and onboard intelligence.

KEY FEATURES:

- Charges up to 8 vehicles simultaneously via expandable power stations
- Intelligent power-sharing prioritizes low-SOC vehicles and balances load
- Ultra-efficient IGBT technology with integrated AC-to-DC power server
- GBT CAN protocol compatibility available via add-on kit
- CAN communication for lithium battery integration
- Works with all PosiCharge BMIDs for adaptive charging and data capture
- Supports multiple vehicles and battery types on one system
- Automatic start/stop, anti-arcing disconnect, auto-thermal shutdown
- Euro or Burton connector options
- Low maintenance, easy installation, and reliable performance