

MVS 800

Multi-Port, Multi-Vehicle Fast Charge System



CE Compliant version available

Technical Specifications

	MVS 800: Powerserver
Power Rating	80kW
Utility Requirements	480 / 600 VAC, 3-phase
Full Load Amp Draw	100A / 80A
Max Circuit Breaker Rating	125A / 100A
Power Factor	0.96
Efficiency	95%
Weight	1,405 LBS
Dimensions	62"H X 42"W X 27"D

	Powerstation
Power Rating	60kW
Battery Voltage Range	24V - 96V
Max Output Current (Dual Mode)	250A
Max Output Current (Single Mode)	500A
Weight	304 LBS
Dimensions	30"H X 30"W X 19"D
Communication Port	RS232



The MVS 800 is our multiple-port, multi-vehicle fast charge system, designed to lower utility costs and maximize available infrastructure. An MVS 800 can charge up to 16 industrial vehicles (e.g.tow tugs, baggage tractors, belt loaders, etc.) at the same time. PosiCharge’s intelligent power-sharing technology prioritizes vehicles with the lowest state of charge while continuing to distribute power across all connected units, delivering faster charging and greater cost savings as more vehicles are charged at once.

Like the DVS, MVS features the highest power quality and most diverse multi-voltage, multi-amperage flexibility of any fast charging system available today. MVS systems are installed all across the world’s largest airports, as well as Fortune and Global 100 companies. And like all PosiCharge chargers, the MVS 800 works with a broad range of battery voltages and has the same data management and onboard intelligence.

KEY FEATURES:

- Charges up to 16 vehicles simultaneously via expandable power stations
- Rugged NEMA 3R Enclosure Rating, provides all environment/weather operation
- Intelligent power-sharing prioritizes low-SOC vehicles and balances load
- Ultra-efficient IGBT technology with integrated AC-to-DC power server
- GBT CAN protocol compatibility available via add-on kit
- CAN communication for lithium battery integration
- Works with all PosiCharge BMIDs for adaptive charging and data capture
- Supports multiple vehicles and battery types on one system
- Automatic start/stop, anti-arcing disconnect, auto-thermal shutdown
- Euro or Burton connector options
- Low maintenance, easy installation, and reliable performance